Module 6: Assignment 1

**Tasks To Be Performed:**

1. Create a virtual network in West US

2. Create another virtual network in South India

3. Deploy virtual machine in West US with the virtual network in West US

4. Deploy virtual machine in South India inside virtual network in South India

5. Create VNet-VNet peering to connect West US and South India VM

6. Check this by pinging VM1 to VM2 via ping command using private IP

address

Solution:

2. Create another virtual network in South India

4. Deploy virtual machine in South India inside virtual network in South India

Create a virtual machine   ···

Help me create a low cost VM   Help me create a VM optimized for high availability   Help me choose the right VM size for my workload

Basics   Disks   Networking   Management   Monitoring   Advanced   Tags   Review + create

Create a virtual machine that runs Linux or Windows. Select an image from Azure marketplace or use your own customized image. Complete the Basics tab then Review + create to provision a virtual machine with default parameters or review each tab for full customization. Learn more 🗗

ℹ This subscription may not be eligible to deploy VMs of certain sizes in certain regions.

Project details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription * ⓘ | Free Trial   ∨ |

    Resource group * ⓘ | (New) Resource group   ∨ |
    Create new

Instance details

A resource group is a container that holds related resources for an Azure solution.

Virtual machine name * ⓘ

Name *

Region * ⓘ | module6   ✓ |

Availability options ⓘ   **OK**   Cancel

Zone options ⓘ
    Choose up to 3 availability zones, one VM per zone

< Previous   Next : Disks >   **Review + create**

Create a virtual machine ...

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size for my workload |

Basics Disks Networking Management Monitoring Advanced Tags Review + create

Create a virtual machine that runs Linux or Windows. Select an image from Azure marketplace or use your own customized image. Complete the Basics tab then Review + create to provision a virtual machine with default parameters or review each tab for full customization. Learn more ⤢

ℹ This subscription may not be eligible to deploy VMs of certain sizes in certain regions.

Project details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription * ⓘ

| Free Trial | ⌄ |

    Resource group * ⓘ

| module6 | ⌄ |

Create new

Instance details

Virtual machine name * ⓘ

| vm-southindia | ✓ |

Region * ⓘ

| (Asia Pacific) South India | ⌄ |

Availability options ⓘ

| No infrastructure redundancy required | ⌄ |

Security type ⓘ

| Trusted launch virtual machines | ⌄ |

Configure security features

| < Previous | Next : Disks > | **Review + create** |

Create a virtual machine ...

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size for my workload |

Configure security features

Image * ⓘ
> 🔴 Ubuntu Server 22.04 LTS - x64 Gen2 (free services eligible)   ⌄

See all images | Configure VM generation

VM architecture ⓘ
- ◯ Arm64
- ⦿ x64

Run with Azure Spot discount ⓘ
☐

> ⓘ You are in the free trial period. Costs associated with this VM can be covered by any remaining credits on your subscription.
> Learn more ⎘

Size * ⓘ
> Standard_B1s - 1 vcpu, 1 GiB memory (₹880.62/month) (free services eligible)   ⌄

See all sizes

Enable Hibernation ⓘ
☐

> ⓘ Hibernate does not currently support Trusted launch and Confidential virtual
> machines for Linux images. Learn more ⎘

Administrator account

Authentication type ⓘ
- ◯ SSH public key
- ⦿ Password

Username * ⓘ

| < Previous | Next : Disks > | Review + create |

Create a virtual machine ...

Help me create a low cost VM	Help me create a VM optimized for high availability	Help me choose the right VM size for my workload

machines for Linux images. Learn more ⬈

Administrator account

Authentication type ⓘ
- ○ SSH public key
- ● Password

Username * ⓘ   `Jungkook` ✓

Password *   `••••••••••••` ✓

Confirm password *   `••••••••••••` ✓

Inbound port rules

Select which virtual machine network ports are accessible from the public internet. You can specify more limited or granular network access on the Networking tab.

Public inbound ports * ⓘ
- ○ None
- ● Allow selected ports

Select inbound ports *   `HTTP (80), SSH (22)` ▾

- ☑ HTTP (80)
- ☐ HTTPS (443)
- ☑ SSH (22)

< Previous	Next : Disks >	**Review + create**

Create a virtual machine ...

Help me create a low cost VM	Help me create a VM optimized for high availability	Help me choose the right VM size

Basics   Disks   **Networking**   Management   Monitoring   Advanced   Tags   Review + create

Define network connectivity for your virtual machine by configuring network interface card (NIC) settings. You can control ports, inbound and outbound connectivity with security group rules, or place behind an existing load balancing solution. Learn more ⬈

Network interface

When creating a virtual machine, a network interface will be created for you.

Virtual network * ⓘ   `(new) vm-southindia-vnet` ▾
Create new

Subnet * ⓘ   `(new) default (10.0.0.0/24)` ▾

Public IP ⓘ   `(new) vm-southindia-ip` ▾
Create new

NIC network security group ⓘ
- ○ None
- ● Basic
- ○ Advanced

Public inbound ports * ⓘ
- ○ None
- ● Allow selected ports

Select inbound ports *   `HTTP (80), SSH (22)` ▾

⚠ This will allow all IP addresses to access your virtual machine. This is only

< Previous	Next : Management >	**Review + create**

Create virtual network   ✕

The Microsoft Azure Virtual Network service enables Azure resources to securely communicate with each other in a virtual network which is a logical isolation of the Azure cloud dedicated to your subscription. You can connect virtual networks to other virtual networks, or your on-premises network. Learn more ⬈

Name *   `vnet1` ✓

Address space

The virtual network's address space, specified as one or more address prefixes in CIDR notation (e.g. 192.168.1.0/24).

	Address range *	Addresses	Overlap	
☐	10.0.0.0/16	10.0.0.0 - 10.0.255.255 (65536 addresses)	None	🗑 ⋯
		(0 Addresses)	None	

Subnets

The subnet's address range in CIDR notation. It must be contained by the address space of the virtual network.

	Subnet name	Address range	Addresses	
☐	default	10.0.0.0/24	10.0.0.0 - 10.0.0.255 (256 addresses)	🗑 ⋯
			(0 Addresses)	

OK	Discard

Create a virtual machine ···

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size for my workload |

Basics   Disks   **Networking**   Management   Monitoring   Advanced   Tags   Review + create

Define network connectivity for your virtual machine by configuring network interface card (NIC) settings. You can control ports, inbound and outbound connectivity with security group rules, or place behind an existing load balancing solution.
Learn more

Network interface

When creating a virtual machine, a network interface will be created for you.

Virtual network * ⓘ	(new) vnet1 ⌄
	Create new
Subnet * ⓘ	(new) default (10.0.0.0/24) ⌄
Public IP ⓘ	(new) vm-southindia-ip ⌄
	Create new
NIC network security group ⓘ	○ None
	● Basic
	○ Advanced
Public inbound ports * ⓘ	○ None
	● Allow selected ports
Select inbound ports *	HTTP (80), SSH (22) ⌄

⚠ **This will allow all IP addresses to access your virtual machine.** This is only

| < Previous | Next : Management > | **Review + create** |

---

1. Create a virtual network in West US

**3. Deploy virtual machine in West US with the virtual network in West US**

Create a virtual machine ...

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size for my workload |

Basics Disks Networking Management Monitoring Advanced Tags Review + create

Create a virtual machine that runs Linux or Windows. Select an image from Azure marketplace or use your own customized image. Complete the Basics tab then Review + create to provision a virtual machine with default parameters or review each tab for full customization. Learn more ⬀

> ℹ This subscription may not be eligible to deploy VMs of certain sizes in certain regions.

Project details

Select the subscription to manage deployed resources and costs. Use resource groups like folders to organize and manage all your resources.

Subscription * ⓘ

| Free Trial ⌄ |

    Resource group * ⓘ

| module6 ⌄ |

Create new

Instance details

Virtual machine name * ⓘ

| vm-westus ✓ |

Region * ⓘ

| (US) West US ⌄ |

Availability options ⓘ

| No infrastructure redundancy required ⌄ |

Security type ⓘ

| Trusted launch virtual machines ⌄ |

Configure security features

| < Previous | Next : Disks > | **Review + create** |

Create a virtual machine ...

Help me create a low cost VM	Help me create a VM optimized for high availability	Help me choose the right VM size for my workload

Configure security features

Image * ⓘ	🔶 Ubuntu Server 22.04 LTS - x64 Gen2 (free services eligible) ▾

See all images | Configure VM generation

VM architecture ⓘ
- ⚪ Arm64
- 🔘 x64

Run with Azure Spot discount ⓘ
☐

ℹ You are in the free trial period. Costs associated with this VM can be covered by any remaining credits on your subscription.
Learn more ↗

Size * ⓘ	Standard_B1s - 1 vcpu, 1 GiB memory (₹753.08/month) (free services eligible) ▾

See all sizes

Enable Hibernation ⓘ
☐

ℹ Hibernate does not currently support Trusted launch and Confidential virtual machines for Linux images. Learn more ↗

Administrator account

Authentication type ⓘ
- ⚪ SSH public key
- 🔘 Password

Username * ⓘ

< Previous	Next : Disks >	**Review + create**

Create a virtual machine ...

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size for my workload |

machines for Linux images. Learn more ⧉

Administrator account

Authentication type ⓘ

○ SSH public key
● Password

Username * ⓘ

    Jungkook   ✓

Password *

    ••••••••••••   ✓

Confirm password *

    ••••••••••••   ✓

Inbound port rules

Select which virtual machine network ports are accessible from the public internet. You can specify more limited or granular network access on the Networking tab.

Public inbound ports * ⓘ

○ None
● Allow selected ports

Select inbound ports *

    HTTP (80), SSH (22)   ⌄

    ☑ HTTP (80)
    ☐ HTTPS (443)
    ☑ SSH (22)

| < Previous | Next : Disks > | **Review + create** |

Home > Virtual machines >

Create a virtual machine

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size |

Basics   Disks   **Networking**   Management   Monitoring   Advanced   Tags   Review + create

Define network connectivity for your virtual machine by configuring network interface card (NIC) settings. You can control ports, inbound and outbound connectivity with security group rules, or place behind an existing load balancing solution.
Learn more ⧉

Network interface

When creating a virtual machine, a network interface will be created for you.

Virtual network * ⓘ

    (new) vm-westus-vnet   ⌄
    Create new

Subnet * ⓘ

    (new) default (10.0.0.0/24)   ⌄

Public IP ⓘ

    (new) vm-westus-ip   ⌄
    Create new

NIC network security group ⓘ

○ None
● Basic
○ Advanced

Public inbound ports * ⓘ

○ None
● Allow selected ports

Select inbound ports *

    HTTP (80), SSH (22)   ⌄

⚠ This will allow all IP addresses to access your virtual machine. This is only

| < Previous | Next : Management > | **Review + create** |

Create virtual network

✕

The Microsoft Azure Virtual Network service enables Azure resources to securely communicate with each other in a virtual network which is a logical isolation of the Azure cloud dedicated to your subscription. You can connect virtual networks to other virtual networks, or your on-premises network. Learn more ⧉

Name *

    vnet2   ✓

Address space

The virtual network's address space, specified as one or more address prefixes in CIDR notation (e.g. 192.168.1.0/24).

☐	Address range *	Addresses	Overlap	
☐	20.0.0.0/16 ✓	20.0.0.0 - 20.0.255.255 (65536 addresses)	None	🗑 ⋯
		(0 Addresses)	None	

Subnets

The subnet's address range in CIDR notation. It must be contained by the address space of the virtual network.

☐	Subnet name	Address range	Addresses	
☐	default ✓	20.0.0.0/24 ✓	20.0.0.0 - 20.0.0.255 (256 addresses)	🗑 ⋯
			(0 Addresses)	

| **OK** | Discard |

Create a virtual machine   ...

| Help me create a low cost VM | Help me create a VM optimized for high availability | Help me choose the right VM size for my workload |

Basics   Disks   **Networking**   Management   Monitoring   Advanced   Tags   Review + create

Define network connectivity for your virtual machine by configuring network interface card (NIC) settings. You can control ports, inbound and outbound connectivity with security group rules, or place behind an existing load balancing solution.
Learn more ⌕

Network interface

When creating a virtual machine, a network interface will be created for you.

Virtual network * ⓘ
[(new) vnet2   ⌄]
Create new

Subnet * ⓘ
[(new) default (20.0.0.0/24)   ⌄]

Public IP ⓘ
[(new) vm-westus-ip   ⌄]
Create new

NIC network security group ⓘ
○ None
⦿ Basic
○ Advanced

Public inbound ports * ⓘ
○ None
⦿ Allow selected ports

Select inbound ports *
[HTTP (80), SSH (22)   ⌄]

⚠ **This will allow all IP addresses to access your virtual machine.** This is only

[< Previous]   [Next : Management >]   [**Review + create**]

Virtual machines 📌 ...
Default Directory (aldrinfigeredo1508gmail.onmicrosoft.com)

+ Create ⌄   ⇄ Switch to classic   🕐 Reservations ⌄   ⚙ Manage view ⌄   ↻ Refresh   ↓ Export to CSV   ⟲ Open query | ⊘ Assign tags   ▷ Start   ↻ Restart   ⬜ Stop   🗑 Delete   ⊞ Services ⌄   ⌖ Maintenance ⌄   ✕

Filter for any field...   Subscription equals **all**   Type equals **all**   Resource group equals **all** ✕   Location equals **all** ✕   +▽ Add filter

Showing 1 to 2 of 2 records.   No grouping ⌄   ⊞ List view ⌄

☐ Name ↑↓	Subscription ↑↓	Resource group ↑↓	Location ↑↓	Status ↑↓	Operating system ↑↓	Size ↑↓	Public IP address ↑↓	Disks ↑↓	
☐ 🖥 vm-southindia	Free Trial	module6	South India	Running	Linux	Standard_B1s	20.235.135.80	1	...
☐ 🖥 vm-westus	Free Trial	module6	West US	Running	Linux	Standard_B1s	40.78.121.21	1	...

---

5. Create VNet-VNet peering to connect West US and South India VM

Virtual networks 📌 ...
Default Directory (aldrinfigeredo1508gmail.onmicrosoft.com)

+ Create   ⚙ Manage view ⌄   ↻ Refresh   ↓ Export to CSV   ⟲ Open query   ⊘ Assign tags   ✕

Filter for any field...   Subscription equals **all**   Resource group equals **all** ✕   Location equals **all** ✕   +▽ Add filter

Showing 1 to 2 of 2 records.   No grouping ⌄   ⊞ List view ⌄

☐ Name ↑	Resource group ↑↓	Location ↑↓	Subscription ↑↓	
☐ ↔ vnet1	module6	South India	Free Trial	...
☐ ↔ vnet2	module6	West US	Free Trial	...

Virtual networks

Default Directory (aldrinfigeredo1508gmail.onmicr...

+ Create   ⚙ Manage view ∨   ···

Filter for any field...

Name ↑↓
‹›› vnet1	···
‹›› vnet2	···

vnet1 | Peerings ☆ ···
Virtual network

🔍 Search

- 🏷 Tags
- ✖ Diagnose and solve problems
- ∨ Settings
  - ‹›› Address space
  - 🖊 Connected devices
  - ‹›› Subnets
  - ✖ Bastion
  - 🛡 DDoS protection
  - ☁ Firewall
  - 🛡 Microsoft Defender for Cloud
  - ⚙ Network manager
  - 🖥 DNS servers
  - ⟨⟩ Peerings ☆
  - 🔗 Service endpoints
  - ⟨ Private endpoints

+ Add   ↻ Refresh   ⬇ Export to CSV | 🗑 Delete   ↻ Sync

Virtual network peering enables you to seamlessly connect two or more virtual networks in Azur

🔍 Filter by name...

Name ↑↓	Peering sync status ↑↓

Add a peering to get started

Add peering ⋯

vnet1

Virtual network peering enables you to seamlessly connect two or more virtual networks in Azure. This will allow resources in either virtual network to directly connect and communicate with resources in the peered virtual network.

Remote virtual network summary

Peering link name *	vnet1tovnet2
Virtual network deployment model ⓘ	⦿ Resource manager
	◯ Classic
I know my resource ID ⓘ	☐
Subscription *	Free Trial ⌄
Virtual network *	vnet2 (module6) ⌄

Remote virtual network peering settings

Allow 'vnet2' to access 'vnet1' ⓘ	☑
Allow 'vnet2' to receive forwarded traffic from 'vnet1' ⓘ	☑
Allow gateway or route server in 'vnet2' to forward traffic to 'vnet1' ⓘ	☐
Enable 'vnet2' to use 'vnet1's' remote gateway or route server ⓘ	☐

Add   Cancel

Add peering ...
vnet1

Remote virtual network peering settings

Allow 'vnet2' to access 'vnet1' ⓘ ☑

Allow 'vnet2' to receive forwarded traffic
from 'vnet1' ⓘ ☑

Allow gateway or route server in 'vnet2' to
forward traffic to 'vnet1' ⓘ ☐

Enable 'vnet2' to use 'vnet1's' remote
gateway or route server ⓘ ☐

Local virtual network summary

Peering link name * [vnet1tovnet2]

Local virtual network peering settings

Allow 'vnet1' to access 'vnet2' ⓘ ☑

Allow 'vnet1' to receive forwarded traffic
from 'vnet2' ⓘ ☑

Allow gateway or route server in 'vnet1' to
forward traffic to 'vnet2' ⓘ ☐

Enable 'vnet1' to use 'vnet2's' remote
gateway or route server ⓘ ☐

[**Add**] [Cancel]

Home > Virtual networks > vnet1

Virtual networks
Default Directory (aldrinfigeredo1508gmail.onmicr...

+ Create ⚙ Manage view ∨ ···

Filter for any field...

Name ↑

↔ vnet1   ···
↔ vnet2   ···

vnet1 | Peerings ☆ ···
Virtual network

🔍 peering   ✕ ✕ «

∨ Settings

   ⚛ Peerings

+ Add ↻ Refresh ↓ Export to CSV | 🗑 Delete ⟳ Sync

Virtual network peering enables you to seamlessly connect two or more virtual networks in Azure. The virtual networks appear as one for connectivity purposes. Learn more ↗

🔍 Filter by name...

Name ↑↓	Peering sync status ↑↓	Peering state ↑↓	Remo... ↑↓	Virtu... ↑↓
vnet1tovnet2	✅ Fully Synchronized	✅ Connected	vnet2	Disabled

✕

6. Check this by pinging VM1 to VM2 via ping command using private IP address

CA. Jungkook@vm-southindia: ~

```
System information as of Fri Sep  6 08:06:26 UTC 2024

 System load:  0.09            Processes:             104
 Usage of /:   5.9% of 28.89GB Users logged in:       0
 Memory usage: 34%             IPv4 address for eth0: 10.0.0.4
 Swap usage:   0%

Expanded Security Maintenance for Applications is not enabled.

10 updates can be applied immediately.
10 of these updates are standard security updates.
To see these additional updates run: apt list --upgradable

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status



The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

Jungkook@vm-southindia:~$
```


Home > Virtual machines > vm-westus

Virtual machines «
Default Directory (aldrinfigeredo1508gmail.onmicr...

+ Create ∨   ⇄ Switch to classic   ···

Filter for any field...

Name ↑↓

🖥 vm-southindia   ···
🖥 vm-westus   ···

🔌 **vm-westus | Connect** ☆ ···
Virtual machine

🔍 Search   ◇   «

🖥 Overview
📋 Activity log
🔑 Access control (IAM)
🏷 Tags
🔧 Diagnose and solve problems
∨ Connect
   🔌 Connect

↻ Refresh   🔧 Troubleshoot ∨   🔀 More Options ∨   🗨 Feedback

Connecting using
Private IP address | 20.0.0.4   ∨

Admin username
Jungkook   \

Port (change)
22   Check access ⓘ

Just-in-time policy
Unsupported by plan ⓘ

```
Jungkook@vm-southindia:~$ ping 20.0.0.4
PING 20.0.0.4 (20.0.0.4) 56(84) bytes of data.
64 bytes from 20.0.0.4: icmp_seq=2 ttl=64 time=201 ms
64 bytes from 20.0.0.4: icmp_seq=3 ttl=64 time=201 ms
64 bytes from 20.0.0.4: icmp_seq=4 ttl=64 time=201 ms
64 bytes from 20.0.0.4: icmp_seq=5 ttl=64 time=201 ms
64 bytes from 20.0.0.4: icmp_seq=6 ttl=64 time=201 ms
64 bytes from 20.0.0.4: icmp_seq=7 ttl=64 time=201 ms
64 bytes from 20.0.0.4: icmp_seq=8 ttl=64 time=201 ms
```

Home > Virtual machines > vm-westus

Virtual machines

Default Directory (aldrinfigeredo1508gmail.onmicr...

+ Create ∨   ⇄ Switch to classic   ···

Filter for any field...

Name ↑↓

💻 vm-southindia   ···

💻 vm-westus   ···

⊘ vm-westus | Connect ☆ ···
Virtual machine

🔍 Search   ◇   «

💻 Overview

📋 Activity log

👥 Access control (IAM)

🏷 Tags

🔧 Diagnose and solve problems

∨ Connect

○ Refresh   🔧 Troubleshoot ∨   ⚙ More Options ∨   🗨 Feedback

Connecting using
Public IP address | 40.78.121.21   ∨

Public IP address | 40.78.121.21

Private IP address | 20.0.0.4

22   Check access ⓘ

Home > Virtual machines > vm-southindia

Virtual machines

Default Directory (aldrinfigeredo1508gmail.onmicr...

+ Create ∨   ⇄ Switch to classic   ···

Filter for any field...

Name ↑↓

💻 vm-southindia   ···

💻 vm-westus   ···

⊘ vm-southindia | Connect ☆ ···
Virtual machine

🔍 Search   ◇   «

💻 Overview

📋 Activity log

👥 Access control (IAM)

🏷 Tags

🔧 Diagnose and solve problems

∨ Connect

○ Refresh   🔧 Troubleshoot ∨   ⚙ More Options ∨   🗨 Feedback

Connecting using
Private IP address | 10.0.0.4   ∨

Public IP address | 20.235.135.80

Private IP address | 10.0.0.4

22   Check access ⓘ

```
 System information as of Fri Sep  6 08:09:10 UTC 2024

  System load:  0.07            Processes:            102
  Usage of /:   5.2% of 28.89GB Users logged in:      0
  Memory usage: 34%             IPv4 address for eth0: 20.0.0.4
  Swap usage:   0%

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status


The list of available updates is more than a week old.
To check for new updates run: sudo apt update


The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

Jungkook@vm-westus:~$ ping 10.0.0.4
PING 10.0.0.4 (10.0.0.4) 56(84) bytes of data.
64 bytes from 10.0.0.4: icmp_seq=1 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=2 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=3 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=4 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=5 ttl=64 time=203 ms
64 bytes from 10.0.0.4: icmp_seq=6 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=7 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=8 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=9 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=10 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=11 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=12 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=13 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=14 ttl=64 time=200 ms
64 bytes from 10.0.0.4: icmp_seq=15 ttl=64 time=201 ms
64 bytes from 10.0.0.4: icmp_seq=16 ttl=64 time=201 ms
```