```
1 import components.simplereader.SimpleReader;
7
8 / * *
9 * Program to convert an XML RSS (version 2.0) feed from a given URL into the
10 * corresponding HTML output file.
12 * @author Vaishnavi Kasabwala
13 *
14 */
15 public final class RSSReader {
      /**
17
18
       * Private constructor so this utility class cannot be instantiated.
19
20
      private RSSReader() {
21
      }
22
23
24
      * Outputs the "opening" tags in the generated HTML file. These are the
25
       * expected elements generated by this method:
26
27
       * <html> <head> <title>the channel tag title as the page title</title>
28
       * </head> <body>
29
       * <h1>the page title inside a link to the <channel> link</h1>
       * 
30
31
       * the channel description
32
       * 
33
       * 
34
      * 
35
      * Date
       * Source
36
37
       * News
       * 
38
39
40
      * @param channel
41
                    the channel element XMLTree
      * @param out
42
43
                    the output stream
44
       * @updates out.content
45
       * @requires [the root of channel is a <channel> tag] and out.is_open
       * @ensures out.content = #out.content * [the HTML "opening" tags]
46
47
48
      private static void outputHeader(XMLTree channel, SimpleWriter out) {
49
          assert channel != null : "Violation of: channel is not null";
50
          assert out != null : "Violation of: out is not null";
          assert channel.isTag() && channel.label().equals("channel") : ""
51
52
                  + "Violation of: the label root of channel is a <channel> tag";
53
          assert out.isOpen() : "Violation of: out.is_open";
54
55
          // title
56
          int titleNum = getChildElement(channel, "title");
57
          XMLTree title = channel.child(titleNum);
58
59
          out.print("<html> <head> <title>");
          if (title.numberOfChildren() > 0) {
60
61
              out.print(title.child(0).label());
62
          }
```

```
63
           out.println("</title>");
 64
 65
           out.println("</head> <body>");
 66
 67
           //link
 68
           int linkNum = getChildElement(channel, "link");
 69
           XMLTree link = channel.child(linkNum);
 70
 71
           out.print("<h1>");
 72
           if (link.numberOfChildren() > 0) {
               out.print("<a href=\"" + link.child(0).label() + "\">");
 73
 74
               if (title.numberOfChildren() > 0) {
 75
                  out.print(title.child(0).label());
 76
 77
              out.println("</a></h1>");
 78
           }
 79
 80
           //description
           int descriptionNum = getChildElement(channel, "description");
 81
          XMLTree description = channel.child(descriptionNum);
 82
 83
 84
           out.print("");
 85
           if (description.numberOfChildren() > 0) {
 86
               out.print(description.child(0).label());
 87
 88
           out.println("");
 89
 90
           out.println("");
 91
           out.println("DateSourceNews");
 92
       }
 93
       /**
 94
 95
        * Outputs the "closing" tags in the generated HTML file. These are the
 96
        * expected elements generated by this method:
 97
        * 
 98
99
        * </body> </html>
100
101
        * @param out
102
                    the output stream
        * @updates out.contents
103
        * @requires out.is_open
104
        * @ensures out.content = #out.content * [the HTML "closing" tags]
105
106
107
       private static void outputFooter(SimpleWriter out) {
108
           assert out != null : "Violation of: out is not null";
109
           assert out.isOpen() : "Violation of: out.is_open";
110
111
           out.println("");
           out.println("</body>");
112
113
           out.println("</html>");
114
       }
115
       /**
116
        * Finds the first occurrence of the given tag among the children of the
117
118
        * given {@code XMLTree} and return its index; returns -1 if not found.
119
```

```
120
        * @param xml
121
                     the {@code XMLTree} to search
        * @param tag
122
123
                     the tag to look for
124
        * @return the index of the first child of type tag of the {@code XMLTree}
125
                or -1 if not found
        * @requires [the label of the root of xml is a tag]
126
127
        * @ensures 
128
        * getChildElement =
129
          [the index of the first child of type tag of the {@code XMLTree} or
130
            -1 if not found]
131
        * 
132
        */
       private static int getChildElement(XMLTree xml, String tag) {
133
           assert xml != null : "Violation of: xml is not null";
134
           assert tag != null : "Violation of: tag is not null";
135
136
           assert xml.isTag() : "Violation of: the label root of xml is a tag";
137
           int n = xml.numberOfChildren();
138
139
           int index = -1;
140
           int i = 0;
141
142
           while (i < n && index == -1) {</pre>
143
               if (xml.child(i).label().equals(tag)) {
144
                   index = i;
145
146
               i++;
147
148
           return index;
149
       }
150
151
152
        * Processes one news item and outputs one table row. The row contains three
153
        * elements: the publication date, the source, and the title (or
154
        * description) of the item.
155
156
        * @param item
157
                     the news item
158
        * @param out
159
                     the output stream
        * @updates out.content
160
        * @requires [the label of the root of item is an <item> tag] and
161
162
                    out.is open
        * @ensures 
163
164
        * out.content = #out.content *
165
           [an HTML table row with publication date, source, and title of news item]
        * 
166
167
       private static void processItem(XMLTree item, SimpleWriter out) {
168
           assert item != null : "Violation of: item is not null";
169
           assert out != null : "Violation of: out is not null";
170
           assert item.isTag() && item.label().equals("item") : ""
171
172
                   + "Violation of: the label root of item is an <item> tag";
173
           assert out.isOpen() : "Violation of: out.is_open";
174
175
           int indexPubDate = getChildElement(item, "pubDate");
176
           int indexSource = getChildElement(item, "source");
```

```
177
           int indexTitle = getChildElement(item, "title");
           int indexDescription = qetChildElement(item, "description");
178
           int indexLink = getChildElement(item, "link");
179
180
           out.println("");
181
182
183
           //publication date (if pubDate exists, it is required to have a child)
184
           if (indexPubDate >= 0) {
               out.println("" + item.child(indexPubDate).child(0).label()
185
186
                      + "");
187
           } else {
188
               out.println("No date available");
189
           }
190
           //source
191
192
           if (indexSource >= 0
193
                  && item.child(indexSource).numberOfChildren() > 0) {
194
               XMLTree source = item.child(indexSource);
               out.print("");
195
               out.print("<a href=\"" + source.attributeValue("url") + "\">");
196
197
               out.println(source.child(0).label() + "</a>");
198
           } else {
199
               out.println("No source available");
200
           }
201
202
           // link (if link exists, it is required to have a child)
203
204
           if (indexTitle >= 0 && item.child(indexTitle).numberOfChildren() > 0) {
205
               XMLTree title = item.child(indexTitle);
206
               out.print("");
207
               if (indexLink >= 0
                      && item.child(indexLink).numberOfChildren() > 0) {
208
209
                  XMLTree link = item.child(indexLink);
210
                   out.print("<a href=\"" + link.child(0).label() + "\">");
211
               }
212
               out.println(title.child(0).label() + "</a>");
213
           } else if (item.child(indexDescription).numberOfChildren() > 0) {
214
               XMLTree description = item.child(indexDescription);
215
               out.print("");
216
               if (indexLink >= 0
                      && item.child(indexLink).numberOfChildren() > 0) {
217
218
                  XMLTree link = item.child(indexLink);
                   out.print("<a href=\"" + link.child(0).label() + "\">");
219
220
               }
221
               out.println(description.child(0).label() + "</a>");
222
223
               out.print("No title available");
224
           }
225
226
           out.println("");
227
       }
228
       /**
229
230
        * Main method.
231
        * @param args
232
233
                     the command line arguments; unused here
```