

Exercise 3

```
MySQL 8.0 Command Line Cli  X  +  v
mysql>
mysql>
mysql> select * from S order by City DESC;
+----+-----+-----+-----+
| S# | Sname | Status | City |
+----+-----+-----+-----+
| S2 | Pallavi | 30 | Pune |
| S1 | Vaishnavi | 20 | Nanded |
| S3 | Malhari | 10 | Mumbai |
+----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select * from P order by City ASC, Pname ASC;
+----+-----+-----+-----+
| P# | Pname | Color | Weight | City |
+----+-----+-----+-----+
| P1 | Pen | Blue | 5.2 | Nanded |
| P3 | Book | Pink | 12.3 | Nashik |
| P2 | Pensil | Black | 8.1 | Pune |
+----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select * from S where Status between 10 and 20;
+----+-----+-----+-----+
| S# | Sname | Status | City |
+----+-----+-----+-----+
| S1 | Vaishnavi | 20 | Nanded |
| S3 | Malhari | 10 | Mumbai |
+----+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> select Pname, Weight from P where Weight < 10 or Weight > 15;
+-----+-----+
| Pname | Weight |
+-----+-----+
| Pen | 5.2 |
| Pensil | 8.1 |
+-----+-----+
2 rows in set (0.00 sec)

mysql> select Pname from P where Pname LIKE 'S%';
Empty set (0.00 sec)

MySQL 8.0 Command Line Cli  X  +  v
+----+-----+-----+-----+
| S# | Sname | Status | City |
+----+-----+-----+-----+
| S1 | Vaishnavi | 20 | Nanded |
| S3 | Malhari | 10 | Mumbai |
+----+-----+-----+-----+
2 rows in set (0.00 sec)

mysql> select Pname, Weight from P where Weight < 10 or Weight > 15;
+-----+-----+
| Pname | Weight |
+-----+-----+
| Pen | 5.2 |
| Pensil | 8.1 |
+-----+-----+
2 rows in set (0.00 sec)

mysql> select Pname from P where Pname LIKE 'S%';
Empty set (0.00 sec)

mysql> select * from S where City LIKE 'L%';
Empty set (0.00 sec)

mysql> selects * from J where Jname LIKE '__n%';
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use
near 'selects * from J where Jname LIKE '__n%' at line 1
mysql> SELECT *
-> FROM J
-> WHERE Jname LIKE '__n%';
Empty set (0.00 sec)

mysql> select Jname from J;
+-----+
| Jname |
+-----+
| Alpha |
| Beta |
| Gamma |
+-----+
3 rows in set (0.00 sec)

mysql> |
```

```
MySQL 8.0 Command Line Cli x + v
Enter password: ****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 9
Server version: 8.0.41 MySQL Community Server - GPL

Copyright (c) 2000, 2025, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> show databases;
+-----+
| Database |
+-----+
| exercise |
| information_schema |
| mydatabase |
| mysql |
| performance_schema |
| practice1 |
| sys |
+-----+
7 rows in set (0.03 sec)

mysql> use exercise;
Database changed
mysql> show tables;
+-----+
| Tables_in_exercise |
+-----+
| j |
| p |
| s |
| sdept |
| semp |
| spj |
+-----+
6 rows in set (0.01 sec)

mysql> select * from j, p, s, sdept, semp, spj;
```

```
MySQL 8.0 Command Line Cli x + v
mysql> select * from j;
+----+-----+-----+
| J# | Jname | City |
+----+-----+-----+
| J1 | Alpha | Mumbai |
| J2 | Beta | Nagpur |
| J3 | Gamma | Pune |
+----+-----+-----+
3 rows in set (0.00 sec)

mysql> select * from p;
+----+-----+-----+-----+-----+
| P# | Pname | Color | Weight | City |
+----+-----+-----+-----+-----+
| P1 | Pen | Blue | 5.2 | Nanded |
| P2 | Pensil | Black | 8.1 | Pune |
| P3 | Book | Pink | 12.3 | Nashik |
+----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select * from s;
+----+-----+-----+-----+
| S# | Sname | Status | City |
+----+-----+-----+-----+
| S1 | Vaishnavi | 20 | Nanded |
| S2 | Pallavi | 30 | Pune |
| S3 | Malhari | 10 | Mumbai |
+----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> select * from spj;
+----+-----+-----+-----+
| S# | P# | J# | Qty |
+----+-----+-----+-----+
| S1 | P1 | J1 | 300 |
| S1 | P2 | J2 | 200 |
| S2 | P1 | J1 | 100 |
| S3 | P3 | J3 | 150 |
+----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from semp;
```

```
MySQL 8.0 Command Line CLI x + v
| S3 | P3 | J3 | 150 |
+-----+
4 rows in set (0.00 sec)

mysql> select * from semp;
+-----+-----+-----+-----+-----+
| EMPNO | EMPNAME | BASIC | DEPTNO | DEPTHEAD |
+-----+-----+-----+-----+-----+
| 1 | SUNIL | 6000 | 10 | NULL |
| 2 | HIREN | 8000 | 20 | NULL |
| 3 | ALI | 4000 | 10 | 1 |
| 4 | GEORGE | 6000 | 2 | NULL |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql> select * from sdept;
+-----+-----+
| DEPTNO | DEPTNAME |
+-----+-----+
| 10 | Development |
| 20 | Training |
+-----+-----+
2 rows in set (0.00 sec)

mysql> select Sname from s where binary left (Sname, 1) = upper(left(Sname,1));
+-----+
| Sname |
+-----+
| Vaishnavi |
| Pallavi |
| Malhari |
+-----+
3 rows in set, 1 warning (0.00 sec)

mysql> select upper(Sname) as SupplierNameUpper from S;
+-----+
| SupplierNameUpper |
+-----+
| VAISHNAVI |
| PALLAVI |
| MALHARI |
+-----+
3 rows in set (0.00 sec)

MySQL 8.0 Command Line CLI x + v
3 rows in set (0.00 sec)

mysql> select lower(Sname) as suppliernamelower from S;
+-----+
| suppliernamelower |
+-----+
| vaishnavi |
| pallavi |
| malhari |
+-----+
3 rows in set (0.00 sec)

mysql> select lpad (Sname, 25, ' ') as paddedsuppliername from S;
+-----+
| paddedsuppliername |
+-----+
|          Vaishnavi |
|          Pallavi |
|          Malhari |
+-----+
3 rows in set (0.00 sec)

mysql> select replace(Sname, 'la', 'ro') as modifiedsuppliername from S;
+-----+
| modifiedsuppliername |
+-----+
| Vaishnavi |
| Palrovi |
| Malhari |
+-----+
3 rows in set (0.00 sec)

mysql> select replace(replace(Sname, 'l','r'),'a','o') as modifiedsuppliername from S;
+-----+
| modifiedsuppliername |
+-----+
| Voishnovi |
| Porrovi |
| Morhori |
+-----+
3 rows in set (0.00 sec)

mysql> select Sname, length(Sname) as namelength from S;
```

```
MySQL 8.0 Command Line CLI X + v
+-----+
3 rows in set (0.00 sec)

mysql> select Sname, length(Sname) as namelength from S;
+-----+
| Sname | namelength |
+-----+
| Vaishnavi | 9 |
| Pallavi | 7 |
| Malhari | 7 |
+-----+
3 rows in set (0.00 sec)

mysql> select * from S where soundex(Sname) = soundex('BLOKE');
Empty set (0.00 sec)

mysql> select Sname,
-> case
-> when status = 10 then 'TEN'
-> when status = 20 then 'Twenty'
-> when status = 30 then 'Thirty'
-> when status = 30 then 'FOURTY'
-> when status = 30 then 'FIFTY'
-> else 'Other'
-> end as statusText
-> from S;
+-----+
| Sname | statusText |
+-----+
| Vaishnavi | Twenty |
| Pallavi | Thirty |
| Malhari | TEN |
+-----+
3 rows in set (0.00 sec)

mysql> SELECT Sname,
-> CASE
-> WHEN Status = 10 THEN 'TEN'
-> WHEN Status = 20 THEN 'Twenty'
-> WHEN Status = 30 THEN 'Thirty'
-> WHEN Status = 40 THEN 'Forty'
-> WHEN Status = 50 THEN 'Fifty'
-> ELSE 'Other'
```

```
MySQL 8.0 Command Line CLI X + v
3 rows in set (0.00 sec)

mysql> SELECT Sname,
-> CASE
-> WHEN Status = 10 THEN 'TEN'
-> WHEN Status = 20 THEN 'Twenty'
-> WHEN Status = 30 THEN 'Thirty'
-> WHEN Status = 40 THEN 'Forty'
-> WHEN Status = 50 THEN 'Fifty'
-> ELSE 'Other'
-> END AS statusText
-> FROM S;
+-----+
| Sname | statusText |
+-----+
| Vaishnavi | Twenty |
| Pallavi | Thirty |
| Malhari | TEN |
+-----+
3 rows in set (0.00 sec)

mysql> SELECT Sname, Status FROM S;
+-----+
| Sname | Status |
+-----+
| Vaishnavi | 20 |
| Pallavi | 30 |
| Malhari | 10 |
+-----+
3 rows in set (0.00 sec)

mysql> select dayname(curdate()) as currentDay;
+-----+
| currentDay |
+-----+
| Monday |
+-----+
1 row in set (0.00 sec)

mysql> select curdate() as currentdate;
+-----+
| currentdate |
+-----+
```