

# Assignment 4

```
MySQL 8.0 Command Line Cll  X  +  v
Enter password: ****
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 11
Server version: 8.0.41 MySQL Community Server - GPL

Copyright (c) 2000, 2025, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> SELECT * FROM users;
ERROR 1046 (3D000): No database selected
mysql> show databases;
+-----+
| Database |
+-----+
| exercise |
| information_schema |
| mydatabase |
| mysql |
| performance_schema |
| practice1 |
| sys |
+-----+
7 rows in set (0.02 sec)

mysql> use practice1;
Database changed
mysql> SELECT * FROM users;
ERROR 1146 (42S02): Table 'practice1.users' doesn't exist
mysql> show tables;
+-----+
| Tables_in_practice1 |
+-----+
| customers |
| orders |
| salespeople |
+-----+
3 rows in set (0.01 sec)
```

```
MySQL 8.0 Command Line Cll x + v

mysql> select * from salespeople limit 5;
+-----+
| Snum | Sname | City | Comm |
+-----+
| 1001 | Peel | London | 0.12 |
| 1002 | Serres | San Jose | 0.13 |
| 1004 | Motika | London | 0.11 |
| 1007 | Rifkin | Barcelona | 0.15 |
| 1003 | Axelrod | New York | 0.10 |
+-----+
5 rows in set (0.00 sec)

mysql> select 'Onum','Amt','Odate', from orders;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'from orders' at line 1
mysql> select 'Onum','Amt','Odate', from 'orders';
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'from 'orders'' at line 1
mysql> select 'Onum','Amt','Odate' from 'orders';
+-----+
| Onum | Amt | Odate |
+-----+
| 3001 | 18.69 | 1990-10-03 |
| 3003 | 767.19 | 1990-10-03 |
| 3005 | 1900.10 | 1990-10-03 |
| 3006 | 1098.16 | 1990-10-03 |
| 3009 | 1713.23 | 1990-10-04 |
| 3007 | 75.75 | 1990-10-04 |
| 3008 | 4723.00 | 1990-10-05 |
| 3010 | 1309.95 | 1990-10-06 |
| 3011 | 9891.88 | 1990-10-06 |
+-----+
9 rows in set (0.00 sec)

mysql> select * from 'customers' where Snum = 1001;
+-----+
| Cnum | Cname | City | Rating | Snum |
+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
+-----+
2 rows in set (0.00 sec)

MySQL 8.0 Command Line Cll x + v

+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
+-----+
2 rows in set (0.00 sec)

mysql> select 'City','Sname','Snum','Comm' from 'salespeople';
+-----+
| City | Sname | Snum | Comm |
+-----+
| London | Peel | 1001 | 0.12 |
| San Jose | Serres | 1002 | 0.13 |
| London | Motika | 1004 | 0.11 |
| Barcelona | Rifkin | 1007 | 0.15 |
| New York | Axelrod | 1003 | 0.10 |
+-----+
5 rows in set (0.00 sec)

mysql> select 'Rating','Cname' from 'customers' where 'City' = 'San jose';
ERROR 1054 (42S22): Unknown column 'San jose' in 'where clause'
mysql> select 'Rating','Cname' from 'customers' where 'City' = 'San Jose';
ERROR 1054 (42S22): Unknown column 'San Jose' in 'where clause'
mysql> select 'Rating','Cname' from 'customers' where 'City' = 'San Jose';
+-----+
| Rating | Cname |
+-----+
| 200 | Liu |
| 300 | Cisneros |
+-----+
2 rows in set (0.00 sec)

mysql> select distinct 'Snum' from 'orders';
+-----+
| Snum |
+-----+
| 1007 |
| 1004 |
| 1003 |
| 1002 |
| 1001 |
+-----+
5 rows in set (0.00 sec)

mysql>
```