

```
C pc.c > main()
1  #include <stdio.h>
2
3  #define PI 3.14
4  #define MAX 100
5  #define NAME "Navi"
6
7  int main() {
8      printf("Value of PI = %.2f\n", PI);
9      printf("Max Value = %d\n", MAX);
10     printf("Name = %s\n", NAME);
11
12     return 0;
13 }
14
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS C:\Users\ACER\Desktop\jss> ./a.exe
```

```
Value of PI = 3.14
```

```
Max Value = 100
```

```
Name = Navi
```

```
PS C:\Users\ACER\Desktop\jss> 
```

Experiment 12: Preprocessors & Directives in C.

Q.1 WAP to define some constant variable in preprocessor.

```
#include <stdio.h>
```

```
#define PI 3.14
```

```
#define MAX 100
```

```
#define NAME "Nani"
```

```
int main() {
```

```
    printf("Value of PI = %.2f\n", PI);
```

```
    printf("Max Value = %d\n", MAX);
```

```
    printf("Name = %s\n", NAME);
```

```
    return 0; }
```

Q.2 WAP to define a function in directives.

```
#include <stdio.h>
```

```
#define square(x) ((x) * (x))
```

```
#define sum(a,b) ((a) + (b))
```

```
int main() {
```

```
    int n=5, a=10, b=20;
```


C pc.c >  SQUARE(x)

```
1  #include <stdio.h>
2
3  #define SQUARE(x) ((x) * (x))
4  #define SUM(a,b) ((a) + (b))
5
6  int main() {
7      int n = 5, a = 10, b = 20;
8
9      printf("Square of %d = %d\n", n, SQUARE(n));
10     printf("Sum = %d\n", SUM(a, b));
11
12     return 0;
13 }
14
```

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

PS C:\Users\ACER\Desktop\jss> gcc pc.c

PS C:\Users\ACER\Desktop\jss> ./a.exe

Square of 5 = 25

Sum = 30

PS C:\Users\ACER\Desktop\jss> 

Expt. No. _____

Page No. _____

```
printf("Square of %d is %d", n, n * n);  
printf("%d\n", sum(a, b));
```

```
return 0;  
}
```