Security Audit Report

Generated on September 26, 2026

Report ID: RPT-AUD-324698

Organization: Admin Organization

Assessment Period: September 26, 2026

Generated By: VAJRA CORE System

Technical Assessment Summary

Metric	Value
Total Devices Assessed	0
Configurations Analyzed	0
Security Audits Performed	0
Overall Compliance Score	0.0%
Risk Level	UNKNOWN

Findings by Severity

Severity	Count
CRITICAL	0
HIGH	0
MEDIUM	0
LOW	0

Device Assessment Details

Detailed Security Findings

[HIGH] Telnet Must Be Disabled
Finding ID: FND-9F314386

Telnet is inherently insecure and must not be enabled. Use SSH version 2 for encrypted remote access.

[HIGH] SSH Must Be Enabled
Finding ID: FND-F8A7DAF8

SSH is the industry standard for secure remote device access. It must be enabled and properly configured.

[MEDIUM] SSH Version 2 Required
Finding ID: FND-FA5AFDC7

SSHv1 is deprecated due to security vulnerabilities. Configure 'ip ssh version 2' to enforce SSHv2 only.

[HIGH] HTTP Management Must Be Disabled
Finding ID: FND-E7F9C37B

Unencrypted HTTP exposes management credentials and configuration. Use 'no ip http server' and enable HTTPS instead.

[MEDIUM] HTTPS Management Should Be Enabled
Finding ID: FND-2751F0F4

HTTPS encrypts management traffic and credentials. Configure with 'ip http secure-server'.

[MEDIUM] Local Authentication Should Be Enabled
Finding ID: FND-EDB58CDB

Configure local user accounts and 'login local' for accountability.

[HIGH] Enable Secret Should Be Configured
Finding ID: FND-B3CD7587

Configure 'enable secret' with a strong password. This is critical for privileged access control.

[LOW] Password Encryption Should Be Enabled
Finding ID: FND-184E56D2

Enable with 'service password-encryption' to obfuscate passwords. Note: This is weak encryption but better than plaintext.

[MEDIUM] Logging Should Be Enabled
Finding ID: FND-DEFC806E

Configure remote syslog server with 'logging '. Enables security event tracking and analysis.

[LOW] Session Timeout Should Be Configured
Finding ID: FND-FC419DE0

Configure 'exec-timeout' or 'timeout login response' to automatically disconnect idle sessions.

Evidence & Provenance

All findings in this report are backed by evidence extracted from actual device configurations. Evidence includes configuration line numbers, extracted configuration snippets, and parser provenance information. **Security Note:** Sensitive information (passwords, keys, secrets) has been sanitized and does not appear in this report.

Remediation Guidance