Security Audit Report

Generated on September 26, 2026

Report ID: RPT-AUD-324698

Organization: Admin Organization

Assessment Period: September 26, 2026

Generated By: VAJRA CORE System

Technical Assessment Summary

Metric	Value
Total Devices Assessed	0
Configurations Analyzed	0
Security Audits Performed	0
Overall Compliance Score	0.0%
Risk Level	UNKNOWN

Findings by Severity

Severity	Count
CRITICAL	0
HIGH	0
MEDIUM	0
LOW	0

Technical Assessment Details

Configuration File: test_cisco_config.cfg

Detected Vendor: Unknown

Assessment Date: 2026-09-26 11:32:14

Security Findings Distribution:

• HIGH: 3 findings

• MEDIUM: 2 findings

Assessment Results:

• FAIL: 5 controls

• PASS: 2 controls

• UNKNOWN: 1 controls

• WARNING: 2 controls

Overall Risk Assessment: HIGH (Score: 72.75)

Device Assessment Details

Detailed Security Findings

[HIGH] Telnet Must Be Disabled
Finding ID: FND-9F314386 | Rule: NET-001 | Status: FAIL

Description: Telnet is inherently insecure and must not be enabled. Use SSH version 2 for encrypted remote access.

Expected: False

Actual: True

Remediation: # Remove 'telnet' from transport input or allowaccess configuration. Ensure SSH remains enabled for secure remote access. # Vendor-specific command not available

Field Path: `remote_access.telnet_enabled`

[HIGH] SSH Must Be Enabled
Finding ID: FND-F8A7DAF8 | Rule: NET-002 | Status: PASS

Description: SSH is the industry standard for secure remote device access. It must be enabled and properly configured.

Expected: True

Actual: True

Field Path: `remote_access.ssh_enabled`

[MEDIUM] SSH Version 2 Required
Finding ID: FND-FA5AFDC7 | Rule: NET-003 | Status: UNKNOWN

Description: SSHv1 is deprecated due to security vulnerabilities. Configure 'ip ssh version 2' to enforce SSHv2 only.

Expected: 2

Actual: N/A

Field Path: `remote_access.ssh_version`

[HIGH] HTTP Management Must Be Disabled
Finding ID: FND-E7F9C37B | Rule: NET-004 | Status: FAIL

Description: Unencrypted HTTP exposes management credentials and configuration. Use 'no ip http server' and enable HTTPS instead.

Expected: False

Actual: True

Remediation: # HTTP transmits credentials in cleartext. Use HTTPS for web management. # Vendor-specific command not available

Field Path: `management.http_enabled`

[MEDIUM] HTTPS Management Should Be Enabled
Finding ID: FND-2751F0F4 | Rule: NET-005 | Status: PASS

Description: HTTPS encrypts management traffic and credentials. Configure with 'ip http secure-server'.

Expected: True

Actual: True

Field Path: `management.https_enabled`

[MEDIUM] Local Authentication Should Be Enabled
Finding ID: FND-EDB58CDB | Rule: NET-006 | Status: FAIL

Description: Configure local user accounts and 'login local' for accountability.

Expected: True

Actual: False

Remediation: # Local authentication provides fallback access and enables user tracking. # Vendor-specific command not available

Field Path: `authentication.local_authentication`

[HIGH] Enable Secret Should Be Configured
Finding ID: FND-B3CD7587 | Rule: NET-007 | Status: FAIL

Description: Configure 'enable secret' with a strong password. This is critical for privileged access control.

Expected: True

Actual: False

Remediation: # Enable secret controls privileged EXEC access. Use strong password. # Vendor-specific command not available

Field Path: `authentication.enable_secret_configured`

[LOW] Password Encryption Should Be Enabled
Finding ID: FND-184E56D2 | Rule: NET-008 | Status: WARNING

Description: Enable with 'service password-encryption' to obfuscate passwords. Note: This is weak encryption but better than plaintext.

Expected: True

Actual: False

Field Path: `authentication.password_encryption`

[MEDIUM] Logging Should Be Enabled

Finding ID: FND-DEFC806E | Rule: NET-009 | Status: FAIL

Description: Configure remote syslog server with 'logging '. Enables security event tracking and analysis.

Expected: True

Actual: False

Remediation: # Security logging is essential for audit trails and incident response. # Vendor-specific command not available

Field Path: `logging.enabled`

[LOW] Session Timeout Should Be Configured

Finding ID: FND-FC419DE0 | Rule: NET-010 | Status: WARNING

Description: Configure 'exec-timeout' or 'timeout login response' to automatically disconnect idle sessions.

Expected: True

Actual: False

Field Path: `access_control.timeout_configured`

Evidence & Provenance

All findings in this report are backed by evidence extracted from actual device configurations. Evidence includes configuration line numbers, extracted configuration snippets, and parser provenance information. **Security Note:** Sensitive information (passwords, keys, secrets) has been sanitized and does not appear in this report.

Remediation Guidance

Priority 1: Critical & High Severity Issues

These issues should be addressed immediately as they pose significant security risks.

[HIGH] Telnet Must Be Disabled:
Remove 'telnet' from transport input or allowaccess configuration. Ensure SSH remains enabled for secure remote access. # Vendor-specific command not available

[HIGH] HTTP Management Must Be Disabled:
HTTP transmits credentials in cleartext. Use HTTPS for web management. # Vendor-specific command not available

[HIGH] Enable Secret Should Be Configured:
Enable secret controls privileged EXEC access. Use strong password. # Vendor-specific command not available

Priority 2: Medium & Low Severity Issues

These issues should be addressed as part of regular security maintenance.

[MEDIUM] Local Authentication Should Be Enabled:
Local authentication provides fallback access and enables user tracking. # Vendor-specific command not available

[MEDIUM] Logging Should Be Enabled:
Security logging is essential for audit trails and incident response. # Vendor-specific command not available

General Security Recommendations

- Implement a regular configuration review process
- Establish security configuration baselines
- Enable comprehensive logging and monitoring
- Implement automated compliance checking
- Schedule periodic security assessments