## **CUI** DEVICES

**date** 10/10/2019

page 1 of 3

SERIES: SJ1-355XNG | DESCRIPTION: 3.5 MM AUDIO JACK


#### **FEATURES**

- low profile design
- switch options include:
- no switch
- tip switch
- tip and ring switch





#### **PART NUMBER KEY**



Note: 1. Tip and ring switch model only

#### **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	Α
contact resistance <sup>2</sup>	between terminal and mating plug between terminal in a closed circuit			50 30	$m\Omega$
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	at 50/60 Hz for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
terminal strength	any direction for 10 seconds			500	g
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-0				
RoHS	yes				

Notes: 2. When measured at a current of less than 100 mA / 1 kHz


#### **SOLDERABILITY**


parameter	conditions/description	min	typ	max	units
wave soldering	dipped in solder pot for 5±0.5 seconds at	255	260	265	°C


### **MECHANICAL DRAWING**


TOLERANCE:  $X.X \pm 0.2mm$  $X.XX \pm 0.1mm$  $X.XXX \pm 0.05mm$ 

units: mm[inches]











	MATERIAL	PLATING
terminal 1	brass	tin
terminal 2	copper alloy	tin
terminal 3	copper alloy	tin
terminal 4	brass	tin
terminal 5	brass	tin
plastic	PBT	





Model No.	SJ1-3553NG	SJ1-3554NG	SJ1-3555NG
Schematic	°1 °3 °3	01 03 04 02	01 03 05 04 02
PIN			
1	sleeve	sleeve	sleeve
2	tip	tip	tip
3	ring	ring	ring
4	NP	tip switch	tip switch
5	NP	NP	ring switch

Additional Resources: Product Page | 3D Model | PCB Footprint

CUI Devices | SERIES: SJ1-355XNG | DESCRIPTION: 3.5 MM AUDIO JACK date 10/10/2019 | page 3 of 3

#### **REVISION HISTORY**

rev.	description	date
1.0	initial release	02/07/2006
1.01	new template applied	02/15/2012
1.02	updated datasheet	04/18/2017
1.03	brand update	10/10/2019

The revision history provided is for informational purposes only and is believed to be accurate.

# **CUI** DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

### **CUI Devices**:

SJ1-3553NG SJ1-3555NG SJ1-3555NG-GR SJ1-3555NG-PI SJ1-3555NG-BE