

Dask IO for sequentially splitting, merging and resplitting multidimensional arrays

Timothée Guédon, Valérie Hayot-Sasson, Tristan Glatard

Department of Computer Science and Software Engineering, Concordia University, Montreal, Canada

Abstract—**Todo.**

Index Terms—**multidimensional, array, split, merge, resplit, IO, processing, Dask, Python**

I. INTRODUCTION

With the improvement of acquisition methods in several scientific domains such as health sciences, geology and astrophysics, new big data challenges have emerged. Such challenges includes processing big amounts of data and manipulating heavy files like ultra high resolution images. Big Brain, a brain model providing microscopic data (20 micrometers) for modeling and simulation [1] is an example of ultra high resolution images in the neuroscience field.

A. Multidimensional array chunking

On the one hand, scientific applications often model problems as multidimensional arrays that must be stored in chunks for later processing and analysis. Chunking allows for efficient queries and great flexibility in adding new data, among other things. On the other hand, block algorithms are necessary when data cannot be entirely loaded in memory and to parallelize computations.

Multidimensional array chunking raises the need for tools to efficiently split, merge and “resplit” or “rechunk” data files. Previous work in [2] show that naive algorithms to split an array into several files and merge back those files into one output file perform very poorly due to millions of seeks occurring on disk.

B. The occurrence of seeks

For this study we manipulate multidimensional arrays stored in hdf5 files, that is why we assume that files are written in row-major order (a.k.a “C” ordering), where the fastest moving dimension in the file is the last dimension in the array and the slowest moving dimension in the file is the first dimension in the array. For example a 3D array with dimensions i, j and k would be written on disk by writing the complete columns in the k dimension first (see Figure ??). As in previous work [2], we assume that the storage layout can be arbitrary as long as it is known to the algorithm.

Retrieving subarrays from an array stored on disk incurs seeks. When accessing a multi-dimensional array, seeks occur in two situations: (1) when an array block is opened for reading or writing, and (2) when the reading or writing process moves within the block to write at different places. While reading the data of interest, one needs to seek to the beginning of each

contiguous piece of data constituting the subarray. For a 3D cuboid of shape C , stored in row-major order, each column of data in the k dimension is contiguously stored. They are therefore $C_j * C_i$ data columns for which a seek is required on disk. Although the seek time depends on various parameters such as the distance in bytes between two data columns, we assume all seeks to incur the same time overhead for the sake of simplicity. We further assume that reducing the number of seeks is representative of reducing the processing speed.

C. The multiple and clustered strategies

Two strategies have been introduced in [2] for the split and merge tasks. To illustrate these strategies we shall apply it to the split task ($R = I$) as it is considered a dual operation of the merge task. The naive strategy to split an array is to repeatedly loading one subarray of shape O and writing it down into an output file [2].

The clustered strategy consists in loading contiguous blocks of data of shape O from the input array in order to write it in one seek in each output file which data has been loaded. This strategy loads data blocks one by one, block columns by block columns or blocks slices by block slices. Using this strategy for resplitting would imply reading multiple input files that are contiguous in the reconstructed image or reading the data of contiguous output files by seeking into input files. In either case one can easily find bad cases in which the algorithm seeks in all dimensions.

The multiple strategy aims at not doing any seek while reading and writing. For example, one would read the input file slice by slice and write this slices contiguously in the output files. The tradeoff lies in switching between files at each buffer loading. Using this strategy for the resplit task would imply reading contiguous columns or slices of data from the input files and writing it contiguously in the output files. This would result in even more switches between input and output files and one can easily find worst cases when using small I and O shapes for example where a smarter strategy would be appreciated.

To the best of our knowledge however, no algorithm has been proposed for the resplit task.

D. Problem definition

We focus on 3D arrays for simplicity. Consider a 3D array of shape $R = (R_i, R_j, R_k)$, stored as input blocks of uniform shape $I = (I_i, I_j, I_k)$. Our goal is to resplit the

input blocks into output blocks of uniform but different shape $O = (O_i, O_j, O_k)$.

A resplit algorithm (Algorithm 1) takes as input a list of input blocks `inBlocks` of shape I , a list of output blocks `outBlocks` of shape O , the amount of available memory m , and a list of buffers `buffersList` defining a partition of array R . The algorithm successively loads the image regions defined by the buffers, and writes them to the output blocks.

For simplicity, we require that all buffers in `buffersList` have the same shape. Our problem is to find the partition `bufferList` that minimizes the number of seeks done by Algorithm 1 given I and O , subject to the amount m of available memory.

Algorithm 1 General resplit algorithm

Inputs: `inFiles`, `outFiles`, `buffersList`
for `buffer` in `buffersList` **do**
 `read(inFiles, buffer)`
 `write(outFiles, buffer)`
end for

E. Baseline solution

Let us consider a baseline solution where the buffers in `bufferList` have the same shape as the input files ($B = I$) and the order is the same order than the storage order i.e. the column order ($[k, j, i]$ order).

F. A particular case: $I = kO$

If the input shape is a multiple of the output shape then the problem is easily solved by reading as many input blocks as can fit in m . In this case, the buffer shape B is a multiple of the input shape I . This solution results in one seek to read each input block, and one seek to write each output block, which is the minimum number of seeks possible for a resplit.

If there is a mismatch between the shapes in any dimension however, we need a strategy to manage this overlap while minimizing the number of seeks.

G. Contributions

This paper makes the following contributions:

- We define the resplit problem
- We propose a first sequential algorithm to efficiently resplit multidimensional arrays
- We give a public implementation of such algorithm in the Python library `dask`
- We enable the use of the clustered strategy for splitting and merging multidimensional arrays in `dask`

II. THE “KEEP” ALGORITHM

III. A MEMORY ANALYSIS OF THE KEEP STRATEGY

IV. METHODS

V. IMPLEMENTATION DETAILS

VI. RESULTS

VII. DISCUSSION

Future work : - the split and merge tasks are special cases of the resplit task, which gives an opportunity to solve the

three problems at once.

VIII. CONCLUSION

IX. ACKNOWLEDGMENTS

REFERENCES

- [1] K. Amunts, C. Lepage, L. Borgeat, H. Mohlberg, T. Dicksccheid, M.-É. Rousseau, S. Bludau, P.-L. Bazin, L. B. Lewis, A.-M. Oros-Peusquens, N. J. Shah, T. Lippert, K. Zilles, and A. C. Evans, “Bigbrain: An ultrahigh-resolution 3d human brain model,” *Science*, vol. 340, no. 6139, pp. 1472–1475, 2013.
- [2] V. Hayot-Sasson, Y. Gao, Y. Yan, and T. Glatard, “Sequential algorithms to split and merge ultra-high resolution 3d images,” in *2017 IEEE International Conference on Big Data (Big Data)*, pp. 415–424, Dec 2017.