PRACTICE QUIZ • 12 MIN

Metrics

Submit your assignment — Try again

Receive grade
TO PASS 66% or higher

Grade 83%

View Feedback
We keep your highest score

Metrics

TOTAL POINTS 6

1. **What would be a logloss value for a binary classification task, if we use constant predictor f(x) = 0.5? Round to two decimal places.** — 1 point

Enter answer here

2. **The best constant predictor for MAE metric is** — 1 point

- [ ] Target median
- [ ] Target mode
- [ ] Target mean
- [ ] Target 50-th percentile
- [ ] 0.5

3. **The best constant predictor for mean squared error is** — 1 point

- [ ] Target mean
- [ ] Average of the target vector
- [ ] $log(y+1)$, where y is target vector
- [ ] Target variance

4. **The best constant prediction for AUC is** — 1 point

- [ ] Target mean
- [ ] 0.5
- [ ] 1
- [ ] Target median
- [ ] Target mean divided by target variance
- [ ] Any constant will lead to the same AUC value

5. **Suppose the target metric is R-squared. What optimization loss should we use for our models?** — 1 point

- [ ] RMSLE
- [ ] RMSE
- [ ] MSE
- [ ] MAE
- [ ] AUC

6. **Calculate AUC for these predictions:** — 1 point

target	prediction
1	0.39
0	0.52
1	0.91
1	0.85
1	0.49
0	0.02
0	0.44

Round to 2 decimal places.

Enter answer here

I, **Hong-Yuan Lin**, understand that submitting work that isn't my own may result in permanent failure of this course or deactivation of my Coursera account.
Learn more about Coursera's Honor Code

Save Submit