Simulation with a basal fluid source **(1.9x10^{-9} m/s)**, performed with an initial stress defined as $\sigma_1 = \sigma_3$, a fault permeability equal to **10^9 m^2,** and Λ=0.7 MPa/°C.

Data in Folder "q0_1.9":

- **Fault_velocity**: fault velocity "Vf" (m/s) fluctuation along the fault during the seismic cycles. *(Data used for Figure 6.c)*
- **Thermal:** Thermal anomalies (°C) fluctuation along the fault during the seismic cycle
- **Time**: Time variable (yrs). Data was printed every 0.1 second during the coseismic period, and every 1 year during the interseismic period.
- **Depth:** Depth of the fault nodes (m).

- **velocity**: fault velocity "Vf" (m/s) fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Anomaly_temperature**: Thermal anomalies (°C) fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Pore_fluid:** Pore-fluid factor (λ) fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Apparent_friction**: apparent friction coefficient fluctuation at 12.75 km depth on the fault during the seismic cycle
- **mean_slip**: mean slip along the fault during the seismic cycles.
- **Time2**: Time variable (yrs) for **Mean_shearStress, velocity, Anomaly_temperature, Pore_fluid, Apparent_friction and Mean_slip** data. Data was printed every 0.1 second during the coseismic period, and every 1 year during the interseismic period.