Simulation with a basal fluid source **(0.75x10^{-9} m/s)**, performed with an initial stress defined as $\boldsymbol{\sigma_1} = \boldsymbol{\sigma_3}$, a fault permeability equal to **10^{9} m^{2},** and Λ=0.7 MPa/°C.

Data in Folder "q0_0.75":

- **Mean_shearStress**: tangential stress "τ" (Pa) fluctuation at 12.75 km depth on the fault during the seismic cycle.
- **velocity**: fault velocity "Vf" (m/s) fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Anomaly_temperature**: Thermal anomalies (°C) fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Pore_fluid:** Pore-fluid factor (λ) fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Apparent_friction**: apparent friction coefficient fluctuation at 12.75 km depth on the fault during the seismic cycle
- **Mean_slip**: mean slip along the fault during the seismic cycles.
- **Time2**: Time variable (yrs) for **Mean_shearStress, velocity, Anomaly_temperature, Pore_fluid, Apparent_friction and Mean_slip** data. Data was printed every 0.1 second during the coseismic period, and every 1 year during the interseismic period.