

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate



TF0394

Datos del Producto Product Information								
Diametro [mm] Diameter	38,1	Cliente Client	ТОҮОТА	Ciclo Product	1106			
Espesor [mm] Wall Thickness	2,9	Tratamiento Termico	NO	Colada _{Heat}	38348			
Trazabilidad Traceability	0			Expediente Manufacturing Order				



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Externo longitudinal OD	0,80	10	±10	0,319	0,261	0,290	25,40	25,00	0,319	0,319	0,69	Daniel Carcacha	07/06/10
В	Longitudinal Externo longitudinal OD	0,80	10	±10	0,319	0,261	0,290	25,40	25,00	0,318	0,317	0,70	Daniel Carcacha	07/06/10
С	Longitudinal Externo longitudinal OD	0,80	10	±10	0,319	0,261	0,290	25,40	25,00	0,318	0,317	0,70	Daniel Carcacha	07/06/10
Е	Longitudinal Interno Longitudinal ID	0,80	10	±10	0,319	0,261	0,290	25,40	24,00	0,319	0,319	0,71	Daniel Carcacha	07/06/10

Instrumentos de Medicion Utilizados:

Calibre Pie de Rey Codigo:

Notas:

- 1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.
- 2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA NO

Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA NO