

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate



CF103

Datos del Producto Product Information									
Diametro [mm]	88,9	Cliente Client		Ciclo Product	65944				
Espesor [mm] Wall Thickness	6,45	Tratamiento Termico Heat Treatment	NO	Colada _{Heat}	50175				
Trazabilidad Traceability	0			Expediente Manufacturing Order					



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam		Tolerancia [%] Tolerance		Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Interno Longitudinal ID	1,00	8	±15	0,593	0,439	0,516	50,80	49,30	0,550	0,552	0,87	Default Default	26/09/07
В	Longitudinal Externo longitudinal OD	1,00	5	±15	0,371	0,274	0,323	50,80	50,80	0,353	0,351	0,85	Default Default	26/09/07

Instrumentos de Medicion Utilizados:

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA SI

Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA YES

1/2