

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate

Tubo patrón número
Reference standard #

2u285





Valores Pedidos / Requested Values

Valores Medidos / Measured Values

	. caiacc, itoquectea i	4.400							00 1110 01 000 7	27 Modeli od 14.400				
Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Δ	Agujero Pasante Drilled hole	3,20	-	-	-	-	-	-	-	-	-	3,20	Sebastian Monteros	07/06/04
В	Chavetero Grove	6,00	50	±15	6,153	4,548	5,350	50,00	49,00	5,400	5,400	5,60	Sebastian Monteros	07/06/04
С	Transversal Externo Transverse OD	1,00	5	±15	0,615	0,455	0,535	50,00	48,00	0,483	0,525	0,97	Sebastian Monteros	07/06/04
D	Longitudinal Externo longitudinal OD	1,00	5	±15	0,615	0,455	0,535	50,00	49,00	0,533	0,521	0,99	Sebastian Monteros	07/06/04
Е	Transversal Interno Transverse ID	1,00	5	±15	0,615	0,455	0,535	50,00	36,00	0,504	0,589	0,99	Sebastian Monteros	07/06/04
F	Longitudinal Interno Longitudinal ID	1,00	5	±15	0,615	0,455	0,535	50,00	48,00	0,530	0,478	0,99	Sebastian Monteros	07/06/04
G	Agujero Pasante Drilled hole	3,20	-	-	-	-	-	-	-	-	-	3,20	Sebastian Monteros	07/06/04

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA NO

Notes:

1.-All dimensions in milimeters unless stated.

1/2

2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA NO



CERTIFICADO PATRON DE CND

TEND

TAND-001-05

17/04/2006

NDT Reference Standard Certificate

Tubo patrón número
Reference standard #

2u285

Datos del Producto Product Information									
Diametro [mm] Diameter	88,9	Cliente Client	Ciclo Product	75479					
Espesor [mm] Wall Thickness	10,7	Tratamiento Termico Heat Treatment	Colada _{Heat}	0					
Trazabilidad Traceability	0		Expediente Manufacturing Order						

Instrumentos de Medicion Utilizados:

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA NO

Notes:

1.-All dimensions in milimeters unless stated.

2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA NO