

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate

Tubo patrón número
Reference standard #

1C1985

Datos del Producto Product Information								
Diametro [mm]	88,9	Cliente Client	DEMO	Ciclo Product	70067			
Espesor [mm] Wall Thickness	5,5	Tratamiento Termico	DEMO	Colada _{Heat}	70792			
Trazabilidad Traceability	0			Expediente Manufacturing Order	DEMO			



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Interno Longitudinal ID	0,93	5	±15	0,316	0,234	0,275	47,60	46,70	0,554	0,562	0,85	N/A N/A	17/06/10
В	Longitudinal Externo longitudinal OD	1,00	5	±15	0,316	0,234	0,275	50,80	46,90	0,298	0,302	0,83	N/A N/A	17/06/10
С	Transversal Externo Transverse OD	1,00	5	±15	0,316	0,234	0,275	50,80	36,20	0,338	0,305	0,86	N/A N/A	17/06/10
D	Transversal Interno Transverse ID	1,00	5	±15	0,316	0,234	0,275	50,80	36,60	0,522	0,531	0,85	N/A N/A	17/06/10

Instrumentos de Medicion Utilizados:

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA SI

Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA YES