

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate

Tubo patrón número Reference standard #

TF0509

Datos del Producto Product Information									
Diametro [mm]	48	Cliente Client	METALMECA NICA S	Ciclo Product	27117				
Espesor [mm] Wall Thickness	11	Tratamiento Termico Heat Treatment	SI	Colada _{Heat}	32707				
Trazabilidad Traceability	0			Expediente Manufacturing Order					



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	[mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Externo longitudinal OD	0,60	11	+1-0	1,211	1,199	1,199	25,00	25,00	1,199	1,199	0,60	Daniel Carcacha	14/07/14
В	Longitudinal Interno Longitudinal ID	0,60	11	+1-0	1,211	1,199	1,199	25,00	24,50	1,199	1,199	0,55	Dante Antunez	12/07/14
С	Longitudinal Externo longitudinal OD	0,60	11	+10-0	1,319	1,199	1,199	25,00	25,00	1,199	1,199	0,60	Daniel Carcacha	14/07/14
D	Longitudinal Externo longitudinal OD	0,60	11	+10-0	1,319	1,199	1,199	25,00	25,00	1,199	1,199	0,60	Daniel Carcacha	14/07/14

Instrumentos de Medicion Utilizados:

Calibre Pie de Rey Codigo:

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA NO

Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA NO