

# CERTIFICADO PATRON DE CND


**TEND** 

NDT Reference Standard Certificate



**TF0270** 

Datos del Producto Product Information								
Diametro [mm]	60,1	Cliente Client	ТуР	Ciclo Product	37267			
Espesor [mm] Wall Thickness	4,75	Tratamiento Termico Heat Treatment	NO	Colada <sub>Heat</sub>	0			
Trazabilidad Traceability	0			Expediente Manufacturing Order	8/8843-05			



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Interno Longitudinal ID	0,60	10	+10-0	0,523	0,475	0,475	25,00	24,50	0,440	0,440	0,44	Daniel Carcacha	28/01/08
В	Longitudinal Externo longitudinal OD	0,60	10	+10-0	0,523	0,475	0,475	25,00	23,50	0,461	0,461	0,44	Daniel Carcacha	28/01/08
С	Transversal Externo Transverse OD	0,60	10	+10-0	0,523	0,475	0,475	25,00	25,00	0,458	0,458	0,44	Daniel Carcacha	28/01/08
D	Transversal Interno Transverse ID	0,60	10	+10-0	0,523	0,475	0,475	25,00	22,00	0,465	0,465	0,49	Daniel Carcacha	29/01/08

### Instrumentos de Medicion Utilizados:

## Comparador a cuchilla Codigo:

### Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA NO

### Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA NO