

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate



1C2152





Valores Pedidos / Requested Values

Valores Medidos / Measured Values

<u>'</u>														
Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Interno Longitudinal ID	1,00	10	±15	0,552	0,408	0,480	50,80	47,60	0,538	0,532	0,93	Dante Antunez	25/03/11
В	Longitudinal Externo longitudinal OD	1,00	6	±15	0,345	0,255	0,300	50,80	48,00	0,332	0,340	0,84	Daniel Carcacha	24/03/11
С	Transversal Externo Transverse OD	1,00	6	±15	0,345	0,255	0,300	50,80	44,00	0,336	0,328	0,84	Daniel Carcacha	24/03/11
D	Transversal Interno Transverse ID	0,89	6	±15	0,345	0,255	0,300	50,80	41,00	0,340	0,326	0,89	Dante Antunez	25/03/11

Instrumentos de Medicion Utilizados:

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA SI

Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA YES

1/2