

CERTIFICADO PATRON DE CND


TEND

NDT Reference Standard Certificate

Tubo patrón número Reference standard #

SS0205

Datos del Producto Product Information								
Diametro [mm]	60,3	Cliente Client	DEMO	Ciclo Product	60038			
Espesor [mm] Wall Thickness	7,2	Tratamiento Termico	DEMO	Colada _{Heat}	38879			
Trazabilidad Traceability	0			Expediente Manufacturing Order	DEMO			



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	Longitud [mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Transversal Externo Transverse OD	0,89	10	±15	0,828	0,612	0,720	44,50	36,20	0,412	0,413	0,83	Dante Antunez	09/06/10
ĸ	Longitudinal Externo longitudinal OD	1,00	10	±15	0,828	0,612	0,720	50,80	37,90	0,385	0,365	0,83	Dante Antunez	09/06/10
(-	Longitudinal Externo longitudinal OD	1,00	7	±15	0,580	0,428	0,504	50,00	36,50	0,407	0,412	0,83	Dante Antunez	09/06/10
D	Transversal Externo Transverse OD	1,00	7	±15	0,580	0,428	0,504	50,00	37,70	0,376	0,402	0,81	Dante Antunez	09/06/10

Instrumentos de Medicion Utilizados:

Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA SI

Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA YES

1/2