

## CERTIFICADO PATRON DE CND


**TEND** 

NDT Reference Standard Certificate



1C954

Datos del Producto Product Information Ciclo Product Cliente Diametro [mm] 88.9 25126 Diameter Espesor [mm]
Wall Thickness Tratamiento Termico Colada 6.45 No 37726 **Heat Treatment** Heat Trazabilidad Expediente Manufacturing Order 0 Traceability



Valores Pedidos / Requested Values

Valores Medidos / Measured Values

Posicion Position	Tipo de Notch Notch Type	Ancho / Diam Max [mm] Max Width / Diam	Profundidad Nominal [%] Depth	Tolerancia [%] Tolerance	Profundidad Maxima [mm] Max Depth	Profundidad Minima [mm] Min Depth	Profundidad Nominal [mm] Nom Depth	Longitud Maxima [mm] Max Length	[mm] Length	Profundida d A [mm] Depth A	Profundida d B [mm] Depth B	Ancho / Diam [mm] Width / Diam	Responsable Responsible	Fecha Date
Α	Longitudinal Interno Longitudinal ID	1,00	5	±15	0,371	0,274	0,323	38,10	36,00	0,358	0,342	0,85	Sebastian Monteros	09/11/06
В	Longitudinal Externo longitudinal OD	1,00	5	±15	0,371	0,274	0,323	38,10	37,00	0,343	0,346	0,85	Sebastian Monteros	09/11/06
С	Transversal Externo Transverse OD	1,00	5	±15	0,371	0,274	0,323	38,10	36,00	0,347	0,335	0,85	Sebastian Monteros	09/11/06
D	Transversal Interno Transverse ID	1,00	5	±15	0,371	0,274	0,323	38,10	35,00	0,331	0,332	0,85	Sebastian Monteros	09/11/06

## Instrumentos de Medicion Utilizados:

## Notas:

1.-Todas las dimensiones son en milimetros excepto que se indique lo contrario.

2.-Minima Profundidad Nominal de las ranuras 0.3 mm.

CERTIFICADO CON REPLICA SI

## Notes:

- 1.-All dimensions in milimeters unless stated.
- 2.-Minimum notch nominal depth 0.3 mm.

CERTIFIED WITH PLASTIC REPLICA YES

1/2