

PARAMETROS ELECTRICOS

Sección mm ²	Resistencia eléctrica (Ohm/Km)				Reactancia inductiva a 50 Hz (Ohm/Km)						
	Cobre		Aluminio		1 x			2x	3x	3/N	4x
	a 20 °C en cc	a 90°C a 50 Hz	a 20°C en cc	a 90°C a 50 Hz							
1,5	12,100	15,429			0,143	0,201	0,320	0,143	0,143		0,112
2,5	7,410	9,448			0,130	0,188	0,302	0,130	0,130		0,106
4	4,610	5,878			0,120	0,178	0,288	0,120	0,120		0,101
6	3,080	3,927			0,114	0,172	0,278	0,114	0,114		0,099
10	1,830	2,333			0,106	0,164	0,264	0,106	0,106		0,095
16	1,150	1,466	1,910	2,449	0,100	0,158	0,251	0,100	0,100		0,090
25	0,727	0,927	1,200	1,539	0,096	0,154	0,238	0,096	0,096	0,096	
35	0,524	0,668	0,868	1,113	0,091	0,149	0,228	0,091	0,091	0,091	
50	0,387	0,494	0,641	0,822	0,089	0,147	0,219	0,089	0,089	0,080	
70	0,268	0,342	0,443	0,568	0,085	0,143	0,209	0,085	0,085	0,077	
95	0,193	0,246	0,320	0,410	0,083	0,141	0,201		0,083	0,076	
120	0,153	0,196	0,253	0,325	0,081	0,139	0,194		0,081	0,074	
150	0,124	0,159	0,206	0,264	0,081	0,139	0,189		0,081	0,075	
185	0,099	0,127	0,164	0,211	0,080	0,138	0,184		0,080	0,075	
240	0,075	0,097	0,125	0,161	0,079	0,137	0,176		0,079	0,074	
300	0,060	0,078	0,100	0,129	0,078	0,136	0,172		0,078	0,074	
400	0,047	0,061	0,078	0,101	0,077	0,135	0,165				
500	0,037	0,048	0,061	0,079	0,076	0,135	0,160				
630	0,023	0,038	0,047	0,061	0,075	0,133	0,151				