



中南大學

CENTRAL SOUTH UNIVERSITY

密码学与应用

实验报告(古典密码部分)

学生姓名	杨凯楠
学 号	8208201004
专业班级	信息安全 2002 班
指导教师	段桂华
学 院	计算机学院
完成时间	2021 年 12 月 1 日

一、凯撒密码

攻击方式：本试验较为简单，只需要对密码进行移位就可，因为比较简单所以我设置为了移位长度从零开始移位，肉眼识别是否成功的方法，成功就结束，不成功移位长度加一。语言采用 C++。

```
D:\杨凯\ykn\C++\cryptotma\x64\Debug\cryptotma.exe
W lmkieoa kb oaynayu swo kb ykqnoa ranu zqpebqhhu ceraj, xqp ep ykqhz jkp xa galp sepdqkp zebbeyqhpu; bkn pda yqnekoepu
atypapaz xu deo hkjc wxoajya xqnop bknpd ej oqyd ranu zenayp mqaopekjo kj deo napqnj wo namgenaz okia ejcajgepu pk arwza,
wjz da swo wp pda owia peia atanyeoecj cnawp oahb-zajewh, bkn da swo hkjcejc pk lqxheod deo lmkolankqo hkra. Wo da swo
pk xacej deo fknjau pkk awnhu kj pda iknks pk oaa wju kb pda bwiehu, pda yanaikju kb hawra-pwgejc swo lanbkniat sdaj
pda hwzeao ikraz bkn pda jecdp;
1
X moljfpb lc pbzobzv txp lc zlopb sbow arqcriiv dfsbk, yrq fq zlrta klq yb hbmq tfqelrq afccfzriqv; clo qeb zroflpfqv
buzfqba yv efp ilkd xypbkzb yropq cloqe fk prze sbow afobzq nrbpqflkp lk efp obqrok xp obnrfoa pljb fkdbrfqv ql bsxab,
xka eb txp xq qeb pxjb qfjb bubozfpfk dobzq pbic-abkfxi, clo eb txp ilkd fkd ql mryifpe efp molpmbolrp ilsb. Xp eb txp
ql ybdfk efp glrokbv qll bxoiv lk qeb jlloot ql pbb xkv lc qeb cxjfv, qeb zbobjlkv lc ibxsb-qxhfk txp mboclojba tebk
qeb ixafbp jlsba clo qeb kfdeg;
1
Y npmkgqc md qcpcaw uyq md amsqac tcpw bsrgdsjjw egtcl, zsr gr amsjb lmr ze icnr ugrfmsr bgddgasjrw; dmp rfc aspgmqgrw
evagreb zw fgq jmlc yzqclac zspqr dmp rf gl qsaf tcpw bgpcar oscqrgmlq ml fgq pcsppl yq pcospceb qmck glaelsgwr rm ctyeb,
ylb fc uyq yr rfc qykc rgke cvcpaggle epcyr qcjd-bclgyj, dmp fc uyq jmlgie rm nszjgqf fgq npmqncpsmq jmtc. Yq fc uyq
rm zcegl fgq hmsplcw rmm cypjw ml rfc kmppmu rm qcc ylw md rfc dykgjw, rfc acpckmlw md jeytc-ryigle uyq ncpdmpkeb ufcl
rfc jybqcq kmteb dmp rfc lgefr;
1
Z oqnlhrd ne rdbqdbx vzr ne bntqrd udqx ctshetkxx fhudm, ats hs bntkc mns ad jdos vhsngts cheehbtksx; enq sgd btqhrhsx
dwbhsdc ax ghr knmf zardmbd atqrs enqsg hm rtbg udqx chqdbz ptdrshnmr nm ghr qdstqm zr qdpthqdc rnld hmfmdthsx sn duzcd,
zmc gd vzr zs sgd rzld shld dwdqbhrhmf fdqzs rdke-cdmhbk, enq gd vzr knmfhmf sn otakhrq ghr oqnrqdqntz knud. Zr gd vzr
sn adfihm ghr intqmdx snn dzqkx nm sgd lqnnqv sn rdd zmx ne sgd ezhkx, sgd bdqdlmxx ne kdzud-szjhmf vzr odqenqldc vgdmd
sgd kzchdr lnuce enq sgd mhfgs;
1
A promise of secrecy was of course very dutifully given, but it could not be kept without difficulty; for the curiosity
excited by his long absence burst forth in such very direct questions on his return as required some ingenuity to evade,
and he was at the same time exercising great self-denial, for he was longing to publish his prosperous love. As he was
to begin his journey too early on the morrow to see any of the family, the ceremony of leave-taking was performed when
the ladies moved for the night;
```

```
Cipher below is encrypted with caesar cipher,
input plaintext to solve this challenge!
-----
V kmjhdnz ja nxxmzxt rvn ja xjpmnz qzmt ypodapggg bdqzi, wpo do xjpgy ijo wz fzko rdocijpo ydaadxpogot;
ajm ocz xpmjdndot zsxdozy wt cdn gjib vwnzixz wpmo ajmoc di npxc qzmt ydmzxo lpznodjin ji cdn mzoipm
i vn mzlpmzmy njhz dibzipdot oj zqvyyz, viy cz rvn vo ocz nvhz odhz zszmxndndib bmzvo nzga-yzidvg, ajm
cz rvn gjibdib oj kpwgdnc cdn kmjnkzmjpn gjqz. Vn cz rvn oj wzbdi cdn ejpmizt ojj zvmgt ji ocz hjmmj
r oj nzz vit ja ocz avhdgt, ocz xzmzhjit ja gzvqz-ovfdib rvn kzmajmhyz rczi ocz gvydzn hjqzy ajm ocz
idbco;
-----
What's the plaintext?
A promise of secrecy was of course very dutifully given, but it could not be kept without difficulty;
for the curiosity excited by his long absence burst forth in such very direct questions on his return
as required some ingenuity to evade, and he was at the same time exercising great self-denial, for
he was longing to publish his prosperous love. As he was to begin his journey too early on the morrow
to see any of the family, the ceremony of leave-taking was performed when the ladies moved for the
night;

Congratulation!
Please input your student id: 8208201004

Your student id(should be 10 digits) is: 8208201004 ? [Y/n]
y
```

1. 代码: #include<iostream>
2. #include<string>
3. using namespace std;
4. int main(void) {
5. string str = " ";
6. int i = 0, j = 1, key;
7. cin >> key;
8. while (key == 1 && j < 26) {
9. while (str[i] != '\\0') {
10. if (str[i] >= 'a' && str[i] <= 'z')

```

11.         cout << char((str[i] - 'a' + j) % 26 + 'a');
12.         else if ((str[i] >= 'A' && str[i] <= 'Z'))
13.             cout << char((str[i] - 'A' + j) % 26 + 'A');
14.         else
15.             cout << str[i];
16.         i++;
17.     }
18.     j++;
19.     i = 0;
20.     cout << endl;
21.     cin >> key;
22. }
23. return 0;
24. }

```

二、仿射密码

仿射密码也是一类经典的古典密码，通常加密方式为将字符映射到数字后计算

$$c = m * a + b \bmod n \quad c = m * a + b \bmod n,$$

再对应回字母表表示密文，解密则使用


$$m = (c - b) * a^{-1} \bmod n \quad m = (c - b) * a^{-1} \bmod n$$

移位密码可以看做 $a=1, b=1$ 的仿射密码。

现已知字母表为"abcdefghijklmnopqrstuvwxyz ., "，分别对应 0~28，连接服务器，获得密文后向服务器输入对应的明文（空格也要附上）。

分析：从本题以后的题我都是用 python 写的，本道题中，首先进行字母数字转换，将字母标点对应成相应的数字，然后对其所有 311 个密钥空间进行爆破攻击，在判断是否攻击成功时，我采用了“e”字母频率初步判断外加关键字匹配方式辅助的方法。取得了不错的攻击效果。在求逆元的时候使用了 gmpy2 库，初步认识到了这一库的强大之处。

结果：



```

Cipher below is encrypted with affine cipher,
input plaintext to solve this challenge!
-----
yemcbumeyv fvmqjomyem.befmzytcbzdmcjgmiffzm,zyqzmbzmcfvteyvgucbvfmistmqcjtmcfmtymcgmcb uf.elmjumtymcbu
mvfj.mhcejvjhtfvkmcjgmbzeyv jtbzymiffzmbzmcfvmyqfvkmucfmcjgmzfrfvmeft.tmjmqbucmyembzwsbvbdlmcbumhyszt
fzjzhfkmyrbhfkjzgm jzzfvmcjgmfutji.bucfgmcb mjtmyzhfmbzmtcfmxyuufuubyzmyemfrfvomrbvtsflmucfmtvbfgmtym
mvfhy..fhtmy fmbzutjzhfmyemdyggyzfuukmuy fmgbutbzdsbucfgmtvjbtmyembztdvbtomyvmifzfry.fzhfkmtcjtmbdc
tmvfuhsfmcb mevy mtcfmjttjh,umyem vlmqjvho;myvmjtm.fjutkmiomtcfmxfgy bzjzhfmyemrbvtsfkmjtyzfmeyvmtcy
ufmhju
-----
What's the plaintext?
of his former way of life nothing had been known in hertfordshire but what he told himself. as to his
real character, had information been in her power, she had never felt a wish of inquiring. his count
enance, voice, and manner had established him at once in the possession of every virtue. she tried to
recollect some instance of goodness, some distinguished trait of integrity or benevolence, that migh
t rescue him from the attacks of mr. darcy or at least, by the predominance of virtue, atone for tho
se cas

Congratulation!
Please input your student id: 8208201004

```

关键代码:

攻击:

```

1. count=0
2. for b in range(0,29):
3.     for a in range(2,29):
4.         count=0
5.         nia=gmpy2.invert(a,29)
6.         for c in C:
7.             P.append(((c-b)*nia)%29)
8.         for c in P:
9.             if c==(ord('e')-97):
10.                 count+=1
11.         if count/lenstr>0.08:
12.             printff()
13.         P.clear()

```

三、列移位攻击

分析：在列移位密码中，首先将明文写入给定尺寸的网格中，然后以密钥中给定的模式读出。

如有明文 WEAREDISCOVEREDFLEEATONCE，并用密钥 3 进行加密，则首先将信息写为（竖着写）

```

W R I O R F E O E
E E S V E L A N J
A D C E D E T C X

```

然后将信息横着读出，得到 WRIORFEOEEESVELANJADCEDETCX，即是最后的密文。（字符不足时会补空格）

本道题由于网页所给形式的问题，我并不知道在密文最后一个字母后面是否还跟随有空格，所以我查看了源码，才发现，源码中根本没有考虑空格的形式，而是直接将情况达到了完美状态：都是标准的矩形，没有空缺。这也是我给学长提的意见之一。针对这种方式我设计了

简便的攻击方式，那便是计算密文长度，然后根据密文长度的因子进行攻击，简便快捷。

```
Cipher below is encrypted with columnar transposition cipher,
input plaintext to solve this challenge!

-----
r bmyey taumgoo sse ge d e sd. ni enhcrs .ceeo .hop ew ru b i metfa s fgeIa dyc t" rt ue a piom
eectye"vtyahudm Mo ftpt etaRCihw xIvsenfenxfhooiYeosrasdeoyril phiophbeoe apcfeaa nopus uno e tarr
f tydeasftalaldwrue irtettrsac gumflc lee rb oat atill imzewhd hn, ea oo elfoy slceater uyn sli
Ettzdhi tec hslwnfom a,uosyoalrhs mmocthylnlhliatco oIos av nult sufe usiee tywuehm,si ,entha fu w i
yiiesetmir swroe sno or,ee ,zs g enyork mn nt.taeyn m osnvbeo hr nM"ao"mlIr oranty acs" vr ,ryires
ir:tmataoet
-----


What's the plaintext?

"Really, Mr. Collins," cried Elizabeth with some warmth, "you puzzle me exceedingly. If what I have
hitherto said can appear to you in the form of encouragement, I know not how to express my refusal i
n such a way as to convince you of its being one." "You must give me leave to flatter myself, my dea
r cousin, that your refusal of my addresses is merely words of course. My reasons for believing it ar
e briefly these: It does not appear to me that my hand is unworthy of your acceptance, or that the es
tablishment

Congratulation!
Please input your student id: 8208201004

Your student id(should be 10 digits) is: 8208201004 ? [Y/n]

```



```
C:\Users\笑露如花\AppData\Local\Programs\Python\Python39\python.exe
eyron elb hmahypleciyfa ettacaou m ognloooops u s as veu nn oug le t e d s tueaf resr dfu. s inteie d eteaynshwfu
cterahslm a..lscdiw er,oue en. th hoiapr tf euet wtw r rsiuay ci ibge usime ftlmecit rfl aes ews r rofbeg e slonaao
t d oy rca, tetie'l l,r ztis m uz eeg w ahe dnp yihoonrm,k eemeanc tonyote." tveatleyfyaonhy u mds mlo csMenoev ab
fteteopr t h ur y en t asnRLMCi"iEahtowt" zmxdlIhIvirs etonerfae nnhtxsyfl hwaoncofsioYm e voars, ru,aorsoydsieyrooe
yasrliirrlh: stp mhmaintooapcohtebht#end

RLrClS i ibhi mwm,y zeexenyIwt vhhtsdae unhfmfuge, on woxe faish ysooieooi i e Y sgeeeolt sfmdroi ayres dssselw
docr.yeo reenia ilts en proeh niuohoyrcpn,rh esbse el .oi,ceEze tseat opz cdg.fh heieoa npaty eo cren kwoh psmruln
u w nn uftbno. omti a aeme,ye unto faomars ryosfos anf lvgtrbeyheldsoae amhdsnryfo ctc at tlhn"ayM ln"rdlatwho
rh"uulmeeil aIa tr ic prooit roeoamtIn totersyes caaatvcy segn"uu vmlvtftryl acs,h urulfydeeime r ueMrssobii er
f e:to tpatmttya wt uaeaeottheaint#end

"ely r oln, re lzbt ihsam amh yupzl eeceigy fwa aethtet adcnapa oyui h omo norgmn,Iko o o oepesm eua nsc a st ovnyuo t
en n. "o utgv elae lte yef yda osn htyu eua fm drse smrl od fcus.M esn o eivn taebifytee tde o pert eta yhn suwrh fyu
eetne rta h salsmn Ral,M.Clis"cidEiaehwt oewrt,"o uzem xednl.I htIhvy ihrosi a pert o ntefr fecuaet nwnthwt xrs yrfsli
uhawya onic o fisbigoe Yums iem ev ofatrmsl,m ercui,ta orrfslo yadessi eeywrso ore yraosfrbleigi r rel hs:I osntapa om
htm adi notyo oracpac,o htteetbihet#end

"Really, Mr. Collins," cried Elizabeth with some warmth, "you puzzle me exceedingly. If what I have hitherto said can
appear to you in the form of encouragement, I know not how to express my refusal in such a way as to convince you of its
being one." "You must give me leave to flatter myself, my dear cousin, that your refusal of my addresses is merely wor
ds of course. My reasons for believing it are briefly these: It does not appear to me that my hand is unworthy of your a
cceptance, or that the establishment#end

Press any key to continue . . .

```

代码：

```
1. str=' '
2. lenstr=len(str)
3. for a in range(3,13):
4.     if lenstr%a==0:
5.         for j in range(0,len(str)//a):
6.             for i in range(0,a):
7.                 print(str[j+lenstr//a*i],end="")
8.             print('#end\n')
```

四、维吉尼亚密码

例如，假设明文为：

ATTACKATDAWN

选择某一关键词并重复而得到密钥，如关键词为 LEMON 时，密钥为：

LEMONLEMONLE

对于明文的第一个字母 A，对应密钥的第一个字母 L，于是使用表格中 L 行字母表进行加密，得到密文第一个字母 L。类似地，明文第二个字母为 T，在表格中使用对应的 E 行进行加密，得到密文第二个字母 X。以此类推，可以得到：

明文：ATTACKATDAWN

密钥：LEMONLEMONLE


密文：LXFOPVEFRNHR

分析：本实验比较难，难点在于寻找密钥的长度、确定密钥长度后重合指数攻击，参数的选择也是尤为重要的。寻找密钥长度时，我遍历了密文，将所有重复出现的密文片段间的长度计算出其公因子，这就是密钥长度，公因子计算中，采用从头到尾 gcd 函数遍历法求得。求得密钥长度后，再将密文分片，分成密钥长度的片，在维吉尼亚密码中，由于较难使用关键字匹配，所以应用重合指数攻击，重合指数攻击中对 IC 范围极其敏感，稍有偏差便不能破解密文（也可能是我算法问题很多，水平比较低）。重合指数的计算方法：

$$IC = (\text{CountLetter}[i] - 1) * \text{CountLetter}[i] / (\text{countlen} * (\text{countlen} - 1))$$

代码：[click here](#)（由于是初学 python 写的代码，并且是零碎时间写的，代码可读性不好）

实现：



```
C:\Users\笑塵如花\AppData\Local\Programs\Python\Python39\python.exe
4
A 4
IC 0.0637543630017452
4
IC 0.06762964717025811
4
IC 0.06663768745924797
4
A 2
[1, 8, 7, 2]
softened tone she declared herself not at all offended; but he continued to apologise for about a quarter of an hour.
Chapter 14 During dinner, Mr. Bennet scarcely spoke at all; but when the servants were withdrawn, he thought it time
to have some conversation with his guest, and therefore started a subject in which he expected him to shine, by observi
ng that he seemed very fortunate in his patroness. Lady Catherine de Bourgh's attention to his wishes, and consideration
for his comfort, appeared very remarkable. Mr. Bennet could not have chosen better. Mr. Collins was eloquent in her pra
ise. The subject elevated him to more than usual solemnity of manner, and with a most important aspect he protested that
he had never in his life witnessed such behaviour in a person of rank—such affability and condescension, as he had hi
mself experienced from Lady Catherine. She had been graciously pleased to approve of both of the discourses which he had
already had the honour of preaching before her. She had also as
zsty
Press any key to continue . . .
```

五、多次一次一密

一次一密是不可攻破的，但是协商、传输密钥却是非常头疼的事情，于是就有人考虑多次使用密钥，但是这样是非常危险的！

已知密钥为 50 个字节，明文为英文句子，加密使用的方式是异或，连接服务器，输入学号，并输入根据获取的密文组解密出密钥，并发到服务器。

注意，应当发送密钥对应的十六进制编码，如密钥是"31"，则应当发送 3331（3 和 1 的 `ascii` 码）。

本道题我认为是最难的一道题，甚至难度直接比肩协议题，耗费了大量时间写代码，并且调试良久也没有将参数改合适，只能获得残破的明文，然后对熟悉的单词进行补全，再从老师法的明文来源里找到原文才能 **congratulation**，可能是我技术太差了吧，还需要不断学习。

程序首先进行双重循环来寻找空字符，每一条密文均与其他密文异或，保存可能的空格符对应的位置，然后还需要进一步判断已记录的位置是否是空字符。

解出“残破的”密钥后，用其对所有密文解密，然后猜测出一组明文，再得出正确的密钥。

实现:

[illegible]

```
#没办法的办法了_法解秘钥
import libnum
m="v0ry rapid i jumps frEm ldY0rasio` tm lov1, from"
m="very rapid i jumps from ldY0rasio` to love, from"
m="very rapid; it jumps from admiration to love, from"
c=0x0f0c22084218585610307176482d772a4043593f7c421845151d200859093d0b29424c534b5f31033f245231477512592927
cipher=hex(c^libnum.s2n(m))
print(cipher)
0x79695071626a392679544a5621595740352e294c5c246a2a783d416c34604f6a5d2b233d6b2b5e23534b24546b55742b464a
```

代码: [click here](#)