



Exceptions & Files

Exceptions

You have already seen **exceptions** in previous code. They occur when something goes wrong, due to incorrect code or input. When an **exception** occurs, the program immediately stops. The following code produces the `ZeroDivisionError` **exception** by trying to divide 7 by 0.

```
num1 = 7
num2 = 0
print(num1/num2)
```

Try It Yourself

Result:

```
>>>
ZeroDivisionError: division by zero
>>>
```

Tap **Try It Yourself** to play around with the code!

Exceptions

Different exceptions are raised for different reasons.

Common exceptions:

ImportError: an import fails;

IndexError: a list is indexed with an out-of-range number;

NameError: an unknown **variable** is used;

SyntaxError: the code can't be parsed properly;

TypeError: a **function** is called on a value of an inappropriate type;

ValueError: a **function** is called on a value of the correct type, but with an inappropriate value.

Python has several other built-in exceptions, such as `ZeroDivisionError` and `OSError`. Third-party libraries also often define their own exceptions.

Exception Handling

To handle exceptions, and to call code when an **exception** occurs, you can use a **try/except** statement.

The **try** block contains code that might throw an **exception**. If that **exception** occurs, the code in the **try** block stops being executed, and the code in the **except** block is run. If no error occurs, the code in the **except** block doesn't run.

For example:

```
try:
    num1 = 7
    num2 = 0
    print(num1 / num2)
    print("Done calculation")
```

```
except ZeroDivisionError:
    print("An error occurred")
    print("due to zero division")
```

Try It Yourself

Result:

```
>>>
An error occurred
due to zero division
>>>
```

In the code above, the `except` statement defines the type of exception to handle (in our case, the `ZeroDivisionError`).

Exception Handling

A `try` statement can have multiple different `except` blocks to handle different exceptions. Multiple exceptions can also be put into a single `except` block using parentheses, to have the `except` block handle all of them.

```
try:
    variable = 10
    print(variable + "hello")
    print(variable / 2)
except ZeroDivisionError:
    print("Divided by zero")
except (ValueError, TypeError):
    print("Error occurred")
```

Try It Yourself

Result:

```
>>>
Error occurred
>>>
```

Tap **Try It Yourself** to play around with the code!

Exception Handling

An `except` statement without any exception specified will catch all errors. These should be used sparingly, as they can catch unexpected errors and hide programming mistakes.
For example:

```
try:
    word = "spam"
    print(word / 0)
except:
    print("An error occurred")
```

Result:

```
>>>
An error occurred
>>>
```

Exception handling is particularly useful when dealing with user input.

finally

To ensure some code runs no matter what errors occur, you can use a **finally** statement. The **finally** statement is placed at the bottom of a **try/except** statement. Code within a **finally** statement always runs after execution of the code in the **try**, and possibly in the **except**, blocks.

```
try:
    print("Hello")
    print(1 / 0)
except ZeroDivisionError:
    print("Divided by zero")
finally:
    print("This code will run no matter what")
```

Try It Yourself

Result:

```
>>>
Hello
Divided by zero
This code will run no matter what
>>>
```

Tap **Try It Yourself** to play around with the code!

finally

Code in a **finally** statement even runs if an uncaught **exception** occurs in one of the preceding blocks.

```
try:
    print(1)
    print(10 / 0)
except ZeroDivisionError:
    print(unknown_var)
finally:
    print("This is executed last")
```

Try It Yourself

Result:

```
>>>
1
This is executed last

ZeroDivisionError: division by zero
During handling of the above exception, another exception occurred:
NameError: name 'unknown_var' is not defined
>>>
```

Tap **Try It Yourself** to play around with the code!

Raising Exceptions

You can raise exceptions by using the **raise** statement.

```
print(1)
raise ValueError
print(2)
```

Try It Yourself

Result:

```
>>>
1
ValueError
>>>
```

You need to specify the **type** of the exception raised.

Raising Exceptions

Exceptions can be raised with arguments that give detail about them.

For example:

```
name = "123"
raise NameError("Invalid name!")
```

Try It Yourself

Result:

```
>>>
NameError: Invalid name!
>>>
```

Tap **Try It Yourself** to play around with the code!

Raising Exceptions

In **except** blocks, the **raise** statement can be used without arguments to re-raise whatever **exception** occurred.

For example:

```
try:
    num = 5 / 0
except:
    print("An error occurred")
    raise
```

Try It Yourself

Result:

```
>>>
An error occurred

ZeroDivisionError: division by zero
>>>
```

Tap **Try It Yourself** to play around with the code!

Assertions

An **assertion** is a sanity-check that you can turn on or turn off when you have finished testing the program.

An expression is tested, and if the result comes up false, an **exception** is raised.

Assertions are carried out through use of the **assert** statement.

```
print(1)
assert 2 + 2 == 4
print(2)
assert 1 + 1 == 3
print(3)
```

Try It Yourself

Result:

```
>>>
1
2
AssertionError
>>>
```

Programmers often place assertions at the start of a function to check for valid input, and after a function call to check for valid output.

Assertions

The **assert** can take a second [argument](#) that is passed to the `AssertionError` raised if the assertion fails.

```
temp = -10
assert (temp >= 0), "Colder than absolute zero!"
```

Try It Yourself

Result:

```
>>>
AssertionError: Colder than absolute zero!
>>>
```

`AssertionError` exceptions can be caught and handled like any other [exception](#) using the **try-except** statement, but if not handled, this type of [exception](#) will terminate the program.

Opening Files

You can use Python to read and write the contents of **files**. Text files are the easiest to manipulate. Before a file can be edited, it must be opened, using the **open function**.

```
myfile = open("filename.txt")
```

The [argument](#) of the **open function** is the **path** to the file. If the file is in the current working directory of the program, you can specify only its name.

Opening Files

You can specify the **mode** used to open a file by applying a second [argument](#) to the **open function**.

Sending "r" means open in read mode, which is the default.

Sending "w" means write mode, for rewriting the contents of a file.

Sending "a" means append mode, for adding new content to the end of the file.

Adding "b" to a mode opens it in **binary** mode, which is used for non-text files (such as image and sound files).

For example:

```
# write mode
open("filename.txt", "w")

# read mode
open("filename.txt", "r")
open("filename.txt")

# binary write mode
open("filename.txt", "wb")
```

You can use the + sign with each of the modes above to give them extra access to files. For example, r+ opens the file for both reading and writing.

Opening Files

Once a file has been opened and used, you should close it. This is done with the **close** method of the file object.

```
file = open("filename.txt", "w")
# do stuff to the file
file.close()
```

We will read/write content to files in the upcoming lessons.

Reading Files

The contents of a file that has been opened in text mode can be read using the **read** method.

```
file = open("filename.txt", "r")
cont = file.read()
print(cont)
file.close()
```

This will print all of the contents of the file "filename.txt".

Reading Files

To read only a certain amount of a file, you can provide a number as an **argument** to the **read** function. This determines the number of **bytes** that should be read. You can make more calls to **read** on the same file object to read more of the file byte by byte. With no **argument**, **read** returns the rest of the file.

```
file = open("filename.txt", "r")
print(file.read(16))
print(file.read(4))
print(file.read(4))
print(file.read())
file.close()
```

Just like passing no arguments, negative values will return the entire contents.

Reading Files

After all contents in a file have been read, any attempts to read further from that file will return an empty **string**, because you are trying to read from the end of the file.

```
file = open("filename.txt", "r")
file.read()
```

```
print("Re-reading")
print(file.read())
print("Finished")
file.close()
```

Result:

```
>>>
Re-reading

Finished
>>>
```

Just like passing no arguments, negative values will return the entire contents.

Reading Files

To retrieve each line in a file, you can use the **readlines method** to return a list in which each element is a line in the file.

For example:

```
file = open("filename.txt", "r")
print(file.readlines())
file.close()
```

Result:

```
>>>
['Line 1 text \n', 'Line 2 text \n', 'Line 3 text']
>>>
```

You can also use a **for** loop to iterate through the lines in the file:

```
file = open("filename.txt", "r")

for line in file:
    print(line)

file.close()
```

Result:

```
>>>
Line 1 text

Line 2 text

Line 3 text
>>>
```

In the output, the lines are separated by blank lines, as the **print function** automatically adds a new line at the end of its output.

Writing Files

To write to files you use the **write method**, which writes a **string** to the file.

For example:


```
file = open("newfile.txt", "w")
file.write("This has been written to a file")
file.close()

file = open("newfile.txt", "r")
print(file.read())
file.close()
```

Try It Yourself

Result:

```
>>>
This has been written to a file
>>>
```

The "w" mode will create a file, if it does not already exist.

Writing Files

When a file is opened in write mode, the file's existing content is deleted.

```
file = open("newfile.txt", "r")
print("Reading initial contents")
print(file.read())
print("Finished")
file.close()

file = open("newfile.txt", "w")
file.write("Some new text")
file.close()

file = open("newfile.txt", "r")
print("Reading new contents")
print(file.read())
print("Finished")
file.close()
```

Try It Yourself

Result:

```
>>>
Reading initial contents
some initial text
Finished
Reading new contents
Some new text
Finished
>>>
```

As you can see, the content of the file has been overwritten.

Writing Files

The `write` method returns the number of **bytes** written to a file, if successful.

```
msg = "Hello world!"
file = open("newfile.txt", "w")
amount_written = file.write(msg)
print(amount_written)
file.close()
```

Try It Yourself

Result:

```
>>>
12
>>>
```

To write something other than a string, it needs to be converted to a string first.

Working with Files

It is good practice to avoid wasting resources by making sure that files are always closed after they have been used. One way of doing this is to use **try** and **finally**.

```
try:
    f = open("filename.txt")
    print(f.read())
finally:
    f.close()
```

This ensures that the file is always closed, even if an error occurs.

Working with Files

An alternative way of doing this is using **with** statements. This creates a temporary **variable** (often called **f**), which is only accessible in the indented block of the **with** statement.

```
with open("filename.txt") as f:
    print(f.read())
```

The file is automatically closed at the end of the **with** statement, even if exceptions occur within it.

End.