Treasure Hunt Game Notebook

Read and Review Your Starter Code

The first piece of code you'll need to write is code to allow users to run the treasure before the pirate does. While you will not be developing the entire game, you will write the sum of the game that represents the intelligent agent, which is a pirate in this case. The pirate will try to find the optimal path to the treasure using deep Q-learning.

Task Type: Edit the **`TreasureMaze.py`** and **`GameExperience.py`** files to complete your implementation.

You have been provided with two Python classes and this notebook to help you with this assignment. The first class, **`TreasureMaze.py`**, represents the environment, which includes a robot (pirate) defined as a method. The second class, **`GameExperience.py`**, stores the episodes—that is, all the states that exist in between the initial state and the terminal state. This is also where you'll create the deep Q-learning algorithm. Finally, this notebook shows how to play a game. Your task is to complete the deep Q-learning implementation in the **`pirate_learning`** method in the **`GameExperience.py`** file.

NOTE: The code block you will need to complete will have **`#TODO:`** as a header.
First, read and review the next few code cells and notebook sections to understand the code that you have been given.

Installation: The following command will install the Keras framework for Tensorflow. Prefix the command with an exclamation. If you use a `Terminal` to view release of pip is available (22.0.3 < 22.2)` at the prompt, remove the exclamation, and run the program from the terminal.

```
!pip install -r requirements.txt
```

```
Requirement already satisfied: numpy==1.26.4 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from -r requirements.txt (line 1)) (1.26.4)
Requirement already satisfied: matplotlib==3.8.4 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from -r requirements.txt (line 2)) (3.8.4)
Requirement already satisfied: scipy==1.13.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from -r requirements.txt (line 3)) (1.13.0)
Requirement already satisfied: tensorflow==2.16.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from -r requirements.txt (line 4)) (2.16.1)
Requirement already satisfied: keras==3.3.3 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from -r requirements.txt (line 5)) (3.3.3)
Requirement already satisfied: contourpy>=1.0.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (1.2.1)
Requirement already satisfied: cycler>=0.10 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (0.12.1)
Requirement already satisfied: fonttools>=4.22.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (4.51.0)
Requirement already satisfied: kiwisolver>=1.3.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (1.4.5)
Requirement already satisfied: packaging>=20.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (24.0)
Requirement already satisfied: pillow>=8 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (10.3.0)
Requirement already satisfied: pyparsing>=2.3.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (3.1.2)
Requirement already satisfied: python-dateutil>=2.7 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from matplotlib==3.8.4->-r requirements.txt (line 2)) (2.9.0.post0)
Requirement already satisfied: tensorflow-intel==2.16.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow==2.16.1->-r requirements.txt (line 4)) (2.16.1)
Requirement already satisfied: absl-py>=1.0.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2.1.0)
Requirement already satisfied: astunparse>=1.6.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (1.6.3)
Requirement already satisfied: flatbuffers>=23.5.26 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (24.3.25)
Requirement already satisfied: gast!=0.5.0,!=0.5.1,!=0.5.2,>=0.2.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (0.5.4)
Requirement already satisfied: google-pasta>=0.1.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (0.2.0)
Requirement already satisfied: h5py>=3.10.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (3.11.0)
Requirement already satisfied: libclang>=13.0.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (18.1.1)
Requirement already satisfied: ml-dtypes~=0.3.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (0.3.2)
Requirement already satisfied: opt-einsum>=2.3.2 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (3.3.0)
Requirement already satisfied: protobuf!=4.21.0,!=4.21.1,!=4.21.2,!=4.21.3,!=4.21.4,!=4.21.5,<5.0.0dev,>=3.20.3 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (4.25.3)
Requirement already satisfied: requests<3,>=2.21.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2.31.0)
Requirement already satisfied: setuptools in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (65.5.0)
Requirement already satisfied: six>=1.12.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (1.16.0)
Requirement already satisfied: termcolor>=1.1.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2.4.0)
Requirement already satisfied: typing-extensions>=3.6.6 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (4.11.0)
Requirement already satisfied: wrapt>=1.11.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (1.16.0)
Requirement already satisfied: grpcio<2.0,>=1.24.3 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (1.62.2)
Requirement already satisfied: tensorboard<2.17,>=2.16 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2.16.2)
Requirement already satisfied: tensorflow-io-gcs-filesystem>=0.23.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (0.37.0)
Requirement already satisfied: rich in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from keras==3.3.3->-r requirements.txt (line 5)) (13.7.1)
Requirement already satisfied: namex in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from keras==3.3.3->-r requirements.txt (line 5)) (0.0.8)
Requirement already satisfied: optree in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from keras==3.3.3->-r requirements.txt (line 5)) (0.11.0)
Requirement already satisfied: wheel<1.0,>=0.23.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from astunparse>=1.6.0->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (0.43.0)
Requirement already satisfied: charset-normalizer<4,>=2 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from requests<3,>=2.21.0->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (3.3.2)
Requirement already satisfied: idna<4,>=2.5 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from requests<3,>=2.21.0->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (3.7)
Requirement already satisfied: urllib3<3,>=1.21.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from requests<3,>=2.21.0->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2.2.1)
Requirement already satisfied: certifi>=2017.4.17 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from requests<3,>=2.21.0->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2024.2.2)
Requirement already satisfied: markdown>=2.6.8 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorboard<2.17,>=2.16->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (3.6)
Requirement already satisfied: tensorboard-data-server<0.8.0,>=0.7.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorboard<2.17,>=2.16->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (0.7.2)
Requirement already satisfied: werkzeug>=1.0.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from tensorboard<2.17,>=2.16->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (3.0.2)
Requirement already satisfied: MarkupSafe>=2.1.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from werkzeug>=1.0.1->tensorboard<2.17,>=2.16->tensorflow-intel==2.16.1->tensorflow==2.16.1->-r requirements.txt (line 4)) (2.1.5)
Requirement already satisfied: markdown-it-py>=2.2.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from rich->keras==3.3.3->-r requirements.txt (line 5)) (3.0.0)
Requirement already satisfied: pygments<3.0.0,>=2.13.0 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from rich->keras==3.3.3->-r requirements.txt (line 5)) (2.17.2)
Requirement already satisfied: mdurl~=0.1 in /home/codio/.pyenv/versions/3.11.9/lib/python3.11/site-packages (from markdown-it-py>=2.2.0->rich->keras==3.3.3->-r requirements.txt (line 5)) (0.1.2)
```

Maze Object Generation

NOTE: The following code block contains six 8x8 mazes that will be used as a maze object:

```
qmaze = np.array([
        [ 0.,  1.,  2.,  3.,  4.,  5.,  6.,  7.],
        [ 8.,  9., 10., 11., 12., 13., 14., 15.],
        [16., 17., 18., 19., 20., 21., 22., 23.],
        [24., 25., 26., 27., 28., 29., 30., 31.],
        [32., 33., 34., 35., 36., 37., 38., 39.],
        [40., 41., 42., 43., 44., 45., 46., 47.],
        [48., 49., 50., 51., 52., 53., 54., 55.],
        [56., 57., 58., 59., 60., 61., 62., 63.]])
```

Helper Functions and Global Variables

The **`show()`** helper function shows a visual representation of the maze object.

```
def show(qmaze):
    plt.grid('on')
    nrows, ncols = qmaze.maze.shape
    ax = plt.gca()
    ax.set_xticks(np.arange(0.5, nrows, 1))
    ax.set_yticks(np.arange(0.5, ncols, 1))
    ax.set_xticklabels([])
    ax.set_yticklabels([])
    canvas = np.copy(qmaze.maze)
    for row,col in qmaze.visited:
        canvas[row,col] = 0.6
    pirate_row, pirate_col = qmaze.state
    canvas[pirate_row, pirate_col] = 0.3   # pirate cell
    canvas[nrows-1, ncols-1] = 0.9 # treasure cell
    img = plt.imshow(canvas, interpolation='none', cmap='gray')
    return img
```

The **`play_game`** can move in four directions: left, right, up, and down.

Note: When the agent moves, its experience is stored in **`GameExperience`**, where the agent can choose to replay the environment in the previously experienced state. This is called experience replay. Experience replay is a technique that stores the agent's experiences at each time step in a dataset pooled over many episodes. The agent can then train over mini-batches sampled from the replay memory. The agent can store the last **`mem_size`** number of moves. You can experiment with this number, but the default value is set to 1000.

```
LEFT = 0
UP = 1
RIGHT = 2
DOWN = 3

# Exploration factor
epsilon = 0.1

# Actions dictionary
actions_dict = {
    LEFT: 'left',
    UP: 'up',
    RIGHT: 'right',
    DOWN: 'down',
}

num_actions = len(actions_dict)
```

The example code block and output below shows creating a maze object and performing one action (`LEFT`), which returns the reward. The resulting updated environment is visualized.

```
# Create a maze object
qmaze = TreasureMaze(maze)
# Show the maze
show(qmaze)
```

```
# Update the maze by moving the agent in the direction of LEFT
# Return the reward
reward = qmaze.act(LEFT)
print("reward=", reward)
```

```
reward= -0.04
```

NOTE: The **`play_game`** function simulates a full game based on the provided trained model. The other parameters include the TreasureMaze object, the starting position of the pirate and the amount of time to make sure the model can win. The model should win in a max.

```
def play_game(model, qmaze, pirate_cell):
    qmaze.reset(pirate_cell)
    envstate = qmaze.observe()
    while True:
        prev_envstate = envstate
        # get next action
        q = model.predict(prev_envstate)
        action = np.argmax(q[0])

        # apply action, get rewards and new state
        envstate, reward, game_status = qmaze.act(action)
        if game_status == 'win':
            return True
        elif game_status == 'lose':
            return False
```

Note: The **`completion_check`** function helps you to determine whether the pirate can win any game at all. If your maze is not well-designed, the pirate may not win any game at all. In this case, the model may continue training and never win. The `completion_check` function is a debugging function that helps to notify you in case you run into this sentiment. It runs:

```
def completion_check(model, qmaze, pirate_cell,time_limit):
    for cell in qmaze.free_cells:
        if not qmaze.valid_actions(cell):
            continue
        if not play_game(model, qmaze, cell,time_limit):
            return False
    return True
```

Note: The **`experience_replay`** function is the block below will build the neural network model. Review the code and note the number of layers, as well as the activation, optimizer, and loss functions that are used to train the model.

```
def build_model(maze):
    model = Sequential()
    model.add(Dense(maze.size, input_shape=(maze.size,)))
    model.add(PReLU())
    model.add(Dense(maze.size))
    model.add(PReLU())
    model.add(Dense(num_actions))
    model.compile(optimizer='adam', loss='mse')
    return model
```

Note: The **`train_time`** parameter in the block below is used to help predict in cases a public version in the current models can fail—good each action a in given state and time to the model is followed by maximizing the game environment. Values of 1 and above should have been achieved.

If you're interested in reading up on the difficulties, check out a discussion for TensorFlow to run this code now in TensorFlow computation graph, please refer to the link: https://stackoverflow.com/questions/tens...to-a-panic.

Tensorflow GPU Warning

You can run **`nvidia-smi`** in the terminal to see if you have a GPU and if it is available/recommended. If it is running CUDA Version, GPU will not be used. Then it is simply running from CPU and not GPU.

```
!nvidia-smi
```

```
Sun Jul 21 20:08:04 2024
+---------------------------------------------------------------------------------------+
| NVIDIA-SMI 535.54.03              Driver Version: 535.54.03    CUDA Version: 12.2     |
|-----------------------------------------+----------------------+----------------------+
| GPU  Name                 Persistence-M | Bus-Id        Disp.A | Volatile Uncorr. ECC |
| Fan  Temp   Perf          Pwr:Usage/Cap |         Memory-Usage | GPU-Util  Compute M. |
|                                         |                      |               MIG M. |
|=========================================+======================+======================|
|   0  Tesla T4                       Off | 00000000:00:1E.0 Off |                    0 |
| N/A   34C    P8               9W /  70W |      2MiB / 15360MiB |      0%      Default |
|                                         |                      |                  N/A |
+-----------------------------------------+----------------------+----------------------+

+---------------------------------------------------------------------------------------+
| Processes:                                                                            |
|  GPU   GI   CI        PID   Type   Process name                            GPU Memory |
|        ID   ID                                                             Usage      |
|=======================================================================================|
|  No running processes found                                                           |
+---------------------------------------------------------------------------------------+
```

#TODO: Complete the Q-Training Algorithm Code Block

This is your deep Q-learning implementation. The part of your deep Q-learning implementation is to find the best possible navigation sequence that results in reaching the treasure cell while maximizing the reward. A Q-value is calculated for each action taken. Eventually, the agent should learn the optimal number of steps to achieve a 100% win rate.

Pseudocode:
For each epoch, Reset the environment at a random starting cell (agent_cell = random) state to that cell
Note: Number of epochs is set to 8 times the number of cells in the maze.

```
    For each epoch:
        Set initial state = agent_cell
        Set initial reward = 0.0
        While game_status is not game_over:
            previous_envstate = current state
            If exploring, take a random valid exploration action and
            Else, take the action from the highest Q-value
            Apply the action to the environment to get the updated state and reward for an action variable
            Update the reward = reward + the reward from the game
        Store episode (experience) in episode memory
        If training:
            Train the model and update Q-value table
            Update the model with the episode memory, inputs, and targets
```

Note: Update the model with the episode memory, inputs, and targets.

Finally, if the win rate is above the threshold and your model passes the completion check, that would be your epoch.

Note: A 50% win rate (**`SUCCESS_THRESHOLD = 0.5`**) would have achieved the maze if many minutes had passed during the last evaluation, the pirate happened to get to the treasure. Be sure to review the **`completion_check`** function to see how it works.

You will need to complete the section starting with #TODO: ADD. Please see the pseudocode above as guidance.

```
# Define exploration factor
epsilon = 0.1  # Exploration factor

# Actions dictionary
actions_dict = {
    LEFT: 'left',
    UP: 'up',
    RIGHT: 'right',
    DOWN: 'down',
}

num_actions = len(actions_dict)

# Exploration factor
epsilon = 0.1

# Actions dictionary
actions_dict = {
    LEFT: 'left',
    UP: 'up',
    RIGHT: 'right',
    DOWN: 'down',
}

num_actions = len(actions_dict)

# Maze object
qmaze = TreasureMaze(maze)

# Initialize experience replay object
experience = GameExperience(model, max_memory=max_memory)

# Initialize variables
n_epoch = 15000
max_memory = 1000
data_size = 32
weights_file = "weights_file.h5"
name = "data_structure"

# Iterate over the epochs
for epoch in range(n_epoch):
    loss = 0.0
    rat_cell = random.choice(qmaze.free_cells)
    qmaze.reset(rat_cell)
    game_over = False

    # Get initial envstate (1d flattened canvas)
    envstate = qmaze.observe()

    n_episodes = 0
    while not game_over:
        previous_envstate = envstate
        # Choose action (exploration or exploitation)
        if np.random.rand() < epsilon:
            action = random.choice(qmaze.valid_actions())
        else:
            action = np.argmax(experience.predict(previous_envstate))

        # Apply action, get reward and new envstate
        envstate, reward, game_status = qmaze.act(action)
        if game_status == 'win':
            win_history.append(1)
            game_over = True
        elif game_status == 'lose':
            win_history.append(0)
            game_over = True

        # Store episode (experience)
        experience.remember([previous_envstate, action, reward, envstate], game_over)

        # Train neural network model
        inputs, targets = experience.get_data(data_size=data_size)
        h = model.fit(
            inputs,
            targets,
            epochs=8,
            batch_size=16,
            verbose=0,
        )
        loss = model.evaluate(inputs, targets, verbose=0)

        n_episodes += 1

    if len(win_history) > hsize:
        win_rate = sum(win_history[-hsize:]) / hsize

    dt = datetime.datetime.now() - start_time
    t = format_time(dt.total_seconds())
    template = "Epoch: {:03d}/{:d} | Loss: {:.4f} | Episodes: {:d} | Win count: {:d} | Win rate: {:.3f} | time: {}"
    print(template.format(epoch, n_epoch-1, loss, n_episodes, sum(win_history), win_rate, t))
    # We simply check if training has exhausted all free cells and if in all
    # cases the agent won
    if win_rate > 0.9 : epsilon = 0.05
    if sum(win_history[-hsize:]) == hsize and completion_check(model, qmaze):
        print("Reached 100%% win rate at epoch: %d" % (epoch,))
        break

# Save trained model weights and architecture, this will be used by the visualization code
model.save_weights("model.weights.h5", overwrite=True)
with open("model.architecture.json", "w") as outfile:
    outfile.write(model.to_json())

# Save the epoch counter to disk
with open("model.epoch", "w") as outfile:
    outfile.write("%d" % (epoch,))

# Save the win history to disk
with open("model.win_history", "w") as outfile:
    outfile.write("%s" % (win_history,))

# Clean up
print("files: %s, %s, %s" % (weights_file, "model.architecture.json", "model.epoch"))
print("n_epoch: %d, max_mem: %d, data: %d, weights: %s" % (n_epoch, max_memory, data_size, weights_file))
print("start_time:", start_time)
print("end_time:", datetime.datetime.now())
```

WARNING! If you did not interpret the assignment, the code **will** error out at this section.

```
# Load the model weights and architecture
from keras.models import model_from_json
with open("model.architecture.json", "r") as infile:
    model = model_from_json(infile.read())
model.load_weights("model.weights.h5")

# Load the epoch counter from disk
with open("model.epoch", "r") as infile:
    start_epoch = int(infile.read())

# Load the win history from disk
with open("model.win_history", "r") as infile:
    win_history = eval(infile.read())

print("Loaded start_epoch: %d" % (start_epoch,))
print("Loaded win_history: %s" % (win_history,))
```

```
Loaded start_epoch: 1
Loaded win_history: [1, 1, 1, 
```

```
Epoch: 295/299 | Loss: 0.0001 | Episodes: 19 | Win count: 207 | Win rate: 0.656 | time: 342.4 seconds
Epoch: 296/299 | Loss: 0.0001 | Episodes: 16 | Win count: 208 | Win rate: 0.656 | time: 342.6 seconds
Epoch: 297/299 | Loss: 0.0001 | Episodes: 9 | Win count: 209 | Win rate: 0.656 | time: 342.8 seconds
Epoch: 298/299 | Loss: 0.0000 | Episodes: 28 | Win count: 210 | Win rate: 0.688 | time: 343.3 seconds
Epoch: 299/299 | Loss: 0.0004 | Episodes: 133 | Win count: 210 | Win rate: 0.656 | time: 345.6 seconds
```

Note: This cell will check to see if the model passes the completion check. Note: This could take several minutes.

In [14]:
```
completion_check(model, qmaze)
```

Out[14]:
```
False
```

This cell will test your model for one game. It will start the pirate at the top-left corner and run **play_game()**. The agent should find a path from the starting position to the target (treasure). The treasure is located in the bottom-right corner.

In [15]:
```
pirate_start = (0, 0)
play_game(model, qmaze, pirate_start)
show(qmaze)
```

Out[15]:
```
<matplotlib.image.AxesImage at 0x79caac0cdf50>
```



Save and Submit Your Work

Hint: To use the markdown block below, double click in the **Type Markdown and LaTeX:** α**2** block below, to turn it back to html, Run the cell.

After you have finished creating the code for your notebook, save your work. Make sure that your notebook contains your name in the filename (e.g. Doe_Jane_ProjectTwo.html). Download this file as an .html file clicking on ***file*** in *Jupyter Notebook*, navigating down to ***Download as*** and clicking on ***.html***. Download a copy of your .html file and submit it to Brightspace.

In [ ]:
```
```