Non-stop casino games

Client-server communications

Protocol description

September, 2026 © polishchuk.com

Table of contents

Table of contents
The basics
Required request parameters
Client authentication
Game list request
Game select
Paytable
Get game options
Set game options
Errors

The basics

Websocket protocol is used for communications between client and server.

Client initiates the connections, and sends requests to the server when needed.

Both client and server use JSON for data wrapping.

Client may not send the next command to the server until it receives a reply to the previous one.

Required request parameters

Regular request looks like this:

```
{  "set": "something",
   "foo": "bar",
   // ... some other options
}
```

Either `set` or `get` option must be present in client request.

In reply the server will repeat the entire request in `on` option.

```
{  "on": {
          "set": "something",
          "foo": "bar",
          // ...all other options from original request
   },
   "something": // ... main result can be found here
   // ... server may send some other options as well
}
```

Server will execute the command and send the result in the option named as `set` or `get` in request.

Client authentication

Request	`var jrequest = {`
	`  "set": "authentication",`
	`  "location": window.location,`
	`};`
	
	`// convert json object to string`
	`var str_request = JSON.stringify( jrequest );`
	`// send string to server`
	`websocket.send ( str_request );`

Successful reply	`{`
	`  "on": {`
	`  "set": "authentication",`
	`  // ... request parameters repeated`
	`  },`
	`  "authentication": true,`
	`  "eval": "some text"`
	`}`
	
	`// client must evaluate the received string:`
	`(function(w) {`
	`  eval(reply.eval);`
	`}(websocket));`

Error	`{`
	`  "on": {`
	`  "set": "authentication",`
	`  // ... request parameters repeated`
	`  },`
	`  "authentication": false,`
	`  "eval": "some text"`
	`}`
	
	`// client must evaluate the received string:`
	`(function(w) {`
	`  eval(reply.eval);`
	`}(websocket));`

In the following requests the `on` option in reply will not be mentioned. But it will always be present there.

Game list request

Request	<pre>{ "get": "game_list" }</pre>

Successful reply	<pre>{
	  "game_list": [
	  {
	  "tag": "bananasGoBahamas",
	  "title": "Bananas Go Bahamas",
	  "id": 8
	  },
	  {
	  "tag": "bingo", // unique short game name
	  "title": "Bingo 5x5", // game title
	  "id": 1 // unique game ID
	  },
	  {
	  "tag": "bookOfRa",
	  "title": "Book Of Ra",
	  "id": 6
	  },
	  // ...
	  ]
	}</pre>

Error	<pre>{ "game_list": false }</pre>

Game select

Request	<pre>{ "set": "game", "game": "bananasGoBahamas" }</pre>

Successful reply	<pre>{
	  "game": {
	  "tag": "bananasGoBahamas",
	  "id": 8,
	  "family": "slot1",
	  "size": {
	  "width": 5, // reels number
	  "height": 3 // items per visible part of the reel
	  },
	  "paytable": // paytable, see description below
	  "lines": // lines configuration, , see description below
	  "config": {
	  "lines": 10 // maximum number of lines available
	  },
	  "bigwin_level": // big win trigger levels
	  },
	  "bets": // array of possible bet sums
	  "previous": // information about previous bet
	  "wallet": // wallet information, total balance and currency name
	}</pre>

Error	<pre>{ "game": false }</pre>

Paytable

Request

```
{
	"get": "paytable",
	"multiplier": false // optional
}
```

Successful reply

```
{
	"tag": "bananasGoBahamas", // unique game short name
	"id": 8, // game unique ID
	"family": "slot1", // game family
	"size": {
		"width": 5, // number of reels
		"height": 3 // number of visible cells per reel
	},
	"paytable": {
		"regular": // symbol type (regular|scatter|wild)
		[
			{
				"id": 1, // unique per game ID
				"name": "nine", // friendly name
				"price": // either multiplier or price
				[	// (depends on multiplier
					//  option in request)
					0,	// price for 1 symbol
					10,	// price for 2 symbols
					25	// ...
				]
			}
		], // ...
	},
	"lines": [	// lines configuration
		[
			"XX---",	// upper row of the screen
			"--X--",
			"---XX"
		]
	],
	"config": {
		"lines": 10	// maximum number of lines
	},
	"bigwin_level": [	// big win trigger values
		20, 100, 250
	]
}
```

Error

```
{
	"paytable": false
}
```

Get game options

Request

```
{
	"get": "options"
}
```

Successful reply

```
{
	"options": {
		// see below
	}
}
```

Error

```
{
	"options": false
}
```

Set game options

Request	`{`
	`  "set": "options",`
	`  "num_lines": 9,  // optional, number of lines selected (integer)`
	`  "bet_sum": 2.50  // optional, bet sum (float)`
	`}`

Successful reply	`{`
	`  "options": {`
	`  "bet_sum": 2.50,  // actual bet sum`
	`  "num_lines": 9  // actual number of selected lines`
	`  }`
	`}`

Error	`{`
	`  "options": false`
	`}`

Errors

In case of any problems/errors, server will reply with `{"error":CODE}`
Possible codes are:

Code	Description
1	Unspecified error
2	Client sent broken JSON
3	Client sent wrong request (error in some parameter)
4	Server lost database connection
5	Not authenticated
6	Unknown game
7	Forbidden. Some client actions are available in test mode only.
8	Problem with PHP, probably it sent the wrong JSON. See server logs for details.
9	PHP request timed out
10	Server error
11	Server error, set in PHP
12	Low balance. The player has no sufficient funds to continue.
13	External session identifier is incorrect
14	Wrong state. Client attempted to perform action which is not available due to current game state.
15	Wrong state. The client must bet first.
16	The client did not send an “index” parameter. Required for some games.
17	Bonus activated, and bet sum is not the same as specified in bonus options.
18	URL hash is incorrect
19	System can not continue

20	Wrong voucher