

API Specification

(v1.0.3)

Contents

1. Overview	4
2. Operator API	4
1) Launch Game	5
2) Create User (Transfer)	7
3) Deposit User Funds (Transfer)	8
4) Withdraw User Funds (Transfer)	10
5) Withdraw All User Funds (Transfer)	11
6) Retrieving User Information (Transfer)	13
7) Pull Report by Date	14
8) Pull Report by Index	16
9) Get Wager Details	19
10) Get Vendor List	21
11) Get Game List	22
12) Get Agent Information	24
13) Get Sub Agent Balances	25
14) Deposit Agent	27
15) Withdraw Agent	29
16) Get Wager Detail URL	31
17) Get Free Round List	33
18) Apply Free Round	34
19) Cancel Free Round	36
3. Wallet Callback API (Seamless Integration)	38

1) Get User Balance	38
2) Change User Balance	39
3) Delivering Game Details	42
4. Appendix	44
1) API Response Codes	44
2) Game type	44
5. Model	45
1) User	45
2) Wager	45
3) Vendor	45
4) VendorGame	46

1. Overview

- **API Address:** You can find the API address in the "Settings and Information" section of the back office.
- **Headers:** All requests must include the "*Content-Type: application/json*" header.
- **Time Format:** Use UTC+0 for all DateTime values.
- **Request Method:** All requests must be made using the *POST* method.

2. Operator API

- Time-out information

When calling operator APIs, there must be a delay between requests.

- ReportByDate (5 seconds)
- ReportById (5 seconds)
- GetWagerInfo (1 second)
- GetVendors (1 second)
- GetVendorGames (1 second)
- GetAgentInfo (3 seconds)
- GetUserInfo (3 seconds)
- GetDetailUrl (1 second)
- CreateUser (1 second)
- GetGameUrl (6 seconds per user - 10 times per minute)
- Deposit (1 second per user)
- Withdraw (1 second per user)
- WithdrawAll (1 second per user)

1) Launch Game

You need to call this API to launch a game.

The vendorCode must be a code retrieved from the GetVendors API.

– Request Parameters

Field	Type	Description	Required
method	String	GetGameUrl	Y
token	String	agent token	Y
agentCode	String	agent code	Y
userCode	String	site user code	Y
nickname	String	nickname	N
vendorCode	String	vendor code	Y
gameCode	String	This is the game code required to launch a specific game. To obtain the game code, refer to the 2.11 API and check if a value is available.	N
currencyCode	String	currency	Y
language	String	language used	N
channel	String	desktop or mobile	N
freeRounds	String	free rounds {bet} {count} {expire} ex."3.00 100 24" Bet:3.00 Free Round count : 100 Expire hours : 24	N
freeRoundsCode	String	Operator will get this value in callback's freeRoundsCode field	N

customGameName	String	ex. "VIP", "VVIP"	N
homeUrl	String	Home url	N
isDemo	Bool	Demo mode	N
lowRtp	Double	If you want 80% rtp, send 0.8	N
highRtp	Double		N
betMultiplier	Double	This will be applied in bets of game	N

– Request Example

```
{
  "method": "GetGameUrl",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "userCode": "Player1",
  "nickName": "Dice",
  "vendorCode": "slot-pragmatic",
  "gameCode": "vs20olympx",
  "currencyCode": "JPY",
  "channel": "desktop",
  "language": "en",
  "lowRtp": 0.6,
  "highRtp": 0.8
}
```

– Response Parameters

Field	Type	Description
status	Integer	response code (see Appendix 4.1)
msg	String	response message
launchUrl	String	site user code

– Response Example

• success

```
{  
  "status": 0,  
  "msg": "SUCCESS",  
  "launchUrl": "https://evolution.com/entry?JSESSIONID=TVE12E22154G"  
}
```

• error

```
{  
  "status": 12,  
  "msg": "INVALID_VENDOR"  
}
```

2) Create User (Transfer)

If you're using the transfer method, this API must be called to create a new user.

– Request Parameters

Field	Type	Description	Required
method	String	CreateUser	Y
token	String	agent token	Y
agentCode	String	agent code	Y
userCode	String	site user code	Y

– Request Example

```
{  
  "method": "CreateUser",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "userCode": "Player1"  
}
```

```
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
userCode	String	Site user code

– Response Example

• **success**

```
{  
  "status": 0,  
  "msg": "SUCCESS",  
  "userCode": "Player1"  
}
```

• **error**

```
{  
  "status": 7,  
  "msg": "DUPLICATE_USER"  
}
```

3) Deposit User Funds (Transfer)

To deposit funds into a user's account, you must call this API.

– Request Parameters

Field	Type	Description	Required
method	String	Deposit	Y
token	String	agent token	Y
agentCode	String	agent code	Y
userCode	String	site user code	Y

currencyCode	String	currency	Y
amount	Decimal	amount	Y

– Request Example

```
{
  "method": "Deposit",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "userCode": "Player1",
  "currencyCode": "JPY",
  "amount": 10000
}
```

– Response Parameters

Field	Type	Description
status	Integer	response code (see Appendix 4.1)
msg	String	response message
prevBalance	Decimal	user balance before change
balance	Decimal	user balance after change

– Response Example

• success

```
{
  "status": 0,
  "msg": "SUCCESS",
  "prevBalance": 100000,
  "balance": 110000
}
```

• error

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

4) Withdraw User Funds (Transfer)

To withdraw funds from a user's account, you must call this API.

– Request Parameters

Field	Type	Description	Required
method	String	Withdraw	Y
token	String	agent token	Y
agentCode	String	agent code	Y
userCode	String	site user code	Y
currencyCode	String	currency	Y
amount	Decimal	amount	Y

– Request Example

```
{
  "method": "Withdraw",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "userCode": "Player1",
  "currencyCode": "JPY",
  "amount": 10000
}
```

– Response Parameters

Field	Type	Description
-------	------	-------------

status	Integer	Response code (see Appendix 4.1)
msg	String	response message
prevBalance	Decimal	user balance before change
balance	Decimal	user balance after change

– Response Example

• **success**

```
{
  "status": 0,
  "msg": "SUCCESS",
  "prevBalance": 100000,
  "balance": 90000
}
```

• **error**

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

5) Withdraw All User Funds (Transfer)

To withdraw all funds from a user's account, you must call this API.

– Request Parameters

Field	Type	Description	Required
method	String	WithdrawAll	Y
token	String	agent token	Y
agentCode	String	agent code	Y
userCode	String	site user code	Y
currencyCode	String	currency	Y

– Request Example

```
{  
  "method": "WithdrawAll",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "userCode": "Player1",  
  "currencyCode": "JPY"  
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
prevBalance	Decimal	User money before change
balance	Decimal	Money held by user after change

– Response Example

• success

```
{  
  "status": 0,  
  "msg": "SUCCESS",  
  "prevBalance": 90000,  
  "balance": 0  
}
```

• error

```
{  
  "status": 5,  
  "msg": "INVALID_USER"
```

```
}
```

6) Retrieving User Information (Transfer)

To retrieve user information from Transfer, you need to call this API.

– Request Parameters

Field	Type	Description	Required
method	String	GetUserInfo	Y
token	String	agent token	Y
agentCode	String	agent code	Y
userCode	String	site user code *If empty, check all user information	N

– Request Example

```
{  
  "method": "GetUserInfo",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "userCode": "Player1"  
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
users	List<User>	User information *Refer to model 5.1 for user details

– Response Example

- **success**

```
{
  "status": 0,
  "msg": "SUCCESS",
  "users": [
    {
      "userCode": "Player 1",
      "balances": { "JPY" : 100000 }
    }
  ]
}
```

- **error**

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

7) Pull Report by Date

To retrieve the completed transaction history up to the most recent transaction, you must call this API.

If the difference between *startDate* and *endDate* exceeds 5 minutes or the time format is invalid, an INVALID_TIME error will be returned.

– Request Parameters

Field	Type	Description	Required
method	String	ReportByDate	Y
token	String	agent token	Y
agentCode	String	agent code	Y

startDate	DateTime	start date and time	Y
endDate	DateTime	end date and time	Y

– Request Example

```
{
  "method": "ReportByDate",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "startDate": "2023-06-25 10:00:00",
  "endDate": "2023-06-25 10:05:00"
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
wagers	List<Wager>	Transaction information *For detailed information on Wager, refer to Model 5.2

– Response Example

• success

```
{
  "status": 0,
  "msg": "SUCCESS",
  "wagers": [
    {
      "userCode": "Player1",
      "vendorCode": "casino-evolution",
      "gameType": 2,
      "gameCode": "LightningBac0001",

```

```

    "gameRoundId": "16033298890220",
    "wagerId": 25641,
    "currencyCode": "JPY",
    "betAmount": 1000,
    "payoutAmount": 2000,
    "beforeBalance": 10000,
    "afterBalance": 11000,
    "detail": null,
    "createdOn": "2023-06-25 10:00:12",
    "modifiedOn": "2023-06-25 10:00:30",
    "settlementOn": "2023-06-25 10:00:30",
    "isFinished": true,
    "status": 1
  },
  ...
]
}

```

• error

```

{
  "status": 20,
  "msg": "INVALID_TIME"
}

```

8) Pull Report by Index

Use this API to retrieve wager details by wager ID.

For the first request, set the `startWagerId` to 0. For subsequent requests, set it to `lastWagerId + 1`.

In the response, if any wager has `isFinished = false`, you must call the "Get Wager Details" API again to retrieve the full details..

– Request Parameters

Field	Type	Description	Required
method	String	ReportById _	Y
token	String	agent token	Y
agentCode	String	agent code	Y
startWagerId	Long	starting index	Y
count	Integer	number of details	Y

– Request Example

```
{  
  "method": "ReportById",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "start WagerId": 25641,  
  "count": 100  
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
lastWagerId	Long	Last history ID
wagers	List<Wager>	wager information *For detailed information about Wagers, please refer to Model 5.2

– Response Example

• success

```
{  
  "status": 0,
```

```

“msg”:“SUCCESS”,
“lastWagerId”: 25645 ,
“wagers”: [
{
  “userCode”:“Player1”,
  “vendorCode”:“slot-pragmatic”,
  “gameType”      : 2,
  “gameCode”:“vs20olympgate”,
  “gameRoundId”:“16033298890220”,
  “wagerId”: 25641,
  “currencyCode”:“JPY”,
  “betAmount”: 1000,
  “payoutAmount”: 2000,
  “beforeBalance”: 10000,
  “afterBalance”: 11000,
  “detail”: null,
  “createdOn”:“2023-06-25 10:00:12”,
  “modifiedOn”:“2023-06-25 10:00:30”,
  “settlementOn”:“2023-06-25 10:00:30”,
  “isFinished”: true,
  “status”: 1
},
...
]
}

```

- **error**

```

{
  “status”: 1,
  “msg”:“INTERNAL_ERROR”
}

```

9) Get Wager Details

To retrieve wager details, you must call this API using the wager ID. If no information is found, an INVALID_WAGER (18) error is returned. If the wager details are incomplete, the response will include the details with `isFinished = false`.

– Request Parameters

Field	Type	Description	Required
method	String	GetWagerInfo	Y
token	String	agent token	Y
agentCode	String	agent code	Y
wagerId	Long	wager ID	Y

– Request Example

```
{  
  "method": "GetWagerInfo",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "wagerId": 25641  
}
```

– Response Parameters

Field	Type	Description
status	Integer	response code (see Appendix 4.1)
msg	String	response message
wager	Wager	wager information

– Response Example

• **success**

```
{  
  "status": 0,  
  "msg": "SUCCESS",  
  "wager": {  
    "userCode": "Player1",  
    "vendorCode": "casino-evolution",  
    "gameType": 2,  
    "gameCode": "LightningBac0001",  
    "gameRoundId": "16033298890220",  
    "wagerId": 25641,  
    "currencyCode": "JPY",  
    "betAmount": 1000,  
    "payoutAmount": 2000,  
    "beforeBalance": 10000,  
    "afterBalance": 11000,  
    "detail": null,  
    "createdOn": "2023-06-25 10:00:12",  
    "modifiedOn": "2023-06-25 10:00:30",  
    "settlementOn": "2023-06-25 10:00:30",  
    "isFinished": true,  
    "status": 1  
  }  
}
```

• **error**

```
{  
  "status": 18,
```

```
"msg": "INVALID_WAGER"
```

```
}
```

10) Get Vendor List

To retrieve the list of game vendors, you need to call this API.

– Request Parameters

Field	Type	Description	Required
method	String	GetVendors	Y
token	String	agent token	Y
agentCode	String	agent code	Y

– Request Example

```
{  
  "method": "GetVendors",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova"  
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
vendors	List<Vendor>	list of game companies *For vendor details, refer to Model 5.3

– Response example

• success

```
{
```

```

"status": 0,
"msg": "SUCCESS",
"vendors": [
  {
    "vendorCode": "casino-evolution",
    "vendorName": "Evolution",
    "gameType": 2
  },
  ...
]
}

```

- **error**

```

{
  "status": 5,
  "msg": "INVALID_USER"
}

```

11) Get Game List

To view the list of games for a specific game vendor, you must call this API.

– Request Parameters

Field	Type	Description	Required
method	String	GetVendorGames	Y
token	String	agent token	Y
agentCode	String	agent code	Y
vendorCode	String	vendor code	Y

– Request Example

```

{
  "method": "GetVendorGames",

```

```

“token”:”s3dcvdfeff4f889765xfd5123”,
“agentCode”:”nova”,
“vendorCode”:”slot-pragmatic”

```

```

}

```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
vendorGames	List<VendorGame>	List of game companies * For detailed information on VendorGame , refer to Model 5.4

– Response Example

• success

```

{
  “status”: 0,
  “msg”:”SUCCESS”,
  “vendorGames”: [
    {
      “gameCode”:”vs20olympgate”,
      “gameName”:”{\\”en \”:\\”Gate of Olympus\\”, \\”en \”:\\”Gates of Olympus\\”}”,
      “gameType”: 1,
      “imageUrl”:”{\\”en\\”:\\”https://api-
sg57.ppgames.net/game_pic/square/200/vs20olympgate.png\\”}”
    },
    ...
  ]
}

```

• error

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

12) Get Agent Information

To retrieve agent information from Transfer, you must call this API.

– Request Parameters

Field	Type	Description	Required
method	String	GetAgentInfo	Y
token	String	agent token	Y
agentCode	String	agent code	Y

– Request Example

```
{
  "method": "GetAgentInfo",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova"
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
balance	Decimal	agent's balance

– Response Example

• success

```
{
  "status": 0,
```



```

    "msg": "SUCCESS",
    "balance": { "JPY": 1000000 }
}

```

• **error**

```

{
  "status": 3,
  "msg": "INVALID_AGENT"
}

```

13) Get Sub Agent Balances

Returns the wallet balances of the requesting agent together with every direct sub-agent. Each row is one wallet (one agent, one currency, one provider bucket).

– Request Parameters

Field	Type	Description	Required
method	String	GetSubAgentBalances	Y
token	String	agent token	Y
agentCode	String	agent code	Y
currencyCode	String	currency. omit to return all currencies.	N

– Request Example

```

{
  "method": "GetSubAgentBalances",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "currencyCode": "USD"
}

```

```
}
```

– Response Parameters

Field	Type	Description
status	Integer	response code (see Appendix 4.1)
msg	String	response message
data	Array	list of balance entries
data[].agentCode	String	agent that owns the wallet
data[].providerCode	String	wallet bucket. equals agentCode for the agent's main wallet.
data[].currencyCode	String	currency
data[].balance	Decimal	current balance

– Response Example

success

```
{  
  "status": 0,  
  "msg": "SUCCESS",  
  "data": [  
    { "agentCode": "nova", "providerCode": "nova", "currencyCode": "USD", "balance":  
      330000 },  
    { "agentCode": "AAAA", "providerCode": "AAAA", "currencyCode": "USD", "balance":  
      50000 },  
    { "agentCode": "BBBB", "providerCode": "BBBB", "currencyCode": "USD", "balance":  
      12000 }  
  ]  
}
```

error

```
{  
  "status": 3,  
  "msg": "INVALID_AGENT"  
}
```

14) Deposit Agent

Transfers funds from the requesting agent's wallet to a direct sub-agent. The amount is debited from the agent and credited to the sub-agent in a single atomic operation.

– Request Parameters

Field	Type	Description	Required
method	String	DepositAgent	Y
token	String	agent token	Y
agentCode	String	agent code (sender)	Y
subAgentCode	String	direct sub-agent code (receiver)	Y
currencyCode	String	currency. defaults to agent currency.	N
amount	Decimal	amount. must be greater than zero.	Y
requestKey	String	client-supplied request id for tracing	N

– Request Example

```
{  
  "method": "DepositAgent",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "subAgentCode": "AAAA",  
  "currencyCode": "USD",  
  "amount": 10000,  
  "requestKey": "trans-2026-05-08-0001"  
}
```

– Response Parameters

Field	Type	Description
status	Integer	response code (see Appendix 4.1)
msg	String	response message
agentCode	String	agent code (sender)
prevAgentBalance	Decimal	agent balance before the transfer
agentBalance	Decimal	agent balance after the transfer
subAgentCode	String	sub-agent code (receiver)
prevSubAgentBalance	Decimal	sub-agent balance before the transfer
subAgentBalance	Decimal	sub-agent balance after the transfer
amount	Decimal	transferred amount
currencyCode	String	currency

– Response Example

success

```
{
  "status": 0,
  "msg": "SUCCESS",
  "agentCode": "nova",
  "prevAgentBalance": 330000,
  "agentBalance": 320000,
  "subAgentCode": "AAAA",
  "prevSubAgentBalance": 50000,
  "subAgentBalance": 60000,
  "amount": 10000,
  "currencyCode": "USD"
}
```

error

```
{
  "status": 8,
  "msg": "INSUFFICIENT_MONEY"
}
```

15) Withdraw Agent

Pulls funds from a direct sub-agent's wallet back into the requesting agent's wallet. The amount is debited from the sub-agent and credited to the agent in a single atomic operation.

– Request Parameters

Field	Type	Description	Required
method	String	WithdrawAgent	Y
token	String	agent token	Y
agentCode	String	agent code (receiver)	Y
subAgentCode	String	direct sub-agent code (sender)	Y
currencyCode	String	currency. defaults to agent currency.	N
amount	Decimal	amount. must be greater than zero.	Y
requestKey	String	client-supplied request id for tracing	N

– Request Example

```
{
  "method": "WithdrawAgent",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "subAgentCode": "AAAA",
```

```

"currencyCode": "USD",
"amount": 5000,
"requestKey": "trans-2026-05-08-0002"
}

```

– Response Parameters

Field	Type	Description
status	Integer	response code (see Appendix 4.1)
msg	String	response message
agentCode	String	agent code (receiver)
prevAgentBalance	Decimal	agent balance before the transfer
agentBalance	Decimal	agent balance after the transfer
subAgentCode	String	sub-agent code (sender)
prevSubAgentBalance	Decimal	sub-agent balance before the transfer
subAgentBalance	Decimal	sub-agent balance after the transfer
amount	Decimal	transferred amount
currencyCode	String	currency

– Response Example

success

```

{
  "status": 0,
  "msg": "SUCCESS",
  "agentCode": "nova",
  "prevAgentBalance": 320000,
  "agentBalance": 325000,
  "subAgentCode": "AAAA",
  "prevSubAgentBalance": 60000,
  "subAgentBalance": 55000,

```

```

    "amount": 5000,
    "currencyCode": "USD"
  }
  error
  {
    "status": 8,
    "msg": "INSUFFICIENT_MONEY"
  }

```

16) Get Wager Detail URL

To retrieve wager details using the wager ID, you must call this API.

– Request Parameters

Field	Type	Description	Required
method	String	GetDetailUrl	Y
token	String	agent token	Y
agentCode	String	agent code	Y
wagerId	Long	wager ID	Y

– Request Example

```

{
  "method": "GetDetailUrl",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "wagerId": 25641
}

```

– Response Parameters

Field	Type	Description
-------	------	-------------

status	Integer	Response code (see Appendix 4.1)
msg	String	response message
detailUrl	String	Transaction details URL

– Response Example

• success

```
{
  "status": 0,
  "msg": "SUCCESS",
  "detailUrl": "https://api.xyz.com / GameDetail?token =
s3dcvdfeff4f889765xfd5123 &wagerId= 25641"
}
```

• error

```
{
  "status": 18,
  "msg": "INVALID_WAGER"
}
```


17) Get Free Round List

Retrieves the list of available bet amounts that can be granted as free rounds for the given vendor and game. Use the returned values when calling Apply Free Round.

If the vendor or game does not support free rounds, the returned list is empty.

– Request Parameters

Field	Type	Description	Required
method	String	GetFreeRoundList	Y
token	String	Agent token	Y
agentCode	String	Agent code	Y
vendorCode	String	Vendor code (returned by GetVendors)	Y
gameCode	String	Game code (returned by GetVendorGames)	Y
currencyCode	String	Currency code (ISO 4217). Defaults to agent currency.	N

– Request Example

```
{  
  "method": "GetFreeRoundList",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "agentCode": "nova",  
  "vendorCode": "slot-pragmatic",  
  "gameCode": "vs20olympx",  
  "currencyCode": "USD"  
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix - API Response

		Codes)
msg	String	Response message
freeRounds	Array<Decimal>	Available per-spin bet amounts that can be applied

– Response Example

success

```
{
  "status": 0,
  "msg": "SUCCESS",
  "freeRounds": [ 0.10, 0.20, 0.50, 1.00 ]
}
```

error

```
{
  "status": 12,
  "msg": "INVALID_VENDOR"
}
```

18) Apply Free Round

Grants a number of free spins to a player on a specific game. The user must already exist; the bet amount must be one of the values returned by Get Free Round List.

Free rounds expire automatically after expireHours hours, even if the player has not consumed all spins.

– Request Parameters

Field	Type	Description	Required
method	String	ApplyFreeRound	Y
token	String	Agent token	Y
agentCode	String	Agent code	Y
userCode	String	Target player's user code	Y
vendorCode	String	Vendor code	Y

		(returned by GetVendors)	
gameCode	String	Game code (returned by GetVendorGames)	Y
currencyCode	String	Currency code (ISO 4217). Defaults to agent currency.	N
betAmount	Decimal	Per-spin bet amount. Must be one of the values returned by GetFreeRoundList.	Y
spinCount	Integer	Number of free spins to grant	Y
expireHours	Decimal	Validity window in hours (e.g. 24)	Y

– Request Example

```
{
  "method": "ApplyFreeRound",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "userCode": "Player1",
  "vendorCode": "slot-pragmatic",
  "gameCode": "vs20olympx",
  "currencyCode": "USD",
  "betAmount": 0.20,
  "spinCount": 30,
  "expireHours": 24
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see

		Appendix - API Response Codes)
msg	String	Response message

– Response Example

success

```
{
  "status": 0,
  "msg": "SUCCESS"
}
```

error

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

19) Cancel Free Round

Cancels any active free-round campaign that the player has on the given game. Spins that have already been played are not refunded; only the remaining unused free rounds are removed.

– Request Parameters

Field	Type	Description	Required
method	String	CancelFreeRound	Y
token	String	Agent token	Y
agentCode	String	Agent code	Y
userCode	String	Target player's user code	Y
vendorCode	String	Vendor code (returned by GetVendors)	Y
gameCode	String	Game code (returned by	Y

		GetVendorGames)	
currencyCode	String	Currency code (ISO 4217). Defaults to agent currency.	N

– Request Example

```
{
  "method": "CancelFreeRound",
  "token": "s3dcvdfeff4f889765xfd5123",
  "agentCode": "nova",
  "userCode": "Player1",
  "vendorCode": "slot-pragmatic",
  "gameCode": "vs20olympx",
  "currencyCode": "USD"
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix - API Response Codes)
msg	String	Response message

– Response Example

success

```
{
  "status": 0,
  "msg": "SUCCESS"
}
```

error

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

3. Wallet Callback API (Seamless Integration)

- For seamless API integration, the site must implement the following callback APIs.

- GetBalance
- ChangeBalance
- Timeout Requirement

All API responses must be returned within 2 seconds.

- Site Endpoint

The site provides its own endpoint for these callbacks.

Example: <https://stake.com>

1) Get User Balance

The API calls this endpoint to retrieve the user's balance from the site.

– Request Parameters

Field	Type	Description	Required
method	String	GetBalance	Y
token	String	agent token	Y
userCode	String	site user code	Y
currencyCode	String	currency	Y

– Request Example

```
{  
  "method": "GetBalance",  
  "token": "s3dcvdfeff4f889765xfd5123",  
  "userCode": "Player1",  
  "currencyCode": "JPY"  
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
balance	Decimal	User's money

– Response Example

• **success**

```
{  
  "status": 0,  
  "msg": "SUCCESS",  
  "balance": 10000  
}
```

• **error**

```
{  
  "status": 5,  
  "msg": "INVALID_USER"  
}
```

2) Change User Balance

This API is called when a user places a bet, wins, cancels, or receives a bonus/jackpot. The corresponding amount to be deducted or credited is sent to the site through this API.

To reduce complexity on the site side, simply apply the `amount` value—whether it's a bet, win, cancellation, bonus, or jackpot.

Every **Debit** has a corresponding **Credit** or **Cancel**, which can be identified using the `wagerId`.

You must set up a **cron job** to verify that a **Credit** or **Cancel** has been received for every **Debit**.

If no corresponding Credit or Cancel is received within **10 minutes** of the Debit, the site must manually check and process the result using the `GetWagerInfo` API.

Transaction Types:

0 – Debit, 1 – Credit, 2 – Cancel

If a transaction includes multiple matching pairs, you can use the **pair reference code** to differentiate them.

– Request Parameters

Field	Type	Description	Required
method	String	ChangeBalance	Y
token	String	agent token	Y
userCode	String	site user code	Y
currencyCode	String	currency	Y
vendorCode	String	vendor code	Y
txnType	Int	transaction type	Y
wagerId	Long	wager ID	Y
detail	String	detail data	N
pairCode	String	pair reference code	N
txnCode	String	transaction code	Y
amount	Decimal	amount	Y
gameCode	String	game code	N
gameRoundId	String	game round ID	N
createdOn	DateTime	created date	Y
isFinished	Boolean		Y
isFreeRound	Boolean	if free round, true	Y

– Request Example

```
{  
  "method": "ChangeBalance",
```



```

“token”:”s3dcvdfeff4f889765xfd5123”,
“userCode”:”Player1”,
“currencyCode”:”JPY”,
“vendorCode”:”slot-pragmatic”,
“txnType”: 0,
“txnCode”:”321209”,
“pairCode”: null,
“wagerId”: 12345,
“detail”:”,
“amount”: -2000,
“gameCode”:”vs20olympgate”,
“gameRoundId”:”4988503233898”,
“createdOn”:”2023-06-28 12:00:00”,
“isFinished” : false,
“isFreeRound” : false

```

```

}

```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message
balance	Decimal	user's balance

– Response Example

• **SUCCESS**

```

{
“status”: 0,
“msg”:”SUCCESS”,
“balance”: 10000
}

```

- **error**

```
{
  "status": 5,
  "msg": "INVALID_USER"
}
```

3) Delivering Game Details

Once the game details are finalized, they are sent to the site using this API.

– Request Parameters

Field	Type	Description	Required
method	String	UpdateDetail	Y
token	String	agent token	Y
wagerId	Long	wager ID	Y
detail	String	Detail data	Y

– Request Example

```
{
  "method": "UpdateDetail",
  "token": "s3dcvdfeff4f889765xfd5123",
  "wagerId": 25641,
  "detail": "{\"uuid \": \"99ce43fb-8a35-456b-967d-1c46dd835411\"}"
}
```

– Response Parameters

Field	Type	Description
status	Integer	Response code (see Appendix 4.1)
msg	String	response message

– Response Example

- **success**

```
{  
  "status": 0,  
  "msg": "SUCCESS"
```

```
}
```

- **error**

```
{  
  "status": 18 ,  
  "msg": "INVALID_WAGER"  
}
```

4. Appendix

1) API Response Codes

Code	Message	Description
0	SUCCESS	Success
1	INTERNAL_ERROR	Server internal error
2	INVALID_ACTION	Request error
3	INVALID_AGENT	Agent error
4	BLOCK_AGENT	Blocked agent
5	INVALID_USER	User error
6	BLOCK_USER	Blocked user
7	DUPLICATE_USER	Duplicate users
8	INSUFFICIENT_MONEY	Insufficient balance
12	INVALID_VENDOR	Vendor error
13	INVALID_PARAMETER	Invalid request parameter
14	NETWORK_ERROR	Network error
15	MAINTENANCE	System under maintenance
18	INVALID_WAGER	Invalid transaction or wager ID
20	INVALID_TIME	Invalid time format or range
21	DUPLICATE_REQUESTKEY	Duplicate request key (for duplicate prevention)
22	TIMEOUT_ERROR	Request timed out

2) Game type

Code	Description
1	Slot
2	Live Casino

5. Model

1) User

Field	Type	Description
userCode	String	user code
balances	Map<String,Decimal>	user's balance

2) Wager

Field	Type	Description
userCode	String	user code
vendorCode	String	vendor code
gameType	Integer	game type (see Appendix 4.2)
gameCode	String	game code
gameRoundId	String	game round ID
wagerId	Integer	wager ID
betAmount	Decimal	bet amount
payoutAmount	Decimal	payout amount
beforeBalance	Decimal	balance before change
afterBalance	Decimal	balance after change
detail	String	detail data
createdOn	DateTime	created date
modifiedOn	DateTime	modified date
settlementOn	DateTime	settlement date
status	Integer	status

3) Vendor

Field	Type	Description
vendorCode	String	code

vendorName	String	name
gameType	Integer	game type (see Appendix 4.2)

4) VendorGame

Field	Type	Description
gameCode	String	game code
gameName	String	game name
gameType	Integer	game type (see Appendix 4.2)
imageUrl	String	path to obtain game images