# Turret v0 on its bench stand print queue

Gyropup retained prototype workstreams · Revision: cd276824fcbe0bea6c3c39099120afd465b751a3

All parts: 23 of 23

Original leg, rig, turret and earlier body planning lists. Current front/rear-pack robot manufacturing plan remains incomplete. Checklist marks track parts, not purchased quantities. This list does not qualify fit, strength or a complete robot.

| Done | Part ID | Order | Part | Material | Quantity | Grams | Hours | Print setup | Printed |
|---|---|---|---|---|---|---|---|---|---|
| ☐ | print/turret/stand_box | 1 | stand_box | petg | 1 | 402 | 16.1 | See note below | ☐ |
| **Print setup:** Placement and instructions 200 × 200 × 150 mm · straight printed PETG upside down; 4 x M5 + 4 x M3 inserts for the bottom, 2 x M3 x 4.3 (94459A130) for the dock (set with a flat tip, the top face on a flat plate, then check the pan base's seat flat; the dock adapter's M3s no longer than its base + 5 mm: 0.7 mm of plate over the pilots), 4 x M3 for the board 2 mm walls, 40 % gyroid | | | | | | | | | |
| ☐ | print/turret/cartridge_body | 2 | cartridge_body Model export pending | pa6-cf | 1 | 169 | 11.1 | Placement and instructions 166 × 103 × 82 mm · straight PA6-CF on its base; supports under the chute 100 % | ☐ |
| ☐ | print/turret/tilt_yoke | 3 | tilt_yoke Model export pending | pa6-cf | 1 | 126 | 8.3 | Placement and instructions 173 × 91 × 40 mm · straight PA6-CF on its back; 4 x M4 x 12 to the turntable (heads 6 mm down in the 12 mm bridge) 100 % | ☐ |
| ☐ | print/turret/pan_ring | 4 | pan_ring Model export pending | pa6-cf | 1 | 78 | 5.1 | Placement and instructions 81 × 81 × 41 mm · straight PA6-CF upside down; DIN 471-50 circlip; 4 x M4 inserts 100 % | ☐ |
| ☐ | print/turret/pan_base | 5 | pan_base Model export pending | pa6-cf | 1 | 70 | 4.6 | Placement and instructions 160 × 158 × 47 mm · straight PA6-CF on its foot; 4 x M5 x 16 into the head ring, 2 x Ø5 dowels 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/stand_bottom | 6 | stand_bottom | petg | 1 | 98 | 3.9 | Placement and instructions 240 × 200 × 8 mm · straight printed PETG flat; 4 x M3 x 8 into the corner bosses; 4 rubber feet; two ribs the pack slides on 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/cradle | 7 | cradle Model export pending | pa6-cf | 1 | 48 | 3.1 | Placement and instructions 150 × 114 × 10 mm · straight PA6-CF flat, no supports: the rail frame (D48); 8 x M3 inserts for the aluminium cheek plates 100 % | ☐ |

| Done | Part ID | Order | Part | Material | Quantity | Grams | Hours | Print setup | Printed |
|---|---|---|---|---|---|---|---|---|---|
| ☐ | print/turret/ring_carrier | 8 | ring_carrier Model export pending | pa6-cf | 1 | 30 | 2 | Placement and instructions 73 × 65 × 12 mm · straight PA6-CF on its top face; 3 x M3 x 10 flat heads up into the base; 3 x M3 inserts for the ring 100 % | ☐ |
| ☐ | print/turret/dial | 9 | dial Model export pending | petg | 1 | 22 | 0.9 | Placement and instructions 91 × 91 × 44 mm · straight PETG; 4 x M3 x 8 down into the feed servo's horn, from the top 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/flywheel | 10 | flywheel Model export pending | pa6-cf | 2 | 12 | 0.8 | Placement and instructions 30 × 30 × 12 mm · straight PA6-CF on its top face; on the X2216's prop adapter: washer + M5 nylon-insert nut; bore reamed to 5.00 100 % | ☐ |
| ☐ | print/turret/hopper | 11 | hopper Model export pending | petg | 1 | 20 | 0.8 | Placement and instructions 103 × 102 × 65 mm · straight translucent PETG standing; 3 x M3 to the housing; three ridges for the lid's latches, the notch for its key 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/flywheel_tyre | 12 | flywheel_tyre Model export pending | tpu95 | 2 | 6 | 0.6 | Placement and instructions 38 × 38 × 12 mm · straight TPU 95A tyre 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/barrel | 13 | barrel Model export pending | petg | 1 | 13 | 0.5 | Placement and instructions 35 × 30 × 100 mm · straight PETG standing; last 15 mm blaze orange 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/board_bay | 14 | board_bay Model export pending | petg | 1 | 13 | 0.5 | Placement and instructions 59 × 58 × 49 mm · straight PETG on its back; 4 x M3 x 8 flat heads to the -y yoke arm; 4 x M3 inserts for the boards; two ridges for the lid's latches 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/hopper_lid | 15 | hopper_lid Model export pending | petg | 1 | 12 | 0.5 | See note below | ☐ |
| **Print setup:** Placement and instructions 110 × 107 × 26 mm · straight PETG upside down (the latches in the bed plane), on the flap's hinge lugs and the latches: supports under the disc only; three snap latches onto the hopper's ridges, push on, pull off; keyed, goes on one way 2 mm walls, 40 % gyroid | | | | | | | | | |
| ☐ | print/turret/pan_pinion | 16 | pan_pinion Model export pending | pa6-cf | 1 | 8 | 0.5 | Placement and instructions 29 × 29 × 17 mm · straight PA6-CF; 4 x M2 to the horn; turns -3 x pan about the servo axis 100 % | ☐ |
| ☐ | print/turret/ring_driver | 17 | ring_driver Model export pending | pa6-cf | 1 | 8 | 0.5 | Placement and instructions 40 × 39 × 14 mm · straight PA6-CF on its top face; in the turntable's bore (ribs + CA) 100 % | ☐ |
| ☐ | print/turret/base_board_carrier | 18 | base_board_carrier Model export pending | pa6-cf | 1 | 5 | 0.3 | Placement and instructions 70 × 32 × 8 mm · straight Removable board carrier; exterior face on bed, standoffs up; service requires bumper removal 100 % | ☐ |

| Done | Part ID | Order | Part | Material | Quantity | Grams | Hours | Print setup | Printed |
|---|---|---|---|---|---|---|---|---|---|
| ☐ | print/turret/board_bay_lid | 19 | board_bay_lid Model export pending | petg | 1 | 6 | 0.3 | Placement and instructions 66 × 58 × 12 mm · straight PETG flat (the latches in the bed plane); two snap latches onto the bay's ridges, push on, pull off 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/horn_boss | 20 | horn_boss Model export pending | pa6-cf | 1 | 2 | 0.2 | Placement and instructions 20 × 20 × 9 mm · straight PA6-CF on an end face; between the +y plate and the tilt servo's horn (4 x M3 x 14 flat heads) 100 % | ☐ |
| ☐ | print/turret/pan_spacer | 21 | pan_spacer Model export pending | pa6-cf | 1 | 3 | 0.2 | Placement and instructions 59 × 59 × 4 mm · straight PA6-CF on its wide end; between the 61810 inner race and the circlip 100 % | ☐ |
| ☐ | print/turret/laser_mount | 22 | laser_mount Model export pending | petg | 1 | 4 | 0.1 | Placement and instructions 33 × 25 × 18 mm · straight PETG; 3 x M3 boresight, 2 x M3 x 10 to the socket pad 2 mm walls, 40 % gyroid | ☐ |
| ☐ | print/turret/pivot_spacer | 23 | pivot_spacer Model export pending | pa6-cf | 1 | 1 | 0.1 | Placement and instructions 18 × 18 × 4 mm · straight PA6-CF on its boss face, land up; between the -y plate and the MR126 (the shoulder screw through it) 100 % | ☐ |