Turret v0 on its bench stand print queue

Gyropup retained prototype workstreams · Revision: cd276824fcbe0bea6c3c39099120afd465b751a3

All parts: 23 of 23

Original leg, rig, turret and earlier body planning lists. Current front/rear-pack robot manufacturing plan remains incomplete. Checklist marks track parts, not purchased quantities. This list does not qualify fit, strength or a complete robot.

Done	Part ID	Order	Part	Material	Quantity	Grams	Hours	Print setup	Printed
☐	print/turret/stand_box	1	stand_box	petg	1	402	16.1	See note below	☐
Print setup: Placement and instructions 200 × 200 × 150 mm · straight printed PETG upside down; 4 x M5 + 4 x M3 inserts for the bottom, 2 x M3 x 4.3 (94459A130) for the dock (set with a flat tip, the top face on a flat plate, then check the pan base's seat flat; the dock adapter's M3s no longer than its base + 5 mm: 0.7 mm of plate over the pilots), 4 x M3 for the board 2 mm walls, 40 % gyroid									
☐	print/turret/cartridge_body	2	cartridge_body Model export pending	pa6-cf	1	169	11.1	Placement and instructions 166 × 103 × 82 mm · straight PA6-CF on its base; supports under the chute 100 %	☐
☐	print/turret/tilt_yoke	3	tilt_yoke Model export pending	pa6-cf	1	126	8.3	Placement and instructions 173 × 91 × 40 mm · straight PA6-CF on its back; 4 x M4 x 12 to the turntable (heads 6 mm down in the 12 mm bridge) 100 %	☐
☐	print/turret/pan_ring	4	pan_ring Model export pending	pa6-cf	1	78	5.1	Placement and instructions 81 × 81 × 41 mm · straight PA6-CF upside down; DIN 471-50 circlip; 4 x M4 inserts 100 %	☐
☐	print/turret/pan_base	5	pan_base Model export pending	pa6-cf	1	70	4.6	Placement and instructions 160 × 158 × 47 mm · straight PA6-CF on its foot; 4 x M5 x 16 into the head ring, 2 x Ø5 dowels 2 mm walls, 40 % gyroid	☐
☐	print/turret/stand_bottom	6	stand_bottom	petg	1	98	3.9	Placement and instructions 240 × 200 × 8 mm · straight printed PETG flat; 4 x M3 x 8 into the corner bosses; 4 rubber feet; two ribs the pack slides on 2 mm walls, 40 % gyroid	☐
☐	print/turret/cradle	7	cradle Model export pending	pa6-cf	1	48	3.1	Placement and instructions 150 × 114 × 10 mm · straight PA6-CF flat, no supports: the rail frame (D48); 8 x M3 inserts for the aluminium cheek plates 100 %	☐

Done	Part ID	Order	Part	Material	Quantity	Grams	Hours	Print setup	Printed
☐	print/turret/ring_carrier	8	ring_carrier Model export pending	pa6-cf	1	30	2	Placement and instructions 73 × 65 × 12 mm · straight PA6-CF on its top face; 3 x M3 x 10 flat heads up into the base; 3 x M3 inserts for the ring 100 %	☐
☐	print/turret/dial	9	dial Model export pending	petg	1	22	0.9	Placement and instructions 91 × 91 × 44 mm · straight PETG; 4 x M3 x 8 down into the feed servo's horn, from the top 2 mm walls, 40 % gyroid	☐
☐	print/turret/flywheel	10	flywheel Model export pending	pa6-cf	2	12	0.8	Placement and instructions 30 × 30 × 12 mm · straight PA6-CF on its top face; on the X2216's prop adapter: washer + M5 nylon-insert nut; bore reamed to 5.00 100 %	☐
☐	print/turret/hopper	11	hopper Model export pending	petg	1	20	0.8	Placement and instructions 103 × 102 × 65 mm · straight translucent PETG standing; 3 x M3 to the housing; three ridges for the lid's latches, the notch for its key 2 mm walls, 40 % gyroid	☐
☐	print/turret/flywheel_tyre	12	flywheel_tyre Model export pending	tpu95	2	6	0.6	Placement and instructions 38 × 38 × 12 mm · straight TPU 95A tyre 2 mm walls, 40 % gyroid	☐
☐	print/turret/barrel	13	barrel Model export pending	petg	1	13	0.5	Placement and instructions 35 × 30 × 100 mm · straight PETG standing; last 15 mm blaze orange 2 mm walls, 40 % gyroid	☐
☐	print/turret/board_bay	14	board_bay Model export pending	petg	1	13	0.5	Placement and instructions 59 × 58 × 49 mm · straight PETG on its back; 4 x M3 x 8 flat heads to the -y yoke arm; 4 x M3 inserts for the boards; two ridges for the lid's latches 2 mm walls, 40 % gyroid	☐
☐	print/turret/hopper_lid	15	hopper_lid Model export pending	petg	1	12	0.5	See note below	☐
Print setup: Placement and instructions 110 × 107 × 26 mm · straight PETG upside down (the latches in the bed plane), on the flap's hinge lugs and the latches: supports under the disc only; three snap latches onto the hopper's ridges, push on, pull off; keyed, goes on one way 2 mm walls, 40 % gyroid									
☐	print/turret/pan_pinion	16	pan_pinion Model export pending	pa6-cf	1	8	0.5	Placement and instructions 29 × 29 × 17 mm · straight PA6-CF; 4 x M2 to the horn; turns -3 x pan about the servo axis 100 %	☐
☐	print/turret/ring_driver	17	ring_driver Model export pending	pa6-cf	1	8	0.5	Placement and instructions 40 × 39 × 14 mm · straight PA6-CF on its top face; in the turntable's bore (ribs + CA) 100 %	☐

Done	Part ID	Order	Part	Material	Quantity	Grams	Hours	Print setup	Printed
☐	print/turret/base_board_carrier	18	base_board_carrier Model export pending	pa6-cf	1	5	0.3	Placement and instructions 70 × 32 × 8 mm · straight Removable board carrier; exterior face on bed, standoffs up; service requires bumper removal 100 %	☐
☐	print/turret/board_bay_lid	19	board_bay_lid Model export pending	petg	1	6	0.3	Placement and instructions 66 × 58 × 12 mm · straight PETG flat (the latches in the bed plane); two snap latches onto the bay's ridges, push on, pull off 2 mm walls, 40 % gyroid	☐
☐	print/turret/horn_boss	20	horn_boss Model export pending	pa6-cf	1	2	0.2	Placement and instructions 20 × 20 × 9 mm · straight PA6-CF on an end face; between the +y plate and the tilt servo's horn (4 x M3 x 14 flat heads) 100 %	☐
☐	print/turret/pan_spacer	21	pan_spacer Model export pending	pa6-cf	1	3	0.2	Placement and instructions 59 × 59 × 4 mm · straight PA6-CF on its wide end; between the 61810 inner race and the circlip 100 %	☐
☐	print/turret/laser_mount	22	laser_mount Model export pending	petg	1	4	0.1	Placement and instructions 33 × 25 × 18 mm · straight PETG; 3 x M3 boresight, 2 x M3 x 10 to the socket pad 2 mm walls, 40 % gyroid	☐
☐	print/turret/pivot_spacer	23	pivot_spacer Model export pending	pa6-cf	1	1	0.1	Placement and instructions 18 × 18 × 4 mm · straight PA6-CF on its boss face, land up; between the -y plate and the MR126 (the shoulder screw through it) 100 %	☐