## 版本号

系统版本号定义长度为12位如: BX1086550101

```
第[1] 位固定为B.

第[2-3] 表示项目代号 如:X1

第[3-5] 表示地区 如:086

第[6-7] 预留缺省 如:55

第[8-11] 表示版本 如:0101
```

## 目录结构

vendor下面添加目录结构如下:



vendor/bn/app 此目录用来放置源码app.

如: vendor/bn/app/BN\_MMITest/

• vendor/bn/products/coral

```
存放具体项目相关的文件
如: vendor/bn/products/coral/app 存放三方独立app.
目前Tmake.sh 从 ftp://ftpdown:ftpdown@10.58.144.14:35021/release_apk/自动下载.

vendor/bn/products/coral/configs
存放项目配置文件如:
build_number.txt
otherapks.yml
```

vendor/bn/script/

存放定制化编译脚本如:

## 编译命令

./Tmake.sh -t aosp\_coral -v userdebug

```
usage() {
   cat <<USAGE
Usage:
   bash $0 [OPTIONS]
Description:
   Builds Android tree for given TARGET_PRODUCT, Default add otherapks to build
   -c, --clean_build
       Clean build - build from scratch by removing entire out dir
   -h, --help
       Display this help message
    -i, --image
       Specify image to be build/re-build (bootimg/sysimg/usrimg/all Default: all)
       Specifies the number of jobs to run simultaneously (Default: CPU core Number)
   -k, --kernel_defconf
       Specify defconf file to be used for compiling Kernel
    -1, --log_file
       Log file to store build logs (Default: time.log)
   -m, --module
       Module to be build (make e.g.:snod clean clobber)
       Project to be build (mmm e.g.:packages/app/Settings)
   -t, --target
       target to be build
    -u, --update-api
       Update APIs
    -v, --build_variant
        Build variant (Default: eng)
USAGE
}
```