

ASSIGNMENT – 10

NAME: G. OMKAR

HT.NO: 2403A52039

BATCH: 03

Task-1:

Syntax and Error Detection

Task: Identify and fix syntax, indentation, and variable errors in the given script.

```
def add_numbers(a, b)

result = a + b

return reslt

print(add_numbers(10 20))
```

Expected Output:

- Corrected code with proper syntax (: after function, fixed variable name, corrected function call).
- AI should explain what was fixed

Prompt: Identify and fix syntax, indentation, and variable errors in

the

given script.

```
def add_numbers(a, b)
```


```
    result = a + b
```

```
    return reslt
```


```
print(add_numbers(10 20)).
```

even explain the errors.

Code:



OP:



Observation: It has corrected the errors and even explained it. Bug: def add_numbers(a, b) is missing a colon (:) at the end of the function definition. Fix: Add a colon: def add_numbers(a, b):. Bug: The variable reslt in the return statement is misspelled. Fix: Correct the variable name to result. Bug: print(add_numbers(10

20)) is missing a comma between 10 and 20. Fix: Add a comma: `print(add_numbers(10, 20))`. Bug: The print statement has an extra closing parenthesis: `print(add_numbers(10, 20))`. Fix: Remove the extra parenthesis.

Task-2:

Logical and Performance Issue Review

Task: Optimize inefficient logic while keeping the result correct.

```
# buggy_code_task2.py
```

```
def find_duplicates(nums):
```

```
    duplicates = []
```

```
    for i in range(len(nums)):
```

```
        for j in range(len(nums)):
```

```
            if i != j and nums[i] == nums[j] and nums[i] not in duplicates:
```

```
                duplicates.append(nums[i])
```

```
    return duplicates
```

```
numbers = [1,2,3,2,4,5,1,6,1,2]
```

```
print(find_duplicates(numbers))
```

Expected Output:

- More efficient duplicate detection (e.g., using sets).
- AI should explain the optimization.

Prompt: Optimize inefficient logic while keeping the result correct.

```
def find_duplicates(nums):
    duplicates = []
    for i in range(len(nums)):
        for j in range(len(nums)):
            if i != j and nums[i] == nums[j] and nums[i] not in duplicates:
                duplicates.append(nums[i])
    return duplicates

numbers = [1,2,3,2,4,5,1,6,1,2]
print(find_duplicates(numbers)). use sets and give explanation for correction
```

Code:

```
def find_duplicates(nums):
    """
    nums (list): A list of integers.

    Returns:
    list: A list of duplicate elements.
    """
    seen = set()  # Set to track seen elements
    duplicates = set()  # Set to track duplicates

    for num in nums:
        if num in seen:
            duplicates.add(num)  # Add to duplicates if already seen
        else:
            seen.add(num)  # Add to seen if not already seen

    return list(duplicates)  # Convert duplicates set to a list

# Test the function
numbers = [1, 2, 3, 2, 4, 5, 1, 6, 1, 2]
print(find_duplicates(numbers))
```

return duplicates
numbers = [1,2,3,2,4,5,1,6,1,2]
print(find_duplicates(numbers)). use sets and give explanation for correction

Used 1 sentence:

Here's the optimized version of the find_duplicates function using sets, along with an explanation of the corrections:

Optimized Code:

```
def find_duplicates(nums):
    """
    Finds duplicate elements.

    Args:
        nums (list): A list of integers.
    """
    seen = set()
    duplicates = set()

    for num in nums:
        if num in seen:
            duplicates.add(num)
        else:
            seen.add(num)

    return list(duplicates)
```

OP:

Task: Refactor messy code into clean, PEP 8-compliant, well-

structured code.

```
# buggy_code_task3.py
```

```
def c(n):
```

```
    x=1
```

```
    for i in range(1,n+1):
```

```
        x=x*i
```

```
    return x
```

```
print(c(5))
```

Expected Output:

Function renamed to calculate_factorial.

Proper indentation, variable naming, docstrings, and formatting.

AI should provide a more readable version

Prompt: Refactor messy code into clean, PEP 8-compliant, well-structured code.

```
def c(n):
```

```
    x=1
```

```
    for i in range(1,n+1):
```


```
        x=x*i
```

return x

print(c(5))


Function renamed to calculate_factorial. Proper indentation, variable naming, docstrings, and formatting

Code:



```
1 def calculate_factorial(n: int) -> int:
2     """
3     Calculate the factorial of a given number.
4
5     Args:
6         n (int): The number to calculate the factorial for.
7
8     Returns:
9         int: The factorial of the given number.
10    """
11    factorial = 1
12    for i in range(1, n + 1):
13        factorial *= i
14    return factorial
15
16 # Test the function
17 if __name__ == "__main__":
18     print(calculate_factorial(5))
```

OP:



```
1 def calculate_factorial(n: int) -> int:
2     """
3     Calculate the factorial of a given number.
4
5     Args:
6         n (int): The number to calculate the factorial for.
7
8     Returns:
9         int: The factorial of the given number.
10    """
11    factorial = 1
12    for i in range(1, n + 1):
13        factorial *= i
14    return factorial
15
16 # Test the function
17 if __name__ == "__main__":
18     print(calculate_factorial(5))
```

Observation: Renamed c to calculate_factorial to make the function name descriptive and meaningful.

Renamed x to factorial for clarity. Added a Google-style docstring to describe the function's purpose, arguments, and return value.

Ensured proper indentation and spacing.

Added type hints for the function argument and return value.

Wrapped the test call in an if __name__ == "__main__": block to ensure the function is only executed when the script is run directly.

Task-4:

Security and Error Handling Enhancement

Task: Add security practices and exception handling to the code.

```
# buggy_code_task4.py
```

```
import sqlite3
```

```
def get_user_data(user_id):
```

```
    conn = sqlite3.connect("users.db")
```

```
    cursor = conn.cursor()
```

```
    query = f"SELECT * FROM users WHERE id = {user_id};" #
```

Potential SQL injection risk

```
    cursor.execute(query)
```

```
    result = cursor.fetchall()
```

```
    conn.close()
```

```
    return result
```

```
user_input = input("Enter user ID: ")
```

```
print(get_user_data(user_input))
```


Expected Output:

Safe query using parameterized SQL (? placeholders).

Try-except block for database errors.

Input validation before query execution.

Prompt: Add security practices and exception handling to the code.

```
import sqlite3
```

```
def get_user_data(user_id):
```

```
    conn = sqlite3.connect("users.db")
```

```
    cursor = conn.cursor()
```

```
    query = f"SELECT * FROM users WHERE id = {user_id};" #
```

Potential SQL injection risk

```
    cursor.execute(query)
```

```
    result = cursor.fetchall()
```

```
    conn.close()
```


```
    return result
```

```
user_input = input("Enter user ID: ")
```

```
print(get_user_data(user_input)).
```

Safe query using parameterized SQL (? placeholders). Try-except block for database errors. Input validation before query execution.

Code:



```
10 Lab > task1.py > get_user_data
1 import sqlite3
2 def setup_database():
3     """
4     Create the 'users' table and insert sample data if it doesn't already exist.
5     """
6     try:
7         # Connect to the database
8         conn = sqlite3.connect("users.db")
9         cursor = conn.cursor()
10        # Create the 'users' table
11        cursor.execute("""
12        CREATE TABLE IF NOT EXISTS users (
13            id INTEGER PRIMARY KEY,
14            name TEXT NOT NULL,
15            email TEXT NOT NULL
16        );
17        """)
18        # Insert sample data
19        cursor.execute("INSERT OR IGNORE INTO users (id, name, email) VALUES (1, 'John Doe', 'john.doe@example.com')")
20        cursor.execute("INSERT OR IGNORE INTO users (id, name, email) VALUES (2, 'Jane Smith', 'jane.smith@example.com')")
21        # Commit changes and close the connection
22        conn.commit()
23        conn.close()
24        print("Database setup complete.")
25    except sqlite3.Error as e:
26        print(f"Database error: {e}")
27    except Exception as e:
28        print(f"An error occurred: {e}")
29
30 def get_user_data(user_id: int):
31     """
32     Retrieve user data from the database for a given user ID.
33
34     Args:
35         user_id (int): The ID of the user to retrieve data for.
36
37     Returns:
38         list: A list of user data rows, or an error message if an exception occurs.
39     """
```

to enter a user ID and validates the input to ensure it is a positive integer.

4. Error Handling:

- Handles database errors (sqlite3.Error) and invalid input (ValueError).

Example Input/Output:

Input:

Enter User ID: 1

Output:


Database setup complete. User data: [(1, 'John Doe', 'john.doe@example.com')]

Input:


Enter user ID: abc

Output:

Invalid input. User ID must be a positive integer.



OP:



Observation:

This Python script is designed to manage a simple SQLite database for user data. It includes two main functions: `setup_database` and `get_user_data`. The `setup_database` function ensures that the database (users.db) is properly initialized. It creates a `users` table if it doesn't already exist and inserts sample data for testing purposes. This function uses the `CREATE TABLE IF NOT EXISTS` SQL statement to avoid duplicate table creation and the `INSERT OR IGNORE` statement to prevent duplicate entries. The `get_user_data` function retrieves user data for a given user ID using parameterized SQL queries (`?`).

placeholders) to prevent SQL injection attacks. It connects to the database, executes the query, fetches the results, and closes the connection. The script also includes robust error handling to manage database-related errors (`sqlite3.Error`) and unexpected exceptions. In the `if __name__ == "__main__":` block, the script first sets up the database and then prompts the user to enter a user ID. The input is validated to ensure it is a positive integer, and if valid, the `get_user_data` function is called to fetch and display the user data. If the user ID is invalid or no data is found, appropriate error messages are displayed. This script demonstrates best practices for database management, including input validation, parameterized queries, and proper resource handling.

Task-5:

Automated Code Review Report Generation

Task: Generate a review report for this messy code.

```
# buggy_code_task5.py
```

```
def calc(x,y,z):
```

```
    if z=="add":
```

```
        return x+y
```

```
    elif z=="sub": return x-y
```

```
    elif z=="mul":
```

```
        return x*y
```

```
elif z=="div":
```

```
    return x/y
```

```
else: print("wrong")
```

```
print(calc(10,5,"add"))
```

```
print(calc(10,0,"div"))
```

Expected Output:

AI-generated review report should mention:

- o Missing docstrings
- o Inconsistent formatting (indentation, inline return)
- o Missing error handling for division by zero
- o Non-descriptive function/variable names
- o Suggestions for readability and PEP 8 compliance

Prompt: Generate a review report for this messy code.

```
def calc(x,y,z):
```

```
    if z=="add":
```

```
return x+y

elif z=="sub": return x-y

elif z=="mul":

return x*y

elif z=="div":

return x/y


else: print("wrong")

print(calc(10,5,"add"))


print(calc(10,0,"div"))
```

include: Missing docstrings. Inconsistent formatting (indentation, inline return). Missing error handling for division by zero. Non-descriptive function/variable names. Suggestions for readability and PEP 8 compliance

Code:



OP:



Observation: A detailed Google-style docstring was added to describe the function's purpose, parameters, return values, and exceptions. Indentation and formatting were made consistent. Removed inline returns for better readability. Added a check for division by zero and raised a ZeroDivisionError with a clear message. Renamed calc to calculate_operation and variables x, y, and z to num1, num2, and operation. Added spaces around operators and blank lines where necessary