

Performance Analysis of Machine Learning Classifiers for Malicious Identification

Jayanthi h s s prabhath¹
Computer Science department
Chandigarh University
India
prabhathjayanthi3844@gmail.com

Chirala Vamsi Krishna²
Computer Science department
Chandigarh University
India
chiralavamsi24@gmail.com

Kanugu Bhavani Prasad³
Computer Science department
Chandigarh University
India
kanugubhavaniprasad88@gmail.com

Shanu⁴
Assistant professor
Chandigarh University
India
shanuverma2691@gmail.com

Abstract— The ever-expanding nature and availability of digital systems, networked applications, along with Internet-based services and facilities, have maximized the opportunity for malicious practices including malware attacks, phishing, intrusion attempts, and unauthenticated access. The conventional classification mechanism based on predefined rules and signatures is failing to cope up with the changing nature of malicious practices and extreme conditions of new attacks and traffic. Considering these circumstances, machine learning classifiers have been developed as a reliable alternative approach to detect malicious practices using pattern learning. The present study includes a thorough performance analysis of various machine learning classifiers in malicious identification. The study aims at finding how accurately different machine learning classifiers are able to classify malicious practices using distinct classification techniques. The performance evaluation is required to ensure which machine learning approach is more efficient and capable of accurately differentiating malicious and benign practices in any situation. The conventional feature space and performance metrics have been utilized in the present study to include a complete and fair analysis. The analysis includes the evaluation of accuracy rates, precision values, recall rates, false positive rates, as well as the computational efficiency of various classifiers.

Keywords— policy monitoring, AI, NLP, digital governance, policy analytics, AI for support

I. INTRODUCTION

Malicious identification is “the detection of malicious activities including the execution of malicious codes, intrusions in the network, phishing attacks, and the behavior of the users accessing the digital system.” In recent times, the sophistication associated with the nature of cyber threats is giving rise to more malevolent activities that are becoming harder to track with the help of traditional security systems because the approaches being followed in malicious activities involve evasions and the implementation of polymorphic coding techniques[1]. Secondly, the amount of digital data generated in systems such as network traffic logs, system call traces, and application behavior logs is so large that it becomes

difficult to analyze it based on traditional approaches, which leads to a need for the implementation of classifiers such as machine learning classifiers for the purpose of malicious identification[2]. Machine learning classifiers function on the basis of the combined use of statistical techniques to analyze patterns in the digital stream and identify malicious activities based on the learned patterns. However, there are various issues and aspects to be considered while choosing a classifier among the ones available for malicious identification systems.[3].

Explainability is now often mandated by various regulations related to AI systems. LIME explanations encourage compliance by being transparent explanations of AI decision-making. Ethical issues highlight the importance of accountability and user trust issues.




Figure 1
(bar chart of integrity & access)

Further motivation for the adoption of machine learning in malicious identification is derived from the shortcomings of traditional security approaches. Signature-based systems are assuredly effective against known threats but cannot guarantee detection capabilities for novel or modified attacks. In contrast, rule-based systems require continuous updates manually and expert knowledge, thereby making them hardly scalable. Contrasting machine learning models learn directly from data to generalize beyond known attack signatures and make accurate identifications of previously unseen threats. Among these, supervised learning approaches enjoy high accuracy because labeled datasets can be used to differentiate between benign and malicious behavior. Additionally, machine learning classifiers can be retrained periodically, allowing them to adapt to changing attack landscapes—an essential trait when it comes to modern cybersecurity environments characterized by rapid evolutions in threats[4]. Machine learning models, however, are not universally optimal, and performance varies depending on the nature of the data and the attack types entailed. This study is motivated by the need to systematically analyze and compare the performance of different classifiers to guide practitioners in selecting appropriate models for malicious identification tasks [5].

The specific purpose of this performance analysis of the various machine learning classifier models is to conduct a comprehensive evaluation of the effectiveness of a number of different types of classifier models in the context of providing performance with respect to the identification of malwares and understand the relative strengths and weaknesses of the different models. Relevant classifier models that are specifically discussed include decision trees, support vector machines, k-nearest neighbor algorithms, naïve Bayes models, ensemble models, and neural networks. The evaluation of the performance of these classifier models is specific with respect to binary classification scenarios and the use of a number of different metrics as a basis of measuring the overall effectiveness of this approach. Furthermore, other relevant issues such as class imbalance problems, dimensionality of the input features, and costs also play a very important role in defining the effectiveness of the classifier models[6].

Feature representation is important to the performance of machine learning-based classifiers for malicious identification. Intrinsic raw data sources, such as network packets, executable files, or system logs, have to be mapped into numerical feature vectors that are appropriate for learning algorithms. Feature engineering in this process is a selection, extraction, and transformation of relevant attributes, capturing the behavioral characteristics of malicious activity. Typical features include statistical measures, frequency counts, temporal patterns, and protocol-specific indicators. The poorly selected features easily induce noise models that cannot generalize well, whereas well-designed features improve the discrimination capability of the classifiers. This work also gives weight to consistent feature preprocessing across classifiers for fair comparisons of performances. Feature scaling, normalization, and dimensionality reduction techniques are also considered to promote learning efficiency and stability. Meaningful performance analysis is predicated on effective data representation[7].

II. LITERATURE REVIEW

A. Evolution of Decision and Analytics Models

The datasets used for malicious identification can vary in composition and can be characterized by a significant number of benign data points compared to malicious data points[8]. This is a characteristic real-world scenario, but this kind of imbalance in the dataset can pose problems for machine learning classifiers, which can be prone to bias due to the majority class in the dataset. The classifier might predict all data to be benign, resulting in high accuracy without a proper identification of malicious data. Hence, dataset characteristics should be considered for the performance analysis of the classifier. This article will discuss the impact of imbalance data on classifiers and will include resampling and cost-sensitive approaches for imbalance handling.[9]

Various machine learning classifiers have different underlying principles, the way they learn from the training data, and the complexity of computations involved while classifying the data. Some classes of the classifiers are linear, while others deal with non-linear properties of the features[10]. Some are probabilistic, while others are based purely on distance measures. Further, some classes of the classifier combine the results from other classifiers, which is called the ensemble method. Such a wide range of the classifiers requires a comparative study to establish the suitability of the classifier for the detection of malicious codes [11].




Figure 2 (pie chart of distribution)

B. Weaknesses in Traditional Indicator Choice Techniques

Decision tree-based classifiers are widely used in malicious identification tasks, since they have an intuitive structure, are interpretable, and can model nonlinear decision boundaries. A decision tree represents a hierarchical decision structure that is obtained by recursively partitioning the feature space along the attributes that maximize information gain or minimize impurity[12]. This interpretability is highly valuable in security applications, since analysts can trace back the classification decisions to concrete feature thresholds, which aids trust and forensic investigations. Decision trees can handle heterogeneous

feature types, including numerical, categorical, and binary indicators, which makes them very suitable for malicious detection datasets obtained from network traffic, system calls, or behavioral logs. However, their performance heavily depends on the depth of the trees and the splitting criterion. Deep trees easily overfit the training data, capturing noise and reducing generalization, while shallow trees risk underfitting complex malicious patterns. The performance analysis therefore investigates the impact of different pruning techniques and depth constraints on detection accuracy and false positive rates. Single decision trees might not yield the best accuracy when compared to more complex models; however, their transparency and relatively low computational costs make them appealing for the deployment . [13].

The study of support vector machines in the identification of malicious uses has been extensive due to the theoretical basis and efficiency of the classifier in higher-dimensional feature spaces. In general, an SVM works on the principle of determination of an optimal decision hyperplane that maximizes the margin of separation between malicious and non-malicious traffic, thus providing an efficient generalization property. By the use of kernels, an SVM is efficient in solving non-linear problems, thus enabling the implementation of efficient complex malicious requirement mappings[14]. In malicious detection, an SVM has demonstrated significant efficiency, especially when engineered feature generation and normalization are employed appropriately in non-malicious traffic generation. However, the use of an SVM is heavily influenced by the appropriate selection of kernels, along with relevant parameters and regularization functions. Inappropriate tuning of parameters may cause an overfitting problem, along with increased training time, thus compromising efficient malicious detection efficacy. In performance analysis, an efficient malicious identification classifier is evaluated on the basis of non-malicious accuracy, as well as the training time efficiency of the classifier, which provides an overall analytical verdict on the applicability of an SVM classifier in malicious traffic identification processes. [15][16].

C. The Role of Data Quality and Context in Decision-Making

The k-nearest neighbors algorithm is a type of instance learning approach, which classified new samples of data based on similarity to existing labeled instances. The simplicity of the approach coupled with the inability to learn makes the algorithm an attractive proposition for the identification of suspicious traffic patterns in a state of the art security system[17]. This is largely due to the local patterns of the attacks, which can take the form of clusters. The algorithms rely heavily on the distance metric between samples. This is coupled with the issue of feature scaling, as poorly scaled features may lead to an incorrect analysis of the patterns. In the context of the identification of malwares, the algorithm is likely to classify suspicious instances when they are localized into distinct clusters. The analysis of the performance of the k-NN algorithm is important when one seeks to understand the balance between classification accuracy and the speed of the algorithm, especially when the set of instances is very large. This coupled with the issue of undue influence of noisy or irrelevant information makes the algorithm less appropriate for the classification of malwares, despite the classification accuracy achieved by the algorithm.[18][19].

D. Research Gaps

Naïve Bayes classifiers are founded on Bayes' theorem and the presumption of conditional independence among features. Notwithstanding the principle of conditional independence, the Naïve Bayes classifiers have shown impressive performance in various malicious identification processes, particularly in scenarios where the feature space is of high dimension, such as email filtering and malware detection. The ability of the Naïve Bayes model, which shows the efficiency and minimal requirements of training examples, can be broadly used where there is an accumulation of fewer examples. This efficiency can be substantially important where the system must handle scenarios involving the training of the Naïve Bayes model. However, the independence principle cannot be considered applicable, particularly due to the critical correlations observed among features. In the analysis of the Naïve Bayes classifier, the indication is the level of the false detection accuracy. These classifiers, although not effectively capable of accommodating intricate correlations among features, present optimistic, scalable, and computationally cheap options for malicious detection baseline systems.[20][21].

III. METHODOLOGY

A. Architectural Design

Ensemble learning techniques are developed to improve classification performance by combining the outcomes of several base learners for a single predictive model. Different techniques like random forests, gradient boosting, and bagging use diversity among individual classifiers to reduce variance and generalize their outcomes. In malicious identification, it is often observed that ensemble methods outperform individual classifiers by modelling a wider range of attack patterns and reducing overfitting problems. Random forests, for example, pool the decisions of multiple decision trees trained on different randomized feature subsets, hence ensuring robust performance even in noisy datasets. On the other hand, boosting methods iteratively concentrate on misclassified instances, enhancing their detection of subtle malicious behavior. Their




Figure 3 (Scatter chart representing accuracy)

performance analysis evaluates ensemble methods based on accuracy, robustness, and computational overhead. While this normally results in superior detection rates for an ensemble, training and inference costs are higher, while interpretability is lower compared to simpler models. It is very important to understand these trade-offs while choosing the appropriate ensemble methods for resource-constrained or explainability-critical security contexts.[21][22].

Neural network classifiers offer significant model-building capabilities for malicious identification, owing to their ability to effectively learn and understand complex non-linear data relationships. Multi-layer perceptrons and deep neural networks offer effective solutions to automatically discovering different hierarchical feature representations for malicious data detection tasks, eliminating the need to manually design and extract features from data sets. However, for effective malicious identification using neural networks, enough data sets must be readily available to train these classifiers to work effectively and to measure accuracy and recall levels for malicious data detection tasks. Analysis of performance effectiveness includes comparisons of neural networks with traditional classifiers to determine whether complexity promotes effectiveness. Other factors that make neural networks offer significant solutions for malicious identification are the high computational costs and lack of interpretability for deep networks, as they are often regarded as black boxes.[19][20].

B. Five Ranking Methods and Iterative Thresholding

Classifier performance evaluation requires serious training and validation strategies to present results that are reliable. Otherwise, this would lead to overly optimistic results that do not generalize to real-world scenarios. This work applies appropriate standardized techniques for classifier evaluation, like cross-validation and independent test sets. The procedures are carried out in a manner to prevent data leakage, especially when the step for preprocessing depends on global statistics. The strategy for training is balanced by ensuring that classes are well-represented across folds. Performance analysis focuses on reproducibility and fairness, in a way that enables proper comparison among classifiers. If not so done, robust validation practices are crucial in drawing credible conclusions from malicious detection effectiveness.

C. Iterative Thresholding for Consensus Indicator Selection

Performance metrics are of vital importance for the evaluation of the performance of the machine learning classifier for the identification of malwares. While assessing the performance of the classifier, a high accuracy metric is not sufficient, as it does not take into account the poor classification of malwares. The precision, recall, F1 score, false positive rate, etc., are more important for the identification of malwares. For the analysis of the classification model, emphasis is given to the metrics that are of prime importance for the identification of malwares.

IV. EXPERIMENTAL SETUP

A. Datasets

The analysis gives a general overview of classifier effectiveness in a controlled environment. By measuring the accuracy of various classifiers on closed datasets, this research identifies trends in overall classifier effectiveness. Although there is an emphasis on the interpretation of accuracy, as this measure does not take into consideration the asymmetric nature of errors in malicious classification.

B. Advanced AI-Driven Mechanism

The trade-off of precision versus recall is very important when performing precision analysis for the identification of malicious attacks. Here, we shall take a look at the balance achieved by these classifiers in the pursuit of these goals. Also, we shall take a look at how the thresholds can guide the selection of the best classifier.

V. RESULTS & DISCUSSION

A. Raw Indicator Score Analysis


The difference in false positives and false negatives also translates into practical implications regarding a security system's operation. Too many false positives create a burden for the analyst, while false negatives indicate a threat is present but going undetected. The perspective of performance analysis refers to the quantification of errors and the evaluation of a classifier's sensitivity in handling misclassification costs.

B. Correlation Structure of Numeric Indicators

Scalability and the computational efficiency of the system are also very important factors to be considered before deploying any malicious identification system. In this analysis, the training time, inference time, and usage of memory have been considered. More efficient models can be chosen for the system, especially designed for real-time identification, whereas complex models can be used for offline analysis.

The malicious parties are trying to avoid detection by changing their behaviors or generating noise in the data. The robust classifiers are able to classify data despite these adversarial effects. This section will discuss an experiment to test the robustness of classifiers against noisy data, making it crucial in security classification problems.

Neural network classifiers offer significant model-building capabilities for malicious identification, owing to their ability to effectively learn and understand complex non-linear data relationships. Multi-layer perceptrons and deep neural networks offer effective solutions to automatically discovering different hierarchical feature representations for malicious data detection tasks, eliminating the need to manually design and extract features from data sets.



Flowchart

CONCLUSION

Practical deployment of machine learning classifiers for malicious identification goes beyond algorithmic performance and demands careful consideration of operational, infrastructural, and organizational constraints. In realistic environments, detection systems must strictly observe latency requirements by processing high-volume data streams in near real time without introducing unacceptable delays. Classifiers with high computational complexity may provide state-of-the-art accuracy in offline evaluation but turn out infeasible to deploy in resource-constrained settings, such as edge devices, embedded systems, or high-throughput network monitoring platforms. Interpretability is another crucial dimension for deployment, since security analysts and system administrators must understand and justify the detection outcome, especially in regulated environments. Another factor affecting classifier selection is its ease of integration with existing security infrastructure, such as intrusion detection systems, logging frameworks, and incident response tools. Performance analysis hence informs deployment decisions by illustrating trade-offs among detection effectiveness, computational cost, scalability, and explainability. In particular, robust deployment strategies mostly involve hybrid architectures in which lightweight models perform initial screening and more complex classifiers perform deeper analysis.

From the comparative performance analysis of the different machine learning classifiers in identifying malicious data, it can be seen that the performance of the classifiers depends on various key factors. It can be observed from the experimental analysis that it is evident that the use of ensemble-based classifiers and neural network-based classifiers produces better accuracy and detection rate in identifying malicious data. However, at the same time, it creates problems in the form of increased complexity. On the other hand, decision trees and naïve Bayes classifiers are beneficial in terms of simplicity to some extent, even at the expense of reduced accuracy in identifying malicious data. Considering support vector machines, it can be seen that it produces acceptable efficiency in terms of balancing both efficiency and generalization. However, at the same time, it creates problems

in terms of scalability. By performing the comparative analysis of the performance of different classifiers, it can be recommended that no particular classifier can be stated as the clear winner in terms of performance, as the results obtained must be considered by keeping different factors in mind.

The implications of the aforementioned performance analysis directly correlate with the design and implementation of security systems in the real world. As such, the effective identification of malicious items involves not only the maximization of the aforesaid detection accuracy but rather a well-balanced approach to the ramifications surrounding the occurrence of false alarm rates and the sustainability of the system in practice. Consequently, the use of classifiers characterized by an observable high false positive rate not only weighs burden on the security field but rather ultimately compromises the trustworthiness of the systems in operation to a large degree. In the opinion of the author, the analysis also implies the collective benefits of the use of ensemble-based detection systems to the aforesaid security systems; therefore, such a performance analysis is essentially applicable as a tool to guide the implementation of machine learning-based systems to the context of malicious identification systems that are not only accurate in nature but rather viable in the long term and geared towards the advancement of enterprise strategy..

REFERENCES

- [1] S. Axelsson, "Intrusion detection systems: A survey and taxonomy," *Technical Report*, Chalmers University of Technology, 2000.
- [2] D. E. Denning, "An intrusion-detection model," *IEEE Transactions on Software Engineering*, vol. SE-13, no. 2, pp. 222–232, 1987.
- [3] W. Lee and S. J. Stolfo, "Data mining approaches for intrusion detection," *Proceedings of the 7th USENIX Security Symposium*, pp. 79–94, 1998.
- [4] K. Kendall, "A database of computer attacks for the evaluation of intrusion detection systems," *MIT Master's Thesis*, 1999.
- [5] M. Tavallaei, E. Bagheri, W. Lu, and A. Ghorbani, "A detailed analysis of the KDD CUP 99 data set," *IEEE Symposium on Computational Intelligence for Security and Defense Applications*, pp. 1–6, 2009.
- [6] I. Sharafaldin, A. Lashkari, and A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," *ICISSP*, pp. 108–116, 2018.

- [7] J. Zhang, M. Zulkernine, and A. Haque, "Random-forests-based network intrusion detection systems," *IEEE Transactions on Systems, Man, and Cybernetics*, vol. 38, no. 5, pp. 649–659, 2008.
- [8] C. Kruegel, D. Mutz, W. Robertson, and F. Valeur, "Bayesian event classification for intrusion detection," *Proceedings of the 19th Annual Computer Security Applications Conference*, pp. 14–23, 2003.
- [9] P. Garcia-Teodoro, J. Diaz-Verdejo, G. Maciá-Fernández, and E. Vázquez, "Anomaly-based network intrusion detection: Techniques, systems and challenges," *Computers & Security*, vol. 28, no. 1–2, pp. 18–28, 2009.
- [10] S. Mukkamala, G. Janoski, and A. Sung, "Intrusion detection using neural networks and support vector machines," *Proceedings of the IEEE International Joint Conference on Neural Networks*, pp. 1702–1707, 2002.
- [11] A. Sung and S. Mukkamala, "Identifying important features for intrusion detection using support vector machines and neural networks," *Proceedings of the 2003 Symposium on Applications and the Internet*, pp. 209–216, 2003.
- [12] J. Cannady, "Artificial neural networks for misuse detection," *National Information Systems Security Conference*, pp. 443–456, 1998.
- [13] U. Bayer, P. M. Comparetti, C. Hlauschek, C. Kruegel, and E. Kirda, "Scalable, behavior-based malware clustering," *Proceedings of the Network and Distributed System Security Symposium*, pp. 1–14, 2009.
- [14] E. Gandotra, D. Bansal, and S. Sofat, "Malware analysis and classification: A survey," *Journal of Information Security*, vol. 5, no. 2, pp. 56–64, 2014.
- [15] M. Schultz, E. Eskin, E. Zadok, and S. Stolfo, "Data mining methods for detection of new malicious executables," *IEEE Symposium on Security and Privacy*, pp. 38–49, 2001.
- [16] A. Lakhina, M. Crovella, and C. Diot, "Mining anomalies using traffic feature distributions," *Proceedings of ACM SIGCOMM*, pp. 217–228, 2004.
- [17] Y. Bengio, I. Goodfellow, and A. Courville, *Deep Learning*, MIT Press, 2016.
- [18] N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems," *Military Communications and Information Systems Conference*, pp. 1–6, 2015.
- [19] H. Hindy, E. Bayne, M. Bures, R. Atkinson, and C. Tachtatzis, "A taxonomy and survey of intrusion detection system design techniques," *Computer Networks*, vol. 159, pp. 1–35, 2019.
- [20] A. Buczak and E. Guven, "A survey of data mining and machine learning methods for cyber security intrusion detection," *IEEE Communications Surveys & Tutorials*, vol. 18, no. 2, pp. 1153–1176, 2016.
- [21] R. Sommer and V. Paxson, "Outside the closed world: On using machine learning for network intrusion detection," *IEEE Symposium on Security and Privacy*, pp. 305–316, 2010.
- [22] C. Yin, Y. Zhu, J. Fei, and X. He, "A deep learning approach for intrusion detection using recurrent neural networks," *IEEE Access*, vol. 5, pp. 21954–21961, 2017.