

Architetture dei Sistemi di Elaborazione O2GOLOV	Delivery date: 23 November 2023
Laboratory 5	Expected delivery of lab_5.zip must include: This file in pdf format.

Exercise 1:

Software Optimizations

Starting from Exercise 2 of Lab 4, you are required to further speedup the benchmark (*my_c_benchmark*) ☺.

For readability, provide the previously used configurations (Cut & Paste).

Parameters	Configuration 1	Configuration 2	Configuration 4	Configuration 5
First changed parameter	Fetch buffer size =64	Decode width= 8	Fetch width =2	Int alu =6
Second changed parameter	Fetch queuesize= 64	Robeentries = 32	Rename Iqentries =6	Int muldiv =6
Third changed parameter	Rename Iqentries =6	DispatchWidth=4	DispatchWidt h=4	Fp alu =6
Forth changed parameter	Rename width= 4			Fp mul div =6

Original CPI (no hardware optimization):

	Configuration 1	Configuration 2	Configuration 4	Configuration 5
CPI	1.411405	1.983529	1.401	2.083105
Speedup (w.r.t. the Original CPI)	1.476	1.05	1.487	1

Despite the hardware enhancements for increasing the CPU performance, remember that optimizing compilers for programs in high-level code also exist. The aim of optimizing compilers is to minimize or maximize some attributes of an executable computer program (code size, performance, etc.). They are also aware of hardware enhancements to perform very accurate optimizations.

Compilers can be your best friend (or worst enemy!). The more information you provide in your program, the better the optimized program will be.

You can compile your programs with different SW optimization strategies and/or additional features. In the *setup_default* file:

```
ase_riscv_gem5_sim > $ setup_default
>
6 ##### CROSS COMPILER RISCV #####
7 #####
8 #####
9 export CC="/mnt/d/gem5_simulator/riscv_toolchain/bin/riscv64-unknown-elf-gcc"
10 export CC_INSTALLATION_PATH="/mnt/d/gem5_simulator/riscv_toolchain/"
11 ## optimization flags for the compiler
12 export OPTIMIZATION_FLAGS="-O0"
13
```

You can change the line 12.

Simulate the program for different optimization levels and collect statistics. You are required to change the OPTIMIZATION_FLAGS variable in the *setup_default*. O0 is the default value, you need to change the optimization value accordingly to the values in parenthesis in the following Table.

DO NOT CONFUSE -O3 WITH O3 PROCESSOR.

TABLE1: IPC for different compiler optimization levels and configurations

Optimization \ Configuration	Opt lvl 0 (-O0)	Opt lvl 1 (-O1)	Opt lvl 2 (-O2)	Opt size (-Os)	Opt lvl 3 (-O3)	Opt lvl 2 (-O2 -- fast-math)
Original Configuration	0.480053	0.396446	0.443626	0.415027	0.443626	0.458622
Configuration 1	0.690089	0.698714	0.697473	0.666775	0.697473	0.698427
Configuration 2	0.495579	0.442223	0.472293	0.454492	0.472293	0.474487
Configuration 3	0.697355	0.695496	0.679530	0.652294	0.679530	0.699144
Configuration 4	0.472914	0.423587	0.436623	0.419600	0.436623	0.456496
Program Size [Bytes]	3228	3044	3032	3016	3032	3032

Regarding the Program Size (Code and Data!!), you can retrieve the size from:

```
~/ase_riscv_gem5_sim$ /opt/riscv-2023.10.18/bin/riscv64-unknown-elf-size --format=gnu --radix=10 ./programs/my_c_benchmark/my_c_benchmark.elf
```

For brave and curious guys:

For visualize the enabled optimizations from the compiler perspective, you can run:

```
~/my_gem5Dir$ /opt/riscv-2023.10.18/bin/riscv64-unknown-elf-gcc -Q -O2 --help=optimizers
```

By changing the “-O2” parameter with the desired one, you will find the enabled/disabled optimizations.

Here are some possible types of optimizations:

- https://en.wikipedia.org/wiki/Optimizing_compiler
- <https://gcc.gnu.org/onlinedocs/gcc/Optimize-Options.html>


Exercise 2:

Given your benchmark (`my_c_benchmark.o`), select the best optimization to obtain **your best angle of optimization**, compared to the baseline configuration (`riscv_o3_custom.py; -O0`).

1. Based on Table 1 (from Exercise 1), select the best optimization (for example, the green box corresponding to Configuration 1 with `-O2`).

Optimization Configuration	Opt lvl 0 (-O0)	Opt lvl 1 (-O1)	Opt lvl 2 (-O2)	Opt size (-Os)	Opt lvl 3 (-O3)	Opt lvl 2 (-O2 --fast- math)
Original Configuration		0.396446				
Configuration 1						
Configuration 2						
Configuration 3	0.697355					
Configuration 4						
Configuration 5						
Program Size [Bytes]						

2. By using **Konata**, overlap the two pipelines (the original obtained with `riscv_o3_custom.py` and the optimized corresponding to the best SW-HW combination) to compute your angle of optimization.




Compute the angle α (named optimization angle) existing between the traces.

Hint: To load different traces in **Konata**, load them separately. Afterward, right-click in the pipeline visualizer and select “transparent mode”. You need to adjust the scale!

3. To compute the **angle of optimization** α :

$$\alpha = \arctan\left(\frac{\text{ClockCycles}_{\text{baseline}}}{\text{Instructions}_{\text{baseline}}}\right) - \arctan\left(\frac{\text{ClockCycles}_{\text{optimized}}}{\text{Instructions}_{\text{optimized}}}\right)$$



The angle of optimization is equal to: 9,51

4. Do you see any visual improvements (for example, a less discontinued pipeline)? Yes, why?
No, why? What is happening? How they could be improved?

Le discontinuità sono dovuti alla branch misprediction ma il questo caso esse non cambiano in meglio, il principale miglioramento è dovuto alla minore presenza di stalli orizzontali dovuti all'ottimizzazione dei valori della pipeline