

Analysis of Available Data

Load the corpora

```
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.4      v readr      2.1.5
## v forcats    1.0.0      v stringr   1.5.1
## v ggplot2    3.5.1      v tibble    3.2.1
## v lubridate  1.9.3      v tidyr     1.3.1
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(tidymodels)
```

```
## -- Attaching packages ----- tidymodels 1.2.0 --
## v broom       1.0.5      v rsample    1.2.1
## v dials       1.3.0      v tune       1.2.1
## v infer       1.0.7      v workflows  1.1.4
## v modeldata   1.4.0      v workflowsets 1.1.0
## v parsnip     1.2.1      v yardstick  1.3.2
## v recipes     1.1.0
## -- Conflicts ----- tidymodels_conflicts() --
## x scales::discard() masks purrr::discard()
## x dplyr::filter()   masks stats::filter()
## x recipes::fixed() masks stringr::fixed()
## x dplyr::lag()      masks stats::lag()
## x yardstick::spec() masks readr::spec()
## x recipes::step()   masks stats::step()
## * Search for functions across packages at https://www.tidymodels.org/find/
```

```
library(jsonlite)
```

```
##
## Attaching package: 'jsonlite'
##
## The following object is masked from 'package:purrr':
##
##     flatten
```

```
set.seed(42)
```

```
load_kuk_subcorpus_metadata <- function(crp) {
  read_tsv(paste(c(
    "../corpora/KUK_1.0/metadata/", crp, "_DocumentFileFormat.tsv"
  )), collapse = "")) %>%
```

```

    filter(FileFormat == "TXT") %>%
    full_join(
      read_tsv(paste(c(
        "../corpora/KUK_1.0/metadata/",
        crp,
        "_DocumentIdentificationGenreProperties.tsv"
      )), collapse = ""),
      by = "KUK_ID"
    ) %>%
    mutate(across(where(is.numeric), as.character)) %>%
    mutate(subcorpus = crp) %>%
    select(KUK_ID, FileName, FileFormat, FolderPath, subcorpus, everything())
  }

kuky_orig <- fromJSON("../corpora/KUKY/argumentative.json")$documents %>%
  as_tibble() %>%
  bind_rows(
    fromJSON("../corpora/KUKY/normative.json")$documents %>% as_tibble()
  ) %>%
  rename(KUK_ID = doc_id) %>%
  select(!c(plainText, doc_name)) %>%
  select(KUK_ID, everything())

kuky_kuk <- load_kuk_subcorpus_metadata("KUKY") %>%
  filter(FolderPath == "data/KUKY/TXT")

## Rows: 448 Columns: 4
## -- Column specification -----
## Delimiter: "\t"
## chr (4): KUK_ID, FileName, FileFormat, FolderPath
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
## Rows: 224 Columns: 12
## -- Column specification -----
## Delimiter: "\t"
## chr (8): KUK_ID, SourceDB, Anonymized, RecipientType, RecipientIndividuation...
## lgl (4): SourceID, DocumentTitle, ClarityPursuit, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
kuky <- kuky_kuk %>% full_join(kuky_orig, by = "KUK_ID")
czcdc <- load_kuk_subcorpus_metadata("CzCDC")

## Rows: 237723 Columns: 4
## -- Column specification -----
## Delimiter: "\t"
## chr (4): KUK_ID, FileName, FileFormat, FolderPath
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
## Rows: 237723 Columns: 12
## -- Column specification -----

```

```

## Delimiter: "\t"
## chr (10): KUK_ID, SourceDB, SourceID, DocumentTitle, Anonymized, RecipientTy...
## lgl (2): ClarityPursuit, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
eso <- load_kuk_subcorpus_metadata("ES0")

## Rows: 11230 Columns: 4
## -- Column specification -----
## Delimiter: "\t"
## chr (3): KUK_ID, FileFormat, FolderPath
## dbl (1): FileName
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
## Rows: 5615 Columns: 12
## -- Column specification -----
## Delimiter: "\t"
## chr (10): KUK_ID, SourceDB, SourceID, DocumentTitle, Anonymized, RecipientTy...
## lgl (2): ClarityPursuit, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
frbo <- load_kuk_subcorpus_metadata("FrBo")

## Rows: 638 Columns: 4
## -- Column specification -----
## Delimiter: "\t"
## chr (4): KUK_ID, FileName, FileFormat, FolderPath
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
## Rows: 319 Columns: 12
## -- Column specification -----
## Delimiter: "\t"
## chr (10): KUK_ID, SourceDB, SourceID, DocumentTitle, Anonymized, RecipientTy...
## lgl (2): ClarityPursuit, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
lifrlaw <- load_kuk_subcorpus_metadata("LiFRLaw")

## Rows: 36 Columns: 4
## -- Column specification -----
## Delimiter: "\t"
## chr (4): KUK_ID, FileName, FileFormat, FolderPath
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
## Rows: 18 Columns: 11
## -- Column specification -----
## Delimiter: "\t"

```

```
## chr (9): KUK_ID, SourceDB, SourceID, DocumentTitle, Anonymized, Recipient Ty...
## lgl (2): ClarityPursuit, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
ombuflayers <- load_kuk_subcorpus_metadata("OmbuFlyers")
```

```
## Rows: 234 Columns: 4
## -- Column specification -----
## Delimiter: "\t"
## chr (4): KUK_ID, FileName, FileFormat, FolderPath
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
## Rows: 117 Columns: 12
## -- Column specification -----
## Delimiter: "\t"
## chr (8): KUK_ID, DocumentTitle, Anonymized, RecipientType, RecipientIndividu...
## lgl (4): SourceDB, SourceID, ClarityPursuit, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
df <- bind_rows(kuky, czcdc) %>%
  bind_rows(eso) %>%
  bind_rows(frbo) %>%
  bind_rows(lifrlaw) %>%
  bind_rows(ombuflayers)
```

```
str(df)
```

```
## tibble [244,016 x 35] (S3: tbl_df/tbl/data.frame)
## $ KUK_ID : chr [1:244016] "671918e2c6537d54ff0626db" "671918e2c6537d54ff0626dc" "6...
## $ FileName : chr [1:244016] "orig_Certifikáty autorizovaných inspektorů" "red_Co je ...
## $ FileFormat : chr [1:244016] "TXT" "TXT" "TXT" "TXT" ...
## $ FolderPath : chr [1:244016] "data/KUKY/TXT" "data/KUKY/TXT" "data/KUKY/TXT" "data/KUKY/TXT" ...
## $ subcorpus : chr [1:244016] "KUKY" "KUKY" "KUKY" "KUKY" ...
## $ SourceDB : chr [1:244016] "SourceDB" "SourceDB" "SourceDB" "SourceDB" ...
## $ SourceID : chr [1:244016] NA NA NA NA ...
## $ DocumentTitle : chr [1:244016] NA NA NA NA ...
## $ ClarityPursuit : logi [1:244016] NA NA NA NA NA ...
## $ Anonymized.x : chr [1:244016] "No" "No" "No" "No" ...
## $ RecipientType.x : chr [1:244016] "natural person" "natural person" "natural person" "natu...
## $ RecipientIndividuation.x : chr [1:244016] "public" "public" "public" "public" ...
## $ AuthorType.x : chr [1:244016] "individual" "individual" "individual" "authority" ...
## $ Objectivity.x : chr [1:244016] "quasiobjective" "quasiobjective" "quasiobjective" "quas...
## $ LegalActType.x : chr [1:244016] "normative" "normative" "normative" "normative" ...
## $ Bindingness.x : logi [1:244016] FALSE FALSE FALSE FALSE FALSE FALSE ...
## $ Readability : chr [1:244016] "low" "high" "low" "low" ...
## $ SyllogismBased : chr [1:244016] "false" "false" "false" "false" ...
## $ DocumentVersion : chr [1:244016] "Original" "Redesign" "Original" "Original" ...
## $ ParentDocumentID : chr [1:244016] NA NA NA NA ...
## $ LegalActType.y : chr [1:244016] "normative" "normative" "normative" "normative" ...
## $ Objectivity.y : chr [1:244016] "quasiobjective" "quasiobjective" "quasiobjective" "quas...
```

```
## $ Bindingness.y          : logi [1:244016] FALSE FALSE FALSE FALSE FALSE FALSE ...
## $ AuthorType.y          : chr [1:244016] "individual" "individual" "individual" "authority" ...
## $ RecipientType.y       : chr [1:244016] "natural person" "natural person" "natural person" "natu
## $ RecipientIndividuation.y: chr [1:244016] "public" "public" "public" "public" ...
## $ Anonymized.y          : chr [1:244016] "No" "No" "No" "No" ...
## $ Anonymized            : chr [1:244016] NA NA NA NA ...
## $ RecipientType         : chr [1:244016] NA NA NA NA ...
## $ RecipientIndividuation : chr [1:244016] NA NA NA NA ...
## $ AuthorType            : chr [1:244016] NA NA NA NA ...
## $ Objectivity           : chr [1:244016] NA NA NA NA ...
## $ LegalActType          : chr [1:244016] NA NA NA NA ...
## $ Bindingness           : logi [1:244016] NA NA NA NA NA NA ...
## $ Recipient Type        : chr [1:244016] NA NA NA NA ...
```


Properties of KUKY

```
kuky_properties_df <- fromJSON(
  "../corpora/KUKY/argumentative.json"
)$documents %>%
  as_tibble() %>%
  bind_rows(
    fromJSON("../corpora/KUKY/normative.json")$documents %>% as_tibble()
  ) %>%
  rename(KUK_ID = doc_id) %>%
  mutate(doclen = str_length(plainText))

print(kuky_properties_df %>% group_by(Readability) %>% count())
```

```
## # A tibble: 3 x 2
## # Groups:   Readability [3]
##   Readability     n
##   <chr>         <int>
## 1 high           125
## 2 low             38
## 3 medium         61
```

```
kuky_properties_df %>% ggplot(aes(x = Readability, y = doclen)) +
  geom_boxplot()
```



Quick peek into other parts of the data set:

Subcorpus	Low # of chars	High # of chars
CzCDC/ConCo	2.000	18.000
CzCDC/SupAdmCo	3.000	30.000
CzCDC/SupCo	3.000	10.000
ESO	7.000	40.000
FrBo/articles	4.000	15.000

Filter out duplicates

Some subcorpora overlap (*FrBo* with *ESO*, and multiple subcorpora with *KUKY*).

The usage of documents with `ClarityPursuit == NA` is questionable, let's exclude such documents. This effectively comes with a price of excluding the whole *ESO* subcorpus.

The usage of documents with `ClarityPursuit == TRUE` is also questionable as they're not reviewed in the same manner as the documents from *KUKY*, yet at the same time they are less likely to be as "unreadable" as the documents with `ClarityPursuit == FALSE`. Such documents could very well be readable, interfering with the training process. This effectively comes with a price of excluding the whole *FrBo/analyses* subcorpus.

After filtering `ClarityPursuit == NA` out, the only remaining overlaps are with *KUKY*. Let's keep the documents from *KUKY* as they are associated with a more careful readability evaluation.

```
df %>%
  group_by(FileName) %>%
  mutate(n = n()) %>%
```

```

filter(n > 1) %>%
select(FileName, subcorpus, Readability, ClarityPursuit) %>%
arrange(FileName) %>%
print(n = 80)

```

```

## # A tibble: 80 x 4
## # Groups:   FileName [40]
##   FileName      subcorpus Readability ClarityPursuit
##   <chr>          <chr>      <chr>      <lg1>
## 1 100          ESO        <NA>       NA
## 2 100          FrBo      <NA>      TRUE
## 3 102          ESO        <NA>       NA
## 4 102          FrBo      <NA>      TRUE
## 5 110          ESO        <NA>       NA
## 6 110          FrBo      <NA>      TRUE
## 7 14           ESO        <NA>       NA
## 8 14           FrBo      <NA>      TRUE
## 9 142          ESO        <NA>       NA
## 10 142         FrBo      <NA>      TRUE
## 11 148          ESO        <NA>       NA
## 12 148          FrBo      <NA>      TRUE
## 13 152          ESO        <NA>       NA
## 14 152          FrBo      <NA>      TRUE
## 15 154          ESO        <NA>       NA
## 16 154          FrBo      <NA>      TRUE
## 17 156          ESO        <NA>       NA
## 18 156          FrBo      <NA>      TRUE
## 19 158          ESO        <NA>       NA
## 20 158          FrBo      <NA>      TRUE
## 21 16           ESO        <NA>       NA
## 22 16           FrBo      <NA>      TRUE
## 23 170          ESO        <NA>       NA
## 24 170          FrBo      <NA>      TRUE
## 25 176          ESO        <NA>       NA
## 26 176          FrBo      <NA>      TRUE
## 27 18           ESO        <NA>       NA
## 28 18           FrBo      <NA>      TRUE
## 29 190          ESO        <NA>       NA
## 30 190          FrBo      <NA>      TRUE
## 31 200          ESO        <NA>       NA
## 32 200          FrBo      <NA>      TRUE
## 33 202          ESO        <NA>       NA
## 34 202          FrBo      <NA>      TRUE
## 35 204          ESO        <NA>       NA
## 36 204          FrBo      <NA>      TRUE
## 37 206          ESO        <NA>       NA
## 38 206          FrBo      <NA>      TRUE
## 39 208          ESO        <NA>       NA
## 40 208          FrBo      <NA>      TRUE
## 41 24           ESO        <NA>       NA
## 42 24           FrBo      <NA>      TRUE
## 43 28           ESO        <NA>       NA
## 44 28           FrBo      <NA>      TRUE
## 45 30           ESO        <NA>       NA

```

## 46 30	FrBo	<NA>	TRUE
## 47 42	ESO	<NA>	NA
## 48 42	FrBo	<NA>	TRUE
## 49 44	ESO	<NA>	NA
## 50 44	FrBo	<NA>	TRUE
## 51 54	ESO	<NA>	NA
## 52 54	FrBo	<NA>	TRUE
## 53 68	ESO	<NA>	NA
## 54 68	FrBo	<NA>	TRUE
## 55 70	ESO	<NA>	NA
## 56 70	FrBo	<NA>	TRUE
## 57 76	ESO	<NA>	NA
## 58 76	FrBo	<NA>	TRUE
## 59 Duchody	KUKY	low	NA
## 60 Duchody	OmbuFlye~	<NA>	FALSE
## 61 Odpadni-vody	KUKY	low	NA
## 62 Odpadni-vody	OmbuFlye~	<NA>	FALSE
## 63 ockovani-1_kusv	KUKY	high	NA
## 64 ockovani-1_kusv	LiFRLaw	<NA>	TRUE
## 65 ockovani-3_orig	KUKY	low	NA
## 66 ockovani-3_orig	LiFRLaw	<NA>	FALSE
## 67 orig_Certifikáty autorizovaných inspekt~	KUKY	low	NA
## 68 orig_Certifikáty autorizovaných inspekt~	FrBo	<NA>	FALSE
## 69 orig_financovani_politickych_stran	KUKY	low	NA
## 70 orig_financovani_politickych_stran	FrBo	<NA>	FALSE
## 71 red_Co je to územní plánování_final_při~	KUKY	high	NA
## 72 red_Co je to územní plánování_final_při~	FrBo	<NA>	TRUE
## 73 stavarska-1_kusv	KUKY	high	NA
## 74 stavarska-1_kusv	LiFRLaw	<NA>	TRUE
## 75 stavarska-2_orig	KUKY	low	NA
## 76 stavarska-2_orig	LiFRLaw	<NA>	FALSE
## 77 zaloba-1_orig	KUKY	medium	NA
## 78 zaloba-1_orig	LiFRLaw	<NA>	FALSE
## 79 zaloba-2_kusv	KUKY	high	NA
## 80 zaloba-2_kusv	LiFRLaw	<NA>	TRUE

```
df <- df %>%
  filter(!is.na(Readability) | !is.na(ClarityPursuit)) %>%
  filter(ClarityPursuit == FALSE | is.na(ClarityPursuit))

df <- df %>%
  group_by(FileName) %>%
  mutate(n = n()) %>%
  ungroup() %>%
  filter(n == 1 | !is.na(Readability)) %>%
  select(-n)
```

The dataset is now free of overlaps.

Prepare for ML

Classes


```
df <- df %>%
  mutate(class = if_else(Readability %in% c("high", "medium"), "good", "bad"))

readable <- df %>% filter(class == "good")
unreadable <- df %>% filter(class == "bad")

str(readable)
```

```
## tibble [186 x 36] (S3: tbl_df/tbl/data.frame)
## $ KUK_ID : chr [1:186] "671918e2c6537d54ff0626dc" "673b7a37c6537d54ff062b8d" "673b7a37c6537d54ff062b8d" ...
## $ FileName : chr [1:186] "red_Co je to územní plánování_final_přidat odkaz na manuál" "red_Co je to územní plánování_final_přidat odkaz na manuál" ...
## $ FileFormat : chr [1:186] "TXT" "TXT" "TXT" "TXT" ...
## $ FolderPath : chr [1:186] "data/KUKY/TXT" "data/KUKY/TXT" "data/KUKY/TXT" "data/KUKY/TXT" ...
## $ subcorpus : chr [1:186] "KUKY" "KUKY" "KUKY" "KUKY" ...
## $ SourceDB : chr [1:186] "SourceDB" "SourceDB" "SourceDB" "SourceDB" ...
## $ SourceID : chr [1:186] NA NA NA NA ...
## $ DocumentTitle : chr [1:186] NA NA NA NA ...
## $ ClarityPursuit : logi [1:186] NA NA NA NA NA NA ...
## $ Anonymized.x : chr [1:186] "No" "No" "No" "No" ...
## $ RecipientType.x : chr [1:186] "natural person" "natural person" "natural person" "natural person" ...
## $ RecipientIndividuation.x : chr [1:186] "public" "public" "public" "public" ...
## $ AuthorType.x : chr [1:186] "individual" "individual" "authority" "authority" ...
## $ Objectivity.x : chr [1:186] "quasiobjective" "quasiobjective" "quasiobjective" "quasiobjective" ...
## $ LegalActType.x : chr [1:186] "normative" "normative" "normative" "normative" ...
## $ Bindingness.x : logi [1:186] FALSE FALSE FALSE FALSE FALSE FALSE ...
## $ Readability : chr [1:186] "high" "high" "high" "medium" ...
## $ SyllogismBased : chr [1:186] "false" "false" "false" "false" ...
## $ DocumentVersion : chr [1:186] "Redesign" "Redesign" "Redesign" "Original" ...
## $ ParentDocumentID : chr [1:186] NA NA NA NA ...
## $ LegalActType.y : chr [1:186] "normative" "normative" "normative" "normative" ...
## $ Objectivity.y : chr [1:186] "quasiobjective" "quasiobjective" "quasiobjective" "quasiobjective" ...
## $ Bindingness.y : logi [1:186] FALSE FALSE FALSE FALSE FALSE FALSE ...
## $ AuthorType.y : chr [1:186] "individual" "individual" "authority" "authority" ...
## $ RecipientType.y : chr [1:186] "natural person" "natural person" "natural person" "natural person" ...
## $ RecipientIndividuation.y : chr [1:186] "public" "public" "public" "public" ...
## $ Anonymized.y : chr [1:186] "No" "No" "No" "No" ...
## $ Anonymized : chr [1:186] NA NA NA NA ...
## $ RecipientType : chr [1:186] NA NA NA NA ...
## $ RecipientIndividuation : chr [1:186] NA NA NA NA ...
## $ AuthorType : chr [1:186] NA NA NA NA ...
## $ Objectivity : chr [1:186] NA NA NA NA ...
## $ LegalActType : chr [1:186] NA NA NA NA ...
## $ Bindingness : logi [1:186] NA NA NA NA NA NA ...
## $ Recipient Type : chr [1:186] NA NA NA NA ...
## $ class : chr [1:186] "good" "good" "good" "good" ...
```

```
str(unreadable)
```

```
## tibble [237,926 x 36] (S3: tbl_df/tbl/data.frame)
## $ KUK_ID : chr [1:237926] "671918e2c6537d54ff0626db" "671918e2c6537d54ff0626dd" "671918e2c6537d54ff0626dd" ...
## $ FileName : chr [1:237926] "orig_Certifikáty autorizovaných inspektorů" "orig_finanční" "orig_finanční" ...
## $ FileFormat : chr [1:237926] "TXT" "TXT" "TXT" "TXT" ...
## $ FolderPath : chr [1:237926] "data/KUKY/TXT" "data/KUKY/TXT" "data/KUKY/TXT" "data/KUKY/TXT" ...
## $ subcorpus : chr [1:237926] "KUKY" "KUKY" "KUKY" "KUKY" ...
```

```
## $ SourceDB : chr [1:237926] "SourceDB" "SourceDB" "SourceDB" "SourceDB" ...
## $ SourceID : chr [1:237926] NA NA NA NA ...
## $ DocumentTitle : chr [1:237926] NA NA NA NA ...
## $ ClarityPursuit : logi [1:237926] NA NA NA NA NA NA ...
## $ Anonymized.x : chr [1:237926] "No" "No" "No" "No" ...
## $ RecipientType.x : chr [1:237926] "natural person" "natural person" "natural person" "natu
## $ RecipientIndividuation.x: chr [1:237926] "public" "public" "public" "public" ...
## $ AuthorType.x : chr [1:237926] "individual" "individual" "authority" "authority" ...
## $ Objectivity.x : chr [1:237926] "quasiobjective" "quasiobjective" "quasiobjective" "quas
## $ LegalActType.x : chr [1:237926] "normative" "normative" "normative" "normative" ...
## $ Bindingness.x : logi [1:237926] FALSE FALSE FALSE FALSE FALSE FALSE ...
## $ Readability : chr [1:237926] "low" "low" "low" "low" ...
## $ SyllogismBased : chr [1:237926] "false" "false" "false" "false" ...
## $ DocumentVersion : chr [1:237926] "Original" "Original" "Original" "Original" ...
## $ ParentDocumentID : chr [1:237926] NA NA NA NA ...
## $ LegalActType.y : chr [1:237926] "normative" "normative" "normative" "normative" ...
## $ Objectivity.y : chr [1:237926] "quasiobjective" "quasiobjective" "quasiobjective" "quas
## $ Bindingness.y : logi [1:237926] FALSE FALSE FALSE FALSE FALSE FALSE ...
## $ AuthorType.y : chr [1:237926] "individual" "individual" "authority" "authority" ...
## $ RecipientType.y : chr [1:237926] "natural person" "natural person" "natural person" "natu
## $ RecipientIndividuation.y: chr [1:237926] "public" "public" "public" "public" ...
## $ Anonymized.y : chr [1:237926] "No" "No" "No" "No" ...
## $ Anonymized : chr [1:237926] NA NA NA NA ...
## $ RecipientType : chr [1:237926] NA NA NA NA ...
## $ RecipientIndividuation : chr [1:237926] NA NA NA NA ...
## $ AuthorType : chr [1:237926] NA NA NA NA ...
## $ Objectivity : chr [1:237926] NA NA NA NA ...
## $ LegalActType : chr [1:237926] NA NA NA NA ...
## $ Bindingness : logi [1:237926] NA NA NA NA NA NA ...
## $ Recipient Type : chr [1:237926] NA NA NA NA ...
## $ class : chr [1:237926] "bad" "bad" "bad" "bad" ...
```

Data set parameters

```
.split_prop <- 4 / 5 # proportion of testing data in the dataset
.no_folds <- 10 # no. of folds in v-fold cross-validation
.balance <- 3 / 10 # proportion of positive samples in the target dataset

dssize_positive <- count(readable)[[1, 1]]
dssize_total <- dssize_positive / .balance
dssize_negative <- dssize_total - dssize_positive

print(c(
  paste(c(
    "Data set size:", dssize_total
  ), collapse = " "),
  paste(c(
    "Positive class size:", dssize_positive
  ), collapse = " "),
  paste(c(
    "Negative class size:", dssize_negative
  ), collapse = " "),
  paste(c(
```

```

    "Training data set size:", dssize_total * .split_prop
  ), collapse = " "),
  paste(c(
    "Training positive class size:", dssize_positive * .split_prop
  ), collapse = " "),
  paste(c(
    "Training negative class size:", dssize_negative * .split_prop
  ), collapse = " "),
  paste(c(
    "One fold size:", (dssize_total * .split_prop) / .no_folds
  ), collapse = " "),
  paste(c(
    "One fold positive class size:", (dssize_positive * .split_prop) / .no_folds
  ), collapse = " "),
  paste(c(
    "One fold negative class size:", (dssize_negative * .split_prop) / .no_folds
  ), collapse = " "),
  paste(c(
    "Evaluation data set size:", dssize_total * (1 - .split_prop)
  ), collapse = " "),
  paste(c(
    "Evaluation positive class size:", dssize_positive * (1 - .split_prop)
  ), collapse = " "),
  paste(c(
    "Evaluation negative class size:", dssize_negative * (1 - .split_prop)
  ), collapse = " ")
), quote = FALSE)

```

```

## [1] Data set size: 620           Positive class size: 186
## [3] Negative class size: 434        Training data set size: 496
## [5] Training positive class size: 148.8 Training negative class size: 347.2
## [7] One fold size: 49.6            One fold positive class size: 14.88
## [9] One fold negative class size: 34.72 Evaluation data set size: 124
## [11] Evaluation positive class size: 37.2 Evaluation negative class size: 86.8

```

Data set undersampling and split

```

df <- df # TODO: undersample here!

df_split <- df %>% initial_split(prop = .split_prop)
training_set <- training(df_split)
evaluation_set <- testing(df_split)

folds <- vfold_cv(training_set, v = .no_folds, strata = class)

print(df_split)

## <Training/Testing/Total>
## <190489/47623/238112>

print(folds)

## # 10-fold cross-validation using stratification
## # A tibble: 10 x 2

```

```
##      splits      id
##      <list>      <chr>
## 1 <split [171440/19049]> Fold01
## 2 <split [171440/19049]> Fold02
## 3 <split [171440/19049]> Fold03
## 4 <split [171440/19049]> Fold04
## 5 <split [171440/19049]> Fold05
## 6 <split [171440/19049]> Fold06
## 7 <split [171440/19049]> Fold07
## 8 <split [171440/19049]> Fold08
## 9 <split [171440/19049]> Fold09
## 10 <split [171441/19048]> Fold10
```