

EFA

```
set.seed(42)

library(igraph)

##
## Attaching package: 'igraph'
## The following objects are masked from 'package:stats':
##
##      decompose, spectrum
## The following object is masked from 'package:base':
##
##      union

library(corrplot)

## corrplot 0.95 loaded

library(QuantPsyc) # for the multivariate normality test

## Loading required package: boot
## Loading required package: dplyr
##
## Attaching package: 'dplyr'
## The following objects are masked from 'package:igraph':
##
##      as_data_frame, groups, union
## The following objects are masked from 'package:stats':
##
##      filter, lag
## The following objects are masked from 'package:base':
##
##      intersect, setdiff, setequal, union
## Loading required package: purrr
##
## Attaching package: 'purrr'
## The following objects are masked from 'package:igraph':
##
##      compose, simplify
## Loading required package: MASS
##
## Attaching package: 'MASS'
```

```

## The following object is masked from 'package:dplyr':
##
##   select
##
## Attaching package: 'QuantPsyc'
## The following object is masked from 'package:base':
##
##   norm
library(dunn.test)
library(nFactors) # for the scree plot

## Loading required package: lattice
##
## Attaching package: 'lattice'
## The following object is masked from 'package:boot':
##
##   melanoma
##
## Attaching package: 'nFactors'
## The following object is masked from 'package:lattice':
##
##   parallel
library(psych) # for PA FA

##
## Attaching package: 'psych'
## The following object is masked from 'package:boot':
##
##   logit
library(caret) # highly correlated features removal

## Loading required package: ggplot2
##
## Attaching package: 'ggplot2'
## The following objects are masked from 'package:psych':
##
##   %+%, alpha
##
## Attaching package: 'caret'
## The following object is masked from 'package:purrr':
##
##   lift
library(tidyverse)

## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v forcats   1.0.0      v stringr   1.5.1
## v lubridate 1.9.3      v tibble   3.2.1

```

```
## v readr      2.1.5      v tidyr      1.3.1

## -- Conflicts ----- tidyverse_conflicts() --
## x lubridate::%--%()      masks igraph::%--%()
## x ggplot2::%+%()      masks psych::%+%()
## x ggplot2::alpha()      masks psych::alpha()
## x tibble::as_data_frame() masks dplyr::as_data_frame(), igraph::as_data_frame()
## x purrr::compose()      masks igraph::compose()
## x tidyr::crossing()      masks igraph::crossing()
## x dplyr::filter()      masks stats::filter()
## x dplyr::lag()      masks stats::lag()
## x caret::lift()      masks purrr::lift()
## x MASS::select()      masks dplyr::select()
## x purrr::simplify()      masks igraph::simplify()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors

library(paletteer) # color palettes

library(conflicted) # to resolve QuantPsyc x dplyr conflicts
conflict_prefer("select", "dplyr")

## [conflicted] Will prefer dplyr::select over any other package.
conflict_prefer("filter", "dplyr")

## [conflicted] Will prefer dplyr::filter over any other package.
```

Load and tidy data

```
pretty_names <- read_csv("../feat_name_mapping.csv")

## Rows: 85 Columns: 2
## -- Column specification -----
## Delimiter: ","
## chr (2): name_orig, name_pretty
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
data <- read_csv("../measurements/measurements.csv")

## Rows: 754 Columns: 108
## -- Column specification -----
## Delimiter: ","
## chr (20): fpath, KUK_ID, FileName, FileFormat, FolderPath, subcorpus, Source...
## dbl (85): RuleAbstractNouns, RuleAmbiguousRegards, RuleAnaphoricReferences, ...
## lgl (3): ClarityPursuit, SyllogismBased, Bindingness
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
.firstnonmetacolumn <- 17

data_no_nas <- data %>%
  select(!c(
    fpath,
```

```

# KUK_ID,
# FileName,
FolderPath,
# subcorpus,
DocumentTitle,
ClarityPursuit,
Readability,
SyllogismBased,
SourceDB
)) %>%
# replace -1s in variation coefficients with NAs
mutate(across(c(
  `RuleDoubleAdpos.max_allowable_distance.v`,
  `RuleTooManyNegations.max_negation_frac.v`,
  `RuleTooManyNegations.max_allowable_negations.v`,
  `RuleTooManyNominalConstructions.max_noun_frac.v`,
  `RuleTooManyNominalConstructions.max_allowable_nouns.v`,
  `RuleCaseRepetition.max_repetition_count.v`,
  `RuleCaseRepetition.max_repetition_frac.v`,
  `RulePredSubjDistance.max_distance.v`,
  `RulePredObjDistance.max_distance.v`,
  `RuleInfVerbDistance.max_distance.v`,
  `RuleMultiPartVerbs.max_distance.v`,
  `RuleLongSentences.max_length.v`,
  `RulePredAtClauseBeginning.max_order.v`,
  `mattr.v`,
  `maentropy.v`
), ~ na_if(.x, -1))) %>%
# replace NAs with 0s
replace_na(list(
  RuleGPcoordovs = 0,
  RuleGPdeverbaddr = 0,
  RuleGPpatinstr = 0,
  RuleGPdeverbsubj = 0,
  RuleGPadjective = 0,
  RuleGPpatbenperson = 0,
  RuleGPwordorder = 0,
  RuleDoubleAdpos = 0,
  RuleDoubleAdpos.max_allowable_distance.v = 0,
  RuleAmbiguousRegards = 0,
  RuleReflexivePassWithAnimSubj = 0,
  RuleTooManyNegations = 0,
  RuleTooManyNegations.max_negation_frac.v = 0,
  RuleTooManyNegations.max_allowable_negations.v = 0,
  RuleTooManyNominalConstructions.max_noun_frac.v = 0,
  RuleTooManyNominalConstructions.max_allowable_nouns.v = 0,
  RuleFunctionWordRepetition = 0,
  RuleCaseRepetition.max_repetition_count.v = 0,
  RuleCaseRepetition.max_repetition_frac.v = 0,
  RuleWeakMeaningWords = 0,
  RuleAbstractNouns = 0,
  RuleRelativisticExpressions = 0,
  RuleConfirmationExpressions = 0,

```

```

RuleRedundantExpressions = 0,
RuleTooLongExpressions = 0,
RuleAnaphoricReferences = 0,
RuleLiteraryStyle = 0,
RulePassive = 0,
RulePredSubjDistance = 0,
RulePredSubjDistance.max_distance.v = 0,
RulePredObjDistance = 0,
RulePredObjDistance.max_distance.v = 0,
RuleInfVerbDistance = 0,
RuleInfVerbDistance.max_distance.v = 0,
RuleMultiPartVerbs = 0,
RuleMultiPartVerbs.max_distance.v = 0,
RuleLongSentences.max_length.v = 0,
RulePredAtClauseBeginning.max_order.v = 0,
RuleVerbalNouns = 0,
RuleDoubleComparison = 0,
RuleWrongValencyCase = 0,
RuleWrongVerbominalCase = 0,
RuleIncompleteConjunction = 0
)) %>%
# replace NAs with medians
mutate(across(c(
  RuleDoubleAdpos.max_allowable_distance,
  RuleTooManyNegations.max_negation_frac,
  RuleTooManyNegations.max_allowable_negations,
  RulePredSubjDistance.max_distance,
  RulePredObjDistance.max_distance,
  RuleInfVerbDistance.max_distance,
  RuleMultiPartVerbs.max_distance
), ~ coalesce(., median(., na.rm = TRUE)))) %>%
# merge GPs
mutate(
  GPs = RuleGPcoordovs +
    RuleGPdeverbaddr +
    RuleGPpatinstr +
    RuleGPdeverbsubj +
    RuleGPadjective +
    RuleGPPatbenperson +
    RuleGPwordorder
) %>%
select(!c(
  RuleGPcoordovs,
  RuleGPdeverbaddr,
  RuleGPpatinstr,
  RuleGPdeverbsubj,
  RuleGPadjective,
  RuleGPPatbenperson,
  RuleGPwordorder
))

data_clean <- data_no_nas %>%
# norm data expected to correlate with text length

```

```

mutate(across(c(
  GPs,
  RuleDoubleAdpos,
  RuleAmbiguousRegards,
  RuleFunctionWordRepetition,
  RuleWeakMeaningWords,
  RuleAbstractNouns,
  RuleRelativisticExpressions,
  RuleConfirmationExpressions,
  RuleRedundantExpressions,
  RuleTooLongExpressions,
  RuleAnaphoricReferences,
  RuleLiteraryStyle,
  RulePassive,
  RuleVerbalNouns,
  RuleDoubleComparison,
  RuleWrongValencyCase,
  RuleWrongVerbominalCase,
  RuleIncompleteConjunction,
  num_hapax,
  RuleReflexivePassWithAnimSubj,
  RuleTooManyNominalConstructions,
  RulePredSubjDistance,
  RuleMultiPartVerbs,
  RulePredAtClauseBeginning
), ~ .x / word_count)) %>%
mutate(across(c(
  RuleTooFewVerbs,
  RuleTooManyNegations,
  RuleCaseRepetition,
  RuleLongSentences,
  RulePredObjDistance,
  RuleInfVerbDistance
), ~ .x / sent_count)) %>%
# remove variables identified as "u counts"
select(!c(
  RuleTooFewVerbs,
  RuleTooManyNegations,
  RuleTooManyNominalConstructions,
  RuleCaseRepetition,
  RuleLongSentences,
  RulePredAtClauseBeginning,
  syllab_count,
  char_count
)) %>%
# remove variables identified as unreliable
select(!c(
  RuleAmbiguousRegards,
  RuleFunctionWordRepetition,
  RuleDoubleComparison,
  RuleWrongValencyCase,
  RuleWrongVerbominalCase
)) %>%

```

```

# remove artificially limited variables
select(!c(
  RuleCaseRepetition.max_repetition_frac,
  RuleCaseRepetition.max_repetition_frac.v
)) %>%
# remove further variables belonging to the 'acceptability' category
select(!c(RuleIncompleteConjunction)) %>%
mutate(across(c(
  class,
  FileFormat,
  subcorpus,
  DocumentVersion,
  LegalActType,
  Objectivity,
  AuthorType,
  RecipientType,
  RecipientIndividuation,
  Anonymized
), ~ as.factor(.x)))

# no NAs should be present now
data_clean[!complete.cases(data_clean[,firstnonmetacolumn:ncol(data_clean)]), ]

## # A tibble: 0 x 79
## # i 79 variables: KUK_ID <chr>, FileName <chr>, FileFormat <fct>,
## #   subcorpus <fct>, SourceID <chr>, DocumentVersion <fct>,
## #   ParentDocumentID <chr>, LegalActType <fct>, Objectivity <fct>,
## #   Bindingness <lgl>, AuthorType <fct>, RecipientType <fct>,
## #   RecipientIndividuation <fct>, Anonymized <fct>, Recipient Type <chr>,
## #   class <fct>, RuleAbstractNouns <dbl>, RuleAnaphoricReferences <dbl>,
## #   RuleCaseRepetition.max_repetition_count <dbl>, ...

data_clean_scaled <- data_clean %>%
  mutate(across(class, ~ .x == "good")) %>%
  mutate(across(.firstnonmetacolumn:ncol(data_clean), ~ scale(.x)))

## Warning: There was 1 warning in `mutate()`.
## i In argument: `across(.firstnonmetacolumn:ncol(data_clean), ~scale(.x))`.
## Caused by warning:
## ! Using an external vector in selections was deprecated in tidysselect 1.1.0.
## i Please use `all_of()` or `any_of()` instead.
## # Was:
##   data %>% select(.firstnonmetacolumn)
##
## # Now:
##   data %>% select(all_of(.firstnonmetacolumn))
##
## See <https://tidysselect.r-lib.org/reference/faq-external-vector.html>.

```

Important features identification

```

feature_importances <- tibble(
  feat_name = character(), p_value = numeric()
)

```

```

)

for (i in .firstnonmetacolumn:ncol(data_clean)) {
  fname <- names(data_clean)[i]

  formula_single <- reformulate(fname, "class")

  glm_model <- glm(formula_single, data_clean, family = "binomial")
  glm_coefficients <- summary(glm_model)$coefficients
  row_index <- which(rownames(glm_coefficients) == fname)
  p_value <- glm_coefficients[row_index, 4]

  feature_importances <- feature_importances %>%
    add_row(feet_name = fname, p_value = p_value)
}
feature_importances

## # A tibble: 63 x 2
##   feat_name                p_value
##   <chr>                  <dbl>
## 1 RuleAbstractNouns      1.87e- 3
## 2 RuleAnaphoricReferences 6.60e- 1
## 3 RuleCaseRepetition.max_repetition_count 7.22e- 2
## 4 RuleCaseRepetition.max_repetition_count.v 4.79e- 3
## 5 RuleConfirmationExpressions 9.85e- 2
## 6 RuleDoubleAdpos        3.12e- 1
## 7 RuleDoubleAdpos.max_allowable_distance 1.90e- 4
## 8 RuleDoubleAdpos.max_allowable_distance.v 3.56e- 6
## 9 RuleInfVerbDistance    3.55e-15
## 10 RuleInfVerbDistance.max_distance 5.57e- 2
## # i 53 more rows

selected_features <- feature_importances %>%
  mutate(selected = p_value <= 0.05)
selected_features %>% write_csv("selected_features.csv")
selected_features_names <- selected_features %>%
  filter(selected) %>%
  pull(feet_name)

```

Correlations

See Levshina (2015: 353–54).

```

analyze_correlation <- function(data) {
  cor_matrix <- cor(data)

  cor_tibble_long <- cor_matrix %>%
    as_tibble() %>%
    mutate(feet1 = rownames(cor_matrix)) %>%
    pivot_longer(!feet1, names_to = "feet2", values_to = "cor") %>%
    mutate(abs_cor = abs(cor))

  cor_matrix_upper <- cor_matrix
  cor_matrix_upper[lower.tri(cor_matrix_upper)] <- 0
}

```



```

cor_tibble_long_upper <- cor_matrix_upper %>%
  as_tibble() %>%
  mutate(feats1 = rownames(cor_matrix)) %>%
  pivot_longer(!feats1, names_to = "feat2", values_to = "cor") %>%
  mutate(abs_cor = abs(cor)) %>%
  filter(feats1 != feat2 & abs_cor > 0)

list(
  cor_matrix = cor_matrix,
  cor_matrix_upper = cor_matrix_upper,
  cor_tibble_long = cor_tibble_long,
  cor_tibble_long_upper = cor_tibble_long_upper
)
}

data_purish <- data_clean %>% select(any_of(selected_features_names))

```

what unites the low-communality variables we threw out:

- variations have little to do with any other variables in the dataset; there is no factor stemming from the remainder of the feature set to explain them
-

High correlations

```

.hcorrcutoff <- 0.9

analyze_correlation(data_purish)$cor_tibble_long %>%
  filter(feats1 != feat2 & abs_cor > .hcorrcutoff) %>%
  arrange(feats1, -abs_cor) %>%
  print(n = 100)

```

```

## # A tibble: 22 x 4
##   feat1                feat2          cor abs_cor
##   <chr>                <chr>        <dbl>  <dbl>
## 1 RuleLongSentences.max_length ari          0.944    0.944
## 2 RuleLongSentences.max_length gf           0.922    0.922
## 3 ari                  fkg1          0.984    0.984
## 4 ari                  gf           0.978    0.978
## 5 ari                  smog          0.951    0.951
## 6 ari                  RuleLongSentences.max_length 0.944    0.944
## 7 atl                 cli           0.960    0.960
## 8 cli                 atl           0.960    0.960
## 9 fkg1                ari           0.984    0.984
## 10 fkg1                gf           0.967    0.967
## 11 fkg1                smog          0.949    0.949
## 12 gf                 smog          0.987    0.987
## 13 gf                 ari           0.978    0.978
## 14 gf                 fkg1          0.967    0.967
## 15 gf                 RuleLongSentences.max_length 0.922    0.922
## 16 hpoint             word_count    0.957    0.957
## 17 maentropy          mattr          0.964    0.964
## 18 mattr              maentropy    0.964    0.964
## 19 smog              gf           0.987    0.987

```

## 20 smog	ari	0.951	0.951
## 21 smog	fkg1	0.949	0.949
## 22 word_count	hpoint	0.957	0.957

exclude:

- **ari:** corr. w/ RuleLongSentences.max_length > 0.94; sentence length seems more universal, let's make it a substitute
- **gf:** corr. w/ RuleLongSentences.max_length > 0.92; sentence length seems more universal, let's make it a substitute
- **maentropy:** corr. w/ mattr > 0.96, but mattr is implemented in QuitaUp. besides, the interesting thing about maentropy is its variation
- **smog:** corr. w/ fkg1 almost 0.95, but fkg1 coefficients adjusted for Czech are available
- **atl:** corr. w/ cli around 0.96; unlike cli, atl is not a readability metric

```
high_correlations <- findCorrelation(
  cor(data_purish),
  verbose = TRUE, cutoff = .hcorrcutoff
)
```

```
## Compare row 7 and column 34 with corr 0.944
## Means: 0.4 vs 0.208 so flagging column 7
## Compare row 34 and column 40 with corr 0.978
## Means: 0.382 vs 0.201 so flagging column 34
## Compare row 40 and column 48 with corr 0.987
## Means: 0.369 vs 0.193 so flagging column 40
## Compare row 48 and column 38 with corr 0.949
## Means: 0.349 vs 0.187 so flagging column 48
## Compare row 35 and column 36 with corr 0.96
## Means: 0.261 vs 0.182 so flagging column 35
## Compare row 50 and column 41 with corr 0.957
## Means: 0.185 vs 0.179 so flagging column 50
## Compare row 42 and column 45 with corr 0.964
## Means: 0.175 vs 0.179 so flagging column 45
## All correlations <= 0.9
```

```
names(data_purish)[high_correlations]
```

```
## [1] "RuleLongSentences.max_length" "ari"
## [3] "gf"                          "smog"
## [5] "atl"                         "word_count"
## [7] "mattr"
```

```
data_pureish_striphigh <- data_purish %>% select(!all_of(high_correlations))
```

```
analyze_correlation(data_pureish_striphigh)$cor_tibble_long %>%
  filter(feet1 != feet2 & abs_cor > .hcorrcutoff) %>%
  arrange(feet1, -abs_cor) %>%
  print(n = 100)
```

```
## # A tibble: 0 x 4
```

```
## # i 4 variables: feet1 <chr>, feet2 <chr>, cor <dbl>, abs_cor <dbl>
```

Low correlations

```
# 0.35 instead of 0.3 otherwise the FA bootstrapping would freeze
.lcorrcutoff <- 0.35
```

```
low_correlating_features <- analyze_correlation(data_pureish_striphigh)$
  cor_tibble_long %>%
  filter(feat1 != feat2) %>%
  group_by(feat1) %>%
  summarize(max_cor = max(abs_cor)) %>%
  filter(max_cor < .lcorrcutoff) %>%
  pull(feat1)
```

```
feature_importances %>% filter(feat_name %in% low_correlating_features)
```

```
## # A tibble: 9 x 2
##   feat_name                p_value
##   <chr>                  <dbl>
## 1 RuleAbstractNouns      0.00187
## 2 RuleCaseRepetition.max_repetition_count.v 0.00479
## 3 RuleRedundantExpressions 0.0104
## 4 RuleRelativisticExpressions 0.00205
## 5 RuleTooManyNegations.max_negation_frac.v 0.0365
## 6 RuleTooManyNominalConstructions.max_noun_frac.v 0.00000311
## 7 RuleVerbalNouns        0.0000748
## 8 RuleWeakMeaningWords    0.0386
## 9 GPs                    0.0138
```


```
data_pure <- data_pureish_striphigh %>%
  select(!any_of(low_correlating_features))
```

```
cnames <- map(
  colnames(data_pure),
  function(x) {
    pull(pretty_names %>%
      filter(name_orig == x), name_pretty)
  }
) %>% unlist()
```


```
colnames(data_pure) <- cnames
```

Visualisation

```
corrplot(cor(data_pure))
```



```
corrplot(abs(cor(data_pure)))
```




```
my_colors <- paletteer::paletteer_d("ggthemes::Classic_10_Medium")

network_edges <- analyze_correlation(data_pure)$cor_tibble_long_upper %>%
  filter(abs_cor > .lcorrcutoff)

network <- graph_from_data_frame(
  network_edges,
  directed = FALSE
)
E(network)$weight <- network_edges$abs_cor
network_communities <- cluster_optimal(network)

network_membership <- membership(network_communities)

plot(
  network,
  layout = layout_fruchterman_reingold,
  vertex.color = map(
    network_communities$membership,
    function(x) my_colors[x]
  ) %>% unlist(use.names = FALSE),
  vertex.size = 6,
  vertex.label.color = "black",
  vertex.label.cex = 0.7
)
```



Scaling

```
data_scaled <- data_pure %>%
  mutate(across(seq_along(data_pure), ~ scale(.x)[, 1])))
```

Check for normality

```
mult.norm(data_scaled %>% as.data.frame())$mult.test
```

```
##          Beta-hat      kappa p-val
## Skewness 1168.858 146886.540    0
## Kurtosis 2987.165   456.508    0
```

Low (null) p-values show that we can reject the hypothesis that the data would be in a multivariate normal


distribution. I.e. the distribution isn't multivariate normal.

first FA

No. of factors

```
eigen <- eigen(cor(data_scaled))
par <- nFactors::parallel(
  subject = nrow(data_scaled),
  var = ncol(data_scaled),
  rep = 100,
  quantile = .95,
  model = "factors"
)
scree <- nScree(x = eigen$values, aparallel = par$eigen$gevpea)
plotnScree(scree)
```


Non Graphical Solutions to Scree Test



```
fa.parallel(data_scaled, fm = "pa", fa = "fa", n.iter = 20)
```

```
## Warning in fa.stats(r = r, f = f, phi = phi, n.obs = n.obs, np.obs = np.obs, :
## The estimated weights for the factor scores are probably incorrect. Try a
## different factor score estimation method.
```

Parallel Analysis Scree Plots



Parallel analysis suggests that the number of factors = 8 and the number of components = NA

Model

<https://www.rdocumentation.org/packages/psych/versions/2.5.3/topics/fa>

produces ultra-Heywood cases when nfactors = 9

```
fa_1 <- fa(
  data_scaled,
  nfactors = 9,
  fm = "pa",
  rotate = "promax",
  oblique.scores = TRUE,
  scores = "tenBerge",
  n.iter = 100
)
```

Loading required namespace: GPArotation

Warning in fa.stats(r = r, f = f, phi = phi, n.obs = n.obs, np.obs = np.obs, :
The estimated weights for the factor scores are probably incorrect. Try a
different factor score estimation method.

Warning in fac(r = r, nfactors = nfactors, n.obs = n.obs, rotate = rotate, : An
ultra-Heywood case was detected. Examine the results carefully

fa_1

```
## Factor Analysis with confidence intervals using method = fa(r = data_scaled, nfactors = 9, n.iter = 100,
##   scores = "tenBerge", fm = "pa", oblique.scores = TRUE)
## Factor Analysis using method = pa
## Call: fa(r = data_scaled, nfactors = 9, n.iter = 100, rotate = "promax",
##   scores = "tenBerge", fm = "pa", oblique.scores = TRUE)
```



```

## Standardized loadings (pattern matrix) based upon correlation matrix
##          PA1  PA2  PA7  PA4  PA6  PA5  PA3  PA9  PA8  h2
## doubleADPdist.m    -0.08 -0.08 -0.05  0.08 -0.06  0.00  0.17 -0.06  0.66 0.46
## doubleADPdist.v     0.01  0.39 -0.07  0.01 -0.04  0.00  0.06  0.09  0.58 0.52
## VERBcomp           0.64  0.01  0.06  0.50  0.29 -0.11 -0.03  0.07  0.03 0.59
## literary           0.00 -0.03  0.13  0.16 -0.27  0.13 -0.08 -0.03 -0.03 0.24
## compoundVERBs       1.04 -0.15  0.35 -0.28 -0.33  0.05  0.02  0.16 -0.01 0.73
## compoundVERBsdist.m 0.25 -0.05  0.80 -0.09 -0.10 -0.06  0.12 -0.05  0.05 0.47
## compoundVERBsdist.v -0.12  0.26  0.29  0.00 -0.17  0.02  0.07 -0.03 -0.02 0.33
## passives            0.01 -0.08  0.03 -0.22 -0.83  0.09  0.02 -0.08  0.04 0.56
## predorder.m        -0.66 -0.07  0.15  0.20  0.06 -0.06  0.08 -0.01 -0.12 0.61
## predorder.v        -0.08  0.00  0.65  0.15  0.02  0.02 -0.08 -0.06 -0.07 0.55
## obj                0.14 -0.05  0.01  0.92  0.18  0.12  0.06 -0.05  0.05 0.70
## predobjdist.m      -0.05 -0.11  0.63 -0.10  0.01 -0.06  0.12  0.05 -0.07 0.38
## predobjdist.v       0.02  0.15  0.53  0.05 -0.03  0.05 -0.01  0.01 -0.03 0.37
## subj              0.57  0.14 -0.18 -0.04 -0.12  0.06  0.22  0.08 -0.06 0.54
## predsubjdist.m     -0.38 -0.05  0.23  0.05  0.15  0.03  0.44  0.20 -0.06 0.50
## predsubjdist.v     -0.21  0.12  0.46  0.15  0.01  0.06  0.01 -0.09 -0.11 0.48
## VERBfrac.m         0.90 -0.06  0.17  0.03  0.34  0.00  0.05  0.06  0.02 0.91
## VERBfrac.v        -0.48 -0.08  0.09 -0.21  0.24  0.05 -0.01  0.06  0.15 0.38
## NEGcount.m         -0.02 -0.08 -0.09  0.18  0.01  0.97  0.03  0.02 -0.01 0.95
## NEGcount.v         0.22  0.08 -0.01  0.06 -0.05  0.74 -0.01  0.05  0.02 0.60
## NEGfrac.m         -0.05 -0.04 -0.11 -0.16  0.40  0.25  0.09 -0.13 -0.05 0.36
## NOUNcount.m        -0.91  0.02  0.02 -0.03 -0.01 -0.13 -0.04  0.03  0.03 0.81
## NOUNcount.v        -0.08 -0.11  0.42  0.03  0.00  0.01 -0.07 -0.09  0.28 0.41
## activity           0.80 -0.01  0.12  0.26  0.47  0.00  0.03 -0.11 -0.05 0.93
## cli                0.34 -0.01 -0.10 -0.12  0.10  0.03 -0.10  0.76 -0.06 0.70
## entropy            0.01  0.78  0.16 -0.16  0.08  0.09 -0.34  0.16  0.04 0.86
## fkgl              -0.40 -0.06 -0.02  0.52 -0.25  0.07  0.00  0.22  0.10 0.96
## fre                0.09  0.08  0.10 -0.46  0.17 -0.09  0.01 -0.67 -0.09 1.01
## hpoint            -0.06  0.98 -0.01  0.03  0.00  0.00  0.04 -0.07  0.01 0.94
## maentropy          -0.33  0.04  0.06 -0.12  0.11  0.05 -0.78  0.18 -0.14 0.73
## entropy.v          0.03  0.09  0.26 -0.03  0.11  0.05  0.56  0.01  0.10 0.42
## mamr               0.70 -0.06 -0.11 -0.01 -0.05 -0.04  0.23  0.14 -0.12 0.73
## hapaxes            0.08 -0.82  0.11 -0.13  0.09  0.01 -0.23  0.12 -0.02 0.74
## sentcount          0.14  0.93  0.01 -0.22  0.25 -0.08 -0.01  0.03 -0.07 0.86
## verbdist          -0.87 -0.02  0.02 -0.20 -0.18 -0.07  0.08 -0.06 -0.06 0.79
##
##              u2 com
## doubleADPdist.m    0.5440 1.3
## doubleADPdist.v    0.4751 1.9
## VERBcomp           0.4063 2.5
## literary           0.7583 3.1
## compoundVERBs       0.2653 1.7
## compoundVERBsdist.m 0.5329 1.3
## compoundVERBsdist.v 0.6703 3.1
## passives            0.4365 1.2
## predorder.m        0.3914 1.5
## predorder.v        0.4514 1.2
## obj                0.2996 1.2
## predobjdist.m      0.6174 1.3
## predobjdist.v      0.6271 1.2
## subj              0.4622 1.9
## predsubjdist.m     0.5039 3.4
## predsubjdist.v     0.5202 2.1

```

```

## VERBfrac.m          0.0918 1.4
## VERBfrac.v          0.6245 2.4
## NEGcount.m          0.0546 1.1
## NEGcount.v          0.3983 1.2
## NEGfrac.m           0.6398 2.8
## NOUNcount.m         0.1879 1.0
## NOUNcount.v         0.5917 2.2
## activity            0.0727 2.0
## cli                 0.2983 1.6
## entropy             0.1429 1.7
## fkg1                0.0397 3.0
## fre                 -0.0086 2.1
## hpoint              0.0562 1.0
## maentropy           0.2746 1.7
## entropy.v           0.5816 1.7
## mamr                0.2703 1.5
## hapaxes             0.2649 1.3
## sentcount           0.1409 1.3
## verbdist            0.2053 1.3
##
##
##          PA1  PA2  PA7  PA4  PA6  PA5  PA3  PA9  PA8
## SS loadings      6.75 3.37 2.52 2.04 1.88 1.68 1.49 1.36 1.01
## Proportion Var    0.19 0.10 0.07 0.06 0.05 0.05 0.04 0.04 0.03
## Cumulative Var    0.19 0.29 0.36 0.42 0.47 0.52 0.56 0.60 0.63
## Proportion Explained 0.31 0.15 0.11 0.09 0.08 0.08 0.07 0.06 0.05
## Cumulative Proportion 0.31 0.46 0.57 0.66 0.75 0.82 0.89 0.95 1.00
##
## With factor correlations of
##          PA1  PA2  PA7  PA4  PA6  PA5  PA3  PA9  PA8
## PA1  1.00  0.10 -0.62 -0.24  0.35 -0.27  0.05 -0.08 -0.31
## PA2  0.10  1.00  0.19  0.31 -0.25  0.29 -0.07  0.22  0.11
## PA7 -0.62  0.19  1.00  0.38 -0.34  0.30  0.06  0.13  0.33
## PA4 -0.24  0.31  0.38  1.00 -0.45  0.24 -0.13  0.30  0.05
## PA6  0.35 -0.25 -0.34 -0.45  1.00 -0.25  0.12 -0.33 -0.03
## PA5 -0.27  0.29  0.30  0.24 -0.25  1.00 -0.19 -0.03  0.11
## PA3  0.05 -0.07  0.06 -0.13  0.12 -0.19  1.00 -0.10 -0.15
## PA9 -0.08  0.22  0.13  0.30 -0.33 -0.03 -0.10  1.00  0.00
## PA8 -0.31  0.11  0.33  0.05 -0.03  0.11 -0.15  0.00  1.00
##
## Mean item complexity = 1.8
## Test of the hypothesis that 9 factors are sufficient.
##
## df null model = 595 with the objective function = 28.74 with Chi Square = 21280.42
## df of the model are 316 and the objective function was 4.25
##
## The root mean square of the residuals (RMSR) is 0.03
## The df corrected root mean square of the residuals is 0.04
##
## The harmonic n.obs is 754 with the empirical chi square 618.11 with prob < 8.9e-22
## The total n.obs was 754 with Likelihood Chi Square = 3120.31 with prob < 0
##
## Tucker Lewis Index of factoring reliability = 0.743
## RMSEA index = 0.108 and the 90 % confidence intervals are 0.105 0.112
## BIC = 1026.68

```

```

## Fit based upon off diagonal values = 0.99
## Coefficients and bootstrapped confidence intervals
##
##      low  PA1 upper  low  PA2 upper  low  PA7 upper  low
## doubleADPdist.m    -0.30 -0.08  0.07 -0.15 -0.08  0.04 -0.23 -0.05  0.23 -0.07
## doubleADPdist.v    -0.16  0.01  0.14  0.27  0.39  0.56 -0.18 -0.07  0.15 -0.09
## VERBcomp           0.45  0.64  0.77 -0.05  0.01  0.07 -0.03  0.06  0.12  0.32
## literary           -0.11  0.00  0.09 -0.11 -0.03  0.03 -0.02  0.13  0.24  0.07
## compoundVERBs       0.75  1.04  1.18 -0.19 -0.15 -0.08  0.14  0.35  0.45 -0.39
## compoundVERBsdist.m 0.10  0.25  0.35 -0.11 -0.05  0.03  0.46  0.80  1.08 -0.18
## compoundVERBsdist.v -0.24 -0.12 -0.02  0.17  0.26  0.37  0.09  0.29  0.43 -0.11
## passives           -0.12  0.01  0.06 -0.14 -0.08 -0.02 -0.07  0.03  0.11 -0.34
## predorder.m        -0.80 -0.66 -0.49 -0.12 -0.07 -0.01  0.00  0.15  0.31  0.10
## predorder.v        -0.24 -0.08  0.04 -0.06  0.00  0.08  0.32  0.65  0.89  0.06
## obj                0.05  0.14  0.23 -0.12 -0.05 -0.01 -0.06  0.01  0.09  0.61
## predobjdist.m      -0.24 -0.05  0.17 -0.19 -0.11 -0.03  0.30  0.63  0.96 -0.19
## predobjdist.v      -0.11  0.02  0.14  0.04  0.15  0.27  0.29  0.53  0.72 -0.03
## subj               0.41  0.57  0.73  0.08  0.14  0.20 -0.26 -0.18 -0.07 -0.13
## predsubjdist.m     -0.48 -0.38 -0.24 -0.10 -0.05  0.00  0.07  0.23  0.41 -0.09
## predsubjdist.v     -0.36 -0.21 -0.06  0.05  0.12  0.20  0.24  0.46  0.64  0.05
## VERBfrac.m         0.67  0.90  1.06 -0.09 -0.06 -0.01  0.05  0.17  0.24 -0.01
## VERBfrac.v        -0.64 -0.48 -0.29 -0.16 -0.08  0.01 -0.04  0.09  0.24 -0.33
## NEGcount.m         -0.08 -0.02  0.04 -0.11 -0.08 -0.01 -0.14 -0.09  0.03  0.10
## NEGcount.v         0.14  0.22  0.28  0.01  0.08  0.16 -0.07 -0.01  0.06  0.01
## NEGfrac.m          -0.13 -0.05  0.09 -0.12 -0.04  0.04 -0.22 -0.11  0.05 -0.29
## NOUNcount.m        -1.09 -0.91 -0.65 -0.03  0.02  0.07 -0.04  0.02  0.11 -0.10
## NOUNcount.v        -0.28 -0.08  0.02 -0.17 -0.11 -0.01  0.16  0.42  0.64 -0.06
## activity           0.58  0.80  0.96 -0.05 -0.01  0.03  0.03  0.12  0.17  0.18
## cli                0.25  0.34  0.46 -0.06 -0.01  0.06 -0.19 -0.10  0.02 -0.22
## entropy            -0.08  0.01  0.08  0.63  0.78  0.94  0.02  0.16  0.24 -0.25
## fkg1              -0.49 -0.40 -0.27 -0.09 -0.06 -0.04 -0.07 -0.02  0.05  0.34
## fre                -0.01  0.09  0.13  0.03  0.08  0.10 -0.02  0.10  0.14 -0.70
## hpoint             -0.10 -0.06  0.01  0.82  0.98  1.16 -0.06 -0.01  0.06 -0.01
## maentropy          -0.43 -0.33 -0.23 -0.03  0.04  0.09 -0.11  0.06  0.15 -0.24
## entropy.v          -0.14  0.03  0.21 -0.01  0.09  0.20  0.05  0.26  0.47 -0.12
## mamr               0.54  0.70  0.86 -0.11 -0.06  0.01 -0.23 -0.11  0.04 -0.08
## hapaxes            -0.02  0.08  0.13 -0.97 -0.82 -0.68 -0.01  0.11  0.18 -0.20
## sentcount          0.08  0.14  0.23  0.77  0.93  1.10 -0.04  0.01  0.07 -0.32
## verbdist           -1.03 -0.87 -0.65 -0.06 -0.02  0.02 -0.05  0.02  0.09 -0.32
##
##      PA4 upper  low  PA6 upper  low  PA5 upper  low  PA3
## doubleADPdist.m    0.08  0.25 -0.29 -0.06  0.25 -0.16  0.00  0.10  0.03  0.17
## doubleADPdist.v    0.01  0.12 -0.21 -0.04  0.19 -0.14  0.00  0.09 -0.08  0.06
## VERBcomp           0.50  0.76  0.13  0.29  0.55 -0.18 -0.11 -0.05 -0.08 -0.03
## literary           0.16  0.26 -0.51 -0.27 -0.05  0.05  0.13  0.33 -0.14 -0.08
## compoundVERBs      -0.28 -0.17 -0.48 -0.33 -0.17 -0.02  0.05  0.14 -0.04  0.02
## compoundVERBsdist.m -0.09  0.00 -0.20 -0.10 -0.01 -0.17 -0.06  0.01  0.00  0.12
## compoundVERBsdist.v 0.00  0.12 -0.38 -0.17 -0.02 -0.05  0.02  0.12 -0.02  0.07
## passives           -0.22 -0.13 -1.26 -0.83 -0.43  0.01  0.09  0.25 -0.04  0.02
## predorder.m        0.20  0.32 -0.11  0.06  0.25 -0.18 -0.06  0.06 -0.08  0.08
## predorder.v        0.15  0.26 -0.08  0.02  0.12 -0.06  0.02  0.15 -0.18 -0.08
## obj                0.92  1.29  0.09  0.18  0.33  0.06  0.12  0.30  0.01  0.06
## predobjdist.m      -0.10 -0.02 -0.14  0.01  0.11 -0.26 -0.06  0.08 -0.15  0.12
## predobjdist.v       0.05  0.17 -0.16 -0.03  0.09 -0.05  0.05  0.14 -0.11 -0.01
## subj              -0.04  0.04 -0.25 -0.12 -0.03 -0.03  0.06  0.17  0.09  0.22
## predsubjdist.m     0.05  0.23  0.00  0.15  0.29 -0.12  0.03  0.17  0.25  0.44

```

## predsubjdist.v	0.15	0.25	-0.10	0.01	0.11	-0.02	0.06	0.20	-0.11	0.01
## VERBfrac.m	0.03	0.09	0.17	0.34	0.57	-0.07	0.00	0.04	0.00	0.05
## VERBfrac.v	-0.21	-0.09	0.07	0.24	0.43	-0.12	0.05	0.15	-0.17	-0.01
## NEGcount.m	0.18	0.34	-0.09	0.01	0.07	0.72	0.97	1.37	-0.10	0.03
## NEGcount.v	0.06	0.15	-0.15	-0.05	0.03	0.57	0.74	1.17	-0.12	-0.01
## NEGfrac.m	-0.16	-0.04	0.13	0.40	0.73	0.08	0.25	0.45	-0.03	0.09
## NOUNcount.m	-0.03	0.05	-0.11	-0.01	0.05	-0.27	-0.13	-0.07	-0.14	-0.04
## NOUNcount.v	0.03	0.15	-0.12	0.00	0.18	-0.11	0.01	0.11	-0.18	-0.07
## activity	0.26	0.38	0.29	0.47	0.77	-0.04	0.00	0.07	0.01	0.03
## cli	-0.12	0.03	-0.10	0.10	0.21	-0.19	0.03	0.12	-0.35	-0.10
## entropy	-0.16	-0.07	0.00	0.08	0.18	0.04	0.09	0.21	-0.53	-0.34
## fkg1	0.52	0.76	-0.42	-0.25	-0.12	0.04	0.07	0.14	-0.06	0.00
## fre	-0.46	-0.30	0.09	0.17	0.36	-0.15	-0.09	0.02	-0.03	0.01
## hpoint	0.03	0.06	-0.06	0.00	0.07	-0.03	0.00	0.06	-0.01	0.04
## maentropy	-0.12	-0.02	0.01	0.11	0.25	-0.01	0.05	0.24	-1.13	-0.78
## entropy.v	-0.03	0.07	-0.06	0.11	0.26	-0.12	0.05	0.19	0.38	0.56
## mamr	-0.01	0.07	-0.19	-0.05	0.04	-0.18	-0.04	0.04	0.15	0.23
## hapaxes	-0.13	-0.06	0.00	0.09	0.18	-0.07	0.01	0.08	-0.38	-0.23
## sentcount	-0.22	-0.13	0.15	0.25	0.37	-0.17	-0.08	-0.04	-0.08	-0.01
## verbdist	-0.20	-0.11	-0.40	-0.18	-0.04	-0.17	-0.07	-0.01	-0.01	0.08
##	upper	low	PA9	upper	low	PA8	upper			
## doubleADPdist.m	0.31	-0.24	-0.06	0.08	0.24	0.66	1.09			
## doubleADPdist.v	0.16	-0.05	0.09	0.27	0.18	0.58	1.01			
## VERBcomp	0.06	-0.01	0.07	0.27	-0.25	0.03	0.37			
## literary	0.02	-0.13	-0.03	0.15	-0.31	-0.03	0.25			
## compoundVERBs	0.12	0.06	0.16	0.40	-0.67	-0.01	0.52			
## compoundVERBsdist.m	0.31	-0.17	-0.05	0.04	-0.26	0.05	0.42			
## compoundVERBsdist.v	0.21	-0.12	-0.03	0.06	-0.21	-0.02	0.24			
## passives	0.15	-0.18	-0.08	0.13	-0.61	0.04	0.58			
## predorder.m	0.29	-0.31	-0.01	0.26	-0.39	-0.12	0.12			
## predorder.v	0.09	-0.21	-0.06	0.08	-0.38	-0.07	0.28			
## obj	0.19	-0.12	-0.05	0.10	-0.34	0.05	0.57			
## predobjdist.m	0.39	-0.18	0.05	0.26	-0.33	-0.07	0.19			
## predobjdist.v	0.11	-0.14	0.01	0.14	-0.28	-0.03	0.26			
## subj	0.39	-0.04	0.08	0.20	-0.48	-0.06	0.26			
## predsubjdist.m	0.72	0.01	0.20	0.50	-0.37	-0.06	0.27			
## predsubjdist.v	0.19	-0.27	-0.09	0.05	-0.43	-0.11	0.27			
## VERBfrac.m	0.11	-0.02	0.06	0.14	-0.12	0.02	0.11			
## VERBfrac.v	0.05	-0.16	0.06	0.20	-0.14	0.15	0.48			
## NEGcount.m	0.06	-0.19	0.02	0.10	-0.40	-0.01	0.27			
## NEGcount.v	0.04	-0.08	0.05	0.14	-0.36	0.02	0.30			
## NEGfrac.m	0.17	-0.51	-0.13	0.01	-0.42	-0.05	0.23			
## NOUNcount.m	0.01	-0.11	0.03	0.10	-0.27	0.03	0.41			
## NOUNcount.v	0.03	-0.25	-0.09	0.03	-0.05	0.28	0.70			
## activity	0.12	-0.18	-0.11	-0.05	-0.18	-0.05	0.10			
## cli	-0.03	0.67	0.76	1.07	-0.37	-0.06	0.17			
## entropy	-0.24	0.07	0.16	0.41	-0.19	0.04	0.36			
## fkg1	0.04	0.16	0.22	0.44	-0.12	0.10	0.41			
## fre	0.17	-1.00	-0.67	-0.57	-0.26	-0.09	0.08			
## hpoint	0.11	-0.14	-0.07	-0.02	-0.24	0.01	0.36			
## maentropy	-0.59	0.07	0.18	0.57	-0.29	-0.14	0.03			
## entropy.v	0.88	-0.30	0.01	0.19	-0.19	0.10	0.54			
## mamr	0.37	0.02	0.14	0.28	-0.58	-0.12	0.21			
## hapaxes	-0.15	0.06	0.12	0.25	-0.28	-0.02	0.19			

```
## sentcount          0.04 -0.05  0.03  0.08 -0.30 -0.07  0.22
## verbdist           0.16 -0.22 -0.06  0.00 -0.15 -0.06  0.02
##
## Interfactor correlations and bootstrapped confidence intervals
##      lower estimate upper
## PA1-PA2 -0.12    0.0967  0.28
## PA1-PA7 -0.84   -0.6207  0.39
## PA1-PA4 -1.00   -0.2376  0.37
## PA1-PA6 -0.82    0.3499  0.59
## PA1-PA5 -0.64   -0.2707  0.34
## PA1-PA3 -0.51    0.0454  0.36
## PA1-PA9 -0.42   -0.0767  0.29
## PA1-PA8 -0.51   -0.3059  0.19
## PA2-PA7 -0.18    0.1877  0.56
## PA2-PA4 -0.18    0.3053  0.50
## PA2-PA6 -0.31   -0.2468  0.55
## PA2-PA5 -0.22    0.2910  0.48
## PA2-PA3 -0.23   -0.0695  0.36
## PA2-PA9 -0.16    0.2241  0.30
## PA2-PA8 -0.13    0.1123  0.29
## PA7-PA4 -0.57    0.3833  0.85
## PA7-PA6 -0.69   -0.3442  0.80
## PA7-PA5 -0.43    0.2951  0.59
## PA7-PA3 -0.39    0.0601  0.46
## PA7-PA9 -0.38    0.1252  0.38
## PA7-PA8 -0.39    0.3267  0.42
## PA4-PA6 -0.66   -0.4451  0.72
## PA4-PA5 -0.38    0.2418  0.55
## PA4-PA3 -0.36   -0.1289  0.49
## PA4-PA9 -0.43    0.2967  0.44
## PA4-PA8 -0.32    0.0521  0.45
## PA6-PA5 -0.44   -0.2453  0.38
## PA6-PA3 -0.37    0.1152  0.35
## PA6-PA9 -0.41   -0.3301  0.35
## PA6-PA8 -0.34   -0.0263  0.32
## PA5-PA3 -0.41   -0.1919  0.28
## PA5-PA9 -0.34   -0.0278  0.23
## PA5-PA8 -0.27    0.1108  0.33
## PA3-PA9 -0.33   -0.0975  0.29
## PA3-PA8 -0.31   -0.1472  0.35
## PA9-PA8 -0.25   -0.0015  0.33
```

Healthiness diagnostics

```
fa_1$loadings[] %>%
  as_tibble() %>%
  mutate(feats = cnames) %>%
  select(feats, everything()) %>%
  pivot_longer(!feats) %>%
  mutate(value = abs(value)) %>%
  group_by(feats) %>%
  summarize(maxload = max(value)) %>%
  arrange(maxload)
```

```
## # A tibble: 35 x 2
##   feat          maxload
##   <chr>         <dbl>
## 1 literary      0.267
## 2 compoundVERBsdist.v 0.292
## 3 NEGfrac.m     0.400
## 4 NOUNcount.v   0.424
## 5 predsubjdist.m 0.437
## 6 predsubjdist.v 0.463
## 7 VERBfrac.v    0.479
## 8 fkg1          0.516
## 9 predobjdist.v 0.525
## 10 entropy.v    0.561
## # i 25 more rows
```

```
fa_1$communality %>% sort()
```

```
##      literary compoundVERBsdist.v      NEGfrac.m      predobjdist.v
##      0.2416525      0.3296794      0.3601689      0.3729226
##      VERBfrac.v      predobjdist.m      NOUNcount.v      entropy.v
##      0.3755086      0.3826177      0.4082917      0.4184301
##      doubleADPdist.m compoundVERBsdist.m      predsubjdist.v      predsubjdist.m
##      0.4560091      0.4671012      0.4798399      0.4961259
##      doubleADPdist.v      subj      predorder.v      passives
##      0.5248710      0.5377723      0.5485923      0.5634874
##      VERBcomp      NEGcount.v      predorder.m      obj
##      0.5936647      0.6016981      0.6085826      0.7004213
##      cli      maentropy      mamr      compoundVERBs
##      0.7017128      0.7254411      0.7296938      0.7347473
##      hapaxes      verbdist      NOUNcount.m      entropy
##      0.7350817      0.7946721      0.8120502      0.8571486
##      sentcount      VERBfrac.m      activity      hpoint
##      0.8590817      0.9081530      0.9273428      0.9438129
##      NEGcount.m      fkg1      fre
##      0.9454264      0.9603051      1.0085624
```

```
fa_1$communality[fa_1$communality < 0.5] %>% names()
```

```
## [1] "doubleADPdist.m"      "literary"      "compoundVERBsdist.m"
## [4] "compoundVERBsdist.v" "predobjdist.m" "predobjdist.v"
## [7] "predsubjdist.m"      "predsubjdist.v" "VERBfrac.v"
## [10] "NEGfrac.m"      "NOUNcount.v"      "entropy.v"
```

```
fa_1$complexity %>% sort()
```

```
##      hpoint      NOUNcount.m      NEGcount.m      obj
##      1.021970      1.049967      1.107250      1.188772
##      predorder.v      predobjdist.v      passives      NEGcount.v
##      1.212926      1.217932      1.224465      1.226073
##      verbdist      predobjdist.m      doubleADPdist.m      hapaxes
##      1.257344      1.271641      1.280541      1.333635
##      sentcount compoundVERBsdist.m      VERBfrac.m      mamr
##      1.343466      1.349938      1.381732      1.456405
##      predorder.m      cli      entropy.v      maentropy
##      1.477622      1.599286      1.689031      1.690295
##      entropy      compoundVERBs      doubleADPdist.v      subj
```

```
##          1.724179          1.730186          1.880323          1.896206
##          activity      predsubjdist.v          fre      NOUNcount.v
##          2.005256          2.074407          2.141251          2.172268
##          VERBfrac.v          VERBcomp      NEGfrac.m          fkg1
##          2.419905          2.484551          2.775734          2.984126
##          literary compoundVERBsdist.v      predsubjdist.m
##          3.093669          3.146079          3.403237
```

```
fa_1$complexity[fa_1$complexity > 2] %>% names()
```

```
## [1] "VERBcomp"          "literary"          "compoundVERBsdist.v"
## [4] "predsubjdist.m"      "predsubjdist.v"    "VERBfrac.v"
## [7] "NEGfrac.m"          "NOUNcount.v"       "activity"
## [10] "fkg1"              "fre"
```

Feature engineering

```
data_engineered_1 <- data_scaled %>%
  # remove low-communality variables
  select(!c(
    doubleADPdist.m,
    doubleADPdist.v,
    literary,
    compoundVERBsdist.m,
    compoundVERBsdist.v,
    predobjdist.m,
    predobjdist.v,
    predsubjdist.v,
    VERBfrac.v,
    NEGfrac.m,
    NOUNcount.v,
    entropy.v
  )) %>%
  # remove confound variables
  select(!c(cli, fkg1, fre))

det(cor(data_engineered_1))
```

```
## [1] 1.282125e-07
```

```
KMO(data_engineered_1)
```

```
## Kaiser-Meyer-Olkin factor adequacy
## Call: KMO(r = data_engineered_1)
## Overall MSA = 0.83
## MSA for each item =
```


```
##          VERBcomp  compoundVERBs      passives  predorder.m  predorder.v
##          0.86      0.90      0.77      0.85      0.83
##          obj      subj predsubjdist.m  VERBfrac.m  NEGcount.m
##          0.56      0.93      0.80      0.88      0.72
##          NEGcount.v  NOUNcount.m  activity      entropy      hpoint
##          0.67      0.92      0.89      0.69      0.70
##          maentropy  mamr      hapaxes      sentcount  verbdist
##          0.60      0.91      0.77      0.74      0.92
```

second FA

No. of vectors

```
fa.parallel(data_engineered_1, fm = "pa", fa = "fa", n.iter = 20)
```

Parallel Analysis Scree Plots



```
## Parallel analysis suggests that the number of factors = 5 and the number of components = NA
```

Model

```
fa_2 <- fa(  
  data_engineered_1,  
  nfactors = 5,  
  fm = "pa",  
  rotate = "promax",  
  oblique.scores = TRUE,  
  scores = "tenBerge",  
  n.iter = 100  
)  
fa_2
```

```
## Factor Analysis with confidence intervals using method = fa(r = data_engineered_1, nfactors = 5, n.i  
##   scores = "tenBerge", fm = "pa", oblique.scores = TRUE)  
## Factor Analysis using method = pa  
## Call: fa(r = data_engineered_1, nfactors = 5, n.iter = 100, rotate = "promax",  
##   scores = "tenBerge", fm = "pa", oblique.scores = TRUE)  
## Standardized loadings (pattern matrix) based upon correlation matrix  
##           PA1  PA2  PA4  PA3  PA5  h2  u2 com  
## VERBcomp    0.23  0.05  0.61  0.05 -0.04 0.56 0.437 1.3  
## compoundVERBs 0.75  0.00 -0.12  0.09 -0.17 0.55 0.454 1.2
```



```

## passives      0.03  0.01 -0.60  0.23 -0.12 0.35 0.653 1.4
## predorder.m  -0.85 -0.03  0.02  0.00 -0.16 0.69 0.315 1.1
## predorder.v  -0.54  0.10  0.05  0.16 -0.02 0.35 0.649 1.3
## obj          -0.31  0.00  0.45  0.41 -0.05 0.46 0.543 2.8
## subj         0.61  0.14 -0.07  0.05 -0.28 0.52 0.481 1.6
## predsubjdist.m -0.54  0.02 -0.02 -0.04 -0.28 0.30 0.696 1.5
## VERBfrac.m   0.64 -0.04  0.42 -0.07 -0.10 0.88 0.116 1.8
## NEGcount.m   0.03 -0.10 -0.16  0.89  0.13 0.76 0.241 1.1
## NEGcount.v   0.26  0.05 -0.18  0.79  0.11 0.62 0.379 1.4
## NOUNcount.m  -0.82  0.04 -0.16 -0.17  0.10 0.81 0.193 1.2
## activity     0.49 -0.05  0.61 -0.02 -0.07 0.89 0.109 2.0
## entropy      0.03  0.76  0.03  0.10  0.46 0.86 0.144 1.7
## hpoint      -0.10  0.98 -0.03  0.03 -0.03 0.96 0.037 1.0
## maentropy    -0.09 -0.02  0.06  0.12  0.71 0.54 0.463 1.1
## mamr         0.65 -0.03  0.03 -0.03 -0.39 0.72 0.282 1.7
## hapaxes      0.14 -0.83  0.07 -0.04  0.25 0.75 0.255 1.3
## sentcount    0.22  0.87  0.10 -0.22  0.03 0.82 0.185 1.3
## verbdist     -0.69 -0.01 -0.39 -0.14 -0.06 0.79 0.211 1.7
##
##
##              PA1  PA2  PA4  PA3  PA5
## SS loadings      5.09 3.00 2.04 1.72 1.30
## Proportion Var    0.25 0.15 0.10 0.09 0.07
## Cumulative Var    0.25 0.40 0.51 0.59 0.66
## Proportion Explained 0.39 0.23 0.16 0.13 0.10
## Cumulative Proportion 0.39 0.61 0.77 0.90 1.00
##
## With factor correlations of
##      PA1  PA2  PA4  PA3  PA5
## PA1  1.00 0.11  0.39 -0.23 -0.21
## PA2  0.11 1.00  0.14  0.37  0.00
## PA4  0.39 0.14  1.00  0.08 -0.32
## PA3 -0.23 0.37  0.08  1.00  0.00
## PA5 -0.21 0.00 -0.32  0.00  1.00
##
## Mean item complexity = 1.5
## Test of the hypothesis that 5 factors are sufficient.
##
## df null model = 190 with the objective function = 15.87 with Chi Square = 11830.77
## df of the model are 100 and the objective function was 1.88
##
## The root mean square of the residuals (RMSR) is 0.03
## The df corrected root mean square of the residuals is 0.05
##
## The harmonic n.obs is 754 with the empirical chi square 335.06 with prob < 3.9e-27
## The total n.obs was 754 with Likelihood Chi Square = 1393.99 with prob < 7.3e-227
##
## Tucker Lewis Index of factoring reliability = 0.788
## RMSEA index = 0.131 and the 90 % confidence intervals are 0.125 0.137
## BIC = 731.45
## Fit based upon off diagonal values = 0.99
## Measures of factor score adequacy
##
##              PA1  PA2  PA4  PA3  PA5
## Correlation of (regression) scores with factors 0.97 0.99 0.93 0.93 0.9
## Multiple R square of scores with factors 0.94 0.98 0.87 0.86 0.8

```

```

## Minimum correlation of possible factor scores      0.87 0.96 0.74 0.72 0.6
##
## Coefficients and bootstrapped confidence intervals
##          low  PA1 upper  low  PA2 upper  low  PA4 upper  low
## VERBcomp      0.14  0.23  0.32 -0.02  0.05  0.11  0.45  0.61  0.78 -0.02
## compoundVERBs  0.53  0.75  0.92 -0.07  0.00  0.06 -0.25 -0.12  0.01  0.00
## passives      -0.09  0.03  0.14 -0.05  0.01  0.07 -0.75 -0.60 -0.46  0.14
## predorder.m   -0.94 -0.85 -0.71 -0.08 -0.03  0.02 -0.11  0.02  0.13 -0.08
## predorder.v   -0.64 -0.54 -0.40  0.04  0.10  0.17 -0.06  0.05  0.16  0.08
## obj           -0.40 -0.31 -0.18 -0.05  0.00  0.04  0.34  0.45  0.57  0.34
## subj          0.49  0.61  0.71  0.09  0.14  0.19 -0.17 -0.07  0.04 -0.01
## predsubjdist.m -0.67 -0.54 -0.40 -0.03  0.02  0.06 -0.16 -0.02  0.11 -0.12
## VERBfrac.m     0.49  0.64  0.77 -0.07 -0.04  0.00  0.30  0.42  0.56 -0.13
## NEGcount.m     -0.04  0.03  0.08 -0.13 -0.10 -0.05 -0.24 -0.16 -0.08  0.81
## NEGcount.v     0.17  0.26  0.31  0.01  0.05  0.10 -0.26 -0.18 -0.09  0.74
## NOUNcount.m    -0.96 -0.82 -0.62  0.00  0.04  0.07 -0.28 -0.16 -0.07 -0.22
## activity       0.39  0.49  0.58 -0.07 -0.05 -0.01  0.49  0.61  0.75 -0.07
## entropy       -0.03  0.03  0.09  0.72  0.76  0.81 -0.05  0.03  0.11  0.05
## hpoint        -0.13 -0.10 -0.05  0.95  0.98  1.00 -0.07 -0.03  0.02  0.01
## maentropy     -0.18 -0.09  0.00 -0.06 -0.02  0.02 -0.05  0.06  0.17  0.07
## mamr          0.49  0.65  0.78 -0.08 -0.03  0.02 -0.06  0.03  0.13 -0.09
## hapaxes       0.07  0.14  0.21 -0.86 -0.83 -0.80  0.00  0.07  0.15 -0.10
## sentcount     0.14  0.22  0.29  0.83  0.87  0.91  0.04  0.10  0.16 -0.28
## verbdist      -0.79 -0.69 -0.56 -0.04 -0.01  0.02 -0.53 -0.39 -0.29 -0.23
##
##          PA3 upper  low  PA5 upper
## VERBcomp      0.05  0.14 -0.12 -0.04  0.03
## compoundVERBs  0.09  0.20 -0.38 -0.17 -0.02
## passives      0.23  0.33 -0.27 -0.12  0.01
## predorder.m   0.00  0.10 -0.40 -0.16  0.06
## predorder.v   0.16  0.25 -0.11 -0.02  0.08
## obj           0.41  0.51 -0.12 -0.05  0.02
## subj          0.05  0.10 -0.47 -0.28 -0.15
## predsubjdist.m -0.04  0.04 -0.56 -0.28 -0.06
## VERBfrac.m    -0.07 -0.01 -0.22 -0.10 -0.03
## NEGcount.m     0.89  0.98  0.05  0.13  0.26
## NEGcount.v     0.79  0.85  0.04  0.11  0.20
## NOUNcount.m    -0.17 -0.12  0.01  0.10  0.21
## activity      -0.02  0.02 -0.13 -0.07 -0.03
## entropy       0.10  0.16  0.38  0.46  0.61
## hpoint        0.03  0.06 -0.07 -0.03  0.02
## maentropy     0.12  0.20  0.63  0.71  0.92
## mamr         -0.03  0.02 -0.67 -0.39 -0.20
## hapaxes      -0.04  0.01  0.20  0.25  0.33
## sentcount    -0.22 -0.17 -0.02  0.03  0.09
## verbdist     -0.14 -0.05 -0.15 -0.06  0.01
##
## Interfactor correlations and bootstrapped confidence intervals
##          lower estimate upper
## PA1-PA2 -0.28  0.1079  0.34
## PA1-PA4 -0.81  0.3904  0.60
## PA1-PA3 -0.68 -0.2280  0.63
## PA1-PA5 -0.42 -0.2124  0.45
## PA2-PA4 -0.18  0.1382  0.48
## PA2-PA3 -0.20  0.3711  0.62

```

```
## PA2-PA5 -0.22 -0.0046 0.38
## PA4-PA3 -0.35 0.0840 0.40
## PA4-PA5 -0.44 -0.3245 0.47
## PA3-PA5 -0.24 0.0013 0.26
```

Healthiness diagnostics

```
fa_2$loadings[] %>%
  as_tibble() %>%
  mutate(feats = colnames(data_engineered_1)) %>%
  select(feats, everything()) %>%
  pivot_longer(!feats) %>%
  mutate(value = abs(value)) %>%
  group_by(feats) %>%
  summarize(maxload = max(value)) %>%
  arrange(maxload)
```

```
## # A tibble: 20 x 2
##   feat          maxload
##   <chr>          <dbl>
## 1 obj          0.447
## 2 predsubjdist.m 0.544
## 3 predorder.v    0.544
## 4 passives      0.603
## 5 VERBcomp      0.606
## 6 subj          0.613
## 7 activity      0.614
## 8 VERBfrac.m    0.644
## 9 mamr          0.650
## 10 verbdist     0.687
## 11 maentropy     0.714
## 12 compoundVERBs 0.746
## 13 entropy       0.764
## 14 NEGcount.v    0.794
## 15 NOUNcount.m   0.817
## 16 hapaxes       0.829
## 17 predorder.m   0.850
## 18 sentcount     0.870
## 19 NEGcount.m    0.888
## 20 hpoint       0.976
```

```
fa_2$communality %>% sort()
```

## predsubjdist.m	passives	predorder.v	obj	subj
## 0.3037867	0.3468791	0.3505151	0.4574124	0.5188582
## maentropy	compoundVERBs	VERBcomp	NEGcount.v	predorder.m
## 0.5372362	0.5461787	0.5627326	0.6208769	0.6852554
## mamr	hapaxes	NEGcount.m	verbdist	NOUNcount.m
## 0.7184793	0.7454838	0.7586160	0.7893884	0.8071030
## sentcount	entropy	VERBfrac.m	activity	hpoint
## 0.8150467	0.8557144	0.8841659	0.8906305	0.9625622

```
fa_2$communality[fa_2$communality < 0.5] %>% names()
```

```
## [1] "passives"      "predorder.v"   "obj"           "predsubjdist.m"
```

```
fa_2$complexity %>% sort()
```

```
##          hpoint    predorder.m    maentropy    NEGcount.m    compoundVERBs
##      1.026114      1.070268      1.109904      1.141679      1.197415
##    NOUNcount.m    predorder.v      hapaxes      sentcount      VERBcomp
##      1.203861      1.263880      1.270866      1.295166      1.310073
##    NEGcount.v      passives    predsubjdist.m      subj      mamr
##      1.369062      1.393392      1.515239      1.582351      1.661518
##      entropy      verbdist      VERBfrac.m      activity      obj
##      1.688315      1.704079      1.823346      1.950707      2.812552
```

```
fa_2$complexity[fa_2$complexity > 2] %>% names()
```

```
## [1] "obj"
```

Feature engineering

```
data_engineered_2 <- data_engineered_1 %>%
  # remove low-communality features
  select(!c(
    passives,
    predorder.v,
    obj,
    predsubjdist.m
  ))
```

```
det(cor(data_engineered_2))
```

```
## [1] 1.289469e-06
```

```
KMO(data_engineered_2)
```

```
## Kaiser-Meyer-Olkin factor adequacy
## Call: KMO(r = data_engineered_2)
## Overall MSA = 0.84
## MSA for each item =
```

```
##      VERBcomp    compoundVERBs    predorder.m      subj    VERBfrac.m
##      0.84      0.94      0.94      0.94      0.86
##    NEGcount.m    NEGcount.v    NOUNcount.m    activity    entropy
##      0.66      0.64      0.91      0.88      0.72
##      hpoint    maentropy      mamr      hapaxes      sentcount
##      0.70      0.65      0.90      0.77      0.77
##      verbdist
##      0.90
```


```
final_collist <- data_engineered_2 %>% colnames()
```

Final FA

No. of vectors

```
fa.parallel(data_engineered_2, fm = "pa", fa = "fa", n.iter = 20)
```

Parallel Analysis Scree Plots



Parallel analysis suggests that the number of factors = 5 and the number of components = NA

Model

```
fa_res <- fa(
  data_engineered_2,
  nfactors = 5,
  fm = "pa",
  rotate = "promax",
  oblique.scores = TRUE,
  scores = "tenBerge",
  n.iter = 100
)
fa_res
```

```
## Factor Analysis with confidence intervals using method = fa(r = data_engineered_2, nfactors = 5, n.i
##   scores = "tenBerge", fm = "pa", oblique.scores = TRUE)
## Factor Analysis using method = pa
## Call: fa(r = data_engineered_2, nfactors = 5, n.iter = 100, rotate = "promax",
##   scores = "tenBerge", fm = "pa", oblique.scores = TRUE)
## Standardized loadings (pattern matrix) based upon correlation matrix
##           PA1  PA2  PA5  PA3  PA4  h2  u2 com
## VERBcomp    0.16  0.09  0.60  0.01 -0.01 0.52 0.482 1.2
## compoundVERBs 0.79 -0.05 -0.08  0.02  0.00 0.53 0.465 1.0
## predorder.m -0.76  0.02  0.02  0.03 -0.12 0.52 0.482 1.1
## subj        0.75  0.11 -0.16  0.00 -0.14 0.54 0.459 1.2
## VERBfrac.m   0.61 -0.06  0.43 -0.06 -0.03 0.90 0.096 1.9
## NEGcount.m  -0.11 -0.05  0.04  0.91  0.00 0.83 0.170 1.0
## NEGcount.v   0.17  0.07 -0.03  0.80  0.02 0.68 0.322 1.1
## NOUNcount.m -0.89  0.07 -0.09 -0.10 -0.02 0.84 0.165 1.1
```

```

## activity      0.39 -0.03  0.65  0.00 -0.06  0.91  0.095 1.7
## entropy      0.10  0.71 -0.06  0.01  0.55  0.95  0.055 1.9
## hpoint      -0.13  0.99  0.04  0.06 -0.05  0.96  0.040 1.1
## maentropy    -0.08 -0.11 -0.03  0.01  0.77  0.64  0.358 1.1
## mamr         0.74 -0.04 -0.02 -0.05 -0.26  0.71  0.287 1.3
## hapaxes      0.18 -0.88 -0.01 -0.09  0.29  0.77  0.229 1.3
## sentcount    0.22  0.80  0.09 -0.15  0.05  0.77  0.232 1.3
## verbdist     -0.69  0.00 -0.29 -0.07 -0.10  0.75  0.247 1.4
##
##
##          PA1  PA2  PA5  PA3  PA4
## SS loadings      4.67 2.95 1.53 1.52 1.15
## Proportion Var    0.29 0.18 0.10 0.10 0.07
## Cumulative Var    0.29 0.48 0.57 0.67 0.74
## Proportion Explained 0.39 0.25 0.13 0.13 0.10
## Cumulative Proportion 0.39 0.64 0.77 0.90 1.00
##
## With factor correlations of
##          PA1  PA2  PA5  PA3  PA4
## PA1  1.00 0.18  0.60 -0.17 -0.26
## PA2  0.18 1.00  0.07  0.29  0.16
## PA5  0.60 0.07  1.00 -0.17 -0.15
## PA3 -0.17 0.29 -0.17  1.00  0.28
## PA4 -0.26 0.16 -0.15  0.28  1.00
##
## Mean item complexity = 1.3
## Test of the hypothesis that 5 factors are sufficient.
##
## df null model = 120 with the objective function = 13.56 with Chi Square = 10128.02
## df of the model are 50 and the objective function was 0.76
##
## The root mean square of the residuals (RMSR) is 0.02
## The df corrected root mean square of the residuals is 0.03
##
## The harmonic n.obs is 754 with the empirical chi square 60.5 with prob < 0.15
## The total n.obs was 754 with Likelihood Chi Square = 562.84 with prob < 6.5e-88
##
## Tucker Lewis Index of factoring reliability = 0.876
## RMSEA index = 0.117 and the 90 % confidence intervals are 0.108 0.125
## BIC = 231.57
## Fit based upon off diagonal values = 1
## Measures of factor score adequacy
##
##          PA1  PA2  PA5  PA3  PA4
## Correlation of (regression) scores with factors 0.97 0.99 0.94 0.94 0.94
## Multiple R square of scores with factors 0.94 0.98 0.88 0.88 0.88
## Minimum correlation of possible factor scores 0.89 0.97 0.76 0.76 0.75
##
## Coefficients and bootstrapped confidence intervals
##          low  PA1 upper  low  PA2 upper  low  PA5 upper  low  PA3
## VERBcomp    0.04  0.16  0.28  0.05  0.09  0.14  0.45  0.60  0.81 -0.04  0.01
## compoundVERBs 0.69  0.79  0.86 -0.10 -0.05 -0.01 -0.18 -0.08  0.03 -0.04  0.02
## predorder.m -0.91 -0.76 -0.62 -0.03  0.02  0.07 -0.10  0.02  0.13 -0.06  0.03
## subj        0.64  0.75  0.82  0.07  0.11  0.16 -0.27 -0.16 -0.02 -0.04  0.00
## VERBfrac.m   0.52  0.61  0.72 -0.09 -0.06 -0.03  0.31  0.43  0.58 -0.10 -0.06
## NEGcount.m  -0.15 -0.11 -0.06 -0.08 -0.05 -0.02  0.00  0.04  0.09  0.83  0.91

```

```

## NEGcount.v      0.12  0.17  0.22  0.04  0.07  0.12 -0.09 -0.03  0.02  0.70  0.80
## NOUNcount.m    -0.98 -0.89 -0.78  0.04  0.07  0.11 -0.18 -0.09 -0.03 -0.15 -0.10
## activity        0.29  0.39  0.53 -0.07 -0.03 -0.01  0.45  0.65  0.88 -0.03  0.00
## entropy         0.05  0.10  0.13  0.68  0.71  0.74 -0.11 -0.06 -0.01 -0.02  0.01
## hpoint          -0.16 -0.13 -0.10  0.96  0.99  1.01  0.00  0.04  0.07  0.03  0.06
## maentropy       -0.13 -0.08 -0.03 -0.14 -0.11 -0.08 -0.09 -0.03  0.03 -0.02  0.01
## mamr            0.64  0.74  0.82 -0.09 -0.04  0.01 -0.14 -0.02  0.12 -0.11 -0.05
## hapaxes         0.12  0.18  0.24 -0.91 -0.88 -0.85 -0.07 -0.01  0.04 -0.13 -0.09
## sentcount       0.15  0.22  0.30  0.77  0.80  0.84  0.02  0.09  0.17 -0.18 -0.15
## verbdist        -0.78 -0.69 -0.62 -0.03  0.00  0.03 -0.45 -0.29 -0.18 -0.11 -0.07
##                upper    low    PA4 upper
## VERBcomp        0.06 -0.06 -0.01  0.04
## compoundVERBs    0.08 -0.06  0.00  0.05
## predorder.m     0.13 -0.18 -0.12 -0.06
## subj            0.06 -0.20 -0.14 -0.08
## VERBfrac.m      -0.02 -0.07 -0.03  0.01
## NEGcount.m       1.01 -0.04  0.00  0.03
## NEGcount.v       0.87 -0.02  0.02  0.08
## NOUNcount.m     -0.06 -0.07 -0.02  0.02
## activity         0.04 -0.10 -0.06 -0.02
## entropy          0.04  0.49  0.55  0.60
## hpoint           0.08 -0.07 -0.05 -0.02
## maentropy        0.05  0.73  0.77  0.84
## mamr             0.00 -0.32 -0.26 -0.20
## hapaxes          -0.04  0.24  0.29  0.33
## sentcount        -0.11  0.01  0.05  0.10
## verbdist         -0.01 -0.14 -0.10 -0.06
##
## Interfactor correlations and bootstrapped confidence intervals
##                lower estimate upper
## PA1-PA2  0.085    0.183  0.26
## PA1-PA5 -0.629    0.604  0.98
## PA1-PA3 -0.676   -0.168  0.81
## PA1-PA4 -0.597   -0.261  0.33
## PA2-PA5 -0.015    0.069  0.41
## PA2-PA3 -0.032    0.289  0.38
## PA2-PA4 -0.033    0.162  0.29
## PA5-PA3 -0.456   -0.173  0.31
## PA5-PA4 -0.411   -0.155  0.44
## PA3-PA4 -0.380    0.284  0.48

```

Healthiness diagnostics

```

fa_res$loadings[] %>%
  as_tibble() %>%
  mutate(feats = colnames(data_engineered_2)) %>%
  select(feats, everything()) %>%
  pivot_longer(!feats) %>%
  mutate(value = abs(value)) %>%
  group_by(feats) %>%
  summarize(maxload = max(value)) %>%
  arrange(maxload)

```

```
## # A tibble: 16 x 2
```

```
##      feat      maxload
##      <chr>      <dbl>
##  1 VERBcomp      0.596
##  2 VERBfrac.m    0.607
##  3 activity      0.651
##  4 verbdist      0.694
##  5 entropy       0.711
##  6 mamr          0.737
##  7 subj          0.746
##  8 predorder.m   0.756
##  9 maentropy     0.775
## 10 compoundVERBs 0.785
## 11 NEGcount.v    0.800
## 12 sentcount     0.800
## 13 hapaxes       0.884
## 14 NOUNcount.m   0.888
## 15 NEGcount.m    0.907
## 16 hpoint        0.985
```

```
fa_res$communality %>% sort()
```

```
##      VERBcomp  predorder.m  compoundVERBs      subj      maentropy
##      0.5177499    0.5183563    0.5349995    0.5414778    0.6418761
##      NEGcount.v      mamr      verbdist      sentcount      hapaxes
##      0.6782765    0.7133565    0.7530430    0.7675342    0.7707273
##      NEGcount.m  NOUNcount.m  VERBfrac.m      activity      entropy
##      0.8304061    0.8350764    0.9038775    0.9052379    0.9451047
##      hpoint
##      0.9601740
```

```
fa_res$communality[fa_res$communality < 0.5] %>% names()
```

```
## character(0)
```

```
fa_res$complexity %>% sort()
```

```
## compoundVERBs  NEGcount.m      hpoint  predorder.m  NOUNcount.m
##      1.029554    1.039301    1.050565    1.057554    1.063257
##      maentropy  NEGcount.v      VERBcomp      subj      sentcount
##      1.063520    1.113116    1.193647    1.212563    1.260463
##      mamr      hapaxes      verbdist      activity  VERBfrac.m
##      1.261246    1.317476    1.397513    1.667989    1.864981
##      entropy
##      1.941602
```

```
fa_res$complexity[fa_res$complexity > 2] %>% names()
```


```
## character(0)
```

Loadings

Comrey and Lee (1992): loadings excelent > .70 > very good > .63 > good > .55 > fair > .45 > poor > .32

```
fa.diagram(fa_res)
```


Factor Analysis



```
fa_res$loadings
```

```
##
## Loadings:
##          PA1    PA2    PA5    PA3    PA4
## VERBcomp      0.159      0.596
## compoundVERBs 0.785
## predorder.m  -0.756      -0.120
## subj          0.746  0.115 -0.157      -0.139
## VERBfrac.m    0.607      0.432
## NEGcount.m    -0.110      0.907
## NEGcount.v    0.171      0.800
## NOUNcount.m  -0.888      -0.103
## activity      0.391      0.651
## entropy       0.711      0.547
## hpoint       -0.134  0.985
## maentropy     -0.109      0.775
## mamr          0.737      -0.258
## hapaxes       0.179 -0.884      0.286
## sentcount     0.217  0.800     -0.150
## verbdist     -0.694     -0.285
##
##          PA1    PA2    PA5    PA3    PA4
## SS loadings  4.259 2.954 1.103 1.519 1.102
## Proportion Var 0.266 0.185 0.069 0.095 0.069
## Cumulative Var 0.266 0.451 0.520 0.615 0.684
```

```
for (i in 1:fa_res$nfactors) {
  cat("\n-----", colnames(fa_res$loadings)[i], "-----\n")
}
```

```

loadings <- fa_res$loadings[, i]
load_df <- data.frame(loading = loadings)

load_df_filtered <- load_df %>%
  mutate(abs_l = abs(loading)) %>%
  mutate(str = case_when(
    abs_l > 0.70 ~ "****",
    abs_l <= 0.70 & abs_l > 0.63 ~ "*** ",
    abs_l <= 0.63 & abs_l > 0.55 ~ "**  ",
    abs_l <= 0.55 & abs_l > 0.45 ~ "*   ",
    abs_l <= 0.45 & abs_l > 0.32 ~ ".    ",
    .default = ""
  )) %>%
  arrange(-abs_l) %>%
  filter(abs_l > 0.1)

load_df_filtered %>%
  mutate(across(c(loading, abs_l), ~ round(.x, 3))) %>%
  print()

cat("\n")
}

```

```

##
## ----- PA1 -----
##           loading abs_l str
## NOUNcount.m   -0.888 0.888 ****
## compoundVERBs  0.785 0.785 ****
## predorder.m   -0.756 0.756 ****
## subj          0.746 0.746 ****
## mamr          0.737 0.737 ****
## verbdist      -0.694 0.694 ***
## VERBfrac.m    0.607 0.607 **
## activity      0.391 0.391 .
## sentcount     0.217 0.217
## hapaxes       0.179 0.179
## NEGcount.v    0.171 0.171
## VERBcomp      0.159 0.159
## hpoint        -0.134 0.134
## NEGcount.m    -0.110 0.110
##
##
## ----- PA2 -----
##           loading abs_l str
## hpoint        0.985 0.985 ****
## hapaxes      -0.884 0.884 ****
## sentcount     0.800 0.800 ****
## entropy       0.711 0.711 ****
## subj         0.115 0.115
## maentropy     -0.109 0.109
##
##
## ----- PA5 -----

```

```

##          loading abs_l  str
## activity      0.651 0.651 ***
## VERBcomp      0.596 0.596 **
## VERBfrac.m    0.432 0.432 .
## verbdist     -0.285 0.285
## subj         -0.157 0.157
##
##
## ----- PA3 -----
##          loading abs_l  str
## NEGcount.m     0.907 0.907 ****
## NEGcount.v     0.800 0.800 ****
## sentcount     -0.150 0.150
## NOUNcount.m   -0.103 0.103
##
##
## ----- PA4 -----
##          loading abs_l  str
## maentropy      0.775 0.775 ****
## entropy       0.547 0.547 *
## hapaxes       0.286 0.286
## mamr         -0.258 0.258
## subj         -0.139 0.139
## predorder.m  -0.120 0.120

```

hypotheses:

- **PA1:** register – narrativity, richness of expression; shorter clauses (-technical / +narrative)
 - long nominal constr., predicate far down, verbs far apart / compound verbs, overt subjects, morphologically diverse, more verbs, activity
- **PA2:** text length (-short / +long)
 - hapaxes load negatively, because I normed them over word count
- **PA5:** activity (-passive / +active)
 - more adjectives / many verbs, more verbcomps
 - nothing to do with compound verbs
 - but something to do with verbal complements
 - UPOS of passives annotated as ADJ in UD
- **PA3:** negations (-less negated / +more negated)
- **PA4:** lexical richness (-poor / +rich)

strong correlations (but not necessarily significant):

- **PA1+PA5** (-0.67 / **+0.60** / +0.81): narrative texts are active, technical texts are passive

significant correlations (CIs not spanning over 0):

- **PA1+PA2** (+0.10 / **+0.18** / +0.26): narrative texts tend to be slightly longer
 - strange? but the correlation isn't as strong
- **PA2+PA5** (+0.00 / **+0.07** / +0.45): longer texts are more active
 - PA2 behavior opposite to what one would expect

NOTE: variables with low communalities are excluded from the analysis, yet still likely play a role in legal writing readability. this includes both those selected for the analysis and the excluded ones.

NOTE: some high-correlating variables were excluded from the FA.

Uniquenesses

```
fa_res$uniquenesses %>% round(3)
```

```
##      VERBcomp compoundVERBs  predorder.m      subj  VERBfrac.m
##      0.482      0.465      0.482      0.459      0.096
##      NEGcount.m  NEGcount.v  NOUNcount.m  activity  entropy
##      0.170      0.322      0.165      0.095      0.055
##      hpoint      maentropy      mamr      hapaxes  sentcount
##      0.040      0.358      0.287      0.229      0.232
##      verbdist
##      0.247
```

Distributions over factors

```
analyze_distributions <- function(data_factors_long, variable) {
  plot <- data_factors_long %>%
    ggplot(aes(x = factor_score, y = !!sym(variable))) +
    geom_boxplot() +
    facet_grid(factor ~ .)
  print(plot)

  formula <- reformulate(variable, "factor_score")
  factors <- levels(data_factors_long$factor)

  min_p_values <- numeric()
  for (f in factors) {
    data <- data_factors_long %>% filter(factor == f)

    cat(
      "\nTest for the significance of differences in",
      variable, "over", f, ":\n\n"
    )

    dunn <- dunn.test(
      data$factor_score, data[[variable]],
      alt = TRUE, method = "bonferroni"
    )
    min_p_values <- c(min_p_values, min(dunn$altP.adjusted))
  }

  cat(
    "\np < 5e-2\tfound in:",
    factors[min_p_values < 0.05],
    "\np < 1e-2\tfound in:",
    factors[min_p_values < 0.01],
    "\np < 1e-3\tfound in:",
    factors[min_p_values < 0.001],
    "\np < 1e-4\tfound in:",
    factors[min_p_values < 0.0001], "\n"
  )
}

data_factors <- bind_cols(data_clean, fa_res$scores %>% as.data.frame())
```


```

cnames <- map(
  colnames(data_factors),
  function(x) {
    name <- pull(pretty_names %>%
      filter(name_orig == x), name_pretty)
    if (length(name) == 1) {
      return(name)
    } else {
      return(x)
    }
  }
) %>% unlist()
colnames(data_factors) <- cnames

data_factors_long <- data_factors %>%
  pivot_longer(PA1:PA4, names_to = "factor", values_to = "factor_score") %>%
  mutate(across(
    factor,
    ~ factor(.x, levels = c("PA1", "PA2", "PA5", "PA3", "PA4"))
  ))


data_factors_long %>%
  ggplot(aes(x = factor_score, y = class)) +
  facet_grid(factor ~ .) +
  theme(legend.position = "bottom") +
  geom_jitter(width = 0, height = 0.1, alpha = 0.2)

```



class

```
analyze_distributions(data_factors_long, "class")
```



```
##
## Test for the significance of differences in class over PA1 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 126.7269, df = 1, p-value = 0
##
##
##               Comparison of x by group
##               (Bonferroni)
## Col Mean-|
## Row Mean |      bad
## -----+-----
##    good | -11.25730
##         |  0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in class over PA2 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 4.3681, df = 1, p-value = 0.04
##
```

```

##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |          bad
## -----+-----
##      good |    2.089988
##          |    0.0366*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in class over PA5 :
##
##      Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 66.1797, df = 1, p-value = 0
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |          bad
## -----+-----
##      good |   -8.135091
##          |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in class over PA3 :
##
##      Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 32.512, df = 1, p-value = 0
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |          bad
## -----+-----
##      good |    5.701925
##          |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in class over PA4 :
##
##      Kruskal-Wallis rank sum test
##


```



```
## data: x and group
## Kruskal-Wallis chi-squared = 42.0912, df = 1, p-value = 0
##
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean |      bad
## -----+-----
##      good |  6.487771
##           |  0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA5 PA3 PA4
```

subcorpus

```
analyze_distributions(data_factors_long, "subcorpus")
```



```
##
## Test for the significance of differences in subcorpus over PA1 :
##
```

```

## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 367.4879, df = 4, p-value = 0
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY      LiFRLaw
## -----+-----
## FrBo | -18.12656
##      | 0.0000*
##
## KUKY | -4.397196  12.79333
##      | 0.0001*   0.0000*
##
## LiFRLaw | -1.688090  1.090683 -0.935521
##      | 0.9139   1.0000   1.0000
##
## OmbuFlye | -5.873484  3.374214 -3.361550 -0.087571
##      | 0.0000*  0.0074*  0.0078*   1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA2 :
##
## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 4.895, df = 4, p-value = 0.3
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY      LiFRLaw
## -----+-----
## FrBo | 0.691349
##      | 1.0000
##
## KUKY | 1.649817  1.113294
##      | 0.9898   1.0000
##
## LiFRLaw | 1.400227  1.297050  1.117258
##      | 1.0000   1.0000   1.0000
##
## OmbuFlye | -0.234238 -0.597786 -1.155916 -1.426199
##      | 1.0000   1.0000   1.0000   1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##

```

```


## Test for the significance of differences in subcorpus over PA5 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 110.959, df = 4, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY      LiFRLaw
## -----+-----
##   FrBo | -10.16261
##         |  0.0000*
##         |
##   KUKY | -6.687235  2.611257
##         |  0.0000*  0.0902
##         |
## LiFRLaw |  0.571656  2.132759  1.713677
##         |  1.0000  0.3294  0.8659
##         |
## OmbuFlye | -4.799832  0.349228 -1.014940 -1.963114
##         |  0.0000*  1.0000  1.0000  0.4963
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA3 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 100.0432, df = 4, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY      LiFRLaw
## -----+-----
##   FrBo |  9.887361
##         |  0.0000*
##         |
##   KUKY |  4.675599 -4.518170
##         |  0.0000*  0.0001*
##         |
## LiFRLaw |  1.855136  0.341381  1.054870
##         |  0.6358  1.0000  1.0000
##         |
## OmbuFlye |  3.769452 -1.261441  1.119595 -0.691979
##         |  0.0016*  1.0000  1.0000  1.0000
##
## alpha = 0.05

```

```
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA4 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 24.5286, df = 4, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY      LiFRLaw
## -----+-----
##   FrBo |      4.228071
##         |      0.0002*
##         |
##   KUKY |      2.074281   -1.851174
##         |      0.3805      0.6414
##         |
## LiFRLaw |     -0.423701   -1.073575   -0.777744
##         |      1.0000      1.0000      1.0000
##         |
## OmbuFlye |    -1.086128   -3.301276   -2.238183    0.091937
##         |      1.0000      0.0096*      0.2521      1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA5 PA3
```

subcorpus wo/ LiFRLaw

```
analyze_distributions(
  data_factors_long %>% filter(subcorpus != "LiFRLaw"), "subcorpus"
)
```



```
##
## Test for the significance of differences in subcorpus over PA1 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 367.2784, df = 3, p-value = 0
##
##
##           Comparison of x by group
##           (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY
## -----|-----
##   FrBo | -18.12400
##         |  0.0000*
##         |
##   KUKY | -4.398355  12.78960
##         |  0.0001*  0.0000*
##         |
## OmbuFlye | -5.870726  3.375713 -3.358166
##         |  0.0000*  0.0044*  0.0047*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA2 :
```

```


##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 3.2066, df = 3, p-value = 0.36
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY
## -----+-----
##      FrBo |      0.707561
##            |      1.0000
##            |
##      KUKY |      1.650663      1.098516
##            |      0.5928      1.0000
##            |
## OmbuFlye |     -0.225616     -0.597355     -1.147841
##            |      1.0000      1.0000      1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA5 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 108.5966, df = 3, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY
## -----+-----
##      FrBo |     -10.16932
##            |      0.0000*
##            |
##      KUKY |     -6.695230      2.609106
##            |      0.0000*      0.0545
##            |
## OmbuFlye |     -4.798707      0.353850     -1.009348
##            |      0.0000*      1.0000      1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA3 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group

```

```
## Kruskal-Wallis chi-squared = 99.1033, df = 3, p-value = 0
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY
## -----+-----
##      FrBo |      9.888077
##            |      0.0000*
##            |
##      KUKY |      4.673653      -4.520964
##            |      0.0000*      0.0000*
##            |
## OmbuFlye |      3.769553      -1.261709      1.120783
##            |      0.0010*      1.0000      1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in subcorpus over PA4 :
##
##      Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 23.972, df = 3, p-value = 0
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |      CzCDC      FrBo      KUKY
## -----+-----
##      FrBo |      4.230854
##            |      0.0001*
##            |
##      KUKY |      2.078297      -1.849528
##            |      0.2261      0.3863
##            |
## OmbuFlye |     -1.086490     -3.303088     -2.240791
##            |      1.0000      0.0057*      0.1502
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA5 PA3
```

AuthorType

```
analyze_distributions(data_factors_long, "AuthorType")
```



```
##
## Test for the significance of differences in AuthorType over PA1 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 340.431, df = 1, p-value = 0
##
##
##           Comparison of x by group
##           (Bonferroni)
## Col Mean-|
## Row Mean |   authorit
## -----+-----
## individu | -18.45077
##           |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in AuthorType over PA2 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 1.7006, df = 1, p-value = 0.19
##
```



```


##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |   authorit
## -----+-----
## individu |   1.304053
##          |   0.1922
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in AuthorType over PA5 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 43.8958, df = 1, p-value = 0
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |   authorit
## -----+-----
## individu |  -6.625390
##          |   0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in AuthorType over PA3 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 60.8503, df = 1, p-value = 0
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |   authorit
## -----+-----
## individu |   7.800661
##          |   0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in AuthorType over PA4 :
##
##   Kruskal-Wallis rank sum test
##

```

```
## data: x and group
## Kruskal-Wallis chi-squared = 17.5505, df = 1, p-value = 0
##
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean |   authorit
## -----+-----
## individu |   4.189331
##          |   0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA5 PA3 PA4
```

RecipientType

```
analyze_distributions(data_factors_long, "RecipientType")
```



```
##
## Test for the significance of differences in RecipientType over PA1 :
##
```

```

## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 274.7923, df = 2, p-value = 0
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean | combined legal pe
## -----+-----
## legal pe | -3.556014
##          | 0.0011*
##          |
## natural  | -16.57496 -2.247529
##          | 0.0000* 0.0738
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientType over PA2 :
##
## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 23.3807, df = 2, p-value = 0
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean | combined legal pe
## -----+-----
## legal pe | 3.882907
##          | 0.0003*
##          |
## natural  | 3.599127 -2.650511
##          | 0.0010* 0.0241*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientType over PA5 :
##
## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 92.961, df = 2, p-value = 0
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean | combined legal pe

```

```

## -----+-----
## legal pe |    0.192234
##          |    1.0000
##          |
## natural  |   -9.407062  -3.505768
##          |    0.0000*    0.0014*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientType over PA3 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 101.3913, df = 2, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |    combined    legal pe
## -----+-----
## legal pe |    1.259825
##          |    0.6232
##          |
## natural  |    10.04052    2.263746
##          |    0.0000*    0.0708
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientType over PA4 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 21.9911, df = 2, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |    combined    legal pe
## -----+-----
## legal pe |    1.256302
##          |    0.6270
##          |
## natural  |    4.677943    0.379369
##          |    0.0000*    1.0000
##
## alpha = 0.05
## Reject Ho if p <= alpha
##


```

```
## p < 5e-2 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA5 PA3 PA4
```

court decisions often with RecipientType = combined.

RecipientIndividuation

```
analyze_distributions(data_factors_long, "RecipientIndividuation")
```



```
##
## Test for the significance of differences in RecipientIndividuation over PA1 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 213.054, df = 2, p-value = 0
##
##
##           Comparison of x by group
##           (Bonferroni)
## Col Mean-|
## Row Mean |      bulk  individu
## -----+-----
## individu | -0.658353
##          |      1.0000
##          |
```

```

## public | -8.680142 -13.83849
##         | 0.0000* 0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientIndividuation over PA2 :
##
## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 39.4788, df = 2, p-value = 0
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean | bulk individu
## -----+-----
## individu | 5.840692
##         | 0.0000*
##         |
## public | 3.555540 -3.832922
##         | 0.0011* 0.0004*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientIndividuation over PA5 :
##
## Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 72.9615, df = 2, p-value = 0
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean | bulk individu
## -----+-----
## individu | 2.905428
##         | 0.0110*
##         |
## public | -2.069169 -8.521702
##         | 0.1156 0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientIndividuation over PA3 :
##
## Kruskal-Wallis rank sum test
##

```


```

## data: x and group
## Kruskal-Wallis chi-squared = 45.7366, df = 2, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      bulk    individu
## -----+-----
## individu |    0.536624
##          |    1.0000
##          |
##   public |    4.205896    6.334174
##          |    0.0001*    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in RecipientIndividuation over PA4 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 39.7899, df = 2, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      bulk    individu
## -----+-----
## individu |    1.758924
##          |    0.2358
##          |
##   public |    4.838917    5.340624
##          |    0.0000*    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA2 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA2 PA5 PA3 PA4

```

Objectivity

```
analyze_distributions(data_factors_long, "Objectivity")
```



```
##
## Test for the significance of differences in Objectivity over PA1 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 0.5086, df = 1, p-value = 0.48
##
##
##               Comparison of x by group
##               (Bonferroni)
## Col Mean-|
## Row Mean |   persuasi
## -----+-----
## quasiobj |   0.713161
##          |   0.4757
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Objectivity over PA2 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 5.3827, df = 1, p-value = 0.02
##
```



```


##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |   persuasi
## -----+-----
## quasiobj |  -2.320070
##           |    0.0203*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Objectivity over PA5 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 5.8222, df = 1, p-value = 0.02
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |   persuasi
## -----+-----
## quasiobj |  -2.412913
##           |    0.0158*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Objectivity over PA3 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 0.5808, df = 1, p-value = 0.45
##
##
##                                     Comparison of x by group
##                                     (Bonferroni)
## Col Mean-|
## Row Mean |   persuasi
## -----+-----
## quasiobj |   0.762133
##           |   0.4460
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Objectivity over PA4 :
##
##   Kruskal-Wallis rank sum test
##

```

```
## data: x and group
## Kruskal-Wallis chi-squared = 0.3873, df = 1, p-value = 0.53
##
##
##
## Comparison of x by group
## (Bonferroni)
## Col Mean-|
## Row Mean |   persuasi
## -----+-----
## quasiobj | -0.622358
##          |    0.5337
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA2 PA5
## p < 1e-2 found in:
## p < 1e-3 found in:
## p < 1e-4 found in:
```

Bindingness

```
analyze_distributions(data_factors_long, "Bindingness")
```



```
##
## Test for the significance of differences in Bindingness over PA1 :
##
```

```

##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 356.1166, df = 1, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      FALSE
## -----+-----
##      TRUE |    18.87105
##           |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Bindingness over PA2 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 0.8725, df = 1, p-value = 0.35
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      FALSE
## -----+-----
##      TRUE |   -0.934087
##           |    0.3503
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Bindingness over PA5 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 97.2718, df = 1, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      FALSE
## -----+-----
##      TRUE |    9.862645
##           |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha

```

```
##
## Test for the significance of differences in Bindingness over PA3 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 52.7326, df = 1, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      FALSE
## -----+-----
##      TRUE |  -7.261724
##           |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## Test for the significance of differences in Bindingness over PA4 :
##
##   Kruskal-Wallis rank sum test
##
## data: x and group
## Kruskal-Wallis chi-squared = 17.2115, df = 1, p-value = 0
##
##
##                               Comparison of x by group
##                               (Bonferroni)
## Col Mean-|
## Row Mean |      FALSE
## -----+-----
##      TRUE |  -4.148671
##           |    0.0000*
##
## alpha = 0.05
## Reject Ho if p <= alpha
##
## p < 5e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-2 found in: PA1 PA5 PA3 PA4
## p < 1e-3 found in: PA1 PA5 PA3 PA4
## p < 1e-4 found in: PA1 PA5 PA3 PA4
```

Feature-factor correlations


```
data_factors_longer <- data_factors_long %>%
  pivot_longer(
    abstractNOUNs:verbdist,
    names_to = "feat", values_to = "feat_value"
  )

data_factors_correlations <- data_factors_longer %>%
```

```
group_by(feats, factor) %>%
  summarize(correlation = cor(feats_value, factor_score))
```

`summarize()` has grouped output by 'feats'. You can override using the
``.groups` argument.

```
data_factors_correlations %>%
  filter(feats %in% final_collist) %>%
  ggplot(aes(
    x = factor,
    y = feats,
    fill = correlation,
    label = round(correlation, 2)
  )) +
  geom_tile() +
  geom_text() +
  scale_fill_gradient2()
```



```
data_factors_correlations %>%
  filter(!(feats %in% final_collist)) %>%
  ggplot(aes(
    x = factor,
    y = feats,
    fill = correlation,
    label = round(correlation, 2)
  )) +
  geom_tile() +
  geom_text()
```

```
scale_fill_gradient2()
```

