

Parsing

Recommended Reading: Ch. 12-14th

Jurafsky & Martin 2nd edition

PI Disclosure: This set includes adapted material from Rada Mihalcea, Raymond Mooney and Dan Jurafsky

Today

- Parsing with CFGs
 - Bottom-up, top-down
 - Ambiguity
 - CKY parsing
 - Early algorithm

Parsing with CFGs

- Parsing with CFGs refers to the task of assigning proper trees to input strings
- Proper: a tree that covers **all and only the elements of the input** and **has an S at the top**
- It doesn't actually mean that the system can select the correct tree from among all the possible trees

Parsing with CFGs

- As with everything of interest, parsing involves a **search**
- We'll start with some basic methods:
 - Top down parsing
 - Bottom up parsing
- Real algorithms:
 - Cocke-Kasami-Younger (CKY)
 - Earley parser


For Now

- Assume...
 - You have all the words already in some buffer
 - The input isn't POS tagged
 - We won't worry about morphological analysis
 - All the words are known


Top-Down Search

- Since we're trying to find trees rooted with an S (Sentences), why not start with the rules that give us an S .
- Then we can work our way down from there to the words.
- As an example let's parse the sentence:
 - Book that flight


Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing



Top Down Parsing



Top Down Parsing



Top Down Parsing

S
/
VP


Top Down Parsing

S
/
VP
/
Verb


Top Down Parsing

S
/
VP
/
Verb
\
book


Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing




Top Down Parsing



Top Down Parsing



Top Down Parsing



Bottom-Up Parsing

- Of course, we also want trees that cover the input words. So we might also start with trees that link up with the words in the right way.
- Then work your way up from there to larger and larger trees.


Bottom Up Parsing

book that flight


Bottom Up Parsing

Noun
|
book that flight


Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing




Bottom Up Parsing



Bottom Up Parsing



Bottom Up Parsing



Top-Down and Bottom-Up

- Top-down
 - Only searches for trees that can be answers (i.e. S' s)
 - But also suggests trees that are not consistent with any of the words
- Bottom-up
 - Only forms trees consistent with the words
 - But suggests trees that make no sense globally



Control

- Of course, in both cases we left out how to keep track of the search space and how to make choices
 - Which node to try to expand next
 - Which grammar rule to use to expand a node
- One approach is called backtracking
 - Make a choice, if it works out then fine
 - If not then back up and make a different choice

Problems

- Even with the best filtering, backtracking methods are doomed because of ambiguity
 - Attachment ambiguity
 - Coordination ambiguity

Ambiguity



Dynamic Programming

- DP search methods fill tables with partial results and thereby
 - Avoid doing avoidable repeated work
 - Efficiently store ambiguous structures with shared sub-parts.
- We'll cover two approaches that roughly correspond to top-down and bottom-up approaches:
 - Cocke-Kasami-Younger (CKY)
 - Earley parser

CKY Parsing

- First we'll limit our grammar to epsilon-free, binary rules (more later)
- Consider the rule $A \rightarrow BC$
 - If there is an A somewhere in the input then there must be a B followed by a C in the input.
 - If the A spans from i to j in the input then there must be some k s.t. $i < k < j$
 - ie. the B splits from the C someplace

Problem

- What if your grammar isn't binary?
 - As in the case of the TreeBank grammar?
- Convert it to binary... any arbitrary CFG can be rewritten into Chomsky-Normal Form automatically.
- What does this mean?

Problem

- More specifically, we want our rules to be of the form

$A \rightarrow BC$

Or

$A \rightarrow w$

That is, rules can expand to either 2 non-terminals or to a single terminal.

Binarization Intuition

- Eliminate chains of unit productions.
- Introduce new intermediate non-terminals into the grammar that distribute rules with **length** > 2 over several rules.

- So... $S \rightarrow A B C$ turns into

$S \rightarrow X C$ and

$X \rightarrow A B$

Where X is a symbol that doesn't occur anywhere else in the the grammar.

Sample L1 Grammar

Grammar	Lexicon
$S \rightarrow NP VP$	$Det \rightarrow that \mid this \mid a$
$S \rightarrow Aux NP VP$	$Noun \rightarrow book \mid flight \mid meal \mid money$
$S \rightarrow VP$	$Verb \rightarrow book \mid include \mid prefer$
$NP \rightarrow Pronoun$	$Pronoun \rightarrow I \mid she \mid me$
$NP \rightarrow Proper-Noun$	$Proper-Noun \rightarrow Houston \mid NWA$
$NP \rightarrow Det Nominal$	$Aux \rightarrow does$
$Nominal \rightarrow Noun$	$Preposition \rightarrow from \mid to \mid on \mid near \mid through$
$Nominal \rightarrow Nominal Noun$	
$Nominal \rightarrow Nominal PP$	
$VP \rightarrow Verb$	
$VP \rightarrow Verb NP$	
$VP \rightarrow Verb NP PP$	
$VP \rightarrow Verb PP$	
$VP \rightarrow VP PP$	
$PP \rightarrow Preposition NP$	

CNF Conversion

\mathcal{L}_1 Grammar	\mathcal{L}_1 in CNF
$S \rightarrow NP VP$	$S \rightarrow NP VP$
$S \rightarrow Aux NP VP$	$S \rightarrow X1 VP$
	$X1 \rightarrow Aux NP$
$S \rightarrow VP$	$S \rightarrow book \mid include \mid prefer$
	$S \rightarrow Verb NP$
	$S \rightarrow X2 PP$
	$S \rightarrow Verb PP$
	$S \rightarrow VP PP$
$NP \rightarrow Pronoun$	$NP \rightarrow I \mid she \mid me$
$NP \rightarrow Proper-Noun$	$NP \rightarrow TWA \mid Houston$
$NP \rightarrow Det Nominal$	$NP \rightarrow Det Nominal$
$Nominal \rightarrow Noun$	$Nominal \rightarrow book \mid flight \mid meal \mid money$
$Nominal \rightarrow Nominal Noun$	$Nominal \rightarrow Nominal Noun$
$Nominal \rightarrow Nominal PP$	$Nominal \rightarrow Nominal PP$
$VP \rightarrow Verb$	$VP \rightarrow book \mid include \mid prefer$
$VP \rightarrow Verb NP$	$VP \rightarrow Verb NP$
$VP \rightarrow Verb NP PP$	$VP \rightarrow X2 PP$
	$X2 \rightarrow Verb NP$
$VP \rightarrow Verb PP$	$VP \rightarrow Verb PP$
$VP \rightarrow VP PP$	$VP \rightarrow VP PP$
$PP \rightarrow Preposition NP$	$PP \rightarrow Preposition NP$

CKY Parsing: Intuition

- Consider the rule $D \rightarrow w$
 - Terminal (word) forms a constituent
 - Trivial to apply
- Consider the rule $A \rightarrow B C$
 - If there is an A somewhere in the input then there must be a B followed by a C in the input
 - First, precisely define span $[i, j]$
 - If A spans from i to j in the input then there must be some k such that $i < k < j$
 - Easy to apply: we just need to try out different values for k

CKY Parsing: Table

- Any constituent can conceivably span $[i, j]$ for all $0 \leq i < j \leq N$, where N = length of input string
 - We need an $N \times N$ table to keep track of all spans...
 - But we only need half of the table
- Semantics of table: cell $[i, j]$ contains A iff A spans i to j in the input string
 - Of course, must be allowed by the grammar!

CKY Parsing: Table-Filling

- So let's fill this table...
 - And look at the cell [$0, N$]: which means?
- But how?

CKY Parsing: Table-Filling

- In order for A to span $[i, j]$:
 - $A \rightarrow B C$ is a rule in the grammar, and
 - There must be a B in $[i, k]$ and a C in $[k, j]$ for some $i < k < j$
- Operationally:
 - To apply rule $A \rightarrow B C$, look for a B in $[i, k]$ and a C in $[k, j]$
 - In the table: look left in the row and down in the column


CKY Algorithm

```
function CKY-PARSE(words, grammar) returns table  
  
  for  $j \leftarrow$  from 1 to LENGTH(words) do  
     $table[j - 1, j] \leftarrow \{A \mid A \rightarrow words[j] \in grammar\}$   
    for  $i \leftarrow$  from  $j - 2$  downto 0 do  
      for  $k \leftarrow i + 1$  to  $j - 1$  do  
         $table[i, j] \leftarrow table[i, j] \cup$   
           $\{A \mid A \rightarrow BC \in grammar,$   
             $B \in table[i, k],$   
             $C \in table[k, j]\}$ 
```

Note

- We arranged the loops to fill the table a column at a time, from left to right, bottom to top.
 - This assures us that whenever we're filling a cell, the parts needed to fill it are already in the table (to the left and below)
 - It's somewhat natural in that it processes the input left to right a word at a time
 - Known as online

Example



CKY Parser Example

CKY Notes

- Since it's bottom up, CKY populates the table with a lot of **phantom constituents**.
 - To avoid this we can switch to a top-down control strategy
 - Or we can add some kind of filtering that blocks constituents where they can not happen in a final analysis.
- Is there a parsing algorithm for arbitrary CFGs that combines dynamic programming and top-down control?

Earley Parsing

- Allows arbitrary CFGs
- Top-down control
- Fills a table in a single sweep over the input
 - Table is length $N+1$; N is number of words
 - Table entries represent a set of states (s_i):
 - A grammar rule
 - Information about progress made in completing the sub-tree represented by the rule
 - Span of the sub-tree

States/Locations

- $S \rightarrow \bullet VP, [0,0]$
 - A VP is predicted at the start of the sentence
- $NP \rightarrow Det \bullet Nominal, [1,2]$
 - An NP is in progress; the Det goes from 1 to 2
- $VP \rightarrow V NP \bullet, [0,3]$
 - A VP has been found starting at 0 and ending at 3

Earley

- As with most dynamic programming approaches, the answer is found by looking in the table in the right place.
- In this case, there should be an S state in the final column that spans from 0 to N and is complete. That is,
 - $S \rightarrow \alpha \bullet [0, N]$
- If that's the case you're done.

Earley

- So sweep through the table from 0 to N...
 - New predicted states are created by starting top-down from S
 - New incomplete states are created by advancing existing states as new constituents are discovered
 - New complete states are created in the same way.

Earley

- More specifically...
 1. **Predict** all the states you can upfront
 2. Read a word
 1. Extend states based on matches
 2. Generate new predictions
 3. Go to step 2
 3. When you're out of words, look at the chart to see if you have a winner

Earley

- Proceeds incrementally, left-to-right
 - Before it reads word 5, it has already built all hypotheses that are consistent with first 4 words
 - Reads word 5 & attaches it to immediately preceding hypotheses. Might yield new constituents that are then attached to hypotheses immediately preceding *them* ...
 - E.g., attaching **D** to **A** \rightarrow **B C . D E** gives **A** \rightarrow **B C D . E**
 - Attaching **E** to that gives **A** \rightarrow **B C D E .**
 - Now we have a complete **A** that we can attach to hypotheses immediately preceding the **A**, etc.

Earley

- Three Main Operators:
 - **Predictor**: If state s_i has a non terminal to the right we add to s_i all alternatives to generate the non terminal
 - **Scanner**: when there is POS to the right of the dot in s_i then scanner will try to match it with an input word and if a successful match is found the new state will be added to s_i
 - **Completer**: if the dot is at the end of the production then the completer looks for all states looking for the non terminal that has been found and advances the position of the dot for those states.

Core Earley Code

```
function EARLEY-PARSE(words, grammar) returns chart  
  
  ENQUEUE( $(\gamma \rightarrow \bullet S, [0, 0])$ , chart[0])  
  for  $i \leftarrow$  from 0 to LENGTH(words) do  
    for each state in chart[i] do  
      if INCOMPLETE?(state) and  
        NEXT-CAT(state) is not a part of speech then  
        PREDICTOR(state)  
      elseif INCOMPLETE?(state) and  
        NEXT-CAT(state) is a part of speech then  
        SCANNER(state)  
      else  
        COMPLETER(state)  
    end  
  end  
  return(chart)
```

Earley Code

```
procedure PREDICTOR( $(A \rightarrow \alpha \bullet B \beta, [i, j])$ )  
  for each  $(B \rightarrow \gamma)$  in GRAMMAR-RULES-FOR( $B, grammar$ ) do  
    ENQUEUE( $(B \rightarrow \bullet \gamma, [j, j])$ ,  $chart[j]$ )  
  end  
  
procedure SCANNER( $(A \rightarrow \alpha \bullet B \beta, [i, j])$ )  
  if  $B \subset \text{PARTS-OF-SPEECH}(word[j])$  then  
    ENQUEUE( $(B \rightarrow word[j], [j, j+1])$ ,  $chart[j+1]$ )  
  end if  
  
procedure COMPLETER( $(B \rightarrow \gamma \bullet, [j, k])$ )  
  for each  $(A \rightarrow \alpha \bullet B \beta, [i, j])$  in  $chart[j]$  do  
    ENQUEUE( $(A \rightarrow \alpha B \bullet \beta, [i, k])$ ,  $chart[k]$ )  
  end
```


Example

- Book that flight
- We should find... an S from 0 to 3 that is a completed state...

Chart[0]₀Book₁ the₂ flight₃

S0	$\gamma \rightarrow \bullet S$	[0,0]	Dummy start state
S1	$S \rightarrow \bullet NP VP$	[0,0]	Predictor
S2	$S \rightarrow \bullet Aux NP VP$	[0,0]	Predictor
S3	$S \rightarrow \bullet VP$	[0,0]	Predictor
S4	$NP \rightarrow \bullet Pronoun$	[0,0]	Predictor
S5	$NP \rightarrow \bullet Proper-Noun$	[0,0]	Predictor
S6	$NP \rightarrow \bullet Det Nominal$	[0,0]	Predictor
S7	$VP \rightarrow \bullet Verb$	[0,0]	Predictor
S8	$VP \rightarrow \bullet Verb NP$	[0,0]	Predictor
S9	$VP \rightarrow \bullet Verb NP PP$	[0,0]	Predictor
S10	$VP \rightarrow \bullet Verb PP$	[0,0]	Predictor
S11	$VP \rightarrow \bullet VP PP$	[0,0]	Predictor

Note that given a grammar, these entries are the same for all inputs; they can be pre-loaded.

Chart[1]

S12	<i>Verb</i> → <i>book</i> •	[0,1]	Scanner
S13	<i>VP</i> → <i>Verb</i> •	[0,1]	Completer
S14	<i>VP</i> → <i>Verb</i> • <i>NP</i>	[0,1]	Completer
S15	<i>VP</i> → <i>Verb</i> • <i>NP PP</i>	[0,1]	Completer
S16	<i>VP</i> → <i>Verb</i> • <i>PP</i>	[0,1]	Completer
S17	<i>S</i> → <i>VP</i> •	[0,1]	Completer
S18	<i>VP</i> → <i>VP</i> • <i>PP</i>	[0,1]	Completer
S19	<i>NP</i> → • <i>Pronoun</i>	[1,1]	Predictor
S20	<i>NP</i> → • <i>Proper-Noun</i>	[1,1]	Predictor
S21	<i>NP</i> → • <i>Det Nominal</i>	[1,1]	Predictor
S22	<i>PP</i> → • <i>Prep NP</i>	[1,1]	Predictor

Charts[2] and [3]

S23	<i>Det</i> → <i>that</i> •	[1,2]	Scanner
S24	<i>NP</i> → <i>Det</i> • <i>Nominal</i>	[1,2]	Completer
S25	<i>Nominal</i> → • <i>Noun</i>	[2,2]	Predictor
S26	<i>Nominal</i> → • <i>Nominal Noun</i>	[2,2]	Predictor
S27	<i>Nominal</i> → • <i>Nominal PP</i>	[2,2]	Predictor
S28	<i>Noun</i> → <i>flight</i> •	[2,3]	Scanner
S29	<i>Nominal</i> → <i>Noun</i> •	[2,3]	Completer
S30	<i>NP</i> → <i>Det Nominal</i> •	[1,3]	Completer
S31	<i>Nominal</i> → <i>Nominal</i> • <i>Noun</i>	[2,3]	Completer
S32	<i>Nominal</i> → <i>Nominal</i> • <i>PP</i>	[2,3]	Completer
S33	<i>VP</i> → <i>Verb NP</i> •	[0,3]	Completer
S34	<i>VP</i> → <i>Verb NP</i> • <i>PP</i>	[0,3]	Completer
S35	<i>PP</i> → • <i>Prep NP</i>	[3,3]	Predictor
S36	<i>S</i> → <i>VP</i> •	[0,3]	Completer
S37	<i>VP</i> → <i>VP</i> • <i>PP</i>	[0,3]	Completer

Efficiency

- For such a simple example, there seems to be a lot of useless stuff in there.
- Why?
 - It's predicting things that aren't consistent with the input
 - That's the flipside to the CKY problem.

Details

- As with CKY that isn't a parser until we add the backpointers so that each state knows where it came from.

Back to Ambiguity

- Did we solve it?

Ambiguity

- No...
 - Both CKY and Earley will result in multiple **S** structures for the **[0,N]** table entry.
 - They both efficiently store the sub-parts that are shared between multiple parses.
 - And they obviously avoid re-deriving those sub-parts.
 - But neither can tell us which one is right.

Ambiguity

- In most cases, humans don't notice incidental ambiguity (lexical or syntactic). It is resolved on the fly and never noticed.
- We'll try to model that with probabilities.