

Tree Borrows

Neven Villani,¹ Johannes Hostert,² Derek Dreyer,³ Ralf Jung²

PLDI'25

2025-06-19

¹Univ. Grenoble Alpes, Verimag

²ETH Zurich

³MPI-SWS

Rust's type system provides powerful optimizations

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
  
    *x = 13;  
  
    *y = 20;  
  
    *x  
  
}
```

Rust's type system provides powerful optimizations

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
    *x = 13;  
    *y = 20;  
    *x  
}
```

mutable thus disjoint

*x is unchanged

Rust's type system provides powerful optimizations

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
    *x = 13;  
    *y = 20;  
    *x  
}
```

mutable thus disjoint

*x has known value

*x is unchanged

always returns 13

Rust's type system provides powerful optimizations

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
  
    *x = 13;  
  
    *y = 20;  
  
    13 // formerly *x: one fewer load from memory  
  
}
```

Type-level guarantees for references



`&mut` → mutation, no aliasing

`&` → aliasing, no mutation

Escape hatch: **unsafe**

Can **bypass typechecks** to implement **low-level manipulations**

```
unsafe {  
    // Code within this block has relaxed typechecking  
    . . .  
}
```

Within **unsafe** it is **the programmer's responsibility** to check

- that pointers are non-null
- that memory is initialized
- ...

What if **unsafe** code is misused ?

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
    *x = 13;  
    *y = 20;  
    *x  
}
```

```
fn main() {  
    let mut root = 42;  
    let ptr = &raw mut root;  
    let x = unsafe { &mut *ptr };  
    let y = unsafe { &mut *ptr };  
    println!("{}", write_both(x, y));  
}
```


What if **unsafe** code is misused ?

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
    *x = 13;  
    *y = 20;  
    *x  
}
```

```
fn main() {  
    let mut root = 42;  
    let ptr = &raw mut root;  
    let x = unsafe { &mut *ptr };  
    let y = unsafe { &mut *ptr };  
    println!("{}", write_both(x, y));  
}
```

What if **unsafe** code is misused ?

```
fn write_both(x: &mut i32, y: &mut i32) -> i32 {  
    *x = 13;  
    *y = 20;  
    *x  
}  
  
fn main() {  
    let mut root = 42;  
    let ptr = &raw mut root;  
    let x = unsafe { &mut *ptr };  
    let y = unsafe { &mut *ptr };  
    println!("{}", write_both(x, y));  
}
```

Not the compiler's responsibility

Within **unsafe** it is **the programmer's responsibility** to check

- that pointers are non-null
- that memory is initialized
- compliance with aliasing rules **NEW!**

Tree Borrows (TB): defines those aliasing rules

Not the compiler's responsibility

Within `unsafe` it is the programmer's responsibility to check

- that pointers are non-null
- that memory is initialized

- **Sounds familiar?**

Stacked Borrows has the same purpose,
Tree Borrows is its successor.

Stacked Borrows (SB)

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```

A diagram showing a memory stack. It consists of a single rectangular box with the word "root" inside. The box has a double-line border, with the top line being thicker than the bottom line.

- new stack at root

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




root

- ✓ root is at the top

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




- ✓ root is at the top
- push ptr

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




- ✓ ptr is at the top
- push x

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




- pop until ptr is at the top

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




- pop until ptr is at the top

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




- pop until ptr is at the top
- push y

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```




- search for x

Desired outcome: UB

In safe Rust, the Borrow Checker makes borrows well-bracketed. Stacked Borrows extends the well-bracketedness to **unsafe**.

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;
```

UB!



Can't use x if it is not in the stack

Desired outcome: UB

SB was **implemented** in Miri (official interpreter and UB detector)


→ included in many projects' CI

→ several bugs detected (e.g. in stdlib)

SB was **implemented** in Miri (official interpreter and UB detector)

→ included in many projects' CI


→ several bugs detected (e.g. in stdlib)



SB was **implemented** in Miri (official interpreter and UB detector)

→ included in many projects' CI

→ several bugs detected (e.g. in stdlib)



Stacked Borrows: asserting uniqueness too early?
Should we allow the optimizer to add spurious
stores? #133

Open

rust-lang / unsafe-code-guidelines

Code Issues 214 Pull requests Actions Projects Security Insights

Storing an object as &Header, but reading the
data past the end of the header #256

New issue

Open

rust-lang / unsafe-code-guidelines

Code Issues 214 Pull requests Actions Projects Security Insights

Stacked Borrows: raw pointer usable only for T
too strict? #134

Open

rust-lang / unsafe-code-guidelines

Code Issues 214 Pull requests Actions Projects Security Insights

Stacked Borrows: How precise should UnsafeCell
be tracked? #236

New issue

Open



Ralfjung opened on Jun
Currently, when looking
through arrays, structs



Confusion about stacked borrows



Sign Up

Log In



Inconsistency between stacked borrows and my mental
model

Tree Borrows

Neven Villani

New issue

rust-lang / unsafe-code-guidelines

Code Issues 214 Pull requests Actions Projects Security Insights

Stacked Borrows: Disabled has more effects than
expected #274

Open



help

Stacked Borrows incompatible with Garbage Collectors?

Sign Up

Log In

foconoco

There

I was

with S

incom

item o

Are st

hatch

approx

Stacked Borrows cannot properly handle extern
type #276

Open

Open

Open

Open

Open

Open

Open

Open

Open

Open

Open

Open

Open

Open

Open



Help me understand this UB with stacked borrows detected
by `miri`

help

Sign Up

Log In

Search

Menu

Code

Issues

Pull requests

Actions

Projects

Security

Insights

Confusing stacked borrows violation #1364

Closed

New issue

7

Supported by data:

- analysis of 30 000 libraries
- 6000+ tests that otherwise work are declared UB under Stacked Borrows

Tree Borrows allows much more code

Stacked Borrows (SB)

Tree Borrows uses a **tree** instead of a stack to track borrows

Out of 30 000 most downloaded libraries,
> **50% fewer** tests with aliasing UB when using Tree Borrows

Tree Borrows allows much more code

Stacked Borrows (SB)

Tree Borrows uses a **tree** instead of a stack to track borrows

Out of 30 000 most downloaded libraries,
> **50% fewer** tests with aliasing UB when using Tree Borrows


fixes known technical limitations of SB, incl. **pointer offsets**

From Stacks to Trees


```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```




```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```



```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```



```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```




```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```

```
// Scenario 1
```

```
unsafe { *x0.add(1) = 2; }
```



Desired outcome: not UB


```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```

```
// Scenario 1
```

```
unsafe { *x0.add(1) = 2; }
```




Desired outcome: not UB

```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```

// Scenario 2

```
unsafe { *x2.sub(1) = 2; }
```



Desired outcome: not UB


```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```

```
// Scenario 2
```

```
unsafe { *x2.sub(1) = 2; }
```





Desired outcome: not UB

```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```

Desired outcome: not UB


```
let mut root = vec![0, 0, 0];  
let x0 = &raw mut root[0];  
let x2 = &raw mut root[2];  
unsafe { *x0 = 1 };  
unsafe { *x2 = 3 };
```




Desired outcome: not UB

```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```

Desired outcome: not UB




```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```

Desired outcome: not UB



```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```


// Scenario 1

```

unsafe { *x0.add(1) = 2 };

```

Desired outcome: not UB



```

let mut root = vec![0, 0, 0];
let x0 = &raw mut root[0];
let x2 = &raw mut root[2];
unsafe { *x0 = 1 };
unsafe { *x2 = 3 };

```


// Scenario 2

```

unsafe { *x2.sub(1) = 2; }

```

Desired outcome: not UB




A second look at the motivating example

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```

Desired outcome: UB

A second look at the motivating example

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```




Desired outcome: UB

A second look at the motivating example

From Stacks to Trees

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```




Desired outcome: UB

A second look at the motivating example

From Stacks to Trees


```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```



Desired outcome: UB

A second look at the motivating example


```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```



Desired outcome: UB

A second look at the motivating example

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```




Desired outcome: UB

A second look at the motivating example

```
let mut root = 42;  
let ptr = &raw mut root;  
let x = unsafe { &mut *ptr };  
let y = unsafe { &mut *ptr };  
// inline write_both(x, y):  
*x = 13;  
*y = 20;
```

UB!



Desired outcome: UB

Evaluation

TB should enable desired optimizations

i.e. have enough UB to rule out problematic patterns

- formalized in Rocq (+Simuliris)
- a selection of optimizations proven
 - ✓ delete read through `&mut` or `&`
 - ✓ insert read through `&` in function
 - ✓ move read down for `&mut` or `&` in function
- ...

+ read-read reordering!

TB should enable desired optimizations

On reordering reads

In SB:

```
let mut root = 0;  
let x = &mut root;  
let v1 = *x;  
let v2 = root;
```



root, root, x, x, root is well-bracketed

TB should enable desired optimizations

On reordering reads

In SB:

```
let mut root = 0;  
let x = &mut root;  
let v2 = root;  
let v1 = *x;
```



root, root, x, x, root

is well-bracketed

root, root, x, root, x

is not well-bracketed

In TB: a read never prevents another read.

It should be possible to write **unsafe** code free of UB Evaluation

i.e. UB should be predictable and not too common

Tree Borrows reduces aliasing-related UB by over 50%

Only 31 ($< 0.01\%$) tests are regressions, all easily fixable.

(Out of 30 000 libraries, 400 000+ working tests)


“Tree Borrows accepts more real-world programs that call foreign functions than Stacked Borrows due to differences in handling pointer arithmetic.”

A Study of Undefined Behavior Across Foreign Function Boundaries in Rust Libraries,
by I. McCormack, J. Sunshine, J. Aldrich @ ICSE'25

Conclusion

Try it out:

Rust Playground supports TB
play.rust-lang.org



Learn more:

[plf.inf.ethz.ch/research/
pldi25-tree-borrows.html](https://plf.inf.ethz.ch/research/pldi25-tree-borrows.html)

- detailed state machine
- raw pointers
- interior mutability

