

On the Verification of Structured Parameterized Networks

Neven Villani¹, Marius Bozga¹, Radu Iosif¹, Arnaud Sangnier²


AVM'25 @ Timisoara; using material from NETYS'25, CAV'25, and work in progress

2025-09-24

¹VERIMAG, Univ. Grenoble Alpes, CNRS


²DIBRIS, Univ. di Genoa

- (automated) verification of networks
- challenge: size and architecture (communication topology)




- undecidable \rightsquigarrow abstraction


Token ring with resource




Token ring with resource




Token ring with resource




Token ring with resource




Token ring with resource




Token ring with resource



Token ring with resource



Token ring with resource



$$\forall n \geq 2$$

How would we automatically verify this ?

Techniques for non-finite-state systems...

Parameterized model checking of rendezvous systems

(B. Aminof, T. Kotek, S. Rubin, F. Spegni, H. Veith)

✗ not homogeneous (2 kinds of processes)

How would we automatically verify this ?

Techniques for non-finite-state systems...

Parameterized model checking of rendezvous systems


(B. Aminof, T. Kotek, S. Rubin, F. Spegni, H. Veith)

✗ not homogeneous (2 kinds of processes)

Parameterized Verification of Algorithms for Oblivious Robots on a Ring

(A. Sangnier, N. Sznajder, M. Potop-Butucaru, S. Tixeuil)

✗ not a standard architecture (clique, ring, star)



How would we automatically verify this ?

Techniques for non-finite-state systems...

Parameterized model checking of rendezvous systems


(B. Aminof, T. Kotek, S. Rubin, F. Spegni, H. Veith)

✗ not homogeneous (2 kinds of processes)

Parameterized Verification of Algorithms for Oblivious Robots on a Ring

(A. Sangnier, N. Sznajder, M. Potop-Butucaru, S. Tixeuil)

✗ not a standard architecture (clique, ring, star)



Parameterized Model Checking of Token-Passing Systems

(B. Aminof, S. Jacobs, A. Khalimov, S. Rubin)


✗ not a token-passing system (key and lock don't behave like tokens)


Framework requirements

We must be able to express

- an encoding of the **local behavior** of processes
- a description of the **interactions** and **architectures** of arbitrary size
- a **specification language** for safety properties


Framework






Interactions through composition


Framework





Interactions through composition





Interactions through composition












$$X \longrightarrow \text{compose}(\text{rename}_{\text{left} \mapsto \text{mid}}(\text{copy}_{\text{send} \rightsquigarrow \text{acq}, \text{recv} \rightsquigarrow \text{rel}}(X)), \text{rename}_{\text{right} \mapsto \text{mid}}(\text{client}))$$

Representable architectures

Encoded as a CFG for graphs¹ \implies families of bounded TW are representable (missing: ~~square grids~~, cliques)






¹Graph Structure and Monadic Second Order Logic; by B. Courcelle, J. Engelfriet

Safety specification

Safety properties

$\#(\text{🔑})$: number of tokens on 🔑

\sim number of clients who claim to own the key



$$\#(\text{🔑}) + \#(\text{🔒}) > 1$$

Proving safety \approx reachability problem in an infinite family of PNs

- **mutual exclusion**

“at most k processes can enter a critical section simultaneously”

- **uniqueness**

“the entire system contains at most k instances of a resource”

- **uncoverability**

“no process can reach a bad state”

Examples: leader election, semaphores, dining philosophers, ...

Missing: ~~liveness, deadlock freedom~~

An Abstraction Technique

Verification pipeline

An Abstraction Technique


```
Sys  $\longrightarrow$  compose( $X$ , renameleft $\mapsto$ right, right $\mapsto$ left(client'))  
X  $\longrightarrow$  compose(  
    renameleft $\mapsto$ mid(copysend $\leadsto$ acq, recv $\leadsto$ rel( $X$ )),  
    renameright $\mapsto$ mid(client)  
)  
X  $\longrightarrow$  compose(copysend $\leadsto$ acq, recv $\leadsto$ rel(server), client)
```

Verification pipeline

```
Sys  $\rightarrow$  compose( $X$ , renameleft $\mapsto$ right, right $\mapsto$ left(client'))  
X  $\rightarrow$  compose(  
  renameleft $\mapsto$ mid(copysend $\leadsto$ acq, recv $\leadsto$ rel( $X$ )),  
  renameright $\mapsto$ mid(client)  
)  
X  $\rightarrow$  compose(copysend $\leadsto$ acq, recv $\leadsto$ rel(server), client)
```

language \rightarrow

infinite family of PNs




Verification pipeline

```
Sys  $\rightarrow$  compose(X, renameleft $\mapsto$ right, right $\mapsto$ left(client'))  
X  $\rightarrow$  compose(  
  renameleft $\mapsto$ mid(copysend $\leadsto$ acq, recv $\leadsto$ rel(X)),  
  renameright $\mapsto$ mid(client)  
)  
X  $\rightarrow$  compose(copysend $\leadsto$ acq, recv $\leadsto$ rel(server), client)
```

language

infinite family of PNs



safety


$$\#(\text{key}) + \#(\text{lock}) > 1$$

Verification pipeline

```
Sys  $\rightarrow$  compose(X, renameleft $\mapsto$ right, right $\mapsto$ left(client'))  
X  $\rightarrow$  compose(  
  renameleft $\mapsto$ mid(copysend $\leadsto$ acq, recv $\leadsto$ rel(X)),  
  renameright $\mapsto$ mid(client)  
)  
X  $\rightarrow$  compose(copysend $\leadsto$ acq, recv $\leadsto$ rel(server), client)
```

language \rightarrow

infinite family of PNs



~~safety~~

undecidable!





$$\#(\text{key}) + \#(\text{lock}) > 1$$

Verification pipeline

An Abstraction Technique

```

Sys  $\rightarrow$  compose( $X$ , renameleft $\mapsto$ right, right $\mapsto$ left(client'))
X  $\rightarrow$  compose(
  renameleft $\mapsto$ mid(copysend $\leadsto$ acq, recv $\leadsto$ rel( $X$ )),
  renameright $\mapsto$ mid(client)
)
X  $\rightarrow$  compose(copysend $\leadsto$ acq, recv $\leadsto$ rel(server), client)
    
```




Verification pipeline

An Abstraction Technique


```
Sys  $\rightarrow$  compose( $X$ , renameleft $\mapsto$ right, right $\mapsto$ left(client'))  
X  $\rightarrow$  compose(  
  renameleft $\mapsto$ mid(copysend $\leadsto$ acq, recv $\leadsto$ rel( $X$ )),  
  renameright $\mapsto$ mid(client)  
)  
X  $\rightarrow$  compose(copysend $\leadsto$ acq, recv $\leadsto$ rel(server), client)
```

language

infinite family of PNs



abstraction



finite PN

\supseteq
(soundness)

decidable
e.g. LoLA



~~safety~~

undecidable!

$$\#(\text{key}) + \#(\text{lock}) > 1$$



Folding abstraction

An Abstraction Technique




Folding abstraction

An Abstraction Technique




Folding abstraction

An Abstraction Technique





Folding abstraction


An Abstraction Technique



fold
→









Implementing fold

An Abstraction Technique




fold
 \rightarrow

\leftarrow
 \subseteq
 (soundness)




Implementing fold

An Abstraction Technique




fold
→

←--
⊆
(soundness)




Folded system

An Abstraction Technique



Folded system

An Abstraction Technique




$$\text{Sys} \longrightarrow \text{compose}\left(X, \text{rename}_{\text{left} \mapsto \text{right}, \text{right} \mapsto \text{left}}(\text{client}')\right)$$
$$\begin{aligned} X \longrightarrow \text{compose}(& \\ & \text{rename}_{\text{left} \mapsto \text{mid}}\left(\text{copy}_{\text{send} \rightsquigarrow \text{acq}, \text{recv} \rightsquigarrow \text{rel}}(X)\right), \\ & \text{rename}_{\text{right} \mapsto \text{mid}}(\text{client}) \\ &) \end{aligned}$$
$$X \longrightarrow \text{compose}\left(\text{copy}_{\text{send} \rightsquigarrow \text{acq}, \text{recv} \rightsquigarrow \text{rel}}(\text{server}), \text{client}\right)$$

$$\text{Sys} \longrightarrow \text{compose}(\mathbf{X}, \text{rename}_{\text{left} \mapsto \text{right}, \text{right} \mapsto \text{left}}(\text{client}'))$$
$$\begin{aligned} \mathbf{X} \longrightarrow & \text{compose}(\text{rename}_{\text{left} \mapsto \text{mid}}(\text{copy}_{\text{send} \rightsquigarrow \text{acq}, \text{recv} \rightsquigarrow \text{rel}}(\mathbf{X})), \\ & \text{rename}_{\text{right} \mapsto \text{mid}}(\text{client})) \\ &) \end{aligned}$$
$$\mathbf{X} \longrightarrow \text{compose}(\text{copy}_{\text{send} \rightsquigarrow \text{acq}, \text{recv} \rightsquigarrow \text{rel}}(\text{server}), \text{client})$$


Initial marking


From the grammar


$$\text{Sys} \longrightarrow X, \text{client}'$$
$$X \longrightarrow X, \text{client}$$
$$X \longrightarrow \text{server}, \text{client}$$



Initial marking

From the grammar

$$\text{Sys} \longrightarrow X, \text{client}'$$
$$X \longrightarrow X, \text{client}$$
$$X \longrightarrow \text{server}, \text{client}$$










Verifying Dense Graphs

What formalism for architectures ?



Hyperedge **R**eplacement (sparse only)


What formalism for architectures ?



Hyperedge Replacement (sparse only)

Vertex Replacement (incl. some dense)


What formalism for architectures ?



Azure Datacenter Topology
Greenberg et al., SIGCOMM 2009


Key idea

Verifying Dense Graphs




Key idea

Verifying Dense Graphs




Key idea

Verifying Dense Graphs





Key idea

Verifying Dense Graphs





Communication through routers

Verifying Dense Graphs





Communication through routers

Verifying Dense Graphs





Communication through routers

Verifying Dense Graphs





Communication through routers


Verifying Dense Graphs





Communication through routers

Verifying Dense Graphs





$s_1 s_2$




$s_1 s_1 s_1 s_1 s_1 s_2 s_2 s_2 s_2 s_2$

Decidable Restrictions


Token Passing

Decidable Restrictions



Token Passing

Decidable Restrictions



	<i>Known</i>	<i>New</i>	<i>WIP</i>
communication	token passing		
processes	arbitrary	≤ 2 states	≤ 1 non-token state
tokens	exactly 1	arbitrary	exactly 1
architecture	MSO	HR	MSO
property	CTL* \ X	cover	μ -calculus

Parameterized model checking of rendezvous systems;

by B. Aminof, T. Kotek, S. Rubin, F. Spegni, H. Veith; in Distributed Computing (2017)

Conclusion

- semi-algorithm + implementation for HR
- translation procedure for VR
- decidable classes inspired by literature

More details:

- Counting Abstraction and Decidability for the Verification of Structured Parameterized Networks; in CAV'25
- Verifying Parameterized Networks Specified by Vertex-Replacement Graph Grammars; in NETYS'25

Future work

- refinements
- extend decidable classes
- other communication models