Still Needed, Hard to Transfer: Using and Reusing Contextual Skills

Anonymous Author(s)

Abstract

Agent skills provide task-specific capabilities by loading instructions and supporting resources into a language model's context. We investigate what allows the internal states produced from a skill to support another execution. Across model depth, we transplant correct-skill residual states, the hidden vectors passed between model blocks, into a wrong-skill execution. Separately, we block subsequent attention to the skill in the original execution. Across three models from two families on MedCalc and TheoremQA, residual-state transfer weakens before dependence on source access subsides. Content, position and cross-question controls establish that early transfer carries structured skill information. To investigate the later separation, we jointly replace skill states and the source positions' key/value (KV) cache, which stores attention vectors for previously processed tokens. On Qwen3-8B/MedCalc, this raises layer-16 accuracy from 3.5% with residual replacement alone to 42.1%. Cutting subsequent reading of the repaired source reduces accuracy to 7.0%. Skill-state transfer thus depends on more than the replaced residual vectors: compatible source caches can restore part of the effect, while continued source access can remain necessary for the recovered behaviour. The mechanism evidence covers one model–task setting and identifies source caches and subsequent reading as concrete factors to test when reusing contextual skills.

CCS Concepts

• **Computing methodologies** → **Natural language processing**; *Knowledge representation and reasoning*.

Keywords

agent skills, Web agents, large language models, in-context learning, activation patching, context reuse, mechanistic interpretability

1 Introduction

Relevance to the Web and to this track. Web agents rely on machine-readable instructions and descriptions of tools and services to understand how to act across sites [22, 23]. Agent Skills package such procedural knowledge for reuse. We ask how a model uses a loaded skill and when the internal states it produces can support another execution. This connects our study to the Semantics and Knowledge track's interest in machine-readable descriptions that help agents understand and use Web resources, and in knowledge representations that support intelligent agent behaviour.

An Agent Skill packages task instructions, scripts and supporting resources around a `SKILL.md` entry point, which an agent loads when needed [26]. We study the instruction content of a loaded skill. A model can apply that content successfully, but how much of the resulting ability can be reused through its internal states? Reusing states from an earlier execution is an appealing way to share skills and avoid repeated processing. It requires understanding which states contribute to the ability and what else those states need in order to work.

A useful starting point is to move skill states into an execution using an unrelated skill and measure the benefit restored. Task and function vectors show that internal states can transmit task behaviour across contexts [10, 20]. Such transfer may also depend on the computation surrounding the states and on further access to the source. We therefore ask: *how does the ability to transfer a skill's states relate to the ongoing need to read that skill?*

We follow both properties across model depth. First, we replace the hidden vectors at skill-token positions in a wrong-skill execution with vectors from a correct-skill execution. These residual states are the vectors passed between successive model blocks. Second, we block attention to the skill from a chosen layer through the rest of the original correct-skill execution. The fraction of originally correct answers lost measures source-attention dependence.

Figure 1 previews the result. Early residual-state replacement recovers much of the skill's benefit. Deeper in the model, transfer becomes weak while blocking subsequent skill attention still damages the original execution. This ordering recurs across three models from two families and two task domains, including comparisons on identical eligible questions. We use content, position and cross-question controls to establish the effective early probe before interpreting this separation.

What can restore transfer in that interval? Residual replacement leaves the receiver's attention cache in place. This key/value (KV) cache stores vectors that later tokens read through attention. Jointly replacing the skill's residual states and its source-position cache entries restores substantial late transfer in Qwen3-8B/MedCalc. Cutting subsequent reading then removes most of the recovered effect. The source cache and continued reading therefore matter alongside the residual vectors themselves. Earlier reader computation remains unchanged in these tests, so the intervention targets specific source components rather than replaying the donor's complete execution.

Work on layer-wise computation and reusable skill caches highlights how depth and stored context shape model behaviour [13, 25]. We connect these questions through three contributions. First, we validate an early skill-span transfer probe using content, position and cross-question controls (§4.2). Second, we identify a depth interval in which residual transfer is weak while the original execution still depends on skill attention (§4.3). Third, we isolate the contributions of source-position caches and subsequent reading to late transfer in one model–task setting (§4.4). Together, the results identify concrete conditions under which skill states can be reused: the accompanying source cache and the access available after transfer both deserve explicit tests.

WWW '27, Dublin, Ireland
2027.




Figure 1: From effective early transfer to source-cache repair. (a) Early skill states recover most of the donor's benefit on the screened Qwen3-8B/MedCalc set. (b) On common eligible items, residual transfer weakens while source dependence remains high. Dependence is $d(L) = 1 - q(L)$, the fraction of rescued answers lost after cutting source access. (c) At layer 16, replacing source states together with their source cache recovers part of late transfer, and cutting subsequent reading removes most of that recovery. Panels use their indicated evaluation populations.

2 Related Work

Transferring task behaviour through internal states. Task vectors summarize demonstrations as internal vectors that can steer a new example [10]. Function vectors identify attention-head outputs that transmit a task's behaviour across contexts [20]. Natural-language instructions also yield transferable components [5], and instruction patches can interact across layers [2]. The effect of transfer varies with the task and intervention time [15]. These results establish useful transfer settings. We examine how transfer changes across depth relative to the original execution's continued dependence on its skill source.

Tracing context use and execution history. Cumulative context masking tests whether a model still needs source tokens at later layers [18]. Instruction-span and final-position patches can reveal different effects [17]. Joint analyses of masking and state transfer locate subtask execution across layers [25]. Activation patching, the replacement of selected hidden states by states from another run, requires matched controls and careful implementation [9, 27]. Effects can depend on interactions among the intervened components [21]. We pair full-depth transfer and masking profiles, then test source states together with their attention caches. This connects our work to PrefillNotes [13], which shows that precompiled skill caches can be repositioned and composed with a target context. Our focus is when residual-state reuse weakens while source access remains important, and how replacing source-position caches affects that separation.

Skills and reusable context. Agent Skills organize instructions and resources for on-demand use [26]. Benchmarks measure skill retrieval and application [8, 14, 19], while matched-budget evaluations show that their benefit depends on the available computation [7]. We fix the selected skill and study how its loaded content supports execution. A related direction compresses context into aggregated activations [1], learned summary tokens [16], compact hidden states [6], or weight updates [3, 4]. We study naturally occurring states through interventions, providing tests of reuse and source dependence that complement trained compression methods.

3 Problem Formulation

Setting and notation. We supply a skill's instructions directly and hold skill selection fixed. For the same question, the *donor* uses the correct skill and the *receiver* an unrelated skill of equal token length. Let $\mathcal{I}$ be the skill's token positions, called the *source span*; tokens outside it are *readers*. Layers are indexed from zero. The model processes prompt tokens during *prefill*, then generates answer tokens during *decoding*. We compare transferring source states into the receiver with removing source access in the donor (Figure 2).

Residual-state and cache replacement. Let H^L be the residual states, the hidden vectors output by block L. Subscripts D and R denote donor and receiver. State replacement, labelled S, writes

$$S: \qquad H_R^L[\mathcal{I}] \leftarrow H_D^L[\mathcal{I}]. \tag{1}$$

This write occurs during prefill; the receiver then continues normally. Other positions at that layer are unchanged.

Attention matches a query to keys and combines their associated values. The key/value (KV) cache stores these vectors for processed tokens. Let K^ℓ and V^ℓ be the cached keys and values at layer ℓ. Cache replacement, labelled C, writes

$$C: \quad \begin{aligned} K_R^\ell[\mathcal{I}] &\leftarrow K_D^\ell[\mathcal{I}], \\ V_R^\ell[\mathcal{I}] &\leftarrow V_D^\ell[\mathcal{I}], \end{aligned} \qquad 0 \le \ell \le L. \tag{2}$$




Figure 2: Intervention design. (a) The correct-skill donor supplies source residual states (S), source-position key/value (KV) entries through layer L (C), or both (SC) to the wrong-skill receiver. Earlier reader computation is retained. (b) Attention cuts distinguish access by reader tokens from updates within the skill source. After SC, the reader cut begins at $L+1$. In the original correct-skill run, path cuts begin at L. All cuts continue through the remaining prompt processing and decoding.

The combined intervention SC performs both writes. S alone leaves these earlier caches unchanged; neither write replays earlier reader computation. Cache writes precede processing the final prompt token (Appendix A.1).

Cumulative attention knockout. Let z_{ij}^{ℓ} be the attention score from query position i to key position j, including the causal mask that blocks future tokens. At every layer $\ell \geq L$, knockout replaces these scores by

$$\tilde{z}_{ij}^{\ell} = \begin{cases} -\infty, & j \in \mathcal{I}, \\ z_{ij}^{\ell}, & j \notin \mathcal{I}. \end{cases} \tag{3}$$

Softmax converts the modified scores into attention weights: blocked positions receive zero weight and the remaining weights sum to one. The cut applies to every query and attention head (a parallel attention component), during both prefill and decoding. It affects reader access and source-state updates. Path-specific cuts restrict i to readers or to $\mathcal{I}$; a reader cut after SC starts at $L+1$.

Recovery and dependence. Write a_D, a_R and a_I for answer accuracy under the donor, receiver and a specified intervention I. Recovery measures the fraction of the donor's gain restored:

$$\rho(I) = \frac{a_I - a_R}{a_D - a_R}. \tag{4}$$

Thus $\rho = 1$ restores that gain; $\rho > 1$ exceeds donor accuracy. For state replacement at layer L, we write $\rho(L)$. We evaluate *rescued items*, answered incorrectly without a skill and correctly with it, and retain skill groups whose receiver solves no sampled item. Screening uses only unmodified baselines, separately by run, model and task (§4.1).

On the knockout's eligible items, let $q(L)$ be the fraction still correct. Their *source-attention dependence* is

$$d(L) = 1 - q(L). \tag{5}$$

It is the fraction of originally correct answers lost under knockout. Higher values mean stronger dependence on subsequent source attention. We also compare both curves on common eligible items, retaining their own baselines and distinct donor/receiver execution backgrounds.

Depth boundaries. After establishing effective early transfer, define the first half-effect boundaries and their separation as

$$\begin{aligned} T &= \min\{L : \rho(L) < 0.5\}, \\ R &= \min\{L : d(L) \leq 0.5\}, \qquad \Delta = R - T. \end{aligned} \tag{6}$$

Layers with $\rho(L) < 0.5$ and $d(L) > 0.5$ show weak transfer despite strong dependence. Figure 3 shades the interval between the first boundaries and preserves later recrossings.

4 Experiments

4.1 Experimental setup

Tasks and models. We pair MedCalc-Bench [12] with skills from SRA-Bench [19], covering 1,100 questions from 55 clinical calculators. We also use SRA-Bench's TheoremQA subset, with 747 questions and 320 skills. Each question receives its designated skill, holding skill selection fixed. We test Qwen3-8B, Qwen3-0.6B [24] and Mistral-7B-Instruct-v0.3 [11], spanning two model families. Models generate step-by-step answers with greedy decoding, selecting the highest-probability next token at each step. We use no



Figure 3: Depth profiles across three models and two tasks. Blue shows skill-span transfer recovery $\rho(L)$ in a wrong-skill receiver. Orange shows source-attention dependence $d(L) = 1 - q(L)$: the fraction of originally correct answers lost after cumulative attention knockout in the correct-skill execution. Shading spans the first half-effect boundaries, highlighting weak transfer despite strong dependence; later recrossings remain visible. Boundary layers are marked above each panel. Every plotted layer is measured.

tools and apply the corresponding benchmark scorers. On the full MedCalc benchmark, Qwen3-8B achieves 74.2% accuracy with the correct skill, 34.5% without a skill, and 31.5% with an unrelated skill.

Evaluation populations. Our causal comparisons focus on questions rescued by the correct skill, as defined in §3. On MedCalc/Qwen3-8B, 467 rescued questions from 48 calculators enter the span-intervention battery. Retaining skill groups whose wrong-skill receiver solves no sampled item gives 135 questions from 14 calculators. The depth sweeps use this group screen, with separately eligible transfer and knockout items. We also recompute both curves on their common item IDs. TheoremQA uses the same screen, becoming item-level for skills with one question. The source-cache replacement study uses a separate fixed set described in §4.4. These populations estimate effects conditional on baseline skill benefit.

Implementation checks. An identity patch writes the receiver's own states back and should reproduce its output. Correcting an attention-mask mismatch between state capture and decoding restores exact agreement, including all 467 MedCalc identity checks. All main results use the corrected implementation. Appendix A.1 specifies the intervention protocol, and Appendix A.2 records the correction.

4.2 Validation of skill-state transfer

Early transfer recovery. Before comparing transfer across depth, we establish that the intervention transmits useful behaviour. At layer 8 on the screened MedCalc set, replacing states at the skill's token positions recovers most of the correct skill's benefit (Table 1). Patching the last prompt position or the final 16 positions has a much smaller effect. This locates an effective intervention in the skill span. Its larger number of replaced states also makes it a higher-capacity intervention than the final-position alternatives.

Content and position controls. The unrelated-skill, permuted-position and noise controls in Table 1 all yield little recovery. The noise is scaled to match the size, measured by Euclidean norm, of the skill-state change. For the content comparison, the correct and unrelated skills are patched over a common prefix length. The correct prefix recovers 0.65 of the available gain. A mean of same-family skill differences recovers 0.12 on its smaller eligible set of 41 items. Rescaling patched states to match the receiver's norm at each position preserves 0.87 recovery, close to the full-span result. These

Table 1: Early transfer controls, Qwen3-8B/MedCalc, layer 8: 135 items from 14 calculators. Accuracy and recovery ρ are point estimates. Final-position patches replace fewer states than the skill-span patches; other-skill content uses a matched prefix (see text).

Intervention	Accuracy	ρ
Correct skill donor	.919	1.00
Wrong skill receiver	.000	.00
Correct skill span	.815	.89
Last prompt position	.030	.03
Last 16 prompt positions	.059	.06
Other skill content	.044	.05
Correct span, permuted	.044	.05
Norm-matched noise	.022	.02
Identity patch	.000	.00

comparisons identify skill-specific content and its arrangement as important to early transfer. The group screen matters: other-skill and noise controls are more effective in excluded groups, so the control contrast describes the screened population.

Cross-question transfer. In the main prompt order, the skill precedes the question. Causal attention, which restricts a token to attending to earlier positions, prevents those skill states from encoding the later question. We additionally place the skill after the question and obtain donor states from other questions using the same skill. On 151 eligible items from 17 calculators, these states recover 0.98 at layer 8, close to 1.02 for a donor answering the current question. At layer 16, the values separate to 0.29 and 0.49. Early transfer therefore carries information shared across instances, with greater question sensitivity later. Patching individual contiguous quarters of the main skill span also reveals content structure: the formula quarter gives the largest standalone recovery, 0.56. Appendix B provides the additional content and prompt-order controls.

4.3 Depth separation of transfer and dependence

Transfer–dependence separation. With an effective early probe established, we follow state transfer and source-attention knockout across every layer. Figure 3 shows the six model–task combinations. For Qwen3-8B/MedCalc, transfer recovery is 0.74 at layer 12, falls to 0.16 at 13, and is at most 0.07 from layer 15 onward. For cuts beginning at $L \leq 23$ and continuing through the final layer during prompt processing and answer generation, source-attention dependence is 0.88–0.97: most originally correct answers are lost. Dependence is 0.75 at layer 24 and first falls to at most one half at layer 25. Throughout layers 13–24, transfer recovers less than half the gain, while removing further skill attention still loses more than half the rescued answers.

The first crossing summarizes each curve. Qwen3-8B/MedCalc dependence briefly rises above half again at layer 26 before falling below it from layer 27 onward. We retain these fluctuations in the measured curves. The main finding is the separation of the two intervention effects: states become ineffective at correcting the receiving computation while source access still supports the original one.

Table 2: Boundary layers on common eligible items. T/R gives the first half-effect crossings for transfer ($\rho < 0.5$) and source dependence ($d \leq 0.5$), respectively. $\Delta = R - T$ measures their separation in layers.

Task	Model	n	T/R	Δ
MedCalc	Qwen3-8B	134	13/25	12
MedCalc	Qwen3-0.6B	90	11/22	11
MedCalc	Mistral-7B	46	7/27	20
TheoremQA	Qwen3-8B	63	13/21	8
TheoremQA	Qwen3-0.6B	125	11/20	9
TheoremQA	Mistral-7B	65	7/19	12

Common-item and threshold checks. Original transfer and knockout runs can retain different eligible questions. We therefore recompute the curves over the intersection of their item IDs, using eligibility determined from unpatched baselines. Table 2 reports the resulting boundaries. All six pairs match those from the original populations. The source-dependence boundary follows the transfer boundary in all six settings. Using transfer thresholds $\tau = 0.4$ or 0.6 and the corresponding dependence thresholds $1 - \tau$ also preserves the ordering. The gap thus recurs across the two model families and both task domains under common-item evaluation.

Repeated state replacement. On the same 135 MedCalc items, replacing source states over layer windows 8–11, 12–15, 14–19 and 16–35 recovers 0.89, 0.74, 0.16 and 0.06, respectively. Replacement at every layer from the start recovers 0.98. The corresponding TheoremQA results appear in Appendix B. These are consistency checks: with identical preceding context, replacing the full source span once can already reproduce its later donor states under causal attention. Repeated writes therefore need not provide an independent intervention and do not establish that maintaining source states is insufficient.

4.4 Effects of source caches and continued reading

Interventions and evaluation set. We compare S, C and SC as defined in Eqs. 1–2, plus SC followed by a reader cut from layer $L + 1$, denoted SC + recut. This tests source-cache contributions and subsequent reader access while retaining earlier reader computation.

We evaluate layers 8, 12, 16, 24 on a fixed 124-question set from 14 calculators with fresh baselines. Of these, 114 questions are correct with the donor and incorrect with both the wrong-skill and no-skill baselines. Both panels of Figure 4 use these same questions. All 48 own-state controls across four GPU shards reproduce output tokens exactly. Appendix B.1 gives implementation and eligibility details.




Figure 4: Source-state/cache replacement and attention-path tests on the same 114 Qwen3-8B/MedCalc items from 14 skills. (a) Accuracy (%) following residual replacement (S), cache replacement (C), joint repair (SC), or joint repair followed by a reader cut from the next layer. (b) Fraction of donor-correct answers lost when reader-to-source, source-to-source, or both attention paths are cut from the indicated layer onward. The heatmap uses a fixed 0–100% scale with exact values in each cell. Path-cut estimates are offset vertically within each tested layer. Table 3 reports the main contrasts.

Table 3: Focused mechanism contrasts, 114 items from 14 skills. Differences are in percentage points (pp). Writing a_X for accuracy under condition X, the additive interaction is $a_{SC} - a_S - a_C + a_R$, where a_R is receiver accuracy.

Contrast	Difference
L16: $SC - S$	+38.6
L16: additive interaction	+31.6
L16: $SC - (SC + \text{recut})$	+35.1
L24: reader minus self loss	+71.1

Joint replacement gains. At layer 16, residual replacement answers 4/114 questions correctly, cache replacement answers 8/114, and joint repair answers 48/114. Table 3 reports the repair gain. The joint gain exceeds the sum of the individual gains relative to the receiver, showing that the states and their source caches contribute together. At layer 24, joint repair still improves on residual replacement (25.4% versus 0.9%), compared with 18.4% for cache replacement alone. Compatible source caches thus recover part of the late transfer effect.

Continued reading and attention paths. Following joint repair at layer 16, cutting reader-to-source attention reduces accuracy to 8/114. Most of the repaired effect therefore relies on continued reading. To identify what the original cumulative knockout disrupts, we separately cut reader-to-source attention, source-to-source attention, or both in the unmodified donor, during prefill and decoding. At layer 24, reader-only and combined cuts each leave 29/114 questions correct, while a source-self-only cut leaves 110/114 correct. Continued reader access accounts for the dominant tested dependence at this layer. Earlier cuts at layers 8 and 16 damage both paths.

Depth variation and generation limits. After joint repair at layer 24, a reader recut yields 27.2% accuracy, compared with 25.4% without the recut. The repaired-yet-reading-dependent result is therefore supported at layer 16 and varies across the tested depths. The main repair gain is stable to generation-length diagnostics: it remains 38.5 points on the 96 questions whose three baselines finish without truncation. An adverse reassignment of truncated outputs still leaves a 35.1-point gain (Appendix B.1). Taken together, the experiments show that replacing source-position caches can restore part of late residual transfer, and that the recovered behaviour can still depend on reading the skill.

5 Conclusion

Skill-state transfer is shaped by both the transferred component and the source access available afterward. Across three models and two task domains, residual-state transfer weakens before dependence on skill attention subsides. Content and cross-question controls establish that the effective early intervention carries structured skill information.

The focused Qwen3-8B/MedCalc study makes this separation more concrete. Replacing source-position KV caches together with residual states restores substantial late transfer at layer 16, while cutting subsequent source reading removes most of the recovered effect. This identifies source caches and continued reading as two contributors to successful reuse. The intervention leaves earlier reader computation unchanged, and the recutting effect varies with depth, so these results characterize the tested source components rather than all of the receiver's computational history.

For systems that reuse contextual skills, residual-state recovery, source-cache compatibility and subsequent source access are therefore distinct properties to evaluate. Extending the joint interventions to additional models and interactive agent tasks can establish how broadly these conditions govern skill reuse.

References

[1] Thibaud Ardoin, Semira Einsele, Evis Bregu, and Gerhard Wunder. 2026. Prompt Compression via Activation Aggregation. *arXiv preprint arXiv:2607.08399* (2026).

[2] Irina Bigoulaeva, Jonas Rohweder, Subhabrata Dutta, and Iryna Gurevych. 2026. Patches of Nonlinearity: Instruction Vectors in Large Language Models. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, San Diego, California, United States, 12209–12262. doi:10.18653/v1/2026.acl-long.559

[3] Lucas Caccia, Alan Ansell, Edoardo Ponti, Ivan Vulić, and Alessandro Sordoni. 2025. Training Plug-n-Play Knowledge Modules with Deep Context Distillation. In *Conference on Language Modeling (COLM)*. arXiv:2503.08727.

[4] Rujikorn Charakorn, Edoardo Cetin, Shinnosuke Uesaka, and Robert Tjarko Lange. 2026. Doc-to-LoRA: Learning to Instantly Internalize Contexts. *arXiv preprint arXiv:2602.15902* (2026).

[5] Guy Davidson, Todd M. Gureckis, Brenden M. Lake, and Adina Williams. 2025. Do different prompting methods yield a common task representation in language models? *arXiv preprint arXiv:2505.12075* (2025). https://arxiv.org/abs/2505.12075

[6] Tao Ge, Jing Hu, Lei Wang, Xun Wang, Si-Qing Chen, and Furu Wei. 2024. In-context Autoencoder for Context Compression in a Large Language Model. In *International Conference on Learning Representations (ICLR)*. arXiv:2307.06945.

[7] Sina Hajimiri, Masih Aminbeidokhti, Jose Dolz, Ismail Ben Ayed, Issam H. Laradji, Spandana Gella, and Nicolas Gontier. 2026. Are Online Skill and Memory Modules Always Worth Their Tokens? A Budget-Constrained Study of Web Agents. *arXiv preprint arXiv:2606.15017* (2026). https://arxiv.org/abs/2606.15017

[8] Tingxu Han, Yi Zhang, Wei Song, Chunrong Fang, Zhenyu Chen, Youcheng Sun, and Lijie Hu. 2026. SWE-Skills-Bench: Do Agent Skills Actually Help in Real-World Software Engineering? *arXiv preprint arXiv:2603.15401* (2026).

[9] Stefan Heimersheim and Neel Nanda. 2024. How to use and interpret activation patching. *arXiv preprint arXiv:2404.15255* (2024).

[10] Roee Hendel, Mor Geva, and Amir Globerson. 2023. In-Context Learning Creates Task Vectors. In *Findings of the Association for Computational Linguistics: EMNLP 2023*. arXiv:2310.15916.

[11] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, et al. 2023. Mistral 7B. *arXiv preprint arXiv:2310.06825* (2023).

[12] Nikhil Khandekar, Qiao Jin, Guangzhi Xiong, Soren Dunn, Serina S. Applebaum, Zain Anwar, Maame Sarfo-Gyamfi, Conrad W. Safranek, Abid A. Anwar, Andrew Zhang, Aidan Gilson, Maxwell B. Singer, Amisha Dave, Andrew Taylor, Aidong Zhang, Qingyu Chen, and Zhiyong Lu. 2024. MedCalc-Bench: Evaluating Large Language Models for Medical Calculations. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*. arXiv:2406.12036.

[13] Bojie Li. 2026. Models Take Notes at Prefill: KV Cache Can Be Editable and Composable. *arXiv preprint arXiv:2606.17107* (2026). https://arxiv.org/abs/2606.17107

[14] Xiangyi Li, Yimin Liu, Wenbo Chen, et al. 2026. SkillsBench: Benchmarking How Well Agent Skills Work Across Diverse Tasks. *arXiv preprint arXiv:2602.12670* (2026).

[15] Yuxuan Li, Declan Campbell, Stephanie C. Y. Chan, and Andrew Kyle Lampinen. 2025. Just-in-time and distributed task representations in language models. *arXiv preprint arXiv:2509.04466* (2025).

[16] Jesse Mu, Xiang Lisa Li, and Noah Goodman. 2023. Learning to Compress Prompts with Gist Tokens. In *Advances in Neural Information Processing Systems (NeurIPS)*. arXiv:2304.08467.

[17] Aditya Pola and Vineeth N. Balasubramanian. 2025. Where does an LLM begin computing an instruction?. In *UniReps Workshop*. extended abstract; arXiv:2511.10694.

[18] Suzanna Sia, David Mueller, and Kevin Duh. 2024. Where does In-context Learning Happen in Large Language Models?. In *Advances in Neural Information Processing Systems (NeurIPS)*. arXiv:2403.04510.

[19] Weihang Su, Jianming Long, Qingyao Ai, Qiaozhi He, Yichen Tang, Changyue Wang, Yiteng Tu, Yingbo Wang, and Yiqun Liu. 2026. Skill Retrieval Augmentation for Agentic AI. *arXiv preprint arXiv:2604.24594* (2026).

[20] Eric Todd, Millicent L. Li, Arnab Sen Sharma, Aaron Mueller, Byron C. Wallace, and David Bau. 2024. Function Vectors in Large Language Models. In *International Conference on Learning Representations (ICLR)*. arXiv:2310.15213.

[21] Sankaran Vaidyanathan, David Arbour, Aaron Mueller, Scott Niekum, and David Jensen. 2026. The Curse of Multiple Mediators: Hidden Interaction Effects in Activation Patching. *arXiv preprint arXiv:2606.27510* (2026). https://arxiv.org/abs/2606.27510

[22] Zhaoyang Wang, Qianhui Wu, Xuchao Zhang, Chaoyun Zhang, Wenlin Yao, Fazle Elahi Faisal, Baolin Peng, Si Qin, Suman Nath, Qingwei Lin, Chetan Bansal, Dongmei Zhang, Saravan Rajmohan, Jianfeng Gao, and Huaxiu Yao. 2026. WebXSkill: Skill Learning for Autonomous Web Agents. *arXiv preprint arXiv:2604.13318* (2026). https://arxiv.org/abs/2604.13318

[23] Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2025. Agent Workflow Memory. In *Proceedings of the 42nd International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 267)*. PMLR, 63897–63911. https://proceedings.mlr.press/v267/wang25bx.html

[24] An Yang, Anfeng Li, et al. 2025. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388* (2025).

[25] Zhipeng Yang, Junzhuo Li, Siyu Xia, and Xuming Hu. 2025. Internal Chain-of-Thought: Empirical Evidence for Layer-wise Subtask Scheduling in LLMs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. 22536–22564. doi:10.18653/v1/2025.emnlp-main.1147

[26] Barry Zhang, Keith Lazuka, and Mahesh Murag. 2025. Equipping agents for the real world with Agent Skills. Anthropic Engineering. https://www.anthropic.com/engineering/equipping-agents-for-the-real-world-with-agent-skills

[27] Fred Zhang and Neel Nanda. 2024. Towards Best Practices of Activation Patching in Language Models: Metrics and Methods. In *International Conference on Learning Representations (ICLR)*. arXiv:2309.16042.

A Experimental protocols and provenance

Tasks and scoring. The main MedCalc evaluation uses the 55 calculator skills released with SRA-Bench and 20 questions per calculator. The benchmark scorer checks free-form numerical answers against its prescribed tolerances. TheoremQA uses its released prompts, skill assignments and evaluator. All main experiments supply the selected skill directly and generate answers without tool calls. MedCalc questions are grouped by calculator; TheoremQA questions are grouped by skill identity.

Evaluation populations. We distinguish four baseline outcomes: rescued items are incorrect without the skill and correct with it, persistent failures are incorrect in both conditions, kept items are correct in both, and broken items become incorrect with the skill. The main interventions focus on rescued items. The additional receiver screen retains skill groups in which the wrong-skill receiver solves no sampled question. This reduces recovery through disruption of an interfering wrong skill, concentrating the comparison on the contribution of the donor's content. Appendix B compares this group screen with a less restrictive screen that excludes only individually solved receiver items.

A.1 Implementation details

Models and decoding. The main models are Qwen3-8B (36 layers, hidden width 4096), Qwen3-0.6B (28 layers, width 1024), and Mistral-7B-Instruct-v0.3 (32 layers, width 4096). For Mistral, which has no system role in its chat template, system instructions are merged into the user turn. We use greedy decoding. Qwen thinking mode is disabled and checked on the rendered prompt. Attention-mask interventions use explicit attention computation with mask checks, often called eager attention. Earlier residual-replacement

Table 4: Full-dataset rerun against the development subset, Qwen3-8B on MedCalc, layer 8. Recovery is Eq. 4; entries show point estimates. *per-calc* is the main text's restriction, *per-item* the weaker one. Controls reach 0.12 under the group screen and 0.25 under the item screen; each arm uses its own matched baselines.

arm	full, per-calc (n = 135)	subset (n = 60)	full, per-item (n = 369)
transplant `real`	**0.89**	0.87	0.94
same skill, matched prefix	0.65	0.73	0.84
half dose $\alpha = 0.5$	0.04	0.06	0.11
positions permuted	0.05	0.08	0.21
norm-matched noise	0.02	0.10	0.18
other calculator	0.05	—	0.25
other family, mean	0.05	0.06	0.16
same family, mean	0.12	0.05	0.24
identity patch	0.00	0.00	0.00
rank 128 / 64 / 32 / 16	0.77/0.63/0.12/0.05	0.77/0.54/0.13/0.06	0.88/0.70/0.22/0.18
bottom-64 / bottom-16	0.03/0.04	0.00/0.06	0.11/0.12
quarters $q_0/q_1/q_2/q_3$	0.09/**0.56**/0.12/0.05	0.12/0.56/0.12/0.12	0.18/0.64/0.22/0.19

runs use PyTorch scaled dot-product attention. The mechanism experiments use BF16, a 16-bit floating-point format, and a 1,536-token generation limit.

Position and state checks. Donor and receiver prompts use length-matched skills, preserving question positions. Residual patches replace the selected block output during prefill. The captured positions are indexed within the prompt, separately from any answer tokens used for scoring. Identity controls write the receiver's own states back. A final-layer check also verifies that replacing a position's final hidden state reproduces the donor's next-token scores at that position. Attention cuts preserve the causal mask.

Focused mechanism protocol. A bridge on one fixed item from each of 14 calculators compares full-prompt prefill with prefill split before the final prompt token. All 84 own-state checks reproduce their corresponding receiver token sequences exactly. Changing the prefill protocol changes one donor's and one receiver's answer correctness. The formal repair and path comparisons therefore use the same split protocol and fresh no-skill, donor and receiver baselines. Truncation counts and sensitivity analyses are retained with the result records.

A.2 Evaluation scope and intervention provenance

Attention-mask correction. The original state-capture call omitted the attention mask supplied during decoding. Although mathematically equivalent for an unpadded sequence, these calls selected different numerical kernels. Their states differed by 1.2% at layer 8 and 25% at layer 34. Identity patching changed 108/1,766 Qwen3-8B outcomes (6.1%). Matching the masks restores exact identity agreement, including all 467 items in the corrected MedCalc rerun. All main-text state interventions use this correction. Attention knockout operates directly on attention masks and uses no donor-state capture.

Development and replication. The initial MedCalc intervention battery sampled four rescued questions from each of the 40 calculators with the most eligible questions. The corrected full-data rerun uses every rescued question from calculators with at least two, giving 467 items from 48 calculators. The main receiver screen then retains 135 questions from 14 calculators. Historical development results retain their original sample labels. Table 4 shows the corrected rerun alongside the earlier screened subset. Main depth comparisons cover all six model–task combinations, with common-item checks for their two intervention types.

Scientific scope. The experiments characterize supplied skill instructions under fixed selection and controlled generation. The depth ordering is replicated across the tested models and tasks. The source-history repair and path-specific tests provide a more focused result on Qwen3-8B/MedCalc. Interactive browser tasks, skill retrieval errors and learned state compression are natural settings in which to test how these findings extend to agent systems.

B Additional transfer and source-reading analyses

The original MedCalc × Qwen3-8B intervention battery was developed on the forty calculators with the most rescued items, sampling four each: 160 of 467 rescued items, and 60 items over 15 calculators after the receiver-never-solves restriction. We reran each of them with every rescued item of every calculator that has at least two (467 items, 48 calculators), keeping the intervention configuration fixed. The group screen is stricter on the larger set because a calculator must fail on up to twenty items rather than four, so it keeps 135 items over 14 calculators, and we also report the per-item

restriction (369 items over 45), which keeps the items whose own receiver fails.

For the dose and rank controls in Table 4, the state difference is $\delta^L = H_D^L[\mathcal{I}] - H_R^L[\mathcal{I}]$. A dose α writes $H_R^L[\mathcal{I}] + \alpha\delta^L$; $\alpha = 1$ is full replacement and $\alpha = 0.5$ is half dose.

Table 4 also includes a rank-truncation diagnostic. We decompose the injected state-difference matrix into ordered directions using singular value decomposition and retain only the leading k. Increasing k from 32 to 64 restores much of the recovery. A bottom-k control retains the least prominent directions instead. The formula quarter gives the largest standalone recovery in both samples. The same-family mean donor changes from 0.05 to 0.12, on the 41 full-rerun items where it is available.

The depth sweep at one-layer resolution. The subset sweep measured layers 0, 4, 8, 12, 14, 15, 16, 20 and placed the collapse somewhere after 12. At full scale we added 13 and 17–19: recovery is 0.98, 0.98, 0.89, 0.74 at layers 0, 4, 8, 12, then 0.16, 0.16, 0.06, 0.06, 0.07, 0.03, 0.02, 0.03 at 13 through 20 (per-calc; the per-item restriction gives 1.00, 0.98, 0.94, 0.79 then 0.32, 0.34, 0.25, 0.25, 0.23, 0.19, 0.14, 0.17). Under the group screen, layers 13 and 14 both round to 0.16. Under the item screen, they differ at 0.32 and 0.34. Both screens show their largest local decline between layers 12 and 13.

Repeated replacement on TheoremQA.. The corrected Qwen3-8B comparison uses 99 eligible questions from 75 skills with matched donor and wrong-skill receiver baselines. Replacing source residual states at each layer of windows 8–11, 12–15, 14–19 and 16–35 recovers 0.839, 0.613, 0.376 and 0.204, respectively. Layer 16 alone also recovers 0.204. These values come from the completed `t8-win` and `tqa-span` runs, whose compatible baselines are merged before applying the receiver screen. As in MedCalc, the repeated and single-layer writes have the same recovery. With a shared preceding context and full source-span replacement, causal attention can make the later source writes redundant; these results are not an independent test of maintaining a transferable state.

A continuous readout at the same boundary. Accuracy thresholds a generated answer, so an internal change can appear sharper in this measure. We therefore generate the correct-skill reasoning once per item and score that fixed sequence under each intervention. This is teacher forcing: the model receives the recorded preceding tokens rather than generating a new sequence. The mean token log-probability measures how strongly it predicts that reasoning. Log-probabilities use natural logarithms, with units called nats. Higher values indicate that the recorded sequence is more likely.

We normalize this score as $z = (\ell_L - \ell_{\text{recv}})/(\ell_{\text{gold}} - \ell_{\text{recv}})$, where ℓ denotes the mean log-probability and the subscripts identify the patched, receiver and donor conditions. We use z to distinguish this diagnostic from knockout retention q. On 442 donor-correct items from 48 calculators, z is 0.999, 0.989, 0.960, 0.831 at layers 0, 4, 8, 12. It then falls to 0.598 at layer 13, 0.595 at 14, 0.340 at 16, 0.201 at 20, and 0.129 at 24. The layer-12 to layer-13 decline spans 26.8% of the score's range, compared with the 61% behavioural decline. The continuous readout therefore also changes sharply at the accuracy boundary.

The decline is distributed across the four quarters of the reasoning sequence (0.20, 0.26, 0.31, 0.21). Scoring only tokens after the final answer marker is less useful here. Once the reasoning is supplied, all conditions predict the final number closely: median log-probabilities lie between −0.001 and −0.005, and the donor-minus-receiver denominator has median 0.0014, below 0.01 on 59% of items.

Distributed reading and receiver state. An attention head is one of the parallel attention components within a transformer block. Head-level readout from the skill span concentrates in layers 12–21 after normalisation by residual-stream norm. Blocking the 32 highest-ranked heads costs 0.39 of the skill's effect, versus 0.23 for random heads at the same layers (held-out calculators; paired difference 0.154). Reading is distributed rather than confined to a small circuit. After late span replacement, downstream readout remains 0.86–0.99 of the donor's despite weak behavioural recovery. Earlier receiver question-state updates remain unchanged, motivating the interaction tests in §4.4.

B.1 Focused source-history and path-specific experiments

The focused Qwen3-8B/MedCalc experiments fix 124 historical item IDs from 14 calculators before inference and partition them as every fourth ID across four RTX 4090 workers. They use BF16, eager attention, greedy decoding and 1,536 new tokens. Fresh baselines retain 116 donor-correct, receiver-incorrect items, of which 114 also fail without a skill. Both experiments use these same 114 items; all 372 baseline generations agree token-for-token between the two suites. The complete repair grid contains 2,356 generations, the path grid 1,488, and worker identity checks 100. All 48 own-state writebacks are token-exact.

S writes the donor source-span block output at layer L. C replaces only source-position keys and values at layers 0 through L after prefix prefill and before recomputing the final prompt token. SC combines them; SC recutting blocks reader queries to source keys from $L + 1$ onward in that same run. Earlier reader history is unchanged. Reader queries are positions after the source span; source-self queries are positions within it. The path experiments cut the specified edges during both prefill and decoding, preserving the causal mask.

We retain all intervention outcomes, including truncated outputs. For the prespecified SC-minus-S contrast at layer 16, the gain is 38.6 percentage points. The corresponding joint-minus-additive contrast is 31.6 points; SC-minus-recut is 35.1 points. On the 96 items with all three baselines untruncated, SC-minus-S is 38.5 points. At layer 16, S/SC/recut truncate 4/4/3 of 114 outputs; worst-case reassignment of all truncated S and SC outcomes leaves a 35.1-point repair advantage. At layer 24, SC and recut truncate 3/28 outputs and show no additional loss in measured accuracy; this depth is not used to claim independence after repair.

At layer 24, reader and source-self cuts retain 29/114 and 110/114 correct answers. Their loss difference is 71.1 points. Reader cuts truncate 21 outputs; counting all as correct still leaves retention at 50/114, below source-self retention 110/114 (no truncation). Both contrasts survive worst-case reassignment of truncated outputs. Analysis artifacts retain arm-wise counts, hashes and truncation bounds.