Still Needed, Hard to Transfer: Using and Reusing Contextual Skills

Anonymous Author(s)

Abstract

Language models can adapt to new tasks by following instructions provided in context. Reusing the internal states formed from these instructions could allow the resulting task capabilities to be shared across executions. However, it remains unclear how the ability to transfer these states relates to the model's continued dependence on the instructions. We study this relationship using skills, sets of instructions that describe how to perform a task. At different layers, we transfer states at the instruction positions from an execution using the correct skill into one using an unrelated skill. Separately, we block attention to the skill in the original execution. Across four models and two benchmarks, all eight comparisons show that transfer weakens at later layers while the original execution remains strongly dependent on the skill. We then augment state transfer with key/value caches, the stored information used by attention. At layer 16, this joint intervention improves accuracy over state transfer alone by 6.8 to 43.4 percentage points across all eight combinations. For Qwen3-8B/MedCalc, accuracy rises from 3.5% to 42.1%, and blocking subsequent skill reading reduces it to 7.0%. These findings establish a separation between using contextual skills and reusing their internal states, and demonstrate cache-assisted recovery across models and tasks.

CCS Concepts

• **Computing methodologies** → **Natural language processing**. *Knowledge representation and reasoning*.

Keywords

agent skills, Web agents, large language models, in-context learning, activation patching, context reuse, mechanistic interpretability

1 Introduction

Language models can perform new tasks by following instructions in their context. A skill makes such instructions reusable: a calculator skill, for example, specifies a formula, input conventions and the steps for applying them to a new question. A model divides text into tokens and represents each position with an internal vector, or hidden state. If the hidden states formed from these instructions also support reuse, one execution could supply task-relevant information to another without changing the model's weights.

Agent Skills organize instructions, scripts and resources around a `SKILL.md` entry point [32]. Web agents use reusable skills and workflows to guide later actions [28, 29]. This motivates studying whether the internal states formed from such instructions can also be reused. We study this question through controlled question answering after a skill has been selected, isolating the use and transfer of its instructions.




Figure 1: Weak transfer and continued skill use at the same later depth. Copying skill-position states from a correct-skill run into an unrelated-skill run gives strong early recovery (left) and weak late recovery (middle). At that same later depth, the original run still needs skill access: retaining access preserves performance, while cutting it reduces accuracy (right). S and Q label skill and question tokens. Figure 3 gives the measured depth profiles.

The difficulty is interpreting a failed transfer. If copying a skill's hidden states no longer restores performance, has the model stopped needing those instructions, or has the copy failed to supply what the receiving execution needs? Task vectors summarize task demonstrations, while function vectors combine selected internal attention outputs. Both show that internal states can transmit task behaviour across contexts [13, 24]. Yet restoring an execution and disrupting a successful one measure different effects [12]. This motivates our central question: *can skill-state transfer weaken while the original execution still relies on access to the skill?*

We answer this question with two tests across model depth. The first copies hidden states at the skill's token positions from a correct-skill execution into an execution using length-matched text from an unrelated skill. The second blocks attention to the skill in the original correct-skill execution, from a chosen layer onward. Content, position and cross-question controls first establish that early copying transfers skill-relevant information. We then find a consistent separation in eight evaluated combinations of four models and two benchmarks: transfer weakens at later layers while the original execution remains strongly dependent on skill attention (Figure 1).

We next test whether adding information omitted by hidden-state copying can improve late transfer. Attention stores information from previously processed tokens in a key/value (KV) cache. At layer 16, copying these caches together with hidden states improves

WWW '27, Dublin, Ireland
2027.

accuracy over state transfer alone in all eight settings, by 6.8 to 43.4 percentage points. Blocking subsequent skill reading reduces the recovered accuracy in each setting. For Qwen3-8B/MedCalc, joint replacement raises accuracy from 3.5% to 42.1%, and the reading cut reduces it to 7.0%. The shared direction across models and tasks establishes cache-assisted partial restoration alongside continued use of the skill.

The paper follows three steps: validate early transfer (§4.2), establish its separation from continued skill use (§4.3), and test the extent of cache-assisted restoration (§4.4). Together, the tests distinguish the ability to use contextual instructions from the ability to reuse their internal states, and identify cached information as a component that improves reuse.

2 Related Work

State transfer and its interpretation. Task vectors summarize demonstrations as internal vectors [13], and function vectors identify attention outputs that transmit task behaviour [24]. Instructions also yield transferable components [2, 6], whose effects vary with intervention depth [18]. Activation patching, which copies internal states between executions, requires matched controls and careful implementation [12, 33]. In particular, restoring behaviour and disrupting it need not reveal the same components. Interactions with other components can also affect a patching estimate [26]. We use these methodological distinctions to compare skill-state transfer and source dependence across depth.

Depth, source access and context caches. Pola and Balasubramanian [20] locate an onset beyond which selected hidden-state replacements largely cease to change answers in their instruction tasks. Sia et al. [22] use layer-wise context masking, which blocks attention to selected context positions, in machine translation and code generation to locate where attention to the instructional context becomes unnecessary. Joint transfer and masking analyses also locate subtask computation [31]. We instead define the source as an explicit skill-instruction span and compare transfer into a wrong-skill execution with blocking attention to that span in the original execution on common questions. The comparison measures how the two effects separate across depth.

PrefillNotes [16] studies editable and reusable KV caches. In its field-editing tasks, replacing local KV entries can fail when downstream cached conclusions still reflect the old field. It also composes precompiled skill caches into new contexts. Our focus is the depth separation between skill-state transfer and original-run source dependence. We then ask whether copying source caches together with states partially restores late transfer.

Skills and reusable context. Agent Skills organize instructions and resources for on-demand use [32]. Benchmarks study skill retrieval and application [11, 17, 23], while matched-budget evaluations expose their dependence on available computation [10]. We hold skill selection fixed. Other approaches compress context into aggregated activations [1], learned summary tokens [19], hidden states [8], or weight updates [3, 4]. Our interventions characterize naturally occurring states and source dependence without training a compression mechanism.

3 Problem Formulation

Skills, executions and token positions. We supply a skill's instructions directly and hold skill selection fixed. For the same question, the *donor* execution uses the correct skill and the *receiver* execution uses length-matched text from a fixed unrelated skill (Appendix A.1). The skill's token positions, denoted $\mathcal{I}$, form the *source span*. For example, a calculator's formula and input conventions belong to this span. The question does not. *Readers*, denoted $\mathcal{J}$, are positions after the source span, including subsequent prompt tokens and generated answer tokens. Thus receiver names an execution, whereas reader names a token position that can attend to the skill. Causal attention prevents a position from reading future tokens, so tokens before the source cannot read it.

Layers are indexed from zero. The model processes prompt tokens during *prefill* and generates answer tokens during *decoding*. We use greedy decoding, which selects the highest-probability next token. Our main comparison asks what transferring source states restores in the receiver and what blocking source attention removes from the donor.

Hidden-state transfer. Each Transformer block is a processing layer that updates the token vectors. Let H^L denote its output at layer L, also called residual states. Subscripts D and R denote donor and receiver. State replacement, labelled S, writes

$$S: \qquad H_R^L[\mathcal{I}] \leftarrow H_D^L[\mathcal{I}]. \tag{1}$$

The write occurs during prefill, after which the receiver continues with the patched states. Other positions at that layer remain unchanged.

Blocking attention to the skill. In the original correct-skill execution, we block attention to source positions at a chosen layer L and every subsequent layer. We call this *cumulative source-attention knockout*. In attention, a query vector scores keys at available positions, and the resulting weights combine their value vectors. Let z_{ij}^{ℓ} be the attention score from query position i to key position j, including the causal mask that blocks future tokens. At each layer $\ell \geq L$, we set

$$\tilde{z}_{ij}^{\ell} = \begin{cases} -\infty, & j \in \mathcal{I}, \\ z_{ij}^{\ell}, & j \notin \mathcal{I}. \end{cases} \tag{2}$$

The softmax operation converts scores into weights that sum to one. It gives blocked positions zero weight and normalizes the remaining weights. An attention head is one of the block's parallel attention components. The cut applies to all query positions and attention heads during prefill and decoding. It blocks both readers' access to the skill and attention within the skill itself, so its effect measures aggregate source-attention dependence.

The repair extension adds source-cache replacement, denoted C, and combines it with state replacement as SC. Figure 2 previews these operations, whose layer coverage is defined below.

Recovery and dependence. Write a_D, a_R and a_I for answer accuracy under the donor, receiver and an intervention I. Recovery is the fraction of the donor's gain restored in the receiver:

$$\rho(I) = \frac{a_I - a_R}{a_D - a_R}. \tag{3}$$




Figure 2: Timing of state repair, cache repair and the reading cut in the receiver. The prefix contains all prompt tokens except the last. (a) S copies donor source states at block L's output during prefix prefill. (b) C copies source-position key/value (KV) entries at layers 0 through L after prefix prefill, before final-token recomputation. SC combines these two writes, then recomputes the final prompt token and generates. (c) SC + cut installs a reading mask before prefill, blocking reader-to-source attention from $L+1$ onward during prefill and decoding. Source-to-source attention remains unmasked. Reader states and caches evolve through computation rather than direct replacement. Figure 4(b) separately tests cuts in the original correct-skill run.

We require $a_D > a_R$. Thus $\rho = 1$ restores that gain and $\rho > 1$ exceeds donor accuracy. For state replacement at layer L, we write $\rho(L)$. All three accuracies use the same items and the transfer protocol's own unpatched baselines. Section 4.1 defines the evaluation sets.

For knockout, let $q(L)$ be the fraction of eligible, originally correct answers that remain correct. Source-attention dependence is

$$d(L) = 1 - q(L). \tag{4}$$

Higher d means more correct answers are lost when source attention is blocked. We compare ρ and d on common eligible question IDs, while retaining each test's baselines. The two measures describe restoration in the receiver and dependence in the donor. A separate paired-outcome check tests whether individual questions fail both interventions.

Depth boundaries. After establishing effective early transfer, we summarize the curves by their first half-effect boundaries:

$$\begin{aligned} T &= \min\{L : \rho(L) < 0.5\}, \\ R &= \min\{L : d(L) \le 0.5\}, \qquad \Delta = R - T. \end{aligned} \tag{5}$$

We report these boundaries when both crossings exist. The separation set $\mathcal{W} = \{L : \rho(L) < 0.5,\ d(L) > 0.5\}$ contains layers with weak transfer and strong source dependence. This set may contain several intervals. The thresholds summarize half-effect sizes, and Figure 3 retains later threshold crossings. Depth indexes processing layers within each token's computation.

The execution state before generation. For one question, split the complete n-token prompt before its last token u_*. The processed prefix has positions $\mathcal{P} = \{0, \ldots, n-2\}$, including the skill and question. Let $\overline{\mathcal{I}} = \mathcal{P} \setminus \mathcal{I}$. Attention reuses cached keys and values for these processed tokens [21]. At this point, define $C_X^\ell[\mathcal{I}] = (K_X^\ell[\mathcal{I}], V_X^\ell[\mathcal{I}])$, collect all layers as $C_X[\mathcal{I}]$, and write $\mathcal{B}_X = C_X[\overline{\mathcal{I}}]$ for the other prefix caches. With model parameters θ, positions, stopping rule and greedy decoding fixed, the continuation is

$$\hat{y}_X = \mathcal{G}_{\theta, M_X}(u_*, C_X[\mathcal{I}], \mathcal{B}_X). \tag{6}$$

Here M_X specifies attention masks, and $\mathcal{G}$ includes computing u_* and generating the answer from both source and other prefix caches.

Cache replacement and joint repair. After prefix prefill and before computing u_*, cache replacement writes

$$C: \quad C_X^\ell[\mathcal{I}] \leftarrow C_D^\ell[\mathcal{I}], \qquad 0 \le \ell \le L. \tag{7}$$

The prefix is computed without state replacement for C ($X = R$), or with the block-L write for SC ($X = S$). The post-prefill write preserves the other prefix caches. Thus $\mathcal{B}_C = \mathcal{B}_R$ and $\mathcal{B}_{SC} = \mathcal{B}_S$, although $\mathcal{B}_S$ can differ from $\mathcal{B}_R$ through indirect effects of S. Under the causal assumptions in Appendix B.2, ideal state replacement reconstructs source KV at layers above L. The explicit cache write supplies layers 0 through L, giving donor-aligned source caches under SC while retaining the receiver's other prefix caches $\mathcal{B}_S$. Figure 2 shows the write schedule.

From cache repair to output recovery. At this same observation point, flatten the prefix caches into $\mathbf{z}_X = (\mathbf{c}_X, \mathbf{b}_X)$, where $\mathbf{c}_X$ contains exactly the source KV entries at layers $0, \ldots, L$. The remaining vector $\mathbf{b}_X$ includes higher-layer source KV as well as $\mathcal{B}_X$. Adding the cache write to S gives $\mathbf{z}_{SC} = (\mathbf{c}_D, \mathbf{b}_S)$ without changing $\mathbf{b}_S$. For $\varepsilon_X = \|\mathbf{z}_X - \mathbf{z}_D\|_2$,

$$\begin{aligned} \varepsilon_S^2 &= \|\mathbf{c}_S - \mathbf{c}_D\|_2^2 + \|\mathbf{b}_S - \mathbf{b}_D\|_2^2, \\ \varepsilon_{SC}^2 &= \|\mathbf{b}_S - \mathbf{b}_D\|_2^2, \\ \varepsilon_S^2 - \varepsilon_{SC}^2 &= \|\mathbf{c}_S - \mathbf{c}_D\|_2^2 \geq 0. \end{aligned} \tag{8}$$

Here $\|\cdot\|_2$ is the Euclidean length of a vector. For an exact copy, the coordinate decomposition proves that the squared cache distance decreases by precisely the replaced entries' squared error, independently of the causal reconstruction claim above. Appendix B.3 gives a sufficient condition for donor decoding: at every step, the change in each unnormalized token score, called a logit, must be less than half the donor's margin. The margin is the difference between its highest and second-highest scores. The condition includes cache updates and stopping.

Reading cuts and their timing. A *skill-reading cut* blocks reader-to-source attention. A *within-skill attention cut* blocks source-to-source attention. In SC + cut, the reading mask is

$$\widetilde{z}_{ij}^{\ell} = \begin{cases} -\infty, & \ell \geq L+1,\ i \in \mathcal{J},\ j \in \mathcal{I}, \\ z_{ij}^{\ell}, & \text{otherwise.} \end{cases} \tag{9}$$

It is installed before prefix prefill and persists during decoding. Source-to-source attention remains unmasked, but reader computation can change already during prefill. Consequently both M_X and $\mathcal{B}_X$ in Eq. (6) can differ from SC. The separate original-run path tests start their cuts at L, not $L+1$. Adding a within-skill cut to a persistent reading cut is structurally redundant for the output (Appendix B.1).

Three repair contrasts. On one fixed evaluation set under one protocol, let $a_X(L)$ denote accuracy for condition X. Suppressing L on the right, define

$$\begin{aligned} \Delta_{\text{cache}}(L) &= a_{SC} - a_S, \\ \Gamma(L) &= (a_{SC} - a_S) - (a_C - a_R), \\ \Delta_{\text{read}}(L) &= a_{SC} - a_{SC+\text{cut}}. \end{aligned} \tag{10}$$

These measure the added cache benefit, the interaction on the accuracy scale, and sensitivity of joint repair to a reading cut. Positive Γ means the joint gain exceeds the sum of the individual gains. These are intervention contrasts on the accuracy scale. Multiplying them by 100 gives percentage points.

4 Experiments

The experiments follow three questions. Does early state transfer carry skill-relevant information? Does that transfer weaken before dependence on the skill does? Can source-cache replacement restore part of the late transfer deficit?

4.1 Experimental setup

Tasks and models. We pair MedCalc-Bench [15] with skills from SRA-Bench, a benchmark that pairs questions with reusable skill documents [23], covering 1,100 questions from 55 clinical calculators. We also use SRA-Bench's TheoremQA subset, with 747 questions and 320 skills. TheoremQA tests the application of theorems across mathematics, physics, electrical engineering and computer science, and finance [5], extending the evaluation beyond clinical calculations. Each question receives its designated skill. Skill selection is held fixed.

The four main models are Qwen3-8B [30], Mistral-7B-Instruct-v0.3 [14], Llama-3.1-8B-Instruct [9] and DeepSeek-LLM-7B-Chat [7]. The depth study covers all eight combinations of model and benchmark (Table 2). Qwen3-8B and Mistral on TheoremQA use regenerated answers with independently checked grading (Appendix A.2). Models generate step-by-step answers without tools using greedy decoding, and the benchmark scorers evaluate those answers. On the full MedCalc benchmark, Qwen3-8B achieves 74.2% accuracy with the correct skill, 34.5% without one, and 31.5% with an unrelated skill.

Analysis populations. We select questions using earlier with-skill and without-skill outcomes, then re-evaluate unmodified runs, or baselines, under each protocol. The group receiver screen retains a skill only if its receiver solves none of its sampled questions.

For Qwen3-8B/MedCalc, we use 135 questions for controls (Table 1), 134 for common depth curves (Figure 3), 124 for the paired-outcome check (§4.3), and 114 for repair and path cuts (Figure 4). The control donor answers 124/135 correctly. The common depth set intersects transfer eligibility with correct-with-skill, incorrect-without-skill knockout outcomes. The paired check also requires both donors to be correct.

The added control cells require correct donor and incorrect no-skill baselines. Repair uses that rule plus an incorrect receiver for each item. Llama and DeepSeek reuse fixed candidate pools selected by earlier models. Intervention estimates are conditional on these selection rules. Each depth panel uses common question IDs for its two interventions. Repair and path tests likewise share question IDs within each model and task combination, using their own fresh-baseline screen. Appendix A details the distinct selection rules.

Protocol consistency. Historical Qwen3-8B and regenerated Qwen/Mistral TheoremQA runs use different attention implementations for transfer and knockout. Llama and DeepSeek use matching implementations. Repair and path cuts share a protocol with fresh baselines. Identity controls copy receiver states back to their original positions and reproduce its output tokens exactly. Resetting the TheoremQA evaluator before every answer and reversing grading order preserve the labels. Implementation details and corrections are in Appendix A.

4.2 Validation of skill-state transfer

Early transfer recovery. The depth comparison requires a state-transfer test that works at early layers. At layer 8 on the 135-item Qwen3-8B/MedCalc set, copying states at the skill positions yields 110 correct answers. The donor answers 124 of the same 135 questions correctly and the receiver answers none, giving aggregate recovery $\rho = 110/124 = 0.89$ (Table 1). Patching the last prompt position or the final 16 positions has much smaller effects. The skill

Table 1: State-transfer controls at layer 8 across four models and two benchmarks. Entries are accuracy (%). n/G counts questions and skills. Qwen3-8B/MedCalc retains re-evaluated donor failures. The other cells additionally require a correct donor and incorrect no-skill baseline. The two matched-prefix rows replace the same number of leading skill positions with correct or unrelated content. Final-token controls replace fewer positions. Layer 8 is already beyond the transfer boundary for some models (Table 2).

Intervention	Qwen3-8B		Mistral-7B		Llama-3.1-8B		DeepSeek-7B	
	MedCalc	TheoremQA	MedCalc	TheoremQA	MedCalc	TheoremQA	MedCalc	TheoremQA
n/G	135/14	57/49	35/13	61/51	112/20	92/71	25/13	54/45
Correct skill donor	91.9	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Wrong skill receiver	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Correct skill span	**81.5**	**78.9**	**20.0**	**37.7**	**33.0**	**23.9**	**8.0**	**11.1**
Last prompt token	3.0	10.5	5.7	1.6	2.7	12.0	0.0	1.9
Last 16 prompt tokens	5.9	12.3	8.6	6.6	2.7	4.3	4.0	11.1
Correct matched prefix	59.3	71.9	17.1	37.7	35.7	22.8	12.0	7.4
Other-skill matched prefix	4.4	14.0	2.9	8.2	8.0	9.8	8.0	5.6
Correct span, permuted	4.4	22.8	14.3	14.8	4.5	14.1	4.0	5.6
Norm-matched noise	2.2	19.3	8.6	4.9	4.5	9.8	4.0	0.0
Identity patch	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

span is therefore an effective intervention site. The matched-prefix controls below compare content at equal replacement lengths.

Content and position controls. The paired content controls replace a common prefix length with either correct-skill or other-skill information. Correct content recovers 0.65 of the donor's gain, versus 0.05 for other-skill content. Shuffling source positions and injecting random vectors of matching length also give little recovery. The latter is the norm-matched noise control, which preserves the Euclidean length of the skill-state change. Rescaling the correct patch to the receiver's norm still recovers 0.87. Together, these controls support a role for skill-specific content and its arrangement. The expanded table reports the same controls for every model and task. Since layer 8 follows the transfer boundary in several cells, its lower recovery is consistent with Figure 3. An additional layer-2 check gives 56.0% to 93.4% span accuracy across the eight cells, above noise and shuffled-position controls in each case (Appendix A.2).

Cross-question transfer. In the main prompt order, the skill precedes the question. Causal attention prevents those skill states from encoding a later question. We additionally place the skill after the question and take donor states from other questions using the same skill. On 151 eligible items from 17 calculators, these states recover 0.98 at layer 8, close to 1.02 for a donor answering the current question. At layer 16, the values separate to 0.29 and 0.49. Early transfer thus carries information shared across questions, with greater question sensitivity later. Further content, controls varying the strength and retained directions of a state change appear in Appendix B.

4.3 Weak transfer with persistent source dependence

Depth separation. Early transfer is effective, but it weakens before source dependence does. Figure 3 shows the full curves, and Table 2 summarizes their boundaries.

The dependence boundary follows the transfer boundary in all eight comparisons. The gaps are 8 to 20 layers, or 22.2% to 62.5% of model depth (Table 2). The common direction spans both benchmarks and all four model families.

A representative depth profile. For Qwen3-8B/MedCalc, recovery drops from 0.73 at layer 12 to 0.16 at 13 and stays below 0.08 from 15 onward. Dependence remains 0.93 at 13 and 0.75 at 24. Throughout layers 13 to 24, transfer restores less than half of the donor's gain while knockout removes more than half of the originally correct answers (Figure 3).

Paired outcomes and robustness. The separation also occurs within questions. In the Qwen3-8B/MedCalc paired check, 100/124 (80.6%) fail both interventions at layer 13, and 113/124 (91.1%) at 16 (Appendix B). The boundary ordering also holds at thresholds 0.4 and 0.6 in all eight comparisons. Broader screening and later threshold crossings appear in Appendix B.

4.4 Partial restoration with source-cache replacement

Testing an omitted source component. Figure 4 compares all eight model and task combinations, separating receiver repair at $L16$ (panel a) from attention cuts in the original correct-skill run at $L8$, $L16$ and $L24$ (panel b).




Figure 3: State transfer weakens before source-attention dependence across eight combinations of model and task. Rows show MedCalc (top) and TheoremQA (bottom), with models aligned by column. Mint: recovery $\rho(L)$ in the wrong-skill receiver. Pink dash-dotted: dependence $d(L)$ in the original correct-skill run. Each panel uses common eligible questions with each protocol's own baselines. G counts skills. Shading spans the first half-effect boundaries (Table 2). Later threshold crossings remain visible. Knockout blocks both skill reading and within-skill attention. Every layer is measured.

Table 2: Main depth comparison across four open-weight models and two benchmarks. n/G gives common eligible questions/skill groups. T and R are the first half-effect crossings for transfer ($\rho < 0.5$) and aggregate source dependence ($d \le 0.5$). $\Delta = R - T$ is in layers. Δ/D normalizes the gap by the model's layer count. All eight cells use audited common-item populations.

Model	MedCalc-Bench					TheoremQA				
	n/G	T	R	Δ	Δ/D (%)	n/G	T	R	Δ	Δ/D (%)
Qwen3-8B	134/14	13	25	12	33.3	82/66	13	21	8	22.2
Mistral-7B	46/16	7	27	20	62.5	72/58	7	19	12	37.5
Llama-3.1-8B	112/20	7	18	11	34.4	92/71	6	18	12	37.5
DeepSeek-7B	25/13	6	21	15	50.0	54/45	4	19	15	50.0

Repair gains in the receiver. Adding caches improves accuracy over state transfer alone in all eight layer-16 comparisons, by 6.8 to 43.4 percentage points (Figure 4a). Joint-repair accuracy ranges from 10.2% to 62.3%. For Qwen3-8B/MedCalc, S, C and SC answer 4, 8 and 48 of 114 questions correctly (3.5%, 7.0%, 42.1%). The cache benefit is $\Delta_{\text{cache}} = (48 - 4)/114$, or 38.6 percentage points. The accuracy interaction is $\Gamma = (48 - 4 - 8 + 0)/114$, or 31.6 points (Eq. (10)). At layer 24, SC reaches 25.4%, versus 0.9% for S and 18.4% for C. The added benefit of states alongside caches varies. For Mistral/MedCalc at $L16$, SC and C both reach 18.4%, with $\Gamma = -7.9$ points. Table 5 reports all individual conditions and contrasts.

Is complete source state sufficient? We test this on a fixed pool of 124 Qwen3-8B/MedCalc questions from 14 skills, using both an unrelated-skill receiver and a fixed unrelated text receiver (Neutral). All conditions share BF16, eager attention, split prefill and greedy decoding. This pool retains fresh donor failures; it differs from the 114-item repair screen above. For SC at $L8$, $L16$ and $L24$, every source-position K/V tensor at every layer exactly matches the donor before continuation. Explicitly rewriting all source layers changes none of the 744 paired outputs. Yet accuracy drops from 91.9% to 25.8% between $L8$ and $L24$ in the unrelated-skill receiver, and from 91.1% to 26.6% in Neutral (Table 3). Thus missing source-cache layers alone cannot account for the late deficit.

Copying the complete prefix cache reproduces the donor tokens on every question in both contexts. Copying source KV and recomputing the prompt positions after the skill instead reaches 96.8%, although its tokens match the donor on only 48/124 questions per




Figure 4: Repair and attention cuts across four models and two benchmarks. MC denotes MedCalc and TQA denotes TheoremQA. (a) Receiver accuracy at $L16$ for state replacement (S), cache replacement (C), joint repair (SC), and joint repair with a reading cut from $L17$ onward (SC + cut). (b) Correct answers lost in the original correct-skill run under cuts from $L8$, $L16$ or $L24$ onward during prefill and decoding. Skill reading blocks reader-to-source attention. Within-skill attention blocks source-to-source attention. Each row uses the same questions in both panels, with counts in Table 5. Layer numbers index each model's blocks.

Table 3: Complete-source controls on the same 124 Qwen3-8B/MedCalc questions. Entries are accuracy (%). Wrong and Neutral denote the two receiving contexts. C_{all} copies source KV at every layer; it differs from C, which copies only through the intervention layer. The correct-skill donor scores 97.6%.

Intervention	Wrong	Neutral
Receiver	4.8	4.0
C_{all}	29.8	25.0
SC at $L8$	91.9	91.1
SC at $L16$	41.9	28.2
SC at $L24$	25.8	26.6
Copy other prefix KV only	2.4	8.1
Copy complete prefix KV	97.6	97.6
C_{all} + replay later prompt	96.8	96.8

context. The remaining state therefore matters: caches at question and template positions can retain consequences of earlier skill processing. These controls establish neither a minimal state to copy nor a low-cost reuse method. Appendix B.4 gives content and layer-window controls, paired uncertainty estimates and implementation checks.

Reading under joint repair. Reading cuts reduce joint-repair accuracy by 2.2 to 37.7 points across all eight layer-16 comparisons. For Qwen3-8B/MedCalc, accuracy falls from 42.1% to 7.0%, giving $\Delta_{\text{read}} = (48 - 8)/114$, or 35.1 points. Thus the cross-model improvement from adding caches coexists with continued use of the skill. The Qwen3-8B/MedCalc result at $L24$ differs: the cut gives 27.2% versus 25.4% without it. Appendix B.1 documents the layer grid and checks sensitivity to outputs stopped at the generation limit.

Attention paths in the original run. Figure 4(b) tests the original correct-skill execution. At $L8$, both types of cut cause large losses across the eight rows. At $L24$, Skill reading loses 11.9% to 74.6% of correct answers, exceeding Within-skill attention by 6.8 to 71.1 points in every row. The Qwen3-8B/MedCalc contrast is 74.6% versus 3.5%. At this measured depth, later positions' access to the skill has a larger effect than attention among skill positions across all eight settings.

5 Discussion

Potential applications. Our findings suggest a way to evaluate the reuse of contextual skills. Consider a Web agent that repeatedly follows the same instructions across requests. A reusable internal representation would need to preserve task performance in the receiving execution. Our results motivate evaluating this transfer separately from the original execution's dependence on the skill. If a reuse method also removes access to the original instructions, that additional change needs its own evaluation. The observed cache gains motivate reuse methods that carry both hidden states and attention caches across requests. Deployment studies can evaluate their latency, memory use and task performance in interactive Web settings.

Future work. A next step is to investigate which questions benefit from cache replacement. The mathematical analysis connects remaining cache differences to output stability under explicit assumptions. Measuring these differences, their influence on token predictions and the donor's prediction margins could test whether this framework helps distinguish successful from unsuccessful

repairs. The complete-source controls further motivate testing which parts of the receiving history must be recomputed, and whether the required budget can be predicted on held-out skills. Extending these controls beyond Qwen3-8B/MedCalc would test their cross-model and cross-task scope. Separating attention cuts during prompt processing from those during answer generation would clarify when continued skill access matters. Finally, multi-step Web workflows would assess how far the observed separation extends beyond the question-answering settings studied here.

6 Conclusion

Using a contextual skill and reusing its internal states are distinct capabilities. Across four models and two benchmarks, state transfer weakens before the original execution's dependence on skill attention, with half-effect boundaries separated by 8 to 20 layers. Early content controls establish that the transferred states carry skill-relevant information, and the depth comparisons show that this information becomes harder to reuse while the skill remains useful.

Source-cache replacement provides a way to recover part of that transfer. At layer 16, adding caches improves accuracy over states alone by 6.8 to 43.4 percentage points in all eight comparisons, while cutting subsequent skill reading reduces the joint-repair accuracy in each. The mathematical analysis connects cache alignment to output stability under explicit conditions. Together, these findings motivate evaluating state reuse separately from continued skill use and including cached information in the design of reusable skill representations.

References

[1] Thibaud Ardoin, Semira Einsele, Evis Bregu, and Gerhard Wunder. 2026. Prompt Compression via Activation Aggregation. *arXiv preprint arXiv:2607.08399* (2026).

[2] Irina Bigoulaeva, Jonas Rohweder, Subhabrata Dutta, and Iryna Gurevych. 2026. Patches of Nonlinearity: Instruction Vectors in Large Language Models. In *Proceedings of the 64th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, San Diego, California, United States, 12209–12262. doi:10.18653/v1/2026.acl-long.559

[3] Lucas Caccia, Alan Ansell, Edoardo Ponti, Ivan Vulić, and Alessandro Sordoni. 2025. Training Plug-n-Play Knowledge Modules with Deep Context Distillation. In *Conference on Language Modeling (COLM)*. arXiv:2503.08727.

[4] Rujikorn Charakorn, Edoardo Cetin, Shinnosuke Uesaka, and Robert Tjarko Lange. 2026. Doc-to-LoRA: Learning to Instantly Internalize Contexts. *arXiv preprint arXiv:2602.15902* (2026).

[5] Wenhu Chen, Ming Yin, Max Ku, Pan Lu, Yixin Wan, Xueguang Ma, Jianyu Xu, Xinyi Wang, and Tony Xia. 2023. TheoremQA: A Theorem-driven Question Answering Dataset. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. https://arxiv.org/abs/2305.12524 arXiv:2305.12524.

[6] Guy Davidson, Todd M. Gureckis, Brenden M. Lake, and Adina Williams. 2025. Do different prompting methods yield a common task representation in language models? *arXiv preprint arXiv:2505.12075* (2025). https://arxiv.org/abs/2505.12075

[7] DeepSeek-AI. 2024. DeepSeek LLM: Scaling Open-Source Language Models with Longtermism. *arXiv preprint arXiv:2401.02954* (2024).

[8] Tao Ge, Jing Hu, Lei Wang, Xun Wang, Si-Qing Chen, and Furu Wei. 2024. In-context Autoencoder for Context Compression in a Large Language Model. In *International Conference on Learning Representations (ICLR)*. arXiv:2307.06945.

[9] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. 2024. The Llama 3 Herd of Models. *arXiv preprint arXiv:2407.21783* (2024).

[10] Sina Hajimiri, Masih Aminbeidokhti, Jose Dolz, Ismail Ben Ayed, Issam H. Laradji, Spandana Gella, and Nicolas Gontier. 2026. Are Online Skill and Memory Modules Always Worth Their Tokens? A Budget-Constrained Study of Web Agents. *arXiv preprint arXiv:2606.15017* (2026). https://arxiv.org/abs/2606.15017

[11] Tingxu Han, Yi Zhang, Wei Song, Chunrong Fang, Zhenyu Chen, Youcheng Sun, and Lijie Hu. 2026. SWE-Skills-Bench: Do Agent Skills Actually Help in Real-World Software Engineering? *arXiv preprint arXiv:2603.15401* (2026).

[12] Stefan Heimersheim and Neel Nanda. 2024. How to use and interpret activation patching. *arXiv preprint arXiv:2404.15255* (2024).

[13] Roee Hendel, Mor Geva, and Amir Globerson. 2023. In-Context Learning Creates Task Vectors. In *Findings of the Association for Computational Linguistics: EMNLP 2023*. arXiv:2310.15916.

[14] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, et al. 2023. Mistral 7B. *arXiv preprint arXiv:2310.06825* (2023).

[15] Nikhil Khandekar, Qiao Jin, Guangzhi Xiong, Soren Dunn, Serina S. Applebaum, Zain Anwar, Maame Sarfo-Gyamfi, Conrad W. Safranek, Abid A. Anwar, Andrew Zhang, Aidan Gilson, Maxwell B. Singer, Amisha Dave, Andrew Taylor, Aidong Zhang, Qingyu Chen, and Zhiyong Lu. 2024. MedCalc-Bench: Evaluating Large Language Models for Medical Calculations. In *Advances in Neural Information Processing Systems (NeurIPS), Datasets and Benchmarks Track*. arXiv:2406.12036.

[16] Bojie Li. 2026. Models Take Notes at Prefill: KV Cache Can Be Editable and Composable. *arXiv preprint arXiv:2606.17107* (2026). https://arxiv.org/abs/2606.17107

[17] Xiangyi Li, Yimin Liu, Wenbo Chen, et al. 2026. SkillsBench: Benchmarking How Well Agent Skills Work Across Diverse Tasks. *arXiv preprint arXiv:2602.12670* (2026).

[18] Yuxuan Li, Declan Campbell, Stephanie C. Y. Chan, and Andrew Kyle Lampinen. 2025. Just-in-time and distributed task representations in language models. *arXiv preprint arXiv:2509.04466* (2025).

[19] Jesse Mu, Xiang Lisa Li, and Noah Goodman. 2023. Learning to Compress Prompts with Gist Tokens. In *Advances in Neural Information Processing Systems (NeurIPS)*. arXiv:2304.08467.

[20] Aditya Pola and Vineeth N. Balasubramanian. 2025. Where does an LLM begin computing an instruction?. In *UniReps Workshop*. extended abstract. arXiv:2511.10694.

[21] Noam Shazeer. 2019. Fast Transformer Decoding: One Write-Head is All You Need. *arXiv preprint arXiv:1911.02150* (2019). https://arxiv.org/abs/1911.02150

[22] Suzanna Sia, David Mueller, and Kevin Duh. 2024. Where does In-context Learning Happen in Large Language Models?. In *Advances in Neural Information Processing Systems (NeurIPS)*. doi:10.52202/079017-1030

[23] Weihang Su, Jianming Long, Qingyao Ai, Qiaozhi He, Yichen Tang, Changyue Wang, Yiteng Tu, Yingbo Wang, and Yiqun Liu. 2026. Skill Retrieval Augmentation for Agentic AI. *arXiv preprint arXiv:2604.24594* (2026).

[24] Eric Todd, Millicent L. Li, Arnab Sen Sharma, Aaron Mueller, Byron C. Wallace, and David Bau. 2024. Function Vectors in Large Language Models. In *International Conference on Learning Representations (ICLR)*. arXiv:2310.15213.

[25] Yusuke Tsuzuku, Issei Sato, and Masashi Sugiyama. 2018. Lipschitz-Margin Training: Scalable Certification of Perturbation Invariance for Deep Neural Networks. *arXiv preprint arXiv:1802.04034* (2018). https://arxiv.org/abs/1802.04034

[26] Sankaran Vaidyanathan, David Arbour, Aaron Mueller, Scott Niekum, and David Jensen. 2026. The Curse of Multiple Mediators: Hidden Interaction Effects in Activation Patching. *arXiv preprint arXiv:2606.27510* (2026). https://arxiv.org/abs/2606.27510

[27] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention Is All You Need. In *Advances in Neural Information Processing Systems*, Vol. 30. https://arxiv.org/abs/1706.03762

[28] Zhaoyang Wang, Qianhui Wu, Xuchao Zhang, Chaoyun Zhang, Wenlin Yao, Fazle Elahi Faisal, Baolin Peng, Si Qin, Suman Nath, Qingwei Lin, Chetan Bansal, Dongmei Zhang, Saravan Rajmohan, Jianfeng Gao, and Huaxiu Yao. 2026. WebXSkill: Skill Learning for Autonomous Web Agents. *arXiv preprint arXiv:2604.13318* (2026). https://arxiv.org/abs/2604.13318

[29] Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2025. Agent Workflow Memory. In *Proceedings of the 42nd International Conference on Machine Learning (Proceedings of Machine Learning Research, Vol. 267)*. PMLR, 63897–63911. https://proceedings.mlr.press/v267/wang25bx.html

[30] An Yang, Anfeng Li, et al. 2025. Qwen3 Technical Report. *arXiv preprint arXiv:2505.09388* (2025).

[31] Zhipeng Yang, Junzhuo Li, Siyu Xia, and Xuming Hu. 2025. Internal Chain-of-Thought: Empirical Evidence for Layer-wise Subtask Scheduling in LLMs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. 22536–22564. doi:10.18653/v1/2025.emnlp-main.1147

[32] Barry Zhang, Keith Lazuka, and Mahesh Murag. 2025. Equipping agents for the real world with Agent Skills. Anthropic Engineering. https://www.anthropic.com/engineering/equipping-agents-for-the-real-world-with-agent-skills

[33] Fred Zhang and Neel Nanda. 2024. Towards Best Practices of Activation Patching in Language Models: Metrics and Methods. In *International Conference on Learning Representations (ICLR)*. arXiv:2309.16042.

A Experimental protocols and provenance

Tasks and scoring. MedCalc provides 55 calculator skills and 20 questions per calculator through SRA-Bench, scored against prescribed numerical tolerances. TheoremQA uses its released prompts,

Table 4: Screening and full-pool rerun for Qwen3-8B/MedCalc at layer 8. Entries show recovery (Eq. 3). The group screen keeps calculators whose receiver solves no sampled question. The item screen keeps individual receiver failures. Category means related calculator functions. Direction and quarter controls are defined in Appendix B. Each condition uses its own matched baselines. "Not run" marks an unmeasured condition.

Intervention	Full, group screen (n = 135)	Subset (n = 60)	Full, item screen (n = 369)
Correct skill span	**0.89**	0.87	0.94
same skill, matched prefix	0.65	0.73	0.84
Half-strength change $\alpha = 0.5$	0.04	0.06	0.11
positions permuted	0.05	0.08	0.21
norm-matched noise	0.02	0.10	0.18
other calculator	0.05	Not run	0.25
other calculator category, mean	0.05	0.06	0.16
same calculator category, mean	0.12	0.05	0.24
identity patch	0.00	0.00	0.00
Leading directions: 128/64/32/16	0.77/0.63/0.12/0.05	0.77/0.54/0.13/0.06	0.88/0.70/0.22/0.18
Least prominent directions: 64/16	0.03/0.04	0.00/0.06	0.11/0.12
Skill quarters: 1/2/3/4	0.09/**0.56**/0.12/0.05	0.12/0.56/0.12/0.12	0.18/0.64/0.22/0.19

skill assignments and evaluator. Skills are supplied directly, with no tools during generation. Groups are calculators for MedCalc and skill identities for TheoremQA.

Evaluation populations. The original MedCalc list contains 470 previously rescued questions, answered incorrectly without a skill and correctly with one. Eligibility restrictions leave 467 from 48 calculators for corrected transfer controls.

The group screen retains skills with no correct receiver answers, including donor failures. Its 135 questions from 14 calculators yield 124 correct donor and 110 correct layer-8 span answers. Recovery uses the measured donor gain. Intersection with knockout's correct-with-skill, incorrect-without-skill IDs gives 134 depth items, with separate intervention baselines.

The seven added control cells require a fresh correct donor and incorrect no-skill baseline, giving 100% donor accuracy. Repair instead screens individual items. Of 124 candidate IDs, 116 are donor-correct and receiver-incorrect, and 114 also fail without the skill. Repair and path cuts share these 114. The candidate, paired-check and correct-donor counts each equal 124 under different, non-interchangeable rules.

The broader screen in Appendix B retains individual receiver failures. Other-skill and noise interventions are more effective under this broader screen, as reported in Table 4. The common DeepSeek/MedCalc depth set contains 25 questions, so its boundary may be sensitive to sample composition. Changing the half-effect threshold tests the summary rule, not that sampling sensitivity.

A.1 Implementation details

Wrong-skill selection and token matching. Each dataset uses one fixed distractor. MedCalc uses APACHE II, a clinical severity score (`medcalcbench_043`), as a long distractor outside the selected calculators. TheoremQA uses `theoremqa_148`, a mathematical skill about representation theorems and differential equations, selected by fewest assigned questions, then greatest document length. Its assigned items are excluded. We repeat the distractor's tokens if needed and copy the first m into the target span of width m, without padding. All other tokens and positions remain unchanged. This context may repeat or truncate the alternative skill.

Prompt and source boundaries. The user turn has the order `Relevant Skill:`, skill text, a blank line, and the benchmark's question prompt. MedCalc appends the instruction to show calculations and end with `ANSWER: <your answer>`. Its system message asks for a step-by-step score calculation from a patient note. TheoremQA retains the benchmark's science-teacher system message, `Problem:<question>` and `Solution:` user format, and "Therefore, the answer is ..." final-answer requirement. The tokenizer converts text to tokens. Its chat template supplies role labels and the generation prompt. Character offsets identify tokens overlapping the skill text, excluding its header and separator. We replace IDs in [lo, hi), including the start but excluding the end, without decoding and retokenizing.

Models and decoding. The four main models are Qwen3-8B (36 layers, hidden width 4096), Mistral-7B-Instruct-v0.3 (32 layers, width 4096), Llama-3.1-8B-Instruct (32 layers) and DeepSeek-LLM-7B-Chat (30 layers). Llama and DeepSeek state capture and knockout use BF16, a 16-bit floating-point format, and 900 new tokens. Both use eager attention, which explicitly computes attention scores and applies the mask, without further reducing weight precision. DeepSeek and Mistral merge system instructions into the user turn. Llama uses the original weights, configuration and vocabulary with the public distribution's tokenizer template. Decoding is greedy, with Qwen's extended-reasoning mode disabled. Earlier state replacement uses PyTorch scaled dot-product

attention (SDPA). Regenerated Qwen and Mistral TheoremQA runs use SDPA for transfer, eager attention for knockout and 900 new tokens. Historical Qwen3-8B/MedCalc also allows 900 tokens in both runs, with different attention implementations. Repair and path experiments use BF16, eager attention and 1,536 new tokens. All their conditions split prefill before the final prompt token, allowing cache writes before its recomputation. All cuts span prefill and decoding. Layer indices in the path comparisons refer to the measured blocks, not matched computational stages across models.

Position and state checks. Length matching preserves question positions. Patches replace prefill block outputs indexed separately from scored answer tokens. Identity controls write back receiver states. A final-layer patch reproduces donor next-token scores at that position. Cuts preserve the causal mask.

Checking the prefill procedure. A preliminary comparison of full and split prefill uses one item from each of 14 calculators. All 84 own-state checks reproduce receiver tokens exactly. Changing prefill changes one donor's and one receiver's correctness, motivating fresh baselines under the common split protocol. Result records retain truncation counts and sensitivity analyses.

A.2 Evaluation scope and intervention provenance

Attention-mask correction. State capture originally omitted the decoding attention mask. These mathematically equivalent calls for unpadded sequences selected different numerical implementations, producing state differences of 1.2% at layer 8 and 25% at 34. Identity patching changed 108/1,766 Qwen3-8B outcomes (6.1%). Matching masks restores exact identity agreement, including all 467 corrected MedCalc items. All main state interventions use this correction. Knockout modifies masks without donor-state capture.

Development and replication. Initial MedCalc controls sampled four rescued questions from each of the 40 largest eligible calculator groups. The corrected Qwen3-8B rerun uses all rescued questions from groups with at least two (Table 4). The eight-cell depth study uses common items for both interventions.

Extension pools and grading checks. The Llama and DeepSeek extensions use frozen pools of 446 MedCalc and 255 TheoremQA questions inherited from earlier models' eligible transfer items. Each model is screened again on its own unpatched baselines. One DeepSeek/MedCalc candidate cannot reserve 900 answer tokens and is excluded before inference. TheoremQA regrading uses official rules, resetting the parser per answer. Reversed-order and separate-process checks agree before eligibility is recomputed. Qwen3-8B and Mistral TheoremQA regeneration uses 168 and 142 frozen candidates, yielding 82/66 and 72/58 common questions/skills. Neither audit finds grading changes, missing common layer entries or identity failures. Reverse-order and 16 separate-process checks per model agree.

Layer-2 controls use their own screened sets. In the model order of Table 1, the MedCalc question counts are 97, 35, 112, 25 and correct-span counts are 87, 24, 101, 14. TheoremQA counts are 61, 61, 92, 54, with 57, 52, 70, 31 correct. The DeepSeek/TheoremQA cells use the final 54-item grading correction.

Artifact availability. Stored artifacts contain configurations, question IDs, answers and token sequences. An anonymous review archive is not yet linked.

B Additional transfer and source-dependence analyses

The original Qwen3-8B/MedCalc controls sampled four rescued questions from each of 40 calculators (160 items). The group screen retained 60 from 15 calculators. The rerun used all 467 eligible questions from 48 calculators with the same interventions. Screening whole groups now requires failure on up to 20 questions instead of four, retaining 135 from 14 calculators. Screening each item separately retains 369 from 45 calculators (Table 4).

For the dose and rank controls in Table 4, the state difference is $\delta^L = H_D^L[\mathcal{I}] - H_R^L[\mathcal{I}]$. The rank implementation preserves the mean over source positions. Let $\bar{\delta}^L$ repeat that mean at every row, and define $\delta_k^L = \bar{\delta}^L + (\delta^L - \bar{\delta}^L)_k$, where $(\cdot)_k$ retains the leading k components of a singular value decomposition, which ranks directions by how much matrix variation they capture. The dose and rank controls share the notation

$$H_R^L[\mathcal{I}] \leftarrow H_R^L[\mathcal{I}] + \alpha\delta_k^L. \tag{11}$$

Full rank with $\alpha = 1$ is full replacement, and $\alpha = 0.5$ is half the state difference. Rank controls use $\alpha = 1$. Increasing k from 32 to 64 restores much of the recovery. A bottom-k control instead retains the least prominent directions of the centered variation, with the same mean retained. The second of four equal portions of the skill, containing its formula, gives the largest recovery when copied alone in both samples. The same-category mean donor changes from 0.05 to 0.12, on the 41 full-rerun items where it is available. Here category refers to a calculator group derived from skill-title keywords (for example, related fluid calculations). The intervention averages donor-minus-receiver state differences from other calculators in that group.

The depth sweep at one-layer resolution. The subset sweep measured layers 0, 4, 8, 12, 14, 15, 16, 20 and placed the collapse somewhere after 12. At full scale we added 13 and 17 to 19: recovery is 0.98, 0.98, 0.89, 0.74 at layers 0, 4, 8, 12, then 0.16, 0.16, 0.06, 0.06, 0.07, 0.03, 0.02, 0.03 at 13 through 20 under the group screen. The item screen gives 1.00, 0.98, 0.94, 0.79 then 0.32, 0.34, 0.25, 0.25, 0.23, 0.19, 0.14, 0.17. Both screens show their largest local decline between layers 12 and 13.

Broader screening and boundary sensitivity. The item-level screen retains the transfer decline. Paired knockout comparisons use the common-item populations. Using transfer thresholds $\tau = 0.4$ or 0.6 with dependence thresholds $1 - \tau$ preserves the boundary ordering in all eight main comparisons. Qwen3-8B/MedCalc dependence first falls to at most half at layer 25, rises above half again at 26, and remains below half from 27 onward. The curves retain these recrossings.

Same-question joint failures. This check requires correct donors under both protocols, an incorrect transfer receiver and an incorrect no-skill knockout baseline. Joint failures at the transfer boundary are 100/124 (80.6%) for Qwen3-8B at $T = 13$ and 25/43 (58.1%) for Mistral-7B at $T = 7$, on 14 and 15 MedCalc skill groups. These sets

Table 5: Source-cache repair at layer 16 across four models and two benchmarks. n/G counts questions and skills retained using fresh baselines. S, C, SC and SC + cut show accuracy (%). The last three columns show cache benefit Δ_{cache}, accuracy interaction Γ and reading-cut loss Δ_{read} in percentage points (Eq. (10)). Each row uses the same questions for all conditions, with donor accuracy 100% and receiver accuracy 0%. These populations differ from Table 2.

Model	Task	n/G	S	C	SC	SC + cut	Δ_{cache}	Γ	Δ_{read}
Qwen3-8B	MedCalc	114/14	3.5	7.0	**42.1**	7.0	+38.6	+31.6	+35.1
Qwen3-8B	TheoremQA	53/43	18.9	15.1	**62.3**	24.5	+43.4	+28.3	+37.7
Mistral-7B	MedCalc	38/15	7.9	18.4	**18.4**	5.3	+10.5	−7.9	+13.2
Mistral-7B	TheoremQA	59/49	3.4	5.1	**10.2**	6.8	+6.8	+1.7	+3.4
Llama-3.1-8B	MedCalc	104/20	3.8	5.8	**18.3**	9.6	+14.4	+8.7	+8.7
Llama-3.1-8B	TheoremQA	72/56	4.2	12.5	**41.7**	12.5	+37.5	+25.0	+29.2
DeepSeek-7B	MedCalc	21/10	0.0	19.0	**28.6**	19.0	+28.6	+9.5	+9.5
DeepSeek-7B	TheoremQA	46/40	2.2	6.5	**10.9**	8.7	+8.7	+2.2	+2.2

differ from Table 2. Four items in each pass the transfer no-skill baseline despite failing it under knockout.

Repeated replacement as a consistency check. On the 135 screened MedCalc items, replacing source states at layers 8 to 11, 12 to 15, 14 to 19 and 16 to 35 recovers 0.89, 0.74, 0.16, 0.06. Starting at the first layer recovers 0.98. Repeated and single writes produce identical tokens from each starting layer, consistent with Appendix B.2's causal argument.

A continuous readout at the same boundary. We generate correct-skill reasoning once per item, then score that fixed sequence under each intervention. This is teacher forcing: recorded preceding tokens replace newly generated ones. Mean token log-probability uses natural logarithms, measured in nats. Higher values indicate stronger predictions of the recorded sequence. We normalize it as $z = (\ell_L - \ell_{\text{recv}})/(\ell_{\text{gold}} - \ell_{\text{recv}})$, where ℓ is the mean log-probability for the patched, receiver or donor condition. This z differs from knockout retention q.

On 442 donor-correct items from 48 calculators, z is 0.999, 0.989, 0.960, 0.831, 0.598, 0.595, 0.340, 0.201, 0.129 at layers 0, 4, 8, 12, 13, 14, 16, 20, 24. The 0.233 drop from 12 to 13 is near the accuracy boundary in the separate 134-item depth set. The decline spans all four quarters of the reasoning sequence (0.20, 0.26, 0.31, 0.21). After supplying the reasoning, all conditions predict the final number closely: median log-probabilities lie between −0.001 and −0.005. Their donor-minus-receiver denominator has median 0.0014 and is below 0.01 on 59% of items, limiting this readout.

Distributed reading and receiver state. The attention output contributed by skill positions, normalized by the length of the hidden-state vector, concentrates in layers 12 to 21. Blocking the 32 highest-ranked heads costs 0.39 of the skill's effect, versus 0.23 for random heads at the same layers (calculators not used to rank the heads, paired difference 0.154). Reading uses many heads rather than a small subset. After late span replacement, the attention output from skill positions remains 0.86 to 0.99 of the donor's despite weak behavioural recovery. Earlier receiver question-state updates remain unchanged, motivating the interaction tests in §4.4.

B.1 Source-cache repair and attention-path experiments

The focused Qwen3-8B/MedCalc experiments fix Q_0, comprising 124 historical IDs from 14 calculators, before inference. Four NVIDIA RTX 4090 graphics processors each receive every fourth ID, using the 1,536-token protocol in Appendix A.1. Let e_i^X be binary correctness for item i in condition X, with 0 denoting no skill. Selection uses only fresh baselines:

$$Q_{\text{rep}} = \{i \in Q_0 : e_i^D = 1,\ e_i^R = e_i^0 = 0\}. \tag{12}$$

Of 116 donor-correct, receiver-incorrect items, 114 also fail without a skill. On these same 114 items, every condition uses $a_X(L) = |Q_{\text{rep}}|^{-1} \sum_{i \in Q_{\text{rep}}} e_i^X(L)$. All 372 baseline generations agree token-for-token between the two suites. The complete repair grid contains 2,356 generations, the path grid 1,488, and worker identity checks 100. All 48 own-state writebacks are token-exact.

Figure 4 and Table 5 use this rule for eight comparisons with separate candidates. Repair and path tests share item IDs and baseline tokens within each row. Repair is measured at $L8$, $L12$, $L16$ and $L24$, and path cuts at $L8$, $L16$ and $L24$. Writes, masks and contrasts follow Eqs. (7), (9) and (10).

Qwen3-8B/MedCalc truncation sensitivity. We retain all intervention outcomes, including outputs stopped at the generation limit, which we call truncated outputs. For the prespecified difference between SC and S at layer 16, the gain is 38.6 percentage points. The corresponding accuracy interaction Γ is 31.6 points. $SC - (SC + \text{cut})$ is 35.1 points. On the 96 items with all three baselines untruncated, the SC gain over S is 38.5 points. At layer 16, S, SC and SC + cut truncate 4, 4 and 3 of 114 outputs. Scoring truncated S answers as correct and truncated SC answers as incorrect still leaves a 35.1-point repair advantage. At layer 24, SC and SC + cut truncate 3 and 28 outputs and show no additional loss in measured accuracy.

At layer 24, reader and source-self cuts retain 29/114 and 110/114 correct answers. Their loss difference is 71.1 points. Reader cuts truncate 21 outputs. Counting all as correct still leaves retention at 50/114, below source-self retention 110/114 (no truncation). Both contrasts survive this worst-case reassignment. Experiment records

Table 6: Prefix-cache coverage before the final prompt token, assuming deterministic causal computation in exact arithmetic and a complete, contiguous source span with aligned positions and identical preceding tokens. D and R denote donor and receiver source KV. $\mathcal{B}_R$ and $\mathcal{B}_S$ are all other prefix caches from the unpatched and state-patched runs. The entries are identities derived under these assumptions.

Condition	Source KV		Other KV
	$\ell \le L$	$\ell > L$	All layers
Receiver	R	R	$\mathcal{B}_R$
S	R	D	$\mathcal{B}_S$
C	D	R	$\mathcal{B}_R$
SC	D	D	$\mathcal{B}_S$

retain counts for each condition, file checksums and these sensitivity calculations.

Redundant combined cut. With causal attention and otherwise positionwise operations, earlier tokens cannot read the skill. Persistent reading cuts also prevent its changed states from reaching later tokens. Adding a within-skill cut therefore leaves outputs unchanged by induction over layers and generated tokens. We omit this redundant condition. The argument does not apply when later reading is allowed.

B.2 Cache coverage under causal prefill

This deduction assumes a deterministic causal Transformer with masked attention as its only cross-position operation [27], identical parameters and position IDs, and the same exact-arithmetic computation without extra attention cuts. Donor and receiver tokens differ only within the complete, contiguous source interval $\mathcal{I} = [\mathrm{lo}, \mathrm{hi})$ in the prefix.

Proposition (source-cache coverage). Suppose S replaces the entire source output of block L before the next block executes, and the cache write occurs only after prefix prefill. At the observation point in Eq. (6),

$$C_S^\ell[\mathcal{I}] = \begin{cases} C_R^\ell[\mathcal{I}], & \ell \le L, \\ C_D^\ell[\mathcal{I}], & \ell > L. \end{cases} \tag{13}$$

Together with the explicit write at layers 0 through L, this gives $C_{SC}[\mathcal{I}] = C_D[\mathcal{I}]$.

Proof. Block-L KV is computed before the output patch, leaving source caches at $\ell \le L$ unchanged. Before lo, identical tokens and causality give identical states at every layer. After S, all block-L outputs at $i <$ hi therefore match the donor. At these positions, the next block reads only matching earlier or current states, producing matching source KV and outputs. Induction proves the upper-layer case. Equation (7) supplies the lower layers for SC. □

Remaining execution state. The post-prefill write preserves the other caches (Table 6). Under these assumptions,

$$\begin{aligned} \hat{y}_{SC} &= \mathcal{G}_{\theta,M_0}(u_*, C_D[\mathcal{I}], \mathcal{B}_S), \\ \hat{y}_D &= \mathcal{G}_{\theta,M_0}(u_*, C_D[\mathcal{I}], \mathcal{B}_D), \end{aligned} \tag{14}$$

where M_0 is the original mask. Since $\mathcal{B}_S$ need not equal $\mathcal{B}_D$, answers may differ. All-layer source-KV-only replacement instead preserves $\mathcal{B}_R$ and is generally not equivalent to SC.

Under SC + cut, source queries remain unmasked, so the same induction applies. However, $\mathcal{B}_{SC+\mathrm{cut}}$ may differ from $\mathcal{B}_S$, and continuation uses a different mask. The contrast includes both prefill and decoding effects.

Code inspection confirms the stated write ordering. In the additional Qwen3-8B/MedCalc experiment, runtime elementwise checks found zero source-cache discrepancies against the donor for SC at $L8$, $L16$ and $L24$ in both receiving contexts (Appendix B.4). This verifies coverage for those BF16 runs; the proposition retains its exact-arithmetic assumptions.

B.3 A sufficient condition for behavioral recovery

We apply margin-based stability reasoning [25] to cached decoding, adding a sensitivity assumption to Eq. (8).

One-step guarantee. Fix the model, last prompt token u_*, positions and original mask M_0. For vocabulary $\mathcal{V}$, let $F(\mathbf{z}) \in \mathbb{R}^{|\mathcal{V}|}$ map initial prefix caches to next-token logits. Assume finite sensitivity κ over the compared states in Ω. The infinity norm is the largest absolute change in any token score:

$$\|F(\mathbf{z}) - F(\mathbf{z}')\|_\infty \le \kappa \|\mathbf{z} - \mathbf{z}'\|_2, \qquad \mathbf{z}, \mathbf{z}' \in \Omega. \tag{15}$$

For the donor's unique greedy choice y_D, define its positive margin

$$m_D = F_{y_D}(\mathbf{z}_D) - \max_{v \ne y_D} F_v(\mathbf{z}_D) > 0. \tag{16}$$

Proposition. If $2\kappa\varepsilon_{SC} < m_D$, then greedy decoding from $\mathbf{z}_{SC}$ selects y_D. *Proof.* Each logit changes by at most $\kappa\varepsilon_{SC}$. Thus, for every $v \ne y_D$,

$$F_{y_D}(\mathbf{z}_{SC}) - F_v(\mathbf{z}_{SC}) \ge m_D - 2\kappa\varepsilon_{SC} > 0. \tag{17}$$

The factor 2 allows the winning logit to decrease and a competitor to increase. Strict inequality excludes ties. □

Complete generation. Let the donor produce N tokens including its stopping token. $F_t^D(\mathbf{z})$ processes u_* and fixed donor history $y_{D,<t}$ from initial cache $\mathbf{z}$, recomputing all new caches. Assume Eq. (15) for F_t^D with bound κ_t and donor margin $m_{D,t} > 0$. The bound includes all intervening cache updates:

$$\left[\ \forall t \le N :\ 2\kappa_t\varepsilon_{SC} < m_{D,t}\ \right] \implies \hat{y}_{SC} = \hat{y}_D. \tag{18}$$

The first token agrees by the one-step result. If earlier tokens agree, decoding follows the history defining F_t^D, so token t agrees. Induction under the common stopping rule gives an identical sequence, which is correct whenever the donor's answer is correct.

Scope. Common valid κ_t over D, S and SC give SC no larger error bounds (Eq. (8)). Losing cancellation can increase actual errors, so accuracy gains are not guaranteed. Different sequences may answer correctly, making this condition only sufficient. SC+cut changes the mask and prefix and is excluded. Sensitivity bounds and itemwise margins remain unverified.

B.4 Complete-source and receiving-history controls

Population and protocol. The additional Qwen3-8B/MedCalc study uses a frozen 124-question pool from 14 calculator skills, selected using historical outcomes before these interventions. No item is removed based on the new repair outcome. The correct-skill donor answers 121/124 correctly; the no-skill baseline answers 4/124. Wrong uses the original unrelated skill; Neutral uses a predeclared unrelated natural-language document, not a guarantee of zero influence. Source positions and prompt lengths are aligned. The protocol uses BF16, eager attention, split prefill, greedy decoding and a 1536 new-token limit. All 49 conditions per item share this protocol. Fresh screening for a correct donor and incorrect Wrong and no-skill baselines retains 114 questions, reproducing the earlier $L16$ $S/C/SC$ accuracies of 3.5/7.0/42.1%. Table 3 instead reports all 124 items, including donor and receiver errors.

Source coverage and receiving history. Before continuation, *SC* source K/V matches the donor elementwise at all 36 layers for both receivers and $L \in \{8, 16, 24\}$. A further explicit all-layer source write leaves all 744 paired generated token sequences unchanged. Other prefix K/V need not match the donor and can vary with intervention depth. Copying only those other positions gives 3/124 and 10/124 correct answers (Wrong/Neutral); copying the complete prefix cache gives 121/124 in both contexts and reproduces all donor tokens (248/248 pairs). This is a positive control using same-question donor computation. Replacing all source KV and replaying the prompt after the skill gives 120/124 in both contexts. Only 48/124 outputs per context are token-identical to the donor, so replay is not an exact numerical identity under BF16 and different prefill computation shapes.

Paired uncertainty and truncation. The *SC*@8 − *SC*@24 accuracy difference is 66.1 percentage points in Wrong and 64.5 in Neutral. Resampling whole skill groups with replacement 10,000 times gives exploratory 95% percentile intervals of [49.3, 78.5] and [40.5, 82.8] points. The signs are positive/tied/negative in 12/2/0 and 11/2/1 of the 14 groups, respectively. No *SC*@8 output reaches the token cap; *SC*@24 has three capped outputs in Wrong and none in Neutral. Assigning capped outcomes adversarially against the difference still leaves gaps of 63.7 and 64.5 points. These intervals are not adjusted for multiple comparisons. The small number of groups and single model/task limit extrapolation.

Cache content and layer windows. Holding all-layer source coverage fixed, correct-skill KV yields 29.8/25.0% accuracy in Wrong/Neutral, versus 4.8/6.5% for unrelated-skill KV and 1.6/4.0% for a second predeclared neutral text's KV. The Wrong-to-Wrong source write is also a token-exact identity control. Four equally sized eight-layer source writes, at layers 0–7, 8–15, 16–23 and 24–31, yield 3.2/3.2/1.6/4.0% in Wrong and 0.8/4.0/4.8/5.6% in Neutral. These windows individually recover little; comparison with all 36 layers does not identify the minimum required coverage because the write budgets differ. Late *SC* need not improve on C_{all}: at $L24$ in Wrong, accuracy is 25.8% versus 29.8%.

Audit and scope. All 6076 formal records and 14 implementation-check records passed full key-set, identity, source-write and file-hash checks. An independent process regraded answers, with identical labels in forward and reverse order. Cache-coverage claims use saved runtime elementwise checks, not an offline re-execution of the model. The study does not repeat the full transfer/knockout depth sweep, identify a unique semantic variable in other-position caches, or validate the margin sufficient condition.