EDUSHIELD

Child Education Insurance Management System

15 Tables	H2 Console DB	Spring Boot JPA

DATABASE DDL SCHEMA SCRIPT

Complete H2 DDL for all 15 entities — CREATE TABLE, CONSTRAINTS, and INDEXES

Project	EduShield – Child Education Insurance Management System
Script Type	Data Definition Language (DDL)
Database	H2 Console (Spring Boot Embedded — In-Memory / File-based)
Author	**Praveen Vankudoth**
Version / Date	v1.0.0 — March 18, 2026
Tables / Indexes	15 Tables	19 Indexes
Framework	Spring Boot 3.x	Spring Data JPA	Hibernate ORM

Table of Contents

1. Introduction....3
2. DROP Statements....3
3. ROLES....4
4. USERS....4
5. ADDRESS....5
6. POLICY....5
7. POLICY_DOCUMENT_REQUIREMENT....6
8. CHILD....6
9. POLICY_APPLICATION....7
10. NOMINEE....8
11. POLICY_SUBSCRIPTION....8
12. PREMIUM_PAYMENT....9
13. CLAIM....10
14. DOCUMENT....10
15. BENEFIT_CALCULATION....11
16. AUDIT_LOGS....11
17. NOTIFICATIONS....12
18. Seed Data....12
19. Indexes Reference....13

1. Introduction

This document contains the complete Data Definition Language (DDL) script for the EduShield Child Education Insurance Management System database. It covers all 15 entity tables used by Spring Data JPA / Hibernate ORM running against the H2 Console embedded database.

Each section presents the full CREATE TABLE statement for one entity, including all column definitions, PRIMARY KEY, UNIQUE, FOREIGN KEY constraints, and associated CREATE INDEX statements. A seed data section provides the initial INSERT statements for the ROLES table.

H2 Console Access — add the following to application.properties:

```
springdatasourceurl=jdbch2memedushielddb;DB_CLOSE_DELAY=1
springdatasourcedriverclassname=orgh2Driver
springdatasourceusername=sa
springdatasourcepassword=
springh2consoleenabled=true
springh2consolepath=h2console
springjpadatabaseplatform=orghibernatedialectH2Dialect
springjpahibernateddlauto=createdrop

-- Access at: http://localhost:8080/h2-console
```

2 DROP Statements — Idempotent Re-run Safety

The following statements drop all tables in reverse dependency order before recreation. Safe for repeated script execution.

```
SET DB_CLOSE_DELAY 1;

-- Drop in reverse FK dependency order
DROP TABLE IF EXISTS AUDIT_LOGS;
DROP TABLE IF EXISTS NOTIFICATIONS;
DROP TABLE IF EXISTS BENEFIT_CALCULATION;
DROP TABLE IF EXISTS PREMIUM_PAYMENT;
DROP TABLE IF EXISTS DOCUMENT;
DROP TABLE IF EXISTS CLAIM;
DROP TABLE IF EXISTS POLICY_SUBSCRIPTION;
DROP TABLE IF EXISTS POLICY_DOCUMENT_REQUIREMENT;
DROP TABLE IF EXISTS NOMINEE;
DROP TABLE IF EXISTS POLICY_APPLICATION;
DROP TABLE IF EXISTS CHILD;
DROP TABLE IF EXISTS ADDRESS;
DROP TABLE IF EXISTS POLICY;
DROP TABLE IF EXISTS USERS;
DROP TABLE IF EXISTS ROLES;
```

3 ROLES

Stores the four system roles: USER, ADMIN, UNDERWRITER, CLAIMS_OFFICER. Referenced by USERS via FK.

```
CREATE TABLE ROLES (
    ROLE_ID     BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1) NOT NULL,
    ROLE_NAME   VARCHAR(255) NOT NULL,
    CONSTRAINT PK_ROLES      PRIMARY KEY (ROLE_ID),
    CONSTRAINT UQ_ROLES_NAME UNIQUE (ROLE_NAME)
);
```

4 USERS

Central identity table for all system actors. Supports local and Google OAuth2 authentication. Soft-deactivation via IS_ACTIVE flag.

```
CREATE TABLE USERS (
    USER_ID             BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 1510)
NOT NULL,
    NAME                VARCHAR(255) NOT NULL,
    EMAIL               VARCHAR(255) NOT NULL,
    PASSWORD            VARCHAR(255) NOT NULL,
    PHONE               VARCHAR(255),
    ROLE_ID             BIGINT,
    IMAGE_URL           VARCHAR(255),
    PROVIDER            VARCHAR(255),
    RESET_TOKEN         VARCHAR(255),
    RESET_TOKEN_EXPIRY  TIMESTAMP(6),
    IS_ACTIVE           BOOLEAN DEFAULT TRUE,
    CREATED_AT          TIMESTAMP(6) DEFAULT NOW(),
    CONSTRAINT PK_USERS       PRIMARY KEY (USER_ID),
    CONSTRAINT UQ_USERS_EMAIL UNIQUE (EMAIL),
    CONSTRAINT FK_USERS_ROLE  FOREIGN KEY (ROLE_ID) REFERENCES ROLES(ROLE_ID)
);
```

5 ADDRESS

Optional one-to-one address record for a user profile. UNIQUE constraint on USER_ID enforces the 1:1 relationship.

```
CREATE TABLE ADDRESS (
    ADDRESS_ID  BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 3) NOT NULL,
    USER_ID     BIGINT NOT NULL,
    STREET      VARCHAR(255) NOT NULL,
    CITY        VARCHAR(100) NOT NULL,
    STATE       VARCHAR(100) NOT NULL,
    PINCODE     VARCHAR(10)  NOT NULL,
    CONSTRAINT PK_ADDRESS      PRIMARY KEY (ADDRESS_ID),
    CONSTRAINT UQ_ADDRESS_USER UNIQUE (USER_ID),
    CONSTRAINT FK_ADDRESS_USER FOREIGN KEY (USER_ID) REFERENCES USERS(USER_ID)
);
```

6 POLICY

Insurance product catalog. Created and managed by Admin. IS_ACTIVE controls visibility; DELETED enables soft-removal.

```
CREATE TABLE POLICY (
    POLICY_ID                BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH
98) NOT NULL,
    POLICY_NAME              VARCHAR(255)   NOT NULL,
    DESCRIPTION              VARCHAR(255),
    BASE_PREMIUM             NUMERIC(38, 2) NOT NULL,
    DURATION_YEARS           INTEGER        NOT NULL,
    MIN_CHILD_AGE            INTEGER        NOT NULL,
    MAX_CHILD_AGE            INTEGER        NOT NULL,
    RISK_COVERAGE_AMOUNT     NUMERIC(38, 2) NOT NULL,
    MATURITY_BENEFIT_AMOUNT  NUMERIC(38, 2) NOT NULL,
    BONUS_PERCENTAGE         NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    DEATH_BENEFIT_MULTIPLIER NUMERIC(38, 2) NOT NULL DEFAULT 1.00,
    WAIVER_OF_PREMIUM        BOOLEAN        NOT NULL DEFAULT FALSE,
    IS_ACTIVE                BOOLEAN        NOT NULL DEFAULT TRUE,
    DELETED                  BOOLEAN        NOT NULL DEFAULT FALSE,
    CONSTRAINT PK_POLICY PRIMARY KEY (POLICY_ID)
);
```

7 POLICY_DOCUMENT_REQUIREMENT

Mandatory document checklist per policy per lifecycle stage (APPLICATION or CLAIM). Used by the underwriter portal to gate the Approve button.

```
CREATE TABLE POLICY_DOCUMENT_REQUIREMENT (
    ID            BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 33) NOT NULL,
    POLICY_ID     BIGINT       NOT NULL,
    DOCUMENT_TYPE VARCHAR(255) NOT NULL,
    STAGE         VARCHAR(255) NOT NULL,
    CONSTRAINT PK_PDR     PRIMARY KEY (ID),
    CONSTRAINT FK_PDR_POL FOREIGN KEY (POLICY_ID) REFERENCES POLICY(POLICY_ID)
);
```

8 CHILD

Beneficiary (child) profiles registered by parent users. DATE_OF_BIRTH drives policy age eligibility checks at application time.

```
CREATE TABLE CHILD (
    CHILD_ID       BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 76) NOT
NULL,
    USER_ID        BIGINT       NOT NULL,
    CHILD_NAME     VARCHAR(255) NOT NULL,
    DATE_OF_BIRTH  DATE         NOT NULL,
    GENDER         VARCHAR(255) NOT NULL,
    SCHOOL_NAME    VARCHAR(255),
    EDUCATION_GOAL VARCHAR(255),
    CONSTRAINT PK_CHILD      PRIMARY KEY (CHILD_ID),
    CONSTRAINT FK_CHILD_USER FOREIGN KEY (USER_ID) REFERENCES USERS(USER_ID)
);
```

9 POLICY_APPLICATION

Core application entity. Drives the primary state machine: PENDING → APPROVED / REJECTED → ACTIVE → LAPSED / EXPIRED / CLAIMED. Includes risk score and calculated premium fields.

```
CREATE TABLE POLICY_APPLICATION (
    APPLICATION_ID     BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 113) NOT
NULL,
    POLICY_NUMBER      VARCHAR(255)   NOT NULL,
    USER_ID            BIGINT         NOT NULL,
    CHILD_ID           BIGINT         NOT NULL,
    POLICY_ID          BIGINT         NOT NULL,
    STATUS             VARCHAR(255)   NOT NULL DEFAULT 'PENDING',
    APPLICATION_DATE   DATE           NOT NULL DEFAULT CURRENT_DATE,
    START_DATE         DATE           NOT NULL,
    END_DATE           DATE           NOT NULL,
    APPROVAL_DATE      DATE,
    PAYMENT_FREQUENCY  VARCHAR(255)   NOT NULL,
    CALCULATED_PREMIUM NUMERIC(38, 2),
    TOTAL_PAID_AMOUNT  NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    RISK_SCORE         INTEGER,
    RISK_CATEGORY      VARCHAR(255),
    REJECTION_REASON   VARCHAR(255),
    CONSTRAINT PK_PA         PRIMARY KEY (APPLICATION_ID),
    CONSTRAINT UQ_POLICY_NUM UNIQUE (POLICY_NUMBER),
    CONSTRAINT FK_PA_USER    FOREIGN KEY (USER_ID)   REFERENCES USERS(USER_ID),
    CONSTRAINT FK_PA_CHILD   FOREIGN KEY (CHILD_ID)  REFERENCES CHILD(CHILD_ID),
    CONSTRAINT FK_PA_POLICY  FOREIGN KEY (POLICY_ID) REFERENCES POLICY(POLICY_ID)
);


-- Indexes
CREATE INDEX IDX_PA_USER_ID   ON POLICY_APPLICATION(USER_ID);
CREATE INDEX IDX_PA_STATUS    ON POLICY_APPLICATION(STATUS);
CREATE INDEX IDX_PA_CHILD_ID  ON POLICY_APPLICATION(CHILD_ID);
CREATE INDEX IDX_PA_POLICY_ID ON POLICY_APPLICATION(POLICY_ID);
```

10 NOMINEE

Alternate beneficiary record. One-to-one with POLICY_APPLICATION enforced by UNIQUE constraint on APPLICATION_ID.

```
CREATE TABLE NOMINEE (
    NOMINEE_ID     BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 113) NOT
NULL,
    APPLICATION_ID BIGINT       NOT NULL,
    NOMINEE_NAME   VARCHAR(255) NOT NULL,
    RELATIONSHIP   VARCHAR(255) NOT NULL,
    PHONE          VARCHAR(255) NOT NULL,
    CONSTRAINT PK_NOMINEE    PRIMARY KEY (NOMINEE_ID),
    CONSTRAINT UQ_NOM_APP    UNIQUE (APPLICATION_ID),
    CONSTRAINT FK_NOM_APP    FOREIGN KEY (APPLICATION_ID) REFERENCES
POLICY_APPLICATION(APPLICATION_ID)
);
```

11 POLICY_SUBSCRIPTION

Live subscription created on application approval. Tracks total paid amount, coverage, and maturity date throughout the policy lifetime.

```
CREATE TABLE POLICY_SUBSCRIPTION (
    SUBSCRIPTION_ID     BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 26242)
NOT NULL,
    SUBSCRIPTION_NUMBER VARCHAR(255)   NOT NULL,
    APPLICATION_ID      BIGINT         NOT NULL,
    STATUS              VARCHAR(255)   NOT NULL DEFAULT 'APPROVED',
    PREMIUM_AMOUNT      NUMERIC(38, 2) NOT NULL,
    COVERAGE_AMOUNT     NUMERIC(38, 2) NOT NULL,
    TOTAL_PAID_AMOUNT   NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    START_DATE          DATE           NOT NULL,
    END_DATE            DATE           NOT NULL,
    MATURITY_DATE       DATE           NOT NULL,
    CONSTRAINT PK_SUB     PRIMARY KEY (SUBSCRIPTION_ID),
    CONSTRAINT UQ_SUB_NUM UNIQUE (SUBSCRIPTION_NUMBER),
    CONSTRAINT UQ_SUB_APP UNIQUE (APPLICATION_ID),
    CONSTRAINT FK_SUB_APP FOREIGN KEY (APPLICATION_ID) REFERENCES
POLICY_APPLICATION(APPLICATION_ID)
);


-- Indexes
CREATE INDEX IDX_SUB_APP_ID ON POLICY_SUBSCRIPTION(APPLICATION_ID);
CREATE INDEX IDX_SUB_STATUS ON POLICY_SUBSCRIPTION(STATUS);
```

12 PREMIUM_PAYMENT

Individual premium payment transactions. Each record represents one payment against a subscription. LATE_FEE captures overdue surcharges.

```
CREATE TABLE PREMIUM_PAYMENT (
    PAYMENT_ID      BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 10) NOT
NULL,
    SUBSCRIPTION_ID BIGINT         NOT NULL,
    APPLICATION_ID  BIGINT,
    AMOUNT          NUMERIC(38, 2) NOT NULL,
    DUE_DATE        DATE           NOT NULL,
    PAYMENT_DATE    DATE           NOT NULL,
    LATE_FEE        NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    STATUS          VARCHAR(255)   NOT NULL DEFAULT 'COMPLETED',
    CONSTRAINT PK_PP      PRIMARY KEY (PAYMENT_ID),
    CONSTRAINT FK_PP_SUB  FOREIGN KEY (SUBSCRIPTION_ID) REFERENCES
POLICY_SUBSCRIPTION(SUBSCRIPTION_ID),
    CONSTRAINT FK_PP_APP  FOREIGN KEY (APPLICATION_ID)  REFERENCES
POLICY_APPLICATION(APPLICATION_ID)
);


-- Indexes
CREATE INDEX IDX_PP_SUB_ID ON PREMIUM_PAYMENT(SUBSCRIPTION_ID);
CREATE INDEX IDX_PP_DATE   ON PREMIUM_PAYMENT(PAYMENT_DATE);
```

13 CLAIM

Education benefit claims raised against active subscriptions. Claims lifecycle: SUBMITTED → UNDER_REVIEW → APPROVED / REJECTED → PAID. PAYOUT_DATE set to T+7 on approval.

```
CREATE TABLE CLAIM (
    CLAIM_ID          BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 6) NOT
NULL,
    SUBSCRIPTION_ID   BIGINT         NOT NULL,
    USER_ID           BIGINT         NOT NULL,
    CLAIM_TYPE        VARCHAR(255)   NOT NULL,
    CLAIM_AMOUNT      NUMERIC(38, 2) NOT NULL,
    CLAIM_DATE        DATE           NOT NULL,
    STATUS            VARCHAR(255)   NOT NULL DEFAULT 'SUBMITTED',
    APPROVAL_DATE     DATE,
    PAYOUT_DATE       DATE,
    REJECTION_REASON  VARCHAR(255),
    CONSTRAINT PK_CLAIM      PRIMARY KEY (CLAIM_ID),
    CONSTRAINT FK_CLAIM_SUB  FOREIGN KEY (SUBSCRIPTION_ID) REFERENCES
POLICY_SUBSCRIPTION(SUBSCRIPTION_ID),
    CONSTRAINT FK_CLAIM_USER FOREIGN KEY (USER_ID)         REFERENCES USERS(USER_ID)
);


-- Indexes
CREATE INDEX IDX_CLAIM_SUB_ID ON CLAIM(SUBSCRIPTION_ID);
CREATE INDEX IDX_CLAIM_USER   ON CLAIM(USER_ID);
CREATE INDEX IDX_CLAIM_STATUS ON CLAIM(STATUS);
```

14 DOCUMENT

Uploaded document metadata. Binary stored on filesystem or cloud storage. At least one of APPLICATION_ID or CLAIM_ID must be non-null per record.

```
CREATE TABLE DOCUMENT (
    DOCUMENT_ID         BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 140)
NOT NULL,
    UPLOADED_BY_USER_ID BIGINT        NOT NULL,
    APPLICATION_ID      BIGINT,
    CLAIM_ID            BIGINT,
    DOCUMENT_TYPE       VARCHAR(255)  NOT NULL,
    FILE_NAME           VARCHAR(255)  NOT NULL,
    FILE_PATH           VARCHAR(255)  NOT NULL,
    UPLOAD_DATE         TIMESTAMP(6)  NOT NULL DEFAULT NOW(),
    CONSTRAINT PK_DOC      PRIMARY KEY (DOCUMENT_ID),
    CONSTRAINT FK_DOC_USER FOREIGN KEY (UPLOADED_BY_USER_ID) REFERENCES USERS(USER_ID),
    CONSTRAINT FK_DOC_APP  FOREIGN KEY (APPLICATION_ID)      REFERENCES
POLICY_APPLICATION(APPLICATION_ID),
    CONSTRAINT FK_DOC_CLM  FOREIGN KEY (CLAIM_ID)            REFERENCES CLAIM(CLAIM_ID)
);


-- Indexes
CREATE INDEX IDX_DOC_APP_ID ON DOCUMENT(APPLICATION_ID);
CREATE INDEX IDX_DOC_CLM_ID ON DOCUMENT(CLAIM_ID);
```

15 BENEFIT_CALCULATION

Actuarial benefit projections per subscription. Generated by BenefitCalculationService at policy approval. TOTAL_BENEFIT is the final payout figure.

```
CREATE TABLE BENEFIT_CALCULATION (
    CALCULATION_ID      BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1) NOT NULL,
    SUBSCRIPTION_ID     BIGINT         NOT NULL,
    BENEFIT_TYPE        VARCHAR(255)   NOT NULL,
    CALCULATION_DATE    DATE           NOT NULL DEFAULT CURRENT_DATE,
    BASE_AMOUNT         NUMERIC(38, 2) NOT NULL,
    ANNUAL_INCREMENT    NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    GUARANTEED_ADDITION NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    LOYALTY_BONUS       NUMERIC(38, 2) NOT NULL DEFAULT 0.00,
    TOTAL_BENEFIT       NUMERIC(38, 2) NOT NULL,
    CONSTRAINT PK_BC     PRIMARY KEY (CALCULATION_ID),
    CONSTRAINT FK_BC_SUB FOREIGN KEY (SUBSCRIPTION_ID) REFERENCES
POLICY_SUBSCRIPTION(SUBSCRIPTION_ID)
);
```

16 AUDIT_LOGS

Append-only compliance audit trail. No UPDATE or DELETE ever performed. No FK on USER_ID — log records survive user deactivation. Three performance indexes for common filter patterns.

```
CREATE TABLE AUDIT_LOGS (
    ID          BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 58) NOT NULL,
    USER_ID     BIGINT,
    USER_EMAIL  VARCHAR(255),
    ROLE        VARCHAR(255),
    ACTION      VARCHAR(255)  NOT NULL,
    ENTITY_TYPE VARCHAR(255),
    ENTITY_ID   BIGINT,
    DESCRIPTION VARCHAR(1000),
    IP_ADDRESS  VARCHAR(255),
    TIMESTAMP   TIMESTAMP(6)  NOT NULL DEFAULT NOW(),
    CONSTRAINT PK_AUDIT PRIMARY KEY (ID)
);


-- Indexes
CREATE INDEX IDX_AUDIT_USER_ID  ON AUDIT_LOGS(USER_ID);
CREATE INDEX IDX_AUDIT_ACTION   ON AUDIT_LOGS(ACTION);
CREATE INDEX IDX_AUDIT_TIMESTAMP ON AUDIT_LOGS(TIMESTAMP);
```

17 NOTIFICATIONS

In-app notification records for the Angular notification panel. Supports user-specific notifications (USER_ID set) and role-broadcast notifications (RECIPIENT_ROLE set, USER_ID null).

```
CREATE TABLE NOTIFICATIONS (
    ID             BIGINT GENERATED BY DEFAULT AS IDENTITY (START WITH 1 RESTART WITH 5) NOT NULL,
    USER_ID        BIGINT,
    TITLE          VARCHAR(255),
    MESSAGE        VARCHAR(500),
    TYPE           VARCHAR(255),
    RECIPIENT_ROLE VARCHAR(255),
    TARGET_URL     VARCHAR(255),
    IS_READ        BOOLEAN      NOT NULL DEFAULT FALSE,
    CREATED_AT     TIMESTAMP(6) DEFAULT NOW(),
    CONSTRAINT PK_NOTIF PRIMARY KEY (ID)
);


-- Indexes
CREATE INDEX IDX_NOTIF_USER_ID   ON NOTIFICATIONS(USER_ID);
CREATE INDEX IDX_NOTIF_RECIPIENT ON NOTIFICATIONS(RECIPIENT_ROLE);
CREATE INDEX IDX_NOTIF_IS_READ   ON NOTIFICATIONS(IS_READ);
```

18 Seed Data — ROLES Table

These four INSERT statements must be executed after schema creation to populate the ROLES lookup table. All user accounts depend on this data.

```
-- Seed the four system roles
INSERT INTO ROLES (ROLE_NAME) VALUES ('USER');
INSERT INTO ROLES (ROLE_NAME) VALUES ('ADMIN');
INSERT INTO ROLES (ROLE_NAME) VALUES ('UNDERWRITER');
INSERT INTO ROLES (ROLE_NAME) VALUES ('CLAIMS_OFFICER');

-- Optional: default Admin account (DEVELOPMENT ONLY)
-- Remove before production deployment
-- INSERT INTO USERS (NAME, EMAIL, PASSWORD, IS_ACTIVE, ROLE_ID)
-- VALUES ('Praveen Vankudoth', 'praveen@edushield.dev',
--         '$2a$12$REPLACE_WITH_BCRYPT_HASH', TRUE,
--         (SELECT ROLE_ID FROM ROLES WHERE ROLE_NAME = 'ADMIN'));
```

19 Indexes Reference

All 19 indexes defined across the schema, with their target table, column, and the query pattern each one optimizes.

Index Name	Table	Column	Query Pattern
IDX_PA_USER_ID	POLICY_APPLICATION	USER_ID	All applications by a customer.
IDX_PA_STATUS	POLICY_APPLICATION	STATUS	Filter by lifecycle status.
IDX_PA_CHILD_ID	POLICY_APPLICATION	CHILD_ID	All applications for a child.
IDX_PA_POLICY_ID	POLICY_APPLICATION	POLICY_ID	All applications for a policy.
IDX_SUB_APP_ID	POLICY_SUBSCRIPTION	APPLICATION_ID	Join application → subscription.
IDX_SUB_STATUS	POLICY_SUBSCRIPTION	STATUS	Filter by subscription status.
IDX_PP_SUB_ID	PREMIUM_PAYMENT	SUBSCRIPTION_ID	All payments for a subscription.
IDX_PP_DATE	PREMIUM_PAYMENT	PAYMENT_DATE	Date-range payment history.
IDX_CLAIM_SUB_ID	CLAIM	SUBSCRIPTION_ID	All claims on a subscription.
IDX_CLAIM_USER	CLAIM	USER_ID	All claims by a customer.
IDX_CLAIM_STATUS	CLAIM	STATUS	Claims Officer queue filter.
IDX_DOC_APP_ID	DOCUMENT	APPLICATION_ID	Docs for an application.
IDX_DOC_CLM_ID	DOCUMENT	CLAIM_ID	Docs for a claim.
IDX_AUDIT_USER_ID	AUDIT_LOGS	USER_ID	Audit events by actor.
IDX_AUDIT_ACTION	AUDIT_LOGS	ACTION	Filter by action code.
IDX_AUDIT_TIMESTAMP	AUDIT_LOGS	TIMESTAMP	Date-range audit queries.
IDX_NOTIF_USER_ID	NOTIFICATIONS	USER_ID	Notifications for a user.
IDX_NOTIF_RECIPIENT	NOTIFICATIONS	RECIPIENT_ROLE	Broadcast notifications by role.
IDX_NOTIF_IS_READ	NOTIFICATIONS	IS_READ	Unread count for badge.

[END OF DDL SCHEMA SCRIPT v1.0.0]

EduShield – Prepared by Praveen Vankudoth | H2 Console Database | March 2026