IBOOKTRACK · HANDOVER DOCUMENTATION

Frontend Documentation

A unified Warehouse Management System and Executive Dashboard for Innodata's book-digitization pipeline.

Generated 2026-08-09 · Ivan, Divan, John & Francis

iBookTrack — Frontend Documentation



Next.js 15 (App Router) + React 19 + TypeScript. Lives in `frontend/`. Runs on port **3000** by default.

Table of Contents

1. Tech Stack
2. Directory Layout
3. Routing & Pages
4. Shared Components
5. Hooks & Libs
6. Authentication Flow
7. Talking to the Backend
8. Styling
9. State & Data Fetching Patterns
10. Adding a New Page — Recipe
11. Build & Deploy

Tech Stack

Package	Version	Purpose
`next`	^15.3	App Router, RSC, image optimization
`react`	19.2	UI
`typescript`	5.7	Types
`tailwindcss`	^4.2	Utility CSS (v4 — no `tailwind.config.js`)
`@radix-ui/*`	latest	Accessible primitives behind shadcn/ui
`lucide-react`	^0.564	Icon set
`sonner`	^1.7	Toast notifications
`recharts`	2.15	Dashboard charts
`react-hook-form` + `zod`	latest	Forms + validation
`bwip-js`	^4.9	Barcode rendering for Locator
`next-themes`	^0.4	Dark/light theme

Scripts:

- `npm run dev` → `next dev` (http://localhost:3000)
- `npm run build` → `next build`
- `npm start` → `next start`
- `npm run lint` → `eslint .`

Directory Layout

```
frontend/
├── app/                          # App Router — folder = route
│   ├── layout.tsx                # root layout (theme provider, sonner)
│   ├── page.tsx                  # redirects to /landing-page
│   ├── globals.css               # Tailwind v4 + design tokens
│   ├── landing-page/             # marketing page sections
│   ├── login/, register/, forgot-password/
│   ├── Dashboard/                # uppercase D directory
│   ├── warehouse/                # legacy single-station scanner
│   ├── warehouse-inventory/      # primary intake + flag UI
│   ├── checkpoints/              # 8-stage send/receive monitor
│   ├── intake/, inventory/
│   ├── qa/                       # Book Inspection & Endorsement
│   ├── transmission/             # transmission monitor
│   ├── locator/                  # warehouse locator + barcodes
│   ├── reports/, settings/, notifications/
├── components/
│   ├── ui/                       # shadcn-generated primitives (button, card, …)
│   ├── dashboard-sidebar.tsx     # global left nav (550+ lines)
│   ├── stats-bar.tsx             # 4-card metrics row
│   ├── transmission-queue.tsx    # live transmission list
│   ├── missing-item-log.tsx      # flagged/non-processable books
│   ├── scanner-input.tsx         # auto-focusing barcode input
│   ├── book-info-card.tsx, intake-summary.tsx, …
│   └── …
├── hooks/
│   ├── use-toast.ts              # wraps sonner
│   └── use-live-notifications.ts # polling notification feed
├── lib/
│   ├── auth-api.ts               # token storage + authFetch wrapper
│   ├── live-notifications.ts     # notification helpers
│   └── utils.ts                  # `cn()` for class merging
├── public/                       # logo, screenshots
└── styles/
```

Routing & Pages

App Router conventions: each folder under `app/` is a route segment, and a `page.tsx` inside it is the entry component. Loading and error UIs are standard Next.js conventions when present.

Route	File	Purpose
`/`	`app/page.tsx`	`redirect('/landing-page')`
`/landing-page`	`app/landing-page/page.tsx`	Public marketing site
`/login`	`app/login/page.tsx`	Email + password sign-in
`/register`	`app/register/page.tsx`	New user signup
`/forgot-password`	`app/forgot-password/page.tsx`	Password reset email
`/Dashboard` ⚠️	`app/Dashboard/page.tsx`	Home — stats, charts, transmission queue, flagged books
`/warehouse-inventory`	`app/warehouse-inventory/page.tsx`	Primary intake. Scan ISBNs, mark processable/non-processable, flag inline
`/warehouse`	`app/warehouse/page.tsx`	Legacy variant; superseded by `/warehouse-inventory`
`/intake`	`app/intake/page.tsx`	Pre-warehouse inspection
`/inventory`	`app/inventory/page.tsx`	Inventory checkpoint
`/checkpoints`	`app/checkpoints/page.tsx`	8-station handshake monitor; advance/rollback boxes
`/qa`	`app/qa/page.tsx`	Book Inspection & Endorsement — flag per ISBN with page-no remarks
`/transmission`	`app/transmission/page.tsx`	Live transmission feed
`/locator`	`app/locator/page.tsx`	Find & print box barcode + bin location
`/reports`	`app/reports/page.tsx`	Filterable reports/exports
`/settings`	`app/settings/page.tsx`	Profile + preferences
`/notifications`	`app/notifications/page.tsx`	Notification feed

> ⚠ **WARNING**
>
> **Casing:** `/Dashboard` uses an uppercase `D` while every other route is lowercase. Works on Windows/macOS, **breaks on Linux deployments** (Vercel, Docker). Rename to `/dashboard` and update 25 references before shipping to production.

Shared Components

The big ones — most other components are page-specific and self-explanatory.

`components/dashboard-sidebar.tsx`

Global left rail. Navigation links, profile dropdown, notifications dropdown. Uses `useLiveNotifications()` for live counts.

> **NOTE**
>
> The previously hard-coded `sampleNotifications` array has already been removed during turnover cleanup.

`components/stats-bar.tsx`

Four-card row across the top of the Dashboard: Active Lots, Boxes In Pipeline, Books Transmitted Today, Non-Processable / Flagged Books. Last card opens a modal listing the flagged scans.

`components/transmission-queue.tsx`

Live transmission feed card. Polled every 20s.

`components/missing-item-log.tsx`

"Flagged / Non-Processable Books" table on the Dashboard. Fetches `/api/warehouse/rejected-books?limit=50` and maps each `rejection_reason` via the `FLAG_LABELS` record (23 keys; see Project Overview).

`components/scanner-input.tsx`

Single-line barcode input that auto-focuses, debounces, and fires `onScan(isbn)` on Enter or after a quiet period. Used on `/warehouse-inventory`, `/locator`, `/checkpoints`.

`components/book-info-card.tsx`

Shows the iLMS metadata (title, publisher, language, etc.) for a scanned ISBN.

`components/ui/*`

shadcn/ui primitives generated via `components.json`. Don't hand-edit unless you intend to fork them — re-running shadcn would overwrite changes.

Hooks & Libs

`lib/auth-api.ts` (the most important shared file)

Exports:

Symbol	Purpose
`storeTokenData()`	Save tokens to `localStorage`
`getTokenData()`	Read tokens
`clearTokenData()`	Wipe tokens
`isTokenExpired()`	True if `expires_at` < now + 5min buffer
`refreshAccessToken()`	POST `/api/auth/refresh`, stores new access token
`getValidAccessToken()`	Refresh if needed, return access token (or null)
`authFetch(url, options)`	Drop-in `fetch` that injects `Authorization: Bearer …`. Redirects to `/login` on 401.
`authRequest({endpoint,…})`	Used by login/register pages.

> Always import `authFetch` for **any** call to a protected backend route. Never construct headers manually — you'll forget refresh.

`hooks/use-toast.ts`

Thin wrapper around `sonner` so the rest of the app uses `toast({ title, description, variant })`.


`hooks/use-live-notifications.ts`

Periodic polling for notification badges in the sidebar. Replace with WebSocket/SSE if you want push behavior.

`lib/utils.ts`

`cn(...inputs)` — `clsx` + `tailwind-merge` for conditional class names.

Authentication Flow



> ⚠ **WARNING**
>
> Tokens live in `localStorage` and are therefore vulnerable to XSS. Acceptable for an internal intranet tool; **migrate to httpOnly cookies if you ever expose this app on the public internet.**

The frontend uses custom JWTs for authentication. Tokens are managed by the backend and stored securely.

Styling

- **Tailwind v4** — no `tailwind.config.js`. Configuration lives in `frontend/postcss.config.mjs` and `app/globals.css` (CSS variables for design tokens, `@theme inline` block).
- **Dark mode** via `next-themes`, toggled in the sidebar menu.
- **shadcn/ui** components use semantic tokens (`bg-card`, `text-foreground`, `border-input`, etc.). Never reach for raw colors like `bg-gray-200`.

Build & Deploy

Local production preview

```
cd frontend
npm run build
npm start
```

Vercel (recommended)

- Import the repo, set the **Root Directory** to `frontend/`.
- Environment variables (Project Settings → Environment Variables):
  - `NEXT_PUBLIC_API_URL` (the backend's public URL)
- Build command auto-detected (`next build`).

Static hosting

Not supported — the app uses dynamic routes and server features. Deploy a Node host or Vercel.

Common deploy gotchas

- **Linux casing:** rename `app/Dashboard/` → `app/dashboard/` first.
- **CORS:** the backend must list the deployed frontend origin in `FRONTEND_URL` or `FRONTEND_URLS`.
- **Mixed content:** if backend is `http://` and frontend is `https://`, browsers will block requests. Both must be HTTPS in prod.