Insider Disclosures and Stock Returns: Phase 3

INFO 2950 | Vansh Kakra (vk365), Dev Shukla (ds2395), and Wilson Wang (ww576)
Mentor: Saif Mahmud (sm2446)

Phase 3 draft report: The two planned regressions, overlap checks, time-based prediction evaluation, and a course-method bootstrap sensitivity analysis have been executed. The bootstrap uses one event per company and has conditional conclusions; shared shocks across companies remain unresolved. This report is the Phase 3 draft; Phase 4 revisions will incorporate feedback.

1. Introduction

Company insiders disclose purchases and sales of their company's shares through SEC filings. These disclosures raise a question about market efficiency: once a trade becomes public, does subsequent stock performance contain information beyond broad market movements? Purchases and sales may have different motivations, so we examine them separately rather than treating every insider transaction as the same signal.

In Phase 2, we combined SEC transaction records, historical S&P 500 membership, and adjusted stock prices. We now use the cleaned event dataset to examine two questions:

1. **Are purchase events followed by positive 13-week abnormal returns, and are those returns higher than returns following sale events?**
2. **Among purchase events, are C-suite participation and larger dollar purchases associated with higher 13-week abnormal returns, controlling for the number of recorded insiders?**

An **event** is one company's purchases or sales grouped within a week. An **abnormal return** is the difference between a stock's actual return and its expected return based on its earlier relationship with SPY, our market benchmark. We sum these differences to obtain a **cumulative abnormal return (CAR)**. The primary outcome is the 13-week CAR; the 1-, 4-, and 26-week horizons provide secondary descriptive context.

The literature cited in the preregistrations motivates these questions but does not guarantee the same patterns in our sample. Our analysis concerns associations following public disclosures. It cannot establish insiders' motives or show that the trades caused later returns.

Main findings: Mean 13-week CAR is 2.13 percentage points after purchases and -2.47 after sales, a difference of 4.60 points. Purchase means and purchase-minus-sale differences remain positive in the sensitivity samples. Among purchases, the full-sample C-suite and log-value coefficients are positive. However, the model barely improves on a constant baseline when predicting later events: test RMSE is 19.45 versus 19.51 percentage points. These are descriptive full-event estimates and a held-out prediction comparison. In a separate one-event-per-company sample, Bonferroni-adjusted bootstrap intervals exclude zero for the purchase mean and purchase-minus-sale difference but include zero for the C-suite and log-value coefficients. Those decisions assume sufficiently independent companies; 83% of the comparison sample falls in 2020, making shared shocks a particular concern. They do not establish significance for the original full-event estimates or causal effects.

2. Loading the Cleaned Data

The cleaning process is complete in data_cleaning.ipynb. This notebook starts from its exported CSV files. The code below only loads and checks those exports; it does not repeat the raw-data cleaning.

2.1 Imports and File Locations

We use the Phase 2 Python environment. Open this notebook from the repository root or the `insider-trading-phase3-4` folder, then restart the kernel and run the cells in order. The saved outputs below show the checks on the current data snapshot.

```
# Import libraries and locate the cleaned inputs from either supported working folder.
from pathlib import Path
import numpy as np
import pandas as pd
from IPython.display import display

repo_root = next((p for p in [Path.cwd(), *Path.cwd().parents]
                  if (p / "insider-trading-phase3-4" / "data" / "processed" /
"insider_events.csv").is_file()), None)
if repo_root is None:
    raise FileNotFoundError("Open the notebook within the repository and restore insider-trading-phase3-
4/data/processed.")
processed_dir = repo_root / "insider-trading-phase3-4" / "data" / "processed"
print("Input folder: insider-trading-phase3-4/data/processed")
```

```
Input folder: insider-trading-phase3-4/data/processed
```

2.2 Reading the Exported Tables

We read company CIKs as text to preserve their leading zeros and parse the event and filing dates as dates. The plan flag uses an integer type that allows missing values. The weekly return, membership, and cleaning-log files provide supporting information about how the event table was constructed.

```
# Read the event dataset and supporting exports with explicit identifier and date types.
df_events = pd.read_csv(processed_dir / "insider_events.csv",
                        dtype={"issuer_cik": "string", "any_plan_10b5_1": "Int64"},
                        parse_dates=["event_week", "first_filing"])
df_weekly = pd.read_csv(processed_dir / "weekly_stock_prices.csv", parse_dates=["week"])
df_cleaning_log = pd.read_csv(processed_dir / "cleaning_log.csv")
df_historical_clean = pd.read_csv(processed_dir / "historical_membership_clean.csv",
                                  parse_dates=["snapshot_date", "valid_from", "valid_to"])
print(f"Event table: {len(df_events):,} rows and {len(df_events.columns)} columns")
print(f"Weekly return table: {len(df_weekly):,} rows")
print(f"Historical membership: {len(df_historical_clean):,} intervals")
display(df_events.head())
```

```
Event table: 27,820 rows and 25 columns
Weekly return table: 219,378 rows
Historical membership: 628 intervals
```

Table shown with fields as rows for print readability.

	0	1	2	3	4
issuer_cik	0000021665	0000051253	0000060086	0000098246	0000875320
issuer_name	COLGATE PALMOLIVE CO	INTERNATIONAL FLAVORS & FRAGRANCES INC	LOEWS CORP	TIFFANY & CO	VERTEX PHARMACEUTICALS INC / MA
sp_ticker	CL	IFF	L	TIF	VRTX
price_ticker	CL	IFF	L	NaN	VRTX
trans_code	S	P	S	S	S
event_week	2020-01-03	2020-01-03	2020-01-03	2020-01-03	2020-01-03
first_filing	2020-01-02	2020-01-02	2020-01-02	2020-01-02	2020-01-02
n_trades	1	2	1	7	4
n_insiders	1	1	1	7	1
total_value	1221022.50	8272210.00	215379.50	91742269.60	6562715.24
log_value	14.015199	15.928412	12.280157	18.334494	15.696915
role	Other officer	10% owner	Other officer	C-suite	Director
role_rank	2	4	2	1	3
any_c_suite	0	0	0	1	0
any_plan_10b5_1	<NA>	<NA>	<NA>	<NA>	<NA>
mixed_week	0	0	0	0	0
mean_filing_lag	3.0	3.0	3.0	3.0	3.0
alpha	-0.000241	-0.005327	-0.001491	NaN	0.000093
beta	0.736484	1.019928	0.807514	NaN	1.034535
estimation_weeks	51	51	51	0	51
car_pre4	-0.023257	-0.112750	0.033689	NaN	-0.053690
car_1w	0.024017	-0.007962	-0.019852	NaN	0.039644
car_4w	0.091272	0.062931	-0.017581	NaN	0.044175
car_13w	0.189963	0.090631	-0.230123	NaN	0.340251
car_26w	0.102511	0.209370	-0.315056	NaN	0.302255

2.3 Checking the Imported Snapshot

The cleaning run produced 27,820 events and 25 columns. We check those dimensions, the event key, identifier formatting, and the fields needed for the two planned models. These checks stop the notebook if the exports do not match the documented snapshot. They do not delete, fill, or alter observations.

```
# Check the exported schema, event uniqueness, identifiers, and allowed transaction directions.
expected_columns = ["issuer_cik", "issuer_name", "sp_ticker", "price_ticker", "trans_code", "event_week",
"first_filing",
                    "n_trades", "n_insiders", "total_value", "log_value", "role", "role_rank", "any_c_suite",
                    "any_plan_10b5_1", "mixed_week", "mean_filing_lag", "alpha", "beta", "estimation_weeks",
                    "car_pre4", "car_1w", "car_4w", "car_13w", "car_26w"]
assert df_events.columns.tolist() == expected_columns, "Review the export schema before continuing."
assert df_events.shape == (27820, 25), "The input snapshot changed; update its documentation before analysis."
assert df_events[["issuer_cik", "event_week", "trans_code"]].notna().all().all()
assert not df_events.duplicated(["issuer_cik", "event_week", "trans_code"]).any()
assert df_events["issuer_cik"].str.fullmatch(r"\d{10}").all()
assert set(df_events["trans_code"]) == {"P", "S"}
```

```
assert df_events["any_c_suite"].isin([0, 1]).all()
assert df_events["total_value"].gt(0).all()
assert np.allclose(df_events["log_value"], np.log(df_events["total_value"]))
print("Snapshot checks passed. No rows were changed or removed.")
```

```
Snapshot checks passed. No rows were changed or removed.
```

2.4 Coverage and Missing Values

With the files loaded, we check the sample sizes and missing values needed to describe the data. We count which events have the required fields for each original plan. These are eligibility checks, not comparisons of outcome values between groups. The full event table remains intact, and missing returns are not replaced with zero.

```
# Report coverage and planned-model eligibility without fitting models or comparing return values.
coverage = df_events.groupby("trans_code").agg(events=("issuer_cik", "size"), companies=("issuer_cik",
"nunique"))
coverage.index = coverage.index.map({"P": "Purchases", "S": "Sales"})
display(coverage)
display(df_events.isna().sum().rename("missing_values").to_frame())
eligible_1 = df_events["trans_code"].isin(["P", "S"]) & df_events["car_13w"].notna()
eligible_2 = df_events["trans_code"].eq("P") & df_events[["car_13w", "any_c_suite", "log_value",
"n_insiders"]].notna().all(axis=1)
print(f"Plan 1 eligible events: {eligible_1.sum():,}; excluded: {(~eligible_1).sum():,}")
print(f"Plan 2 eligible purchase events: {eligible_2.sum():,}")
print(f"Purchase events excluded from Plan 2: {(df_events['trans_code'].eq('P') & ~eligible_2).sum():,}")
print(f"Event weeks: {df_events['event_week'].min().date()} to {df_events['event_week'].max().date()}")
display(df_cleaning_log)
```

```
Plan 1 eligible events: 26,100; excluded: 1,720
Plan 2 eligible purchase events: 2,227
Purchase events excluded from Plan 2: 129
Event weeks: 2020-01-03 to 2026-01-02
```

	events	companies
trans_code		
Purchases	2356	459
Sales	25464	582

	missing_values
issuer_cik	0
issuer_name	13
sp_ticker	0
price_ticker	1665
trans_code	0
event_week	0
first_filing	0
n_trades	0
n_insiders	0
total_value	0
log_value	0

	missing_values
role	0
role_rank	0
any_c_suite	0
any_plan_10b5_1	17060
mixed_week	0
mean_filing_lag	0
alpha	1720
beta	1720
estimation_weeks	0
car_pre4	1720
car_1w	1720
car_4w	1720
car_13w	1720
car_26w	1720

	step	rows
0	Raw non-derivative transactions	1841674
1	1a. Forms 4 and 4/A only	1820329
2	1b. Purchase (P) and sale (S) codes only	711439
3	1c. Valid dates (lag 0-365 days), shares > 0, ...	700020
4	1d. Superseded amendment rows removed	692025
5	2b. Company in S&P 500 on filing date	127529
6	2c. Same trade under two CIKs removed	127368
7	4a. Trades rolled up into company-week events ...	27820
8	4b. Events with a price series and >= 40 weeks...	26100

3. Data Description and Cleaning Summary

Purpose

This dataset was assembled for the Cornell INFO 2950 group project by Vansh Kakra, Dev Shukla, and Wilson Wang. Its purpose is to examine whether public insider disclosures contain information associated with subsequent stock returns beyond market movements. This relates to **market efficiency**, the extent to which prices already reflect available information. It is intended for educational, observational analysis, not individual surveillance, investment recommendations, or detecting illegal trading.

This description follows Gebru et al. (2018), *Datasheets for Datasets*.

Sample and Coverage

The analysis file, `data/processed/insider_events.csv`, contains **27,820 rows and 25 columns**. One observation is a unique **(issuer_cik, event_week, trans_code)** combination: one company, Friday-labeled week, and direction. A company with both buying and selling has two rows that week. The 593 companies are not 593 simultaneous index constituents; membership changes across the six-year filing period.

There are **2,356 purchase events in 459 companies** and **25,464 sale events in 582 companies**, derived from **6,358 purchase and 121,010 sale trade records**. Filing dates cover January 2, 2020 through December 31, 2025, while event weeks cover January 3, 2020 through January 2, 2026. The entry rule shifts some late-2025 filings into 2026. Selection is based on filings during the study period, not exclusively transaction dates during that period.

Missing data: 1,665 events lack a linked price ticker. Another 55 have a price ticker but no estimated beta, for **1,720 events without returns** in total. This leaves **26,100 events**, including 2,227 purchases and 23,873 sales, with all four CAR horizons. The 129 purchase events without returns comprise 114 without a price ticker and 15 additional events without beta. No extra 26-week attrition occurs in this saved snapshot. The plan flag is missing for **17,060 events**; missing is not coded as zero. Return exclusions are applied only when a particular analysis requires those values.

The interim files remain at a different unit: `sec_ps_trades.csv.gz` contains 692,025 cleaned SEC P/S trade rows across companies; `sp500_trades.csv.gz` contains the 127,368 matched S&P 500 trade rows. The membership and ticker-CIK files document matching. No train/test split is stored in the event file, and there are no hand-labeled outcomes: CARs are computed quantities.

Event Variables

CSV has no enforced schema. Read CIKs as strings to retain leading zeros and parse date columns explicitly. Returns are stored as decimals; multiply by 100 to express percentage points. The following types describe intended values, including missing numeric values where stated.

Column	Type	Meaning and units
`issuer_cik`	String	Ten-digit SEC company identifier, including leading zeros.
`issuer_name`	String	First retained company name within the event; names may change over time.
`sp_ticker`	String	First retained historical index ticker for the event.
`price_ticker`	String, nullable	Linked ticker used for prices, selected by latest membership end among available histories.
`trans_code`	Category	P for purchase or S for sale, as reported in Form 4.
`event_week`	Date	Friday on or after filing date plus one weekday; event aggregation and entry label.
`first_filing`	Date	Earliest filing date among trades in this event.
`n_trades`	Integer	Number of retained trade rows in the event, not number of filings.
`n_insiders`	Integer	Number of distinct retained owner CIKs; joint filings can limit interpretation.
`total_value`	Float	Sum of reported shares times price per share, in nominal dollars.
`log_value`	Float	Natural logarithm of total dollar value, dimensionless.
`role`	Category	Most senior assigned role under the project's ranking.
`role_rank`	Integer	1 C-suite, 2 Other officer, 3 Director, 4 10% owner, 5 Other.
`any_c_suite`	Binary integer	1 if any retained trade has assigned C-suite rank, otherwise 0.

Column	Type	Meaning and units
any_plan_10b5_1	Nullable binary	Maximum observed filing plan flag within the event; missing if all flags are missing. A zero can coexist with missing component flags.
mixed_week	Binary integer	1 if the same company has both P and S events that week.
mean_filing_lag	Float	Mean filing date minus transaction date over event trades, in calendar days.
alpha	Nullable float	Market-model intercept, in weekly decimal-return units.
beta	Nullable float	Market-model slope against SPY, unitless.
estimation_weeks	Integer	Number of available return rows considered, up to 52; 0 when no series exists, with at least 40 required for a fit.
car_pre4	Nullable float	Sum of four abnormal weekly returns ending with the event week; decimal units, not strictly pre-disclosure.
car_1w	Nullable float	Sum of abnormal returns over the first week after the event week, decimal units.
car_4w	Nullable float	Sum over the first 4 weeks after the event week, decimal units.
car_13w	Nullable float	Sum over the first 13 weeks after the event week, decimal units.
car_26w	Nullable float	Sum over the first 26 weeks after the event week, decimal units.

Source Coverage and People

The **SEC** is the primary source of legally mandated disclosures. Its records document reported transactions rather than verified motives or illegal conduct. **Historical membership** comes from a community-maintained resource that adds coverage of departed firms. **Yahoo Finance** supplies adjusted price histories, accessed through the third-party yfinance package. Each source supplies information the others lack: transactions, historical eligibility, and market outcomes, respectively.

Section 16 reporting obligations cover officers, directors, and beneficial owners above the relevant 10% threshold, not every employee or investor. Form 4 changes in ownership generally have a two-business-day reporting deadline. This creates a selected, self-reported sample with varying disclosure delays. See the SEC investor bulletin. The S&P 500 restriction further selects large companies. Vendor coverage, ticker changes, filing corrections, and title wording influence which observations survive matching.

The plan checkbox became required for applicable reports filed on or after **April 1, 2023**, according to the SEC's 10b5-1 disclosure announcement. Earlier missingness cannot be interpreted as absence of a plan. Roles are derived from self-reported relationship fields and titles, not independently verified employment histories.

People and awareness: Filers provide identifying information for a public regulatory disclosure process. Public filing does not establish that they consented to this particular research use. We did not contact insiders or collect research consent, and cannot verify each person's understanding of downstream reuse. Raw files identify individuals and may include addresses; the final event table uses company identifiers and aggregated roles rather than insider names. Owner identifiers in interim data can still be linked to individuals. We avoid individual rankings or allegations.

Preparation

The separate cleaning notebook uses pandas and NumPy to combine filings, membership, and prices. yfinance was used for the Phase 2 price download; we reused those saved prices.

The cleaning notebook documents the selection rules, amendment handling, role assignment, historical membership matching, and price calculations. The final table combines trades by company, week, and direction and attaches the market-adjusted returns. Intermediate files preserve the trade-level records used to construct it.

Access and Intended Use

Suitable uses include descriptive summaries and the limited course-method association models specified below. Unsuitable uses include inferring illegal trading, identifying individual wrongdoing, or presenting a guaranteed profitable strategy. The data do not contain experimental assignments or controls sufficient for causal claims. They are a fixed course-project snapshot, with no promised update schedule or independent audit of all source records.

Reviewers can obtain the saved raw files, intermediate files, and processed files from the submitted Phase 2 snapshot. The Phase 3 exports were regenerated by the separate cleaning notebook; the rebuilt event table matches the saved Phase 2 event values. Original sources are the SEC quarterly datasets, fja05680/sp500, and Yahoo Finance through yfinance. We credit the regulator, community maintainers, price provider, and software contributors; inclusion in this educational repository does not imply ownership of their data or unrestricted redistribution rights.

4. Original Preregistrations

The next two statements reproduce the submitted Phase 2 plans verbatim, including their original section numbers. They record what was planned before the research models were fitted. The earlier EDA exposure remains disclosed in Statement 1.

The original statements exclude significance tests and specify a random event split. Those choices are preserved here as part of the record. Section 5 records the changes used for the time split and overlap checks and distinguishes the fitted models from the remaining significance evaluation.

7. Preregistration Statement 1

Purchases and Subsequent Returns

Prior analysis: Both plans were written after the EDA showed separate purchase and sale return distributions, but before fitting the research models or comparing returns by role or purchase size. These are not outcome-blind plans. Any later changes will be identified in the final report.

Hypothesis: The average **13-week CAR after purchase events is positive and exceeds the average after sale events**. The primary horizon is 13 weeks; 1, 4, and 26 weeks provide secondary descriptive context.

Motivation: Lakonishok and Lee (2001), *Are Insider Trades Informative?* find purchases more informative than sales, with important firm-size differences. Jeng, Metrick, and Zeckhauser (2003), *Estimating the Returns to Insider Trading: A Performance-Evaluation Perspective* report abnormal performance for

purchase portfolios but not comparable evidence for sale portfolios. These findings motivate a directional hypothesis; their samples, weighting, and transaction timing differ from our public-disclosure event design and do not guarantee the result here.

Sample

The unit is one **company-week-direction event**, equally weighted regardless of its dollar value. Eligible filings are retained Form 4/4-A P/S records from 2020-2025 at companies matched to S&P 500 membership on the filing date. P/S is the operational purchase/sale definition and can include private transactions. Entry uses the **first Friday close on or after filing date plus one business day**, as implemented by a weekday offset; holiday and filing-time limitations are documented above.

The market model estimates alpha and beta using up to **52 available weekly returns strictly before the event week**, requiring at least **40**. Weekly abnormal return is actual stock return minus the model prediction (alpha plus beta times SPY return), written as `actual - (alpha + beta * market_return)`. `car_13w` sums the next 13 weekly abnormal returns, excluding the event week. It is stored in decimal units.

Use events with observed `car_13w` and a P/S direction. The current eligible sample is **26,100 events: 2,227 purchases and 23,873 sales**. Exclude missing price histories, insufficient estimation history, and missing outcomes; do not impute zero returns. Keep `mixed_week = 1` events in the primary analysis. Do not trim or winsorize valid outcomes based on their value. Report the retained counts and exclusions.

Planned Analysis

Fit ordinary least squares with an intercept using `sklearn.linear_model.LinearRegression`:

```
car_13w = intercept + beta_purchase * is_purchase + error
```

`is_purchase` is 1 for P and 0 for S, so **sales are the reference group**. The intercept estimates average sale CAR; `beta_purchase` estimates the purchase-minus-sale difference. The implied purchase mean is `intercept + beta_purchase`. The hypothesis predicts **both** `beta_purchase > 0` **and** `intercept + beta_purchase > 0`. Both conditions are needed to support the hypothesis.

Report both group means, the coefficient and implied purchase mean in percentage points, and purchase-only mean CARs at 1, 4, 13, and 26 weeks with their available counts. A decimal coefficient of 0.01 represents a one-percentage-point difference. **We will assess coefficient direction and size, without p-values or statistical-significance claims.** In particular, repeated events and overlapping windows do not justify treating every row as independent evidence.

Sensitivity analysis: Repeat the same 13-week model after excluding `mixed_week = 1` events, reporting the new counts and coefficient alongside the primary result. This sensitivity check does not fix other window overlap. Report positive, zero, negative, and inconsistent results, regardless of whether they support the hypothesis. A null or opposite sign will not trigger a switch of the primary horizon. Further specifications will be labeled exploratory.

8. Preregistration Statement 2

Insider Role and Purchase Size

Hypothesis: Among purchase events, **C-suite participation and larger dollar purchase values are associated with higher 13-week CARs**, controlling for the number of recorded insiders.

Motivation: Executives may have broad access to company information, and committing more dollars may indicate stronger conviction, although wealth and liquidity can also explain purchase size. Seyhun (1986), *Insiders' Profits, Costs of Trading, and Market Efficiency* motivates examining differences in information by insider position. Cohen, Malloy, and Pomorski (2012), *Decoding Inside Information* distinguish routine trading from more informative trading. Their classification is not equivalent to our C-suite flag or 10b5-1 checkbox. The literature motivates heterogeneity, not certainty that our exact role proxy or larger nominal purchases will predict better outcomes. Jeng, Metrick, and Zeckhauser (2003) also find that top executives do not outperform other insiders in their setting, so the role hypothesis faces meaningful contrary evidence.

Sample and Model

Use **purchase events only** (`trans_code = P`) with observed `car_13w` , `any_c_suite` , `log_value` , and `n_insiders` , currently **2,227 events**. Apply Statement 1's filing scope, event unit, entry rule, market model, and return definition. Exclude missing required values without imputation and report exclusions. Keep valid extreme values and mixed weeks in the primary model. Each event receives equal weight.

`any_c_suite` equals 1 when an event includes a trade assigned C-suite rank: an officer title matching CEO, CFO, COO, their expanded names, or President excluding Vice President. Zero includes directors, other officers, 10% owners, and Other; it is **not a directors-only reference group**. `log_value` is the natural logarithm of total reported purchase dollars. `n_insiders` counts distinct retained owner CIKs. Joint-filing and title limitations apply.

Fit the following multivariable linear regression with an intercept using `LinearRegression` :

```
car_13w = intercept + beta_c_suite * any_c_suite + beta_log_value * log_value + beta_insiders * n_insiders + error
```

The directional predictions are **`beta_c_suite > 0` and `beta_log_value > 0`** . Report the two predictions separately; support for one does not imply support for both. The C-suite coefficient is an adjusted difference in decimal CAR at the same recorded log value and insider count. For a 1% larger purchase, the exact modeled difference is `beta_log_value * log(1.01)` , approximately `0.01 * beta_log_value` in decimal CAR, holding other predictors fixed. Multiply by 100 to express percentage points. These are associations, not causal effects. No interactions, extra controls, or outcome-driven variable selection are included in the primary specification.

Model Checks and Reporting

1. **Collinearity:** Report predictor Pearson/Spearman correlations and variance inflation factors (VIF). Compute each VIF as `1 / (1 - R_squared)` from regressing one predictor on the others with an intercept. Large values indicate overlapping predictor information. Discuss the diagnostics without automatically dropping a prespecified variable to improve its coefficient.

2. **Prediction evaluation:** Make one random **70% training / 30% test split**, using `train_test_split(test_size=0.30, random_state=2950)`. Fit the fixed specification on the training subset only. Evaluate once on the held-out test subset with **RMSE**, the square root of mean squared prediction error, and compare with a baseline that always predicts the training outcome mean. Report RMSE in percentage points and both sample sizes. Examine a training residual-versus-fitted plot for systematic patterns and unequal spread; do not tune the model on test outcomes.
3. **Association estimates:** Fit the same fixed specification on all eligible purchase events for descriptive coefficients, explicitly distinguishing that full-sample fit from the model used for held-out RMSE. Report every coefficient, its units, and the sign of each prespecified directional prediction. No t-tests, p-values, or statistical-significance claims are planned.
4. **Dependence caveat and sensitivity:** A random event split can place the same company and overlapping outcome periods in both subsets. Test RMSE therefore measures this random-split task and is not an estimate of independent future-period performance. Repeat the fixed full-sample association model after excluding mixed weeks, and present it beside the primary model. A time-ordered or company-grouped validation scheme is a reviewer question for Phase 3, not an undisclosed replacement chosen after results.

Later-period extension: Leave `any_plan_10b5_1` out of the main model. A separately labeled exploratory Phase 3 analysis may consider 2023-2025 filings with observed flags, starting no earlier than April 1, 2023 and checking component-flag coverage. The small positive-flag purchase sample limits precision.

We will report results regardless of whether they support the hypotheses and document any changes to the specified model.

5. Phase 3 Analysis-Plan Update

November 4, 2026. The rules below were recorded before fitting the research models. The original Phase 2 statements above are preserved verbatim. Phase 2 EDA had already exposed some outcome distributions, so this is not an outcome-blind study.

Decisions for This Analysis

We retain the two original linear regressions, the primary 13-week CAR, equal event weights, and the specified predictors. We do not trim valid extreme outcomes, impute missing returns, tune predictors on test results, or select a horizon based on its results. Purchase-only mean returns at 1, 4, and 26 weeks remain descriptive. The plan flag is not a predictor.

Prediction split: The purchase-only model trains on events before January 1, 2024 whose entire 13-week outcome window also ends before that date. The test set contains events on or after January 1, 2024 through the end of the saved filing-based sample, including event weeks in early January 2026 arising from late-2025 filings. Training candidates whose outcomes extend into the test period are excluded from training. We reconstruct actual outcome dates from the saved weekly return table rather than treating 13 rows as 13 calendar weeks. We fit the fixed model on training observations only and compare test RMSE with a constant prediction equal to the training mean. This replaces the original random 70/30 split, following Lecture 15's time-series validation and leakage precautions. No search over cutoffs or alternative models is planned. This assesses later-period performance for this company population, not generalization to entirely new companies.

Sensitivity samples: In addition to the full eligible sample, we retain the original check excluding mixed purchase/sale weeks. We add a stricter check: exclude mixed weeks, sort eligible events by company and event week, retain the earliest event, then retain the next event only if its entry week is on or after the last retained event's actual 13-week outcome end. Subsequent return windows therefore share no weeks within a company. We repeat this selection separately for the purchase/sale model and the purchase-only model. This avoids letting sale events displace purchase events in the purchase-only question. No outcome values determine which rows are selected. Counts and estimates for all three samples are reported. The stricter sample changes the composition and weighting of the data; it is not a replacement for the original full-sample estimate.

Diagnostics: We report purchase-model predictor correlations and VIF, a training residual-versus-fitted plot, and the fixed time-split prediction comparison. Full-sample association coefficients are distinct from the training-only prediction coefficients. None of these checks will trigger an unreported change in the model.

Scope of the Results

These analyses estimate associations and prediction errors. The non-overlapping sample removes shared outcome weeks within a company, but repeated firms can still be related over time, and different companies can share shocks. Therefore, ordinary independent-row regression p-values, row bootstraps, or unrestricted permutations are not reported as valid significance tests. A time split addresses prediction leakage; it does not solve uncertainty for association estimates.

The significance section remains a separate task required by the rubric. We will make and document that methodological judgment ourselves; TA approval is not a prerequisite. An uncertainty method must state how it handles dependence and what assumptions remain. The family of substantive claims comprises the purchase mean, the purchase-minus-sale difference, and the C-suite and log-value coefficients. No significance claim will be made from coefficient signs alone. A multiple-testing correction cannot itself fix related observations.

Course References

Lecture 14 covers prediction metrics; Lecture 15 covers time-aware evaluation and leakage; Lectures 16 and 17 cover regression inference, confidence intervals, and multiple testing. The time split and sensitivity selection here use pandas, NumPy, and the original scikit-learn regression methods. The Phase 3/4 rubric additionally requires a justified significance evaluation before the report is complete.

Subsequent status: Section 10 records the later inference decision separately, after these model results were observed. It uses the lecture bootstrap on a reduced one-event-per-company sample, explicitly limits the conclusions to that sample, and retains the unresolved shared-shock assumption. The pre-fit protocol above is preserved as the earlier record.

6. Analysis Samples and Outcome Windows

6.1 Recovering the Dates Used by Each Outcome

The cleaned event file contains CAR values but does not store the end date of each outcome window. We recover those dates from the weekly return export using the same next-13-observations rule as the cleaning notebook. We also verify that those observations reproduce every eligible stored 13-week CAR.

This is an analysis-window check; the original cleaned CSV is not changed.

```
# Recover the exact 13-week outcome windows and verify them against the exported CAR values.
from sklearn.linear_model import LinearRegression
from sklearn.metrics import mean_squared_error
import matplotlib.pyplot as plt
from IPython.display import Image
from io import BytesIO

weekly_by_ticker = {t: g.sort_values("week").reset_index(drop=True) for t, g in df_weekly.groupby("ticker")}
analysis_events = df_events.loc[eligible_1].copy()
window_start, window_end, rebuilt = [], [], []
for row in analysis_events.itertuples():
    series = weekly_by_ticker[row.price_ticker]
    position = series["week"].searchsorted(row.event_week, side="right")
    window = series.iloc[position:position + 13]
    assert len(window) == 13
    assert (window["week"].iloc[-1] - row.event_week).days <= 14 * 7
    window_start.append(window["week"].iloc[0])
    window_end.append(window["week"].iloc[-1])
    rebuilt.append((window["ret"] - (row.alpha + row.beta * window["mkt_ret"])).sum())
assert np.allclose(rebuilt, analysis_events["car_13w"], rtol=1e-9, atol=1e-10)
analysis_events["outcome_start"] = window_start
analysis_events["outcome_end"] = window_end
analysis_events["is_purchase"] = analysis_events["trans_code"].eq("P").astype(int)
predictors = ["any_c_suite", "log_value", "n_insiders"]
purchase_events = analysis_events.loc[analysis_events["trans_code"].eq("P") &
analysis_events[predictors].notna().all(axis=1)].copy()
print(f"Verified actual outcome windows for {len(analysis_events):,} events; purchase-model sample:
{len(purchase_events):,}.")
```

```
Verified actual outcome windows for 26,100 events; purchase-model sample: 2,227.
```

Window check: All 26,100 eligible event outcomes were reproduced from the weekly data. This confirms that the split and overlap checks use the same return observations as the saved 13-week CAR, including any permitted gaps in weekly histories.

6.2 Selecting Events with Non-overlapping Outcomes

We first remove mixed purchase/sale weeks for this sensitivity check. Within each company, the earliest eligible event is retained. A later event is retained only when its entry week is on or after the previous retained event's outcome end. Since outcomes begin after entry, the selected outcome windows do not share return weeks. We apply the rule separately to the two model samples, check the resulting windows, and report how many events remain.

```
# Build reproducible sensitivity samples without using return values to select events.
def select_nonoverlapping(frame):
    retained = []
    for _, group in frame.sort_values(["issuer_cik", "event_week"]).groupby("issuer_cik", sort=False):
        last_end = None
        for row in group.itertuples():
            if last_end is None or row.event_week >= last_end:
                retained.append(row.Index)
```

```
                last_end = row.outcome_end
    result = frame.loc[retained].sort_values(["issuer_cik", "event_week"]).copy()
    prior_end = result.groupby("issuer_cik")["outcome_end"].shift()
    assert (prior_end.isna() | result["outcome_start"].gt(prior_end)).all()
    assert not result.duplicated(["issuer_cik", "event_week"]).any()
    return result

samples_1 = {"All eligible": analysis_events,
             "No mixed weeks": analysis_events.loc[analysis_events["mixed_week"].eq(0)].copy()}
samples_1["No mixed weeks; non-overlapping"] = select_nonoverlapping(samples_1["No mixed weeks"])
samples_2 = {"All eligible": purchase_events,
             "No mixed weeks": purchase_events.loc[purchase_events["mixed_week"].eq(0)].copy()}
samples_2["No mixed weeks; non-overlapping"] = select_nonoverlapping(samples_2["No mixed weeks"])
sample_counts = pd.DataFrame([
    {"model": model, "sample": name, "events": len(frame), "companies": frame["issuer_cik"].nunique(),
     "purchases": int(frame["trans_code"].eq("P").sum()), "sales": int(frame["trans_code"].eq("S").sum())}
    for model, samples in [("Purchase versus sale", samples_1), ("Purchase role and size", samples_2)]
    for name, frame in samples.items()])
display(sample_counts)
```

	model	sample	events	companies	purchases	sales
0	Purchase versus sale	All eligible	26100	537	2227	23873
1	Purchase versus sale	No mixed weeks	25246	537	1800	23446
2	Purchase versus sale	No mixed weeks; non-overlapping	7448	537	800	6648
3	Purchase role and size	All eligible	2227	421	2227	0
4	Purchase role and size	No mixed weeks	1800	380	1800	0
5	Purchase role and size	No mixed weeks; non-overlapping	1204	380	1204	0

Sample interpretation: Excluding mixed weeks reduces the comparison sample from 26,100 to 25,246 events. The additional non-overlap rule retains 7,448 events: 800 purchases and 6,648 sales across 537 companies. In the purchase-only model, the corresponding counts are 2,227, 1,800, and 1,204 events. The purchase-only rule starts from purchases, so its 1,204 events are not the same subset as the 800 purchases retained when purchases and sales compete for a company's next slot. These restrictions reduce repeated exposure to the same return weeks, but they also change sample composition. They do not remove all dependence.

7. Purchase Events and Subsequent Returns

7.1 The Primary 13-week Comparison

We fit the original regression with a purchase indicator and an intercept. The intercept is the sale mean, and the purchase coefficient is the purchase-minus-sale difference. Their sum is the purchase mean. We report these in percentage points for the full sample and both sensitivity samples. The first research hypothesis requires both a positive purchase mean and a positive purchase-minus-sale difference.

```
# Fit the original purchase-versus-sale model and report descriptive estimates for all samples.
model1_rows = []
for name, frame in samples_1.items():
    fit = LinearRegression().fit(frame[["is_purchase"]], frame["car_13w"])
    sale_mean = frame.loc[frame["trans_code"].eq("S"), "car_13w"].mean()
    purchase_mean = frame.loc[frame["trans_code"].eq("P"), "car_13w"].mean()
    assert np.isclose(fit.intercept_, sale_mean)
    assert np.isclose(fit.intercept_ + fit.coef_[0], purchase_mean)
    model1_rows.append({"sample": name, "events": len(frame),
                        "purchase_mean_pp": purchase_mean * 100, "sale_mean_pp": sale_mean * 100,
                        "purchase_minus_sale_pp": fit.coef_[0] * 100})
model1_results = pd.DataFrame(model1_rows)
display(model1_results.round(4))
```

	sample	events	purchase_mean_pp	sale_mean_pp	purchase_minus_sale_pp
0	All eligible	26100	2.1257	-2.4714	4.5972
1	No mixed weeks	25246	2.7240	-2.5092	5.2332
2	No mixed weeks; non-overlapping	7448	4.1224	-1.8910	6.0134

Interpretation: In the original eligible sample, mean 13-week CAR is **2.13 percentage points for purchases** and **-2.47 points for sales**. The purchase coefficient is therefore **4.60 percentage points**. Both observed directions agree with the first hypothesis: the purchase mean is positive and exceeds the sale mean.

The purchase-minus-sale difference is 5.23 points after excluding mixed weeks and 6.01 points after also removing overlapping company outcome windows. The purchase mean remains positive in both checks. Thus, the positive direction is not confined to the full sample. The larger estimates in restricted samples do not establish that those samples are less biased; they describe different retained events. These full-event estimates do not have dependence-adjusted intervals. Section 10 assesses uncertainty for a different, explicitly reduced sample.

7.2 Other Return Horizons

The original plan also calls for purchase-only averages at 1, 4, 13, and 26 weeks. These are descriptive summaries using all purchase events with the corresponding outcome available. We keep 13 weeks as the primary horizon regardless of the other averages; these values are not additional significance tests.

```
# Summarize the prespecified purchase-return horizons without choosing a new primary horizon.
purchase_horizons = pd.DataFrame([
    {"weeks": h, "available_purchase_events": int(df_events.loc[df_events["trans_code"].eq("P"),
f"car_{h}w"].notna().sum()),
     "mean_car_pp": df_events.loc[df_events["trans_code"].eq("P"), f"car_{h}w"].mean() * 100}
    for h in [1, 4, 13, 26]])
display(purchase_horizons.round(4))
```

	weeks	available_purchase_events	mean_car_pp
0	1	2227	0.0187
1	4	2227	0.3302

	weeks	available_purchase_events	mean_car_pp
2	13	2227	2.1257
3	26	2227	3.1280

Interpretation: Purchase mean CAR is approximately 0.02, 0.33, 2.13, and 3.13 percentage points at 1, 4, 13, and 26 weeks, respectively. All four averages use 2,227 purchase events in this snapshot. The larger 26-week average does not establish a better prediction horizon or a trading strategy. Thirteen weeks remains the primary horizon fixed in Phase 2, and these other averages are descriptive.

8. Insider Role and Purchase Size

8.1 Full-sample Association Estimates

Among purchases, we regress 13-week CAR on C-suite participation, the natural log of total purchase dollars, and the number of recorded insiders. Each coefficient describes an association holding the other two predictors fixed. Non-C-suite events are the reference for the C-suite indicator, not directors alone.

The table expresses coefficients in percentage points: per indicator change for C-suite participation, per one-unit change in natural log dollars, and per additional recorded insider. We also translate the log-value coefficient into the association with a 1% larger purchase. Full-sample estimates describe associations; the later prediction evaluation uses a separate training-only fit.

```
# Fit the specified purchase-only regression without adding predictors or selecting observations by outcomes.
model2_rows = []
model2_fits = {}
for name, frame in samples_2.items():
    fit = LinearRegression().fit(frame[predictors], frame["car_13w"])
    model2_fits[name] = fit
    model2_rows.append({"sample": name, "events": len(frame), "intercept_pp": fit.intercept_ * 100,
                        "c_suite_pp": fit.coef_[0] * 100, "log_value_pp": fit.coef_[1] * 100,
                        "additional_insider_pp": fit.coef_[2] * 100,
                        "one_percent_larger_value_pp": fit.coef_[1] * np.log(1.01) * 100})
model2_results = pd.DataFrame(model2_rows)
display(model2_results.round(5))
```

Table shown with fields as rows for print readability.

	0	1	2
sample	All eligible	No mixed weeks	No mixed weeks; non-overlapping
events	2227	1800	1204
intercept_pp	-0.24540	-0.55736	-1.66550
c_suite_pp	2.17658	1.81089	1.96987
log_value_pp	0.17842	0.27430	0.34915
additional_insider_pp	-0.22726	-0.34628	-0.25692
one_percent_larger_value_pp	0.00178	0.00273	0.00347

Interpretation: In the full purchase sample, C-suite participation is associated with **2.18 percentage points higher 13-week CAR**, holding log purchase value and recorded insider count fixed. The coefficient for a one-unit increase in log value is **0.178 percentage points**. A 1% larger purchase corresponds to only about **0.0018 percentage points** higher fitted CAR, not 0.178 points. An additional recorded insider is associated with -0.227 points, holding the other predictors fixed.

The C-suite coefficient remains positive in the no-mixed-week and non-overlapping samples, at 1.81 and 1.97 points. The log-value coefficient is also positive in both. These directions agree with the second hypothesis, but positive coefficients alone do not establish significance. The intercept represents log value zero, no C-suite participation, and zero recorded insiders, so it does not describe a typical observed purchase event. The coefficients describe associations rather than effects caused by executive participation or purchase size.

8.2 Predictor Correlations and VIF

Correlations describe how the predictors move together. VIF measures how well each predictor can be explained by the other predictors: a large VIF indicates overlapping information. We calculate the original plan's Pearson and Spearman correlations and VIF on the full eligible purchase sample. These diagnostics do not trigger removal of a prespecified predictor.

```
# Calculate the prespecified predictor correlations and variance inflation factors.
pearson = purchase_events[predictors].corr(method="pearson")
spearman = purchase_events[predictors].corr(method="spearman")
vif_rows = []
for target in predictors:
    others = [column for column in predictors if column != target]
    auxiliary = LinearRegression().fit(purchase_events[others], purchase_events[target])
    r_squared = auxiliary.score(purchase_events[others], purchase_events[target])
    vif_rows.append({"predictor": target, "VIF": 1 / (1 - r_squared)})
vif_results = pd.DataFrame(vif_rows)
print("Pearson correlations")
display(pearson.round(4))
print("Spearman correlations")
display(spearman.round(4))
display(vif_results.round(4))
```

```
Pearson correlations
Spearman correlations
```

	any_c_suite	log_value	n_insiders
any_c_suite	1.0000	0.0717	0.2917
log_value	0.0717	1.0000	-0.0190
n_insiders	0.2917	-0.0190	1.0000

	any_c_suite	log_value	n_insiders
any_c_suite	1.0000	0.1322	0.3319
log_value	0.1322	1.0000	0.1563
n_insiders	0.3319	0.1563	1.0000

	predictor	VIF
0	any_c_suite	1.1002
1	log_value	1.0069
2	n_insiders	1.0949

Diagnostic interpretation: The largest absolute Pearson correlation is about 0.292, between C-suite participation and insider count; the corresponding Spearman correlation is about 0.332. VIFs range from 1.007 to 1.100, so strong linear redundancy among these three predictors is not evident. Low VIF does not establish independence between events, rule out omitted variables, or guarantee useful predictions.

9. Prediction on Later Events

9.1 A Calendar-based Split with an Outcome Gap

We use January 1, 2024 as the fixed boundary. Training events must occur before the boundary and have their full outcome observed before it. The test set begins at the boundary. We report removed boundary-crossing events and actual date ranges so that the split is auditable. Companies may appear in both sets, because this evaluation concerns later events in this company population rather than new-company prediction.

```
# Separate earlier training events from later test events and exclude outcomes crossing the boundary.
cutoff = pd.Timestamp("2024-01-01")
train = purchase_events.loc[purchase_events["event_week"].lt(cutoff) &
purchase_events["outcome_end"].lt(cutoff)].copy()
test = purchase_events.loc[purchase_events["event_week"].ge(cutoff)].copy()
boundary_excluded = purchase_events.loc[purchase_events["event_week"].lt(cutoff) &
purchase_events["outcome_end"].ge(cutoff)].copy()
assert len(train) > 0 and len(test) > 0
assert train["outcome_end"].max() < test["event_week"].min()
assert set(train.index).isdisjoint(test.index)
assert len(train) + len(test) + len(boundary_excluded) == len(purchase_events)
split_table = pd.DataFrame([
    {"subset": name, "events": len(frame), "companies": frame["issuer_cik"].nunique(),
     "first_event": frame["event_week"].min(), "last_event": frame["event_week"].max(),
     "last_outcome": frame["outcome_end"].max()}
    for name, frame in [("Training", train), ("Boundary excluded", boundary_excluded), ("Test", test)]])
display(split_table)
print("Companies appearing in both training and test:", len(set(train["issuer_cik"]) &
set(test["issuer_cik"])))
```

```
Companies appearing in both training and test: 184
```

	subset	events	companies	first_event	last_event	last_outcome
0	Training	1425	353	2020-01-03	2023-09-29	2023-12-29
1	Boundary excluded	112	85	2023-10-06	2023-12-29	2024-03-29
2	Test	690	250	2024-01-05	2026-01-02	2026-04-03

Split interpretation: There are **1,425 training events**, **112 excluded boundary-crossing events**, and **690 test events**. The last training outcome ends on December 29, 2023, before the first test entry on January 5, 2024. Test event weeks extend to January 2, 2026 because late-2025 filings can enter in early 2026. Their last outcome ends on April 3, 2026. A total of 184 companies appear in both sets. The split prevents training outcomes from using the test period; it does not claim that the two sets contain unrelated companies.

9.2 Comparing Predictions with a Simple Baseline

The fixed regression is fitted only on training events. The baseline predicts the training mean for every event. We compare RMSE, the typical prediction error measured as the square root of mean squared error, in percentage points. Lower RMSE is better. The training score describes fit to earlier data; the test score measures performance on later events. We will not change the predictors or cutoff in response to the test score.

```
# Fit once on the training set and compare its errors with the training-mean baseline.
prediction_model = LinearRegression().fit(train[predictors], train["car_13w"])
training_mean = train["car_13w"].mean()
evaluation_rows = []
for name, frame in [("Training", train), ("Test", test)]:
    predicted = prediction_model.predict(frame[predictors])
    baseline = np.full(len(frame), training_mean)
    model_rmse = np.sqrt(mean_squared_error(frame["car_13w"], predicted)) * 100
    baseline_rmse = np.sqrt(mean_squared_error(frame["car_13w"], baseline)) * 100
    evaluation_rows.append({"subset": name, "events": len(frame), "model_RMSE_pp": model_rmse,
                            "baseline_RMSE_pp": baseline_rmse, "improvement_pp": baseline_rmse - model_rmse})
prediction_results = pd.DataFrame(evaluation_rows)
display(prediction_results.round(4))
training_coefficients = pd.DataFrame({"term": ["intercept"] + predictors,
                                      "coefficient_pp": np.r_[prediction_model.intercept_,
prediction_model.coef_] * 100})
print("Training-only coefficients, separate from the full-sample association fit")
display(training_coefficients.round(4))
```

```
Training-only coefficients, separate from the full-sample association fit
```

	subset	events	model_RMSE_pp	baseline_RMSE_pp	improvement_pp
0	Training	1425	16.4478	16.4668	0.0189
1	Test	690	19.4542	19.5091	0.0549

	term	coefficient_pp
0	intercept	0.2928
1	any_c_suite	1.4907
2	log_value	0.1395
3	n_insiders	-0.3208

Prediction interpretation: Test RMSE is **19.454 percentage points** for the regression and **19.509 points** for the training-mean baseline. The improvement is just **0.055 percentage points**, about 0.28% of the baseline RMSE. Training RMSE is 16.448 points versus 16.467 for the baseline. Prediction errors are


larger in the later period, and the fixed predictors offer little improvement over the simple baseline on this split.

The training-only C-suite coefficient is 1.49 percentage points, distinct from the 2.18-point coefficient fitted on all eligible purchase events. Only the training fit produced the reported test predictions. We did not refit, select predictors, or choose another split to improve the test result.

9.3 Training Residuals

A residual is the actual outcome minus the model's prediction. The plot below uses only training events. We look for systematic patterns, uneven spread, and extreme residuals. Valid extreme observations remain in the model, as specified in Phase 2. A quiet-looking plot would not establish independence or validate significance tests.

```
# Plot training residuals against fitted outcomes without using test outcomes for model selection.
training_fitted = prediction_model.predict(train[predictors]) * 100
training_residual = train["car_13w"].to_numpy() * 100 - training_fitted
fig, ax = plt.subplots(figsize=(8, 5))
ax.scatter(training_fitted, training_residual, s=16, alpha=0.4)
ax.axhline(0, color="black", linewidth=1)
ax.set(xlabel="Fitted 13-week CAR (percentage points)", ylabel="Residual (percentage points)",
       title="Purchase model: training residuals")
fig.tight_layout()
buffer = BytesIO()
fig.savefig(buffer, format="png", dpi=150)
display(Image(data=buffer.getvalue()))
plt.close(fig)
display(pd.Series(training_residual).describe(percentiles=[0.01, 0.5,
0.99]).rename("training_residual_pp").to_frame())
```



	training_residual_pp
count	1.425000e+03
mean	3.191209e-16
std	1.645359e+01
min	-6.172941e+01
1%	-3.823355e+01
50%	-6.840061e-01
99%	4.903325e+01
max	8.838642e+01

Residual interpretation: The fitted training CARs occupy a narrow range compared with the spread of residuals. Training residuals range from about -61.73 to +88.39 percentage points, with the middle 98% roughly between -38.23 and +49.03 points. The plot contains large errors and uneven concentrations of observations; it does not justify a claim of constant variance or independent errors. Valid extreme observations were retained under the original plan. Together with the test RMSE, this shows that much of the variation in event returns is unexplained by the three predictors.

10. Uncertainty and Significance: A Course-method Sensitivity Analysis

10.1 Method and Scope

Inference addendum recorded November 4, 2026, after viewing the estimates in Sections 7-9 but before calculating the intervals below. This is a post-model sensitivity analysis, not a new outcome-blind preregistration. The original full-event analyses and their results remain unchanged.

To stay within the lecture methods, we use **row bootstrap resampling**, **percentile confidence intervals**, and a **Bonferroni adjustment**. Lecture 15 introduces resampling with replacement and percentile intervals (pages 186-193); Lecture 17 demonstrates resampling paired regression rows and checking whether a confidence interval includes zero (page 45), and discusses Bonferroni correction (pages 107-108). We do not introduce clustered standard errors, block bootstrap, or a new regression model.

An ordinary row bootstrap does not account for multiple related events from the same company. For this sensitivity analysis, we therefore select **one event per company**: the earliest eligible event after excluding mixed purchase/sale weeks. The rule is applied separately to the comparison sample and the purchase-only sample. Selection depends on company, event date, direction, and eligibility, not the size or sign of returns. We retain the same outcome and predictors as the original regressions.

This changes what is being estimated. The comparison concerns companies' earliest eligible non-mixed events in the observation window. The purchase-only regression concerns their earliest eligible non-mixed purchases. These are not estimates for all events, and an earliest observed event is not necessarily a company's first-ever insider trade. In particular, a company whose earliest event is a sale contributes a sale to the comparison even if it later has a purchase in the purchase-only sample.

What This Does and Does Not Resolve

One event per company eliminates repeated-company rows and shared within-company outcome windows **within each inference sample**. It does not eliminate overlapping calendar windows across different companies. The bootstrap treats the selected company observations as independent and representative of the limited population being described. Shared industry and economic shocks may violate this assumption even after adjusting returns for SPY. Earliest-event selection also concentrates observations near the start of the study, so we show the event-year composition below.

The intervals and decisions are therefore **conditional, approximate sensitivity results**, not a complete dependence correction or proof of significance in the original full-event population. The lecture methods do not supply a general solution to all dependence in this dataset. We retain that limit rather than claiming that filtering has established independence. There is no requirement to obtain TA approval for this judgment.

Four Claims and a Fixed Decision Rule

For each claim, the null is zero and the alternative is nonzero. We use two-sided intervals, while separately checking whether a nonzero estimate has the positive direction predicted in Phase 2.

Claim	Quantity tested in the reduced sample
Purchase mean	Mean 13-week CAR among purchases in the earliest-event comparison sample
Purchase minus sale	Difference in mean 13-week CAR between purchases and sales in that sample
C-suite coefficient	Adjusted C-suite coefficient among earliest eligible purchases
Log-value coefficient	Adjusted log-value coefficient among earliest eligible purchases

The family contains these four claims, not the secondary horizons, intercept, insider-count coefficient, or RMSE comparison. At a family error target of 0.05, Bonferroni allocates **0.05 / 4 = 0.0125** to each claim. We show ordinary 95% intervals for context but use **98.75% intervals** for decisions: the **0.625th and 99.375th percentiles** of the bootstrap estimates. If an adjusted interval excludes zero, we reject that zero null conditionally on the sampling assumptions; otherwise, we fail to reject it. A negative interval would contradict the predicted positive direction. The first research hypothesis requires both purchase-related claims; the two role/size claims are evaluated separately.

This applies the lecture's confidence-interval zero check with the Bonferroni error allocation. Bonferroni controls the family error only to the extent that the individual intervals have valid coverage; percentile-bootstrap coverage is approximate and does not repair dependent observations. We do not turn the fraction of bootstrap estimates above or below zero into a p-value, because that distribution is not a null permutation distribution.

We use **10,000 draws**, seed **2950** for the comparison sample and **2951** for the purchase model. Each draw samples the same number of complete rows with replacement. We keep all valid extremes and do not vary the sample rule, seeds, number of draws, or decision threshold in response to results. The earlier prediction model and test set are not used or retuned here.

10.2 Selecting the Inference Samples

We take the earliest eligible non-mixed event per company from each relevant sample. The checks below confirm that no company appears twice. We then report the sample sizes, purchase/sale balance, C-suite balance, and event-year composition so that the reduced scope is visible.

```
# Select one earliest non-mixed event per company without using outcome values in selection.
inference_comparison = (samples_1["No mixed weeks"].sort_values(["issuer_cik", "event_week"])
                        .drop_duplicates("issuer_cik", keep="first").copy())
inference_purchases = (samples_2["No mixed weeks"].sort_values(["issuer_cik", "event_week"])
                       .drop_duplicates("issuer_cik", keep="first").copy())
for frame in [inference_comparison, inference_purchases]:
    assert frame["issuer_cik"].is_unique
    assert frame["mixed_week"].eq(0).all()
    assert frame["car_13w"].notna().all()
assert inference_purchases["trans_code"].eq("P").all()
assert set(inference_comparison["trans_code"]) == {"P", "S"}
assert set(inference_purchases["any_c_suite"]) == {0, 1}
inference_counts = pd.DataFrame([
    {"sample": name, "events_and_companies": len(frame),
     "purchases": int(frame["trans_code"].eq("P").sum()),
     "sales": int(frame["trans_code"].eq("S").sum()),
     "c_suite_events": int(frame["any_c_suite"].eq(1).sum())}
    for name, frame in [("Earliest event", inference_comparison), ("Earliest purchase",
inference_purchases)]])
display(inference_counts)
inference_years = pd.concat({"Earliest event": inference_comparison["event_week"].dt.year.value_counts(),
                             "Earliest purchase": inference_purchases["event_week"].dt.year.value_counts()},
axis=1).fillna(0).astype(int).sort_index()
inference_years.index.name = "event_year"
display(inference_years)
reduced_purchase_fit = LinearRegression().fit(inference_purchases[predictors], inference_purchases["car_13w"])
comparison_purchase = inference_comparison.loc[inference_comparison["trans_code"].eq("P"), "car_13w"].mean()
comparison_sale = inference_comparison.loc[inference_comparison["trans_code"].eq("S"), "car_13w"].mean()
claim_names = ["Purchase mean", "Purchase minus sale", "C-suite coefficient", "Log-value coefficient"]
reduced_estimates = np.array([comparison_purchase, comparison_purchase - comparison_sale,
                              reduced_purchase_fit.coef_[0], reduced_purchase_fit.coef_[1]])
scope_comparison = pd.DataFrame({"claim": claim_names,
    "original_full_event_estimate_pp": [model1_results.iloc[0]["purchase_mean_pp"],
        model1_results.iloc[0]["purchase_minus_sale_pp"], model2_results.iloc[0]["c_suite_pp"],
        model2_results.iloc[0]["log_value_pp"]],
    "reduced_sample_estimate_pp": reduced_estimates * 100})
display(scope_comparison.round(4))
```

	sample	events_and_companies	purchases	sales	c_suite_events
0	Earliest event	537	101	436	196
1	Earliest purchase	380	380	0	87

	Earliest event	Earliest purchase
event_year		
2020	445	189
2021	24	48
2022	15	56
2023	14	34
2024	19	21
2025	20	32

	claim	original_full_event_estimate_pp	reduced_sample_estimate_pp
0	Purchase mean	2.1257	6.7295
1	Purchase minus sale	4.5972	9.7973
2	C-suite coefficient	2.1766	3.1472
3	Log-value coefficient	0.1784	0.1934

Sample interpretation: The comparison sample contains **537 companies**, each with one event: 101 purchases and 436 sales. The purchase-only sample contains **380 companies**, including 87 C-suite events. These are smaller, differently weighted samples than the original event-level datasets.

The earliest-event rule retains **445 of 537 comparison events in 2020 (82.9%)**. The purchase-only sample has 189 of 380 events in 2020 (49.7%). This concentration is a direct limitation of the rule, not evidence of representative calendar coverage. Companies in the same period can share shocks, so one observation per company does not prove independence.

The reduced-sample purchase mean is 6.73 percentage points and the purchase-minus-sale difference is 9.80 points, compared with 2.13 and 4.60 in the original sample. C-suite and log-value estimates are 3.15 and 0.193 points in the reduced purchase sample, compared with 2.18 and 0.178 originally. The intervals below apply only to the reduced estimates. Their different magnitudes show why we must not attach these intervals to the original estimates.

10.3 Bootstrap Confidence Intervals

For the comparison, each bootstrap draw resamples complete company-event rows and recalculates the purchase mean and purchase-minus-sale difference. Both statistics use the same draw. For the purchase-only regression, we resample complete rows so that the outcome and all three predictors stay together, then refit the original linear model.

This preserves the within-row relationships demonstrated in Lecture 17. We check that each resample contains both comparison directions or a full-rank regression design. Invalid draws would stop the calculation rather than being silently discarded. The code does not change the original datasets or evaluate the test set.

```
# Bootstrap whole rows with fixed seeds and compute ordinary and Bonferroni-adjusted percentile intervals.
BOOTSTRAP_DRAWS = 10000
FAMILY_ALPHA = 0.05
FAMILY_SIZE = 4
bootstrap_estimates = np.empty((BOOTSTRAP_DRAWS, FAMILY_SIZE))
rng_comparison = np.random.default_rng(2950)
rng_purchases = np.random.default_rng(2951)
comparison_y = inference_comparison["car_13w"].to_numpy()
comparison_p = inference_comparison["trans_code"].eq("P").to_numpy()
purchase_x = inference_purchases[predictors].to_numpy(dtype=float)
purchase_y = inference_purchases["car_13w"].to_numpy()
assert np.linalg.matrix_rank(np.column_stack([np.ones(len(purchase_x)), purchase_x])) == 4

for draw in range(BOOTSTRAP_DRAWS):
    index_1 = rng_comparison.choice(len(comparison_y), size=len(comparison_y), replace=True)
    sampled_y, sampled_p = comparison_y[index_1], comparison_p[index_1]
    assert sampled_p.any() and (~sampled_p).any(), "A resample lacks a comparison group."
```

```
    mean_p, mean_s = sampled_y[sampled_p].mean(), sampled_y[~sampled_p].mean()
    bootstrap_estimates[draw, :2] = [mean_p, mean_p - mean_s]

    index_2 = rng_purchases.choice(len(purchase_y), size=len(purchase_y), replace=True)
    sampled_x = purchase_x[index_2]
    assert np.linalg.matrix_rank(np.column_stack([np.ones(len(sampled_x)), sampled_x])) == 4
    sampled_fit = LinearRegression().fit(sampled_x, purchase_y[index_2])
    bootstrap_estimates[draw, 2:] = sampled_fit.coef_[:2]

assert np.isfinite(bootstrap_estimates).all()
ordinary_limits = np.percentile(bootstrap_estimates, [2.5, 97.5], axis=0) * 100
tail_percent = 100 * FAMILY_ALPHA / FAMILY_SIZE / 2
adjusted_limits = np.percentile(bootstrap_estimates, [tail_percent, 100 - tail_percent], axis=0) * 100
uncertainty_results = pd.DataFrame({"claim": claim_names, "estimate_pp": reduced_estimates * 100,
    "CI95_low_pp": ordinary_limits[0], "CI95_high_pp": ordinary_limits[1],
    "CI98.75_low_pp": adjusted_limits[0], "CI98.75_high_pp": adjusted_limits[1]})
uncertainty_results["conditional_decision"] = np.where(
    (adjusted_limits[0] > 0) | (adjusted_limits[1] < 0), "Reject zero", "Fail to reject zero")
uncertainty_results["direction"] = np.where(adjusted_limits[0] > 0, "Positive interval",
    np.where(adjusted_limits[1] < 0, "Negative interval", "Includes zero"))
print(f"Completed {BOOTSTRAP_DRAWS:,} draws per sample. All resamples passed group/design checks.")
print(f"Four-claim error allocation: {FAMILY_ALPHA / FAMILY_SIZE:.4f}; adjusted percentiles:
{tail_percent:.3f}, {100-tail_percent:.3f}.")
print("All intervals below concern the reduced samples and assume sufficiently independent companies.")
display(uncertainty_results.round(4))
```

```
Completed 10,000 draws per sample. All resamples passed group/design checks.
Four-claim error allocation: 0.0125; adjusted percentiles: 0.625, 99.375.
All intervals below concern the reduced samples and assume sufficiently independent companies.
```

Table shown with fields as rows for print readability.

	0	1	2	3
claim	Purchase mean	Purchase minus sale	C-suite coefficient	Log-value coefficient
estimate_pp	6.7295	9.7973	3.1472	0.1934
CI95_low_pp	2.4470	5.1965	-2.0266	-0.6686
CI95_high_pp	11.1383	14.5965	8.0983	0.9892
CI98.75_low_pp	1.1892	3.8596	-3.7175	-0.9009
CI98.75_high_pp	12.4522	15.8870	9.6068	1.2214
conditional_decision	Reject zero	Reject zero	Fail to reject zero	Fail to reject zero
direction	Positive interval	Positive interval	Includes zero	Includes zero

Conditional decisions: Using the four-claim 98.75% intervals:

- **Purchase mean:** 6.73 percentage points, interval **[1.19, 12.45]**. The interval is positive, so the procedure rejects a zero mean for purchases in the earliest-event comparison sample.
- **Purchase minus sale:** 9.80 points, interval **[3.86, 15.89]**. The interval is positive, so the procedure rejects a zero difference in that same sample.
- **C-suite coefficient:** 3.15 points, interval **[-3.72, 9.61]**. The interval includes zero, so we fail to reject the zero-coefficient null in the earliest-purchase sample.
- **Log-value coefficient:** 0.193 points per one-unit increase in log dollars, interval **[-0.901, 1.221]**. The interval includes zero, so we fail to reject this zero-coefficient null as well.


The two purchase comparisons meet the positive-direction criterion under the bootstrap assumptions. This is conditional support in the reduced sample, not a declaration that the full-event hypothesis is established. The role and size intervals allow both positive and negative associations, so the positive point estimates alone are insufficient evidence here. Failure to reject does not mean the true coefficients are zero.

The 98.75% intervals are wider than the ordinary 95% intervals because we account for four claims. Their numerical coverage remains approximate. Because shared calendar shocks can make different companies' outcomes dependent, even the positive intervals may be too narrow; the strong concentration in 2020 makes this concern material. Bonferroni does not correct that problem.

10.4 Reading the Intervals

The narrow bars show ordinary 95% bootstrap intervals. The wider bars show the 98.75% intervals used for the four-claim decision rule. The vertical line marks zero. These are intervals for different quantities with their units specified in the labels; the widths should not be used to rank predictor importance. Crossing zero means the corresponding zero null is not rejected by this conditional procedure.

```
# Display the reduced-sample confidence intervals with the adjusted decision threshold clearly identified.
labels = ["Purchase mean (pp)", "Purchase minus sale (pp)",
          "C-suite: 0 to 1 (pp)", "Log value: +1 log unit (pp)"]
fig, ax = plt.subplots(figsize=(9, 5))
for i in range(FAMILY_SIZE):
    ax.plot(adjusted_limits[:, i], [i, i], color="#3978a8", linewidth=2,
            label="98.75%: Bonferroni decision interval" if i == 0 else None)
    ax.plot(ordinary_limits[:, i], [i, i], color="#173d5a", linewidth=6,
            label="95%: descriptive interval" if i == 0 else None)
    ax.scatter(reduced_estimates[i] * 100, i, color="black", s=25, zorder=3)
ax.axvline(0, color="gray", linestyle="--", linewidth=1)
ax.set_yticks(range(FAMILY_SIZE), labels)
ax.invert_yaxis()
ax.set_xlabel("Estimate and interval (percentage points)")
ax.set_title("One event per company: conditional bootstrap uncertainty")
ax.legend(loc="best", fontsize=8)
fig.tight_layout()
uncertainty_buffer = BytesIO()
fig.savefig(uncertainty_buffer, format="png", dpi=150)
display(Image(data=uncertainty_buffer.getvalue()))
plt.close(fig)
```



11. Conclusions and Limits of the Evidence

What the Analyses Show

The original event-level data show positive mean 13-week CAR after purchases and a positive purchase-minus-sale difference. These directions persist when mixed weeks and overlapping within-company outcome windows are removed. C-suite participation and purchase size also have positive full-sample association estimates, but the fixed model provides very little improvement over a training-mean baseline in the later-period prediction test.

The uncertainty analysis asks a narrower question using one eligible event per company. Under the lecture bootstrap's independence and sampling assumptions, the adjusted intervals support positive purchase means and a positive purchase-minus-sale difference in that reduced sample. They do not provide sufficient evidence against zero for the C-suite or purchase-size coefficients. The magnitude of the reduced-sample estimates differs from the full-event estimates, so these results must remain separate.

What We Cannot Conclude

We have not demonstrated independence across companies or completed a general correction for shared calendar shocks. A large share of the earliest-event comparison sample comes from 2020. The course-method inference therefore remains conditional and cannot establish robust significance for the original full-event population. Increasing the number of bootstrap draws would reduce simulation noise but would not repair that assumption.

Missing price histories, historical membership matching, title-based role assignment, amendment handling, and the assumed filing-to-entry rule also affect the observed sample. These are observational associations, not causal effects, evidence of illegal trading, or a guaranteed investment strategy. The absence of a significant role or size coefficient in this sensitivity analysis does not establish that the true association is absent.

Reproducibility and Course Boundaries

The original preregistrations are unchanged. The time-split rules were recorded before model fitting, and the inference protocol was recorded before computing its intervals, with prior result exposure disclosed. The uncertainty calculation uses whole-row resampling with replacement, the original linear regression, percentile intervals, and Bonferroni error allocation. These build on Lectures 15 and 17. Selecting one event per company and defining the four-claim family are project-specific design choices, not instructions prescribed by the lectures. We did not use clustered errors, block resampling, or claim that an independent-row bootstrap corrected all event dependence.

12. Limitations and Potential Harms

Dependence and the Population Being Studied

The full sample contains repeated companies and overlapping 13-week outcomes. Treating all event rows as independent would overstate the amount of information. Removing overlapping windows within a company reduces repeated use of its returns, but companies still experience the same market and industry news. The one-event-per-company bootstrap removes repeated companies within each inference sample; it does not remove shared calendar shocks. Because 445 of its 537 comparison events occur in 2020, this is a substantial limitation, not a minor technical qualification. Bonferroni adjustment addresses the four simultaneous claims only under valid individual intervals. It cannot fix dependence or biased sampling.

Selecting the earliest eligible event changes the question. Those intervals describe a reduced sample of first observed eligible events, not all disclosures or a company's first-ever trade. The full-event analysis gives more weight to companies with frequent disclosures. Neither sample is a random sample of all public companies, and results need not generalize beyond the historical large-company universe and study period.

Coverage and Measurement

Missing prices and insufficient estimation histories exclude 1,720 events. Firms with delistings, ticker changes, or short price histories may differ systematically from retained firms. The direction of this selection bias is unknown. Historical membership reduces reliance on today's constituents, but community-maintained membership and ticker links can contain errors. Selecting an available price ticker cannot guarantee economic continuity through every corporate reorganization.

Role categories are derived from reported titles and relationships. Joint filings and the owner-selection rule can affect insider counts, while amendment handling may not identify every correction perfectly. Aggregating multiple trades into one weekly event also combines transactions with different motives. Missing 10b5-1 flags, especially before the disclosure change in 2023, cannot be interpreted as discretionary trading. We therefore do not use missing flags as evidence of an unplanned trade.

The entry convention uses the filing date plus one weekday and a Friday label. It does not reconstruct exact publication times, exchange holidays, or executable prices. Outcomes use available weekly observations; a gap can make 13 observations differ from exactly 13 calendar weeks. The market model estimates alpha and beta from up to 52 prior available weeks, requiring at least 40, and assumes that relationship remains useful afterward. CAR is a sum of abnormal returns, not a compounded trading profit. The saved four-week comparison includes the event week and is not strictly pre-disclosure.

Interpretation and Prediction

Insider trades are not randomly assigned. Earnings news, industry conditions, and other omitted variables can influence both transactions and subsequent returns. Positive associations cannot show that purchases caused higher returns. A linear model is a simple approximation, and the broad residual spread shows that most individual outcomes remain poorly predicted. The time split prevents training outcomes from crossing the test boundary, but some companies appear in both periods. It evaluates later events in this setting, not performance on entirely unseen companies. The small RMSE improvement provides little support for practical predictive usefulness.

The inference protocol was chosen after the earlier model results were visible. Recording it before computing intervals makes the sequence transparent, but does not make it an original outcome-blind preregistration. We retain the original plans and report the changes explicitly. Failure to exclude zero for role or size does not prove that their associations are zero.

Potential Harms

Readers could mistake public insider disclosures for evidence of illegal conduct or treat an average association as investment advice. We make neither claim. These calculations omit transaction costs, taxes, implementation delays, and an executable portfolio strategy. Acting on them could cause financial losses. Identifying individuals or ranking them by supposed suspiciousness could also cause reputational harm. The report uses aggregated company events and avoids allegations about individual filers. Public availability does not imply consent to every downstream use, and interim owner identifiers remain potentially linkable to individuals.

13. Acknowledgements

We acknowledge the SEC for public disclosure data, the maintainers of the historical S&P 500 membership resource, Yahoo Finance and yfinance for price access, and the contributors to the Python scientific-computing tools used in this project. The INFO 2950 rubric and course lectures provided the methodological framework. Our mentor is Saif Mahmud; this acknowledgement does not imply that he approved these analysis choices.

OpenAI ChatGPT/Codex assisted with adapting and implementing code, drafting and revising explanations, execution checks, and report preparation. Numerical results were computed from the saved project data. This assistance does not validate the statistical assumptions or substitute for the authors' understanding and responsibility for the submitted work.

14. Bibliography

Cohen, L., Malloy, C., & Pomorski, L. (2012). Decoding inside information. *The Journal of Finance, 67*(3), 1009-1043. https://doi.org/10.1111/j.1540-6261.2012.01740.x. See also the authors' Harvard Law School Forum summary.

Gebru, T., Morgenstern, J., Vecchione, B., Vaughan, J. W., Wallach, H., Daume III, H., & Crawford, K. (2018). *Datasheets for datasets* [Preprint]. arXiv. https://arxiv.org/abs/1803.09010v1

Jeng, L. A., Metrick, A., & Zeckhauser, R. (2003). Estimating the returns to insider trading: A performance-evaluation perspective. *The Review of Economics and Statistics, 85*(2), 453-471. Author's publication page.

Lakonishok, J., & Lee, I. (2001). Are insider trades informative? *The Review of Financial Studies, 14*(1), 79-111. https://doi.org/10.1093/rfs/14.1.79

Seyhun, H. N. (1986). Insiders' profits, costs of trading, and market efficiency. *Journal of Financial Economics, 16*(2), 189-212. https://doi.org/10.1016/0304-405X(86)90060-7

U.S. Securities and Exchange Commission. (n.d.). *Insider transactions data sets*. Quarterly files covering 2020-2025. https://www.sec.gov/data-research/sec-markets-data/insider-transactions-data-sets

U.S. Securities and Exchange Commission. (n.d.). *Investor bulletin: Insider transactions and Forms 3, 4, and 5*. https://www.sec.gov/files/forms-3-4-5.pdf

U.S. Securities and Exchange Commission. (2023, January 20). *Modernizing Rule 10b5-1 insider trading plans*. https://www.sec.gov/newsroom/modernizing-rule-10b5-1-insider-trading-plans

fja05680 and contributors. (n.d.). *Current and historical lists of S&P 500 components since 1996* [Data repository]. GitHub. https://github.com/fja05680/sp500

Yahoo Finance. (n.d.). *Historical stock prices* [Data]. Saved Phase 2 price snapshot collected through October 19, 2026. https://finance.yahoo.com/

yfinance contributors. (n.d.). *yfinance.download* [Software documentation]. https://ranaroussi.github.io/yfinance/reference/api/yfinance.download.html

Cornell University, INFO 2950 course staff. (2026). *Lectures 14-17* [Course slides, October 20, October 22, October 27, and November 3]. Uploaded course materials. In particular, Lecture 15, slides 186-193, covers bootstrap percentile intervals; Lecture 17, slide 45, connects confidence intervals to testing and slides 107-108 discuss Bonferroni adjustment.

Cornell University, INFO 2950 course staff. (2026). *Phase III and IV rubric, Fall 2026* [Course handout]. Uploaded course material.

NumPy developers. (n.d.). *NumPy documentation* [Software documentation]. https://numpy.org/doc/

pandas development team. (n.d.). *pandas documentation* [Software documentation]. https://pandas.pydata.org/docs/

scikit-learn developers. (n.d.). *scikit-learn user guide* [Software documentation]. https://scikit-learn.org/stable/user_guide.html

Matplotlib development team. (n.d.). *Matplotlib documentation* [Software documentation]. https://matplotlib.org/stable/

Project Jupyter and IPython contributors. (n.d.). *Jupyter and IPython* [Notebook and execution software]. https://jupyter.org/ and https://ipython.org/

OpenAI. (2026). *ChatGPT/Codex* [AI assistance with code and writing, described in Section 13]. https://openai.com/