

## Lab Exercise 21

### Building a Docker Image for an HTML App Using Nginx

**Name: Zuhair Ahmad**

**Batch: Devops B1**

**SAP ID: 500119134**

#### 1. Setup

**You will need:**

- **Docker installed on your machine.**
- **A simple HTML file for the app.**

#### 2. Step 1: Create the HTML File

**Create a directory for your HTML app and place an index.html file in it.**

```
mkdir nginx-html-app
```

```
cd nginx-html-app
```

**Inside the nginx-html-app directory, create the HTML file.**

```
touch index.html
```

**Edit the index.html file with the following content (or any custom HTML content you want):**

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>

  <title>Welcome to My Nginx HTML App</title>

</head>


<body>

  <h1>Hello, Nginx Docker!</h1>

  <p>This is a simple HTML app served by Nginx in a Docker container.</p>

</body>

</html>
```




### 3. Step 2: Create a Dockerfile

**In the same directory, create a Dockerfile. This file will define how to build the Docker image using Nginx as the base image.**

```
touch Dockerfile
```

**Edit the Dockerfile and add the following content:**

```
FROM nginx:latest  
  
COPY index.html /usr/share/nginx/html/  
  
EXPOSE 80
```



#### 4. Step 3: Build the Docker Image

**Now that you have the Dockerfile and index.html, it's time to build the Docker image.**

**Run the following command to build the image, giving it a tag (e.g., nginx-html-app):**

```
docker build -t nginx-html-app .
```

```
PS C:\Users\Misha> cd C:\Terraform\nginx-html-app
PS C:\Terraform\nginx-html-app> docker build -t nginx-html-app .
ERROR: error during connect: Head "http://%2F%2F.%2Fpipe%2FdockerDesktopLinuxEngine/_ping": open //./pipe/dockerDesktopLinuxEngine: The system cannot find the file specified.
PS C:\Terraform\nginx-html-app> docker build -t nginx-html-app .
[+] Building 13.1s (5/7)
=> [internal] load build definition from dockerfile
=> transferring dockerfile: 107B
=> [internal] load metadata for docker.io/library/nginx:latest
=> [auth] library/nginx:pull token for registry-1.docker.io
=> [internal] load .dockerignore
=> transferring context: 2B
=> [internal] load build context
=> transferring context: 275B
=> [1/2] FROM docker.io/library/nginx:latest@sha256:1beed3ca46acebe9d3fb62e9067f03d05d5bfa97a00f30938a0a35805632
=> resolve docker.io/library/nginx:latest@sha256:1beed3ca46acebe9d3fb62e9067f03d05d5bfa97a00f30938a0a35805632
=> sha256:e2f8e296d9df1dd5e2ddc81e5e758f9762fdb932e982ac6873e36692c3e3c983 1.40kB / 1.40kB
=> sha256:52bc359bcb74bb3d11b94cf3c6d94bcf9bd2d3e450483fb978124ceddb9ca57 1.21kB / 1.21kB
=> sha256:9def903993e4ef9a3faa02bb893b0382768a4d466d51247bf1ea80b119377a1 404B / 404B
=> sha256:d921c57c6a81addac6ca451906699ca6ee8c01fd708805a928181c5370b0a30c 956B / 956B
=> sha256:320b0949be89766f7c6a8746f1971021a8e8c84928af00454c0f9c6e38ebf54c 628B / 628B
=> sha256:266626526d42cf7fe5f56b933db3f4c59c0596b7e2c3a556ba5ec4981daf3e9d 11.53MB / 29.97MB
=> sha256:d7ecd7702a5dbf6d0f79a71edc34b534d08f3051980e2c948fba72db3197fc 18.87MB / 29.78MB
```

**Docker will use the Nginx base image, copy your index.html into the appropriate directory, and build the image.**

## 5. Step 4: Run the Docker Container

**After building the image, you can run the container with the following command:**

```
docker run -d -p 8006:80 nginx-html-app
```


```
PS C:\Terraform\nginx-html-app> docker run -d -p 8006:80 nginx-html-app
b520c9a35feedb7793c205fbbf4cd8b5a2872fae535ac2cd6a38cc0462e8f1f8f
PS C:\Terraform\nginx-html-app>
```

**This command runs the container in detached mode (-d) and maps port 8006 on your host machine to port 80 inside the container, where Nginx is serving your HTML app.**

## 6. Step 5: Verify

**Open a browser and go to `http://localhost:8006`. You should see your HTML page with the**

**message “Hello, Nginx Docker!”.**



## Hello, Nginx Docker!

This is a simple HTML app served by Nginx in a Docker container.

### 7. Step 6: Stop and Remove the Container

Once you're done, you can stop and remove the container:

`docker ps` # to see running containers

```
PS C:\Terraform\nginx-html-app> docker ps
CONTAINER ID   IMAGE          COMMAND                  CREATED        STATUS        PORTS
b520c9a35fee   nginx-html-app "/docker-entrypoint..." About a minute ago Up About a minute 0.0.0.0:8006->80/tcp,
[::]:8006->80/tcp nice_black
PS C:\Terraform\nginx-html-app>
```

`docker stop <container-id>`

`docker rm <container-id>`

```
PS C:\Terraform\nginx-html-app> docker stop b520c9a35feedb7793c205fbf4cd8b5a2872fae535ac2cd6a38cc0462e8f1f8f
b520c9a35feedb7793c205fbf4cd8b5a2872fae535ac2cd6a38cc0462e8f1f8f
PS C:\Terraform\nginx-html-app> docker rm b520c9a35feedb7793c205fbf4cd8b5a2872fae535ac2cd6a38cc0462e8f1f8f
b520c9a35feedb7793c205fbf4cd8b5a2872fae535ac2cd6a38cc0462e8f1f8f
PS C:\Terraform\nginx-html-app>
```