

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT
on

OPERATING SYSTEMS

Submitted by

VANSHIKA MALHOTRA(1BF24CS331)

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

Feb-2026 to June-2026

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019

(Affiliated To Visvesvaraya Technological University, Belgaum)

Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “OPERATING SYSTEMS – 23CS4PCOPS” carried out by Vanshika Malhotra(1BF24CS331), who is Bonafide student of B. M. S. College of Engineering. It is in partial fulfilment for the award of Bachelor of Engineering in Computer Science and Engineering of the Visvesvaraya Technological University, Belgaum during the year Feb-2026 to June-2026

. The Lab report has been approved as it satisfies the academic requirements in respect of a OPERATING SYSTEMS - (23CS4PCOPS) work prescribed for the said degree.

Seema Patil
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Kavitha Sooda
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index Sheet

Sl. No.	Experiment Title	Page No.
1.	Write a C program to simulate the following non-pre-emptive CPU scheduling algorithm to find turnaround time and waiting time. →FCFS → SJF (pre-emptive & Non-preemptive) → Priority (pre-emptive & Non-pre-emptive) →Round Robin (Experiment with different quantum sizes for RR algorithm)	1-21
2.	Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.	21-26
3.	Write a C program to simulate Real-Time CPU Scheduling algorithms: a) Rate- Monotonic b) Earliest-deadline First c)Proportional scheduling	26-32
4.	Write a C program to simulate a)producer-consumer problem using semaphores b) Dining Philosophers problem.	32-38
5.	Write a C program to simulate: a) Bankers' algorithm for the purpose of deadlock avoidance b) Deadlock Detection	39-46
6.	Write a C program to simulate the following contiguous memory allocation techniques. a) Worst-fit b) Best-fit c) First-fit	46-52

7.	Write a C program to simulate page replacement algorithms. a) FIFO b) LRU c) Optimal	52-60
----	---	-------

Course Outcomes

C01	Apply the different concepts and functionalities of Operating System
C02	Analyse various Operating system strategies and techniques
C03	Demonstrate the different functionalities of Operating System.
C04	Conduct practical experiments to implement the functionalities of Operating system.

Program -1

Question:

Write a C program to simulate the following non-pre-emptive CPU scheduling algorithm to find turnaround time and waiting time.

→FCFS

→ SJF (pre-emptive & Non-preemptive)

Code:

=>FCFS:

```
#include<stdio.h>
```

```
void sort(int proc_id[],int at[],int bt[],int n)
{   int
min=at[0],temp=0;   for(int
i=0;i<n;i++)
{
min=at[i];
    for(int j=i;j<n;j++)
    {        if(at[j]<min)
        {            temp=at[i];
at[i]=at[j];            at[j]=temp;
temp=bt[j];
bt[j]=bt[i];
bt[i]=temp;
temp=proc_id[i];
proc_id[i]=proc_id[j];
proc_id[j]=temp;
        }
    }
}
```

```
void main()
{   int n,c=0;   printf("Enter number of
processes: ");   scanf("%d",&n);   int
proc_id[n],at[n],bt[n],ct[n],tat[n],wt[n];
double
avg_tat=0.0,ttat=0.0,avg_wt=0.0,twt=0.
```

```

0;   for(int i=0;i<n;i++)
proc_id[i]=i+1;   printf("Enter arrival
times:\n");   for(int i=0;i<n;i++)
scanf("%d",&at[i]);   printf("Enter burst
times:\n");   for(int i=0;i<n;i++)
scanf("%d",&bt[i]);

    sort(proc_id,at,bt,n);   //completion
time   for(int i=0;i<n;i++)
    {       if(c>=at[i])
c+=bt[i];       else
c+=at[i]-ct[i-1]+bt[i];       ct[i]=c;
    }
    //turnaround time
for(int i=0;i<n;i++)
tat[i]=ct[i]-at[i];   //waiting
time   for(int i=0;i<n;i++)
wt[i]=tat[i]-bt[i];

    printf("FCFS scheduling:\n");   printf("PID\tAT\tBT\tCT\tTAT\tWT\n");
for(int i=0;i<n;i++)
printf("%d\t%d\t%d\t%d\t%d\t%d\t%d\n",proc_id[i],at[i],bt[i],ct[i],tat[i],wt[i]);

    for(int i=0;i<n;i++)
    {
ttat+=tat[i];twt+=wt[i];
    }
    avg_tat=ttat/(double)n;
avg_wt=twt/(double)n;
    printf("\nAverage turnaround time:%lfms\n",avg_tat);
printf("\nAverage waiting time:%lfms\n",avg_wt);
}

```

Result:

Process	Burst Time	Arrival Time	Waiting Time	Turn Around Time
0	5	0	5	
1	3	1	4	7
2	8	2	6	14
3	6	3	13	19

Average Waiting Time: 5.75
Average Turnaround Time: 11.25

Process returned 0 (0x0) execution time : 0.320 s
Press any key to continue.

=>SJF(Non-preemptive):

```
#include <stdio.h>
```

```
struct Process {
int pid;
    int at; // Arrival Time
int bt; // Burst Time    int
ct; // Completion Time    int
tat; // Turnaround Time    int
wt; // Waiting Time    int
done;
};
```

```
int main() {
```

```
int n;
```

```
    printf("Enter number of processes: ");
```

```
    scanf("%d", &n);
```

```
    struct Process p[n];
```

```
    for(int i = 0; i < n; i++) {
```

```

    printf("\nEnter Arrival Time and Burst Time for P%d: ", i + 1);
    p[i].pid = i + 1;
    scanf("%d %d", &p[i].at, &p[i].bt);
    p[i].done = 0;
}

```

```

    int completed = 0, time = 0;
    float totalWT = 0, totalTAT = 0;

```

```

    while(completed < n) {
    int idx = -1;    int
    minBT = 9999;

        // Find process with shortest burst time
    for(int i = 0; i < n; i++) {        if(p[i].at <=
    time && p[i].done == 0) {            if(p[i].bt <
    minBT) {                minBT = p[i].bt;
    idx = i;
        }
    }
    }
}

```

```

    // If no process is available
    if(idx == -1) {        time++;
    }    else {        time +=
    p[idx].bt;        p[idx].ct =
    time;        p[idx].tat =
    p[idx].ct - p[idx].at;
    p[idx].wt = p[idx].tat - p[idx].bt;

        totalWT += p[idx].wt;        totalTAT
    += p[idx].tat;

```



```

        p[idx].done = 1;        completed++;
    }
}

printf("\nPID\tAT\tBT\tCT\tTAT\tWT\n");

for(int i = 0; i < n; i++) {
printf("P%d\t%d\t%d\t%d\t%d\t%d\n",
        p[i].pid,
p[i].at,        p[i].bt,
p[i].ct,
p[i].tat,
p[i].wt);
    }

printf("\nAverage Turnaround Time = %.2f", totalTAT / n);
printf("\nAverage Waiting Time = %.2f\n", totalWT / n);

return 0;
}

```

```

1BF24CS331
Enter number of processes: 4

Enter Arrival Time and Burst Time for P1: 0 6
Enter Arrival Time and Burst Time for P2: 1 8
Enter Arrival Time and Burst Time for P3: 2 7
Enter Arrival Time and Burst Time for P4: 3 3

PID      AT      BT      CT      TAT      WT
P1        0        6        6        6        0
P2        1        8       24       23       15
P3        2        7       16       14        7
P4        3        3        9        6        3

Average Turnaround Time = 12.25
Average Waiting Time = 6.25

Process returned 0 (0x0)   execution time : 28.850 s
Press any key to continue.

```

SJF(PREEMPTIVE):

```
#include <stdio.h>
```

```

struct Process {
int pid;
    int at;    // Arrival Time    int
bt;    // Burst Time    int rt;
// Remaining Time    int ct;
// Completion Time    int tat;
// Turnaround Time    int wt;
// Waiting Time
};

```

```

int main() {
int n;

printf("Enter number of processes: "); scanf("%d",
&n);

struct Process p[n];

for(int i = 0; i < n; i++) {
printf("\nEnter Arrival Time and Burst Time for P%d: ", i + 1);

p[i].pid = i + 1;
scanf("%d %d", &p[i].at, &p[i].bt);

p[i].rt = p[i].bt;
}

int completed = 0, time = 0;
float totalWT = 0, totalTAT = 0;

while(completed < n) {
int idx = -1;    int
minRT = 9999;

// Find process with shortest remaining time
for(int i = 0; i < n; i++) {    if(p[i].at <= time
&& p[i].rt > 0) {    if(p[i].rt < minRT) {
minRT = p[i].rt;    idx = i;
    }
    }
}
}
}

```

```

        // If no process has arrived      if(idx
== -1) {          time++;
    }          else {
        // Execute process for 1 unit time      p[idx].rt--;
time++;

        // If process completed      if(p[idx].rt
== 0) {
completed++;

        p[idx].ct = time;          p[idx].tat
= p[idx].ct - p[idx].at;          p[idx].wt =
p[idx].tat - p[idx].bt;

        totalWT += p[idx].wt;          totalTAT
+= p[idx].tat;
    }
}
}

printf("\nPID\tAT\tBT\tCT\tTAT\tWT\n");

for(int i = 0; i < n; i++) {
printf("P%d\t%d\t%d\t%d\t%d\t%d\n",
    p[i].pid,
p[i].at,
p[i].bt,
p[i].ct,
p[i].tat,
p[i].wt);
}
printf("\n

```

```

Average
Turnaroun
d Time =
%.2f",
totalTAT /
n);

printf("\nAverage Waiting Time = %.2f\n", totalWT / n);

return 0;
}

```

```

1BF24CS331
Enter number of processes: 4

Enter Arrival Time and Burst Time for P1: 0 8
Enter Arrival Time and Burst Time for P2: 1 4
Enter Arrival Time and Burst Time for P3: 2 9
Enter Arrival Time and Burst Time for P4: 3 5

PID      AT      BT      CT      TAT      WT
P1        0        8      17      17        9
P2        1        4       5       4         0
P3        2        9      26      24       15
P4        3        5      10       7         2

Average Turnaround Time = 13.00
Average Waiting Time = 6.50

Process returned 0 (0x0)   execution time : 20.935 s
Press any key to continue.

```

PRIORITY(NON-PREEMPTIVE):

```

#include <stdio.h>

int main() {
    int n, i, j;

    printf("Enter number of processes: ");    scanf("%d",
&n);

    int pid[n], at[n], bt[n], pr[n];    int
ct[n], tat[n], wt[n];    int
completed[n];

    for(i = 0; i < n; i++)
    {
        printf("\nEnter details for Process P%d\n", i + 1);

        pid[i] = i + 1;

        printf("Arrival Time: ");    scanf("%d",
&at[i]);

        printf("Burst Time: ");    scanf("%d",
&bt[i]);

        printf("Priority: ");    scanf("%d",
&pr[i]);

        completed[i] = 0;
    }

```

```

    int current_time = 0;    int
completed_count = 0;

while(completed_count < n)
{
    int highest_priority = 9999;    int
selected = -1;

    for(i = 0; i < n; i++)
    {
        if(at[i] <= current_time && completed[i] == 0)
        {
            if(pr[i] < highest_priority)
            {
                highest_priority = pr[i];    selected
= i;
            }
        }
    }

    if(selected == -1)
    {
        current_time++;
    }    else
    {
        ct[selected] = current_time + bt[selected];

        tat[selected] = ct[selected] - at[selected];    wt[selected]
= tat[selected] - bt[selected];

        current_time = ct[selected];

```

```

        completed[selected] = 1;        completed_count++;
    }
}

printf("\n----- Priority Scheduling (Non-Preemptive) ----- \n");

printf("\nPID\tAT\tBT\tPR\tCT\tTAT\tWT\n");

float total_tat = 0, total_wt = 0;

for(i = 0; i < n; i++)
{
    printf("P%d\t%d\t%d\t%d\t%d\t%d\t%d\n",
        pid[i], at[i], bt[i], pr[i],
ct[i], tat[i], wt[i]);

    total_tat += tat[i];        total_wt
+= wt[i];
}

printf("\nAverage Turnaround Time = %.2f", total_tat / n);    printf("\nAverage
Waiting Time = %.2f\n", total_wt / n);

return 0;
}

```



```
"C:\Users\Vanshika Malhotra\  ×  +  v
1BF24CS331
Enter number of processes: 5

Enter details for Process P1
Arrival Time: 0
Burst Time: 3
Priority: 5

Enter details for Process P2
Arrival Time: 2
Burst Time: 2
Priority: 3

Enter details for Process P3
Arrival Time: 3
Burst Time: 5
Priority: 2

Enter details for Process P4
Arrival Time: 4
Burst Time: 4
Priority: 4

Enter details for Process P5
Arrival Time: 6
Burst Time: 1
Priority: 1

----- Priority Scheduling (Non-Preemptive) -----

PID    AT    BT    PR    CT    TAT    WT
P1      0      3      5      3      3      0
P2      2      2      3     11      9      7
P3      3      5      2      8      5      0
P4      4      4      4     15     11      7
P5      6      1      1      9      3      2

Average Turnaround Time = 6.20
Average Waiting Time = 3.20

Process returned 0 (0x0)  execution time : 21.687 s
Press any key to continue.
```

PRIORITY(PREEMPTIVE):

```
#include <stdio.h>
```

```
int main() {
    int n, i;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    int pid[n], at[n], bt[n], pr[n];
    int rt[n], ct[n], tat[n], wt[n];
    for(i = 0; i < n; i++)
```

```

{
    printf("\nEnter details for Process P%d\n", i + 1);

    pid[i] = i + 1;

    printf("Arrival Time: ");    scanf("%d",
&at[i]);

    printf("Burst Time: ");    scanf("%d",
&bt[i]);

    printf("Priority: ");    scanf("%d",
&pr[i]);
    rt[i] =
bt[i];
}

int current_time = 0;    int
completed = 0;

while(completed < n)
{
    int highest_priority = 9999;    int
selected = -1;

    for(i = 0; i < n; i++)
    {
        if(at[i] <= current_time && rt[i] > 0)
        {
            if(pr[i] < highest_priority)
            {
                highest_priority = pr[i];

```

```

selected = i;
    }
}
}

if(selected == -1)
{
    current_time++;
} else
{
rt[selected]--;

    current_time++;

    if(rt[selected] == 0)
    {
        ct[selected] = current_time;

        tat[selected] = ct[selected] - at[selected];

        wt[selected] = tat[selected] - bt[selected];

        completed++;
    }
}

printf("\n----- Priority Scheduling (Preemptive) ----- \n");
printf("\nPID\tAT\tBT\tPR\tCT\tTAT\tWT\n");

float total_tat = 0, total_wt = 0;

```

```

for(i = 0; i < n; i++)
{
    printf("P%d\t%d\t%d\t%d\t%d\t%d\t%d\n",
        pid[i], at[i], bt[i], pr[i],
        ct[i], tat[i], wt[i]);

    total_tat += tat[i];    total_wt
+= wt[i];
}

printf("\nAverage Turnaround Time = %.2f", total_tat / n);    printf("\nAverage
Waiting Time = %.2f\n", total_wt / n);

return 0;
}

```

```
"C:\Users\Vanshika Malhotra\  × + v
1BF24CS331
Enter number of processes: 5

Enter details for Process P1
Arrival Time: 0
Burst Time: 3
Priority: 3

Enter details for Process P2
Arrival Time: 1
Burst Time: 4
Priority: 2

Enter details for Process P3
Arrival Time: 2
Burst Time: 6
Priority: 4

Enter details for Process P4
Arrival Time: 3
Burst Time: 4
Priority: 6

Enter details for Process P5
Arrival Time: 5
Burst Time: 2
Priority: 10

----- Priority Scheduling (Preemptive) -----

PID    AT    BT    PR    CT    TAT    WT
P1      0     3     3     7     7     4
P2      1     4     2     5     4     0
P3      2     6     4    13    11     5
P4      3     4     6    17    14    10
P5      5     2    10    19    14    12

Average Turnaround Time = 10.00
Average Waiting Time = 6.20

Process returned 0 (0x0)   execution time : 40.536 s
Press any key to continue.
```

ROUND ROBIN:

```
#include <stdio.h>
```

```
int main() {
    int n, tq, i;
    printf("Enter number of processes: ");
```

```

scanf("%d", &n);

printf("Enter Time Quantum: "); scanf("%d",
&tq);

int pid[n], at[n], bt[n], rt[n]; int
ct[n], tat[n], wt[n];

for(i = 0; i < n; i++)
{
    printf("\nEnter details for Process P%d\n", i + 1);

    pid[i] = i + 1;

    printf("Arrival Time: "); scanf("%d",
&at[i]);

    printf("Burst Time: "); scanf("%d",
&bt[i]);
    rt[i] =
bt[i];
}

int completed = 0, current_time = 0;

while(completed < n)
{
    int executed
= 0;

    for(i = 0; i < n; i++)
    {
        if(at[i] <= current_time && rt[i] > 0)

```

```

        {           executed
= 1;

        if(rt[i] > tq)
        {
current_time += tq;           rt[i]
-= tq;           }           else
        {           current_time
+= rt[i];

        ct[i] = current_time;

        tat[i] = ct[i] - at[i];

        wt[i] = tat[i] - bt[i];
rt[i] =
0;

        completed++;
        }
    }
}

if(executed == 0)
{
    current_time++;
}
}

printf("\n----- Round Robin Scheduling ----- \n");
printf("\nPID\tAT\tBT\tCT\tTAT\tWT\n");

float total_tat = 0, total_wt = 0;

```

```

for(i = 0; i < n; i++)
{
    printf("P%d\t%d\t%d\t%d\t%d\t%d\n",
           pid[i], at[i], bt[i],          ct[i],
tat[i], wt[i]);

    total_tat += tat[i];    total_wt
+= wt[i];
}

printf("\nAverage Turnaround Time = %.2f",
       total_tat / n);

printf("\nAverage Waiting Time = %.2f\n",
       total_wt / n);

return 0;
}

```



```
"C:\Users\Vanshika Malhotra\  × + v
1BF24CS331
Enter number of processes: 5
Enter Time Quantum: 2

Enter details for Process P1
Arrival Time: 0
Burst Time: 5

Enter details for Process P2
Arrival Time: 1
Burst Time: 3

Enter details for Process P3
Arrival Time: 2
Burst Time: 1

Enter details for Process P4
Arrival Time: 3
Burst Time: 2

Enter details for Process P5
Arrival Time: 4
Burst Time: 3

----- Round Robin Scheduling -----

PID    AT    BT    CT    TAT    WT
P1      0     5     14    14     9
P2      1     3     12    11     8
P3      2     1     5     3     2
P4      3     2     7     4     2
P5      4     3     13    9     6

Average Turnaround Time = 8.20
Average Waiting Time = 5.40

Process returned 0 (0x0)   execution time : 81.592 s
Press any key to continue.
|
```

PROGRAM-2

MULTI-LEVEL QUEUE

```
#include <stdio.h>
```

```
struct Process {
int pid;
    int qn;    // Queue Number
int at;    // Arrival Time
    int bt;    // Burst Time
```

```

    int rt;    // Remaining Time
int ct;    // Completion Time    int
tat;    // Turnaround Time    int
wt;    // Waiting Time
};

int main() {
int n, tq;

    printf("1BF24CS331\n");
printf("Enter number of processes: ");    scanf("%d",
&n);

    struct Process p[n];

    printf("Enter Time Quantum for Queue 1: ");
scanf("%d", &tq);

    // Input
    for(int i = 0; i < n; i++) {
p[i].pid = i + 1;

        printf("\nEnter Queue No, Arrival Time and Burst Time for P%d: ", i+1);
scanf("%d %d %d", &p[i].qn, &p[i].at, &p[i].bt);

        p[i].rt = p[i].bt;
    }

    int completed = 0, time = 0;    float
avgTAT = 0, avgWT = 0;    // Multi-
Level Queue Scheduling
while(completed < n) {

```

```

int executed = 0;

// Queue 1 - Round Robin (Higher Priority)    for(int
i = 0; i < n; i++) {

    if(p[i].qn == 1 && p[i].at <= time && p[i].rt > 0) {

        executed = 1;

        if(p[i].rt > tq) {
time += tq;           p[i].rt
-= tq;
        }           else {
time += p[i].rt;
p[i].rt =
0;

        p[i].ct = time;
p[i].tat = p[i].ct - p[i].at;           p[i].wt
= p[i].tat - p[i].bt;

        avgTAT += p[i].tat;
avgWT += p[i].wt;           completed++;
        }
    }
}

// Queue 2 - FCFS (Executed only if Queue 1 empty)
if(!executed) {           int idx = -1;           int earliest = 9999;

        for(int i = 0; i < n; i++) {

```

```

        if(p[i].qn == 2 && p[i].at <= time && p[i].rt > 0) {
if(p[i].at < earliest) {          earliest = p[i].at;          idx
= i;
        }
    }
}

```

```

        if(idx != -1) {
time += p[idx].rt;          p[idx].rt
= 0;

        p[idx].ct = time;
p[idx].tat = p[idx].ct - p[idx].at;          p[idx].wt
= p[idx].tat - p[idx].bt;

```

```

        avgTAT += p[idx].tat;
avgWT += p[idx].wt;          completed++;
    }          else
{          time++;
    }
}
}

```

// Output

```
printf("\nPID\tQNo\tAT\tBT\tCT\tTAT\tWT\n");
```

```

    for(int i = 0; i < n; i++) {
printf("P%d\t%d\t%d\t%d\t%d\t%d\t%d\n",
        p[i].pid,
p[i].qn,
p[i].at,          p[i].bt,
p[i].ct,

```

```

p[i].tat,
p[i].wt);
}

printf("\nAverage Turnaround Time = %.2f", avgTAT/n);
printf("\nAverage Waiting Time = %.2f\n", avgWT/n);

return 0;

```

```

1BF24CS331
Enter number of processes: 4
Enter Time Quantum for Queue 1: 2

Enter Queue No, Arrival Time and Burst Time for P1: 1 0 4
Enter Queue No, Arrival Time and Burst Time for P2: 1 0 3
Enter Queue No, Arrival Time and Burst Time for P3: 2 0 8
Enter Queue No, Arrival Time and Burst Time for P4: 1 10 5

PID    QNo    AT    BT    CT    TAT    WT
P1      1      0      4      6      6      2
P2      1      0      3      7      7      4
P3      2      0      8     15     15      7
P4      1     10      5     20     10      5

Average Turnaround Time = 9.50
Average Waiting Time = 4.50

Process returned 0 (0x0)   execution time : 49.434 s
Press any key to continue.
|

```

PROGRAM-3

RATE MONOTONIC

```
#include <stdio.h>
```

```

struct Process {
int pid;   int burst;
int period;  int
remaining;
};

```

```

int main() {    int n,
time, hyper = 20;

    printf("1BF24CS331\n");    printf("Enter
number of processes: ");    scanf("%d",
&n);

    struct Process p[n];

    for(int i = 0; i < n; i++) {
        printf("\nEnter Burst Time and Period for P%d: ", i + 1);

        p[i].pid = i + 1;
        scanf("%d %d", &p[i].burst, &p[i].period);

        p[i].remaining = 0;
    }

    printf("\nGantt Chart:\n");

    for(time = 0; time < hyper; time++) {

        // Release process at start of period
        for(int i = 0; i < n; i++) {            if(time
% p[i].period == 0) {
            p[i].remaining = p[i].burst;
                }
            }

            int idx = -1;            int minPeriod
= 9999;

```

```

        // Higher priority = smaller period        for(int
i = 0; i < n; i++) {
        if(p[i].remaining > 0 && p[i].period < minPeriod) {
minPeriod = p[i].period;
        idx = i;
        }
    }

    if(idx != -1) {
        printf("P%d ", p[idx].pid);
p[idx].remaining--;
    }    else
{
        printf("Idle ");
    }
}

return 0;
}

```

```

1BF24CS331
Enter number of processes: 3

Enter Burst Time and Period for P1: 1 4

Enter Burst Time and Period for P2: 2 5

Enter Burst Time and Period for P3: 1 10

Gantt Chart:
P1 P2 P2 P3 P1 P2 P2 Idle P1 Idle P2 P2 P1 P3 Idle P2 P1 P2 Idle Idle
Process returned 0 (0x0)    execution time : 20.197 s
Press any key to continue.

```

Earliest-deadline First :

```
#include <stdio.h>
```

```

struct Process
{   int pid;   int
burst;   int
period;   int
deadline;   int
remaining;
};

int main() {   int n,
time, hyper = 20;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    struct Process p[n];

    for(int i = 0; i < n; i++) {        printf("\nEnter Burst Time
and Period for P%d: ", i + 1);

        p[i].pid = i + 1;        scanf("%d %d", &p[i].burst,
&p[i].period);

        p[i].remaining = 0;
        p[i].deadline = p[i].period;
    }

    printf("\nGantt Chart:\n");

    for(time = 0; time < hyper; time++) {

        // Release tasks        for(int i = 0; i <
n; i++) {            if(time % p[i].period == 0)
        {                p[i].remaining = p[i].burst;
        p[i].deadline = time + p[i].period;
        }
        }            int
idx = -1;            int
earliest = 9999;

        // Select earliest deadline        for(int i = 0; i < n; i++)
        {            if(p[i].remaining > 0 && p[i].deadline < earliest)
        {                earliest = p[i].deadline;                idx = i;
        }
        }
    }

```



```

        }          if(idx != -1)
    {          printf("P%d ",
p[idx].pid);
p[idx].remaining--;
        }          else {          printf("Idle
");
        }
    }
}

return 0;
}

```

```

1BF24CS331
Enter number of processes: 3

Enter Burst Time and Period for P1: 1 4

Enter Burst Time and Period for P2: 2 5

Enter Burst Time and Period for P3: 1 10

Gantt Chart:
P1 P2 P2 P3 P1 P2 P2 Idle P1 Idle P2 P2 P1 P3 Idle P2 P1 P2 Idle Idle
Process returned 0 (0x0)   execution time : 18.158 s
Press any key to continue.
|

```

Proportional scheduling

```
#include <stdio.h>
```

```

struct Process {
int pid;   int share;
};

```

```

int main() {
int n, total = 0;

```

```

    printf("Enter number of processes: ");
    scanf("%d", &n);

```

```

struct Process p[n];

for(int i = 0; i < n; i++) {    printf("\nEnter
CPU share for P%d: ", i + 1);

    p[i].pid = i + 1;
scanf("%d", &p[i].share);

    total += p[i].share;
}

printf("\nCPU Allocation:\n");

for(int i = 0; i < n; i++) {

    float percent =
        ((float)p[i].share / total) * 100;

    printf("P%d -> %.2f%% CPU Time\n",
        p[i].pid,        percent);
}

return 0;
}

```

```
1bf24cs331
Enter number of processes: 3

Enter CPU share for P1: 2

Enter CPU share for P2: 3

Enter CPU share for P3: 5

CPU Allocation:
P1 -> 20.00% CPU Time
P2 -> 30.00% CPU Time
P3 -> 50.00% CPU Time

Process returned 0 (0x0)    execution time : 16.591 s
Press any key to continue.
|
```

PROGRAM-4

PRODUCER-CONSUMER PROBLEM USING SEMAPHORES

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define BUFFER_SIZE 5
```

```
int buffer[BUFFER_SIZE]; int
```

```
in = 0; int
```

```
out = 0;
```

```
int empty = BUFFER_SIZE; int
```

```
full = 0;
```

```

void produce() {    if
(empty == 0) {
    printf("\nBuffer is full! Cannot produce.\n");    return;
}

    int item;
    printf("Enter item to produce: ");    scanf("%d",
&item);

    buffer[in] = item;
    printf("Produced: %d at index %d\n", item, in);

    in = (in + 1) % BUFFER_SIZE;    empty--;
full++;
}

void consume() {
if (full == 0) {
    printf("\nBuffer is empty! Cannot consume.\n");    return;
}

    int item = buffer[out];
    printf("Consumed: %d from index %d\n", item, out);

    out = (out + 1) % BUFFER_SIZE;
full--;
    empty++;
}

int main() {    int choice;
printf("1BF24CS331\n");

```

```

printf("Buffer Size: %d\n", BUFFER_SIZE);

while (1) {
    printf("\n1. Produce\n2. Consume\n3. Exit\n");
    printf("Current State: [Full slots: %d | Empty slots: %d]\n", full, empty);
    printf("Enter choice: ");

    if (scanf("%d", &choice) != 1) break;

    switch (choice) {
        case 1:
            produce();
            break;
        case 2:
            consume();
            break;
        case 3:
            printf("Exiting...\n");
            exit(0);
        default:
            printf("Invalid choice!\n");
    }
}

return 0;
}

```

```
"C:\Users\Vanshika Malhotra\  ×  +  v
1BF24CS331
Buffer Size: 5

1. Produce
2. Consume
3. Exit
Current State: [Full slots: 0 | Empty slots: 5]
Enter choice: 1
Enter item to produce: 8
Produced: 8 at index 0

1. Produce
2. Consume
3. Exit
Current State: [Full slots: 1 | Empty slots: 4]
Enter choice: 1
Enter item to produce: 4
Produced: 4 at index 1

1. Produce
2. Consume
3. Exit
Current State: [Full slots: 2 | Empty slots: 3]
Enter choice: 2
Consumed: 8 from index 0

1. Produce
2. Consume
3. Exit
Current State: [Full slots: 1 | Empty slots: 4]
Enter choice: 3
Exiting...

Process returned 0 (0x0)   execution time : 34.207 s
Press any key to continue.
|
```

DINNING PHILOSOPHERS PROBLEM

```
#include<stdio.h>

#include<pthread.h>

#include<unistd.h>

#define N 5 // Number of philosophers

pthread_mutex_t forks[N]; // One mutex per fork

pthread_t philosophers[N]; void*

philosopher(void* num)

{

int id = *(int*)num; int left = id; // left

fork index  int right = (id + 1) % N; //

right fork index  while (1) {

printf("Philosopher %d is thinking.\n", id);
```

```

sleep(1); // Thinking
// To avoid deadlock, philosophers with even id pick left then right, // odd
id pick right then left.
if (id % 2 == 0)
{
// Pick up left fork pthread_mutex_lock(&forks[left]);
printf("Philosopher %d picked up left fork %d.\n", id, left);
// Pick up right fork

pthread_mutex_lock(&forks[right]);
printf("Philosopher %d picked up right fork %d.\n", id, right); } else
{ // Pick up right fork pthread_mutex_lock(&forks[right]);
printf("Philosopher %d picked up right fork %d.\n", id, right); // Pick up left fork
pthread_mutex_lock(&forks[left]);
printf("Philosopher %d picked up left fork %d.\n", id, left);
} //
Eating printf("Philosopher %d is eating.\n", id);
sleep(2);
// Put down forks
pthread_mutex_unlock(&forks[left]); pthread_mutex_unlock(&forks[right]);
printf("Philosopher %d put down forks %d and %d.\n", id, left, right);
} return
NULL;
}

int main() { int
i;

int ids[N]; // Initialize forks (mutexes) for (i
= 0; i < N; i++)
{ pthread_mutex_init(&forks[i], NULL);
ids[i] = i;
}

```

```

// Create philosopher threads for
(i = 0; i < N; i++)
{
pthread_create(&philosophers[i], NULL, philosopher, &ids[i]);
} // Join threads (will never happen here, but good practice) for
(i = 0; i < N; i++)
{
pthread_join(philosophers[i], NULL); } //
Destroy mutexes (unreachable here) for (i
= 0; i < N; i++)
{
pthread_mutex_destroy(&forks[i]);
} return
0;
}

```


1BF24CS331

```
Produced: 0 at buffer[0]
Consumed: 0 from buffer[0]
Produced: 1 at buffer[1]
Produced: 2 at buffer[2]
Consumed: 1 from buffer[1]
Produced: 3 at buffer[3]
Consumed: 2 from buffer[2]
Produced: 4 at buffer[4]
Produced: 5 at buffer[0]
Consumed: 3 from buffer[3]
Produced: 6 at buffer[1]
Produced: 7 at buffer[2]
Consumed: 4 from buffer[4]
Produced: 8 at buffer[3]
Produced: 9 at buffer[4]
Consumed: 5 from buffer[0]
Produced: 10 at buffer[0]
Consumed: 6 from buffer[1]
Produced: 11 at buffer[1]
Consumed: 7 from buffer[2]
Produced: 12 at buffer[2]
Consumed: 8 from buffer[3]
Produced: 13 at buffer[3]
Consumed: 9 from buffer[4]
Produced: 14 at buffer[4]
Consumed: 10 from buffer[0]
Produced: 15 at buffer[0]
Consumed: 11 from buffer[1]
Produced: 16 at buffer[1]
Consumed: 12 from buffer[2]
Produced: 17 at buffer[2]
Consumed: 13 from buffer[3]
Produced: 18 at buffer[3]
```

PROGRAM-5

BANKER'S ALGORITHM

```
#include<stdio.h>
```

```
int main() {
    int allocation[10][10], max[10][10], need[10][10];
    int available[10], finish[10], safeSequence[10];    int
    i, j, k, p, r, count = 0;

    printf("1BF24CS331\n");

    printf("Enter number of processes: ");    scanf("%d",
    &p);

    printf("Enter number of resources: ");    scanf("%d",
    &r);

    printf("Enter Allocation Matrix:\n");
    for(i = 0; i < p; i++)    {        for(j =
    0; j < r; j++)
        {
            scanf("%d", &allocation[i][j]);
        }
    }

    printf("Enter Maximum Demand Matrix:\n");
    for(i = 0; i < p; i++)    {        for(j = 0; j < r;
    j++)    {            scanf("%d", &max[i][j]);
        }
    }

    printf("Enter Available Resources:\n");    for(i
    = 0; i < r; i++)
    {
```

```

        scanf("%d", &available[i]);
    }

    // Calculate Need Matrix
    for(i = 0; i < p; i++)    {
    for(j = 0; j < r; j++)
        {
            need[i][j] = max[i][j] - allocation[i][j];
        }
    }

    // Initialize finish array    for(i
= 0; i < p; i++)
    {        finish[i]
= 0;
    }

    while(count < p)
    {        int found
= 0;

        for(i = 0; i < p; i++)
        {            if(finish[i]
== 0)        {
for(j = 0; j < r; j++)
        {
            if(need[i][j] > available[j])
            {                break;
            }
        }
    }        if(j
== r)

```

```

{
    for(k = 0; k < r;
k++)
    {
        available[k] += allocation[i][k];
    }

    safeSequence[count] = i;
count++;
    finish[i] = 1;
    found
= 1;
    }
}
}

if(found == 0)
{
    printf("\nSystem is not in a safe state.\n");
    return
0;
}
}

printf("\nSystem is in a safe state.\n");
printf("Safe
sequence is: ");

for(i = 0; i < p; i++)
{
    printf("P%d", safeSequence[i]);
    if(i != p - 1)
    {
        printf(" -> ");
    }
}
}

```

```

return 0;
}

```

```

1BF24CS331
Enter number of processes: 5
Enter number of resources: 3
Enter Allocation Matrix:
0 1 0
2 0 0
3 0 2
2 1 1
0 0 2
Enter Maximum Demand Matrix:
7 5 3
3 2 2
9 0 2
2 2 2
4 3 3
Enter Available Resources:
3 3 2

System is in a safe state.
Safe sequence is: P1 -> P3 -> P4 -> P0 -> P2
Process returned 0 (0x0)   execution time : 58.771 s
Press any key to continue.
|

```

DEADLOCK DETECTION:

```
#include<stdio.h>
```

```

int main() {
    int allocation[10][10], request[10][10];
    int available[10];   int finish[10], safeSequence[10];
    int i, j, k, p, r, count
    = 0;
    printf("USN-1BF24CS331\n");

    printf("Enter the number of processes: ");   scanf("%d",
    &p);

    printf("Enter the number of resources: ");   scanf("%d",
    &r);

```

```

    // Allocation Matrix    printf("Enter the
allocation matrix:\n");    for(i = 0; i < p;
i++)
    {        printf("Process %d:
", i);

        for(j = 0; j < r; j++)
        {
            scanf("%d", &allocation[i][j]);
        }
    }

    // Request Matrix    printf("Enter the
request matrix:\n");    for(i = 0; i < p;
i++)
    {
        printf("Process %d: ", i);

        for(j = 0; j < r; j++)
        {
            scanf("%d", &request[i][j]);
        }
    }

    // Available Resources    printf("Enter the
available resources: ");    for(i = 0; i < r;
i++)
    {
        scanf("%d", &available[i]);
    }

```

```

    // Initialize finish array    for(i
= 0; i < p; i++)
    {
        finish[i]
= 0;
    }

    while(count < p)
    {
        int found
= 0;

        for(i = 0; i < p; i++)
        {
            if(finish[i] == 0)
            {
                for(j = 0; j
< r; j++)
                {
                    if(request[i][j] > available[j])
                    {
                        break;
                    }
                }
                if(j == r)
                {
                    for(k = 0; k < r; k++)
                    {
                        available[k] += allocation[i][k];
                    }

                    safeSequence[count++] = i;
                    finish[i]
= 1;
                    found = 1;
                }
            }
        }

        if(found == 0)

```

```

        {           break;
        }
    }

    if(count == p)
    {
        printf("\nSystem is in safe state.\n");    printf("Safe
Sequence is: ");

        for(i = 0; i < p; i++)
        {
            printf("P%d ", safeSequence[i]);
        }
    } else
    {
        printf("\nDeadlock detected in the system.\n");
    }

    return 0;
}

```



```
"C:\Users\Vanshika Malhotra\ X + v
USN-1BF24CS331
Enter the number of processes: 5
Enter the number of resources: 3
Enter the allocation matrix:
Process 0: 0 1 0
Process 1: 2 0 0
Process 2: 3 0 3
Process 3: 2 1 1
Process 4: 0 0 2
Enter the request matrix:
Process 0: 0 0 0
Process 1: 2 0 2
Process 2: 0 0 0
Process 3: 1 0 0
Process 4: 0 0 2
Enter the available resources: 0 0 0

System is in safe state.
Safe Sequence is: P0 P2 P3 P4 P1
Process returned 0 (0x0) execution time : 46.257 s
Press any key to continue.
|
```

PROGRAM-6

FIRST FIT, BEST FIT, WORST FIT

```
#include <stdio.h>
```

```
void firstFit(int blockSize[], int blocks, int processSize[], int processes) {
int allocation[processes];
```

```
    for (int i = 0; i < processes; i++)
allocation[i] = -1;
```

```
    int used[blocks];    for (int i =
0; i < blocks; i++)    used[i] =
0;
```

```

    for (int i = 0; i < processes; i++) {
for (int j = 0; j < blocks; j++) {

    // block must be unused
    if (!used[j] && blockSize[j] >= processSize[i]) {
allocation[i] = j;
        used[j] = 1; // mark block as used
break;
    }
}
}

printf("\n--- First Fit ---\n");
printf("Process No.\tProcess Size\tBlock No.\n");

    for (int i = 0; i < processes; i++) {
printf("%d\t%d\t", i + 1, processSize[i]);

        if (allocation[i] != -1)
printf("%d\n", allocation[i] + 1);
        else
            printf("Not
Allocated\n");
    }
}

void bestFit(int blockSize[], int blocks, int processSize[], int processes) {
int allocation[processes];

    for (int i = 0; i < processes; i++)
allocation[i] = -1;

```

```

    int used[blocks];    for (int i =
0; i < blocks; i++)      used[i] =
0;

    for (int i = 0; i < processes; i++) {
int bestIdx = -1;

        for (int j = 0; j < blocks; j++) {

            if (!used[j] && blockSize[j] >= processSize[i]) {

                if (bestIdx == -1 || blockSize[j] < blockSize[bestIdx]) {
bestIdx = j;
                }
            }
        }

        if (bestIdx != -1) {
allocation[i] = bestIdx;      used[bestIdx]
= 1;
        }
    }

    printf("\n--- Best Fit ---\n");
    printf("Process No.\tProcess Size\tBlock No.\n");

    for (int i = 0; i < processes; i++) {
printf("%d\t%d\t", i + 1, processSize[i]);

        if (allocation[i] != -1)
printf("%d\n", allocation[i] + 1);      else
            printf("Not Allocated\n");
    }

```

```

    }
}

```

```

void worstFit(int blockSize[], int blocks, int processSize[], int processes) {
int allocation[processes];

```

```

    for (int i = 0; i < processes; i++)
allocation[i] = -1;

```

```

    int used[blocks];    for (int i =
0; i < blocks; i++)    used[i] =
0;

```

```

    for (int i = 0; i < processes; i++) {
int worstIdx = -1;

```

```

        for (int j = 0; j < blocks; j++) {

```

```

            if (!used[j] && blockSize[j] >= processSize[i]) {

```

```

                if (worstIdx == -1 || blockSize[j] > blockSize[worstIdx]) {
worstIdx = j;
                }
            }
        }
    }

```

```

        if (worstIdx != -1) {
allocation[i] = worstIdx;        used[worstIdx]
= 1;
        }
    }
}

```

```

    printf("\n--- Worst Fit ---\n");    printf("Process
No.\tProcess Size\tBlock No.\n");

    for (int i = 0; i < processes; i++) {    printf("%d\t\t%d\t\t",
i + 1, processSize[i]);

        if (allocation[i] != -1)
printf("%d\n", allocation[i] + 1);    else
        printf("Not Allocated\n");
    }
}

int main() {    int blocks, processes;
printf("1BF24CS331\n");

    printf("Enter number of memory blocks: ");    scanf("%d",
&blocks);

    int blockSize[blocks];

    printf("Enter sizes of memory blocks:\n");    for
(int i = 0; i < blocks; i++) {    scanf("%d",
&blockSize[i]);
    }

    printf("Enter number of processes: ");    scanf("%d",
&processes);

    int processSize[processes];

```

```
    printf("Enter sizes of processes:\n");
    for (int i = 0; i < processes; i++) {
        scanf("%d", &processSize[i]);
    }

    firstFit(blockSize, blocks, processSize, processes);
    bestFit(blockSize, blocks, processSize, processes);    worstFit(blockSize,
    blocks, processSize, processes);

    return 0;
}
```

```

1BF24CS331
Enter number of memory blocks: 5
Enter sizes of memory blocks:
100 500 200 300 600
Enter number of processes: 4
Enter sizes of processes:
212 417 112 426

--- First Fit ---
Process No.      Process Size      Block No.
1                212                2
2                417                5
3                112                3
4                426                Not Allocated

--- Best Fit ---
Process No.      Process Size      Block No.
1                212                4
2                417                2
3                112                3
4                426                5

--- Worst Fit ---
Process No.      Process Size      Block No.
1                212                5
2                417                2
3                112                4
4                426                Not Allocated

Process returned 0 (0x0)   execution time : 25.289 s
Press any key to continue.
|

```

PROGRAM-7

Write a C program to simulate page replacement algorithms. a) FIFO b) LRU

c) Optimal

```
#include <stdio.h>
```

```
#define MAX 50
```

```
// Function to check if page exists in frames
int isPresent(int frames[], int num_frames, int page) {
    for (int i = 0; i <
```

```

num_frames; i++)    {    if (frames[i] == page)
return 1;    }    return 0;
}

// Function to print frames void printFrames(int frames[],
int num_frames)
{    printf("[");    for (int i = 0; i < num_frames;
i++)
    {    if (frames[i] != -1)
printf("%d", frames[i]);    else
printf(" ");

        if (i != num_frames - 1)
printf(" ");    }
printf("]\n");
}

// ----- FIFO ----- void
FIFO(int pages[], int n, int num_frames)
{    int
frames[MAX];    int
page_faults = 0;    int
next = 0;

    for (int i = 0; i < num_frames; i++)    frames[i]
= -1;

    printf("\n--- FIFO Page Replacement ---\n\n");

    for (int i = 0; i < n; i++)
    {    int page =
pages[i];

```



```

        if (!isPresent(frames, num_frames, page))
        {
            frames[next] = page;        next =
(next + 1) % num_frames;
page_faults++;
        }

        printf("Page %d -> ", page);    printFrames(frames,
num_frames);
    }

    printf("\nTotal Page Faults (FIFO): %d\n", page_faults);
}

// ----- LRU ----- void
LRU(int pages[], int n, int num_frames)
{    int frames[MAX];    int
last_used[MAX];    int page_faults = 0;

    for (int i = 0; i < num_frames; i++)
    {        frames[i] = 1;
last_used[i] =
-1;
    }

    printf("\n--- LRU Page Replacement ---\n\n");

    for (int i = 0; i < n; i++)
    {        int page = pages[i];
int found
= 0;

```

```

        // Check if page exists      for (int j
= 0; j < num_frames; j++)
    {      if (frames[j]
== page)
        {      found
= 1;      last_used[j]
= i;      break;
        }
    }

    // Page Fault      if
(!found)    {
int pos = -1;

        // Empty frame available      for
(int j = 0; j < num_frames; j++)
    {      if
(frames[j] == -1)    {      pos
= j;      break;
        }
    }

    // Replace least recently used      if
(pos == -1)
    {
        int min = last_used[0];      pos
= 0;

        for (int j = 1; j < num_frames; j++)
        {
            if (last_used[j] < min)

```

```

        {
            min = last_used[j];
pos = j;
        }
    }
}

frames[pos] = page;
last_used[pos] = i;    page_faults++;
}

printf("Page %d -> ", page);    printFrames(frames,
num_frames);
}

printf("\nTotal Page Faults (LRU): %d\n", page_faults); }

// ----- Optimal ----- void
Optimal(int pages[], int n, int num_frames)
{    int
frames[MAX];    int page_faults
= 0;

    for (int i = 0; i < num_frames; i++)    frames[i]
= -1;

    printf("\n--- Optimal Page Replacement ---\n\n");

    for (int i = 0; i < n; i++)
{        int page = pages[i];

        if (!isPresent(frames, num_frames, page))

```

```

        {            int pos
= -1;

        // Empty frame        for (int j =
0; j < num_frames; j++)
        {            if
(frames[j] == -1)
        {
pos = j;            break;
        }
        }

        // Find optimal replacement
if (pos == -1)
{            int farthest = -
1;

        for (int j = 0; j < num_frames; j++)
        {            int k;            for
(k = i + 1; k < n; k++)
        {
            if (frames[j] == pages[k])                break;
        }

        // Page never used again
if (k == n)            {            pos
= j;            break;
        }

        // Farthest use
if (k > farthest)

```

```

{
    farthest = k;
pos = j;
    }
    }
}

frames[pos] = page;    page_faults++;
}

printf("Page %d -> ", page);    printFrames(frames,
num_frames);
}

printf("\nTotal Page Faults (Optimal): %d\n", page_faults);
}

// ----- Main ----- int
main() {    int n, num_frames;    int
pages[MAX];
printf("1BF24CS331");

    printf("Enter number of pages: ");    scanf("%d",
&n);

    printf("Enter page reference string:\n");    for
(int i = 0; i < n; i++)    scanf("%d",
&pages[i]);

    printf("Enter number of frames: ");    scanf("%d",
&num_frames);

    FIFO(pages, n, num_frames);

```

```
    LRU(pages, n, num_frames);  
    Optimal(pages, n, num_frames);  
  
    return 0;  
}
```

```
"C:\Users\Vanshika Malhotra\ × + v
1BF24CS331Enter number of pages: 12
Enter page reference string:
7 0 1 2 0 3 0 4 2 3 0 3
Enter number of frames: 3

--- FIFO Page Replacement ---

Page 7 -> [7    ]
Page 0 -> [7 0  ]
Page 1 -> [7 0 1]
Page 2 -> [2 0 1]
Page 0 -> [2 0 1]
Page 3 -> [2 3 1]
Page 0 -> [2 3 0]
Page 4 -> [4 3 0]
Page 2 -> [4 2 0]
Page 3 -> [4 2 3]
Page 0 -> [0 2 3]
Page 3 -> [0 2 3]

Total Page Faults (FIFO): 10

--- LRU Page Replacement ---

Page 7 -> [7    ]
Page 0 -> [7 0  ]
Page 1 -> [7 0 1]
Page 2 -> [2 0 1]
Page 0 -> [2 0 1]
Page 3 -> [2 0 3]
Page 0 -> [2 0 3]
Page 4 -> [4 0 3]
Page 2 -> [4 0 2]
Page 3 -> [4 3 2]
Page 0 -> [0 3 2]
Page 3 -> [0 3 2]

Total Page Faults (LRU): 9

--- Optimal Page Replacement ---

Page 7 -> [7    ]
Page 0 -> [7 0  ]
Page 1 -> [7 0 1]
```