



University Institute of Engineering
Department of Computer Science & Engineering

EXPERIMENT:3

NAME : VANSK KUMAR
BRANCH : BE-CSE
SEMESTER : 5TH
SUBJECT NAME : ADBMS

UID : 23BCS10117
SECTION : KRG_1A
SUBJECT : 23CSP-339

1. AIM:-

[EASY]

You are given an EMP table that contains a list of employee IDs (EMP_ID). Some employee IDs may appear multiple times, representing duplicate entries.

Write an SQL query (using **subqueries**) to:

- Identify and exclude all employee IDs that appear more than once in the table.
- From the remaining unique employee IDs, find the **highest employee ID**.

Return the result as a single column named single_highest.

[MEDIUM]

Given tables:

- department(id, dept_name)
- employee(id, name, salary, department_id)

Write a SQL query to retrieve employees with the **highest salary in each department**, displaying their name, salary, and department name, sorted by department name.

[HARD]

Given tables:

- TABLE1(EMPID, Ename, Salary)
- TABLE2(EMPID, Ename, Salary)

Write a SQL query to combine the records from both tables, and for each EMPID, select the employee name and salary with the **minimum values**. The result should display one row per EMPID.

2.TOOLS USED :-

SQL server management studio.

3.CODE:-

--EASY--

```
use subqueries
CREATE TABLE EMP(
EMP_ID INT
)
INSERT INTO EMP (EMP_ID)
VALUES (2), (4), (4), (6), (6), (7), (8), (8);
```

--SELECT *FROM EMP;

```
SELECT MAX(EMP_ID) AS [single_highest]FROM EMP
WHERE EMP_ID NOT IN(
SELECT EMP_ID FROM EMP
GROUP BY EMP_ID
HAVING COUNT(EMP_ID)>1
```

--MEDIUM--

```
CREATE TABLE department (
    id INT PRIMARY KEY,
    dept_name VARCHAR(50)
);
```

-- Create Employee Table

```
CREATE TABLE employee (
    id INT,
    name VARCHAR(50),
    salary INT,
    department_id INT,
    FOREIGN KEY (department_id) REFERENCES department(id)
);
```

-- Insert into Department Table

```
INSERT INTO department (id, dept_name) VALUES
(1, 'IT'),
(2, 'SALES');
```

-- Insert into Employee Table

```
INSERT INTO employee (id, name, salary, department_id) VALUES
(1, 'JOE', 70000, 1),
(2, 'JIM', 90000, 1),
(3, 'HENRY', 80000, 2),
(4, 'SAM', 60000, 2),
(5, 'MAX', 90000, 1);
```

```
SELECT E.name,E.salary,D.dept_name
FROM employee AS E
LEFT JOIN
department as D
On
E.department_id=D.id
```

```

WHERE E.salary IN
(
    SELECT MAX(E2.SALARY)
    FROM employee as E2
    WHERE E2.department_id =E.department_id
)
ORDER BY D.dept_name

```

--HARD--

```

CREATE TABLE TABLE1 (
    EMPID INT,
    Ename VARCHAR(20),
    Salary INT
)
CREATE TABLE TABLE2 (
    EMPID INT,
    Ename VARCHAR(20),
    Salary INT
)

```

```

INSERT INTO TABLE1 (EMPID,Ename,Salary) VALUES
(1, 'AA',1000),
(2, 'BB',300);

```

```

INSERT INTO TABLE2 (EMPID,Ename,Salary) VALUES
(2, 'BB',400),
(3, 'CC',100);

```

```

SELECT EMPID,min(Ename) as Ename,MIN(Salary) as Salary
FROM
(
    SELECT *FROM TABLE1
    UNION
    SELECT *FROM TABLE2
) AS RES
GROUP BY EMPID

```

4.OUTPUT:- [EASY]

100 %	✓ No issues found
Results	Messages
	single_highest
1	7

[MEDIUM]

Results		Messages	
	name	salary	dept_name
1	MAX	90000	IT
2	JIM	90000	IT
3	HENRY	80000	SALES

[HARD]

Results		Messages	
	EMPID	Ename	Salary
1	1	AA	1000
2	2	BB	300
3	3	CC	100

5. LEARNING OUTCOMES:-

- 1.Learned to create tables and insert data in SQL.
- 2.Practiced using subqueries to filter and aggregate data.
- 3.Gained experience with JOINS to combine related tables.
- 4.Learned to handle duplicates and consolidate data using UNION and aggregation.
- 5.Developed problem-solving skills for retrieving specific information from databases.