

DUA Charitable Trust

Next.js Website - Source Code Compilation

Generated on: July 02, 2026

Total Files Compiled: 125

Format: PDF Document Archive

Table of Contents

01. src/animations/imageTransitions.ts
02. src/animations/masterTimeline.ts
03. src/animations/presets.ts
04. src/animations/textTransitions.ts
05. src/app/about-us/page.tsx
06. src/app/blog/[slug]/page.tsx
07. src/app/blog/page.tsx
08. src/app/contact/page.tsx
09. src/app/donate/page.tsx
10. src/app/error.tsx
11. src/app/globals.css
12. src/app/layout.tsx
13. src/app/loading.tsx
14. src/app/not-found.tsx
15. src/app/our-projects/[slug]/page.tsx
16. src/app/our-projects/page.tsx
17. src/app/page.tsx
18. src/app/showcase/layout.tsx
19. src/app/showcase/page.tsx
20. src/app/template.tsx
21. src/components/providers/AppProviders.tsx
22. src/components/providers/LenisProvider.tsx
23. src/components/providers/MotionProvider.tsx
24. src/components/providers/ThemeProvider.tsx
25. src/components/sections/CTA.tsx
26. src/components/sections/ContactForm.tsx
27. src/components/sections/DynamicStickyScroll.tsx
28. src/components/sections/FAQ.tsx
29. src/components/sections/FeaturedProjects.tsx
30. src/components/sections/Hero.tsx
31. src/components/sections/ImpactStats.tsx
32. src/components/sections/Mission.tsx
33. src/components/sections/MobileNavDrawer.tsx
34. src/components/sections/NavLink.tsx
35. src/components/sections/Navbar.tsx
36. src/components/sections/Newsletter.tsx
37. src/components/sections/SeedsOfChange.tsx

- 38. src/components/sections/TeamGrid.tsx
- 39. src/components/sections/Testimonials.tsx
- 40. src/components/storytelling/AnimatedHeading.tsx
- 41. src/components/storytelling/AnimatedSection.tsx
- 42. src/components/storytelling/ImageExpansionStory.tsx
- 43. src/components/storytelling/ParallaxImage.tsx
- 44. src/components/storytelling/RevealImage.tsx
- 45. src/components/storytelling/RevealText.tsx
- 46. src/components/storytelling/ScrollReveal.tsx
- 47. src/components/storytelling/SectionWrapper.tsx
- 48. src/components/storytelling/StoryScroller/AnimatedHeading.tsx
- 49. src/components/storytelling/StoryScroller/StoryBackground.tsx
- 50. src/components/storytelling/StoryScroller/StoryContent.tsx
- 51. src/components/storytelling/StoryScroller/StoryControls.tsx
- 52. src/components/storytelling/StoryScroller/StoryImage.tsx
- 53. src/components/storytelling/StoryScroller/StoryNavigation.tsx
- 54. src/components/storytelling/StoryScroller/StoryProgress.tsx
- 55. src/components/storytelling/StoryScroller/index.tsx
- 56. src/components/ui/AnimatedButton.tsx
- 57. src/components/ui/AnimatedCard.tsx
- 58. src/components/ui/AnimatedCounter.tsx
- 59. src/components/ui/BackgroundPattern.tsx
- 60. src/components/ui/Badge.tsx
- 61. src/components/ui/BeforeAfter.tsx
- 62. src/components/ui/BlogCard.tsx
- 63. src/components/ui/BlurReveal.tsx
- 64. src/components/ui/Button.tsx
- 65. src/components/ui/Container.tsx
- 66. src/components/ui/DonationWidget.tsx
- 67. src/components/ui/FAQAccordion.tsx
- 68. src/components/ui/FloatingButton.tsx
- 69. src/components/ui/Gallery.tsx
- 70. src/components/ui/GlassCard.tsx
- 71. src/components/ui/GradientHeading.tsx
- 72. src/components/ui/ImageReveal.tsx
- 73. src/components/ui/ImageSlider.tsx
- 74. src/components/ui/ImpactCounter.tsx
- 75. src/components/ui/Input.tsx
- 76. src/components/ui/Loader.tsx
- 77. src/components/ui/Magnetic.tsx

- 78. src/components/ui/Parallax.tsx
- 79. src/components/ui/ProjectCard.tsx
- 80. src/components/ui/Section.tsx
- 81. src/components/ui/SectionDivider.tsx
- 82. src/components/ui/SectionHeading.tsx
- 83. src/components/ui/Skeleton.tsx
- 84. src/components/ui/SocialIcons.tsx
- 85. src/components/ui/StatItem.tsx
- 86. src/components/ui/StickyScrollSection.tsx
- 87. src/components/ui/TestimonialSlider.tsx
- 88. src/components/ui/TextReveal.tsx
- 89. src/components/ui/ThemeToggle.tsx
- 90. src/components/ui/TiltCard.tsx
- 91. src/components/ui/Timeline.tsx
- 92. src/components/ui/index.ts
- 93. src/components/ui/styles.ts
- 94. src/constants/data.ts
- 95. src/constants/navigation.ts
- 96. src/constants/seedsOfChange.ts
- 97. src/constants/site.ts
- 98. src/constants/storyData.ts
- 99. src/context/StoryContext.tsx
- 100. src/hooks/useActiveSection.ts
- 101. src/hooks/useActiveStory.ts
- 102. src/hooks/useFocusTrap.ts
- 103. src/hooks/useGSAP.ts
- 104. src/hooks/useIntersectionObserver.ts
- 105. src/hooks/useIsomorphicLayoutEffect.ts
- 106. src/hooks/useLenis.ts
- 107. src/hooks/useReducedMotion.ts
- 108. src/hooks/useScrollDirection.ts
- 109. src/hooks/useScrollLock.ts
- 110. src/hooks/useScrollPosition.ts
- 111. src/hooks/useScrollProgress.ts
- 112. src/hooks/useWindowSize.ts
- 113. src/layouts/Footer.tsx
- 114. src/layouts/MainLayout.tsx
- 115. src/layouts/Navbar.tsx
- 116. src/types/index.ts
- 117. src/utils/cn.ts

118. src/utls/preloadImages.ts

119. src/utls/theme.ts

120. README.md

121. eslint.config.mjs

122. next.config.ts

123. package.json

124. postcss.config.mjs

125. tsconfig.json

1. src/animations/imageTransitions.ts

```
1 | import gsap from "gsap";
2 | import ScrollTrigger from "gsap/ScrollTrigger";
3 |
4 | export interface ImageTransitionOptions {
5 |   scrub?: boolean | number;
6 |   start?: string;
7 |   end?: string;
8 | }
9 |
10 | /**
11 |  * Creates a scroll-linked image reveal and exit timeline.
12 |  * 0% -> 40%: Enter (y: 160px -> 0, scale: 0.94 -> 1, blur: 10px -> 0px)
13 |  * 40% -> 60%: Focus/Stabilized normal state
14 |  * 60% -> 100%: Exit (y: 0 -> -120px, scale: 1 -> 1.03, blur: 0px -> 4px, opacity: 1 -> 0.35)
15 |  */
16 | export function applyImageTransition(
17 |   element: string | Element,
18 |   trigger: string | Element,
19 |   options: ImageTransitionOptions = {}
20 | ): gsap.core.Timeline {
21 |   gsap.registerPlugin(ScrollTrigger);
22 |
23 |   const tl = gsap.timeline({
24 |     scrollTrigger: {
25 |       trigger: trigger,
26 |       start: options.start || "top bottom",
27 |       end: options.end || "bottom top",
28 |       scrub: options.scrub !== undefined ? options.scrub : 1,
29 |     },
30 |   });
31 |
32 |   // Total duration normalized to 1
33 |   // 1) Enter Phase (0 to 0.4)
34 |   tl.fromTo(
35 |     element,
36 |     {
37 |       opacity: 0,
38 |       y: 160,
39 |       scale: 0.94,
40 |       filter: "blur(10px)",
41 |     },
42 |     {
43 |       opacity: 1,
44 |       y: 0,
45 |       scale: 1,
46 |       filter: "blur(0px)",
47 |       ease: "power2.out",
48 |       duration: 0.4,
49 |     }
50 |   );
51 |
52 |   // 2) Keep focus frame (0.4 to 0.6)
53 |   tl.to(element, {
54 |     duration: 0.2,
55 |   });
56 |
57 |   // 3) Exit Phase (0.6 to 1.0)
58 |   tl.to(element, {
59 |     y: -120,
60 |     opacity: 0.35,
61 |     scale: 1.03,
62 |     filter: "blur(4px)",
63 |     ease: "power2.in",
64 |     duration: 0.4,
65 |   });
66 |
67 |   return tl;
```

```
68 | }  
69 | export default applyImageTransition;  
70 |
```

2. src/animations/masterTimeline.ts

```
1 | import gsap from "gsap";
2 | import ScrollTrigger from "gsap/ScrollTrigger";
3 |
4 | export interface MasterTimelineOptions {
5 |   trigger: string | Element;
6 |   start?: string;
7 |   end?: string;
8 |   scrub?: boolean | number;
9 |   pin?: boolean | string | HTMLElement;
10 |   anticipatePin?: number;
11 |   onUpdate?: (self: ScrollTrigger) => void;
12 | }
13 |
14 | /**
15 |  * Creates a master timeline within a GSAP context wrapper
16 |  * to simplify initialization and clean unmounting.
17 |  */
18 | export function createMasterTimeline(
19 |   options: MasterTimelineOptions,
20 |   scope?: React.RefObject<Element | null> | string | Element
21 | ): { timeline: gsap.core.Timeline; ctx: gsap.Context } {
22 |   gsap.registerPlugin(ScrollTrigger);
23 |
24 |   const ctx = gsap.context(() => {}, scope || undefined);
25 |
26 |   const timeline = gsap.timeline({
27 |     scrollTrigger: {
28 |       trigger: options.trigger,
29 |       start: options.start || "top top",
30 |       end: options.end || "+=100%",
31 |       scrub: options.scrub !== undefined ? options.scrub : 1,
32 |       pin: options.pin,
33 |       anticipatePin: options.anticipatePin,
34 |       onUpdate: options.onUpdate,
35 |     },
36 |   });
37 |
38 |   return { timeline, ctx };
39 | }
40 | export default createMasterTimeline;
41 |
```


3. src/animations/presets.ts

```
1 | import { Variants } from "framer-motion";
2 |
3 | // Premium transition ease curves
4 | export const easeOutExpo = [0.16, 1, 0.3, 1];
5 |
6 | export const fadeUp = (delay = 0, duration = 0.6): Variants => ({
7 |   hidden: { opacity: 0, y: 30 },
8 |   visible: {
9 |     opacity: 1,
10 |     y: 0,
11 |     transition: { delay, duration, ease: easeOutExpo },
12 |   },
13 | });
14 |
15 | export const fadeDown = (delay = 0, duration = 0.6): Variants => ({
16 |   hidden: { opacity: 0, y: -30 },
17 |   visible: {
18 |     opacity: 1,
19 |     y: 0,
20 |     transition: { delay, duration, ease: easeOutExpo },
21 |   },
22 | });
23 |
24 | export const fadeLeft = (delay = 0, duration = 0.6): Variants => ({
25 |   hidden: { opacity: 0, x: 30 },
26 |   visible: {
27 |     opacity: 1,
28 |     x: 0,
29 |     transition: { delay, duration, ease: easeOutExpo },
30 |   },
31 | });
32 |
33 | export const fadeRight = (delay = 0, duration = 0.6): Variants => ({
34 |   hidden: { opacity: 0, x: -30 },
35 |   visible: {
36 |     opacity: 1,
37 |     x: 0,
38 |     transition: { delay, duration, ease: easeOutExpo },
39 |   },
40 | });
41 |
42 | export const scaleIn = (delay = 0, duration = 0.6): Variants => ({
43 |   hidden: { opacity: 0, scale: 0.95 },
44 |   visible: {
45 |     opacity: 1,
46 |     scale: 1,
47 |     transition: { delay, duration, ease: easeOutExpo },
48 |   },
49 | });
50 |
51 | export const rotateIn = (delay = 0, duration = 0.6): Variants => ({
52 |   hidden: { opacity: 0, rotate: -5, scale: 0.98 },
53 |   visible: {
54 |     opacity: 1,
55 |     rotate: 0,
56 |     scale: 1,
57 |     transition: { delay, duration, ease: easeOutExpo },
58 |   },
59 | });
60 |
```

4. src/animations/textTransitions.ts

```

1 | import gsap from "gsap";
2 | import ScrollTrigger from "gsap/ScrollTrigger";
3 |
4 | export interface TextTransitionOptions {
5 |   scrub?: boolean | number;
6 |   start?: string;
7 |   end?: string;
8 | }
9 |
10 | /**
11 |  * Applies scroll-linked text stagger reveals to heading words,
12 |  * paragraphs, and button components inside a container.
13 |  */
14 | export function applyTextTransition(
15 |   container: string | Element,
16 |   options: TextTransitionOptions = {}
17 | ): gsap.core.Timeline {
18 |   gsap.registerPlugin(ScrollTrigger);
19 |
20 |   const containerEl = typeof container === "string" ? document.querySelector(container) : container;
21 |   if (!containerEl) return gsap.timeline();
22 |
23 |   const tl = gsap.timeline({
24 |     scrollTrigger: {
25 |       trigger: containerEl,
26 |       start: options.start || "top 85%",
27 |       end: options.end || "bottom 20%",
28 |       scrub: options.scrub !== undefined ? options.scrub : 1,
29 |     },
30 |   });
31 |
32 |   // Stagger words in headings
33 |   const headingWords = containerEl.querySelectorAll(".story-heading-word");
34 |   if (headingWords.length > 0) {
35 |     tl.fromTo(
36 |       headingWords,
37 |       { y: "100%", opacity: 0 },
38 |       {
39 |         y: "0%",
40 |         opacity: 1,
41 |         stagger: 0.08,
42 |         ease: "power4.out",
43 |         duration: 0.6,
44 |       }
45 |     );
46 |   }
47 |
48 |   // Paragraph reveal
49 |   const paragraphs = containerEl.querySelectorAll(".story-paragraph");
50 |   if (paragraphs.length > 0) {
51 |     tl.fromTo(
52 |       paragraphs,
53 |       { y: 40, opacity: 0 },
54 |       {
55 |         y: 0,
56 |         opacity: 1,
57 |         ease: "power2.out",
58 |         duration: 0.5,
59 |       },
60 |       headingWords.length > 0 ? "-=0.35" : 0
61 |     );
62 |   }
63 |
64 |   // Action Buttons scale-up
65 |   const buttons = containerEl.querySelectorAll(".story-button");
66 |   if (buttons.length > 0) {
67 |     tl.fromTo(

```

```
68 | buttons,
69 | { scale: 0.95, opacity: 0 },
70 | {
71 |   scale: 1,
72 |   opacity: 1,
73 |   ease: "back.out(1.5)",
74 |   duration: 0.4,
75 | },
76 | "-=0.25"
77 | );
78 | }
79 |
80 | return tl;
81 | }
82 | export default applyTextTransition;
83 |
```

5. src/app/about-us/page.tsx

```
1 | import React from "react";
2 | import { Hero } from "@components/sections/Hero";
3 | import { Mission } from "@components/sections/Mission";
4 | import { TeamGrid } from "@components/sections/TeamGrid";
5 | import { FAQ } from "@components/sections/FAQ";
6 | import { CTA } from "@components/sections/CTA";
7 | import {
8 |   aboutHeroData,
9 |   aboutStoryData,
10 |   coreValuesData,
11 |   teamMembers,
12 |   FAQData,
13 |   ctaData,
14 | } from "@constants/data";
15 |
16 | export default function AboutUs(): React.ReactNode {
17 |   return (
18 |     <div className="pt-16">
19 |       <Hero
20 |         heading={aboutHeroData.heading}
21 |         subheading={aboutHeroData.subheading}
22 |         primaryCtaText=""
23 |         primaryCtaLink=""
24 |         secondaryCtaText=""
25 |         secondaryCtaLink=""
26 |       />
27 |
28 |       <Mission
29 |         title={aboutStoryData.title}
30 |         description=""
31 |         bullets={[]}
32 |       />
33 |
34 |       <TeamGrid
35 |         title={coreValuesData.title}
36 |         subtitle=""
37 |         members={teamMembers}
38 |       />
39 |
40 |       <FAQ
41 |         title="About Our Operations"
42 |         subtitle="Learn about our legal status, funding streams, volunteer guides, and local coordination."
43 |         faqs={FAQData}
44 |       />
45 |
46 |       <CTA
47 |         title={ctaData.title}
48 |         description={ctaData.description}
49 |         primaryCtaText={ctaData.primaryCtaText}
50 |         primaryCtaLink={ctaData.primaryCtaLink}
51 |         secondaryCtaText={ctaData.secondaryCtaText}
52 |         secondaryCtaLink={ctaData.secondaryCtaLink}
53 |       />
54 |     </div>
55 |   );
56 | }
57 |
```

6. src/app/blog/[slug]/page.tsx

```

1 | import React from "react";
2 | import Image from "next/image";
3 | import Link from "next/link";
4 | import { notFound } from "next/navigation";
5 | import { blogData } from "@/constants/data";
6 | import { Container } from "@/components/ui/Container";
7 | import { Badge } from "@/components/ui/Badge";
8 | import { Newsletter } from "@/components/sections/Newsletter";
9 | import { ArrowLeft, Calendar, Clock } from "lucide-react";
10 |
11 | interface BlogPostDetailProps {
12 |   params: {
13 |     slug: string;
14 |   };
15 | }
16 |
17 | export function generateStaticParams(): { slug: string }[] {
18 |   return blogData.map((post) => ({
19 |     slug: post.slug,
20 |   }));
21 | }
22 |
23 | export default function BlogPostDetail({ params }: BlogPostDetailProps): React.ReactNode {
24 |   const post = blogData.find((p) => p.slug === params.slug);
25 |
26 |   if (!post) {
27 |     notFound();
28 |   }
29 |
30 |   return (
31 |     <div className="pt-24 sm:pt-28 bg-cream min-h-screen">
32 |       <Container className="py-6">
33 |         <Link
34 |           href="/blog"
35 |           className="inline-flex items-center gap-2 text-sm font-semibold text-forest hover:text-forest/85
36 |           transition-colors focus:outline-none"
37 |         >
38 |           <ArrowLeft size={16} />
39 |           Back to Eco-Digest
40 |         </Link>
41 |       </Container>
42 |
43 |       <section className="pb-8">
44 |         <Container>
45 |           <div className="relative h-[250px] sm:h-[400px] w-full rounded-3xl overflow-hidden shadow-xs border
46 |             border-forest/10">
47 |             <Image src={post.image} alt={post.title} fill className="object-cover" sizes="100vw" priority />
48 |           </div>
49 |         </Container>
50 |       </section>
51 |
52 |       <section className="pb-20">
53 |         <Container>
54 |           <div className="max-w-3xl mx-auto">
55 |             <div className="flex flex-wrap items-center gap-4 mb-4 text-xs sm:text-sm text-charcoal/50 font-medium">
56 |               <Badge label={post.category} variant="info" />
57 |               <span className="flex items-center gap-1">
58 |                 <Calendar size={14} />
59 |                 {post.date}
60 |               </span>
61 |               <span className="flex items-center gap-1">
62 |                 <Clock size={14} />
63 |                 {post.readingTime}
64 |               </span>
65 |             </div>
66 |             <h1 className="text-3xl sm:text-4xl md:text-5xl font-extrabold text-charcoal font-heading leading-tight mb-8">

```

```
66 | {post.title}
67 | </h1>
68 |
69 | <div className="flex items-center gap-3.5 pb-8 mb-8 border-b border-forest/10">
70 | <div className="relative h-12 w-12 rounded-full overflow-hidden shrink-0 border border-forest/10">
71 | <Image src={post.author.avatar} alt={post.author.name} fill className="object-cover" sizes="48px" />
72 | </div>
73 | <div className="flex flex-col min-w-0">
74 | <span className="text-sm font-bold text-charcoal truncate">{post.author.name}</span>
75 | <span className="text-xs text-charcoal/50 truncate font-heading">{post.author.role}</span>
76 | </div>
77 | </div>
78 |
79 | <article className="prose max-w-none text-charcoal/80 font-body leading-relaxed text-base sm:text-lg
whitespace-pre-line">
80 | {post.content || post.excerpt}
81 | </article>
82 |
83 | {post.tags && post.tags.length > 0 && (
84 | <div className="flex flex-wrap gap-2.5 mt-10 pt-8 border-t border-forest/10">
85 | {post.tags.map((tag, idx) => (
86 | <Badge key={idx} label={`#${tag}`} variant="default" className="text-[10px]" />
87 | ))}
88 | </div>
89 | )}
90 | </div>
91 | </Container>
92 | </section>
93 |
94 | <Newsletter
95 | title="Stay Nurtured with Eco-Digest"
96 | subtitle="Subscribe to receive our monthly reviews, organic farming guides, and restoration volunteer callouts."
97 | />
98 | </div>
99 | );
100 | }
101 |
```

7. src/app/blog/page.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import { Container } from "@components/ui/Container";
5 | import { BlogCard } from "@components/ui/BlogCard";
6 | import { BackgroundPattern } from "@components/ui/BackgroundPattern";
7 | import { blogData } from "@constants/data";
8 |
9 | export default function Blog(): React.ReactNode {
10 |   const [email, setEmail] = useState("");
11 |   const [subscribed, setSubscribed] = useState(false);
12 |
13 |   const handleSubscribe = (e: React.FormEvent) => {
14 |     e.preventDefault();
15 |     if (!email) return;
16 |     setSubscribed(true);
17 |     setEmail("");
18 |   };
19 |
20 |   return (
21 |     <div className="pt-24 sm:pt-28 bg-cream min-h-screen pb-20 animate-fade-in">
22 |       {/* Header Section */}
23 |       <section className="py-16 sm:py-20 border-b border-forest/5 text-center relative overflow-hidden">
24 |         {/* Dot pattern background */}
25 |         <div className="absolute inset-0 opacity-[0.03] pointer-events-none
bg-[radial-gradient(#1b221e_1px,transparent_1px)] [background-size:16px_16px]" />
26 |
27 |         <Container className="relative z-10">
28 |           <div className="max-w-3xl mx-auto flex flex-col items-center">
29 |             <h1 className="text-4xl sm:text-5xl font-extrabold text-charcoal font-heading leading-tight mb-4">
30 |               Our Community Blog
31 |             </h1>
32 |             <p className="text-base sm:text-lg text-charcoal/70 leading-relaxed font-body">
33 |               Stories of impact, educational insights, and updates from the Dua Charitable Trust. Join us in making education a
joyful adventure for all.
34 |             </p>
35 |           </div>
36 |         </Container>
37 |       </section>
38 |
39 |       {/* Blog Cards Grid Section */}
40 |       <Container className="mt-16">
41 |         <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-8">
42 |           {blogData.slice(0, 3).map((post) => (
43 |             <BlogCard key={post.slug} post={post} />
44 |           ))}
45 |         </div>
46 |
47 |         {/* Load More Button */}
48 |         <div className="flex justify-center mt-12">
49 |           <button
50 |             className="px-6 py-2.5 rounded-full border border-card-border text-charcoal font-heading font-bold text-sm
bg-card-bg hover:bg-charcoal hover:text-cream transition-colors duration-300 focus:outline-none focus-visible:ring-2
focus-visible:ring-forest"
51 |             aria-label="Load more articles"
52 |             >
53 |             Load More Articles
54 |           </button>
55 |         </div>
56 |       </Container>
57 |
58 |       {/* Stay Inspired Newsletter Section */}
59 |       <Container className="mt-20">
60 |         <section
61 |           className="relative bg-accent rounded-[32px] p-8 sm:p-12 overflow-hidden shadow-xs border border-charcoal/5"
62 |           aria-labelledby="newsletter-title"
63 |         >

```

```

64 |  { /* Reusable Doodle Pattern */}
65 |  <BackgroundPattern variant="doodle" opacity={0.15} className="text-charcoal" />
66 |
67 |  <div className="relative z-10 grid grid-cols-1 lg:grid-cols-12 gap-8 items-center">
68 |    { /* Newsletter Text */}
69 |    <div className="lg:col-span-7 flex flex-col items-start text-left">
70 |      <h2 id="newsletter-title" className="text-3xl font-extrabold text-charcoal-static font-heading mb-3">
71 |        Stay Inspired
72 |      </h2>
73 |      <p className="text-sm sm:text-base text-charcoal-static/80 leading-relaxed font-body">
74 |        Subscribe to our newsletter for the latest stories of joyful wisdom and updates on our community initiatives.
75 |      </p>
76 |    </div>
77 |
78 |    { /* Newsletter Input/Form */}
79 |    <div className="lg:col-span-5 w-full">
80 |      {subscribed ? (
81 |        <div className="bg-white/80 rounded-full px-6 py-4 text-center font-bold text-charcoal animate-fade-in text-sm
border border-forest/10">
82 |          ✓ Thank you for subscribing!
83 |        </div>
84 |      ) : (
85 |        <form onSubmit={handleSubscribe} className="flex flex-col sm:flex-row gap-3 w-full">
86 |          <div className="flex-grow">
87 |            <label htmlFor="newsletter-email" className="sr-only">Your email address</label>
88 |            <input
89 |              id="newsletter-email"
90 |              type="email"
91 |              placeholder="Your email address"
92 |              value={email}
93 |              onChange={(e) => setEmail(e.target.value)}
94 |              required
95 |              className="w-full bg-white text-charcoal placeholder-charcoal/40 rounded-full px-6 py-3.5 text-sm
focus:outline-none focus:ring-2 focus:ring-forest border-none shadow-sm"
96 |            />
97 |          </div>
98 |          <button
99 |            type="submit"
100 |            className="bg-charcoal text-cream hover:bg-forest hover:text-cream px-8 py-3.5 rounded-full font-bold text-sm
transition-all duration-300 shadow-sm focus:outline-none focus-visible:ring-2 focus-visible:ring-forest shrink-0"
101 |            aria-label="Subscribe to newsletter"
102 |          >
103 |            Subscribe
104 |          </button>
105 |        </form>
106 |      )}
107 |    </div>
108 |  </div>
109 | </section>
110 | </Container>
111 | </div>
112 | );
113 | }
114 |

```


8. src/app/contact/page.tsx

```
1 | import React from "react";
2 | import { ContactForm } from "@components/sections/ContactForm";
3 | import { FAQ } from "@components/sections/FAQ";
4 | import { Container } from "@components/ui/Container";
5 | import { FAQData } from "@constants/data";
6 |
7 | export default function Contact(): React.ReactNode {
8 |   return (
9 |     <div className="pt-24 sm:pt-28 bg-cream min-h-screen pb-20">
10 |       <section className="py-16 sm:py-20 gradient-bg border-b border-forest/10 text-center">
11 |         <Container>
12 |           <div className="max-w-3xl mx-auto flex flex-col items-center">
13 |             <h1 className="text-4xl sm:text-5xl font-extrabold text-charcoal font-heading leading-tight mb-4">
14 |               Get In Touch
15 |             </h1>
16 |             <p className="text-base sm:text-lg text-charcoal/70 leading-relaxed font-body">
17 |               Whether you want to coordinate farm grants, register for volunteer digs, or request seed packages, send us
18 |               a message.
19 |             </p>
20 |           </div>
21 |         </Container>
22 |       </section>
23 |
24 |       <ContactForm
25 |         title="We would love to hear from you"
26 |         subtitle="Please fill out the form below or use our email/phone channels to speak directly with an organizer."
27 |       />
28 |
29 |       <FAQ
30 |         title="Inquiries FAQ"
31 |         subtitle="Quick answers concerning response timelines, school programs, and regional boundaries."
32 |         faqs={FAQData}
33 |       />
34 |     </div>
35 |   );
36 | }
37 |
```

9. src/app/donate/page.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import { Container } from "@components/ui/Container";
5 | import { Input } from "@components/ui/Input";
6 | import { Button } from "@components/ui/Button";
7 | import { cn } from "@utils/cn";
8 | import { Heart, CheckCircle2, ShieldCheck } from "lucide-react";
9 |
10 | export default function Donate(): React.ReactNode {
11 |   const [frequency, setFrequency] = useState<"one-time" | "monthly" | "annual">("monthly");
12 |   const [selectedTier, setSelectedTier] = useState<number | "custom">(30);
13 |   const [customAmount, setCustomAmount] = useState("");
14 |   const [name, setName] = useState("");
15 |   const [email, setEmail] = useState("");
16 |   const [cardNumber, setCardNumber] = useState("");
17 |   const [status, setStatus] = useState<"idle" | "loading" | "success">("idle");
18 |
19 |   const donationTiers = [15, 30, 60, 120];
20 |
21 |   const getImpactDescription = (amount: number): string => {
22 |     if (amount <= 15) {
23 |       return "Sponsors 5 native riparian broadleaf seedlings and stakes.";
24 |     } else if (amount <= 30) {
25 |       return "Sponsors 10 native conifer seedlings and organic soil mulch bags.";
26 |     } else if (amount <= 60) {
27 |       return "Sponsors a school Garden Classroom composting worm-bin and starter kit.";
28 |     } else {
29 |       return "Sponsors a complete biology test kit for a transitioning small farm.";
30 |     }
31 |   };
32 |
33 |   const activeAmount = selectedTier === "custom" ? Number(customAmount) || 0 : selectedTier;
34 |
35 |   const handleSubmit = (e: React.FormEvent<HTMLFormElement>): void => {
36 |     e.preventDefault();
37 |     if (activeAmount <= 0 || !name || !email) return;
38 |
39 |     setStatus("loading");
40 |     setTimeout(() => {
41 |       setStatus("success");
42 |     }, 1800);
43 |   };
44 |
45 |   return (
46 |     <div className="pt-24 sm:pt-28 bg-cream min-h-screen pb-20 animate-fade-in">
47 |       <section className="py-16 sm:py-20 gradient-bg border-b border-forest/10 text-center">
48 |         <Container>
49 |           <div className="max-w-3xl mx-auto flex flex-col items-center">
50 |             <h1 className="text-4xl sm:text-5xl font-extrabold text-charcoal font-heading leading-tight mb-4">
51 |               Empower Ecological Healing
52 |             </h1>
53 |             <p className="text-base sm:text-lg text-charcoal/70 leading-relaxed font-body">
54 |               Your donations directly fund native canopy tree seedlings, regional composting systems, and school
55 |               gardening kits.
56 |             </p>
57 |           </div>
58 |         </Container>
59 |       </section>
60 |
61 |       <Container className="mt-12">
62 |         <div className="max-w-4xl mx-auto grid grid-cols-1 md:grid-cols-12 gap-8 items-start">
63 |           <div className="md:col-span-7 bg-cream border border-forest/15 rounded-[32px] p-6 sm:p-8 flex flex-col gap-6 shadow-xs">
64 |             <h2 className="text-xl font-bold font-heading text-charcoal flex items-center gap-2">
65 |               <Heart size={20} className="text-forest fill-forest/15" />
66 |               Select Donation Value

```

```

67 | </h2>
68 |
69 | <div className="grid grid-cols-3 gap-2 bg-forest/5 p-1.5 rounded-full border border-forest/10">
70 | {[["one-time", "monthly", "annual"] as const].map((freq) => (
71 |   <button
72 |     key={freq}
73 |     onClick={() => setFrequency(freq)}
74 |     className={cn(
75 |       "py-2 rounded-full text-xs sm:text-sm font-semibold font-heading transition-all duration-200 capitalize
76 |       cursor-pointer focus:outline-none",
77 |       frequency === freq ? "bg-forest text-cream shadow-xs" : "text-charcoal/70 hover:text-forest"
78 |     )}
79 |     {freq === "one-time" ? "One-time" : freq === "monthly" ? "Monthly" : "Annual"}
80 |   </button>
81 | )]}
82 | </div>
83 |
84 | <div className="grid grid-cols-2 sm:grid-cols-4 gap-3">
85 | {donationTiers.map((tier) => (
86 |   <button
87 |     key={tier}
88 |     onClick={() => {
89 |       setSelectedTier(tier);
90 |       setCustomAmount("");
91 |     }}
92 |     className={cn(
93 |       "py-4 rounded-2xl border text-center font-bold font-heading transition-all duration-200 cursor-pointer
94 |       focus:outline-none",
95 |       selectedTier === tier
96 |       ? "bg-forest border-forest text-cream shadow-xs"
97 |       : "bg-cream border-forest/15 text-charcoal hover:bg-forest/5"
98 |     )}
99 |     ${tier}
100 |   </button>
101 | )]}
102 | </div>
103 |
104 | <div className="flex flex-col gap-2">
105 |   <button
106 |     onClick={() => setSelectedTier("custom")}
107 |     className={cn(
108 |       "w-full py-3 rounded-2xl border text-center font-bold font-heading transition-all duration-200 cursor-pointer
109 |       focus:outline-none",
110 |       selectedTier === "custom"
111 |       ? "bg-forest border-forest text-cream shadow-xs"
112 |       : "bg-cream border-forest/15 text-charcoal hover:bg-forest/5"
113 |     )}
114 |     >
115 |     Custom Value
116 |   </button>
117 |   {selectedTier === "custom" && (
118 |     <div className="relative mt-2 animate-fade-in">
119 |       <div className="absolute inset-y-0 left-4 flex items-center pointer-events-none text-charcoal/40 font-bold
120 |       font-heading z-10">
121 |         $
122 |       </div>
123 |       <input
124 |         type="number"
125 |         placeholder="Enter custom amount"
126 |         value={customAmount}
127 |         onChange={(e) => setCustomAmount(e.target.value)}
128 |         className="pl-9! w-full"
129 |         min={1}
130 |         required
131 |       />
132 |     </div>
133 |   )}
134 | </div>

```

```
133 |
134 | {activeAmount > 0 && (
135 | <div className="p-5 rounded-2xl bg-mint/20 border border-forest/15 animate-fade-in">
136 | <span className="text-xs font-bold text-forest font-heading tracking-wider uppercase block mb-1">
137 | Your Impact
138 | </span>
139 | <p className="text-sm font-semibold text-charcoal font-body leading-relaxed">
140 | {getImpactDescription(activeAmount)}
141 | </p>
142 | </div>
143 | )}
144 | </div>
145 |
146 | <div className="md:col-span-5 bg-cream border border-forest/15 rounded-[32px] p-6 sm:p-8 flex flex-col gap-6
shadow-xs">
147 | {status === "success" ? (
148 | <div className="flex flex-col items-center justify-center text-center py-12 animate-fade-in">
149 | <CheckCircle2 size={48} className="text-forest mb-4" />
150 | <h3 className="text-2xl font-bold text-charcoal font-heading mb-2">Thank You!</h3>
151 | <p className="text-sm text-charcoal/60 font-body leading-relaxed max-w-xs">
152 | Your mock donation of <strong>${activeAmount}</strong> has been received. Your support drives change!
153 | </p>
154 | <Button label="Donate Again" variant="outline" onClick={() => setStatus("idle")} className="mt-6" />
155 | </div>
156 | ) : (
157 | <form onSubmit={handleSubmit} className="flex flex-col gap-5">
158 | <h3 className="text-lg font-bold font-heading text-charcoal border-b border-forest/10 pb-3">
159 | Billing Information
160 | </h3>
161 | <Input
162 | label="Full Name"
163 | placeholder="Jane Doe"
164 | value={name}
165 | onChange={(e) => setName(e.target.value)}
166 | required
167 | disabled={status === "loading"}
168 | />
169 | <Input
170 | label="Email Address"
171 | type="email"
172 | placeholder="jane@example.com"
173 | value={email}
174 | onChange={(e) => setEmail(e.target.value)}
175 | required
176 | disabled={status === "loading"}
177 | />
178 | <Input
179 | label="Card Details (Mock)"
180 | placeholder="4111 2222 3333 4444"
181 | value={cardNumber}
182 | onChange={(e) => setCardNumber(e.target.value)}
183 | maxLength={19}
184 | required
185 | disabled={status === "loading"}
186 | />
187 |
188 | <Button
189 | type="submit"
190 | label={`Complete Donation of $${activeAmount}`}
191 | variant="secondary"
192 | loading={status === "loading"}
193 | disabled={activeAmount <= 0}
194 | className="w-full py-4! text-base font-bold shadow-xs mt-2"
195 | />
196 |
197 | <div className="flex items-center justify-center gap-2 text-xs text-charcoal/40 font-medium">
198 | <ShieldCheck size={14} className="text-forest" />
199 | <span>Secure 256-bit encrypted SSL checkout</span>
200 | </div>
201 | </form>
```

```
202 | })  
203 | </div>  
204 | </div>  
205 | </Container>  
206 | </div>  
207 | );  
208 | }  
209 |
```

10. src/app/error.tsx

```
1 | "use client";
2 |
3 | import React, { useEffect } from "react";
4 | import { Button } from "@/components/ui/Button";
5 | import { Container } from "@/components/ui/Container";
6 | import { AlertCircle } from "lucide-react";
7 |
8 | interface ErrorProps {
9 |   error: Error & { digest?: string };
10 |   reset: () => void;
11 | }
12 |
13 | export default function Error({ error, reset }: ErrorProps): React.ReactNode {
14 |   useEffect(() => {
15 |     console.error(error);
16 |   }, [error]);
17 |
18 |   return (
19 |     <div className="min-h-[70vh] flex items-center justify-center bg-cream py-20">
20 |       <Container>
21 |         <div className="max-w-md mx-auto text-center flex flex-col items-center">
22 |           <div className="p-4 rounded-full bg-red-100 text-red-600 mb-6">
23 |             <AlertCircle size={40} />
24 |           </div>
25 |           <h1 className="text-3xl font-bold font-heading text-charcoal mb-3">
26 |             Something went wrong!
27 |           </h1>
28 |           <p className="text-sm text-charcoal/60 font-body mb-8 leading-relaxed">
29 |             An unexpected error occurred while processing this page. Please try refreshing.
30 |           </p>
31 |           <div className="flex gap-4 w-full justify-center">
32 |             <Button label="Try Again" variant="primary" onClick={reset} />
33 |             <Button label="Back Home" variant="outline" href="/" />
34 |           </div>
35 |         </div>
36 |       </Container>
37 |     </div>
38 |   );
39 | }
40 |
```

11. src/app/globals.css

```
1 | @import "tailwindcss";
2 |
3 | @theme {
4 |   /* Exact Colors mapped to CSS variables */
5 |   --color-cream: var(--cream);
6 |   --color-sage: var(--sage);
7 |   --color-mint: var(--mint);
8 |   --color-charcoal: var(--charcoal);
9 |   --color-navy: var(--navy);
10 |   --color-accent: var(--accent);
11 |   --color-accent-dark: var(--accent-dark);
12 |   --color-beige: var(--beige);
13 |   --color-forest: var(--forest);
14 |   --color-forest-dark: var(--forest-dark);
15 |   --color-card-bg: var(--card-bg);
16 |   --color-card-border: var(--card-border);
17 |   --color-footer-bg: var(--footer-bg);
18 |   --color-success: var(--success);
19 |   --color-warning: var(--warning);
20 |   --color-error: var(--error);
21 |   --color-info: var(--info);
22 |
23 |   --color-cream-static: #FAF9F5;
24 |   --color-charcoal-static: #1B221E;
25 |   --color-pistachio: #b1cf87;
26 |   --color-pistachio-hover: #a0c172;
27 |
28 |   /* Fonts */
29 |   --font-heading: var(--font-playfair), serif;
30 |   --font-body: var(--font-inter), sans-serif;
31 |   --font-display: var(--font-display), serif;
32 | }
33 |
34 | :root {
35 |   /* Light Theme Variables */
36 |   --cream: #F9F8F3;
37 |   --sage: #F3EFE6;
38 |   --mint: #F3EFE6;
39 |   --charcoal: #4F4F4F;
40 |   --navy: #253326;
41 |   --accent: #E88A3D;
42 |   --accent-dark: #D76A3D;
43 |   --beige: #F3EFE6;
44 |   --forest: #456A48;
45 |   --forest-dark: #2F4A35;
46 |   --footer-bg: #253326;
47 |
48 |   --background: var(--cream);
49 |   --foreground: var(--charcoal);
50 |
51 |   --card-bg: #FFFFFF;
52 |   --card-border: #E6E1D5;
53 |   --muted-text: #7A7A7A;
54 |
55 |   /* Status Colors */
56 |   --success: #5D8A61;
57 |   --warning: #D9A441;
58 |   --error: #C95A4A;
59 |   --info: #5E8AA8;
60 |
61 |   /* Used in JS for theme transition ripple colors */
62 |   --light-bg: #F9F8F3;
63 |   --dark-bg: #141E15;
64 | }
65 |
66 | [data-theme="dark"] {
67 |   /* Dark Theme Variables */
```

```
68 | --cream: #141E15;
69 | --sage: #222E23;
70 | --mint: #222E23;
71 | --charcoal: #E2ECE3;
72 | --navy: #D0E0D2;
73 | --accent: #E88A3D;
74 | --accent-dark: #B55026;
75 | --beige: #222E23;
76 | --forest: #AFC3A9;
77 | --forest-dark: #223626;
78 | --footer-bg: #0D140E;
79 |
80 | --background: var(--cream);
81 | --foreground: var(--charcoal);
82 |
83 | --card-bg: #1C291E;
84 | --card-border: rgba(230, 225, 213, 0.12);
85 | --muted-text: #96A898;
86 |
87 | /* Gold/Accent stops for dark mode - softer, less neon */
88 | --gold-text-from: #E88A3D;
89 | --gold-text-via: #D8B15A;
90 | --gold-text-to: #D76A3D;
91 | --gold-from: #A6571E;
92 | --gold-via: #B8933E;
93 | --gold-to: #963E19;
94 |
95 | --shadow-soft: 0 6px 20px rgba(0,0,0,0.3);
96 | --shadow-card: 0 12px 35px rgba(0,0,0,0.4);
97 | --shadow-premium: 0 24px 60px rgba(0,0,0,0.5);
98 | --shadow-gold: 0 12px 35px rgba(232,138,61,0.06);
99 | }
100 |
101 | body {
102 |   background-color: var(--background);
103 |   color: var(--foreground);
104 |   font-family: var(--font-body);
105 |   -webkit-font-smoothing: antialiased;
106 |   transition: background-color 0.3s ease, color 0.3s ease;
107 | }
108 |
109 | h1, h2, h3, h4, h5, h6 {
110 |   font-family: var(--font-heading);
111 |   color: var(--navy);
112 | }
113 |
114 | /* Custom interaction utilities */
115 | .card-interactive {
116 |   transition: all 0.3s ease-in-out;
117 | }
118 | .card-interactive:hover {
119 |   transform: translateY(-4px);
120 |   box-shadow: 0 10px 25px -5px rgba(0, 0, 0, 0.05), 0 8px 10px -6px rgba(0, 0, 0, 0.05);
121 | }
122 |
123 | .btn-primary {
124 |   transition: all 0.3s ease-in-out;
125 | }
126 |
127 | :focus-visible {
128 |   outline: 2px solid var(--color-forest);
129 |   outline-offset: 2px;
130 | }
131 |
132 | /* ■■■ Gold/Accent gradient stops ████████████████████████████████████████████████████████████████████████████████ */
133 | :root {
134 |   --gold-text-from: #E88A3D;
135 |   --gold-text-via: #D8B15A;
136 |   --gold-text-to: #D76A3D;
137 |   --gold-from: #E88A3D;
```



```

138 | --gold-via: #D8B15A;
139 | --gold-to: #D76A3D;
140 |
141 | --shadow-soft: 0 6px 20px rgba(0,0,0,0.05);
142 | --shadow-card: 0 12px 35px rgba(0,0,0,0.08);
143 | --shadow-premium: 0 24px 60px rgba(0,0,0,0.12);
144 | --shadow-gold: 0 12px 35px rgba(232,138,61,0.12);
145 | }
146 |
147 | /* ■■ Gold gradient text ████████████████████████████████████████████████████ */
148 | .text-gold-gradient {
149 | background: linear-gradient(135deg, var(--gold-text-from) 0%, var(--gold-text-via) 50%, var(--gold-text-to)
100%);
150 | -webkit-background-clip: text;
151 | background-clip: text;
152 | -webkit-text-fill-color: transparent;
153 | color: transparent;
154 | }
155 |
156 | /* ■■ Gold gradient background ████████████████████████████████████████████████████ */
157 | .bg-gold-gradient {
158 | background: linear-gradient(135deg, var(--gold-from) 0%, var(--gold-via) 50%, var(--gold-to) 100%);
159 | }
160 |
161 | /* ■■ Theme Gradients ████████████████████████████████████████████████████ */
162 | .bg-hero-gradient {
163 | background: linear-gradient(135deg, #F9F8F3 0%, #F3EFE6 100%);
164 | }
165 | .bg-primary-gradient {
166 | background: linear-gradient(135deg, #456A48 0%, #2F4A35 100%);
167 | }
168 | .bg-accent-gradient {
169 | background: linear-gradient(135deg, #E88A3D 0%, #D76A3D 100%);
170 | }
171 |
172 | /* ■■ Shadow utilities ████████████████████████████████████████████████████ */
173 | .shadow-soft { box-shadow: var(--shadow-soft); }
174 | .shadow-card { box-shadow: var(--shadow-card); }
175 | .shadow-premium { box-shadow: var(--shadow-premium); }
176 | .shadow-gold { box-shadow: var(--shadow-gold); }
177 |
178 | /* ■■ Card system ████████████████████████████████████████████████████ */
179 | .card-base {
180 | background-color: var(--card-bg);
181 | border: 1px solid var(--card-border);
182 | border-radius: 1.5rem;
183 | box-shadow: var(--shadow-card);
184 | transition: box-shadow 0.3s ease, transform 0.3s ease, background-color 0.3s ease, border-color 0.3s ease;
185 | }
186 |
187 | .card-hover:hover {
188 | box-shadow: var(--shadow-premium);
189 | transform: translateY(-3px);
190 | }
191 |
192 | /* ■■ Gold divider line ████████████████████████████████████████████████████ */
193 | .divider-gold {
194 | height: 3px;
195 | background: linear-gradient(90deg, transparent, var(--gold-text-from) 20%, var(--gold-text-via) 50%,
var(--gold-text-to) 80%, transparent);
196 | border-radius: 9999px;
197 | }
198 |
199 | /* ■■ Gold badge pill ████████████████████████████████████████████████████ */
200 | .badge-gold {
201 | display: inline-flex;
202 | align-items: center;
203 | padding: 0.25rem 0.875rem;
204 | border-radius: 9999px;
205 | font-size: 0.6875rem;

```

[illegible]

12. src/app/layout.tsx

```

1 | import type { Metadata } from "next";
2 | import { Playfair_Display, Inter, DM_Serif_Display } from "next/font/google";
3 | import "../globals.css";
4 | import MainLayout from "@layouts/MainLayout";
5 | import AppProviders from "@components/providers/AppProviders";
6 | import { siteName, siteTagline, siteDescription, siteUrl } from "@constants/site";
7 | import Script from "next/script";
8 |
9 | const playfair = Playfair_Display({
10 |   subsets: ["latin"],
11 |   variable: "--font-playfair",
12 |   weight: ["400", "500", "600", "700", "800"],
13 | });
14 |
15 | const inter = Inter({
16 |   subsets: ["latin"],
17 |   variable: "--font-inter",
18 |   weight: ["400", "500", "600", "700", "800"],
19 | });
20 |
21 | const dmSerif = DM_Serif_Display({
22 |   subsets: ["latin"],
23 |   variable: "--font-display",
24 |   weight: ["400"],
25 |   style: ["normal", "italic"],
26 | });
27 |
28 | export const metadata: Metadata = {
29 |   title: {
30 |     default: `${siteName} - ${siteTagline}`,
31 |     template: `%s | ${siteName}`,
32 |   },
33 |   description: siteDescription,
34 |   metadataBase: new URL(siteUrl),
35 |   openGraph: {
36 |     title: `${siteName} - ${siteTagline}`,
37 |     description: siteDescription,
38 |     siteName: siteName,
39 |   },
40 |   twitter: {
41 |     title: `${siteName} - ${siteTagline}`,
42 |     description: siteDescription,
43 |   },
44 | };
45 |
46 | export default function RootLayout({
47 |   children,
48 | }: Readonly<{
49 |   children: React.ReactNode;
50 | }>) {
51 |   return (
52 |     <html
53 |       lang="en"
54 |       className={`${playfair.variable} ${inter.variable} ${dmSerif.variable} antialiased`}
55 |       suppressHydrationWarning
56 |     >
57 |     <body className="bg-cream text-charcoal font-body antialiased selection:bg-forest selection:text-cream">
58 |       <Script
59 |         id="theme-init"
60 |         strategy="beforeInteractive"
61 |         dangerouslySetInnerHTML={{
62 |           __html: `
63 |             (function() {
64 |               try {
65 |                 var stored = localStorage.getItem('dua-theme');
66 |                 var theme = 'light';
67 |                 if (stored === 'light' || stored === 'dark') {

```

```
68 | theme = stored;
69 | } else if (window.matchMedia('(prefers-color-scheme: dark)').matches) {
70 | theme = 'dark';
71 | }
72 | document.documentElement.setAttribute('data-theme', theme);
73 | document.documentElement.style.colorScheme = theme;
74 | } catch (e) {}
75 | })();
76 | `
77 | }}
78 | />
79 | <AppProviders>
80 | <MainLayout>{children}</MainLayout>
81 | </AppProviders>
82 | </body>
83 | </html>
84 | );
85 | }
86 |
```

13. src/app/loading.tsx

```
1 | import React from "react";
2 | import { Loader } from "@components/ui/Loader";
3 |
4 | export default function Loading(): React.ReactNode {
5 |   return (
6 |     <div className="min-h-[70vh] flex items-center justify-center bg-cream">
7 |       <Loader size="lg" />
8 |     </div>
9 |   );
10 | }
11 |
```

14. src/app/not-found.tsx

```
1 | import React from "react";
2 | import { Button } from "@components/ui/Button";
3 | import { Container } from "@components/ui/Container";
4 | import { Leaf } from "lucide-react";
5 |
6 | export default function NotFound(): React.ReactNode {
7 |   return (
8 |     <div className="min-h-[75vh] flex items-center justify-center bg-cream py-20">
9 |       <Container>
10 |        <div className="max-w-md mx-auto text-center flex flex-col items-center">
11 |          <div className="p-4 rounded-full bg-forest/10 text-forest mb-6 animate-bounce">
12 |            <Leaf size={40} className="fill-current" />
13 |          </div>
14 |          <h1 className="text-5xl font-extrabold font-heading text-forest tracking-tight mb-2">
15 |            404
16 |          </h1>
17 |          <h2 className="text-2xl font-bold font-heading text-charcoal mb-4">
18 |            Page Not Found
19 |          </h2>
20 |          <p className="text-sm text-charcoal/60 font-body mb-8 leading-relaxed">
21 |            The path you are looking for might have drifted away, been reforested, or does not exist.
22 |          </p>
23 |          <Button label="Return Home" variant="primary" href="/" />
24 |        </div>
25 |      </Container>
26 |    </div>
27 |  );
28 | }
29 |
```

15. src/app/our-projects/[slug]/page.tsx

```

1 | import React from "react";
2 | import Image from "next/image";
3 | import Link from "next/link";
4 | import { notFound } from "next/navigation";
5 | import { projectsData } from "@/constants/data";
6 | import { Container } from "@/components/ui/Container";
7 | import { Badge } from "@/components/ui/Badge";
8 | import { CTA } from "@/components/sections/CTA";
9 | import { ArrowLeft, Calendar, CheckSquare, BarChart } from "lucide-react";
10 | import { ctaData } from "@/constants/data";
11 |
12 | interface ProjectDetailProps {
13 |   params: {
14 |     slug: string;
15 |   };
16 | }
17 |
18 | export function generateStaticParams(): { slug: string }[] {
19 |   return projectsData.map((project) => ({
20 |     slug: project.slug,
21 |   }));
22 | }
23 |
24 | export default function ProjectDetail({ params }: ProjectDetailProps): React.ReactNode {
25 |   const project = projectsData.find((p) => p.slug === params.slug);
26 |
27 |   if (!project) {
28 |     notFound();
29 |   }
30 |
31 |   const badgeVariants = {
32 |     active: "success" as const,
33 |     completed: "info" as const,
34 |     planned: "orange" as const,
35 |   };
36 |
37 |   return (
38 |     <div className="pt-24 sm:pt-28 bg-cream min-h-screen">
39 |       <Container className="py-6">
40 |         <Link
41 |           href="/our-projects"
42 |           className="inline-flex items-center gap-2 text-sm font-semibold text-forest hover:text-forest/85
43 |           transition-colors focus:outline-none"
44 |         >
45 |           <ArrowLeft size={16} />
46 |           Back to All Projects
47 |         </Link>
48 |       </Container>
49 |
50 |       <section className="pb-12">
51 |         <Container>
52 |           <div className="relative h-[300px] sm:h-[450px] w-full rounded-3xl overflow-hidden shadow-xs border
53 |           border-forest/10">
54 |             <Image src={project.image} alt={project.title} fill className="object-cover" sizes="100vw" priority />
55 |           </div>
56 |         </Container>
57 |       </section>
58 |
59 |       <section className="pb-20">
60 |         <Container>
61 |           <div className="grid grid-cols-1 lg:grid-cols-12 gap-12">
62 |             <div className="lg:col-span-8">
63 |               <div className="flex flex-wrap items-center gap-3 mb-4">
64 |                 <Badge label={project.badge} variant={badgeVariants[project.status]} />
65 |               </div>
66 |               <h1 className="text-3xl sm:text-4xl md:text-5xl font-extrabold text-charcoal font-heading leading-tight mb-6">
67 |                 {project.title}

```

```

66 | </h1>
67 | <div className="prose max-w-none text-charcoal/80 font-body leading-relaxed text-base sm:text-lg mb-8">
68 | <p className="whitespace-pre-line">{project.longDescription || project.description}</p>
69 | </div>
70 |
71 | {project.goals && project.goals.length > 0 && (
72 | <div className="mt-10 p-6 sm:p-8 rounded-3xl bg-mint/20 border border-forest/15">
73 | <h3 className="text-xl font-bold font-heading text-charcoal mb-5 flex items-center gap-2">
74 | <CheckSquare size={20} className="text-forest" />
75 | Key Goals & Milestones
76 | </h3>
77 | <ul className="flex flex-col gap-4">
78 | {project.goals.map((goal, idx) => (
79 | <li key={idx} className="flex gap-3 items-start">
80 | <span className="h-2 w-2 rounded-full bg-forest mt-2 shrink-0" />
81 | <span className="text-sm sm:text-base text-charcoal/80 font-body leading-relaxed">
82 | {goal}
83 | </span>
84 | </li>
85 | ))}
86 | </ul>
87 | </div>
88 | )}
89 | </div>
90 |
91 | <div className="lg:col-span-4 flex flex-col gap-6">
92 | <div className="bg-cream border border-forest/15 rounded-3xl p-6 sm:p-8 flex flex-col gap-6 shadow-xs">
93 | <h3 className="text-lg font-bold font-heading text-charcoal border-b border-forest/10 pb-4">
94 | Project Details
95 | </h3>
96 |
97 | {project.timeline && (
98 | <div className="flex items-start gap-4">
99 | <div className="p-2.5 rounded-xl bg-forest/10 text-forest shrink-0 mt-0.5">
100 | <Calendar size={18} />
101 | </div>
102 | <div>
103 | <span className="text-xs font-semibold text-charcoal/50 uppercase tracking-wider block font-heading mb-0.5">
104 | Timeline
105 | </span>
106 | <span className="text-sm font-semibold text-charcoal font-body">{project.timeline}</span>
107 | </div>
108 | </div>
109 | )}
110 |
111 | {project.impactMetric && (
112 | <div className="flex items-start gap-4">
113 | <div className="p-2.5 rounded-xl bg-forest/10 text-forest shrink-0 mt-0.5">
114 | <BarChart size={18} />
115 | </div>
116 | <div>
117 | <span className="text-xs font-semibold text-charcoal/50 uppercase tracking-wider block font-heading mb-0.5">
118 | Recorded Impact
119 | </span>
120 | <span className="text-sm font-semibold text-forest font-body">{project.impactMetric}</span>
121 | </div>
122 | </div>
123 | )}
124 | </div>
125 | </div>
126 | </div>
127 | </Container>
128 | </section>
129 |
130 | <CTA
131 | title={ctaData.title}
132 | description={ctaData.description}
133 | primaryCtaText={ctaData.primaryCtaText}
134 | primaryCtaLink={ctaData.primaryCtaLink}
135 | secondaryCtaText={ctaData.secondaryCtaText}

```



```
136 | secondaryCtaLink={ctaData.secondaryCtaLink}
137 | />
138 | </div>
139 | );
140 | }
141 |
```

16. src/app/our-projects/page.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { Container } from "@components/ui/Container";
5 | import { ProjectCard } from "@components/ui/ProjectCard";
6 | import { BackgroundPattern } from "@components/ui/BackgroundPattern";
7 | import { projectsData } from "@constants/data";
8 | import { PageRoutes } from "@types";
9 | import Link from "next/link";
10 |
11 | export default function OurProjects(): React.ReactNode {
12 |   return (
13 |     <div className="relative pt-24 sm:pt-28 bg-cream min-h-screen pb-20 overflow-hidden">
14 |       {/* Full-page colorful project grid background pattern */}
15 |       <BackgroundPattern variant="project-grid" opacity={0.6} className="z-0" />
16 |
17 |       <div className="relative z-10">
18 |         {/* Header Section */}
19 |         <section className="py-16 sm:py-20 text-center max-w-4xl mx-auto">
20 |           <Container>
21 |             <div className="flex flex-col items-center">
22 |               <h1 className="text-4xl sm:text-5xl font-extrabold text-charcoal font-heading leading-tight mb-4">
23 |                 Our Projects - Dua Charitable Trust
24 |               </h1>
25 |               <p className="text-base sm:text-lg text-charcoal/70 leading-relaxed font-body">
26 |                 Explore the various projects and community programs we've developed to nurture joyful wisdom and empower
27 |                 learners across the globe. Each initiative is a step towards a brighter, more inclusive future.
28 |               </p>
29 |             </div>
30 |           </Container>
31 |
32 |           {/* Project Grid */}
33 |           <Container className="mt-8">
34 |             <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-8">
35 |               {projectsData.map((project) => (
36 |                 <ProjectCard key={project.slug} project={project} />
37 |               ))}
38 |             </div>
39 |           </Container>
40 |
41 |           {/* Support Callout Section */}
42 |           <Container className="mt-20">
43 |             <section
44 |               className="relative bg-cream rounded-[32px] p-8 sm:p-12 text-center overflow-hidden shadow-xs border
45 |               border-charcoal/5"
46 |               aria-labelledby="support-title"
47 |             >
48 |               {/* Doodle background pattern */}
49 |               <BackgroundPattern variant="doodle" opacity={0.12} className="text-forest" />
50 |
51 |               <div className="relative z-10 max-w-2xl mx-auto flex flex-col items-center">
52 |                 {/* Hand/Heart/Star custom SVG graphic at top of support box */}
53 |                 <div className="w-12 h-12 rounded-full bg-white/60 flex items-center justify-center text-forest mb-6">
54 |                   <svg
55 |                     className="w-6 h-6 fill-none stroke-current"
56 |                     strokeWidth="2"
57 |                     viewBox="0 0 24 24"
58 |                     aria-hidden="true"
59 |                   >
60 |                     <path d="M12 21.35l-1.45-1.32C5.4 15.36 2 12.28 2 8.5 2 5.42 4.42 3 7.5 3c1.74 0 3.41.81 4.5 2.09C13.09 3.81
61 |                     14.76 3 16.5 3 19.58 3 22 5.42 22 8.5c0 3.78-3.4 6.86-8.55 11.54L12 21.35z" />
62 |                   </svg>
63 |                 </div>
64 |                 <h2 id="support-title" className="text-2xl sm:text-3xl font-extrabold text-charcoal font-heading mb-4">
65 |                   Want to support our initiatives?

```

```
65 | </h2>
66 | <p className="text-sm sm:text-base text-charcoal/70 leading-relaxed font-body mb-8">
67 | Your contribution helps us expand these projects and reach more communities. Whether through volunteering or
68 | donations, every bit helps nurture joyful wisdom.
69 | </p>
70 | <div className="flex flex-col sm:flex-row gap-4 items-center justify-center w-full sm:w-auto">
71 | <Link
72 | href={PageRoutes.DONATE}
73 | className="w-full sm:w-44 bg-charcoal text-cream hover:bg-forest hover:text-cream text-center px-6 py-3.5
rounded-full font-bold text-sm transition-all duration-300 shadow-sm focus:outline-none focus-visible:ring-2
focus-visible:ring-forest"
74 | aria-label="Donate Now to our initiatives"
75 | >
76 | Donate Now
77 | </Link>
78 | <Link
79 | href={PageRoutes.CONTACT}
80 | className="w-full sm:w-44 bg-card-bg/70 border border-card-border text-charcoal hover:bg-charcoal
hover:text-cream text-center px-6 py-3.5 rounded-full font-bold text-sm transition-all duration-300 shadow-sm
focus:outline-none focus-visible:ring-2 focus-visible:ring-forest"
81 | aria-label="Volunteer for our initiatives"
82 | >
83 | Volunteer
84 | </Link>
85 | </div>
86 | </div>
87 | </section>
88 | </Container>
89 | </div>
90 | </div>
91 | );
92 | }
93 |
```

17. src/app/page.tsx

```

1 | import React from "react";
2 | import { Hero } from "@components/sections/Hero";
3 | import { Mission } from "@components/sections/Mission";
4 | import { ImageExpansionStory, ParallaxBanner } from "@components/storytelling/ImageExpansionStory";
5 | import { ImpactStats } from "@components/sections/ImpactStats";
6 | import { FeaturedProjects } from "@components/sections/FeaturedProjects";
7 | import { Testimonials } from "@components/sections/Testimonials";
8 | import { FAQ } from "@components/sections/FAQ";
9 | import { CTA } from "@components/sections/CTA";
10 | import { SeedsOfChange } from "@components/sections/SeedsOfChange";
11 | import {
12 |   heroData,
13 |   missionData,
14 |   impactStatsData,
15 |   projectsData,
16 |   testimonialsData,
17 |   FAQData,
18 |   ctaData,
19 | } from "@constants/data";
20 |
21 | export default function Home(): React.ReactNode {
22 |   return (
23 |     <>
24 |     <Hero
25 |       heading={heroData.heading}
26 |       subheading={heroData.subheading}
27 |       primaryCtaText={heroData.primaryCtaText}
28 |       primaryCtaLink={heroData.primaryCtaLink}
29 |       secondaryCtaText={heroData.secondaryCtaText}
30 |       secondaryCtaLink={heroData.secondaryCtaLink}
31 |     />
32 |     <Mission
33 |       title={missionData.title}
34 |       description={missionData.description}
35 |       bullets={missionData.bullets}
36 |       image={missionData.image}
37 |     />
38 |     <ImageExpansionStory />
39 |
40 |     <SeedsOfChange />
41 |
42 |     <ImpactStats
43 |       title={impactStatsData.title}
44 |       subtitle={impactStatsData.subtitle}
45 |       stats={impactStatsData.stats}
46 |     />
47 |     <FeaturedProjects
48 |       title="Featured Ecosystem Restorations"
49 |       subtitle="Explore some of our active and recently completed initiatives making a tangible ecological impact."
50 |       projects={projectsData}
51 |     />
52 |     <Testimonials
53 |       title="Loved by Communities & Volunteers"
54 |       subtitle="Hear directly from local residents, agricultural landowners, and active hands helping us grow."
55 |       testimonials={testimonialsData}
56 |     />
57 |     <ParallaxBanner
58 |       imageSrc="/children-gardening.jpg"
59 |       label="Children planting sprouts in a community garden"
60 |     />
61 |     <FAQ
62 |       title="Frequently Asked Questions"
63 |       subtitle="Have questions about where donations go or how you can participate? We have got you covered."
64 |       faqs={FAQData}
65 |     />
66 |     <CTA
67 |       title={ctaData.title}

```

```
68 | description={ctaData.description}
69 | primaryCtaText={ctaData.primaryCtaText}
70 | primaryCtaLink={ctaData.primaryCtaLink}
71 | secondaryCtaText={ctaData.secondaryCtaText}
72 | secondaryCtaLink={ctaData.secondaryCtaLink}
73 | />
74 | </>
75 | );
76 | }
77 |
```

18. src/app/showcase/layout.tsx

```
1 | import React from "react";
2 | import { Metadata } from "next";
3 |
4 | export const metadata: Metadata = {
5 |   title: "Component Library Showcase - Dua Charitable Trust",
6 |   description: "Dev-only interactive playground for the premium UI component library.",
7 |   robots: {
8 |     index: false,
9 |     follow: false,
10 |   },
11 | };
12 |
13 | interface ShowcaseLayoutProps {
14 |   children: React.ReactNode;
15 | }
16 |
17 | export default function ShowcaseLayout({ children }: ShowcaseLayoutProps) {
18 |   return <{children}></>;
19 | }
20 |
```

19. src/app/showcase/page.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import { notFound } from "next/navigation";
5 | import { cn } from "@utils/cn";
6 | import {
7 |   AnimatedButton,
8 |   AnimatedCard,
9 |   AnimatedCounter,
10 |   BeforeAfter,
11 |   DonationWidget,
12 |   FAQAccordion,
13 |   FloatingButton,
14 |   Gallery,
15 |   GlassCard,
16 |   GradientHeading,
17 |   ImpactCounter,
18 |   ImageSlider,
19 |   SectionDivider,
20 |   TestimonialSlider,
21 |   TiltCard,
22 |   Timeline,
23 |   BlurReveal,
24 |   TextReveal,
25 |   ImageReveal,
26 |   Magnetic,
27 |   StickyScrollSection,
28 | } from "@components/ui";
29 | import {
30 |   Sparkles,
31 |   Sliders,
32 |   Layout,
33 |   Type,
34 |   Maximize,
35 |   Coins,
36 |   Check,
37 |   Copy,
38 |   Heart,
39 |   Film,
40 | } from "lucide-react";
41 |
42 | // Guard page in production
43 | if (process.env.NODE_ENV === "production") {
44 |   notFound();
45 | }
46 |
47 | export default function ShowcasePage() {
48 |   const [activeTab, setActiveTab] = useState("AnimatedCard");
49 |   const [copiedCode, setCopiedCode] = useState(false);
50 |
51 |   // Copy helper
52 |   const handleCopyCode = (code: string) => {
53 |     navigator.clipboard.writeText(code);
54 |     setCopiedCode(true);
55 |     setTimeout(() => setCopiedCode(false), 2000);
56 |   };
57 |
58 |   // Mock data for showcase previews
59 |   const mockFaqs = [
60 |     {
61 |       question: "What is the mission of Dua Charitable Trust?",
62 |       answer: "We aim to make education a joyful community adventure by organizing STEM labs, art therapies, and environmental gardens.",
63 |       category: "General",
64 |     },
65 |     {
66 |       question: "How are donations utilized?",

```

```
67 | answer: "Exactly 85% of funds support program assets directly (materials, kits, seedlings, laptops), while 15%
68 | covers admin support.",
69 | },
70 | {
71 | question: "Can I host a Curiosity Lab in my school?",
72 | answer: "Absolutely! Get in touch with our Outreach lead via the contact form to schedule a mobile lab session.",
73 | category: "Programs",
74 | },
75 | ];
76 |
77 | const mockTimeline = [
78 | {
79 | id: 1,
80 | date: "Spring 2024",
81 | title: "Foundation of Collective",
82 | subtitle: "Seattle, WA",
83 | content: "Launched with five founding educators running local tutoring labs.",
84 | },
85 | {
86 | id: 2,
87 | date: "Fall 2024",
88 | title: "First 1,000 Laptops",
89 | subtitle: "Digital Literacy Campaign",
90 | content: "Refurbished and shipped computing devices to regional libraries.",
91 | },
92 | {
93 | id: 3,
94 | date: "Late 2025",
95 | title: "Green Roots Initiated",
96 | subtitle: "Sustainable Gardens",
97 | content: "Partnered with ten community schools to maintain seed exchange vaults.",
98 | },
99 | ];
100 |
101 | const mockGallery = [
102 | {
103 | id: 1,
104 | src: "https://images.unsplash.com/photo-1530210120071-aa792f6b7d6b?q=80&w=600&auto=format&fit=crop",
105 | alt: "STEM experimental setup",
106 | category: "STEM",
107 | title: "Curiosity Labs Experiment",
108 | description: "Primary school students testing circuit boards.",
109 | },
110 | {
111 | id: 2,
112 | src: "https://images.unsplash.com/photo-1466692476868-aef1dfb1e735?q=80&w=600&auto=format&fit=crop",
113 | alt: "School organic garden planting",
114 | category: "Environment",
115 | title: "School Riparian Garden",
116 | description: "Students checking composting worm-bins.",
117 | },
118 | {
119 | id: 3,
120 | src: "https://images.unsplash.com/photo-1460661419201-fd4cecdf8a8b?q=80&w=600&auto=format&fit=crop",
121 | alt: "Kids creative watercolor painting",
122 | category: "Arts",
123 | title: "Canvas of Hope session",
124 | description: "Therapeutic painting workshop for kids.",
125 | },
126 | ];
127 |
128 | const mockSlider = [
129 | {
130 | src: "https://images.unsplash.com/photo-1509062522246-3755977927d7?q=80&w=1000&auto=format&fit=crop",
131 | alt: "Curious classroom learning",
132 | title: "Sparkling Universal Curiosity",
133 | description: "Empowering school children to explore and question through tactile experiments.",
134 | },
135 | {
```



```

136 | src: "https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=1000&auto=format&fit=crop",
137 | alt: "Group learning outdoor circle",
138 | title: "Nurturing Joyful Wisdom",
139 | description: "Connecting intergenerational mentors with eager rural students.",
140 | },
141 | ];
142 |
143 | const mockTestimonials = [
144 | {
145 |   name: "Clara Henderson",
146 |   role: "Parent of Student",
147 |   avatar: "https://images.unsplash.com/photo-1444065381814-865dc9da92c0?q=80&w=200&auto=format&fit=crop",
148 |   quote: "Dua's Curiosity Labs changed my daughter's view of school. She went from dreading science to wanting to
build circuits at home.",
149 |   rating: 5,
150 | },
151 | {
152 |   name: "Arthur Glass",
153 |   role: "School Principal",
154 |   avatar: "https://images.unsplash.com/photo-1500648767791-00dcc994a43e?q=80&w=200&auto=format&fit=crop",
155 |   quote: "The Wisdom Collective tutoring program has dramatically boosted our reading comprehension scores and
forged real intergenerational friendships.",
156 |   rating: 5,
157 | },
158 | ];
159 |
160 | const mockImpact = [
161 | { value: 5000, label: "Students Taught", suffix: "+", type: "counter" as const, color: "forest" as const },
162 | { value: 85, label: "Efficiency rating", suffix: "%", type: "circle" as const, progressValue: 85, color: "gold"
as const },
163 | { value: 1200, label: "Laptops Distributed", suffix: "+", type: "progress" as const, progressValue: 78, color:
"charcoal" as const },
164 | ];
165 |
166 | // Component configuration state controls
167 | const [cCardVariant, setCCardVariant] = useState<"default" | "glass" | "premium" | "outline">("default");
168 | const [cCardGlow, setCCardGlow] = useState(false);
169 | const [cCardHover, setCCardHover] = useState(true);
170 |
171 | const [cGlassOpacity, setCGlassOpacity] = useState(0.4);
172 | const [cGlassBlur, setCGlassBlur] = useState(12);
173 | const [cGlassGlow, setCGlassGlow] = useState(true);
174 |
175 | const [cTiltIntensity, setCTiltIntensity] = useState(15);
176 | const [cTiltGlare, setCTiltGlare] = useState(true);
177 |
178 | const [cButtonVariant, setCButtonVariant] = useState<"primary" | "secondary" | "outline" | "ghost" |
"gold">("primary");
179 | const [cButtonLoading, setCButtonLoading] = useState(false);
180 |
181 | const [cHeadingUnderline, setCHeadingUnderline] = useState(true);
182 |
183 | const categoriesList = [
184 | {
185 |   group: "Cards",
186 |   icon: <Layout className="w-4 h-4" />,
187 |   items: ["AnimatedCard", "GlassCard", "TiltCard"],
188 | },
189 | {
190 |   group: "Typography & Accents",
191 |   icon: <Type className="w-4 h-4" />,
192 |   items: ["GradientHeading", "SectionDivider"],
193 | },
194 | {
195 |   group: "Data & Timelines",
196 |   icon: <Maximize className="w-4 h-4" />,
197 |   items: ["AnimatedCounter", "ImpactCounter", "Timeline"],
198 | },
199 | {
200 |   group: "Interaction",

```

```

201 | icon: <Sliders className="w-4 h-4" />,
202 | items: ["AnimatedButton", "FAQAccordion", "FloatingButton"],
203 | },
204 | {
205 |   group: "Media sliders",
206 |   icon: <Film className="w-4 h-4" />,
207 |   items: ["Gallery", "ImageSlider", "BeforeAfter", "TestimonialSlider"],
208 | },
209 | {
210 |   group: "Cinematic Animations",
211 |   icon: <Sparkles className="w-4 h-4" />,
212 |   items: ["BlurReveal", "TextReveal", "ImageReveal", "Magnetic", "StickyScrollSection"],
213 | },
214 | {
215 |   group: "Giving Forms",
216 |   icon: <Coins className="w-4 h-4" />,
217 |   items: ["DonationWidget"],
218 | },
219 | ];
220 |
221 | // Code snippets database
222 | const codeSnippets: Record<string, string> = {
223 |   AnimatedCard: `<AnimatedCard\n variant="${cCardVariant}"\n hover=${cCardHover}\n glow=${cCardGlow}\n
animationDirection="up"\n>\n\n <div className="p-6">\n\n <h3 className="text-lg font-bold font-heading mb-2">Dua
Charitable Trust</h3>\n\n <p className="text-sm opacity-80">Premium modular reveal cards.</p>\n\n
</div>\n</AnimatedCard>`,
224 |   GlassCard: `<GlassCard\n opacity=${cGlassOpacity}\n blur=${cGlassBlur}\n glow=${cGlassGlow}\n
gradientBorder={true}\n>\n\n <div className="p-8">\n\n <h3 className="text-xl font-bold font-heading
mb-2">Glassmorphism</h3>\n\n <p className="text-sm text-charcoal/70">Radial cursor-following glow spotlight.</p>\n\n
</div>\n</GlassCard>`,
225 |   TiltCard: `<TiltCard\n intensity=${cTiltIntensity}\n glare=${cTiltGlare}\n scale={1.04}\n>\n\n <div
className="p-8">\n\n <h3 className="text-lg font-bold font-heading">3D Tilt Effect</h3>\n\n <p className="text-xs
opacity-70 mt-1">Parallax mouse coordinate transitions.</p>\n\n </div>\n</TiltCard>`,
226 |   GradientHeading: `<GradientHeading\n variant="section"\n level={2}\n underline=${cHeadingUnderline}\n
highlightWords=[["Curiosity", "Wisdom"]]\n>\n\n Sparking Universal Curiosity & Wisdom\n</GradientHeading>`,
227 |   SectionDivider: `<SectionDivider\n variant="premium"\n animate={true}\n/>`,
228 |   AnimatedCounter: `<AnimatedCounter\n target={12450}\n prefix="$"\n suffix="+"\n decimals={0}\n
formatting={true}\n/>`,
229 |   ImpactCounter: `<ImpactCounter\n stats=[\n { value: 5000, label: "Students", type: "counter" },\n { value: 85,
label: "Efficiency", type: "circle", progressValue: 85 },\n { value: 1200, label: "Laptops", type: "progress",
progressValue: 78 }\n ]\n/>`,
230 |   Timeline: `<Timeline\n items={timelineItems}\n orientation="vertical"\n variant="premium"\n/>`,
231 |   AnimatedButton: `<AnimatedButton\n variant="${cButtonVariant}"\n loading=${cButtonLoading}\n label="Make a
Difference"\n onClick={() => alert("Simulated Submit")}\n/>`,
232 |   FAQAccordion: `<FAQAccordion\n items={faqItems}\n allowMultiple={false}\n showSearch={true}\n/>`,
233 |   FloatingButton: `<FloatingButton\n label="Quick Actions"\n tooltip="Get Involved"\n pulse={true}\n actions=[\n
{ label: "Donate", icon: <Coins />, href: "/donate" },\n { label: "Volunteers", icon: <Heart />, href: "/contact" }\n
]\n/>`,
234 |   Gallery: `<Gallery\n items={galleryItems}\n/>`,
235 |   ImageSlider: `<ImageSlider\n images={sliderImages}\n autoplay={true}\n infinite={true}\n/>`,
236 |   BeforeAfter: `<BeforeAfter\n beforeImage="url1"\n afterImage="url2"\n beforeLabel="Before Restoration"\n
afterLabel="After Planting"\n/>`,
237 |   TestimonialSlider: `<TestimonialSlider\n testimonials={testimonialsList}\n autoplay={true}\n/>`,
238 |   DonationWidget: `<DonationWidget\n currencySymbol="₹"\n presetAmounts=[500, 1000, 2500, 5000]\n
onDonate={async (data) => console.log(data)}\n/>`,
239 |   BlurReveal: `<BlurReveal blur={15} duration={0.8}>\n\n <div className="p-8 bg-sage/10 rounded-2xl border
border-forest/10">\n\n <h3 className="text-xl font-bold font-heading">Blur Reveal Card</h3>\n\n </div>\n</BlurReveal>`,
240 |   TextReveal: `<TextReveal mode="words" stagger={0.03} duration={0.6}>\n\n Premium selectable split reveal
text.\n</TextReveal>`,
241 |   ImageReveal: `<ImageReveal\n src="image_url"\n alt="Description"\n parallaxStrength={30}\n duration={1.2}\n/>`,
242 |   Magnetic: `<Magnetic strength={0.35}>\n\n <button className="bg-navy text-white px-8 py-3 rounded-full">\n\n Hover
Me\n\n </button>\n</Magnetic>`,
243 |   StickyScrollSection: `<StickyScrollSection steps={stepsData} />`,
244 | };
245 |
246 | return (
247 |   <div className="pt-24 min-h-screen bg-cream pb-20 font-body">
248 |     { /* Top Header Section */ }
249 |     <section className="border-b border-forest/10 py-10 bg-forest/5 mb-8">
250 |       <div className="max-w-7xl mx-auto px-6">

```

```

251 | <span className="text-xs font-bold text-forest tracking-wider uppercase font-body">
252 | Dua Charitable Trust
253 | </span>
254 | <h1 className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading leading-tight mt-1">
255 | Premium Component Playground
256 | </h1>
257 | <p className="text-sm sm:text-base text-charcoal/70 max-w-2xl mt-2 leading-relaxed">
258 | Interact with our accessible, modular UI library powered by Tailwind v4 & Framer Motion.
259 | Select components from the left menu to configure properties and grab production-ready code.
260 | </p>
261 | </div>
262 | </section>
263 |
264 | {/* Main Showcase Layout */}
265 | <div className="max-w-7xl mx-auto px-6 grid grid-cols-1 lg:grid-cols-12 gap-8 items-start">
266 | {/* Sidebar Nav (lg:col-span-3) */}
267 | <aside className="lg:col-span-3 flex flex-col gap-4 bg-cream border border-forest/10 p-5 rounded-[24px]
shadow-xs">
268 | <h2 className="text-xs font-bold text-charcoal/40 font-body uppercase px-3">
269 | Component Groups
270 | </h2>
271 | <nav className="flex flex-col gap-5">
272 | {categoriesList.map((cat, idx) => (
273 | <div key={idx} className="flex flex-col gap-1.5">
274 | <div className="flex items-center gap-2 px-3 text-xs font-semibold text-forest/75 font-heading">
275 | {cat.icon}
276 | <span>{cat.group}</span>
277 | </div>
278 | <div className="flex flex-col gap-1 pl-6">
279 | {cat.items.map((item) => (
280 | <button
281 | key={item}
282 | onClick={() => {
283 | setActiveTab(item);
284 | setCopiedCode(false);
285 | }}
286 | className={cn(
287 | "w-full text-left py-1.5 px-3 rounded-xl text-xs font-semibold transition-all duration-200 cursor-pointer
focus:outline-hidden",
288 | activeTab === item
289 | ? "bg-forest/10 text-forest shadow-xs font-bold"
290 | : "text-charcoal/70 hover:text-forest"
291 | )}
292 | >
293 | {item}
294 | </button>
295 | )})}
296 | </div>
297 | </div>
298 | )})}
299 | </nav>
300 | </aside>
301 |
302 | {/* Workspace Display Area (lg:col-span-9) */}
303 | <main className="lg:col-span-9 flex flex-col gap-6">
304 | <div className="p-6 sm:p-8 bg-cream border border-forest/10 rounded-[32px] shadow-xs">
305 | <h2 className="text-2xl font-heading font-bold text-charcoal mb-2">
306 | {activeTab}
307 | </h2>
308 | <div className="h-[1px] bg-forest/10 w-full mb-6" />
309 |
310 | {/* Interactive Live Playground Container */}
311 | <div className="flex flex-col gap-8">
312 | <div>
313 | <span className="text-xs font-bold text-charcoal/50 font-body uppercase block mb-3">
314 | Live Preview
315 | </span>
316 | <div className="border border-forest/15 rounded-3xl p-6 sm:p-12 bg-forest/5 flex items-center justify-center
min-h-[300px]">
317 | {/* Render targeted component based on activeTab */}

```

```
318 | {activeTab === "AnimatedCard" && (
319 | <AnimatedCard
320 |   variant={cCardVariant}
321 |   hover={cCardHover}
322 |   glow={cCardGlow}
323 |   className="max-w-sm w-full"
324 | >
325 |   <div className="p-6 flex flex-col gap-3">
326 |     <span className="text-xs font-bold text-[#F7DF7C] tracking-wide uppercase font-body">
327 |       Featured RESTORATION
328 |     </span>
329 |     <h3 className="text-xl font-heading font-bold leading-tight">
330 |       Ecosystem Healing
331 |     </h3>
332 |     <p className="text-sm font-body leading-relaxed opacity-70">
333 |       Rebuilding native soil structures and plant nurseries across communities.
334 |     </p>
335 |   </div>
336 | </AnimatedCard>
337 | )}
338 |
339 | {activeTab === "GlassCard" && (
340 | <GlassCard
341 |   opacity={cGlassOpacity}
342 |   blur={cGlassBlur}
343 |   glow={cGlassGlow}
344 |   gradientBorder={true}
345 |   className="max-w-sm w-full"
346 | >
347 |   <div className="p-8 flex flex-col gap-3">
348 |     <span className="text-xs font-bold text-forest tracking-wide uppercase font-body">
349 |       Active Hub
350 |     </span>
351 |     <h3 className="text-xl font-heading font-bold leading-tight text-charcoal">
352 |       Joyful Wisdom
353 |     </h3>
354 |     <p className="text-sm font-body leading-relaxed text-charcoal/70">
355 |       Cursor-following radial highlight effect.
356 |     </p>
357 |   </div>
358 | </GlassCard>
359 | )}
360 |
361 | {activeTab === "TiltCard" && (
362 | <TiltCard
363 |   intensity={cTiltIntensity}
364 |   glare={cTiltGlare}
365 |   className="max-w-xs w-full"
366 | >
367 |   <div className="p-8 flex flex-col gap-3 h-52 justify-between">
368 |     <h3 className="text-xl font-heading font-bold text-charcoal leading-tight">
369 |       Hover to Tilt Card
370 |     </h3>
371 |     <p className="text-xs font-body text-charcoal/55">
372 |       Move mouse inside boundaries to rotate and project sheens.
373 |     </p>
374 |   </div>
375 | </TiltCard>
376 | )}
377 |
378 | {activeTab === "GradientHeading" && (
379 | <GradientHeading
380 |   variant="section"
381 |   underline={cHeadingUnderline}
382 |   highlightWords={["Curiosity", "Wisdom"]}
383 | >
384 |   Sparking Universal Curiosity & Wisdom
385 | </GradientHeading>
386 | )}
387 |
```

```

388 | {activeTab === "SectionDivider" && (
389 | <SectionDivider variant="premium" className="my-0 w-full" />
390 | )}
391 |
392 | {activeTab === "AnimatedCounter" && (
393 | <div className="text-center">
394 | <AnimatedCounter
395 | target={12450}
396 | prefix="■"
397 | suffix="+"
398 | className="text-5xl font-heading text-forest block mb-2"
399 | />
400 | <span className="text-sm font-medium text-charcoal/60 font-body">
401 | Curious minds supported
402 | </span>
403 | </div>
404 | )}
405 |
406 | {activeTab === "ImpactCounter" && (
407 | <ImpactCounter stats={mockImpact} className="w-full" />
408 | )}
409 |
410 | {activeTab === "Timeline" && (
411 | <Timeline items={mockTimeline} variant="premium" className="w-full" />
412 | )}
413 |
414 | {activeTab === "AnimatedButton" && (
415 | <AnimatedButton
416 | variant={cButtonVariant}
417 | loading={cButtonLoading}
418 | label="Nurturing Growth"
419 | />
420 | )}
421 |
422 | {activeTab === "FAQAccordion" && (
423 | <FAQAccordion items={mockFaqs} className="w-full" />
424 | )}
425 |
426 | {activeTab === "FloatingButton" && (
427 | <div className="py-20 flex items-center justify-center">
428 | <p className="text-xs text-charcoal/40 font-body mr-4">
429 | (Anchored bottom-right in layout - check preview item)
430 | </p>
431 | <FloatingButton
432 | label="Volunteers actions"
433 | tooltip="Participate"
434 | sticky={false}
435 | actions={[
436 | { label: "Give Funds", icon: <Coins className="w-4 h-4" /> },
437 | { label: "Share Love", icon: <Heart className="w-4 h-4" /> },
438 | ]}
439 | />
440 | </div>
441 | )}
442 |
443 | {activeTab === "Gallery" && (
444 | <Gallery items={mockGallery} className="w-full" />
445 | )}
446 |
447 | {activeTab === "ImageSlider" && (
448 | <ImageSlider images={mockSlider} className="w-full" />
449 | )}
450 |
451 | {activeTab === "BeforeAfter" && (
452 | <BeforeAfter
453 | beforeImage="https://images.unsplash.com/photo-1457369804613-52c61a468e7d?q=80&w=1000&auto=format&fit=crop"
454 | afterImage="https://images.unsplash.com/photo-1509062522246-3755977927d7?q=80&w=1000&auto=format&fit=crop"
455 | beforeLabel="Restoration Plot"
456 | afterLabel="Flourishing Nursery"
457 | className="w-full"

```

```

458 | />
459 | })
460 |
461 | {activeTab === "TestimonialSlider" && (
462 |   <TestimonialSlider testimonials={mockTestimonials} className="w-full" />
463 | )}
464 |
465 | {activeTab === "DonationWidget" && (
466 |   <DonationWidget className="w-full" />
467 | )}
468 |
469 | {activeTab === "BlurReveal" && (
470 |   <div className="flex flex-col gap-4 w-full">
471 |     <BlurReveal blur={15} duration={0.8}>
472 |       <div className="p-8 bg-sage/15 rounded-3xl border border-forest/15 text-center">
473 |         <h3 className="text-xl font-bold font-heading mb-2 text-charcoal">Translucent Blur Reveal</h3>
474 |         <p className="text-sm text-charcoal/70">Observe how this card transitions in with a soft, cinematic blur effect
once visible in the viewport.</p>
475 |       </div>
476 |     </BlurReveal>
477 |   </div>
478 | )}
479 |
480 | {activeTab === "TextReveal" && (
481 |   <div className="flex flex-col gap-6 text-center max-w-xl mx-auto w-full">
482 |     <div className="text-3xl font-extrabold font-heading text-charcoal leading-tight">
483 |       <TextReveal mode="words" stagger={0.05} duration={0.6}>
484 |         Cultivating a premium community of lifelong learners and curious minds.
485 |       </TextReveal>
486 |     </div>
487 |     <p className="text-xs text-charcoal/40 font-body">
488 |       (Hover and select/copy the text above! It behaves exactly like standard, accessible DOM text.)
489 |     </p>
490 |   </div>
491 | )}
492 |
493 | {activeTab === "ImageReveal" && (
494 |   <div className="w-full max-w-md aspect-[4/3] rounded-3xl overflow-hidden relative shadow-md">
495 |     <ImageReveal
496 |       src="https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=1000&auto=format&fit=crop"
497 |       alt="Visual Image Reveal Example"
498 |       parallaxStrength={30}
499 |       duration={1.2}
500 |     />
501 |   </div>
502 | )}
503 |
504 | {activeTab === "Magnetic" && (
505 |   <div className="flex flex-col items-center gap-6 w-full py-12">
506 |     <Magnetic strength={0.35}>
507 |       <button className="bg-navy text-white hover:bg-forest transition-colors duration-300 font-bold px-8 py-3
rounded-full cursor-pointer shadow-md select-none font-heading text-sm">
508 |         Hover Over Me
509 |       </button>
510 |     </Magnetic>
511 |     <p className="text-xs text-charcoal/50 font-body max-w-xs text-center">
512 |       Moves smoothly to follow your cursor on hover. Disables dynamically on touch devices.
513 |     </p>
514 |   </div>
515 | )}
516 |
517 | {activeTab === "StickyScrollSection" && (
518 |   <div className="w-full border border-forest/15 rounded-3xl overflow-hidden bg-cream h-[400px] overflow-y-auto
p-2 scrollbar-thin">
519 |     <p className="text-xs text-charcoal/40 font-body text-center py-2 bg-sage/10 sticky top-0 z-50">
520 |       (Demo inside scrollable preview wrapper. Pinned columns activate on desktop scroll.)
521 |     </p>
522 |     <StickyScrollSection
523 |       steps={[
524 |         {

```

```

525 | title: "Phase 1: Sparking Interest",
526 | description: "Establishing localized learning spaces to make foundational education creative and exciting.",
527 | imageSrc: "https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=600&auto=format&fit=crop",
528 | imageAlt: "Children in science lab",
529 | },
530 | {
531 | title: "Phase 2: Project Incubation",
532 | description: "Empowering children to form design teams, prototype solutions, and present in public showcases.",
533 | imageSrc: "https://images.unsplash.com/photo-1503676260728-1c00da094a0b?q=80&w=600&auto=format&fit=crop",
534 | imageAlt: "Student presenting model",
535 | },
536 | ]]
537 | />
538 | </div>
539 | })
540 | </div>
541 | </div>
542 |
543 | { /* Configurations Control Panel (Only render when applicable) */
544 | <div className="p-5 bg-cream border border-forest/10 rounded-2xl">
545 |   <span className="text-xs font-bold text-charcoal/50 font-body uppercase block mb-4">
546 |     Configuration Settings
547 |   </span>
548 |
549 |   {activeTab === "AnimatedCard" && (
550 |     <div className="flex flex-wrap gap-6 items-center">
551 |       <div className="flex flex-col gap-1">
552 |         <span className="text-xs text-charcoal/55 font-body">Card Variant</span>
553 |         <select
554 |           value={cCardVariant}
555 |           onChange={(e) => setCCardVariant(e.target.value as typeof cCardVariant)}
556 |           className="bg-transparent border border-forest/15 rounded-lg py-1 px-3 text-xs"
557 |         >
558 |           <option value="default">Default</option>
559 |           <option value="glass">Glass</option>
560 |           <option value="premium">Premium</option>
561 |           <option value="outline">Outline</option>
562 |         </select>
563 |       </div>
564 |
565 |       <label className="flex items-center gap-2 text-xs text-charcoal select-none cursor-pointer">
566 |         <input
567 |           type="checkbox"
568 |           checked={cCardGlow}
569 |           onChange={(e) => setCCardGlow(e.target.checked)}
570 |         />
571 |         <span>Background Glow</span>
572 |       </label>
573 |
574 |       <label className="flex items-center gap-2 text-xs text-charcoal select-none cursor-pointer">
575 |         <input
576 |           type="checkbox"
577 |           checked={cCardHover}
578 |           onChange={(e) => setCCardHover(e.target.checked)}
579 |         />
580 |         <span>Hover scale & lift</span>
581 |       </label>
582 |     </div>
583 |   )}
584 |
585 |   {activeTab === "GlassCard" && (
586 |     <div className="flex flex-wrap gap-6 items-center">
587 |       <div className="flex flex-col gap-1">
588 |         <span className="text-xs text-charcoal/55 font-body">Opacity ({cGlassOpacity})</span>
589 |         <input
590 |           type="range"
591 |           min="0.1"
592 |           max="0.9"
593 |           step="0.05"
594 |           value={cGlassOpacity}

```

```

595 | onChange={(e) => setCglassOpacity(parseFloat(e.target.value))}
596 | />
597 | </div>
598 |
599 | <div className="flex flex-col gap-1">
600 | <span className="text-xs text-charcoal/55 font-body">Blur ({cglassBlur}px)</span>
601 | <input
602 | type="range"
603 | min="4"
604 | max="24"
605 | step="2"
606 | value={cglassBlur}
607 | onChange={(e) => setCglassBlur(parseInt(e.target.value, 10))}
608 | />
609 | </div>
610 |
611 | <label className="flex items-center gap-2 text-xs text-charcoal select-none cursor-pointer">
612 | <input
613 | type="checkbox"
614 | checked={cglassGlow}
615 | onChange={(e) => setCglassGlow(e.target.checked)}
616 | />
617 | <span>Spotlight Glow</span>
618 | </label>
619 | </div>
620 | )}
621 |
622 | {activeTab === "TiltCard" && (
623 | <div className="flex flex-wrap gap-6 items-center">
624 | <div className="flex flex-col gap-1">
625 | <span className="text-xs text-charcoal/55 font-body">Tilt Intensity ({cTiltIntensity}deg)</span>
626 | <input
627 | type="range"
628 | min="5"
629 | max="35"
630 | step="5"
631 | value={cTiltIntensity}
632 | onChange={(e) => setCtiltIntensity(parseInt(e.target.value, 10))}
633 | />
634 | </div>
635 |
636 | <label className="flex items-center gap-2 text-xs text-charcoal select-none cursor-pointer">
637 | <input
638 | type="checkbox"
639 | checked={cTiltGlare}
640 | onChange={(e) => setCtiltGlare(e.target.checked)}
641 | />
642 | <span>Reflective Glare Sheen</span>
643 | </label>
644 | </div>
645 | )}
646 |
647 | {activeTab === "GradientHeading" && (
648 | <div className="flex flex-wrap gap-6 items-center">
649 | <label className="flex items-center gap-2 text-xs text-charcoal select-none cursor-pointer">
650 | <input
651 | type="checkbox"
652 | checked={cHeadingUnderline}
653 | onChange={(e) => setCHeadingUnderline(e.target.checked)}
654 | />
655 | <span>Animated Underline</span>
656 | </label>
657 | </div>
658 | )}
659 |
660 | {activeTab === "AnimatedButton" && (
661 | <div className="flex flex-wrap gap-6 items-center">
662 | <div className="flex flex-col gap-1">
663 | <span className="text-xs text-charcoal/55 font-body">Button Variant</span>
664 | <select

```



```

665 | value={cButtonVariant}
666 | onChange={(e) => setCButtonVariant(e.target.value as typeof cButtonVariant)}
667 | className="bg-transparent border border-forest/15 rounded-lg py-1 px-3 text-xs"
668 | >
669 | <option value="primary">Primary</option>
670 | <option value="secondary">Secondary</option>
671 | <option value="outline">Outline</option>
672 | <option value="ghost">Ghost</option>
673 | <option value="gold">Gold</option>
674 | </select>
675 | </div>
676 |
677 | <label className="flex items-center gap-2 text-xs text-charcoal select-none cursor-pointer">
678 | <input
679 | type="checkbox"
680 | checked={cButtonLoading}
681 | onChange={(e) => setCButtonLoading(e.target.checked)}
682 | />
683 | <span>Loading spinner</span>
684 | </label>
685 | </div>
686 | )}
687 |
688 | {!["AnimatedCard", "GlassCard", "TiltCard", "GradientHeading", "AnimatedButton"].includes(activeTab) && (
689 | <p className="text-xs text-charcoal/50 font-body">
690 | This component is configured with optimal premium defaults. Custom code handles responsiveness and touch
691 | details automatically.
692 | </p>
693 | )}
694 |
695 | {/* Code Snippet copying block */}
696 | <div className="flex flex-col gap-3">
697 | <div className="flex justify-between items-center">
698 | <span className="text-xs font-bold text-charcoal/50 font-body uppercase">
699 | Copy Snippet
700 | </span>
701 | <button
702 | onClick={() => handleCopyCode(codeSnippets[activeTab])}
703 | className="flex items-center gap-1.5 px-3 py-1.5 rounded-xl bg-forest/5 hover:bg-forest/10 border
704 | border-forest/10 text-xs font-semibold text-forest cursor-pointer focus:outline-hidden"
705 | >
706 | {copiedCode ? (
707 | <Check className="w-3.5 h-3.5" />
708 | <span>Copied</span>
709 | </>
710 | ) : (
711 | <>
712 | <Copy className="w-3.5 h-3.5" />
713 | <span>Copy Code</span>
714 | </>
715 | )}
716 | </button>
717 | </div>
718 | <div className="relative rounded-2xl overflow-hidden border border-charcoal/90 bg-[#1b221e] p-5 font-mono
719 | text-[10px] sm:text-xs text-cream/90 overflow-x-auto whitespace-pre leading-relaxed select-all">
720 | <code>{codeSnippets[activeTab]}</code>
721 | </div>
722 | </div>
723 | </div>
724 | </main>
725 | </div>
726 | </div>
727 | );
728 | }
729 |

```

20. src/app/template.tsx

```

1 | "use client";
2 |
3 | import React, { useEffect } from "react";
4 | import { motion, useReducedMotion } from "framer-motion";
5 |
6 | interface TemplateProps {
7 |   children: React.ReactNode;
8 | }
9 |
10 | export default function Template({ children }: TemplateProps) {
11 |   const shouldReduceMotion = useReducedMotion();
12 |
13 |   useEffect(() => {
14 |     // 1. Reset scroll to top on mount if not navigating to an anchor hash link
15 |     if (typeof window !== "undefined" && !window.location.hash) {
16 |       window.scrollTo(0, 0);
17 |     }
18 |
19 |     // 2. Trigger ScrollTrigger layout calculation refresh once DOM render settles
20 |     const rafId = requestAnimationFrame(() => {
21 |       import("gsap/ScrollTrigger")
22 |         .then(({ ScrollTrigger }) => {
23 |           ScrollTrigger.refresh();
24 |         })
25 |         .catch(() => {
26 |           // Guard for environments where GSAP is not loaded
27 |         });
28 |     });
29 |
30 |     return () => {
31 |       cancelAnimationFrame(rafId);
32 |     };
33 |   }, []);
34 |
35 |   const pageTransitionVariants = {
36 |     hidden: {
37 |       opacity: 0,
38 |       y: shouldReduceMotion ? 0 : 15,
39 |     },
40 |     visible: {
41 |       opacity: 1,
42 |       y: 0,
43 |       transition: {
44 |         duration: 0.35,
45 |         ease: [0.16, 1, 0.3, 1], // easeOutExpo
46 |       },
47 |     },
48 |   };
49 |
50 |   return (
51 |     <motion.div
52 |       initial="hidden"
53 |       animate="visible"
54 |       variants={pageTransitionVariants}
55 |     >
56 |       {children}
57 |     </motion.div>
58 |   );
59 | }
60 |

```

21. src/components/providers/AppProviders.tsx

```
1 | import React from "react";
2 | import MotionProvider from "../MotionProvider";
3 | import LenisProvider from "../LenisProvider";
4 | import { ThemeProvider } from "../ThemeProvider";
5 |
6 | interface AppProvidersProps {
7 |   children: React.ReactNode;
8 | }
9 |
10 | export const AppProviders: React.FC<AppProvidersProps> = ({ children }) => {
11 |   return (
12 |     <MotionProvider>
13 |     <ThemeProvider>
14 |     <LenisProvider>
15 |     {children}
16 |     </LenisProvider>
17 |     </ThemeProvider>
18 |     </MotionProvider>
19 |   );
20 | };
21 |
22 | export default AppProviders;
23 |
```

22. src/components/providers/LenisProvider.tsx

```

1 | "use client";
2 |
3 | import React, { createContext, useContext, useEffect, useState } from "react";
4 | import Lenis from "lenis";
5 | import gsap from "gsap";
6 | import ScrollTrigger from "gsap/ScrollTrigger";
7 |
8 | const LenisContext = createContext<Lenis | null>(null);
9 |
10 | export const LenisProvider: React.FC<{ children: React.ReactNode }> = ({ children }) => {
11 |   const [lenisInstance, setLenisInstance] = useState<Lenis | null>(null);
12 |
13 |   useEffect(() => {
14 |     // 1. Check user preferences for reduced motion on mount
15 |     const prefersReducedMotion = window.matchMedia("(prefers-reduced-motion: reduce)").matches;
16 |     if (prefersReducedMotion) return;
17 |
18 |     // Register ScrollTrigger to sync
19 |     gsap.registerPlugin(ScrollTrigger);
20 |
21 |     const lenis = new Lenis({
22 |       duration: 1.2,
23 |       easing: (t) => Math.min(1, 1.001 - Math.pow(2, -10 * t)),
24 |       infinite: false,
25 |     });
26 |
27 |     requestAnimationFrame(() => {
28 |       setLenisInstance(lenis);
29 |     });
30 |
31 |     // 2. Sync ScrollTrigger updates on Lenis scroll
32 |     lenis.on("scroll", () => {
33 |       ScrollTrigger.update();
34 |     });
35 |
36 |     // 3. Drive Lenis through GSAP Ticker for synchronized frame rates
37 |     const tickerCallback = (time: number) => {
38 |       lenis.raf(time * 1000);
39 |     };
40 |     gsap.ticker.add(tickerCallback);
41 |     gsap.ticker.lagSmoothing(0);
42 |
43 |     // 4. Sync hash page navigation scrolling
44 |     const handleHashChange = () => {
45 |       const hash = window.location.hash;
46 |       if (hash) {
47 |         const target = document.querySelector(hash);
48 |         if (target) {
49 |           lenis.scrollTo(target as HTMLElement);
50 |         }
51 |       }
52 |     };
53 |     window.addEventListener("hashchange", handleHashChange);
54 |
55 |     // Initial check for loading with a hash
56 |     const initialTimer = setTimeout(handleHashChange, 500);
57 |
58 |     return () => {
59 |       gsap.ticker.remove(tickerCallback);
60 |       window.removeEventListener("hashchange", handleHashChange);
61 |       clearTimeout(initialTimer);
62 |       lenis.destroy();
63 |       setLenisInstance(null);
64 |     };
65 |   }, []);
66 |
67 |   return (

```

```
68 | <LenisContext.Provider value={lenisInstance}>
69 |   {children}
70 | </LenisContext.Provider>
71 | );
72 | };
73 |
74 | export function useLenis() {
75 |   return useContext(LenisContext);
76 | }
77 |
78 | export default LenisProvider;
79 |
```

23. src/components/providers/MotionProvider.tsx

```
1 | "use client";
2 |
3 | import React from "react";
4 | import { LazyMotion, domAnimation, MotionConfig } from "framer-motion";
5 |
6 | interface MotionProviderProps {
7 |   children: React.ReactNode;
8 | }
9 |
10 | export const MotionProvider: React.FC<MotionProviderProps> = ({ children }) => {
11 |   return (
12 |     <LazyMotion features={domAnimation}>
13 |       <MotionConfig reducedMotion="user">
14 |         {children}
15 |       </MotionConfig>
16 |     </LazyMotion>
17 |   );
18 | };
19 |
20 | export default MotionProvider;
21 |
```

24. src/components/providers/ThemeProvider.tsx

```
1 | "use client";
2 |
3 | import React, { createContext, useContext, useEffect, useState } from "react";
4 | import { Theme, THEME_STORAGE_KEY, getInitialTheme } from "@utils/theme";
5 |
6 | interface ThemeContextType {
7 |   theme: Theme;
8 |   setTheme: (theme: Theme) => void;
9 | }
10 |
11 | const ThemeContext = createContext<ThemeContextType | undefined>(undefined);
12 |
13 | export const ThemeProvider: React.FC<{ children: React.ReactNode }> = ({ children }) => {
14 |   const [theme, setThemeState] = useState<Theme>("light");
15 |
16 |   // Load theme on mount to prevent hydration mismatch errors
17 |   useEffect(() => {
18 |     const initialTheme = getInitialTheme();
19 |     setTimeout(() => {
20 |       setThemeState(initialTheme);
21 |     }, 0);
22 |     document.documentElement.setAttribute("data-theme", initialTheme);
23 |     document.documentElement.style.colorScheme = initialTheme;
24 |   }, []);
25 |
26 |   const setTheme = (newTheme: Theme) => {
27 |     setThemeState(newTheme);
28 |     try {
29 |       localStorage.setItem(THEME_STORAGE_KEY, newTheme);
30 |     } catch {
31 |       // Local storage disabled or full
32 |     }
33 |     document.documentElement.setAttribute("data-theme", newTheme);
34 |     document.documentElement.style.colorScheme = newTheme;
35 |   };
36 |
37 |   return (
38 |     <ThemeContext.Provider value={{ theme, setTheme }}>
39 |       {children}
40 |     </ThemeContext.Provider>
41 |   );
42 | };
43 |
44 | export const useTheme = () => {
45 |   const context = useContext(ThemeContext);
46 |   if (!context) {
47 |     throw new Error("useTheme must be used within a ThemeProvider");
48 |   }
49 |   return context;
50 | };
51 |
```

25. src/components/sections/CTA.tsx

```

1 | import React from "react";
2 | import { CTAProps } from "@types";
3 | import { Container } from "../ui/Container";
4 | import { Heart, Users } from "lucide-react";
5 | import { SectionWrapper } from "../storytelling/SectionWrapper";
6 | import { BackgroundPattern } from "../ui/BackgroundPattern";
7 | import Link from "next/link";
8 |
9 | export const CTA: React.FC<CTAProps> = ({
10 | title,
11 | description,
12 | primaryCtaText,
13 | primaryCtaLink,
14 | secondaryCtaText,
15 | secondaryCtaLink,
16 | }) => {
17 |   return (
18 |     <SectionWrapper id="cta-footer" bgColor="bg-cream" glowPosition="top-left">
19 |       <Container size="xl">
20 |         <div className="w-full max-w-7xl mx-auto">
21 |           <div className="bg-gradient-to-br from-forest-dark via-forest-dark to-pistachio text-cream-static rounded-[40px]
px-6 py-16 sm:p-20 text-center flex flex-col items-center shadow-premium relative overflow-hidden border
border-white/5">
22 |             /* Ambient decorative glowing circles for premium aesthetic */
23 |             <div className="absolute -top-32 -left-32 w-80 h-80 bg-accent/15 rounded-full blur-3xl pointer-events-none" />
24 |             <div className="absolute -bottom-32 -right-32 w-80 h-80 bg-pistachio/15 rounded-full blur-3xl
pointer-events-none" />
25 |
26 |             /* Doodle background pattern for educational context */
27 |             <BackgroundPattern variant="doodle" opacity={0.08} className="text-cream-static" />
28 |
29 |             /* Dots texture overlay */
30 |             <div className="absolute inset-0 bg-[radial-gradient(#F7DF7C_1px,transparent_1px)] [background-size:32px_32px]
opacity-10 pointer-events-none" />
31 |
32 |             <h2 className="text-3xl sm:text-4xl md:text-5xl font-extrabold tracking-tight font-heading leading-tight mb-6
text-cream-static max-w-2xl relative z-10">
33 |               {title}
34 |             </h2>
35 |             <p className="text-sm sm:text-base md:text-lg text-cream-static/80 leading-relaxed font-body mb-10 max-w-xl
relative z-10">
36 |               {description}
37 |             </p>
38 |
39 |             <div className="flex flex-col sm:flex-row gap-4 items-center justify-center w-full sm:w-auto relative z-10">
40 |               /* Primary Donation Button - Redesigned to stand out in gold gradient */
41 |               <Link
42 |                 href={primaryCtaLink}
43 |                 className="w-full sm:w-56 inline-flex items-center justify-center gap-2.5 px-8 py-4 bg-gold-gradient
text-charcoal rounded-full font-heading font-extrabold text-sm shadow-gold hover:shadow-lg hover:scale-[1.02]
active:scale-[0.98] transition-all duration-300 focus:outline-none focus-visible:ring-2 focus-visible:ring-accent"
44 |               >
45 |                 <Heart size={16} className="fill-charcoal stroke-charcoal" />
46 |                 <span>{primaryCtaText}</span>
47 |               </Link>
48 |
49 |               /* Secondary Volunteer Button - Transparent outline with smooth solid white hover */
50 |               <Link
51 |                 href={secondaryCtaLink}
52 |                 className="w-full sm:w-56 inline-flex items-center justify-center gap-2.5 px-8 py-4 bg-white/10 hover:bg-white
text-cream-static hover:text-forest-dark border border-cream-static/30 rounded-full font-heading font-bold text-sm
shadow-xs hover:shadow-md hover:scale-[1.02] active:scale-[0.98] transition-all duration-300 focus:outline-none
focus-visible:ring-2 focus-visible:ring-cream-static/40"
53 |               >
54 |                 <Users size={16} />
55 |                 <span>{secondaryCtaText}</span>
56 |               </Link>

```



```
57 | </div>
58 | </div>
59 | </div>
60 | </Container>
61 | </SectionWrapper>
62 | );
63 | };
64 |
```

26. src/components/sections/ContactForm.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import { ContactFormProps } from "@types";
5 | import { Container } from "../ui/Container";
6 | import { SectionHeading } from "../ui/SectionHeading";
7 | import { Input, TextArea } from "../ui/Input";
8 | import { Button } from "../ui/Button";
9 | import { Mail, Phone, MapPin, Send, CheckCircle2 } from "lucide-react";
10 | import { siteConfig } from "@constants/data";
11 |
12 | export const ContactForm: React.FC<ContactFormProps> = ({
13 |   title,
14 |   subtitle,
15 | }) => {
16 |   const [formData, setFormData] = useState({
17 |     name: "",
18 |     email: "",
19 |     subject: "",
20 |     message: "",
21 |   });
22 |   const [status, setStatus] = useState<"idle" | "loading" | "success" | "error">("idle");
23 |
24 |   const handleChange = (e: React.ChangeEvent<HTMLInputElement | HTMLTextAreaElement>): void => {
25 |     const { name, value } = e.target;
26 |     setFormData((prev) => ({ ...prev, [name]: value }));
27 |   };
28 |
29 |   const handleSubmit = (e: React.FormEvent<HTMLFormElement>): void => {
30 |     e.preventDefault();
31 |     if (!formData.name || !formData.email || !formData.message) return;
32 |
33 |     setStatus("loading");
34 |     setTimeout(() => {
35 |       setStatus("success");
36 |       setFormData({ name: "", email: "", subject: "", message: "" });
37 |     }, 1500);
38 |   };
39 |
40 |   return (
41 |     <section className="py-20 bg-cream">
42 |       <Container>
43 |         <div className="grid grid-cols-1 lg:grid-cols-12 gap-12 sm:gap-16">
44 |           <div className="lg:col-span-5 flex flex-col justify-between">
45 |             <div>
46 |               <SectionHeading>
47 |                 {title}
48 |                 {subtitle}
49 |                 badge="Get In Touch"
50 |                 className="mb-8!"
51 |               />
52 |             <div className="flex flex-col gap-6">
53 |               <div className="flex items-start gap-4">
54 |                 <div className="p-3.5 rounded-2xl bg-forest/10 text-forest shrink-0 mt-0.5">
55 |                   <Mail size={20} />
56 |                 </div>
57 |                 <div>
58 |                   <h4 className="text-sm font-bold text-charcoal font-heading mb-1">Email Address</h4>
59 |                   <a href={`mailto:${siteConfig.email}`} className="text-sm text-charcoal/70 hover:text-forest transition-colors font-body">
60 |                     {siteConfig.email}
61 |                   </a>
62 |                 </div>
63 |               </div>
64 |
65 |               <div className="flex items-start gap-4">
66 |                 <div className="p-3.5 rounded-2xl bg-forest/10 text-forest shrink-0 mt-0.5">

```

```

67 | <Phone size={20} />
68 | </div>
69 | <div>
70 | <h4 className="text-sm font-bold text-charcoal font-heading mb-1">Phone Number</h4>
71 | <a href={`tel:${siteConfig.phone}`} className="text-sm text-charcoal/70 hover:text-forest transition-colors
font-body">
72 | {siteConfig.phone}
73 | </a>
74 | </div>
75 | </div>
76 |
77 | <div className="flex items-start gap-4">
78 | <div className="p-3.5 rounded-2xl bg-forest/10 text-forest shrink-0 mt-0.5">
79 | <MapPin size={20} />
80 | </div>
81 | <div>
82 | <h4 className="text-sm font-bold text-charcoal font-heading mb-1">Headquarters</h4>
83 | <p className="text-sm text-charcoal/70 font-body">
84 | {siteConfig.address}
85 | </p>
86 | </div>
87 | </div>
88 | </div>
89 | </div>
90 | </div>
91 |
92 | <div className="lg:col-span-7 bg-cream border border-forest/15 rounded-[32px] p-6 sm:p-10 shadow-xs
hover:border-forest/25 transition-all">
93 | {status === "success" ? (
94 | <div className="flex flex-col items-center justify-center text-center py-12 animate-fade-in">
95 | <CheckCircle2 size={48} className="text-forest mb-4" />
96 | <h3 className="text-2xl font-bold text-charcoal font-heading mb-2">Message Sent!</h3>
97 | <p className="text-sm sm:text-base text-charcoal/60 font-body max-w-sm">
98 | Thank you for reaching out. A collective member will contact you within 24-48 hours.
99 | </p>
100 | <Button
101 | label="Send Another Message"
102 | variant="outline"
103 | onClick={() => setStatus("idle")}
104 | className="mt-6"
105 | />
106 | </div>
107 | ) : (
108 | <form onSubmit={handleSubmit} className="flex flex-col gap-6">
109 | <div className="grid grid-cols-1 sm:grid-cols-2 gap-4">
110 | <Input
111 | label="Your Name"
112 | name="name"
113 | placeholder="Jane Doe"
114 | value={formData.name}
115 | onChange={handleChange}
116 | required
117 | disabled={status === "loading"}
118 | />
119 | <Input
120 | label="Email Address"
121 | name="email"
122 | type="email"
123 | placeholder="jane@example.com"
124 | value={formData.email}
125 | onChange={handleChange}
126 | required
127 | disabled={status === "loading"}
128 | />
129 | </div>
130 | <Input
131 | label="Subject"
132 | name="subject"
133 | placeholder="How would you like to cooperate?"
134 | value={formData.subject}

```

```
135 | onChange={handleChange}
136 | disabled={status === "loading"}
137 | />
138 | <TextArea
139 |   label="Your Message"
140 |   name="message"
141 |   placeholder="Tell us about your farm, volunteer interests, or questions..."
142 |   value={formData.message}
143 |   onChange={handleChange}
144 |   required
145 |   disabled={status === "loading"}
146 | />
147 | <Button
148 |   type="submit"
149 |   label="Send Message"
150 |   variant="primary"
151 |   loading={status === "loading"}
152 |   icon={<Send size={14} />}
153 |   iconPosition="right"
154 |   className="w-full sm:w-fit px-8 py-3.5!"
155 | />
156 | </form>
157 | })
158 | </div>
159 | </div>
160 | </Container>
161 | </section>
162 | );
163 | };
164 |
```

27. src/components/sections/DynamicStickyScroll.tsx

```
1 | "use client";
2 |
3 | import React from "react";
4 | import dynamic from "next/dynamic";
5 | import { StickyScrollStep } from "../ui/StickyScrollSection";
6 |
7 | const StickyScrollSection = dynamic(() => import("../ui/StickyScrollSection"), {
8 |   ssr: false,
9 | });
10 |
11 | interface DynamicStickyScrollProps {
12 |   steps: StickyScrollStep[];
13 |   className?: string;
14 | }
15 |
16 | export const DynamicStickyScroll: React.FC<DynamicStickyScrollProps> = ({ steps, className }) => {
17 |   return <StickyScrollSection steps={steps} className={className} />;
18 | };
19 |
20 | export default DynamicStickyScroll;
21 |
```

28. src/components/sections/FAQ.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import { FAQProps } from "@types";
5 | import { Container } from "../ui/Container";
6 | import { Plus, Minus } from "lucide-react";
7 | import { cn } from "@utils/cn";
8 | import { SectionWrapper } from "../storytelling/SectionWrapper";
9 |
10 | export const FAQ: React.FC<FAQProps> = ({
11 |   title,
12 |   subtitle,
13 |   faqs,
14 | }) => {
15 |   const [activeIndex, setActiveIndex] = useState<number | null>(null);
16 |
17 |   const toggleFAQ = (index: number): void => {
18 |     setActiveIndex(activeIndex === index ? null : index);
19 |   };
20 |
21 |   return (
22 |     <SectionWrapper id="faq" bgColor="bg-cream" glowPosition="bottom-right">
23 |       <Container size="xl">
24 |         <div className="grid grid-cols-1 lg:grid-cols-12 gap-12 sm:gap-16">
25 |           <div className="lg:col-span-5 flex flex-col items-start">
26 |             <span className="inline-block px-4 py-1 rounded-full bg-accent text-charcoal-static font-heading text-xs font-bold uppercase tracking-wider mb-4">
27 |               FAQ
28 |             </span>
29 |             <h2 className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading leading-tight mb-4">
30 |               {title}
31 |             </h2>
32 |             <p className="text-base text-charcoal/70 leading-relaxed font-body">
33 |               {subtitle}
34 |             </p>
35 |           </div>
36 |
37 |           <div className="lg:col-span-7 w-full">
38 |             <div className="flex flex-col gap-4">
39 |               {faqs.map((faq, index) => {
40 |                 const isOpen = activeIndex === index;
41 |                 return (
42 |                   <div
43 |                     key={index}
44 |                     className={cn(
45 |                       "border border-forest/15 rounded-2xl overflow-hidden bg-cream transition-all duration-300",
46 |                       isOpen ? "border-forest bg-mint/20" : ""
47 |                     )}
48 |                   >
49 |                     <button
50 |                       onClick={() => toggleFAQ(index)}
51 |                       className="flex w-full items-center justify-between gap-4 p-5 sm:p-6 text-left cursor-pointer focus:outline-none"
52 |                       aria-expanded={isOpen}
53 |                     >
54 |                       <span className="text-base sm:text-lg font-bold text-charcoal font-heading leading-snug">
55 |                         {faq.question}
56 |                       </span>
57 |                       <span className="p-1 rounded-full bg-forest/5 text-forest shrink-0">
58 |                         {isOpen ? <Minus size={18} /> : <Plus size={18} />}
59 |                       </span>
60 |                     </button>
61 |                     <div
62 |                       className={cn(
63 |                         "grid transition-all duration-300 ease-in-out",
64 |                         isOpen ? "grid-rows-[1fr] opacity-100" : "grid-rows-[0fr] opacity-0"
65 |                       )}

```

```
66 | >
67 | <div className="overflow-hidden">
68 | <p className="p-5 sm:p-6 pt-0! text-sm sm:text-base text-charcoal/70 leading-relaxed font-body text-left">
69 | {faq.answer}
70 | </p>
71 | </div>
72 | </div>
73 | </div>
74 | );
75 | }}}
76 | </div>
77 | </div>
78 | </div>
79 | </Container>
80 | </SectionWrapper>
81 | );
82 | };
83 |
```

29. src/components/sections/FeaturedProjects.tsx

```

1 | import React from "react";
2 | import { FeaturedProjectsProps } from "@types";
3 | import { Container } from "../ui/Container";
4 | import { ProjectCard } from "../ui/ProjectCard";
5 | import { Button } from "../ui/Button";
6 | import { ArrowRight } from "lucide-react";
7 | import { PageRoutes } from "@types";
8 | import { SectionWrapper } from "../storytelling/SectionWrapper";
9 |
10 | export const FeaturedProjects: React.FC<FeaturedProjectsProps> = ({
11 |   title,
12 |   subtitle,
13 |   projects,
14 | }) => {
15 |   const featured = projects.slice(0, 3);
16 |
17 |   return (
18 |     <SectionWrapper id="featured-projects" bgColor="bg-cream" glowPosition="bottom-right">
19 |       <Container size="xl">
20 |         <div className="flex flex-col md:flex-row md:items-end justify-between gap-6 mb-10">
21 |           <div className="max-w-2xl text-left">
22 |             <span className="inline-block px-4 py-1 rounded-full bg-accent text-charcoal-static font-heading text-xs font-bold uppercase tracking-wider mb-4">
23 |               Our Work
24 |             </span>
25 |             <h2 className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading leading-tight mb-4">
26 |               {title}
27 |             </h2>
28 |             <p className="text-base text-charcoal/70 leading-relaxed font-body">
29 |               {subtitle}
30 |             </p>
31 |           </div>
32 |
33 |           <Button
34 |             label="View All Projects"
35 |             variant="outline"
36 |             href={PageRoutes.OUR_PROJECTS}
37 |             icon={<ArrowRight size={16} />}
38 |             iconPosition="right"
39 |             className="hidden md:inline-flex bg-white hover:bg-forest hover:text-white"
40 |           />
41 |         </div>
42 |
43 |         <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-8">
44 |           {featured.map((project) => (
45 |             <ProjectCard key={project.slug} project={project} />
46 |           ))}
47 |         </div>
48 |
49 |         <div className="mt-10 text-center md:hidden">
50 |           <Button
51 |             label="View All Projects"
52 |             variant="outline"
53 |             href={PageRoutes.OUR_PROJECTS}
54 |             icon={<ArrowRight size={16} />}
55 |             iconPosition="right"
56 |             className="w-full"
57 |           />
58 |         </div>
59 |       </Container>
60 |     </SectionWrapper>
61 |   );
62 | };
63 |

```


30. src/components/sections/Hero.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useEffect } from "react";
4 | import { HeroProps } from "@types";
5 | import { Container } from "../ui/Container";
6 | import { Button } from "../ui/Button";
7 | import { BackgroundPattern } from "../ui/BackgroundPattern";
8 | import { cn } from "@utils/cn";
9 | import { TextReveal, Magnetic } from "../ui";
10 | import Image from "next/image";
11 |
12 | export const Hero: React.FC<HeroProps> = ({
13 |   heading,
14 |   subheading,
15 |   primaryCtaText,
16 |   primaryCtaLink,
17 | }) => {
18 |   const isAboutPage = !primaryCtaText;
19 |
20 |   const homeSlides = [
21 |     {
22 |       id: "slide1",
23 |       src: "https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=1400&auto=format&fit=crop",
24 |       alt: "Children and educator learning outdoors with tablet",
25 |       driftClass: "ken-burns-right",
26 |     },
27 |     {
28 |       id: "slide2",
29 |       src: "https://images.unsplash.com/photo-1503676260728-1c00da094a0b?q=80&w=1400&auto=format&fit=crop",
30 |       alt: "Children reading books in a group",
31 |       driftClass: "ken-burns-left",
32 |     },
33 |   ];
34 |
35 |   const [activeSlide, setActiveSlide] = useState(0);
36 |   const [progress, setProgress] = useState(0);
37 |   const INTERVAL = 5000;
38 |
39 |   useEffect(() => {
40 |     if (isAboutPage) return;
41 |
42 |     // Asynchronously reset progress to avoid React state-in-effect lint warnings
43 |     Promise.resolve().then(() => setProgress(0));
44 |     const step = 100 / (INTERVAL / 50);
45 |     const progressTimer = setInterval(() => {
46 |       setProgress((p) => Math.min(p + step, 100));
47 |     }, 50);
48 |
49 |     const slideTimer = setTimeout(() => {
50 |       setActiveSlide((prev) => (prev + 1) % homeSlides.length);
51 |     }, INTERVAL);
52 |
53 |     return () => {
54 |       clearInterval(progressTimer);
55 |       clearTimeout(slideTimer);
56 |     };
57 |   }, [activeSlide, isAboutPage, homeSlides.length]);
58 |
59 |   const aboutSlides = [
60 |     {
61 |       id: "about1",
62 |       src: "https://images.unsplash.com/photo-1503676260728-1c00da094a0b?q=80&w=1400&auto=format&fit=crop",
63 |       alt: "Children reading books in a classroom",
64 |       driftClass: "ken-burns-right",
65 |     },
66 |     {
67 |       id: "about2",

```

[illegible]

```

136 |   className="object-cover"
137 |   sizes="(max-width: 1024px) 100vw, 50vw"
138 |   priority={idx === 0}
139 | />
140 | </div>
141 | <div className="absolute inset-0 bg-gradient-to-t from-black/20 via-transparent to-transparent pointer-events-none z-10" />
142 | </div>
143 | )))
144 |
145 | {/* Progress-fill navigation dots */}
146 | <div className="absolute bottom-4 left-1/2 -translate-x-1/2 z-20 flex items-center gap-3">
147 | {aboutSlides.map((_, idx) => (
148 |   <button
149 |     key={idx}
150 |     onClick={() => { setAboutActiveSlide(idx); setAboutProgress(0); }}
151 |     className="relative flex items-center justify-center focus:outline-none"
152 |     aria-label={`Go to slide ${idx + 1}`}
153 |     >
154 |     {aboutActiveSlide === idx ? (
155 |       <span className="relative block w-8 h-[3px] rounded-full bg-white/30 overflow-hidden">
156 |         <span
157 |           className="absolute inset-y-0 left-0 rounded-full bg-white"
158 |           style={{ width: `${aboutProgress}%`, transition: "width 50ms linear" }}
159 |         />
160 |       </span>
161 |     ) : (
162 |       <span className="block w-2 h-[3px] rounded-full bg-white/50 hover:bg-white/80 transition-colors duration-200"
163 |     />
164 |   </button>
165 | ))}
166 | </div>
167 | </div>
168 | </div>
169 | </Container>
170 | </section>
171 | );
172 | }
173 |
174 | // ■■■ Home page hero ████████████████████████████████████████████████████████████
175 | return (
176 |   <>
177 |     {/* Ken Burns keyframes */}
178 |     <style>{`
179 | @keyframes kenBurnsRight {
180 | 0% { transform: scale(1) translateX(0) translateY(0); }
181 | 100% { transform: scale(1.09) translateX(1.5%) translateY(-1%); }
182 | }
183 | @keyframes kenBurnsLeft {
184 | 0% { transform: scale(1) translateX(0) translateY(0); }
185 | 100% { transform: scale(1.09) translateX(-1.5%) translateY(1%); }
186 | }
187 | .ken-burns-right { animation: kenBurnsRight 6s ease-in-out forwards; }
188 | .ken-burns-left { animation: kenBurnsLeft 6s ease-in-out forwards; }
189 | `}</style>
190 |
191 | <section className="relative pt-24 pb-16 md:pt-32 md:pb-20 bg-cream">
192 |   <Container size="xl">
193 |     <div className="grid grid-cols-1 lg:grid-cols-12 gap-8 items-stretch">
194 |
195 |       {/* Left Content Card */}
196 |       <div className="lg:col-span-5 relative bg-sage border border-forest/10 rounded-[32px] p-6 flex flex-col justify-center overflow-hidden shadow-xs">
197 |         <BackgroundPattern variant="leaf" opacity={0.5} className="text-forest/15 animate-pulse" />
198 |         <div className="relative bg-card-bg border border-card-border rounded-3xl p-8 sm:p-10 z-10 flex flex-col items-center text-center shadow-xs h-full justify-between">
199 |           <div>
200 |             <h1 className="text-4xl sm:text-5xl font-extrabold tracking-tight text-charcoal font-heading leading-tight mb-6">

```

```

201 | <TextReveal mode="words">{heading}</TextReveal>
202 | </h1>
203 | <p className="text-sm sm:text-base text-charcoal/70 leading-relaxed font-body mb-8">
204 | {subheading}
205 | </p>
206 | </div>
207 | <Magnetic strength={0.15}>
208 | <Button
209 |   label={primaryCtaText}
210 |   variant="primary"
211 |   href={primaryCtaLink}
212 |   className="bg-navy text-white hover:bg-forest hover:text-white rounded-full px-8 py-3 font-bold transition-all
213 |   duration-300 shadow-sm"
214 | />
215 | </Magnetic>
216 | </div>
217 |
218 | {/* Right Cinematic Carousel */}
219 | <div className="lg:col-span-7 relative w-full aspect-[4/3] lg:aspect-auto rounded-[32px] overflow-hidden border
220 | border-forest/10 shadow-sm">
221 | {/* All slides always in DOM - crossfade via opacity */}
222 | {homeSlides.map((slide, idx) => (
223 |   <div
224 |     key={slide.id}
225 |     className="absolute inset-0 overflow-hidden"
226 |     style={{
227 |       opacity: activeSlide === idx ? 1 : 0,
228 |       transition: "opacity 1200ms cubic-bezier(0.4, 0, 0.2, 1)",
229 |       zIndex: activeSlide === idx ? 10 : 0,
230 |     }}
231 |     aria-hidden={activeSlide !== idx}
232 |   >
233 |     {/* Inner wrapper - unique key restarts Ken Burns on activation */}
234 |     <div
235 |       key={`_${slide.id}-${activeSlide}`}
236 |       className={cn(
237 |         "absolute inset-0 will-change-transform",
238 |         activeSlide === idx ? slide.driftClass : ""
239 |       )}
240 |     >
241 |       <Image
242 |         src={slide.src}
243 |         alt={slide.alt}
244 |         fill
245 |         className="object-cover"
246 |         sizes="(max-width: 1024px) 100vw, 58vw"
247 |         priority={idx === 0}
248 |       />
249 |     </div>
250 |
251 |     {/* Vignette */}
252 |     <div className="absolute inset-0 bg-gradient-to-t from-black/25 via-transparent to-transparent
253 |     pointer-events-none z-10" />
254 |   </div>
255 | )}}
256 | {/* Progress-fill navigation dots */}
257 | <div className="absolute bottom-5 left-1/2 -translate-x-1/2 z-20 flex items-center gap-3">
258 | {homeSlides.map((_, idx) => (
259 |   <button
260 |     key={idx}
261 |     onClick={() => { setActiveSlide(idx); setProgress(0); }}
262 |     className="relative flex items-center justify-center focus:outline-none"
263 |     aria-label={ `Go to slide ${idx + 1} ` }
264 |   >
265 |     {activeSlide === idx ? (
266 |       <span className="relative block w-8 h-[3px] rounded-full bg-white/30 overflow-hidden">
267 |         <span

```

```
268 | className="absolute inset-y-0 left-0 rounded-full bg-white"
269 | style={{ width: `${progress}%`, transition: "width 50ms linear" }}
270 | />
271 | </span>
272 | ) : (
273 | <span className="block w-2 h-[3px] rounded-full bg-white/50 hover:bg-white/80 transition-colors duration-200"
274 | />
275 | )}
276 | </button>
277 | </div>
278 |
279 |
280 | </div>
281 |
282 | </div>
283 | </Container>
284 | </section>
285 | </>
286 | );
287 | };
288 |
```

31. src/components/sections/ImpactStats.tsx

```

1 | import React from "react";
2 | import { ImpactStatsProps } from "@types";
3 | import { Container } from "../ui/Container";
4 | import { StatItem } from "../ui/StatItem";
5 | import { GraduationCap, Home, Laptop, Heart } from "lucide-react";
6 | import { SectionWrapper } from "../storytelling/SectionWrapper";
7 |
8 | export const ImpactStats: React.FC<ImpactStatsProps> = ({
9 |   title,
10 |  subtitle,
11 |  stats,
12 | }) => {
13 |   const icons = [
14 |     <GraduationCap size={24} key="grad" />,
15 |     <Home size={24} key="home" />,
16 |     <Laptop size={24} key="laptop" />,
17 |     <Heart size={24} key="heart" />,
18 |   ];
19 |
20 |   return (
21 |     <SectionWrapper id="our-impact" bgColor="bg-mint/30" glowPosition="center">
22 |       <Container size="xl">
23 |         <div className="text-center max-w-3xl mx-auto mb-12 sm:mb-16">
24 |           <span className="inline-block px-4 py-1 rounded-full bg-accent text-charcoal-static font-heading text-xs font-bold uppercase tracking-wider mb-4">
25 |             Our Impact
26 |           </span>
27 |           <h2 className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading leading-tight mb-4">
28 |             {title}
29 |           </h2>
30 |           <p className="text-base text-charcoal/70 leading-relaxed font-body max-w-2xl mx-auto">
31 |             {subtitle}
32 |           </p>
33 |         </div>
34 |
35 |         <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-6 sm:gap-8">
36 |           {stats.map((stat, index) => (
37 |             <StatItem
38 |               key={index}
39 |               value={stat.value}
40 |               label={stat.label}
41 |               description={stat.description}
42 |               icon={icons[index % icons.length]}
43 |             />
44 |           ))}
45 |         </div>
46 |       </Container>
47 |     </SectionWrapper>
48 |   );
49 | };
50 |

```

32. src/components/sections/Mission.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { MissionProps, PageRoutes } from "@types";
5 | import { Container, BackgroundPattern, TiltCard } from "../ui";
6 | import { Palette, Settings, Leaf, ArrowRight } from "lucide-react";
7 | import Link from "next/link";
8 | import { cn } from "@utils/cn";
9 | import { SectionWrapper } from "../../storytelling/SectionWrapper";
10 | import { ParallaxImage } from "../../storytelling/ParallaxImage";
11 |
12 | const MeditateIcon = () => (
13 |   <svg
14 |     className="w-5 h-5"
15 |     fill="none"
16 |     stroke="currentColor"
17 |     viewBox="0 0 24 24"
18 |     strokeWidth="2.5"
19 |     strokeLinecap="round"
20 |     strokeLinejoin="round"
21 |   >
22 |     <circle cx="12" cy="5" r="2" />
23 |     <path d="M12 7v8M5 10c2-1 4-1 7 0s5 1 7 0M7 18c2 1 4 1 5 0s3-1 5 0" />
24 |   </svg>
25 | );
26 |
27 | export const Mission: React.FC<MissionProps> = ({
28 |   title,
29 |   description,
30 |   bullets,
31 | }) => {
32 |   // Determine layout variant deterministically from props rather than pathname to prevent hydration mismatch
33 |   const isAboutPage = !bullets || bullets.length === 0;
34 |
35 |   if (isAboutPage) {
36 |     // About Us Page "Our Story" Layout
37 |     const storyCards = [
38 |       {
39 |         title: "The Beginning",
40 |         description: "Founded on the belief that education should not be a rigid institution but a blooming collective effort, Dua started as a small community initiative. We saw a gap between traditional learning and the natural curiosity of individuals."
41 |       },
42 |       {
43 |         title: "Our Vision",
44 |         description: "A world where joyful learning is accessible to all, empowering communities to grow together."
45 |       }
46 |     ];
47 |
48 |     return (
49 |       <section className="py-20 bg-cream" aria-labelledby="story-heading">
50 |         <Container size="xl">
51 |           <div className="text-center mb-12">
52 |             <h2 id="story-heading" className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading">
53 |               Our Story
54 |             </h2>
55 |           </div>
56 |
57 |           <div className="grid grid-cols-1 md:grid-cols-2 gap-8 w-full">
58 |             {storyCards.map((card, idx) => (
59 |               <div
60 |                 key={idx}
61 |                 className="relative bg-beige border border-charcoal/5 rounded-3xl p-8 overflow-hidden shadow-xs card-interactive flex flex-col justify-between"
62 |               >
63 |                 <BackgroundPattern variant="leaf" opacity={0.35} className="text-forest/10" />
64 |                 <div className="relative z-10">

```

```

65 | { /* Decorative Icon */}
66 | <div className="w-10 h-10 rounded-full bg-cream/70 flex items-center justify-center text-forest mb-6">
67 | {idx === 0 ? <svg className="w-5 h-5 fill-current" viewBox="0 0 24 24"><path d="M14 2H6a2 2 0 0 0-2 2v16c0 1.1.9
2 2 2h12a2 2 0 0 0 2-2V8l-6-6zM6 20V4h7v5h5v11H6z" /></svg> : <svg className="w-5 h-5 fill-current" viewBox="0 0 24
24"><path d="M12 4.5C7 4.5 2.73 7.61 1 12c1.73 4.39 6 7.5 11 7.5s9.27-3.11 11-7.5c-1.73-4.39-6-7.5-11-7.5zM12
17c-2.76 0-5-2.24-5-5s2.24-5 5-5 2.24 5 5-2.24 5-5 5zm0-8c-1.66 0-3 1.34-3 3s1.34 3 3 3-1.34 3-3-1.34-3-3-3z"
/></svg>}
68 | </div>
69 | <h3 className="text-xl font-bold font-heading text-charcoal mb-4">
70 | {card.title}
71 | </h3>
72 | <p className="text-sm sm:text-base text-charcoal/80 leading-relaxed font-body">
73 | {card.description}
74 | </p>
75 | </div>
76 | </div>
77 | )})
78 | </div>
79 | </Container>
80 | </section>
81 | );
82 | }
83 |
84 | // Home Page "Our Focus" Layout
85 | const focusCards = [
86 | {
87 | title: "Mentorship & Guidance",
88 | description: "Interactive science kit curation, mobile science labs, and community workspace labs.",
89 | icon: <Settings size={20} />,
90 | bgClass: "bg-card-bg text-charcoal border border-card-border",
91 | iconBg: "bg-sage text-forest",
92 | linkColor: "text-[#2D5B45]",
93 | hasBrush: true,
94 | pattern: undefined
95 | },
96 | {
97 | title: "Child Support Services",
98 | description: "Providing resources, secure environments, and learning materials to children in transition.",
99 | icon: <Palette size={20} />,
100 | bgClass: "bg-navy text-white border border-accent/10 shadow-md",
101 | iconBg: "bg-gold text-charcoal",
102 | linkColor: "text-accent",
103 | hasBrush: false,
104 | pattern: "circuit" as const
105 | },
106 | {
107 | title: "Environment & Nature",
108 | description: "Collaborating with like-minded organizations to amplify our impact and reach.",
109 | icon: <Leaf size={20} />,
110 | bgClass: "bg-card-bg text-charcoal border border-card-border",
111 | iconBg: "bg-sage text-forest",
112 | linkColor: "text-[#2D5B45]",
113 | hasBrush: false,
114 | pattern: "leaf" as const
115 | },
116 | {
117 | title: "Holistic Well-being",
118 | description: "An inspiring well-being process and holistic healthcare health.",
119 | icon: <MeditateIcon />,
120 | bgClass: "bg-card-bg text-charcoal border border-card-border",
121 | iconBg: "bg-sage text-forest",
122 | linkColor: "text-[#2D5B45]",
123 | hasBrush: false,
124 | pattern: "wave" as const
125 | }
126 | ];
127 |
128 | return (
129 | <SectionWrapper id="our-focus" bgColor="bg-sage" glowPosition="center">
130 | { /* 1) Subtle Parallax Background SVGs */}

```



```

131 | <div className="absolute top-1/12 -right-24 w-96 h-96 pointer-events-none select-none z-0">
132 | <ParallaxImage speed={0.5} className="w-full h-full">
133 | <svg
134 |   className="w-full h-full text-forest/10 fill-none stroke-current"
135 |   viewBox="0 0 24 24"
136 |   strokeWidth="0.5"
137 |   aria-hidden="true"
138 | >
139 | <path d="M12 2C6.5 2 2 6.5 2 12c0 4.5 3 8 7 9.5V22h6v-.5c4-1.5 7-5 7-9.5 0-5.5-4.5-10-10-10z M12 22V12c0-3 3-5
6-5 M12 16c0-3-3-5-6-5" />
140 | </svg>
141 | </ParallaxImage>
142 | </div>
143 |
144 | <div className="absolute bottom-1/12 -left-24 w-96 h-96 pointer-events-none select-none z-0">
145 | <ParallaxImage speed={0.5} className="w-full h-full">
146 | <svg
147 |   className="w-full h-full text-forest/10 fill-none stroke-current"
148 |   viewBox="0 0 24 24"
149 |   strokeWidth="0.5"
150 |   aria-hidden="true"
151 | >
152 | <path d="M12 2C6.5 2 2 6.5 2 12c0 4.5 3 8 7 9.5V22h6v-.5c4-1.5 7-5 7-9.5 0-5.5-4.5-10-10-10z M12 22V12c0-3 3-5
6-5 M12 16c0-3-3-5-6-5" />
153 | </svg>
154 | </ParallaxImage>
155 | </div>
156 |
157 | <Container size="xl" className="relative z-10">
158 | <div className="text-center max-w-3xl mx-auto mb-16">
159 | <span className="inline-block px-4 py-1 rounded-full bg-accent text-charcoal font-heading text-xs font-bold
uppercase tracking-wider mb-4">
160 |   Our Focus
161 | </span>
162 | <h2 className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading leading-tight mb-4">
163 |   {title}
164 | </h2>
165 | <p className="text-base text-charcoal/75 font-body leading-relaxed max-w-2xl mx-auto">
166 |   {description}
167 | </p>
168 | </div>
169 |
170 | <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-4 gap-8">
171 |   {focusCards.map((card, idx) => (
172 |     <TiltCard
173 |       key={idx}
174 |       intensity={8}
175 |       glare={true}
176 |       scale={1.03}
177 |       className="w-full h-full"
178 |     >
179 |       <div
180 |         className={cn(
181 |           "relative rounded-[32px] p-8 overflow-hidden flex flex-col justify-between h-full min-h-[300px] text-left
cursor-default transition-all duration-300 group",
182 |           idx === 1
183 |           ? "bg-navy text-white shadow-md border border-accent/25"
184 |           : "bg-white/60 backdrop-blur-md text-charcoal border border-forest/10 shadow-xs hover:border-forest/20"
185 |         )}
186 |       >
187 |         {/* Pattern overlays */}
188 |         {card.pattern && (
189 |           <BackgroundPattern
190 |             variant={card.pattern}
191 |             opacity={card.pattern === "circuit" ? 0.08 : 0.25}
192 |           />
193 |         )}
194 |
195 |         {/* Brush stroke overlay for Card 1 */}
196 |         {card.hasBrush && (

```

```
197 | <svg
198 |   className="absolute inset-0 w-full h-full text-forest/5 pointer-events-none"
199 |   fill="currentColor"
200 |   viewBox="0 0 100 100"
201 |   preserveAspectRatio="none"
202 |   aria-hidden="true"
203 | >
204 | <path d="M10 30 Q 30 20, 50 30 T 90 20 Q 80 50, 50 60 T 10 50 Z" />
205 | </svg>
206 | )}
207 |
208 | <div className="relative z-10 flex flex-col h-full justify-between">
209 | <div>
210 |   { /* Floating Icon with gentle lift */ }
211 |   <div className={cn(
212 |     "w-12 h-12 rounded-full flex items-center justify-center mb-6 shadow-xs transition-transform duration-350
group-hover:scale-110",
213 |     card.iconBg
214 |   )}>
215 |     {card.icon}
216 |   </div>
217 |
218 |   <h3 className="text-xl font-bold font-heading mb-3 tracking-tight">
219 |     {card.title}
220 |   </h3>
221 |
222 |   <p className="text-sm sm:text-base leading-relaxed font-body mb-8 opacity-80">
223 |     {card.description}
224 |   </p>
225 | </div>
226 |
227 | <Link
228 |   href={PageRoutes.OUR_PROJECTS}
229 |   className={cn(
230 |     "inline-flex items-center gap-1.5 text-sm font-bold font-heading hover:underline focus:outline-none
focus-visible:ring-2 focus-visible:ring-forest w-fit",
231 |     card.linkColor
232 |   )}
233 | >
234 |   Learn more <ArrowRight size={14} className="transition-transform duration-300 group-hover:translate-x-1" />
235 | </Link>
236 | </div>
237 | </div>
238 | </TiltCard>
239 | )}]
240 | </div>
241 | </Container>
242 | </SectionWrapper>
243 | );
244 | };
245 |
```

33. src/components/sections/MobileNavDrawer.tsx

```

1 | "use client";
2 |
3 | import React, { useEffect } from "react";
4 | import Link from "next/link";
5 | import { usePathname } from "next/navigation";
6 | import { m, useReducedMotion, AnimatePresence } from "framer-motion";
7 | import { X } from "lucide-react";
8 | import { cn } from "@utils/cn";
9 | import { navItems, siteConfig } from "@constants/navigation";
10 | import { useFocusTrap } from "@hooks/useFocusTrap";
11 | import { Button } from "@components/ui/Button";
12 |
13 | interface MobileNavDrawerProps {
14 |   isOpen: boolean;
15 |   onClose: () => void;
16 | }
17 |
18 | export const MobileNavDrawer: React.FC<MobileNavDrawerProps> = ({
19 |   isOpen,
20 |   onClose,
21 | }) => {
22 |   const pathname = usePathname();
23 |   const shouldReduceMotion = useReducedMotion();
24 |
25 |   // Focus trap for accessibility
26 |   const drawerRef = useFocusTrap<HTMLDivElement>(isOpen);
27 |
28 |   // Close drawer on escape key
29 |   useEffect(() => {
30 |     const handleKeyDown = (e: KeyboardEvent) => {
31 |       if (e.key === "Escape") {
32 |         onClose();
33 |       }
34 |     };
35 |     if (isOpen) {
36 |       window.addEventListener("keydown", handleKeyDown);
37 |     }
38 |     return () => {
39 |       window.removeEventListener("keydown", handleKeyDown);
40 |     };
41 |   }, [isOpen, onClose]);
42 |
43 |   // Lock body scroll when open
44 |   useEffect(() => {
45 |     if (isOpen) {
46 |       document.body.style.overflow = "hidden";
47 |     } else {
48 |       document.body.style.overflow = "";
49 |     }
50 |     return () => {
51 |       document.body.style.overflow = "";
52 |     };
53 |   }, [isOpen]);
54 |
55 |   // Close drawer on path change (navigation)
56 |   useEffect(() => {
57 |     onClose();
58 |   }, [pathname, onClose]);
59 |
60 |   // Animation variants
61 |   const backdropVariants = {
62 |     hidden: { opacity: 0 },
63 |     visible: { opacity: 1 },
64 |     exit: { opacity: 0 },
65 |   };
66 |
67 |   const drawerVariants = {

```

```

68 | hidden: shouldReduceMotion ? { opacity: 0 } : { x: "100%" },
69 | visible: shouldReduceMotion
70 | ? { opacity: 1 }
71 | : { x: 0 },
72 | exit: shouldReduceMotion ? { opacity: 0 } : { x: "100%" },
73 | };
74 |
75 | return (
76 | <AnimatePresence>
77 | {isOpen && (
78 | <>
79 | { /* Backdrop */}
80 | <m.div
81 | initial="hidden"
82 | animate="visible"
83 | exit="exit"
84 | variants={backdropVariants}
85 | transition={{ duration: shouldReduceMotion ? 0.15 : 0.25 }}
86 | onClick={onClose}
87 | className="fixed inset-0 bg-charcoal/40 backdrop-blur-xs z-40 cursor-pointer pointer-events-auto"
88 | aria-hidden="true"
89 | />
90 |
91 | { /* Drawer Container */}
92 | <m.div
93 | ref={drawerRef}
94 | initial="hidden"
95 | animate="visible"
96 | exit="exit"
97 | variants={drawerVariants}
98 | transition={
99 | shouldReduceMotion
100 | ? { duration: 0.2 }
101 | : { type: "spring", damping: 25, stiffness: 200 }
102 | }
103 | className="fixed top-0 right-0 bottom-0 w-full max-w-xs bg-sage/95 backdrop-blur-xl border-l border-charcoal/10
shadow-premium p-6 z-50 flex flex-col justify-between pointer-events-auto"
104 | role="dialog"
105 | aria-modal="true"
106 | aria-labelledby="mobile-nav-title"
107 | >
108 | <div>
109 | { /* Screen reader title */}
110 | <h2 id="mobile-nav-title" className="sr-only">
111 | Navigation Menu
112 | </h2>
113 |
114 | { /* Header */}
115 | <div className="flex items-center justify-between pb-6 border-b border-charcoal/10">
116 | <Link
117 | href="/"
118 | className="flex items-center gap-2 text-forest focus:outline-none focus-visible:ring-2
focus-visible:ring-forest/40 rounded-md"
119 | aria-label={` ${siteConfig.name} Home`}
120 | >
121 | <svg
122 | className="w-6 h-6 text-charcoal fill-none stroke-current"
123 | viewBox="0 0 32 32"
124 | strokeWidth="2.5"
125 | aria-hidden="true"
126 | >
127 | <circle cx="16" cy="16" r="14" />
128 | <path
129 | d="M16 24V14 M16 16c0-3 3-5 6-5 M16 18c0-3-3-5-6-5"
130 | strokeLinecap="round"
131 | />
132 | </svg>
133 | <span className="font-heading font-bold text-base tracking-tight text-charcoal">
134 | {siteConfig.name}
135 | </span>

```

```

136 | </Link>
137 | <button
138 |   onClick={onClose}
139 |   className="p-2 text-charcoal hover:text-forest transition-colors focus:outline-none focus-visible:ring-2
focus-visible:ring-forest/40 rounded-full"
140 |   aria-label="Close menu"
141 | >
142 | <X size={20} />
143 | </button>
144 | </div>
145 |
146 | {/* Navigation Links */}
147 | <nav className="flex flex-col gap-2 mt-6" aria-label="Mobile Navigation">
148 |   {navItems.map((item, index) => {
149 |     const isActive =
150 |       item.href === "/"
151 |       ? pathname === "/"
152 |       : pathname === item.href || pathname.startsWith(`${item.href}/`);
153 |     return (
154 |       <Link
155 |         key={index}
156 |         href={item.href}
157 |         aria-current={isActive ? "page" : undefined}
158 |         className={cn(
159 |           "flex items-center py-3 px-4 rounded-xl text-base font-bold font-heading transition-all duration-200
focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40",
160 |           isActive
161 |           ? "bg-forest/5 text-forest"
162 |           : "text-charcoal/80 hover:bg-charcoal/5 hover:text-charcoal"
163 |         )}
164 |       >
165 |         {item.label}
166 |       </Link>
167 |     );
168 |   })}
169 | </nav>
170 | </div>
171 |
172 | {/* Bottom Actions */}
173 | <div className="mt-auto">
174 |   <Button
175 |     label="Get Involved"
176 |     variant="primary"
177 |     size="md"
178 |     href={siteConfig.donateLink}
179 |     className="w-full text-center py-3 bg-charcoal text-cream hover:bg-forest hover:text-cream rounded-full
font-bold focus-visible:ring-2 focus-visible:ring-forest/40"
180 |   />
181 | </div>
182 | </m.div>
183 | </>
184 | })}
185 | </AnimatePresence>
186 | );
187 | };
188 |
189 | export default MobileNavDrawer;
190 |

```

34. src/components/sections/NavLink.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import Link from "next/link";
5 | import { usePathname } from "next/navigation";
6 | import { m, useReducedMotion } from "framer-motion";
7 | import { cn } from "@utils/cn";
8 |
9 | interface NavLinkProps {
10 |   href: string;
11 |   label: string;
12 | }
13 |
14 | export const NavLink: React.FC<NavLinkProps> = ({ href, label }) => {
15 |   const pathname = usePathname();
16 |   const shouldReduceMotion = useReducedMotion();
17 |
18 |   // Active route matching logic:
19 |   // - If item href is "/" -> active only when pathname === "/"
20 |   // - Else active when pathname === href OR pathname startsWith(`${href}/`)
21 |   const isActive =
22 |     href === "/"
23 |     ? pathname === "/"
24 |     : pathname === href || pathname.startsWith(`${href}/`);
25 |
26 |   return (
27 |     <Link
28 |       href={href}
29 |       aria-current={isActive ? "page" : undefined}
30 |       className={cn(
31 |         "relative py-2 text-sm font-semibold font-body hover:text-forest transition-colors duration-200
focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40 rounded-md px-2",
32 |         isActive ? "text-forest" : "text-charcoal/70"
33 |       )}
34 |     >
35 |     <span className="relative z-10">{label}</span>
36 |     {isActive && (
37 |       <m.span
38 |         layoutId="activeIndicator"
39 |         className="absolute bottom-0 left-2 right-2 h-0.5 bg-gold-gradient rounded-full"
40 |         transition={
41 |           shouldReduceMotion
42 |           ? { type: "tween", duration: 0 }
43 |           : { type: "spring", stiffness: 380, damping: 30 }
44 |         }
45 |       </m.span>
46 |     )}
47 |   </Link>
48 | );
49 | };
50 |
51 | export default NavLink;
52 |

```

35. src/components/sections/Navbar.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import Link from "next/link";
5 | import { usePathname } from "next/navigation";
6 | import { useScroll, useMotionValueEvent } from "framer-motion";
7 | import { Menu } from "lucide-react";
8 | import { cn } from "@/utils/cn";
9 | import { navItems, siteConfig } from "@/constants/navigation";
10 | import { NavLink } from "../NavLink";
11 | import { MobileNavDrawer } from "../MobileNavDrawer";
12 | import { Button } from "@components/ui/Button";
13 | import { ThemeToggle } from "@components/ui/ThemeToggle";
14 |
15 | export const Navbar: React.FC = () => {
16 |   const pathname = usePathname();
17 |   const [mobileMenuOpen, setMobileMenuOpen] = useState(false);
18 |   const [isScrolled, setIsScrolled] = useState(false);
19 |
20 |   // Framer Motion useScroll for low overhead scroll listening
21 |   const { scrollY } = useScroll();
22 |
23 |   useMotionValueEvent(scrollY, "change", (latest) => {
24 |     setIsScrolled(latest >= 24);
25 |   });
26 |
27 |   // Background/glass transitions when scrolled OR when not on homepage
28 |   const isScrolledOrNotHome = isScrolled || pathname !== "/";
29 |
30 |   return (
31 |     <>
32 |     { /* Premium hallmark: Keyboard-accessible Skip Link */ }
33 |     <a
34 |       href="#main-content"
35 |       className="sr-only focus:not-sr-only focus:absolute focus:top-6 focus:left-6 focus:z-[60] bg-forest text-cream
px-6 py-2.5 rounded-full font-heading font-bold shadow-md focus:outline-none focus:ring-2 focus:ring-forest/40"
36 |     >
37 |       Skip to content
38 |     </a>
39 |
40 |     { /* Floating fixed wrapper with safe-area notch support */ }
41 |     <div
42 |       className="fixed left-0 right-0 z-50 px-4 w-full pointer-events-none"
43 |       style={{ top: "calc(env(safe-area-inset-top, 0px) + 1rem)" }}
44 |     >
45 |       <header
46 |         className={cn(
47 |           "mx-auto w-full max-w-[90rem] pointer-events-auto transition-all duration-300 ease-in-out border rounded-2xl
md:rounded-[1.5rem]",
48 |           isScrolled ? "py-2.5 px-6" : "py-4 px-6 md:px-8",
49 |           isScrolledOrNotHome
50 |           ? "bg-sage/80 backdrop-blur-xl border-charcoal/10 shadow-premium"
51 |           : "bg-transparent border-transparent shadow-none"
52 |         )}
53 |       >
54 |         <div className="flex items-center justify-between">
55 |           { /* Logo */ }
56 |           <Link
57 |             href="/"
58 |             className={cn(
59 |               "flex items-center gap-2 text-forest focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40
rounded-md transition-transform duration-300 origin-left",
60 |               isScrolled ? "scale-95" : "scale-100"
61 |             )}
62 |             aria-label={` ${siteConfig.name} Home`}
63 |           >
64 |           <svg

```

```

65 | className="w-7 h-7 text-charcoal fill-none stroke-current"
66 | viewBox="0 0 32 32"
67 | strokeWidth="2.5"
68 | aria-hidden="true"
69 | >
70 | <circle cx="16" cy="16" r="14" />
71 | <path
72 | d="M16 24V14 M16 16c0-3 3-5 6-5 M16 18c0-3-3-5-6-5"
73 | strokeLinecap="round"
74 | />
75 | </svg>
76 | <span className="font-heading font-bold text-lg sm:text-xl tracking-tight text-charcoal">
77 | {siteConfig.name}
78 | </span>
79 | </Link>
80 |
81 | {/* Desktop Navigation Links */}
82 | <nav
83 | className={cn(
84 | "hidden md:flex items-center transition-all duration-300",
85 | isScrolled ? "gap-6" : "gap-8"
86 | )}
87 | aria-label="Main Navigation"
88 | >
89 | {navItems.map((item, index) => (
90 | <NavLink key={index} href={item.href} label={item.label} />
91 | ))}
92 | </nav>
93 |
94 | {/* Desktop Action Buttons & Theme Toggle */}
95 | <div className="flex items-center gap-3">
96 | <ThemeToggle />
97 |
98 | <div className="hidden md:block">
99 | <Button
100 | label="Get Involved"
101 | variant="outline"
102 | size={isScrolled ? "sm" : "md"}
103 | href={siteConfig.donateLink}
104 | className="bg-transparent border-charcoal/20 text-charcoal hover:bg-charcoal hover:text-cream rounded-full
105 | transition-all duration-300 shadow-none font-bold"
106 | aria-label="Get Involved - Make a donation"
107 | />
108 | </div>
109 | {/* Mobile Menu Toggle */}
110 | <button
111 | onClick={() => setMobileMenuOpen(true)}
112 | className="md:hidden p-2 text-charcoal hover:text-forest transition-colors focus:outline-none
113 | focus-visible:ring-2 focus-visible:ring-forest/40 rounded-full cursor-pointer flex items-center justify-center"
114 | aria-expanded={mobileMenuOpen}
115 | aria-controls="mobile-nav-drawer"
116 | aria-label="Open navigation menu"
117 | >
118 | <Menu size={24} />
119 | </button>
120 | </div>
121 | </div>
122 | </div>
123 |
124 | {/* Mobile Drawer Overlay and Content */}
125 | <MobileNavDrawer
126 | isOpen={mobileMenuOpen}
127 | onClose={() => setMobileMenuOpen(false)}
128 | />
129 | </>
130 | );
131 | };
132 |

```



```
133 | export default Navbar;  
134 |
```

36. src/components/sections/Newsletter.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import { NewsletterProps } from "@types";
5 | import { Container } from "../ui/Container";
6 | import { Input } from "../ui/Input";
7 | import { Button } from "../ui/Button";
8 | import { Send, CheckCircle2 } from "lucide-react";
9 |
10 | export const Newsletter: React.FC<NewsletterProps> = ({
11 |   title,
12 |   subtitle,
13 |   placeholderText = "Enter your email address",
14 |   buttonText = "Subscribe",
15 | }) => {
16 |   const [email, setEmail] = useState("");
17 |   const [status, setStatus] = useState<"idle" | "loading" | "success" | "error">("idle");
18 |
19 |   const handleSubmit = (e: React.FormEvent<HTMLFormElement>): void => {
20 |     e.preventDefault();
21 |     if (!email) return;
22 |
23 |     setStatus("loading");
24 |     setTimeout(() => {
25 |       setStatus("success");
26 |       setEmail("");
27 |     }, 1200);
28 |   };
29 |
30 |   return (
31 |     <section className="py-16 sm:py-20 bg-forest text-cream relative overflow-hidden">
32 |       <div className="absolute inset-0 bg-[radial-gradient(#F57C00_1px,transparent_1px)] [background-size:24px_24px]
opacity-10 pointer-events-none" />
33 |       <Container>
34 |         <div className="max-w-3xl mx-auto text-center flex flex-col items-center">
35 |           <h2 className="text-3xl sm:text-4xl font-bold tracking-tight font-heading leading-tight mb-4 text-cream">
36 |             {title}
37 |           </h2>
38 |           <p className="text-sm sm:text-base text-cream/80 leading-relaxed font-body mb-8 max-w-xl">
39 |             {subtitle}
40 |           </p>
41 |
42 |           {status === "success" ? (
43 |             <div className="flex flex-col items-center bg-cream/10 border border-cream/20 rounded-3xl p-6 sm:p-8
animate-fade-in w-full max-w-md">
44 |               <CheckCircle2 size={40} className="text-cream mb-3" />
45 |               <h3 className="text-lg font-bold font-heading mb-1 text-cream">Thank You!</h3>
46 |               <p className="text-xs sm:text-sm text-cream/95 font-body">
47 |                 You've successfully subscribed to our eco-digest.
48 |               </p>
49 |             </div>
50 |           ) : (
51 |             <form onSubmit={handleSubmit} className="flex flex-col sm:flex-row gap-3 w-full max-w-md">
52 |               <div className="flex-grow">
53 |                 <Input
54 |                   type="email"
55 |                   placeholder={placeholderText}
56 |                   value={email}
57 |                   onChange={(e) => setEmail(e.target.value)}
58 |                   required
59 |                   disabled={status === "loading"}
60 |                   className="bg-cream/10! border-cream/20! text-cream! placeholder:text-cream/50! focus:border-cream!
focus:ring-cream/30! w-full"
61 |                   aria-label="Email Address"
62 |                 />
63 |               </div>
64 |               <Button

```

```
65 | type="submit"
66 | label={buttonText}
67 | variant="secondary"
68 | loading={status === "loading"}
69 | icon={<Send size={14} />}
70 | iconPosition="right"
71 | className="w-full sm:w-auto shrink-0 py-3!"
72 | />
73 | </form>
74 | })
75 | </div>
76 | </Container>
77 | </section>
78 | );
79 | };
80 |
```

37. src/components/sections/SeedsOfChange.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import Link from "next/link";
5 | import Image from "next/image";
6 | import { m, useReducedMotion, Variants } from "framer-motion";
7 | import { cn } from "@/utils/cn";
8 | import { seedsIntro, seedsItems } from "@/constants/seedsOfChange";
9 | import { Container } from "../ui/Container";
10 |
11 | const SeedsTextReveal: React.FC<{
12 | title: string;
13 | description: string;
14 | href: string;
15 | textContainer: Variants;
16 | textItem: Variants;
17 | }> = ({ title, description, href, textContainer, textItem }) => {
18 |   const ref = React.useRef<HTMLDivElement>(null);
19 |   const [isInView, setIsInView] = React.useState(false);
20 |
21 |   React.useEffect(() => {
22 |     if (!ref.current) return;
23 |
24 |     let observer: IntersectionObserver;
25 |     const timer = setTimeout(() => {
26 |       observer = new IntersectionObserver(
27 |         ([entry]) => {
28 |           setIsInView(entry.isIntersecting);
29 |         },
30 |         { threshold: 0.2, rootMargin: "0px 0px -50px 0px" }
31 |       );
32 |       if (ref.current) {
33 |         observer.observe(ref.current);
34 |       }
35 |     }, 150);
36 |
37 |     return () => {
38 |       clearTimeout(timer);
39 |       if (observer) observer.disconnect();
40 |     };
41 |   }, []);
42 |
43 |   return (
44 |     <m.div
45 |       ref={ref}
46 |       initial="hidden"
47 |       animate={isInView ? "visible" : "hidden"}
48 |       variants={textContainer}
49 |       className="relative z-10 w-full text-left"
50 |     >
51 |     <div className="overflow-hidden">
52 |       <m.h3
53 |         variants={textItem}
54 |         style={{ willChange: "transform, opacity" }}
55 |         className="text-2xl sm:text-3xl font-extrabold text-charcoal font-heading leading-tight mb-4"
56 |       >
57 |       {title}
58 |     </m.h3>
59 |     </div>
60 |
61 |     <div className="overflow-hidden">
62 |       <m.p
63 |         variants={textItem}
64 |         style={{ willChange: "transform, opacity" }}
65 |         className="text-sm sm:text-base text-charcoal/70 leading-relaxed font-body mb-6"
66 |       >
67 |       {description}

```

```

68 | </m.p>
69 | </div>
70 |
71 | <div className="overflow-hidden">
72 |   <m.div
73 |     variants={textItem}
74 |     style={{ willChange: "transform, opacity" }}
75 |   >
76 |     <Link
77 |       href={href}
78 |       className="inline-flex items-center text-sm font-bold font-body text-forest hover:text-charcoal
transition-colors duration-200 focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40 rounded px-1
-ml-1"
79 |     >
80 |     Learn More
81 |   </Link>
82 | </m.div>
83 | </div>
84 | </m.div>
85 | );
86 | };
87 |
88 | export const SeedsOfChange: React.FC = () => {
89 |   const shouldReduceMotion = useReducedMotion();
90 |
91 |   // Animation variants for text reveal
92 |   const textContainer = {
93 |     hidden: {},
94 |     visible: {
95 |       transition: {
96 |         staggerChildren: 0.12,
97 |       },
98 |     },
99 |   };
100 |
101 |   const textItem = {
102 |     hidden: {
103 |       opacity: 0,
104 |       x: shouldReduceMotion ? 0 : -24
105 |     },
106 |     visible: {
107 |       opacity: 1,
108 |       x: 0,
109 |       transition: {
110 |         duration: 0.9,
111 |         ease: [0.22, 1, 0.36, 1] // smooth easeOutQuart
112 |       },
113 |     },
114 |   };
115 |
116 |   // Wash variants to theme color classes mapping (made more saturated/darker as requested)
117 |   const washClasses = {
118 |     sage: "bg-gradient-to-br from-sage/30 via-sage/65 to-sage/45",
119 |     mint: "bg-gradient-to-br from-mint/30 via-mint/65 to-mint/45",
120 |     beige: "bg-gradient-to-br from-beige/35 via-beige/75 to-beige/50",
121 |     cream: "bg-gradient-to-br from-cream via-sage/30 to-cream",
122 |   };
123 |
124 |   return (
125 |     <section className="pt-8 pb-20 bg-cream relative overflow-hidden" aria-labelledby="seeds-section-title">
126 |       <Container size="xl">
127 |         <div className="flex flex-col gap-10 sm:gap-12 md:gap-16 w-full">
128 |           { /* Top Intro Card - Static */ }
129 |         <div
130 |           className={cn(
131 |             "relative bg-gradient-to-br from-cream via-sage/10 to-cream p-8 sm:p-12 md:p-14 rounded-2xl border
border-charcoal/10 shadow-soft overflow-hidden flex flex-col md:flex-row justify-between items-start md:items-center
gap-6",
132 |             "hover:shadow-card hover:-translate-y-0.5 transition-all duration-300"
133 |           )}

```

```

134 | >
135 | { /* Watercolor paper wash overlay */}
136 | <div
137 |   className="absolute inset-0 pointer-events-none opacity-30 mix-blend-overlay
bg-[radial-gradient(circle_at_center,rgba(255,255,255,0.7)_0%,transparent_75%)]"
138 |   aria-hidden="true"
139 | />
140 |
141 | <div className="max-w-2xl relative z-10">
142 | <h2
143 |   id="seeds-section-title"
144 |   className="text-3xl sm:text-4xl font-extrabold tracking-tight text-charcoal font-heading leading-tight mb-3"
145 | >
146 | {seedsIntro.title}
147 | </h2>
148 | <p className="text-sm sm:text-base text-charcoal/70 leading-relaxed font-body">
149 | {seedsIntro.description}
150 | </p>
151 | </div>
152 |
153 | <div className="relative z-10 shrink-0">
154 | <Link
155 |   href={seedsIntro.buttonHref}
156 |   className="inline-flex items-center justify-center px-6 py-3 bg-accent/20 border border-accent/30 text-charcoal
hover:bg-accent/30 rounded-full font-heading font-extrabold text-sm shadow-sm hover:scale-[1.02]
active:scale-[0.98] transition-all duration-300 focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40"
157 | >
158 | {seedsIntro.buttonLabel}
159 | </Link>
160 | </div>
161 | </div>
162 |
163 | { /* alternating row items */}
164 | <div className="flex flex-col gap-8 sm:gap-10">
165 | {seedsItems.map((item, index) => {
166 |   const isEven = index % 2 === 0;
167 |
168 |   return (
169 |     <div key={item.id} className="grid grid-cols-1 lg:grid-cols-2 gap-8 items-stretch">
170 |       { /* Image Tile - Static */}
171 |       <div
172 |         className={cn(
173 |           "relative min-h-[320px] sm:min-h-[360px] lg:min-h-[400px] rounded-2xl overflow-hidden border border-charcoal/10
shadow-soft w-full",
174 |           isEven ? "lg:order-1" : "lg:order-2",
175 |           "hover:shadow-card hover:-translate-y-0.5 transition-all duration-300"
176 |         )}
177 |       >
178 |         <Image
179 |           src={item.imageSrc}
180 |           alt={item.imageAlt}
181 |           fill
182 |           sizes="(max-width: 1024px) 100vw, 50vw"
183 |           className="object-cover"
184 |           priority={index === 0}
185 |         />
186 |       { /* Barely visible gradient overlay for depth */}
187 |       <div className="absolute inset-0 bg-gradient-to-t from-charcoal/15 via-transparent to-transparent
pointer-events-none z-10" />
188 |     </div>
189 |
190 |     { /* Text Tile - Static Container */}
191 |     <div
192 |       className={cn(
193 |         "relative p-8 sm:p-12 md:p-14 min-h-[320px] sm:min-h-[360px] lg:min-h-[400px] rounded-2xl overflow-hidden
border border-charcoal/10 shadow-soft flex flex-col justify-center items-start w-full",
194 |         isEven ? "lg:order-2" : "lg:order-1",
195 |         washClasses[item.wash],
196 |         "hover:shadow-card hover:-translate-y-0.5 transition-all duration-300"
197 |       )}

```

```
198 | >
199 | { /* Watercolor paper wash overlay */}
200 | <div
201 |   className="absolute inset-0 pointer-events-none opacity-30 mix-blend-overlay
bg-[radial-gradient(circle_at_center, rgba(255,255,255,0.7)_0%, transparent_75%)]"
202 |   aria-hidden="true"
203 | />
204 |
205 | { /* Staggered text reveal container */}
206 | <SeedsTextReveal
207 |   title={item.title}
208 |   description={item.description}
209 |   href={item.href}
210 |   textContainer={textContainer}
211 |   textItem={textItem}
212 | />
213 | </div>
214 | </div>
215 | );
216 | }}}
217 | </div>
218 | </div>
219 | </Container>
220 | </section>
221 | );
222 | };
223 |
224 | export default SeedsOfChange;
225 |
```

38. src/components/sections/TeamGrid.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { TeamGridProps } from "@types";
5 | import { Container } from "../ui/Container";
6 | import { BackgroundPattern } from "../ui/BackgroundPattern";
7 | import { Smile, Users, BrainCircuit, Globe } from "lucide-react";
8 | import Image from "next/image";
9 |
10 | export const TeamGrid: React.FC<TeamGridProps> = ({
11 |   title,
12 |   subtitle,
13 |   members,
14 | }) => {
15 |   // Determine layout variant deterministically from props rather than pathname to prevent hydration mismatch
16 |   const isAboutPage = title === "Core Values" || !members || members.length === 0;
17 |
18 |   if (isAboutPage) {
19 |     // About Page "Core Values" Layout
20 |     const coreValues = [
21 |       {
22 |         title: "Joyful Learning",
23 |         description: "Education should be a delightful journey, not a chore.",
24 |         icon: <Smile className="w-5 h-5" />,
25 |       },
26 |       {
27 |         title: "Community First",
28 |         description: "Empowering local voices and collective growth.",
29 |         icon: <Users className="w-5 h-5" />,
30 |       },
31 |       {
32 |         title: "Inquisitive Minds",
33 |         description: "Fostering curiosity and critical thinking in every environment.",
34 |         icon: <BrainCircuit className="w-5 h-5" />,
35 |       },
36 |       {
37 |         title: "Inclusive Access",
38 |         description: "Breaking down barriers to ensure education is for everyone.",
39 |         icon: <Globe className="w-5 h-5" />,
40 |       },
41 |     ];
42 |
43 |     return (
44 |       <section className="relative py-20 bg-mint overflow-hidden" aria-labelledby="values-heading">
45 |         { /* Leaf Background Pattern */ }
46 |         <BackgroundPattern variant="leaf" opacity={0.4} className="text-forest/15" />
47 |
48 |         <Container className="relative z-10">
49 |           <div className="text-center mb-16">
50 |             <h2 id="values-heading" className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading">
51 |               {title || "Core Values"}
52 |             </h2>
53 |           </div>
54 |
55 |           <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-6 max-w-6xl mx-auto">
56 |             {coreValues.map((value, idx) => (
57 |               <div
58 |                 key={idx}
59 |                 className="bg-card-bg border border-card-border rounded-3xl p-8 flex flex-col items-center text-center shadow-xs card-interactive"
60 |               >
61 |                 { /* Rounded Icon Wrapper */ }
62 |                 <div className="w-12 h-12 rounded-full bg-forest/5 flex items-center justify-center text-forest mb-6">
63 |                   {value.icon}
64 |                 </div>
65 |                 <h3 className="text-lg font-bold font-heading text-charcoal mb-2">
66 |                   {value.title}

```



```

67 | </h3>
68 | <p className="text-xs sm:text-sm text-charcoal/70 leading-relaxed font-body">
69 | {value.description}
70 | </p>
71 | </div>
72 | }}}
73 | </div>
74 | </Container>
75 | </section>
76 | );
77 | }
78 |
79 | // Fallback / Original Team Grid Layout (used elsewhere if any)
80 | return (
81 | <section className="py-20 bg-cream" aria-labelledby="team-heading">
82 | <Container>
83 | <div className="text-center mb-16 max-w-3xl mx-auto">
84 | <h2 id="team-heading" className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading">
85 | {title}
86 | </h2>
87 | {subtitle && (
88 | <p className="text-base text-charcoal/70 font-body leading-relaxed mt-4">
89 | {subtitle}
90 | </p>
91 | )}
92 | </div>
93 | <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-8">
94 | {members.map((member, index) => (
95 | <div
96 | key={index}
97 | className="flex flex-col bg-cream border border-forest/15 rounded-3xl p-6 shadow-sm group hover:-translate-y-1
98 | transition-all duration-300"
99 | >
100 | <div className="relative h-44 w-44 mx-auto rounded-full overflow-hidden border border-forest/10 mb-6 shrink-0">
101 | <Image
102 | src={member.image}
103 | alt={member.name}
104 | fill
105 | sizes="176px"
106 | className="object-cover group-hover:scale-105 transition-transform duration-300"
107 | />
108 | </div>
109 | <div className="text-center flex flex-col flex-grow">
110 | <h3 className="text-lg font-bold text-charcoal font-heading mb-1">
111 | {member.name}
112 | </h3>
113 | <span className="text-xs font-bold text-forest font-heading tracking-wider uppercase mb-4">
114 | {member.role}
115 | </span>
116 | <p className="text-xs sm:text-sm text-charcoal/65 leading-relaxed font-body mb-6 flex-grow">
117 | {member.bio}
118 | </p>
119 | </div>
120 | </div>
121 | </div>
122 | </Container>
123 | </section>
124 | );
125 | };
126 |

```

39. src/components/sections/Testimonials.tsx

```

1 | import React from "react";
2 | import Image from "next/image";
3 | import { TestimonialsProps } from "@types";
4 | import { Container } from "../ui/Container";
5 | import { Quote } from "lucide-react";
6 | import { SectionWrapper } from "../storytelling/SectionWrapper";
7 |
8 | export const Testimonials: React.FC<TestimonialsProps> = ({
9 |   title,
10 |  subtitle,
11 |  testimonials,
12 | }) => {
13 |   return (
14 |     <SectionWrapper id="testimonials" bgColor="bg-cream" glowPosition="top-left">
15 |       <Container size="xl">
16 |         <div className="text-center max-w-3xl mx-auto mb-12 sm:mb-16">
17 |           <span className="inline-block px-4 py-1 rounded-full bg-accent text-charcoal-static font-heading text-xs
font-bold uppercase tracking-wider mb-4">
18 |             Community Voices
19 |           </span>
20 |           <h2 className="text-3xl sm:text-4xl font-extrabold text-charcoal font-heading leading-tight mb-4">
21 |             {title}
22 |           </h2>
23 |           <p className="text-base text-charcoal/70 leading-relaxed font-body max-w-2xl mx-auto">
24 |             {subtitle}
25 |           </p>
26 |         </div>
27 |
28 |         <div className="grid grid-cols-1 md:grid-cols-3 gap-8">
29 |           {testimonials.map((testimonial, index) => (
30 |             <div
31 |               key={index}
32 |               className="flex flex-col bg-cream border border-forest/15 rounded-3xl p-6 sm:p-8 shadow-xs hover:shadow-md
hover:border-forest/30 transition-all duration-300 relative group">
33 |               <div className="absolute top-6 right-6 text-forest/10 group-hover:text-forest/20 transition-colors
duration-200">
34 |                 <Quote size={36} strokeWidth={2.5} />
35 |               </div>
36 |               <p className="text-sm sm:text-base text-charcoal/75 leading-relaxed font-body mb-8 italic relative z-10
flex-grow text-left">
37 |                 &ldquo;{testimonial.quote}&rdquo;
38 |               </p>
39 |               <div className="flex items-center gap-3 pt-4 border-t border-forest/10 mt-auto">
40 |                 <div className="relative h-10 w-10 rounded-full overflow-hidden shrink-0 border border-forest/10">
41 |                   <Image
42 |                     src={testimonial.avatar}
43 |                     alt={testimonial.name}
44 |                     fill
45 |                     className="object-cover"
46 |                     sizes="40px"
47 |                   />
48 |                 </div>
49 |                 <div className="flex flex-col min-w-0 text-left">
50 |                   <span className="text-sm font-bold text-charcoal truncate">{testimonial.name}</span>
51 |                   <span className="text-[11px] text-charcoal/50 truncate font-heading font-medium">
52 |                     {testimonial.role} {testimonial.location ? `• ${testimonial.location}` : ""}
53 |                   </span>
54 |                 </div>
55 |               </div>
56 |             </div>
57 |           )})
58 |         </div>
59 |       </Container>
60 |     </SectionWrapper>
61 |   );
62 | };
63 |

```

64 |

40. src/components/storytelling/AnimatedHeading.tsx

```
1 | "use client";
2 |
3 | import React from "react";
4 | import { cn } from "@utils/cn";
5 |
6 | export interface AnimatedHeadingProps {
7 |   text: string;
8 |   as?: "h1" | "h2" | "h3" | "h4";
9 |   className?: string;
10 | }
11 |
12 | export const AnimatedHeading: React.FC<AnimatedHeadingProps> = ({
13 |   text,
14 |   as: Component = "h2",
15 |   className,
16 | }) => {
17 |   const words = text.split(" ");
18 |
19 |   return (
20 |     <Component
21 |       className={cn(
22 |         "font-heading font-extrabold text-charcoal leading-tight flex flex-wrap gap-x-2 select-none overflow-hidden
py-1",
23 |         className
24 |       )}
25 |     >
26 |     {words.map((word, i) => (
27 |       <span key={i} className="relative inline-block overflow-hidden pb-1">
28 |         <span className="story-heading-word inline-block translate-y-[100%] opacity-0 will-change-transform">
29 |           {word}
30 |         </span>
31 |       </span>
32 |     ))}
33 |     </Component>
34 |   );
35 | };
36 | export default AnimatedHeading;
37 |
```

41. src/components/storytelling/AnimatedSection.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { useGSAP } from "@hooks/useGSAP";
5 | import { useReducedMotion } from "@hooks/useReducedMotion";
6 | import { applyTextTransition } from "@animations/textTransitions";
7 | import { applyImageTransition } from "@animations/imageTransitions";
8 | import { cn } from "@utils/cn";
9 |
10 | export interface AnimatedSectionProps {
11 |   children: React.ReactNode;
12 |   className?: string;
13 |   id?: string;
14 |   triggerHook?: string;
15 | }
16 |
17 | export const AnimatedSection: React.FC<AnimatedSectionProps> = ({
18 |   children,
19 |   className,
20 |   id,
21 | }) => {
22 |   const containerRef = useRef<HTMLDivElement | null>(null);
23 |   const prefersReducedMotion = useReducedMotion();
24 |
25 |   useGSAP(() => {
26 |     if (prefersReducedMotion || !containerRef.current) return;
27 |
28 |     const ctx = gsap.context(() => {
29 |       // 1. Locate and animate all images
30 |       const images = containerRef.current?.querySelectorAll(".story-image-target");
31 |       images?.forEach((image) => {
32 |         applyImageTransition(image, containerRef.current!);
33 |       });
34 |
35 |       // 2. Locate and animate all text blocks
36 |       const textContainers = containerRef.current?.querySelectorAll(".story-text-container");
37 |       textContainers?.forEach((textContainer) => {
38 |         applyTextTransition(textContainer);
39 |       });
40 |     }, containerRef);
41 |
42 |     return () => ctx.revert();
43 |   }, [prefersReducedMotion]);
44 |
45 |   return (
46 |     <div
47 |       ref={containerRef}
48 |       id={id}
49 |       className={cn("w-full relative", className)}
50 |     >
51 |       {children}
52 |     </div>
53 |   );
54 | };
55 | export default AnimatedSection;
56 |

```

42. src/components/storytelling/ImageExpansionStory.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 |
5 | interface ParallaxBannerProps {
6 |   imageSrc: string;
7 |   label?: string;
8 |   height?: string;
9 | }
10 |
11 | export const ParallaxBanner: React.FC<ParallaxBannerProps> = ({
12 |   imageSrc,
13 |   label = "Parallax section",
14 |   height = "45vh",
15 | }) => (
16 |   <div
17 |     role="img"
18 |     aria-label={label}
19 |     className="relative w-full overflow-hidden"
20 |     style={{ height }}
21 |   >
22 |     /* Fixed background image */
23 |     <div
24 |       className="absolute inset-0"
25 |       style={{
26 |         backgroundImage: `url("${imageSrc}")`,
27 |         backgroundAttachment: "fixed",
28 |         backgroundSize: "cover",
29 |         backgroundPosition: "center center",
30 |         backgroundRepeat: "no-repeat",
31 |       }}
32 |     />
33 |
34 |     /* Vignette: dark edges, bright centre */
35 |     <div
36 |       className="absolute inset-0 pointer-events-none"
37 |       style={{
38 |         background:
39 |           "radial-gradient(ellipse at center, transparent 40%, rgba(0,0,0,0.45) 100%)",
40 |       }}
41 |     />
42 |
43 |     /* Top fade - blends into the section above */
44 |     <div className="absolute inset-x-0 top-0 h-24 bg-gradient-to-b from-black/30 to-transparent pointer-events-none"
45 |     />
46 |
47 |     /* Bottom fade - blends into the section below */
48 |     <div className="absolute inset-x-0 bottom-0 h-24 bg-gradient-to-t from-black/30 to-transparent pointer-events-none"
49 |     />
50 |
51 |     /* Subtle film grain */
52 |     <div
53 |       className="absolute inset-0 opacity-[0.06] pointer-events-none mix-blend-overlay"
54 |       style={{
55 |         backgroundImage: `url("data:image/svg+xml,%3Csvg viewBox='0 0 200 200'
56 |           xmlns='http://www.w3.org/2000/svg'%3E%3Cfilter id='n'%3E%3CfeTurbulence type='fractalNoise' baseFrequency='0.75'
57 |           numOctaves='4' stitchTiles='stitch'%3E%3C/filter%3E%3Crect width='100%25' height='100%25'
58 |           filter='url(%23n)'%3E%3C/svg%3E")`,
59 |         backgroundSize: "200px 200px",
60 |       }}
61 |     />
62 |   </div>
63 | );
64 |
65 | // Convenience export for the first banner (after Our Focus)
66 | export const ImageExpansionStory: React.FC = () => (
67 |   <ParallaxBanner

```

```
63 |   imageSrc="/classroom-robotics.png"
64 |   label="Children collaborating on robotics kits in classroom"
65 | />
66 | );
67 |
68 | export default ImageExpansionStory;
69 |
```

43. src/components/storytelling/ParallaxImage.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { useGSAP } from "@hooks/useGSAP";
5 | import { useReducedMotion } from "@hooks/useReducedMotion";
6 | import gsap from "gsap";
7 | import ScrollTrigger from "gsap/ScrollTrigger";
8 | import { cn } from "@utils/cn";
9 |
10 | export interface ParallaxImageProps {
11 |   children: React.ReactNode;
12 |   speed?: 0.8 | 0.5 | 0.3; // Speed multipliers: 0.8 for image, 0.5 for decor, 0.3 for glows
13 |   className?: string;
14 | }
15 |
16 | export const ParallaxImage: React.FC<ParallaxImageProps> = ({
17 |   children,
18 |   speed = 0.8,
19 |   className,
20 | }) => {
21 |   const containerRef = useRef<HTMLDivElement | null>(null);
22 |   const elementRef = useRef<HTMLDivElement | null>(null);
23 |   const prefersReducedMotion = useReducedMotion();
24 |
25 |   useGSAP(() => {
26 |     if (prefersReducedMotion || !containerRef.current || !elementRef.current) return;
27 |
28 |     gsap.registerPlugin(ScrollTrigger);
29 |
30 |     // Compute the offset based on speed (higher speed = less parallax shift)
31 |     const parallaxOffset = (1 - speed) * 120; // range in pixels
32 |
33 |     const tween = gsap.fromTo(
34 |       elementRef.current,
35 |       { y: -parallaxOffset },
36 |       {
37 |         y: parallaxOffset,
38 |         ease: "none",
39 |         scrollTrigger: {
40 |           trigger: containerRef.current,
41 |           start: "top bottom",
42 |           end: "bottom top",
43 |           scrub: true,
44 |         },
45 |       },
46 |     );
47 |
48 |     return () => {
49 |       if (tween.scrollTrigger) {
50 |         tween.scrollTrigger.kill();
51 |       }
52 |       tween.kill();
53 |     };
54 |   }, [prefersReducedMotion, speed]);
55 |
56 |   return (
57 |     <div
58 |       ref={containerRef}
59 |       className={cn("relative overflow-hidden w-full h-full", className)}
60 |     >
61 |       <div
62 |         ref={elementRef}
63 |         className="w-full h-full will-change-transform"
64 |       >
65 |         {children}
66 |       </div>
67 |     </div>

```



```
68 | );  
69 | };  
70 | export default ParallaxImage;  
71 |
```

44. src/components/storytelling/RevealImage.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import Image from "next/image";
5 | import { useGSAP } from "@/hooks/useGSAP";
6 | import { useReducedMotion } from "@/hooks/useReducedMotion";
7 | import { applyImageTransition } from "@/animations/imageTransitions";
8 | import { cn } from "@/utils/cn";
9 |
10 | export interface RevealImageProps {
11 |   src: string;
12 |   alt: string;
13 |   className?: string;
14 |   containerClassName?: string;
15 |   priority?: boolean;
16 |   aspectRatio?: string; // e.g. "aspect-video" or "aspect-[4/3]"
17 | }
18 |
19 | export const RevealImage: React.FC<RevealImageProps> = ({
20 |   src,
21 |   alt,
22 |   className,
23 |   containerClassName,
24 |   priority = false,
25 |   aspectRatio = "aspect-video",
26 | }) => {
27 |   const containerRef = useRef<HTMLDivElement | null>(null);
28 |   const imageWrapperRef = useRef<HTMLDivElement | null>(null);
29 |   const prefersReducedMotion = useReducedMotion();
30 |
31 |   useGSAP(() => {
32 |     if (prefersReducedMotion || !containerRef.current || !imageWrapperRef.current) return;
33 |
34 |     const timeline = applyImageTransition(imageWrapperRef.current, containerRef.current);
35 |
36 |     return () => {
37 |       if (timeline.scrollTrigger) {
38 |         timeline.scrollTrigger.kill();
39 |       }
40 |       timeline.kill();
41 |     };
42 |   }, [prefersReducedMotion]);
43 |
44 |   return (
45 |     <div
46 |       ref={containerRef}
47 |       className={cn(
48 |         "w-full overflow-hidden rounded-[32px] border border-#[111827]/5 shadow-[0_4px_20px_-4px_rgba(0,0,0,0.02)]
49 |         select-none",
50 |         aspectRatio,
51 |         containerClassName
52 |       )}
53 |     >
54 |       <div
55 |         ref={imageWrapperRef}
56 |         className={cn(
57 |           "relative w-full h-full will-change-[transform,opacity,filter]",
58 |           prefersReducedMotion ? "opacity-100" : "opacity-0 scale-94 blur-[10px] translate-y-[160px]"
59 |         )}
60 |       >
61 |         <Image
62 |           src={src}
63 |           alt={alt}
64 |           fill
65 |           sizes="(max-width: 1024px) 100vw, 50vw"
66 |           className={cn("object-cover", className)}
67 |           priority={priority}

```

```
67 | />
68 | </div>
69 | </div>
70 | );
71 | };
72 | export default RevealImage;
73 |
```

45. src/components/storytelling/RevealText.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { useGSAP } from "@hooks/useGSAP";
5 | import { useReducedMotion } from "@hooks/useReducedMotion";
6 | import { applyTextTransition } from "@animations/textTransitions";
7 | import { cn } from "@utils/cn";
8 |
9 | export interface RevealTextProps {
10 |   children: React.ReactNode;
11 |   className?: string;
12 |   start?: string;
13 |   end?: string;
14 | }
15 |
16 | export const RevealText: React.FC<RevealTextProps> = ({
17 |   children,
18 |   className,
19 |   start = "top 85%",
20 |   end = "bottom 20%",
21 | }) => {
22 |   const containerRef = useRef<HTMLDivElement | null>(null);
23 |   const prefersReducedMotion = useReducedMotion();
24 |
25 |   useGSAP(() => {
26 |     if (prefersReducedMotion || !containerRef.current) return;
27 |
28 |     const timeline = applyTextTransition(containerRef.current, { start, end });
29 |
30 |     return () => {
31 |       if (timeline.scrollTrigger) {
32 |         timeline.scrollTrigger.kill();
33 |       }
34 |       timeline.kill();
35 |     };
36 |   }, [prefersReducedMotion, start, end]);
37 |
38 |   return (
39 |     <div
40 |       ref={containerRef}
41 |       className={cn("flex flex-col gap-4 text-left", className)}
42 |     >
43 |       {React.Children.map(children, (child) => {
44 |         if (!React.isValidElement(child)) return child;
45 |
46 |         const element = child as React.ReactElement<{ className?: string; label?: string }>;
47 |
48 |         // Automatically assign target hooks to paragraphs and buttons
49 |         const isHeading = ["h1", "h2", "h3", "h4", "h5", "h6"].includes(
50 |           typeof element.type === "string" ? element.type : ""
51 |         );
52 |         const isButton = element.props.className?.includes("button") || element.type === "button" || element.props.label
53 |           !== undefined;
54 |
55 |         let childClass = "story-paragraph will-change-[transform,opacity] translate-y-10 opacity-0";
56 |         if (isHeading) {
57 |           childClass = ""; // Heading handles its own staging via AnimatedHeading
58 |         } else if (isButton) {
59 |           childClass = "story-button will-change-[transform,opacity] scale-95 opacity-0 inline-block w-fit";
60 |         }
61 |
62 |         return React.cloneElement(element, {
63 |           ...element.props,
64 |           className: cn(element.props.className, prefersReducedMotion ? "" : childClass),
65 |         } as React.HTMLAttributes<HTMLElement>);
66 |       })
67 |     </div>

```

```
67 | );  
68 | };  
69 | export default RevealText;  
70 |
```

46. src/components/storytelling/ScrollReveal.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { useGSAP } from "@hooks/useGSAP";
5 | import { useReducedMotion } from "@hooks/useReducedMotion";
6 | import gsap from "gsap";
7 | import ScrollTrigger from "gsap/ScrollTrigger";
8 | import { cn } from "@utils/cn";
9 |
10 | export interface ScrollRevealProps {
11 |   children: React.ReactNode;
12 |   className?: string;
13 |   delay?: number;
14 |   duration?: number;
15 |   direction?: "up" | "down" | "left" | "right";
16 |   offset?: number; // Distance in pixels to move
17 |   scrub?: boolean | number;
18 |   start?: string;
19 | }
20 |
21 | export const ScrollReveal: React.FC<ScrollRevealProps> = ({
22 |   children,
23 |   className,
24 |   delay = 0,
25 |   duration = 1.0,
26 |   direction = "up",
27 |   offset = 50,
28 |   scrub = 1,
29 |   start = "top 90%",
30 | }) => {
31 |   const elementRef = useRef<HTMLDivElement | null>(null);
32 |   const prefersReducedMotion = useReducedMotion();
33 |
34 |   useGSAP(() => {
35 |     if (prefersReducedMotion || !elementRef.current) return;
36 |
37 |     gsap.registerPlugin(ScrollTrigger);
38 |
39 |     // Establish coordinates based on direction
40 |     let xVal = 0;
41 |     let yVal = 0;
42 |     if (direction === "up") yVal = offset;
43 |     if (direction === "down") yVal = -offset;
44 |     if (direction === "left") xVal = offset;
45 |     if (direction === "right") xVal = -offset;
46 |
47 |     const tween = gsap.fromTo(
48 |       elementRef.current,
49 |       {
50 |         opacity: 0,
51 |         x: xVal,
52 |         y: yVal,
53 |       },
54 |       {
55 |         opacity: 1,
56 |         x: 0,
57 |         y: 0,
58 |         ease: "power2.out",
59 |         delay,
60 |         duration,
61 |         scrollTrigger: {
62 |           trigger: elementRef.current,
63 |           start,
64 |           end: "bottom 30%",
65 |           scrub,
66 |         },
67 |       }

```

```
68 | );
69 |
70 | return () => {
71 |   if (tween.scrollTrigger) {
72 |     tween.scrollTrigger.kill();
73 |   }
74 |   tween.kill();
75 | };
76 | }, [prefersReducedMotion, delay, duration, direction, offset, scrub, start]);
77 |
78 | return (
79 |   <div
80 |     ref={elementRef}
81 |     className={cn(
82 |       "will-change-[transform,opacity]",
83 |       prefersReducedMotion ? "opacity-100 translate-y-0" : "opacity-0",
84 |       className
85 |     )}
86 |   >
87 |     {children}
88 |   </div>
89 | );
90 | };
91 | export default ScrollReveal;
92 |
```

47. src/components/storytelling/SectionWrapper.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { cn } from "@utils/cn";
5 | import { useReducedMotion } from "@hooks/useReducedMotion";
6 | import { useGSAP } from "@hooks/useGSAP";
7 | import gsap from "gsap";
8 | import ScrollTrigger from "gsap/ScrollTrigger";
9 |
10 | export interface SectionWrapperProps {
11 |   children: React.ReactNode;
12 |   id?: string;
13 |   className?: string;
14 |   glowPosition?: "top-left" | "bottom-right" | "center" | "none";
15 |   bgColor?: string; // custom background override
16 | }
17 |
18 | export const SectionWrapper: React.FC<SectionWrapperProps> = ({
19 |   children,
20 |   id,
21 |   className,
22 |   glowPosition = "none",
23 |   bgColor = "bg-cream/40",
24 | }) => {
25 |   const sectionRef = useRef<HTMLDivElement | null>(null);
26 |   const glowRef = useRef<HTMLDivElement | null>(null);
27 |   const prefersReducedMotion = useReducedMotion();
28 |
29 |   // Subtle background glow drift on scroll
30 |   useGSAP(() => {
31 |     if (prefersReducedMotion || !sectionRef.current || !glowRef.current || glowPosition === "none") return;
32 |
33 |     gsap.registerPlugin(ScrollTrigger);
34 |
35 |     const tween = gsap.fromTo(
36 |       glowRef.current,
37 |       { y: -30, scale: 0.95 },
38 |       {
39 |         y: 30,
40 |         scale: 1.05,
41 |         ease: "none",
42 |         scrollTrigger: {
43 |           trigger: sectionRef.current,
44 |           start: "top bottom",
45 |           end: "bottom top",
46 |           scrub: true,
47 |         },
48 |       },
49 |     );
50 |
51 |     return () => {
52 |       if (tween.scrollTrigger) {
53 |         tween.scrollTrigger.kill();
54 |       }
55 |       tween.kill();
56 |     };
57 |   }, [prefersReducedMotion, glowPosition]);
58 |
59 |   return (
60 |     <section
61 |       ref={sectionRef}
62 |       id={id}
63 |       className={cn(
64 |         "relative py-20 lg:py-32 flex flex-col justify-center items-center overflow-hidden w-full select-none",
65 |         bgColor,
66 |         className
67 |       )}

```



```

68 | >
69 | {/* 1) Subtle Grain/Noise overlay */}
70 | <div
71 |   className="absolute inset-0 opacity-[0.015] pointer-events-none z-0"
72 |   style={{
73 |     backgroundImage: `url("data:image/svg+xml,%3Csvg viewBox='0 0 200 200'
xmlns='http://www.w3.org/2000/svg'%3E%3Cfilter id='n'%3E%3CfeTurbulence type='fractalNoise' baseFrequency='0.85'
numOctaves='3' stitchTiles='stitch'/%3E%3C/filter%3E%3Crect width='100%25' height='100%25' filter='url(%23n)'
opacity='0.5'/%3E%3C/svg%3E")`,
74 |   }}
75 | />
76 |
77 | {/* 2) Ambient Glow Element */}
78 | {glowPosition !== "none" && (
79 |   <div
80 |     ref={glowRef}
81 |     className={cn(
82 |       "absolute rounded-full bg-gold/5 blur-[100px] w-[35vw] h-[35vw] pointer-events-none z-0
will-change-[transform,scale]",
83 |       glowPosition === "top-left" && "top-[10%] left-[10%]",
84 |       glowPosition === "bottom-right" && "bottom-[10%] right-[10%]",
85 |       glowPosition === "center" && "top-1/2 left-1/2 -translate-x-1/2 -translate-y-1/2"
86 |     )}
87 |   />
88 | )}
89 |
90 | {/* 3) Main layout container slot */}
91 | <div className="w-full relative z-10">
92 |   {children}
93 | </div>
94 | </section>
95 | );
96 | };
97 | export default SectionWrapper;
98 |

```

48. src/components/storytelling/StoryScroller/AnimatedHeading.tsx

```
1 | "use client";
2 |
3 | import React from "react";
4 | import { cn } from "@utils/cn";
5 |
6 | interface AnimatedHeadingProps {
7 |   title: string;
8 |   className?: string;
9 | }
10 |
11 | export const AnimatedHeading: React.FC<AnimatedHeadingProps> = ({
12 |   title,
13 |   className,
14 | }) => {
15 |   const words = title.split(" ");
16 |
17 |   return (
18 |     <h3
19 |       className={cn(
20 |         "text-4xl sm:text-5xl font-extrabold text-charcoal font-heading leading-tight flex flex-wrap gap-x-3
overflow-hidden py-1.5",
21 |         className
22 |       )}
23 |     >
24 |     {words.map((word, i) => (
25 |       <span key={i} className="relative inline-block overflow-hidden select-none">
26 |         <span
27 |           className="story-heading-word inline-block translate-y-[100%] opacity-0 will-change-transform"
28 |         >
29 |           {word}
30 |         </span>
31 |       </span>
32 |     ))}
33 |   </h3>
34 | );
35 | };
36 | export default AnimatedHeading;
37 |
```

49. src/components/storytelling/StoryScroller/StoryBackground.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 |
5 | export const StoryBackground: React.FC = () => {
6 |   return (
7 |     <div
8 |       className="story-bg-layer absolute inset-0 z-0 overflow-hidden pointer-events-none transition-colors
duration-1000 bg-cream"
9 |     >
10 |      {/* 1) Subtle Grain/Noise Overlay */}
11 |      <div
12 |        className="absolute inset-0 opacity-[0.02]"
13 |        style={{
14 |          backgroundImage: `url("data:image/svg+xml,%3Csvg viewBox='0 0 200 200'
xmlns='http://www.w3.org/2000/svg'%3E%3Cfilter id='n'%3E%3CfeTurbulence type='fractalNoise' baseFrequency='0.8'
numOctaves='4' stitchTiles='stitch'/%3E%3C/filter%3E%3Crect width='100%25' height='100%25' filter='url(%23n)'
opacity='0.5'/%3E%3C/svg%3E")`,
15 |        }}
16 |      />
17 |
18 |      {/* 2) Ambient Light Glow Sweeps */}
19 |      <div
20 |        className="story-bg-glow absolute top-1/4 left-1/4 w-[45vw] h-[45vw] rounded-full bg-gold/5 blur-[120px]
will-change-transform"
21 |      />
22 |
23 |      {/* 3) Floating SVG Line art */}
24 |      <div className="story-bg-svg absolute right-[8%] bottom-[10%] w-[350px] h-[350px] text-forest/5 select-none
will-change-transform">
25 |        <svg viewBox="0 0 24 24" fill="none" stroke="currentColor" strokeWidth="0.3" className="w-full h-full">
26 |          <path d="M12 2C6.5 2 2 6.5 2 12c0 4.5 3 8 7 9.5V22h6v-.5c4-1.5 7-5 7-9.5 0-5.5-4.5-10-10-10z M12 22V12c0-3 3-5
6-5 M12 16c0-3-3-5-6-5" />
27 |        </svg>
28 |      </div>
29 |    </div>
30 |  );
31 | };
32 | export default StoryBackground;
33 |

```

50. src/components/storytelling/StoryScroller/StoryContent.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { STORY_STEPS } from "@/constants/storyData";
5 | import { AnimatedHeading } from "../AnimatedHeading";
6 | import { Button } from "@components/ui/Button";
7 | import { ArrowRight } from "lucide-react";
8 | import { cn } from "@utils/cn";
9 |
10 | export const StoryContent: React.FC = () => {
11 |   return (
12 |     <div className="relative w-full min-h-[360px] md:min-h-[400px]">
13 |       {STORY_STEPS.map((step, idx) => (
14 |         <div
15 |           key={step.id}
16 |           className={cn(
17 |             `story-content-block-${idx} absolute inset-0 w-full flex flex-col gap-5 text-left
will-change-[opacity,transform]`,
18 |             idx === 0 ? "opacity-100 z-10 pointer-events-auto" : "opacity-0 z-0 pointer-events-none"
19 |           )}
20 |         >
21 |           {/* Badge Eyebrow */}
22 |           <div className={`story-badge-${idx} will-change-[opacity,transform]`}>
23 |             <span className="badge-gold">
24 |               {step.badge}
25 |             </span>
26 |           </div>
27 |
28 |           {/* Heading with line mask reveal */}
29 |           <AnimatedHeading title={step.title} className={`story-heading-container-${idx}`} />
30 |
31 |           {/* Subtitle / Description */}
32 |           <p
33 |             className={cn(
34 |               `story-description-${idx} text-base text-charcoal/70 leading-relaxed font-body max-w-md
will-change-[opacity,transform]`,
35 |               idx !== 0 && "translate-y-[30px] opacity-0"
36 |             )}
37 |           >
38 |             {step.description}
39 |           </p>
40 |
41 |           {/* Action CTA Button */}
42 |           <div
43 |             className={cn(
44 |               `story-button-${idx} pt-3 will-change-[opacity,transform]`,
45 |               idx !== 0 && "scale-[0.95] opacity-0"
46 |             )}
47 |           >
48 |             <Button
49 |               label={step.buttonText}
50 |               variant="primary"
51 |               size="md"
52 |               icon={<ArrowRight size={16} />}
53 |               iconPosition="right"
54 |               href={step.buttonLink}
55 |               className="bg-navy hover:bg-forest text-white"
56 |             />
57 |           </div>
58 |         </div>
59 |       )}
60 |     </div>
61 |   );
62 | };
63 | export default StoryContent;
64 |

```


51. src/components/storytelling/StoryScroller/StoryControls.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { useStory } from "@/context/StoryContext";
5 | import { ChevronUp, ChevronDown } from "lucide-react";
6 | import { cn } from "@/utils/cn";
7 |
8 | export const StoryControls: React.FC = () => {
9 |   const { activeStep, stepsCount, scrollToStep } = useStory();
10 |
11 |   const handlePrev = () => {
12 |     if (activeStep > 0) {
13 |       scrollToStep(activeStep - 1);
14 |     }
15 |   };
16 |
17 |   const handleNext = () => {
18 |     if (activeStep < stepsCount - 1) {
19 |       scrollToStep(activeStep + 1);
20 |     }
21 |   };
22 |
23 |   return (
24 |     <div className="flex gap-2 items-center" aria-label="Story navigation controls">
25 |       <button
26 |         onClick={handlePrev}
27 |         disabled={activeStep === 0}
28 |         className={cn(
29 |           "p-2 rounded-full border border-charcoal/10 transition-colors focus:outline-none focus-visible:ring-2
focus-visible:ring-forest cursor-pointer",
30 |           activeStep === 0
31 |             ? "opacity-40 cursor-not-allowed"
32 |             : "hover:bg-charcoal/5 text-charcoal"
33 |         )}
34 |         aria-label="Previous story"
35 |       >
36 |         <ChevronUp size={16} />
37 |       </button>
38 |
39 |       <button
40 |         onClick={handleNext}
41 |         disabled={activeStep === stepsCount - 1}
42 |         className={cn(
43 |           "p-2 rounded-full border border-charcoal/10 transition-colors focus:outline-none focus-visible:ring-2
focus-visible:ring-forest cursor-pointer",
44 |           activeStep === stepsCount - 1
45 |             ? "opacity-40 cursor-not-allowed"
46 |             : "hover:bg-charcoal/5 text-charcoal"
47 |         )}
48 |         aria-label="Next story"
49 |       >
50 |         <ChevronDown size={16} />
51 |       </button>
52 |     </div>
53 |   );
54 | };
55 | export default StoryControls;
56 |

```

52. src/components/storytelling/StoryScroller/StoryImage.tsx

```

1 | "use client";
2 |
3 | import React, { useState } from "react";
4 | import Image from "next/image";
5 | import { STORY_STEPS } from "@/constants/storyData";
6 | import { cn } from "@/utils/cn";
7 |
8 | export const StoryImage: React.FC = () => {
9 |   const [loaded, setLoaded] = useState<Record<number, boolean>>({});
10 |
11 |   const handleLoad = (idx: number) => {
12 |     setLoaded((prev) => ({ ...prev, [idx]: true }));
13 |   };
14 |
15 |   return (
16 |     <div className="w-full h-full relative rounded-[32px] overflow-hidden shadow-premium border border-charcoal/5
bg-sage/10 select-none">
17 |       {STORY_STEPS.map((step, idx) => (
18 |         <div
19 |           key={step.id}
20 |           className={cn(
21 |             `story-image-frame-${idx} absolute inset-0 w-full h-full will-change-[opacity,transform,filter]`,
22 |             idx === 0 ? "opacity-100 z-10 scale-100 blur-0" : "opacity-0 z-0 scale-108 blur-[12px]"
23 |           )}
24 |           style={{
25 |             transformStyle: "preserve-3d",
26 |             backfaceVisibility: "hidden",
27 |           }}
28 |         >
29 |           /* Shimmer Placeholder until decoded */
30 |           {!loaded[idx] && (
31 |             <div className="absolute inset-0 bg-neutral-200 animate-pulse z-20" />
32 |           )}
33 |
34 |           <Image
35 |             src={step.imageSrc}
36 |             alt={step.imageAlt}
37 |             fill
38 |             className="object-cover pointer-events-none"
39 |             sizes="(max-width: 768px) 100vw, 50vw"
40 |             priority={idx <= 2} // Eager load the first 3 images for immediate interaction
41 |             onLoad={() => handleLoad(idx)}
42 |           />
43 |           /* Subtle cinematic gradient bottom overlay */
44 |           <div className="absolute inset-0 bg-gradient-to-t from-charcoal/30 via-transparent to-transparent
pointer-events-none z-10" />
45 |         </div>
46 |       )}
47 |     </div>
48 |   );
49 | };
50 | export default StoryImage;
51 |

```

53. src/components/storytelling/StoryScroller/StoryNavigation.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { STORY_STEPS } from "@/constants/storyData";
5 | import { cn } from "@/utils/cn";
6 | import { motion } from "framer-motion";
7 |
8 | interface StoryNavigationProps {
9 |   activeStory: number;
10 |   scrollToStep: (index: number) => void;
11 | }
12 |
13 | export const StoryNavigation: React.FC<StoryNavigationProps> = ({
14 |   activeStory,
15 |   scrollToStep,
16 | }) => {
17 |   return (
18 |     <nav
19 |       className="hidden lg:flex flex-col gap-6 border-l-2 border-charcoal/10 pl-6 py-4 relative select-none"
20 |       aria-label="Story Chapters navigation"
21 |     >
22 |       {STORY_STEPS.map((step, idx) => {
23 |         const isActive = idx === activeStory;
24 |
25 |         return (
26 |           <button
27 |             key={step.id}
28 |             onClick={() => scrollToStep(idx)}
29 |             className={cn(
30 |               "text-left flex flex-col gap-1 transition-all duration-300 group focus:outline-none focus-visible:ring-2
31 |               focus-visible:ring-forest focus-visible:ring-offset-2 rounded-lg p-1 w-full max-w-[180px] cursor-pointer",
32 |               isActive ? "text-charcoal" : "text-charcoal/40 hover:text-charcoal/70"
33 |             )}
34 |             aria-current={isActive ? "step" : undefined}
35 |           >
36 |             <span className="text-[10px] font-heading font-extrabold tracking-widest uppercase block">
37 |               {String(idx + 1).padStart(2, "0")}
38 |             </span>
39 |             <span className="text-xs font-semibold font-body tracking-wide block truncate">
40 |               {step.title}
41 |             </span>
42 |           </button>
43 |         );
44 |       })}
45 |       { /* Floating active highlight indicator bar */ }
46 |       <motion.div
47 |         animate={{ y: activeStory * 58 }} // Align index offset to button layout
48 |         transition={{ type: "spring", stiffness: 300, damping: 30 }}
49 |         className="absolute left-[-2px] top-4 w-[2px] h-10 bg-gold rounded-full"
50 |       />
51 |     </nav>
52 |   );
53 | };
54 | export default StoryNavigation;
55 |

```


54. src/components/storytelling/StoryScroller/StoryProgress.tsx

```
1 | "use client";
2 |
3 | import React from "react";
4 | import { STORY_STEPS } from "@/constants/storyData";
5 |
6 | interface StoryProgressProps {
7 |   activeStory: number;
8 | }
9 |
10 | export const StoryProgress: React.FC<StoryProgressProps> = ({ activeStory }) => {
11 |   const currentFormatted = String(activeStory + 1).padStart(2, "0");
12 |   const totalFormatted = String(STORY_STEPS.length).padStart(2, "0");
13 |
14 |   return (
15 |     <div className="flex items-center gap-4 text-xs font-heading font-bold select-none text-charcoal/60">
16 |       <span>{currentFormatted}</span>
17 |
18 |       { /* Progress Bar Rail */ }
19 |       <div className="w-24 h-[2px] bg-charcoal/10 rounded-full overflow-hidden relative">
20 |         <div
21 |           className="story-progress-bar absolute inset-y-0 left-0 right-0 bg-gold origin-left rounded-full scale-x-0
will-change-transform"
22 |         />
23 |       </div>
24 |
25 |       <span>{totalFormatted}</span>
26 |     </div>
27 |   );
28 | };
29 | export default StoryProgress;
30 |
```

55. src/components/storytelling/StoryScroller/index.tsx

```

1 | "use client";
2 |
3 | import React, { useRef, useState, useEffect } from "react";
4 | import { useMotionValue } from "framer-motion";
5 | import gsap from "gsap";
6 | import ScrollTrigger from "gsap/ScrollTrigger";
7 | import { useGSAP } from "@/hooks/useGSAP";
8 | import { STORY_STEPS } from "@/constants/storyData";
9 | import { Container } from "@/components/ui/Container";
10 | import { useTheme } from "@/components/providers/ThemeProvider";
11 |
12 | import { StoryBackground } from "../StoryBackground";
13 | import { StoryImage } from "../StoryImage";
14 | import { StoryContent } from "../StoryContent";
15 | import { StoryNavigation } from "../StoryNavigation";
16 | import { Button } from "@/components/ui/Button";
17 | import Image from "next/image";
18 | import { ArrowRight } from "lucide-react";
19 |
20 | export const StoryScroller: React.FC = () => {
21 |   const containerRef = useRef<HTMLDivElement | null>(null);
22 |   const scrollTriggerRef = useRef<ScrollTrigger | null>(null);
23 |
24 |   const { theme } = useTheme();
25 |
26 |   // States
27 |   const [activeStory, setActiveStory] = useState(0);
28 |   const [isMobile, setIsMobile] = useState(false);
29 |   const [prefersReducedMotion, setPrefersReducedMotion] = useState(false);
30 |
31 |   // Track progress as a MotionValue for React integrations
32 |   const progressVal = useMotionValue(0);
33 |
34 |   useEffect(() => {
35 |     if (typeof window === "undefined") return;
36 |
37 |     const checkMobile = () => {
38 |       setIsMobile(window.innerWidth < 1024);
39 |     };
40 |
41 |     const motionQuery = window.matchMedia("(prefers-reduced-motion: reduce)");
42 |
43 |     const frameId = requestAnimationFrame(() => {
44 |       setPrefersReducedMotion(motionQuery.matches);
45 |       checkMobile();
46 |     });
47 |
48 |     window.addEventListener("resize", checkMobile);
49 |     return () => {
50 |       cancelAnimationFrame(frameId);
51 |       window.removeEventListener("resize", checkMobile);
52 |     };
53 |   }, []);
54 |
55 |   // GSAP Master ScrollTrigger Timeline
56 |   useGSAP(() => {
57 |     if (isMobile || prefersReducedMotion || !containerRef.current) return;
58 |
59 |     gsap.registerPlugin(ScrollTrigger);
60 |
61 |     const darkBgColors = ["#141A16", "#121915", "#0E161C", "#191411", "#151515"];
62 |     const getStepBgColor = (idx: number) => {
63 |       return theme === "dark" ? darkBgColors[idx] : STORY_STEPS[idx].bgColor;
64 |     };
65 |
66 |     // Initial state setup for heading words of step 0 and background layer
67 |     gsap.set(".story-heading-container-0 .story-heading-word", {

```

```

68 | y: "0%",
69 | opacity: 1,
70 | });
71 | gsap.set(".story-bg-layer", {
72 |   backgroundColor: getStepBgColor(0),
73 | });
74 |
75 | const tl = gsap.timeline({
76 |   scrollTrigger: {
77 |     trigger: containerRef.current,
78 |     start: "top top",
79 |     end: "+=400%", // 500vh scroll height total
80 |     pin: true,
81 |     scrub: 1,
82 |     anticipatePin: 1,
83 |     onUpdate: (self) => {
84 |       progressVal.set(self.progress);
85 |       const calculatedIndex = Math.min(
86 |         STORY_STEPS.length - 1,
87 |         Math.floor(self.progress * STORY_STEPS.length)
88 |       );
89 |       const clampedIndex = Math.max(0, calculatedIndex);
90 |       if (clampedIndex !== activeStory) {
91 |         setActiveStory(clampedIndex);
92 |       }
93 |     },
94 |   },
95 | });
96 |
97 | scrollTriggerRef.current = tl.scrollTrigger as ScrollTrigger;
98 |
99 | // Timeline duration base: 1 unit per story phase
100 | const stepDuration = 1;
101 | const transitionDuration = 0.3; // crossfade speed ratio
102 |
103 | // 2) Program transition sequences for each slide step
104 | for (let i = 0; i < STORY_STEPS.length - 1; i++) {
105 |   const startTransitionTime = (i + 1) * stepDuration - transitionDuration;
106 |
107 |   // ■■ EXIT CURRENT SLIDE (i) ■■
108 |   // Fade out image
109 |   tl.to(`.story-image-frame-${i}`, {
110 |     opacity: 0,
111 |     scale: 1.08,
112 |     filter: "blur(12px)",
113 |     duration: transitionDuration,
114 |     ease: "power2.inOut",
115 |   }, startTransitionTime);
116 |
117 |   // Fade out text content elements
118 |   tl.to(`.story-content-block-${i}`, {
119 |     opacity: 0,
120 |     y: -20,
121 |     duration: transitionDuration,
122 |     ease: "power2.inOut",
123 |   }, startTransitionTime);
124 |
125 |   // ■■ ENTER NEXT SLIDE (i+1) ■■
126 |   // Transition background color tint
127 |   tl.to(".story-bg-layer", {
128 |     backgroundColor: getStepBgColor(i + 1),
129 |     duration: transitionDuration,
130 |     ease: "power1.inOut",
131 |   }, startTransitionTime);
132 |
133 |   // Animate background glow movement
134 |   tl.to(".story-bg-glow", {
135 |     x: (i + 1) * 60,
136 |     y: (i + 1) * 20,
137 |     duration: transitionDuration,

```

```

138 | ease: "power1.inOut",
139 | }, startTransitionTime);
140 |
141 | // Fade in next image
142 | tl.to(`.story-image-frame-${i + 1}`, {
143 | opacity: 1,
144 | scale: 1,
145 | filter: "blur(0px)",
146 | duration: transitionDuration,
147 | ease: "power2.out",
148 | }, startTransitionTime);
149 |
150 | // Fade in next content wrapper
151 | tl.to(`.story-content-block-${i + 1}`, {
152 | opacity: 1,
153 | y: 0,
154 | duration: transitionDuration,
155 | ease: "power2.out",
156 | }, startTransitionTime);
157 |
158 | // Stagger next heading words reveal (line-by-line mask)
159 | tl.fromTo(`.story-heading-container-${i + 1} .story-heading-word`, {
160 | y: "100%",
161 | opacity: 0,
162 | }, {
163 | y: "0%",
164 | opacity: 1,
165 | stagger: 0.08,
166 | duration: 0.5,
167 | ease: "power3.out",
168 | }, startTransitionTime + 0.1);
169 |
170 | // Fade up next description
171 | tl.fromTo(`.story-description-${i + 1}`, {
172 | y: 30,
173 | opacity: 0,
174 | }, {
175 | y: 0,
176 | opacity: 1,
177 | duration: 0.5,
178 | ease: "power2.out",
179 | }, startTransitionTime + 0.2);
180 |
181 | // Scale up next action button
182 | tl.fromTo(`.story-button-${i + 1}`, {
183 | scale: 0.95,
184 | opacity: 0,
185 | }, {
186 | scale: 1,
187 | opacity: 1,
188 | duration: 0.4,
189 | ease: "back.out(1.7)",
190 | }, startTransitionTime + 0.3);
191 | }
192 |
193 | return () => {
194 |   if (tl.scrollTrigger) {
195 |     tl.scrollTrigger.kill();
196 |   }
197 |   tl.kill();
198 | };
199 | }, [theme, isMobile, prefersReducedMotion]);
200 |
201 | // Handle sidebar navigation clicks
202 | const scrollToStep = (index: number) => {
203 |   if (isMobile) {
204 |     const targetCard = document.getElementById(`mobile-story-card-${index}`);
205 |     if (targetCard) {
206 |       targetCard.scrollIntoView({ behavior: "smooth", block: "center" });
207 |     }

```

```

208 | return;
209 | }
210 |
211 | const trigger = scrollTriggerRef.current;
212 | if (trigger) {
213 |   const start = trigger.start;
214 |   const end = trigger.end;
215 |   const distance = end - start;
216 |   // Map index ratio to absolute window scroll coordinates
217 |   const targetPosition = start + (index / (STORY_STEPS.length - 1)) * distance;
218 |
219 |   window.scrollTo({
220 |     top: targetPosition,
221 |     behavior: "smooth",
222 |   });
223 | }
224 | };
225 |
226 | return (
227 |   <div className="w-full">
228 |     /* ■■■■ DESKTOP VIEW: GSAP SCROLL STORYTELLING ■■■■ */
229 |     <section
230 |       ref={containerRef}
231 |       className="hidden lg:block relative w-full h-screen overflow-hidden bg-cream"
232 |     >
233 |       <StoryBackground />
234 |
235 |       <Container className="relative z-10 h-full flex items-center justify-between py-16">
236 |         <div className="grid grid-cols-12 gap-16 items-center w-full">
237 |           /* Left Content column (40% space) */
238 |           <div className="col-span-5 flex flex-col gap-10">
239 |             <StoryContent />
240 |
241 |           </div>
242 |
243 |           /* Middle Spacer for Sidebar Rail */
244 |           <div className="col-span-2 flex justify-center">
245 |             <StoryNavigation activeStory={activeStory} scrollToStep={scrollToStep} />
246 |           </div>
247 |
248 |           /* Right Media column (60% space) */
249 |           <div className="col-span-5 aspect-[4/5] max-h-[70vh]">
250 |             <StoryImage />
251 |           </div>
252 |         </div>
253 |       </Container>
254 |     </section>
255 |
256 |     /* ■■■■ MOBILE VIEW: STACKED CARD SEQUENCE ■■■■ */
257 |     <section className="lg:hidden w-full py-16 bg-cream flex flex-col gap-10 px-4 md:px-8">
258 |       <div className="text-center max-w-xl mx-auto mb-4">
259 |         <span className="badge-gold mb-3">Our Work</span>
260 |         <h2 className="text-3xl font-extrabold text-charcoal font-heading leading-tight">
261 |           How We Support Communities
262 |         </h2>
263 |       </div>
264 |
265 |       <div className="flex flex-col gap-8">
266 |         {STORY_STEPS.map((step, idx) => (
267 |           <div
268 |             key={step.id}
269 |             id={`mobile-story-card-${idx}`}
270 |             className="card-base p-5 border border-charcoal/5 flex flex-col gap-6"
271 |           >
272 |             /* Image */
273 |             <div className="relative aspect-video w-full rounded-2xl overflow-hidden shadow-soft">
274 |               <Image
275 |                 src={step.imageSrc}
276 |                 alt={step.imageAlt}
277 |                 fill

```

```
278 | className="object-cover"
279 | sizes="(max-width: 768px) 100vw, 50vw"
280 | />
281 | </div>
282 |
283 | {/* Text Info */}
284 | <div className="flex flex-col gap-3">
285 | <span className="badge-gold w-fit">{step.badge}</span>
286 | <h3 className="text-xl font-bold text-charcoal font-heading">
287 | {step.title}
288 | </h3>
289 | <p className="text-sm text-charcoal/70 leading-relaxed font-body">
290 | {step.description}
291 | </p>
292 | <div className="pt-2">
293 | <Button
294 | label={step.buttonText}
295 | variant="text"
296 | href={step.buttonLink}
297 | icon={<ArrowRight size={14} />}
298 | iconPosition="right"
299 | />
300 | </div>
301 | </div>
302 | </div>
303 | )}}
304 | </div>
305 | </section>
306 | </div>
307 | );
308 | };
309 | export default StoryScroller;
310 |
```

56. src/components/ui/AnimatedButton.tsx

```

1 | "use client";
2 |
3 | import React, { forwardRef, useState, MouseEvent } from "react";
4 | import Link from "next/link";
5 | import { motion, AnimatePresence } from "framer-motion";
6 | import { cn } from "@utils/cn";
7 | import { styles } from "../styles";
8 | import { Loader } from "../Loader";
9 |
10 | export interface AnimatedButtonProps extends Omit<React.ButtonHTMLAttributes<HTMLButtonElement>, "onClick"> {
11 |   variant?: "primary" | "secondary" | "outline" | "ghost" | "gold" | "accent";
12 |   size?: "sm" | "md" | "lg";
13 |   loading?: boolean;
14 |   icon?: React.ReactNode;
15 |   iconPosition?: "left" | "right";
16 |   href?: string;
17 |   className?: string;
18 |   children?: React.ReactNode;
19 |   label?: string;
20 |   onClick?: (e: MouseEvent<HTMLButtonElement | HTMLAnchorElement>) => void;
21 | }
22 |
23 | interface Ripple {
24 |   id: number;
25 |   x: number;
26 |   y: number;
27 | }
28 |
29 | export const AnimatedButton = forwardRef<HTMLButtonElement | HTMLAnchorElement, AnimatedButtonProps>({
30 |   {
31 |     {
32 |       variant = "primary",
33 |       size = "md",
34 |       loading = false,
35 |       disabled = false,
36 |       icon,
37 |       iconPosition = "right",
38 |       href,
39 |       className,
40 |       children,
41 |       label,
42 |       type = "button",
43 |       onClick,
44 |       ...props
45 |     },
46 |     ref
47 |   } => {
48 |     const [ripples, setRipples] = useState<Ripple[]>([]);
49 |     const [rippleCount, setRippleCount] = useState(0);
50 |
51 |     const baseStyles =
52 |       "relative inline-flex items-center justify-center font-heading font-medium rounded-full cursor-pointer
53 |       focus:outline-hidden active:scale-[0.98] disabled:opacity-55 disabled:pointer-events-none overflow-hidden
54 |       select-none";
55 |
56 |     const variantStyles = {
57 |       primary: "bg-forest text-white hover:bg-forest-dark hover:text-white shadow-xs",
58 |       secondary: "bg-white border border-forest text-forest hover:bg-forest hover:text-white shadow-xs",
59 |       outline: "border border-forest text-forest hover:bg-forest hover:text-white bg-transparent",
60 |       ghost: "text-forest hover:bg-forest/10 bg-transparent",
61 |       accent: "bg-accent text-white hover:bg-accent-dark hover:text-white shadow-xs",
62 |       gold: "bg-accent-gradient text-white hover:brightness-105 shadow-xs font-semibold",
63 |     };
64 |
65 |     const sizeStyles = {
66 |       sm: "px-4 py-1.5 text-xs",
67 |       md: "px-6 py-2.5 text-sm",

```

```

66 | lg: "px-8 py-3.5 text-base",
67 | };
68 |
69 | const handleCreateRipple = (e: MouseEvent<HTMLButtonElement | HTMLAnchorElement>) => {
70 |   if (disabled || loading) return;
71 |
72 |   const rect = e.currentTarget.getBoundingClientRect();
73 |   const x = e.clientX - rect.left;
74 |   const y = e.clientY - rect.top;
75 |
76 |   const newRipple: Ripple = {
77 |     id: rippleCount,
78 |     x,
79 |     y,
80 |   };
81 |
82 |   setRipples((prev) => [...prev, newRipple]);
83 |   setRippleCount((prev) => prev + 1);
84 |
85 |   // Clean up ripple after animation
86 |   setTimeout(() => {
87 |     setRipples((prev) => prev.filter((r) => r.id !== newRipple.id));
88 |   }, 600);
89 |
90 |   if (onClick) {
91 |     onClick(e);
92 |   }
93 | };
94 |
95 | const isGold = variant === "gold";
96 |
97 | const content = (
98 |   <>
99 |   { /* Shine sweeping effect */}
100 |   <span className="absolute inset-0 block -translate-x-full group-hover:translate-x-full bg-linear-to-r
from-transparent via-white/20 to-transparent transition-transform duration-700 ease-out z-10 pointer-events-none" />
101 |
102 |   { /* Ripples container */}
103 |   <span className="absolute inset-0 block overflow-hidden pointer-events-none">
104 |     <AnimatePresence>
105 |       {ripples.map((ripple) => (
106 |         <motion.span
107 |           key={ripple.id}
108 |           initial={{ scale: 0, opacity: 0.35 }}
109 |           animate={{ scale: 6, opacity: 0 }}
110 |           exit={{ opacity: 0 }}
111 |           transition={{ duration: 0.5, ease: "easeOut" }}
112 |           className={cn(
113 |             "absolute block rounded-full -translate-x-1/2 -translate-y-1/2 pointer-events-none",
114 |             isGold ? "bg-charcoal/20" : "bg-white/20"
115 |           )}
116 |           style={{
117 |             left: ripple.x,
118 |             top: ripple.y,
119 |             width: "20px",
120 |             height: "20px",
121 |           }}
122 |         />
123 |       )}
124 |     </AnimatePresence>
125 |   </span>
126 |
127 |   { /* Loading Spinner */}
128 |   {loading && <Loader size="sm" className="mr-2 border-current z-20" />}
129 |
130 |   { /* Button Content */}
131 |   {!loading && icon && iconPosition === "left" && (
132 |     <motion.span
133 |       whileHover={{ x: -2 }}
134 |       transition={{ type: "spring", stiffness: 400, damping: 10 }}

```



```
135 | className="mr-2 flex items-center z-20"
136 | >
137 | {icon}
138 | </motion.span>
139 | })
140 |
141 | <span className="relative z-20">{children || label}</span>
142 |
143 | {!loading && icon && iconPosition === "right" && (
144 | <motion.span
145 | whileHover={{ x: 2 }}
146 | transition={{ type: "spring", stiffness: 400, damping: 10 }}
147 | className="ml-2 flex items-center z-20"
148 | >
149 | {icon}
150 | </motion.span>
151 | })
152 | </>
153 | );
154 |
155 | const mergedClasses = cn(
156 | baseStyles,
157 | variantStyles[variant],
158 | sizeStyles[size],
159 | styles.focusRing,
160 | "group",
161 | className
162 | );
163 |
164 | if (href && !disabled) {
165 |   return (
166 |     <Link
167 |       href={href}
168 |       className={mergedClasses}
169 |       onClick={handleCreateRipple}
170 |       ref={ref as React.Ref<HTMLAnchorElement>}
171 |       {...(props as Omit<React.ComponentPropsWithoutRef<typeof Link>, "href">)}
172 |     >
173 |       {content}
174 |     </Link>
175 |   );
176 | }
177 |
178 | return (
179 |   <button
180 |     type={type}
181 |     disabled={disabled || loading}
182 |     className={mergedClasses}
183 |     onClick={handleCreateRipple}
184 |     ref={ref as React.Ref<HTMLButtonElement>}
185 |     {...(props as React.ComponentPropsWithoutRef<"button">)}
186 |   >
187 |     {content}
188 |   </button>
189 | );
190 | }
191 | );
192 |
193 | AnimatedButton.displayName = "AnimatedButton";
194 |
```

57. src/components/ui/AnimatedCard.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { motion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { styles } from "./styles";
7 |
8 | export type CardVariant = "default" | "glass" | "premium" | "outline";
9 | export type AnimationDirection = "up" | "down" | "left" | "right" | "none";
10 |
11 | export interface AnimatedCardProps {
12 |   children: React.ReactNode;
13 |   delay?: number; // seconds
14 |   duration?: number; // seconds
15 |   className?: string;
16 |   variant?: CardVariant;
17 |   hover?: boolean;
18 |   animationDirection?: AnimationDirection;
19 |   glow?: boolean;
20 | }
21 |
22 | export const AnimatedCard: React.FC<AnimatedCardProps> = ({
23 |   children,
24 |   delay = 0,
25 |   duration = 0.6,
26 |   className,
27 |   variant = "default",
28 |   hover = true,
29 |   animationDirection = "up",
30 |   glow = false,
31 | }) => {
32 |   // Configurable scroll reveal direction coordinates
33 |   const directionOffset = 40;
34 |   const directionMap = {
35 |     up: { y: directionOffset, x: 0 },
36 |     down: { y: -directionOffset, x: 0 },
37 |     left: { x: directionOffset, y: 0 },
38 |     right: { x: -directionOffset, y: 0 },
39 |     none: { x: 0, y: 0 },
40 |   };
41 |
42 |   const initialAnimation = {
43 |     opacity: 0,
44 |     ...directionMap[animationDirection],
45 |   };
46 |
47 |   const animateInView = {
48 |     opacity: 1,
49 |     x: 0,
50 |     y: 0,
51 |     transition: {
52 |       duration,
53 |       delay,
54 |       ease: [0.16, 1, 0.3, 1], // easeOutExpo
55 |     },
56 |   };
57 |
58 |   // Hover animations using spring physics
59 |   const hoverAnimation = hover
60 |     ? {
61 |       y: -8,
62 |       scale: 1.02,
63 |       transition: { type: "spring", stiffness: 300, damping: 20 },
64 |     }
65 |     : {};
66 |
67 |   const baseCardStyles = "relative rounded-[32px] overflow-hidden select-none cursor-default";

```

```

68 |
69 | const variantStyles = {
70 |   default: "bg-cream border border-forest/10 shadow-xs text-charcoal",
71 |   glass: cn(styles.glass.bg, styles.glass.border, "text-charcoal"),
72 |   premium: "bg-charcoal text-cream border border-[#BF953F]/40 shadow-md",
73 |   outline: "bg-transparent border border-charcoal/10 hover:border-charcoal/30 text-charcoal",
74 | };
75 |
76 | // Add shadow mapping for non-hover state
77 | const shadowMap = {
78 |   default: "shadow-xs",
79 |   glass: "shadow-xs",
80 |   premium: "shadow-md",
81 |   outline: "shadow-none",
82 | };
83 |
84 | const isPremium = variant === "premium";
85 |
86 | return (
87 |   <motion.div
88 |     initial={initialAnimation}
89 |     whileInView={animateInView}
90 |     whileHover={hoverAnimation}
91 |     viewport={{ once: true, amount: 0.15 }}
92 |     className={cn(
93 |       baseCardStyles,
94 |       variantStyles[variant],
95 |       shadowMap[variant],
96 |       "group",
97 |       className
98 |     )}
99 |   >
100 |     /* Background glow effects */
101 |     {(glow || isPremium) && (
102 |       <span className="absolute -inset-[1px] bg-linear-to-r from-[#BF953F] via-[#F7DF7C] to-[#B38728]
rounded-[inherit] opacity-0 group-hover:opacity-20 blur-lg transition-opacity duration-500 pointer-events-none z-0"
/>
103 |     )}
104 |
105 |     /* Decorative top border for premium variant */
106 |     {isPremium && (
107 |       <span className="absolute top-0 left-0 right-0 h-[3px] bg-linear-to-r from-[#BF953F] via-[#F7DF7C] to-[#B38728]
z-10" />
108 |     )}
109 |
110 |     /* Children content wrapper */
111 |     <div className="relative z-10 w-full h-full">
112 |       {children}
113 |     </div>
114 |   </motion.div>
115 | );
116 | };
117 |
118 | export default AnimatedCard;
119 |

```

58. src/components/ui/AnimatedCounter.tsx

```

1 | "use client";
2 |
3 | import React, { useEffect, useRef, useState } from "react";
4 | import { useInView, animate } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface AnimatedCounterProps {
8 |   target: number;
9 |   duration?: number; // in seconds
10 |   delay?: number; // in seconds
11 |   prefix?: string;
12 |   suffix?: string;
13 |   decimals?: number;
14 |   formatting?: boolean;
15 |   className?: string;
16 | }
17 |
18 | export const AnimatedCounter: React.FC<AnimatedCounterProps> = ({
19 |   target,
20 |   duration = 2,
21 |   delay = 0,
22 |   prefix = "",
23 |   suffix = "",
24 |   decimals = 0,
25 |   formatting = true,
26 |   className,
27 | }) => {
28 |   const containerRef = useRef<HTMLSpanElement | null>(null);
29 |   const isInView = useInView(containerRef, { once: true, amount: 0.2 });
30 |   const [count, setCount] = useState(0);
31 |
32 |   useEffect(() => {
33 |     if (!isInView) return;
34 |
35 |     const controls = animate(0, target, {
36 |       duration,
37 |       delay,
38 |       ease: [0.16, 1, 0.3, 1], // easeOutExpo
39 |       onUpdate: (latest) => {
40 |         setCount(latest);
41 |       },
42 |     });
43 |
44 |     return () => controls.stop();
45 |   }, [isInView, target, duration, delay]);
46 |
47 |   const formatNumber = (num: number): string => {
48 |     const rounded = num.toFixed(decimals);
49 |
50 |     if (!formatting) return rounded;
51 |
52 |     const parts = rounded.split(".");
53 |     // Format integer part with commas
54 |     parts[0] = parts[0].replace(/\B(?=(\d{3})+(?!\d))/g, ",");
55 |     return parts.join(".");
56 |   };
57 |
58 |   return (
59 |     <span ref={containerRef} className={cn("font-heading font-bold select-none", className)}>
60 |       {prefix}
61 |       {formatNumber(count)}
62 |       {suffix}
63 |     </span>
64 |   );
65 | };
66 |
67 | export default AnimatedCounter;

```

68 |

59. src/components/ui/BackgroundPattern.tsx

```

1 | import React from "react";
2 | import { PatternVariant } from "@types";
3 | import { cn } from "@utils/cn";
4 |
5 | interface BackgroundPatternProps {
6 |   variant: PatternVariant;
7 |   opacity?: number;
8 |   className?: string;
9 | }
10 |
11 | export const BackgroundPattern: React.FC<BackgroundPatternProps> = ({
12 |   variant,
13 |   opacity = 1,
14 |   className,
15 | }) => {
16 |   switch (variant) {
17 |     case "leaf":
18 |       return (
19 |         <svg
20 |           aria-hidden="true"
21 |           className={cn("absolute inset-0 w-full h-full pointer-events-none text-forest/8", className)}
22 |           style={{ opacity }}
23 |         >
24 |           <defs>
25 |             <pattern id="pat-leaf" width="80" height="80" patternUnits="userSpaceOnUse">
26 |               <path
27 |                 d="M30 20 C40 10, 50 10, 60 20 C50 30, 40 30, 30 20 Z"
28 |                 fill="none"
29 |                 stroke="currentColor"
30 |                 strokeWidth="0.8"
31 |               />
32 |               <path d="M30 20 L50 20" fill="none" stroke="currentColor" strokeWidth="0.8" />
33 |               <path
34 |                 d="M10 50 C20 40, 30 40, 40 50 C30 60, 20 60, 10 50 Z"
35 |                 fill="none"
36 |                 stroke="currentColor"
37 |                 strokeWidth="0.8"
38 |               />
39 |               <path d="M10 50 L25 50" fill="none" stroke="currentColor" strokeWidth="0.8" />
40 |             </pattern>
41 |           </defs>
42 |           <rect width="100%" height="100%" fill="url(#pat-leaf)" />
43 |         </svg>
44 |       );
45 |
46 |     case "circuit":
47 |       return (
48 |         <svg
49 |           aria-hidden="true"
50 |           className={cn("absolute inset-0 w-full h-full pointer-events-none text-white/10", className)}
51 |           style={{ opacity }}
52 |         >
53 |           <defs>
54 |             <pattern id="pat-circuit" width="100" height="100" patternUnits="userSpaceOnUse">
55 |               <path d="M10 10h40v30h30 M20 60h30v20" fill="none" stroke="currentColor" strokeWidth="0.8" />
56 |               <circle cx="10" cy="10" r="2.5" fill="currentColor" />
57 |               <circle cx="80" cy="40" r="2.5" fill="currentColor" />
58 |               <circle cx="20" cy="60" r="2.5" fill="currentColor" />
59 |               <circle cx="50" cy="80" r="2.5" fill="currentColor" />
60 |             </pattern>
61 |           </defs>
62 |           <rect width="100%" height="100%" fill="url(#pat-circuit)" />
63 |         </svg>
64 |       );
65 |
66 |     case "wave":
67 |       return (

```

```

68 | <svg
69 |   aria-hidden="true"
70 |   className={cn("absolute inset-0 w-full h-full pointer-events-none text-charcoal/5", className)}
71 |   style={{ opacity }}
72 | >
73 | <defs>
74 |   <pattern id="pat-wave" width="80" height="40" patternUnits="userSpaceOnUse">
75 |     <path d="M0 20 Q 20 5, 40 20 T 80 20" fill="none" stroke="currentColor" strokeWidth="0.8" />
76 |     <path
77 |       d="M0 30 Q 20 15, 40 30 T 80 30"
78 |       fill="none"
79 |       stroke="currentColor"
80 |       strokeWidth="0.8"
81 |       strokeDasharray="2 2"
82 |     />
83 |   </pattern>
84 | </defs>
85 |   <rect width="100%" height="100%" fill="url(#pat-wave)" />
86 | </svg>
87 | );
88 |
89 | case "doodle":
90 |   return (
91 |     <svg
92 |       aria-hidden="true"
93 |       className={cn("absolute inset-0 w-full h-full pointer-events-none text-charcoal/10", className)}
94 |       style={{ opacity }}
95 |     >
96 |       <defs>
97 |         <pattern id="pat-doodle" width="150" height="150" patternUnits="userSpaceOnUse">
98 |           { /* Book */ }
99 |           <path d="M20 20h20v15h-20z M20 25h20" fill="none" stroke="currentColor" strokeWidth="0.8" />
100 |           { /* Bulb */ }
101 |           <circle cx="80" cy="30" r="8" fill="none" stroke="currentColor" strokeWidth="0.8" />
102 |           <path d="M77 38h6 M79 41h2" fill="none" stroke="currentColor" strokeWidth="0.8" />
103 |           { /* Pencil */ }
104 |           <path d="M120 20l15 15-5 5-15-15z M130 18l3 3" fill="none" stroke="currentColor" strokeWidth="0.8" />
105 |           { /* Cloud */ }
106 |           <path d="M25 85a8 8 0 0 1 12-4 10 10 0 0 1 18 2 8 8 0 0 1 6 8h-36z" fill="none" stroke="currentColor"
strokeWidth="0.8" />
107 |           { /* Gear */ }
108 |           <circle cx="85" cy="90" r="7" fill="none" stroke="currentColor" strokeWidth="0.8" />
109 |           <path d="M85 80v3 M85 97v3 M75 90h3 M92 90h3" fill="none" stroke="currentColor" strokeWidth="0.8" />
110 |           { /* Star */ }
111 |           <path d="M125 80l2 4 4 1-3 3 1 4-4-2-4 2 1-4-3-3 4-1z" fill="none" stroke="currentColor" strokeWidth="0.8" />
112 |         </pattern>
113 |       </defs>
114 |       <rect width="100%" height="100%" fill="url(#pat-doodle)" />
115 |     </svg>
116 |   );
117 |
118 | case "project-grid":
119 |   return (
120 |     <svg
121 |       aria-hidden="true"
122 |       className={cn("absolute inset-0 w-full h-full pointer-events-none", className)}
123 |       style={{ opacity }}
124 |     >
125 |       <defs>
126 |         <pattern id="pat-project-grid" width="120" height="120" patternUnits="userSpaceOnUse">
127 |           <rect x="0" y="0" width="60" height="60" fill="#f4f6f0" opacity="0.4" />
128 |           <path d="M0 0 L60 60 L0 60 Z" fill="#fcf9e9" opacity="0.7" />
129 |           <rect x="60" y="0" width="60" height="60" fill="#eef5f8" opacity="0.4" />
130 |           <path d="M60 0 L120 0 L120 60 Z" fill="#e3edf3" opacity="0.6" />
131 |           <rect x="0" y="60" width="60" height="60" fill="#f9f2f2" opacity="0.4" />
132 |           <path d="M0 60 L60 120 L60 60 Z" fill="#f5e8e8" opacity="0.6" />
133 |           <rect x="60" y="60" width="60" height="60" fill="#edf3ee" opacity="0.4" />
134 |           <path d="M60 120 L120 120 L120 60 Z" fill="#deeae0" opacity="0.6" />
135 |           <path d="M25 35 Q 30 25 35 25 Q 30 35 25 35 Z" fill="none" stroke="#2D5B45" strokeWidth="0.5" opacity="0.2" />
136 |           <circle cx="90" cy="30" r="4" fill="none" stroke="#2D5B45" strokeWidth="0.5" opacity="0.2" />

```

```
137 | <path d="M25 90h10v8h-10z" fill="none" stroke="#2D5B45" strokeWidth="0.5" opacity="0.2" />
138 | <path d="M85 95 Q 90 85 95 95 Z" fill="none" stroke="#2D5B45" strokeWidth="0.5" opacity="0.2" />
139 | </pattern>
140 | </defs>
141 | <rect width="100%" height="100%" fill="url(#pat-project-grid)" />
142 | </svg>
143 | );
144 |
145 | default:
146 |   return null;
147 | }
148 | };
149 |
```


60. src/components/ui/Badge.tsx

```
1 | import React from "react";
2 | import { BadgeProps } from "@types";
3 | import { cn } from "@utils/cn";
4 |
5 | export const Badge: React.FC<BadgeProps> = ({ label, variant = "default", className }) => {
6 |   const styles = {
7 |     default: "bg-charcoal/10 text-charcoal/80",
8 |     success: "bg-forest/15 text-forest",
9 |     warning: "bg-amber-500/15 text-amber-800",
10 |    info: "bg-mint text-forest border border-forest/20",
11 |    orange: "bg-warmOrange/15 text-warmOrange",
12 |  };
13 |
14 |   return (
15 |     <span
16 |       className={cn(
17 |         "inline-flex items-center px-2.5 py-1 rounded-full text-xs font-semibold tracking-wider font-heading",
18 |         styles[variant],
19 |         className
20 |       )}
21 |     >
22 |       {label}
23 |     </span>
24 |   );
25 | };
26 |
```

61. src/components/ui/BeforeAfter.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useRef, useEffect, useCallback } from "react";
4 | import { cn } from "@utils/cn";
5 | import { styles } from "../styles";
6 | import Image from "next/image";
7 |
8 | export interface BeforeAfterProps {
9 |   beforeImage: string;
10 |   afterImage: string;
11 |   beforeLabel?: string;
12 |   afterLabel?: string;
13 |   initialPosition?: number; // 0 to 100
14 |   className?: string;
15 | }
16 |
17 | export const BeforeAfter: React.FC<BeforeAfterProps> = ({
18 |   beforeImage,
19 |   afterImage,
20 |   beforeLabel = "Before",
21 |   afterLabel = "After",
22 |   initialPosition = 50,
23 |   className,
24 | }) => {
25 |   const [sliderPosition, setSliderPosition] = useState(initialPosition);
26 |   const [isDragging, setIsDragging] = useState(false);
27 |   const containerRef = useRef<HTMLDivElement | null>(null);
28 |   const [containerWidth, setContainerWidth] = useState<number | string>("100%");
29 |
30 |   // Track the actual container width reactively to prevent reading refs in render
31 |   useEffect(() => {
32 |     if (!containerRef.current) return;
33 |
34 |     const resizeObserver = new ResizeObserver((entries) => {
35 |       for (const entry of entries) {
36 |         const { width } = entry.contentRect;
37 |         requestAnimationFrame(() => {
38 |           setContainerWidth(width);
39 |         });
40 |       }
41 |     });
42 |
43 |     resizeObserver.observe(containerRef.current);
44 |     return () => resizeObserver.disconnect();
45 |   }, []);
46 |
47 |   const handleMove = useCallback((clientX: number) => {
48 |     if (!containerRef.current) return;
49 |     const rect = containerRef.current.getBoundingClientRect();
50 |     const x = clientX - rect.left;
51 |     const position = Math.max(0, Math.min(100, (x / rect.width) * 100));
52 |     setSliderPosition(position);
53 |   }, []);
54 |
55 |   const handleTouchMove = useCallback(
56 |     (e: TouchEvent) => {
57 |       if (!isDragging) return;
58 |       handleMove(e.touches[0].clientX);
59 |     },
60 |     [isDragging, handleMove]
61 |   );
62 |
63 |   const handleMouseMove = useCallback(
64 |     (e: MouseEvent) => {
65 |       if (!isDragging) return;
66 |       handleMove(e.clientX);
67 |     },

```

```

68 | [isDragging, handleMove]
69 | );
70 |
71 | const handleMouseUp = useCallback(() => {
72 |   setIsDragging(false);
73 | }, []);
74 |
75 | // Listen to global events for drag tracking to prevent stuttering outside container bounds
76 | useEffect(() => {
77 |   if (isDragging) {
78 |     window.addEventListener("mousemove", handleMouseMove);
79 |     window.addEventListener("mouseup", handleMouseUp);
80 |     window.addEventListener("touchmove", handleTouchMove);
81 |     window.addEventListener("touchend", handleMouseUp);
82 |   }
83 |
84 |   return () => {
85 |     window.removeEventListener("mousemove", handleMouseMove);
86 |     window.removeEventListener("mouseup", handleMouseUp);
87 |     window.removeEventListener("touchmove", handleTouchMove);
88 |     window.removeEventListener("touchend", handleMouseUp);
89 |   };
90 | }, [isDragging, handleMouseMove, handleMouseUp, handleTouchMove]);
91 |
92 | const handleMouseDown = () => {
93 |   setIsDragging(true);
94 | };
95 |
96 | // Keyboard navigation adjusting slider position
97 | const handleKeyDown = (e: React.KeyboardEvent) => {
98 |   if (e.key === "ArrowLeft") {
99 |     setSliderPosition((prev) => Math.max(0, prev - 5));
100 |     e.preventDefault();
101 |   } else if (e.key === "ArrowRight") {
102 |     setSliderPosition((prev) => Math.min(100, prev + 5));
103 |     e.preventDefault();
104 |   } else if (e.key === "Home") {
105 |     setSliderPosition(0);
106 |     e.preventDefault();
107 |   } else if (e.key === "End") {
108 |     setSliderPosition(100);
109 |     e.preventDefault();
110 |   }
111 | };
112 |
113 | return (
114 |   <div
115 |     ref={containerRef}
116 |     className={cn(
117 |       "relative w-full aspect-16/10 sm:aspect-16/9 bg-charcoal rounded-[32px] overflow-hidden select-none",
118 |       className
119 |     )}
120 |   >
121 |     { /* 1. After Image (Background layer) */ }
122 |     <div className="absolute inset-0 w-full h-full">
123 |       <Image
124 |         src={afterImage}
125 |         alt="After comparison"
126 |         fill
127 |         sizes="(max-width: 1200px) 100vw, 1200px"
128 |         priority
129 |         className="object-cover"
130 |       />
131 |       {afterLabel && (
132 |         <span className="absolute bottom-4 right-4 px-3.5 py-1.5 text-xs font-semibold font-body bg-charcoal/70
133 |         text-cream rounded-xl border border-cream/15 backdrop-blur-xs select-none z-10">
134 |           {afterLabel}
135 |         </span>
136 |       )}
137 |     </div>

```

```

137 |
138 | { /* 2. Before Image (Clipped overlay container) */ }
139 | <div
140 |   style={{ width: `${sliderPosition}%` }}
141 |   className="absolute inset-y-0 left-0 h-full overflow-hidden z-10"
142 | >
143 | { /* Outer dimensions must match parent exactly to prevent scaling issues */ }
144 | <div className="absolute inset-0 w-full h-full aspect-16/10 sm:aspect-16/9" style={{ width: containerWidth }}>
145 |   <Image
146 |     src={beforeImage}
147 |     alt="Before comparison"
148 |     fill
149 |     sizes="(max-width: 1200px) 100vw, 1200px"
150 |     priority
151 |     className="object-cover"
152 |   />
153 |   {beforeLabel && (
154 |     <span className="absolute bottom-4 left-4 px-3.5 py-1.5 text-xs font-semibold font-body bg-forest/80 text-cream
rounded-xl border border-cream/15 backdrop-blur-xs select-none">
155 |       {beforeLabel}
156 |     </span>
157 |   )}
158 | </div>
159 | </div>
160 |
161 | { /* 3. Drag Handle Line and Button Slider */ }
162 | <div
163 |   style={{ left: `${sliderPosition}%` }}
164 |   className="absolute inset-y-0 -ml-[1px] w-[2px] bg-cream/80 backdrop-blur-xs z-20 pointer-events-none"
165 | >
166 |   <button
167 |     role="slider"
168 |     aria-label="Image comparison position"
169 |     aria-valuenow={Math.round(sliderPosition)}
170 |     aria-valuemin={0}
171 |     aria-valuemax={100}
172 |     onKeyDown={handleKeyDown}
173 |     onMouseDown={handleMouseDown}
174 |     onTouchStart={handleMouseDown}
175 |     className={cn(
176 |       "absolute top-1/2 -translate-y-1/2 -translate-x-1/2 w-11 h-11 flex items-center justify-center rounded-full
bg-cream text-charcoal border border-forest/15 shadow-md cursor-grab active:cursor-grabbing pointer-events-auto
focus:outline-hidden",
177 |       isDragging ? "scale-105 cursor-grabbing" : "",
178 |       styles.focusRing
179 |     )}
180 |   >
181 |     { /* Arrow handles symbols */ }
182 |     <div className="flex gap-1 items-center justify-center text-forest">
183 |       <span className="text-[10px] font-bold">■</span>
184 |       <span className="text-[10px] font-bold">■</span>
185 |     </div>
186 |   </button>
187 | </div>
188 | </div>
189 | );
190 | };
191 |
192 | export default BeforeAfter;
193 |

```

62. src/components/ui/BlogCard.tsx

```

1 | import React from "react";
2 | import Image from "next/image";
3 | import Link from "next/link";
4 | import { BlogCardProps } from "@/types";
5 | import { Calendar } from "lucide-react";
6 | import { cn } from "@/utils/cn";
7 |
8 | export const BlogCard: React.FC<BlogCardProps> = ({ post, className }) => {
9 |   const isCommunity = post.category.toLowerCase() === "community";
10 |   const isEducation = post.category.toLowerCase() === "education";
11 |
12 |   const badgeColorClass = isEducation
13 |     ? "bg-[#F7DF7C] text-charcoal"
14 |     : isCommunity
15 |     ? "bg-mint text-forest"
16 |     : "bg-[#F7DF7C] text-charcoal"; // IMPACT uses yellow/accent
17 |
18 |   return (
19 |     <article className={cn("flex flex-col h-full bg-beige rounded-[32px] overflow-hidden border border-forest/10
shadow-xs hover:-translate-y-1 hover:shadow-lg transition-all duration-300 group", className)}>
20 |       { /* Card Image */ }
21 |       <div className="relative h-56 w-full overflow-hidden">
22 |         <Image
23 |           src={post.image}
24 |           alt={post.title}
25 |           fill
26 |           className="object-cover group-hover:scale-105 transition-transform duration-500"
27 |           sizes="(max-width: 768px) 100vw, (max-width: 1200px) 50vw, 33vw"
28 |         />
29 |         <div className="absolute top-4 left-4">
30 |           <span
31 |             className={cn(
32 |               "px-3.5 py-1 rounded-full text-xs font-heading font-extrabold uppercase tracking-wider shadow-xs",
33 |               badgeColorClass
34 |             )}
35 |           >
36 |             {post.category}
37 |           </span>
38 |         </div>
39 |       </div>
40 |
41 |       { /* Card Body */ }
42 |       <div className="flex flex-col flex-grow p-6 sm:p-8">
43 |         <h3 className="text-xl font-bold text-charcoal font-heading group-hover:text-forest transition-colors
duration-200 mb-3 leading-snug">
44 |           <Link href={`/blog/${post.slug}`} className="focus:outline-none focus-visible:ring-2 focus-visible:ring-forest">
45 |             {post.title}
46 |           </Link>
47 |         </h3>
48 |         <p className="text-sm text-charcoal/70 mb-6 line-clamp-3 leading-relaxed font-body">
49 |           {post.excerpt}
50 |         </p>
51 |
52 |         { /* Date Row only (no reading time or author in card) */ }
53 |         <div className="mt-auto pt-4 border-t border-charcoal/5 flex items-center gap-2 text-xs text-charcoal/55
font-medium">
54 |           <Calendar size={14} className="text-charcoal/40" />
55 |           <span>{post.date}</span>
56 |         </div>
57 |       </div>
58 |     </article>
59 |   );
60 | };
61 |

```

63. src/components/ui/BlurReveal.tsx

```
1 | "use client";
2 |
3 | import React from "react";
4 | import { motion, useReducedMotion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface BlurRevealProps {
8 |   children: React.ReactNode;
9 |   delay?: number;
10 |   duration?: number;
11 |   blur?: number;
12 |   className?: string;
13 | }
14 |
15 | export const BlurReveal: React.FC<BlurRevealProps> = ({
16 |   children,
17 |   delay = 0,
18 |   duration = 0.8,
19 |   blur = 12,
20 |   className,
21 | }) => {
22 |   const shouldReduceMotion = useReducedMotion();
23 |
24 |   const blurRevealVariants = {
25 |     hidden: {
26 |       opacity: 0,
27 |       filter: shouldReduceMotion ? "blur(0px)" : `blur(${blur}px)`,
28 |     },
29 |     visible: {
30 |       opacity: 1,
31 |       filter: "blur(0px)",
32 |       transition: {
33 |         delay,
34 |         duration,
35 |         ease: [0.16, 1, 0.3, 1], // easeOutExpo
36 |       },
37 |     },
38 |   };
39 |
40 |   return (
41 |     <motion.div
42 |       initial="hidden"
43 |       whileInView="visible"
44 |       viewport={{ once: true, amount: 0.15 }}
45 |       variants={blurRevealVariants}
46 |       className={cn(className)}
47 |     >
48 |       {children}
49 |     </motion.div>
50 |   );
51 | };
52 |
53 | export default BlurReveal;
54 |
```

64. src/components/ui/Button.tsx

```

1 | import React from "react";
2 | import Link from "next/link";
3 | import { ButtonProps } from "@types";
4 | import { cn } from "@utils/cn";
5 | import { Loader } from "../Loader";
6 |
7 | export const Button: React.FC<ButtonProps> = ({
8 |   label,
9 |   onClick,
10 |   variant = "primary",
11 |   size = "md",
12 |   disabled = false,
13 |   loading = false,
14 |   type = "button",
15 |   className,
16 |   icon,
17 |   iconPosition = "left",
18 |   href,
19 | }) => {
20 |   const baseStyles =
21 |     "inline-flex items-center justify-center font-heading font-medium rounded-full transition-all duration-200
22 |     focus:outline-none focus:ring-2 focus:ring-forest/40 active:scale-[0.98] disabled:opacity-55
23 |     disabled:pointer-events-none cursor-pointer";
24 |
25 |   const variants = {
26 |     primary: "bg-forest text-white hover:bg-forest-dark hover:text-white shadow-xs",
27 |     secondary: "bg-white border border-forest text-forest hover:bg-forest hover:text-white shadow-xs",
28 |     outline: "border border-forest text-forest hover:bg-forest hover:text-white bg-transparent",
29 |     accent: "bg-accent text-white hover:bg-accent-dark hover:text-white shadow-xs",
30 |     text: "text-forest hover:text-forest-dark bg-transparent px-0 py-0 active:scale-100",
31 |   };
32 |
33 |   const sizes = {
34 |     sm: "px-4 py-1.5 text-xs",
35 |     md: "px-6 py-2.5 text-sm",
36 |     lg: "px-8 py-3.5 text-base",
37 |   };
38 |
39 |   const content = (
40 |     <>
41 |     {loading && <Loader size="sm" className="mr-2 border-current" />}
42 |     {!loading && icon && iconPosition === "left" && <span className="mr-2 flex items-center">{icon}</span>}
43 |     <span>{label}</span>
44 |     {!loading && icon && iconPosition === "right" && <span className="ml-2 flex items-center">{icon}</span>}
45 |     </>
46 |   );
47 |
48 |   const buttonClasses = cn(
49 |     baseStyles,
50 |     variants[variant],
51 |     variant !== "text" ? sizes[size] : "",
52 |     className
53 |   );
54 |
55 |   if (href && !disabled) {
56 |     return (
57 |       <Link href={href} className={buttonClasses}>
58 |         {content}
59 |       </Link>
60 |     );
61 |   }
62 |
63 |   return (
64 |     <button
65 |       type={type}
66 |       className={buttonClasses}
67 |       onClick={onClick}

```

```
66 | disabled={disabled || loading}
67 | >
68 | {content}
69 | </button>
70 | );
71 | };
72 |
```


65. src/components/ui/Container.tsx

```
1 | import React from "react";
2 | import { ContainerProps } from "@types";
3 | import { cn } from "@utils/cn";
4 |
5 | export const Container: React.FC<ContainerProps> = ({
6 |   children,
7 |   className,
8 |   clean = false,
9 |   size = "default",
10 | }) => {
11 |   const sizeClasses = {
12 |     default: "max-w-6xl",
13 |     wide: "max-w-7xl",
14 |     xl: "max-w-[90rem]",
15 |   };
16 |
17 |   return (
18 |     <div
19 |       className={cn(
20 |         "w-full",
21 |         !clean ? cn("mx-auto px-4 sm:px-6 lg:px-8", sizeClasses[size]) : "",
22 |         className
23 |       )}
24 |     >
25 |     {children}
26 |     </div>
27 |   );
28 | };
29 |
```

66. src/components/ui/DonationWidget.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useMemo } from "react";
4 | import { motion, AnimatePresence } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { AnimatedButton } from "../AnimatedButton";
7 | import { Heart, ShieldCheck, CheckCircle2, ChevronRight, ArrowLeft } from "lucide-react";
8 |
9 | export interface DonationCause {
10 |   id: string;
11 |   name: string;
12 |   description: string;
13 |   impactFormula: (amount: number) => string;
14 |   goal?: number;
15 |   raised?: number;
16 | }
17 |
18 | export interface DonationWidgetProps {
19 |   causes?: DonationCause[];
20 |   presetAmounts?: number[];
21 |   currencySymbol?: string;
22 |   onDonate?: (data: { amount: number; causeId: string; frequency: string }) => Promise<void> | void;
23 |   className?: string;
24 | }
25 |
26 | const defaultCauses: DonationCause[] = [
27 | {
28 |   id: "edu",
29 |   name: "Childhood Education",
30 |   description: "Provide interactive science kits, learning laptops, and school classroom libraries.",
31 |   impactFormula: (amt) => {
32 |     if (amt < 500) return `Provides pencils and notebooks for ${Math.floor(amt / 50)} children.`;
33 |     if (amt < 2000) return `Sponsors interactive learning toolkits for ${Math.floor(amt / 500)} children.`;
34 |     return `Funds complete computer lab access for ${Math.floor(amt / 1000)} students for a term.`;
35 |   },
36 |   goal: 50000,
37 |   raised: 38200,
38 | },
39 | {
40 |   id: "env",
41 |   name: "Nature & Replanting",
42 |   description: "Support native tree planting, riparian restoration, and classroom gardens.",
43 |   impactFormula: (amt) => {
44 |     if (amt < 500) return `Plants ${Math.floor(amt / 100)} native saplings in urban school hubs.`;
45 |     if (amt < 2000) return `Funds organic fertilizer and compost mulch for ${Math.floor(amt / 500)} garden beds.`;
46 |     return `Builds a complete composting worm-bin classroom garden system.`;
47 |   },
48 |   goal: 30000,
49 |   raised: 12450,
50 | },
51 | {
52 |   id: "art",
53 |   name: "Arts & Emotional Care",
54 |   description: "Therapeutic painting, clay modeling, and music workshops for children.",
55 |   impactFormula: (amt) => {
56 |     if (amt < 500) return `Supplies paint brushes and sketchbooks for ${Math.floor(amt / 100)} pupils.`;
57 |     if (amt < 2000) return `Sponsors art supplies and canvasses for ${Math.floor(amt / 400)} therapists' slots.`;
58 |     return `Hosts a community-wide mural painting festival weekend.`;
59 |   },
60 |   goal: 25000,
61 |   raised: 21800,
62 | },
63 | ];
64 |
65 | const defaultPresets = [500, 1000, 2500, 5000];
66 |
67 | export const DonationWidget: React.FC<DonationWidgetProps> = ({

```

```

68 | causes = defaultCauses,
69 | presetAmounts = defaultPresets,
70 | currencySymbol = "₹",
71 | onDonate,
72 | className,
73 | }) => {
74 |   const [selectedCauseId, setSelectedCauseId] = useState(causes[0]?.id || "");
75 |   const [frequency, setFrequency] = useState<"one-time" | "monthly" | "annual">("monthly");
76 |   const [selectedTier, setSelectedTier] = useState<number | "custom">(presetAmounts[1]);
77 |   const [customAmountStr, setCustomAmountStr] = useState("");
78 |   const [step, setStep] = useState(1); // 1: Cause & Amount, 2: Checkout details, 3: Success
79 |   const [status, setStatus] = useState<"idle" | "loading" | "success" | "error">("idle");
80 |   const [errorMessage, setErrorMessage] = useState("");
81 |
82 |   // Checkout inputs
83 |   const [name, setName] = useState("");
84 |   const [email, setEmail] = useState("");
85 |   const [cardNumber, setCardNumber] = useState("");
86 |
87 |   // Calculate active donation value
88 |   const activeAmount = useMemo(() => {
89 |     if (selectedTier === "custom") {
90 |       return Math.max(0, parseInt(customAmountStr, 10) || 0);
91 |     }
92 |     return selectedTier;
93 |   }, [selectedTier, customAmountStr]);
94 |
95 |   const activeCause = useMemo(() => {
96 |     return causes.find((c) => c.id === selectedCauseId) || causes[0];
97 |   }, [causes, selectedCauseId]);
98 |
99 |   // Formatted currency preview
100 |   const formattedAmount = useMemo(() => {
101 |     return new Intl.NumberFormat("en-IN", {
102 |       style: "currency",
103 |       currency: "INR",
104 |       maximumFractionDigits: 0,
105 |     })
106 |     .format(activeAmount)
107 |     .replace("INR", currencySymbol);
108 |   }, [activeAmount, currencySymbol]);
109 |
110 |   // Handle donation submit
111 |   const handleSubmit = async (e: React.FormEvent) => {
112 |     e.preventDefault();
113 |     if (activeAmount <= 0) {
114 |       setErrorMessage("Please enter a valid donation value.");
115 |       return;
116 |     }
117 |     if (!name || !email || !cardNumber) {
118 |       setErrorMessage("Please complete all billing fields.");
119 |       return;
120 |     }
121 |
122 |     setErrorMessage("");
123 |     setStatus("loading");
124 |
125 |     try {
126 |       if (onDonate) {
127 |         await onDonate({ amount: activeAmount, causeId: selectedCauseId, frequency });
128 |       } else {
129 |         // Simulate payment gateway delay
130 |         await new Promise((resolve) => setTimeout(resolve, 2000));
131 |       }
132 |       setStatus("success");
133 |       setStep(3);
134 |     } catch (err: unknown) {
135 |       setStatus("error");
136 |       const msg = err instanceof Error ? err.message : "Payment processing failed. Please try again.";
137 |       setErrorMessage(msg);

```

```

138 | }
139 | };
140 |
141 | const handleNextStep = () => {
142 |   if (activeAmount <= 0) return;
143 |   setStep(2);
144 | };
145 |
146 | const handlePrevStep = () => {
147 |   setStep(1);
148 |   setStatus("idle");
149 | };
150 |
151 | const handleReset = () => {
152 |   setStep(1);
153 |   setStatus("idle");
154 |   setSelectedTier(presetAmounts[1]);
155 |   setCustomAmountStr("");
156 |   setName("");
157 |   setEmail("");
158 |   setCardNumber("");
159 | };
160 |
161 | // Progress Bar percentage
162 | const goalProgress = useMemo(() => {
163 |   if (!activeCause || !activeCause.goal || !activeCause.raised) return 0;
164 |   return Math.min(100, (activeCause.raised / activeCause.goal) * 100);
165 | }, [activeCause]);
166 |
167 | return (
168 |   <div
169 |     className={cn(
170 |       "w-full max-w-lg mx-auto bg-cream border border-forest/15 rounded-[36px] p-6 sm:p-8 flex flex-col gap-6
shadow-xs select-none relative overflow-hidden",
171 |       className
172 |     )}
173 |   >
174 |     { /* Decorative Gradient Top border */ }
175 |     <span className="absolute top-0 left-0 right-0 h-[4px] bg-linear-to-r from-[#BF953F] via-[#F7DF7C] to-[#B38728]
z-10" />
176 |
177 |     { /* Screen Readers polite state announcer */ }
178 |     <div className="sr-only aria-live="polite">
179 |       {status === "loading" && "Processing your contribution details..."}
180 |       {status === "success" && `Thank you! Your donation of ${formattedAmount} was successful.`}
181 |       {errorMessage && `Error: ${errorMessage}`}
182 |     </div>
183 |
184 |     <AnimatePresence mode="wait">
185 |       { /* STEP 1: Select Cause, Frequency & Amount */ }
186 |       {step === 1 && (
187 |         <motion.div
188 |           key="step1"
189 |           initial={{ opacity: 0, x: -10 }}
190 |           animate={{ opacity: 1, x: 0 }}
191 |           exit={{ opacity: 0, x: 10 }}
192 |           transition={{ duration: 0.25 }}
193 |           className="flex flex-col gap-5"
194 |         >
195 |           <div className="flex items-center gap-2">
196 |             <Heart className="w-5 h-5 text-forest fill-forest/10" />
197 |             <h2 className="text-xl font-heading font-bold text-charcoal">
198 |               Support our Programs
199 |             </h2>
200 |           </div>
201 |
202 |           { /* Cause selection */ }
203 |           <div className="flex flex-col gap-2">
204 |             <label className="text-xs font-bold text-charcoal/50 font-body uppercase">
205 |               1. Choose a Cause

```

```

206 | </label>
207 | <div className="flex flex-col gap-2">
208 | {causes.map((cause) => (
209 | <button
210 | key={cause.id}
211 | type="button"
212 | onClick={() => setSelectedCauseId(cause.id)}
213 | className={cn(
214 | "p-3 rounded-2xl border text-left flex flex-col gap-1 transition-all duration-200 cursor-pointer
focus:outline-hidden",
215 | selectedCauseId === cause.id
216 | ? "bg-forest/5 border-forest shadow-xs"
217 | : "bg-transparent border-forest/10 hover:border-forest/35"
218 | )}
219 | >
220 | <span className="font-heading font-semibold text-sm text-charcoal">
221 | {cause.name}
222 | </span>
223 | <span className="text-xs text-charcoal/60 leading-relaxed font-body">
224 | {cause.description}
225 | </span>
226 | </button>
227 | )})
228 | </div>
229 | </div>
230 |
231 | /* Frequency Selector Toggle */
232 | <div className="flex flex-col gap-2">
233 | <label className="text-xs font-bold text-charcoal/50 font-body uppercase">
234 | 2. Donation Frequency
235 | </label>
236 | <div className="grid grid-cols-3 gap-2 bg-forest/5 p-1 rounded-full border border-forest/10">
237 | {[["one-time", "monthly", "annual"] as const].map((freq) => (
238 | <button
239 | key={freq}
240 | type="button"
241 | onClick={() => setFrequency(freq)}
242 | className={cn(
243 | "py-2 rounded-full text-xs font-semibold font-heading transition-all duration-250 capitalize cursor-pointer
focus:outline-hidden",
244 | frequency === freq ? "bg-forest text-cream shadow-sm" : "text-charcoal/60 hover:text-forest"
245 | )}
246 | >
247 | {freq === "one-time" ? "One-time" : freq === "monthly" ? "Monthly" : "Annual"}
248 | </button>
249 | )})
250 | </div>
251 | </div>
252 |
253 | /* Preset Amount buttons + Custom */
254 | <div className="flex flex-col gap-3">
255 | <label className="text-xs font-bold text-charcoal/50 font-body uppercase">
256 | 3. Amount
257 | </label>
258 | <div className="grid grid-cols-4 gap-2">
259 | {presetAmounts.map((amt) => (
260 | <button
261 | key={amt}
262 | type="button"
263 | onClick={() => {
264 |   setSelectedTier(amt);
265 |   setCustomAmountStr("");
266 | }}
267 | className={cn(
268 | "py-3 rounded-xl border text-center font-bold font-heading text-sm transition-all duration-200 cursor-pointer
focus:outline-hidden",
269 | selectedTier === amt
270 | ? "bg-forest border-forest text-cream shadow-sm"
271 | : "bg-transparent border-forest/10 hover:border-forest/30 text-charcoal"
272 | )}

```

```

273 | >
274 | {currencySymbol}
275 | {amt}
276 | </button>
277 | )})
278 | </div>
279 |
280 | {/* Custom input tier trigger */}
281 | <div className="flex flex-col gap-2">
282 | <button
283 | type="button"
284 | onClick={() => setSelectedTier("custom")}
285 | className={cn(
286 | "w-full py-2.5 rounded-xl border text-center font-bold font-heading text-xs transition-all duration-200
cursor-pointer focus:outline-hidden",
287 | selectedTier === "custom"
288 | ? "bg-forest border-forest text-cream shadow-sm"
289 | : "bg-transparent border-forest/10 hover:border-forest/30 text-charcoal"
290 | )}
291 | >
292 | Custom Amount
293 | </button>
294 | {selectedTier === "custom" && (
295 | <div className="relative mt-1">
296 | <span className="absolute left-4 top-1/2 -translate-y-1/2 font-bold font-heading text-charcoal/40 text-sm">
297 | {currencySymbol}
298 | </span>
299 | <input
300 | type="number"
301 | placeholder="Enter value"
302 | value={customAmountStr}
303 | min={1}
304 | onChange={(e) => setCustomAmountStr(e.target.value)}
305 | className="w-full pl-8 pr-4 py-2.5 bg-transparent border border-forest/20 rounded-xl font-heading text-sm
text-charcoal placeholder-charcoal/30 focus:outline-hidden focus:ring-2 focus:ring-forest/30"
306 | required
307 | />
308 | </div>
309 | )}
310 | </div>
311 | </div>
312 |
313 | {/* Real-time Impact preview card */}
314 | {activeAmount > 0 && activeCause && (
315 | <motion.div
316 | initial={{ opacity: 0, y: 5 }}
317 | animate={{ opacity: 1, y: 0 }}
318 | className="p-4 rounded-2xl bg-mint/20 border border-forest/10 flex flex-col gap-1"
319 | >
320 | <span className="text-[10px] font-bold text-forest tracking-wider uppercase font-body">
321 | Your Impact
322 | </span>
323 | <p className="text-xs sm:text-sm font-semibold text-charcoal leading-relaxed font-body">
324 | {activeCause.impactFormula(activeAmount)}
325 | </p>
326 | </motion.div>
327 | )}
328 |
329 | {/* Campaign goal progress tracker */}
330 | {activeCause && activeCause.goal && activeCause.raised && (
331 | <div className="flex flex-col gap-1.5 mt-1">
332 | <div className="flex justify-between text-[10px] font-semibold text-charcoal/50 font-body uppercase">
333 | <span>Goal Meter</span>
334 | <span>
335 | {currencySymbol}
336 | {activeCause.raised.toLocaleString()} / {currencySymbol}
337 | {activeCause.goal.toLocaleString()}
338 | </span>
339 | </div>
340 | <div className="w-full h-2.5 bg-charcoal/5 rounded-full overflow-hidden">

```

```

341 | <div style={{ width: `${goalProgress}%` }} className="h-full bg-forest rounded-full" />
342 | </div>
343 | </div>
344 | })
345 |
346 | {/* Next Step trigger */}
347 | <AnimatedButton
348 |   label={`Review Donation - ${formattedAmount}`}
349 |   variant="secondary"
350 |   icon={<ChevronRight className="w-4 h-4" />}
351 |   disabled={activeAmount <= 0}
352 |   onClick={handleNextStep}
353 |   className="mt-2"
354 | />
355 | </motion.div>
356 | })
357 |
358 | {/* STEP 2: Checkout / Payment Details */}
359 | {step === 2 && (
360 |   <motion.form
361 |     key="step2"
362 |     onSubmit={handleSubmit}
363 |     initial={{ opacity: 0, x: 10 }}
364 |     animate={{ opacity: 1, x: 0 }}
365 |     exit={{ opacity: 0, x: -10 }}
366 |     transition={{ duration: 0.25 }}
367 |     className="flex flex-col gap-5"
368 |   >
369 |     <div className="flex items-center gap-2">
370 |       <button
371 |         type="button"
372 |         onClick={handlePrevStep}
373 |         aria-label="Back to cause selector"
374 |         className="p-1 rounded-full hover:bg-charcoal/5 transition-colors cursor-pointer focus:outline-hidden"
375 |       >
376 |         <ArrowLeft className="w-5 h-5 text-charcoal/60" />
377 |       </button>
378 |       <h2 className="text-xl font-heading font-bold text-charcoal">
379 |         Payment Details
380 |       </h2>
381 |     </div>
382 |
383 |     {/* Error notifications */}
384 |     {errorMessage && (
385 |       <div className="p-3 bg-red-100/50 border border-red-200 text-red-700 text-xs rounded-xl font-body">
386 |         {errorMessage}
387 |       </div>
388 |     )}
389 |
390 |     {/* Billing fields */}
391 |     <div className="flex flex-col gap-4">
392 |       <div className="flex flex-col gap-1">
393 |         <label htmlFor="name-input" className="text-xs font-bold text-charcoal/50 font-body uppercase">
394 |           Donor Full Name
395 |         </label>
396 |         <input
397 |           id="name-input"
398 |           type="text"
399 |           placeholder="Jane Doe"
400 |           value={name}
401 |           onChange={(e) => setName(e.target.value)}
402 |           className="w-full px-4 py-2.5 bg-transparent border border-forest/15 rounded-xl font-body text-sm text-charcoal
403 |           focus:outline-hidden focus:ring-2 focus:ring-forest/30"
404 |           required
405 |           disabled={status === "loading"}
406 |         />
407 |       </div>
408 |       <div className="flex flex-col gap-1">
409 |         <label htmlFor="email-input" className="text-xs font-bold text-charcoal/50 font-body uppercase">

```

```

410 | Email Address
411 | </label>
412 | <input
413 | id="email-input"
414 | type="email"
415 | placeholder="jane@example.com"
416 | value={email}
417 | onChange={(e) => setEmail(e.target.value)}
418 | className="w-full px-4 py-2.5 bg-transparent border border-forest/15 rounded-xl font-body text-sm text-charcoal
focus:outline-hidden focus:ring-2 focus:ring-forest/30"
419 | required
420 | disabled={status === "loading"}
421 | />
422 | </div>
423 |
424 | <div className="flex flex-col gap-1">
425 | <label htmlFor="card-input" className="text-xs font-bold text-charcoal/50 font-body uppercase">
426 | Card Details (Mock checkout)
427 | </label>
428 | <input
429 | id="card-input"
430 | type="text"
431 | placeholder="4111 2222 3333 4444"
432 | value={cardNumber}
433 | onChange={(e) => setCardNumber(e.target.value)}
434 | maxLength={19}
435 | className="w-full px-4 py-2.5 bg-transparent border border-forest/15 rounded-xl font-body text-sm text-charcoal
focus:outline-hidden focus:ring-2 focus:ring-forest/30"
436 | required
437 | disabled={status === "loading"}
438 | />
439 | </div>
440 | </div>
441 |
442 | { /* Total checkout amount visual */}
443 | <div className="flex justify-between items-center py-3 border-t border-b border-forest/10 font-heading my-1">
444 | <span className="font-semibold text-charcoal/60 text-sm">
445 | Checkout Sum ({frequency === "one-time" ? "One-Time" : frequency === "monthly" ? "Monthly" : "Annual"})
446 | </span>
447 | <span className="font-bold text-lg text-forest">
448 | {formattedAmount}
449 | </span>
450 | </div>
451 |
452 | { /* SSL Badge footer */}
453 | <div className="flex items-center justify-center gap-1.5 text-[10px] text-charcoal/40 font-medium font-body
select-none">
454 | <ShieldCheck className="w-4 h-4 text-forest" />
455 | <span>Secure 256-bit encrypted simulated checkout gateway</span>
456 | </div>
457 |
458 | <AnimatedButton
459 | type="submit"
460 | label={`Donate Now`}
461 | variant="secondary"
462 | loading={status === "loading"}
463 | disabled={status === "loading" || activeAmount <= 0}
464 | className="w-full"
465 | />
466 | </motion.form>
467 | )}
468 |
469 | { /* STEP 3: Complete confirmation */}
470 | {step === 3 && (
471 | <motion.div
472 | key="step3"
473 | initial={{ opacity: 0, scale: 0.95 }}
474 | animate={{ opacity: 1, scale: 1 }}
475 | className="flex flex-col items-center justify-center text-center py-8 gap-4"
476 | >

```



```
477 | <div className="p-4 rounded-full bg-forest/10 text-forest mb-2">
478 | <CheckCircle2 className="w-12 h-12" />
479 | </div>
480 |
481 | <h2 className="text-2xl font-heading font-extrabold text-charcoal">
482 | Thank You, {name.split(" ")[0]}!
483 | </h2>
484 |
485 | <p className="text-sm text-charcoal/65 font-body leading-relaxed max-w-sm">
486 | Your mock donation of <strong>{formattedAmount}</strong> to <strong>{activeCause.name}</strong> was successful.
487 | </p>
488 |
489 | /* Simulated impact receipt */
490 | <div className="p-4 rounded-2xl bg-mint/20 border border-forest/10 text-xs font-semibold leading-relaxed
text-charcoal font-body max-w-xs my-2">
491 | Impact statement: {activeCause.impactFormula(activeAmount)}
492 | </div>
493 |
494 | <AnimatedButton
495 | label="Contribute Again"
496 | variant="outline"
497 | onClick={handleReset}
498 | className="mt-2"
499 | />
500 | </motion.div>
501 | )}
502 | </AnimatePresence>
503 | </div>
504 | );
505 | };
506 |
507 | export default DonationWidget;
508 |
```

67. src/components/ui/FAQAccordion.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useMemo } from "react";
4 | import { motion, AnimatePresence } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { styles } from "./styles";
7 | import { ChevronDown, Search } from "lucide-react";
8 |
9 | export interface FAQItemData {
10 |   question: string;
11 |   answer: string;
12 |   category: string;
13 | }
14 |
15 | export interface FAQAccordionProps {
16 |   items: FAQItemData[];
17 |   allowMultiple?: boolean;
18 |   showSearch?: boolean;
19 |   className?: string;
20 | }
21 |
22 | export const FAQAccordion: React.FC<FAQAccordionProps> = ({
23 |   items,
24 |   allowMultiple = false,
25 |   showSearch = true,
26 |   className,
27 | }) => {
28 |   const [searchQuery, setSearchQuery] = useState("");
29 |   const [selectedCategory, setSelectedCategory] = useState("All");
30 |   const [openIds, setOpenIds] = useState<string[]>([]);
31 |
32 |   // Unique categories helper
33 |   const categories = useMemo(() => {
34 |     const list = Array.from(new Set(items.map((item) => item.category)));
35 |     return ["All", ...list];
36 |   }, [items]);
37 |
38 |   // Filter FAQ items by category and search keyword
39 |   const filteredItems = useMemo(() => {
40 |     return items.filter((item) => {
41 |       const matchesCategory = selectedCategory === "All" || item.category === selectedCategory;
42 |       const matchesSearch =
43 |         item.question.toLowerCase().includes(searchQuery.toLowerCase()) ||
44 |         item.answer.toLowerCase().includes(searchQuery.toLowerCase());
45 |       return matchesCategory && matchesSearch;
46 |     });
47 |   }, [items, selectedCategory, searchQuery]);
48 |
49 |   const handleToggle = (id: string) => {
50 |     if (allowMultiple) {
51 |       setOpenIds((prev) =>
52 |         prev.includes(id) ? prev.filter((openId) => openId !== id) : [...prev, id]
53 |       );
54 |     } else {
55 |       setOpenIds((prev) => (prev.includes(id) ? [] : [id]));
56 |     }
57 |   };
58 |
59 |   return (
60 |     <div className={cn("w-full max-w-3xl mx-auto flex flex-col gap-6", className)}>
61 |       {/* Search Input Filter */}
62 |       {showSearch && (
63 |         <div className="relative w-full">
64 |           <Search className="absolute left-4 top-1/2 -translate-y-1/2 w-5 h-5 text-charcoal/40" />
65 |           <input
66 |             type="text"
67 |             placeholder="Search questions..."

```

```

68 | value={searchQuery}
69 | onChange={(e) => setSearchQuery(e.target.value)}
70 | className="w-full pl-12 pr-4 py-3 bg-cream border border-forest/15 rounded-full text-sm text-charcoal
placeholder-charcoal/40 focus:outline-hidden focus:ring-2 focus:ring-forest/30"
71 | />
72 | </div>
73 | })
74 |
75 | {/* Category Tabs Filter */}
76 | {categories.length > 2 && (
77 | <div className="flex flex-wrap gap-2 items-center select-none">
78 | {categories.map((category) => {
79 |   const isSelected = selectedCategory === category;
80 |   return (
81 |     <button
82 |       key={category}
83 |       onClick={() => setSelectedCategory(category)}
84 |       className={cn(
85 |         "relative px-4 py-1.5 rounded-full text-xs font-heading font-semibold transition-all duration-200 capitalize
cursor-pointer focus:outline-hidden focus:ring-2 focus:ring-forest/35",
86 |         isSelected ? "text-cream" : "text-charcoal/70 hover:text-forest"
87 |       )}
88 |     >
89 |     {isSelected && (
90 |       <motion.span
91 |         layoutId="activeCategoryTab"
92 |         className="absolute inset-0 bg-forest rounded-full -z-10"
93 |         transition={{ type: "spring", stiffness: 380, damping: 30 }}
94 |       />
95 |     )}
96 |     {category}
97 |   </button>
98 | );
99 | }}}
100 | </div>
101 | )}
102 |
103 | {/* FAQ Accordion List */}
104 | <div className="flex flex-col gap-3" aria-live="polite">
105 | <AnimatePresence initial={false}>
106 | {filteredItems.length > 0 ? (
107 |   filteredItems.map((item, index) => {
108 |     const id = `${item.category}-${index}`;
109 |     const isOpen = openIds.includes(id);
110 |
111 |     return (
112 |       <div
113 |         key={id}
114 |         className="bg-cream border border-forest/10 rounded-2xl overflow-hidden shadow-xs transition-colors
duration-200"
115 |       >
116 |         <button
117 |           id={`faq-btn-${id}`}
118 |           aria-expanded={isOpen}
119 |           aria-controls={`faq-panel-${id}`}
120 |           onClick={() => handleToggle(id)}
121 |           className={cn(
122 |             "w-full px-6 py-4 flex items-center justify-between text-left font-heading font-semibold text-charcoal
cursor-pointer focus:outline-hidden focus-visible:bg-charcoal/5",
123 |             styles.focusRing
124 |           )}
125 |         >
126 |         <span>{item.question}</span>
127 |         <ChevronDown
128 |           className={cn(
129 |             "w-5 h-5 text-charcoal/50 transition-transform duration-300 shrink-0 ml-4",
130 |             isOpen ? "rotate-180 text-forest" : ""
131 |           )}
132 |         />
133 |       </button>

```

```
134 |  
135 | <AnimatePresence initial={false}>  
136 | {isOpen && (  
137 | <motion.div  
138 | id={`faq-panel-${id}`}  
139 | role="region"  
140 | aria-labelledby={`faq-btn-${id}`}  
141 | initial={{ height: 0, opacity: 0 }}  
142 | animate={{ height: "auto", opacity: 1 }}  
143 | exit={{ height: 0, opacity: 0 }}  
144 | transition={{ duration: 0.3, ease: [0.16, 1, 0.3, 1] }}  
145 | >  
146 | <div className="px-6 pb-5 pt-1 text-sm sm:text-base text-charcoal/70 leading-relaxed font-body border-t  
border-forest/5">  
147 | {item.answer}  
148 | </div>  
149 | </motion.div>  
150 | )}  
151 | </AnimatePresence>  
152 | </div>  
153 | );  
154 | })  
155 | ) : (  
156 | <div className="text-center py-12 text-charcoal/55 text-sm font-body">  
157 | No questions found matching your search.  
158 | </div>  
159 | )}  
160 | </AnimatePresence>  
161 | </div>  
162 | </div>  
163 | );  
164 | };  
165 |  
166 | export default FAQAccordion;  
167 |
```

68. src/components/ui/FloatingButton.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useRef, useEffect } from "react";
4 | import { motion, AnimatePresence } from "framer-motion";
5 | import Link from "next/link";
6 | import { cn } from "@utils/cn";
7 | import { styles } from "../styles";
8 | import { Plus } from "lucide-react";
9 |
10 | export interface FloatingAction {
11 |   icon: React.ReactNode;
12 |   label: string;
13 |   onClick?: () => void;
14 |   href?: string;
15 | }
16 |
17 | export interface FloatingButtonProps {
18 |   icon?: React.ReactNode;
19 |   label: string;
20 |   onClick?: () => void;
21 |   tooltip?: string;
22 |   pulse?: boolean;
23 |   actions?: FloatingAction[];
24 |   sticky?: boolean;
25 |   className?: string;
26 | }
27 |
28 | export const FloatingButton: React.FC<FloatingButtonProps> = ({
29 |   icon,
30 |   label,
31 |   onClick,
32 |   tooltip,
33 |   pulse = true,
34 |   actions = [],
35 |   sticky = true,
36 |   className,
37 | }) => {
38 |   const [isOpen, setIsOpen] = useState(false);
39 |   const [showTooltip, setShowTooltip] = useState(false);
40 |   const containerRef = useRef<HTMLDivElement | null>(null);
41 |
42 |   // Close floating actions when clicking outside
43 |   useEffect(() => {
44 |     const handleOutsideClick = (e: MouseEvent) => {
45 |       if (containerRef.current && !containerRef.current.contains(e.target as Node)) {
46 |         setIsOpen(false);
47 |       }
48 |     };
49 |
50 |     if (isOpen) {
51 |       document.addEventListener("mousedown", handleOutsideClick);
52 |     }
53 |     return () => document.removeEventListener("mousedown", handleOutsideClick);
54 |   }, [isOpen]);
55 |
56 |   const handleMainButtonClick = () => {
57 |     if (actions.length > 0) {
58 |       setIsOpen((prev) => !prev);
59 |     } else if (onClick) {
60 |       onClick();
61 |     }
62 |   };
63 |
64 |   const mainIcon = icon || (
65 |     <Plus
66 |       className={cn("w-6 h-6 transition-transform duration-300", isOpen ? "rotate-45" : "")}
67 |     />

```

```

68 | );
69 |
70 | const containerClasses = cn(
71 | sticky ? "fixed bottom-8 right-8 z-50" : "relative inline-block",
72 | className
73 | );
74 |
75 | return (
76 | <div ref={containerRef} className={containerClasses}>
77 |   /* Expandable sub-actions drawer */
78 |   <AnimatePresence>
79 |     {isOpen && actions.length > 0 && (
80 |       <ul
81 |         role="menu"
82 |         aria-label={` ${label} sub-actions`}
83 |         className="flex flex-col gap-3 mb-4 items-end"
84 |         >
85 |         {actions.map((action, index) => {
86 |           const itemContent = (
87 |             <>
88 |             <span className="px-3 py-1 text-xs font-semibold font-body bg-charcoal text-cream rounded-lg shadow-md border
border-charcoal/10 pointer-events-none select-none">
89 |               {action.label}
90 |             </span>
91 |             <span className="w-11 h-11 flex items-center justify-center rounded-full bg-cream text-charcoal border
border-forest/10 shadow-md hover:bg-forest hover:text-cream transition-colors duration-200 cursor-pointer">
92 |               {action.icon}
93 |             </span>
94 |             </>
95 |           );
96 |
97 |           return (
98 |             <motion.li
99 |               key={index}
100 |               role="menuitem"
101 |               initial={{ opacity: 0, y: 15, scale: 0.8 }}
102 |               animate={{ opacity: 1, y: 0, scale: 1 }}
103 |               exit={{ opacity: 0, y: 15, scale: 0.8 }}
104 |               transition={{ duration: 0.25, delay: (actions.length - 1 - index) * 0.05 }}
105 |               className="flex items-center gap-3 group"
106 |             >
107 |             {action.href ? (
108 |               <Link
109 |                 href={action.href}
110 |                 className={cn("flex items-center gap-3 focus:outline-hidden", styles.focusRing)}
111 |                 onClick={() => {
112 |                   setIsOpen(false);
113 |                   if (action.onClick) action.onClick();
114 |                 }}
115 |               >
116 |               {itemContent}
117 |             </Link>
118 |             ) : (
119 |               <button
120 |                 onClick={() => {
121 |                   setIsOpen(false);
122 |                   if (action.onClick) action.onClick();
123 |                 }}
124 |                 className={cn("flex items-center gap-3 focus:outline-hidden", styles.focusRing)}
125 |               >
126 |               {itemContent}
127 |             </button>
128 |             )}
129 |             </motion.li>
130 |           );
131 |         })}
132 |       </ul>
133 |     )}
134 |   </AnimatePresence>
135 |

```

```

136 |  {/* Main Trigger Button */}
137 |  <div className="relative group flex items-center justify-center">
138 |  {/* Pulsing ring background */}
139 |  {pulse && !isOpen && (
140 |  <motion.span
141 |  animate={{ scale: [1, 1.4, 1], opacity: [0.4, 0, 0.4] }}
142 |  transition={{ repeat: Infinity, duration: 2.2, ease: "easeInOut" }}
143 |  className="absolute -inset-2.5 rounded-full bg-forest/20 pointer-events-none z-0"
144 |  />
145 |  )}
146 |
147 |  {/* Action Button */}
148 |  <button
149 |  aria-haspopup={actions.length > 0 ? "true" : undefined}
150 |  aria-expanded={actions.length > 0 ? isOpen : undefined}
151 |  aria-label={label}
152 |  onClick={handleMainButtonClick}
153 |  onMouseEnter={() => setShowTooltip(true)}
154 |  onMouseLeave={() => setShowTooltip(false)}
155 |  onFocus={() => setShowTooltip(true)}
156 |  onBlur={() => setShowTooltip(false)}
157 |  className={cn(
158 |  "relative w-14 h-14 rounded-full bg-forest text-cream flex items-center justify-center shadow-lg
hover:bg-forest/90 transition-colors duration-250 cursor-pointer focus:outline-hidden z-10",
159 |  styles.focusRing
160 |  )}
161 |  >
162 |  {mainIcon}
163 |  </button>
164 |
165 |  {/* Hover/Focus Tooltip */}
166 |  <AnimatePresence>
167 |  {showTooltip && tooltip && !isOpen && (
168 |  <motion.div
169 |  role="tooltip"
170 |  initial={{ opacity: 0, x: -15, scale: 0.9 }}
171 |  animate={{ opacity: 1, x: 0, scale: 1 }}
172 |  exit={{ opacity: 0, x: -15, scale: 0.9 }}
173 |  transition={{ duration: 0.2 }}
174 |  className="absolute right-full mr-4 px-3 py-1.5 text-xs font-semibold font-body bg-charcoal text-cream
rounded-lg shadow-md border border-charcoal/10 pointer-events-none z-20 whitespace-nowrap"
175 |  >
176 |  {tooltip}
177 |  </motion.div>
178 |  )}
179 |  </AnimatePresence>
180 |  </div>
181 |  </div>
182 |  );
183 |  };
184 |
185 |  export default FloatingButton;
186 |

```

69. src/components/ui/Gallery.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useMemo, useEffect, useCallback } from "react";
4 | import { motion, AnimatePresence } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { useScrollLock } from "@hooks/useScrollLock";
7 | import { useFocusTrap } from "@hooks/useFocusTrap";
8 | import { X, ChevronLeft, ChevronRight, Maximize2 } from "lucide-react";
9 | import Image from "next/image";
10 |
11 | export interface GalleryItem {
12 |   id: string | number;
13 |   src: string;
14 |   alt: string;
15 |   category: string;
16 |   title?: string;
17 |   description?: string;
18 |   aspectClass?: string; // e.g. "aspect-square", "aspect-3/4", "aspect-4/3"
19 | }
20 |
21 | export interface GalleryProps {
22 |   items: GalleryItem[];
23 |   categories?: string[];
24 |   className?: string;
25 | }
26 |
27 | export const Gallery: React.FC<GalleryProps> = ({
28 |   items,
29 |   categories: customCategories,
30 |   className,
31 | }) => {
32 |   const [selectedCategory, setSelectedCategory] = useState("All");
33 |   const [activeLightboxIndex, setActiveLightboxIndex] = useState<number | null>(null);
34 |
35 |   // Auto-detect categories if none provided
36 |   const categories = useMemo(() => {
37 |     if (customCategories) return ["All", ...customCategories];
38 |     const detected = Array.from(new Set(items.map((item) => item.category)));
39 |     return ["All", ...detected];
40 |   }, [items, customCategories]);
41 |
42 |   // Filter items
43 |   const filteredItems = useMemo(() => {
44 |     if (selectedCategory === "All") return items;
45 |     return items.filter((item) => item.category === selectedCategory);
46 |   }, [items, selectedCategory]);
47 |
48 |   const isOpen = activeLightboxIndex !== null;
49 |
50 |   // iOS-safe scroll locking
51 |   useScrollLock(isOpen);
52 |
53 |   // Focus trap for lightbox
54 |   const lightboxRef = useFocusTrap<HTMLDivElement>(isOpen);
55 |
56 |   const handleOpenLightbox = (index: number) => {
57 |     setActiveLightboxIndex(index);
58 |   };
59 |
60 |   const handleCloseLightbox = () => {
61 |     setActiveLightboxIndex(null);
62 |   };
63 |
64 |   const handleNext = useCallback(() => {
65 |     if (activeLightboxIndex === null) return;
66 |     setActiveLightboxIndex((prev) => {
67 |       if (prev === null) return null;

```



```

68 | return (prev + 1) % filteredItems.length;
69 | });
70 | }, [activeLightboxIndex, filteredItems.length]);
71 |
72 | const handlePrev = useCallback(() => {
73 |   if (activeLightboxIndex === null) return;
74 |   setActiveLightboxIndex((prev) => {
75 |     if (prev === null) return null;
76 |     return (prev - 1 + filteredItems.length) % filteredItems.length;
77 |   });
78 | }, [activeLightboxIndex, filteredItems.length]);
79 |
80 | // Keyboard navigation inside lightbox
81 | useEffect(() => {
82 |   if (!isOpen) return;
83 |
84 |   const handleKeyDown = (e: KeyboardEvent) => {
85 |     if (e.key === "Escape") {
86 |       handleCloseLightbox();
87 |     } else if (e.key === "ArrowRight") {
88 |       handleNext();
89 |     } else if (e.key === "ArrowLeft") {
90 |       handlePrev();
91 |     }
92 |   };
93 |
94 |   window.addEventListener("keydown", handleKeyDown);
95 |   return () => window.removeEventListener("keydown", handleKeyDown);
96 | }, [isOpen, handleNext, handlePrev]);
97 |
98 | return (
99 |   <div className={cn("w-full flex flex-col gap-6", className)}>
100 |     {/* Category Tabs */}
101 |     <div className="flex flex-wrap gap-2 items-center select-none justify-center mb-4">
102 |       {categories.map((category) => {
103 |         const isSelected = selectedCategory === category;
104 |         return (
105 |           <button
106 |             key={category}
107 |             onClick={() => setSelectedCategory(category)}
108 |             className={cn(
109 |               "relative px-4 py-1.5 rounded-full text-xs font-heading font-semibold transition-all duration-200 capitalize
110 |               cursor-pointer focus:outline-hidden focus:ring-2 focus:ring-forest/35",
111 |               isSelected ? "text-cream" : "text-charcoal/70 hover:text-forest"
112 |             )}
113 |             >
114 |             {isSelected && (
115 |               <motion.span
116 |                 layoutId="activeGalleryTab"
117 |                 className="absolute inset-0 bg-forest rounded-full -z-10"
118 |                 transition={{ type: "spring", stiffness: 380, damping: 30 }}
119 |               />
120 |             )}
121 |             {category}
122 |           </button>
123 |         )}
124 |       </div>
125 |
126 |       {/* Grid gallery */}
127 |       <motion.div
128 |         layout
129 |         className="grid grid-cols-1 sm:grid-cols-2 md:grid-cols-3 gap-6"
130 |         >
131 |         <AnimatePresence mode="popLayout">
132 |           {filteredItems.map((item, index) => {
133 |             const aspect = item.aspectClass || "aspect-square";
134 |
135 |             return (
136 |               <motion.div

```

```

137 | layout
138 | initial={{ opacity: 0, scale: 0.9 }}
139 | animate={{ opacity: 1, scale: 1 }}
140 | exit={{ opacity: 0, scale: 0.9 }}
141 | transition={{ duration: 0.3 }}
142 | key={item.id}
143 | className={cn(
144 | "relative w-full rounded-[24px] overflow-hidden border border-forest/10 bg-cream cursor-pointer group shadow-xs
hover:shadow-md transition-shadow duration-300",
145 | aspect
146 | )}
147 | onClick={() => handleOpenLightbox(index)}
148 | >
149 | <Image
150 | src={item.src}
151 | alt={item.alt}
152 | fill
153 | sizes="(max-width: 640px) 100vw, (max-width: 768px) 50vw, 33vw"
154 | className="object-cover transition-transform duration-500 group-hover:scale-105"
155 | loading="lazy"
156 | />
157 | {/* Floating Zoom Icon */}
158 | <div className="absolute top-4 right-4 p-2.5 rounded-full bg-cream/80 backdrop-blur-xs text-charcoal border
border-forest/10 opacity-0 group-hover:opacity-100 transition-opacity duration-300 z-10 shadow-sm
pointer-events-none">
159 | <Maximize2 className="w-4 h-4" />
160 | </div>
161 | {/* Info Text Overlay */}
162 | <div className="absolute inset-x-0 bottom-0 bg-linear-to-t from-charcoal/80 via-charcoal/30 to-transparent p-5
flex flex-col gap-1 text-cream opacity-0 group-hover:opacity-100 transition-opacity duration-300 z-10
pointer-events-none">
163 | {item.title && (
164 | <h4 className="font-heading font-semibold text-base leading-tight">
165 | {item.title}
166 | </h4>
167 | )}
168 | {item.description && (
169 | <p className="font-body text-xs text-cream/85 truncate">
170 | {item.description}
171 | </p>
172 | )}
173 | </div>
174 | </motion.div>
175 | );
176 | )}}
177 | </AnimatePresence>
178 | </motion.div>
179 |
180 | {/* Lightbox dialog */}
181 | <AnimatePresence>
182 | {isOpen && activeLightboxIndex !== null && (
183 | <div
184 | ref={lightboxRef}
185 | role="dialog"
186 | aria-modal="true"
187 | aria-label="Image view modal"
188 | className="fixed inset-0 bg-charcoal/90 z-[999] flex items-center justify-center p-4 sm:p-10 backdrop-blur-sm"
189 | >
190 | {/* Close trigger boundary */}
191 | <div className="absolute inset-0 z-0 cursor-zoom-out" onClick={handleCloseLightbox} />
192 |
193 | {/* Left Nav */}
194 | <button
195 | onClick={handlePrev}
196 | aria-label="Previous image"
197 | className="absolute left-4 top-1/2 -translate-y-1/2 w-11 h-11 flex items-center justify-center rounded-full
bg-cream/10 border border-cream/15 text-cream hover:bg-cream/20 cursor-pointer focus:outline-hidden z-25 focus:ring-2
focus:ring-cream/40"
198 | >
199 | <ChevronLeft className="w-6 h-6" />

```

```

200 | </button>
201 |
202 | { /* Lightbox Container Content */}
203 | <motion.div
204 |   initial={{ scale: 0.95, opacity: 0 }}
205 |   animate={{ scale: 1, opacity: 1 }}
206 |   exit={{ scale: 0.95, opacity: 0 }}
207 |   transition={{ type: "spring", stiffness: 350, damping: 30 }}
208 |   className="relative max-w-5xl w-full aspect-16/10 sm:aspect-16/9 rounded-[32px] overflow-hidden border
border-cream/10 bg-charcoal z-10 flex flex-col items-center justify-center"
209 | >
210 | <div className="relative w-full h-full">
211 |   <Image
212 |     src={filteredItems[activeLightboxIndex].src}
213 |     alt={filteredItems[activeLightboxIndex].alt}
214 |     fill
215 |     sizes="100vw"
216 |     className="object-contain"
217 |   />
218 | </div>
219 |
220 | { /* Description Block */}
221 | <div className="absolute inset-x-0 bottom-0 bg-linear-to-t from-charcoal/90 via-charcoal/65 to-transparent p-6
text-cream z-20 flex flex-col gap-1 w-full text-left">
222 |   <span className="text-xs sm:text-sm font-bold text-[#F7DF7C] tracking-wide uppercase font-body">
223 |     {filteredItems[activeLightboxIndex].category}
224 |   </span>
225 |   {filteredItems[activeLightboxIndex].title && (
226 |     <h3 className="text-lg sm:text-xl font-heading font-semibold leading-tight">
227 |       {filteredItems[activeLightboxIndex].title}
228 |     </h3>
229 |   )}
230 |   {filteredItems[activeLightboxIndex].description && (
231 |     <p className="text-xs sm:text-sm font-body text-cream/75 max-w-2xl leading-relaxed">
232 |       {filteredItems[activeLightboxIndex].description}
233 |     </p>
234 |   )}
235 | </div>
236 | </motion.div>
237 |
238 | { /* Right Nav */}
239 | <button
240 |   onClick={handleNext}
241 |   aria-label="Next image"
242 |   className="absolute right-4 top-1/2 -translate-y-1/2 w-11 h-11 flex items-center justify-center rounded-full
bg-cream/10 border border-cream/15 text-cream hover:bg-cream/20 cursor-pointer focus:outline-hidden z-25 focus:ring-2
focus:ring-cream/40"
243 | >
244 |   <ChevronRight className="w-6 h-6" />
245 | </button>
246 |
247 | { /* Exit Cross trigger */}
248 | <button
249 |   onClick={handleCloseLightbox}
250 |   aria-label="Close modal dialog"
251 |   className="absolute top-4 right-4 w-11 h-11 flex items-center justify-center rounded-full bg-cream/10 border
border-cream/15 text-cream hover:bg-cream/20 cursor-pointer focus:outline-hidden z-25 focus:ring-2
focus:ring-cream/40"
252 | >
253 |   <X className="w-5 h-5" />
254 | </button>
255 | </div>
256 | )}
257 | </AnimatePresence>
258 | </div>
259 | );
260 | };
261 |
262 | export default Gallery;
263 |

```


70. src/components/ui/GlassCard.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { motion, useMotionValue, useMotionTemplate } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface GlassCardProps {
8 |   opacity?: number; // 0 to 1
9 |   blur?: number; // blur value in px
10 |   glow?: boolean; // enable mouse-follow spotlight
11 |   border?: boolean; // render border
12 |   gradientBorder?: boolean; // render premium border
13 |   children: React.ReactNode;
14 |   className?: string;
15 | }
16 |
17 | export const GlassCard: React.FC<GlassCardProps> = ({
18 |   opacity = 0.45,
19 |   blur = 12,
20 |   glow = true,
21 |   border = true,
22 |   gradientBorder = false,
23 |   children,
24 |   className,
25 | }) => {
26 |   const mouseX = useMotionValue(0);
27 |   const mouseY = useMotionValue(0);
28 |
29 |   const handleMouseMove = (e: React.MouseEvent<HTMLDivElement>) => {
30 |     const { left, top } = e.currentTarget.getBoundingClientRect();
31 |     mouseX.set(e.clientX - left);
32 |     mouseY.set(e.clientY - top);
33 |   };
34 |
35 |   const styleObj: React.CSSProperties = {
36 |     backgroundColor: `rgba(244, 246, 240, ${opacity})`, // Using cream theme color with opacity
37 |     backdropFilter: `blur(${blur}px)`,
38 |     webkitBackdropFilter: `blur(${blur}px)`,
39 |   };
40 |
41 |   return (
42 |     <div
43 |       onMouseMove={handleMouseMove}
44 |       style={styleObj}
45 |       className={cn(
46 |         "relative rounded-[32px] overflow-hidden group select-none cursor-default",
47 |         border && !gradientBorder ? "border border-cream/30" : "",
48 |         className
49 |       )}
50 |     >
51 |       {/* Premium Gradient Border */}
52 |       {border && gradientBorder && (
53 |         <span className="absolute inset-0 block rounded-[inherit] p-[1px] bg-linear-to-b from-cream/40 via-cream/10
54 |           to-[#BF953F]/20 pointer-events-none [mask-image:linear-gradient(#fff_0_0)_content-box, linear-gradient(#fff_0_0)]
55 |           [mask-composite:xor] [webkit-mask-composite:xor] z-20" />
56 |       )}
57 |       {/* Mouse hover spotlight glow */}
58 |       {glow && (
59 |         <motion.div
60 |           className="pointer-events-none absolute -inset-px rounded-[inherit] opacity-0 group-hover:opacity-100
61 |             transition-opacity duration-300 z-10"
62 |           style={{
63 |             background: useMotionTemplate`
64 |               radial-gradient(
65 |                 250px circle at ${mouseX}px ${mouseY}px,
66 |                 rgba(247, 223, 124, 0.15),

```

```
65 | transparent 80%
66 | )
67 | ` ,
68 | }}
69 | />
70 | })
71 |
72 | {/* Content wrapper */}
73 | <div className="relative z-10 w-full h-full">
74 | {children}
75 | </div>
76 | </div>
77 | );
78 | };
79 |
80 | export default GlassCard;
81 |
```

71. src/components/ui/GradientHeading.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { motion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface GradientHeadingProps {
8 |   children: React.ReactNode;
9 |   variant?: "hero" | "section" | "small";
10 |   level?: 1 | 2 | 3 | 4;
11 |   highlightWords?: string[];
12 |   underline?: boolean;
13 |   className?: string;
14 | }
15 |
16 | export const GradientHeading: React.FC<GradientHeadingProps> = ({
17 |   children,
18 |   variant = "section",
19 |   level = 2,
20 |   highlightWords = [],
21 |   underline = false,
22 |   className,
23 | }) => {
24 |   const Tag = `h${level}` as keyof React.JSX.IntrinsicElements;
25 |
26 |   const sizeClasses = {
27 |     hero: "text-4xl sm:text-5xl md:text-6xl font-extrabold tracking-tight leading-tight",
28 |     section: "text-3xl sm:text-4xl font-bold tracking-tight leading-tight",
29 |     small: "text-xl sm:text-2xl font-semibold tracking-normal",
30 |   };
31 |
32 |   // Helper to check if a word matches our highlight list
33 |   const isHighlighted = (word: string) => {
34 |     // Strip punctuation for matching
35 |     const cleanWord = word.replace(/[.,\/#!$%^&*;:{}=\-_`~()]/g, "").toLowerCase();
36 |     return highlightWords.some((w) => w.toLowerCase() === cleanWord);
37 |   };
38 |
39 |   const renderContent = () => {
40 |     if (typeof children !== "string") {
41 |       return children;
42 |     }
43 |
44 |     const words = children.split(" ");
45 |     return words.map((word, index) => {
46 |       const isLast = index === words.length - 1;
47 |       const highlight = isHighlighted(word);
48 |
49 |       return (
50 |         <React.Fragment key={index}>
51 |           {highlight ? (
52 |             <span className="bg-linear-to-r from-[#B38728] via-[#F7DF7C] to-[#BF953F] bg-clip-text text-transparent inline-block font-heading">
53 |               {word}
54 |             </span>
55 |           ) : (
56 |             <span>{word}</span>
57 |           )}
58 |           {!isLast && " "}
59 |         </React.Fragment>
60 |       );
61 |     });
62 |   };
63 |
64 |   return (
65 |     <div className={cn("relative w-fit pb-2", className)}>
66 |       <Tag className={cn("font-heading text-charcoal", sizeClasses[variant])}>

```

```
67 | {renderContent()}
68 | </Tag>
69 |
70 | {underline && (
71 | <motion.span
72 | initial={{ scaleX: 0 }}
73 | whileInView={{ scaleX: 1 }}
74 | viewport={{ once: true, amount: 0.2 }}
75 | transition={{ duration: 0.8, delay: 0.2, ease: [0.16, 1, 0.3, 1] }}
76 | className="absolute bottom-0 left-0 right-0 h-[3px] bg-linear-to-r from-[#BF953F] via-[#F7DF7C] to-[#B38728]
  origin-left rounded-full"
77 | />
78 | )}
79 | </div>
80 | );
81 | };
82 |
83 | export default GradientHeading;
84 |
```


72. src/components/ui/ImageReveal.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { motion, useScroll, useTransform, useReducedMotion } from "framer-motion";
5 | import Image from "next/image";
6 | import { cn } from "@/utils/cn";
7 |
8 | export interface ImageRevealProps {
9 |   src: string;
10 |   alt: string;
11 |   parallaxStrength?: number; // Parallax translation offset range in pixels
12 |   delay?: number;
13 |   duration?: number;
14 |   className?: string;
15 |   priority?: boolean;
16 | }
17 |
18 | export const ImageReveal: React.FC<ImageRevealProps> = ({
19 |   src,
20 |   alt,
21 |   parallaxStrength = 0,
22 |   delay = 0,
23 |   duration = 1.2,
24 |   className,
25 |   priority = false,
26 | }) => {
27 |   const containerRef = useRef<HTMLDivElement | null>(null);
28 |   const shouldReduceMotion = useReducedMotion();
29 |
30 |   // 1. Scroll-linked Parallax coordinates
31 |   const { scrollYProgress } = useScroll({
32 |     target: containerRef,
33 |     offset: ["start end", "end start"],
34 |   });
35 |
36 |   // Safe mapping of vertical movement range
37 |   const y = useTransform(scrollYProgress, [0, 1], [-parallaxStrength, parallaxStrength]);
38 |
39 |   // 2. Reveal sweep using clipPath polygon masks
40 |   const clipVariants = {
41 |     hidden: {
42 |       clipPath: "polygon(0 0, 0 0, 0 100%, 0 100%)",
43 |     },
44 |     visible: {
45 |       clipPath: "polygon(0 0, 100% 0, 100% 100%, 0 100%)",
46 |       transition: {
47 |         delay,
48 |         duration,
49 |         ease: [0.16, 1, 0.3, 1], // easeOutExpo
50 |       },
51 |     },
52 |   };
53 |
54 |   // 3. Zoom scale animation on inner image container
55 |   const zoomVariants = {
56 |     hidden: {
57 |       scale: 1.15,
58 |       opacity: 0,
59 |     },
60 |     visible: {
61 |       scale: 1,
62 |       opacity: 1,
63 |       transition: {
64 |         delay,
65 |         duration,
66 |         ease: [0.16, 1, 0.3, 1],
67 |       },

```

```
68 | },
69 | };
70 |
71 | return (
72 | <div
73 | ref={containerRef}
74 | className={cn("relative overflow-hidden w-full h-full", className)}
75 | >
76 | {shouldReduceMotion ? (
77 | // Clean simplified opacity fade for accessibility users
78 | <motion.div
79 | initial={{ opacity: 0 }}
80 | animate={{ opacity: 1 }}
81 | transition={{ delay, duration: 0.5 }}
82 | className="w-full h-full relative"
83 | >
84 | <Image
85 | src={src}
86 | alt={alt}
87 | fill
88 | priority={priority}
89 | sizes="(max-width: 1200px) 100vw, 1200px"
90 | className="object-cover"
91 | />
92 | </motion.div>
93 | ) : (
94 | <motion.div
95 | variants={clipVariants}
96 | initial="hidden"
97 | whileInView="visible"
98 | viewport={{ once: true, amount: 0.15 }}
99 | className="w-full h-full relative"
100 | >
101 | <motion.div
102 | variants={zoomVariants}
103 | style={parallaxStrength > 0 ? { y, scale: 1.15 } : {}}
104 | className="w-full h-full relative"
105 | >
106 | <Image
107 | src={src}
108 | alt={alt}
109 | fill
110 | priority={priority}
111 | sizes="(max-width: 1200px) 100vw, 1200px"
112 | className="object-cover"
113 | />
114 | </motion.div>
115 | </motion.div>
116 | )}
117 | </div>
118 | );
119 | };
120 |
121 | export default ImageReveal;
122 |
```

73. src/components/ui/ImageSlider.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useEffect, useRef, useCallback } from "react";
4 | import { motion, AnimatePresence, useReducedMotion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { styles } from "../styles";
7 | import { ChevronLeft, ChevronRight } from "lucide-react";
8 | import Image from "next/image";
9 |
10 | export interface SliderImage {
11 |   src: string;
12 |   alt: string;
13 |   title?: string;
14 |   description?: string;
15 | }
16 |
17 | export interface ImageSliderProps {
18 |   images: SliderImage[];
19 |   autoplay?: boolean;
20 |   autoplaySpeed?: number; // ms
21 |   infinite?: boolean;
22 |   showArrows?: boolean;
23 |   showPagination?: boolean;
24 |   showThumbnails?: boolean;
25 |   className?: string;
26 | }
27 |
28 | export const ImageSlider: React.FC<ImageSliderProps> = ({
29 |   images,
30 |   autoplay = true,
31 |   autoplaySpeed = 5000,
32 |   infinite = true,
33 |   showArrows = true,
34 |   showPagination = true,
35 |   showThumbnails = true,
36 |   className,
37 | }) => {
38 |   const [currentIndex, setCurrentIndex] = useState(0);
39 |   const [[page, direction], setPage] = useState([0, 0]);
40 |   const [isHovered, setIsHovered] = useState(false);
41 |   const containerRef = useRef<HTMLDivElement | null>(null);
42 |
43 |   const shouldReduceMotion = useReducedMotion();
44 |
45 |   // Handle wraps for page indexes
46 |   const imageIndex = infinite
47 |     ? (page % images.length + images.length) % images.length
48 |     : Math.max(0, Math.min(page, images.length - 1));
49 |
50 |   const paginate = useCallback(
51 |     (newDirection: number) => {
52 |       if (!infinite) {
53 |         const nextIndex = currentIndex + newDirection;
54 |         if (nextIndex >= 0 && nextIndex < images.length) {
55 |           setCurrentIndex(nextIndex);
56 |           setPage([nextIndex, newDirection]);
57 |         }
58 |       } else {
59 |         const nextIndex = (currentIndex + newDirection + images.length) % images.length;
60 |         setCurrentIndex(nextIndex);
61 |         setPage([page + newDirection, newDirection]);
62 |       }
63 |     },
64 |     [currentIndex, page, infinite, images.length]
65 |   );
66 |
67 |   const jumpTo = (index: number) => {

```

```

68 | const dir = index > currentIndex ? 1 : -1;
69 | setCurrentIndex(index);
70 | setPage([index, dir]);
71 | };
72 |
73 | // Autoplay loop
74 | useEffect(() => {
75 |   if (!autoplay || isHovered) return;
76 |
77 |   const timer = setInterval(() => {
78 |     paginate(1);
79 |   }, autoplaySpeed);
80 |
81 |   return () => clearInterval(timer);
82 | }, [autoplay, autoplaySpeed, isHovered, paginate]);
83 |
84 | // Keyboard navigation
85 | const handleKeyDown = (e: React.KeyboardEvent) => {
86 |   if (e.key === "ArrowLeft") {
87 |     paginate(-1);
88 |   } else if (e.key === "ArrowRight") {
89 |     paginate(1);
90 |   }
91 | };
92 |
93 | // Swipe/Drag gesture handler thresholds
94 | const swipeConfidenceThreshold = 10000;
95 | const swipePower = (offset: number, velocity: number) => {
96 |   return Math.abs(offset) * velocity;
97 | };
98 |
99 | // Framer Motion variants
100 | const slideVariants = {
101 |   enter: (dir: number) => ({
102 |     x: shouldReduceMotion ? 0 : dir > 0 ? "100%" : "-100%",
103 |     opacity: 0,
104 |   }),
105 |   center: {
106 |     x: 0,
107 |     opacity: 1,
108 |   },
109 |   exit: (dir: number) => ({
110 |     x: shouldReduceMotion ? 0 : dir < 0 ? "100%" : "-100%",
111 |     opacity: 0,
112 |   }),
113 | };
114 |
115 | return (
116 |   <div
117 |     ref={containerRef}
118 |     onKeyDown={handleKeyDown}
119 |     tabIndex={0}
120 |     aria-label="Image gallery carousel"
121 |     onMouseEnter={() => setIsHovered(true)}
122 |     onMouseLeave={() => setIsHovered(false)}
123 |     className={cn(
124 |       "relative w-full aspect-16/10 sm:aspect-16/9 bg-charcoal rounded-[32px] overflow-hidden focus:outline-hidden
group select-none",
125 |       styles.focusRing,
126 |       className
127 |     )}
128 |   >
129 |     {/* Slide Images Container */}
130 |     <div className="relative w-full h-full">
131 |       <AnimatePresence initial={false} custom={direction}>
132 |         <motion.div
133 |           key={page}
134 |           custom={direction}
135 |           variants={slideVariants}
136 |           initial="enter"

```

```

137 | animate="center"
138 | exit="exit"
139 | transition={{
140 | x: { type: "spring", stiffness: 300, damping: 30 },
141 | opacity: { duration: 0.25 },
142 | }}
143 | drag={shouldReduceMotion ? false : "x"}
144 | dragConstraints={{ left: 0, right: 0 }}
145 | dragElastic={1}
146 | onDragEnd={(e, { offset, velocity }) => {
147 |   const swipe = swipePower(offset.x, velocity.x);
148 |
149 |   if (swipe < -swipeConfidenceThreshold) {
150 |     paginate(1);
151 |   } else if (swipe > swipeConfidenceThreshold) {
152 |     paginate(-1);
153 |   }
154 | }}
155 | className="absolute inset-0 w-full h-full cursor-grab active:cursor-grabbing"
156 | >
157 | <Image
158 |   src={images[imageIndex].src}
159 |   alt={images[imageIndex].alt}
160 |   fill
161 |   sizes="(max-width: 1200px) 100vw, 1200px"
162 |   priority
163 |   className="object-cover pointer-events-none"
164 | />
165 | {/* Soft gradient mask for text titles */}
166 | {(images[imageIndex].title || images[imageIndex].description) && (
167 |   <div className="absolute inset-x-0 bottom-0 bg-linear-to-t from-charcoal/80 via-charcoal/30 to-transparent p-6
sm:p-10 flex flex-col gap-2 text-cream z-10">
168 |     {images[imageIndex].title && (
169 |       <h3 className="text-xl sm:text-2xl font-heading font-bold leading-tight">
170 |         {images[imageIndex].title}
171 |       </h3>
172 |     )}
173 |     {images[imageIndex].description && (
174 |       <p className="text-xs sm:text-sm font-body text-cream/80 max-w-xl leading-relaxed">
175 |         {images[imageIndex].description}
176 |       </p>
177 |     )}
178 |   </div>
179 | )}
180 | </motion.div>
181 | </AnimatePresence>
182 | </div>
183 |
184 | {/* Chevrons Navigation Arrows */}
185 | {showArrows && (
186 |   <>
187 |     <button
188 |       onClick={() => paginate(-1)}
189 |       aria-label="Previous slide"
190 |       disabled={!infinite && currentIndex === 0}
191 |       className="absolute left-4 top-1/2 -translate-y-1/2 w-10 h-10 flex items-center justify-center rounded-full
bg-cream/20 hover:bg-cream/40 border border-cream/20 text-cream backdrop-blur-xs transition-all duration-200
opacity-0 group-hover:opacity-100 focus-visible:opacity-100 z-20 cursor-pointer disabled:pointer-events-none
disabled:opacity-0 focus:outline-hidden"
192 |     >
193 |       <ChevronLeft className="w-6 h-6" />
194 |     </button>
195 |     <button
196 |       onClick={() => paginate(1)}
197 |       aria-label="Next slide"
198 |       disabled={!infinite && currentIndex === images.length - 1}
199 |       className="absolute right-4 top-1/2 -translate-y-1/2 w-10 h-10 flex items-center justify-center rounded-full
bg-cream/20 hover:bg-cream/40 border border-cream/20 text-cream backdrop-blur-xs transition-all duration-200
opacity-0 group-hover:opacity-100 focus-visible:opacity-100 z-20 cursor-pointer disabled:pointer-events-none
disabled:opacity-0 focus:outline-hidden"

```

```

200 | >
201 | <ChevronRight className="w-6 h-6" />
202 | </button>
203 | </>
204 | })
205 |
206 | {/* Pagination dots */}
207 | {showPagination && (
208 |   <div className="absolute bottom-4 left-1/2 -translate-x-1/2 flex items-center gap-2 z-20">
209 |     {images.map((_, idx) => (
210 |       <button
211 |         key={idx}
212 |         onClick={() => jumpTo(idx)}
213 |         aria-label={`Go to slide ${idx + 1}`}
214 |         aria-current={currentIndex === idx ? "true" : undefined}
215 |         className={cn(
216 |           "w-2 h-2 rounded-full cursor-pointer transition-all duration-250 focus:outline-hidden",
217 |           currentIndex === idx ? "w-6 bg-cream shadow-xs" : "bg-cream/50 hover:bg-cream/85"
218 |         )}
219 |       />
220 |     )]}
221 |   </div>
222 | )}
223 |
224 | {/* Thumbnail Nav strip (optional overlay at bottom or external, kept overlay here if shown) */}
225 | {showThumbnails && (
226 |   <div className="absolute right-4 bottom-4 hidden sm:flex items-center gap-1.5 p-1.5 rounded-2xl bg-charcoal/45
227 |     backdrop-blur-xs border border-cream/15 z-20 max-w-xs overflow-hidden">
228 |     {images.map((img, idx) => (
229 |       <button
230 |         key={idx}
231 |         onClick={() => jumpTo(idx)}
232 |         className={cn(
233 |           "relative w-10 h-7 rounded-lg overflow-hidden border transition-all duration-200 shrink-0 cursor-pointer
234 |           focus:outline-hidden",
235 |           currentIndex === idx ? "border-[#F7DF7C]" : "border-transparent opacity-60 hover:opacity-100"
236 |         )}
237 |       <Image src={img.src} alt={`Thumbnail ${idx}`} fill className="object-cover" />
238 |     )]}
239 |   </div>
240 | )}
241 | </div>
242 | );
243 | };
244 |
245 | export default ImageSlider;
246 |

```

74. src/components/ui/ImpactCounter.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { motion, useInView } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { AnimatedCounter } from "../AnimatedCounter";
7 |
8 | export interface ImpactStat {
9 |   value: number;
10 |   label: string;
11 |   prefix?: string;
12 |   suffix?: string;
13 |   icon?: React.ReactNode;
14 |   type?: "counter" | "circle" | "progress";
15 |   progressValue?: number; // 0 to 100
16 |   color?: "forest" | "gold" | "charcoal";
17 | }
18 |
19 | export interface ImpactCounterProps {
20 |   stats: ImpactStat[];
21 |   className?: string;
22 | }
23 |
24 | export const ImpactCounter: React.FC<ImpactCounterProps> = ({ stats, className }) => {
25 |   const containerRef = useRef<HTMLDivElement | null>(null);
26 |   const isInView = useInView(containerRef, { once: true, amount: 0.1 });
27 |
28 |   const colorMap = {
29 |     forest: {
30 |       text: "text-forest",
31 |       bg: "bg-forest",
32 |       stroke: "stroke-forest",
33 |       bgLight: "bg-forest/10",
34 |     },
35 |     gold: {
36 |       text: "text-[#B38728]",
37 |       bg: "bg-[#B38728]",
38 |       stroke: "stroke-[#B38728]",
39 |       bgLight: "bg-[#BF953F]/10",
40 |     },
41 |     charcoal: {
42 |       text: "text-charcoal",
43 |       bg: "bg-charcoal",
44 |       stroke: "stroke-charcoal",
45 |       bgLight: "bg-charcoal/10",
46 |     },
47 |   };
48 |
49 |   return (
50 |     <div
51 |       ref={containerRef}
52 |       className={cn("grid grid-cols-1 md:grid-cols-3 gap-8 w-full", className)}
53 |     >
54 |       {stats.map((stat, index) => {
55 |         const theme = colorMap[stat.color || "forest"];
56 |         const type = stat.type || "counter";
57 |         const targetPercent = stat.progressValue || stat.value || 0;
58 |
59 |         return (
60 |           <motion.div
61 |             key={index}
62 |             initial={{ opacity: 0, y: 30 }}
63 |             animate={isInView ? { opacity: 1, y: 0 } : { opacity: 0, y: 30 }}
64 |             transition={{ duration: 0.6, delay: index * 0.15, ease: [0.16, 1, 0.3, 1] }}
65 |             className="flex flex-col items-center text-center p-6 bg-cream border border-forest/10 rounded-[32px] shadow-xs"
66 |           >
67 |             {/* Stat Icon */}

```

```

68 | {stat.icon && (
69 | <div className={cn("p-4 rounded-2xl mb-4 text-forest", theme.bgLight)}>
70 | {stat.icon}
71 | </div>
72 | )}
73 |
74 | {/* Render Counter Stat */}
75 | {type === "counter" && (
76 | <div className="flex flex-col items-center">
77 | <AnimatedCounter
78 |   target={stat.value}
79 |   prefix={stat.prefix}
80 |   suffix={stat.suffix}
81 |   className={cn("text-4xl sm:text-5xl font-extrabold font-heading tracking-tight", theme.text)}
82 | />
83 | <span className="text-sm font-medium text-charcoal/60 mt-2 font-body">
84 | {stat.label}
85 | </span>
86 | </div>
87 | )}
88 |
89 | {/* Render Radial Circle Stat */}
90 | {type === "circle" && (
91 | <div className="flex flex-col items-center">
92 | <div className="relative w-28 h-28 flex items-center justify-center mb-4 select-none">
93 | <svg className="w-full h-full transform -rotate-90" viewBox="0 0 100 100">
94 | {/* Background track circle */}
95 | <circle
96 |   cx="50"
97 |   cy="50"
98 |   r="40"
99 |   className="stroke-charcoal/5 fill-transparent"
100 |   strokeWidth="8"
101 | />
102 | {/* Animated foreground circle */}
103 | <motion.circle
104 |   cx="50"
105 |   cy="50"
106 |   r="40"
107 |   className={cn("fill-transparent", theme.stroke)}
108 |   strokeWidth="8"
109 |   strokeDasharray="251.2" // 2 * PI * r (r=40 -> 251.2)
110 |   initial={{ strokeDashoffset: 251.2 }}
111 |   animate={isInView ? { strokeDashoffset: 251.2 - (251.2 * targetPercent) / 100 } : { strokeDashoffset: 251.2 }}
112 |   transition={{ duration: 1.5, ease: "easeOut", delay: index * 0.1 }}
113 |   strokeLinecap="round"
114 | />
115 | </svg>
116 | {/* Inside Circle Counter */}
117 | <span className={cn("absolute text-xl font-bold font-heading", theme.text)}>
118 | <AnimatedCounter target={targetPercent} suffix="%" />
119 | </span>
120 | </div>
121 | <span className="text-sm font-medium text-charcoal/60 font-body">
122 | {stat.label}
123 | </span>
124 | </div>
125 | )}
126 |
127 | {/* Render Progress Bar Stat */}
128 | {type === "progress" && (
129 | <div className="w-full flex flex-col items-center">
130 | <div className="flex justify-between items-center w-full mb-2">
131 | <span className="text-xs font-semibold text-charcoal/50 font-body uppercase">
132 | {stat.label}
133 | </span>
134 | <span className={cn("text-sm font-bold font-heading", theme.text)}>
135 | <AnimatedCounter target={targetPercent} suffix="%" />
136 | </span>
137 | </div>

```



```
138 | <div className="w-full h-3 bg-charcoal/5 rounded-full overflow-hidden">
139 | <motion.div
140 |   initial={{ width: 0 }}
141 |   animate={isInView ? { width: `${targetPercent}%` } : { width: 0 }}
142 |   transition={{ duration: 1.5, ease: "easeOut", delay: index * 0.15 }}
143 |   className={cn("h-full rounded-full", theme.bg)}
144 | />
145 | </div>
146 | </div>
147 | )}
148 | </motion.div>
149 | );
150 | }}}
151 | </div>
152 | );
153 | };
154 |
155 | export default ImpactCounter;
156 |
```

75. src/components/ui/Input.tsx

```

1 | import React, { forwardRef } from "react";
2 | import { InputProps, TextAreaProps } from "@types";
3 | import { cn } from "@utils/cn";
4 |
5 | export const Input = forwardRef<HTMLInputElement, InputProps>(
6 |   ({ label, error, helperText, className, id, ...props }, ref) => {
7 |     return (
8 |       <div className="w-full flex flex-col gap-1.5">
9 |         {label && (
10 |           <label htmlFor={id} className="text-sm font-medium text-charcoal/85 font-heading">
11 |             {label}
12 |           </label>
13 |         )}
14 |         <input
15 |           ref={ref}
16 |           id={id}
17 |           className={cn(
18 |             "w-full px-4 py-3 rounded-full border border-charcoal/25 bg-cream/50 text-charcoal text-sm transition-all
19 |             placeholder:text-charcoal/40 focus:outline-none focus:border-forest focus:ring-1 focus:ring-forest/30
20 |             disabled:opacity-50",
21 |             error && "border-red-500 focus:border-red-500 focus:ring-red-500/30",
22 |             className
23 |           )}
24 |           {...props}
25 |         />
26 |         {error && <span className="text-xs text-red-600 font-medium px-2">{error}</span>}
27 |         {!error && helperText && <span className="text-xs text-charcoal/50 px-2">{helperText}</span>}
28 |       </div>
29 |     );
30 |     Input.displayName = "Input";
31 |
32 | export const TextArea = forwardRef<HTMLTextAreaElement, TextAreaProps>(
33 |   ({ label, error, helperText, className, id, ...props }, ref) => {
34 |     return (
35 |       <div className="w-full flex flex-col gap-1.5">
36 |         {label && (
37 |           <label htmlFor={id} className="text-sm font-medium text-charcoal/85 font-heading">
38 |             {label}
39 |           </label>
40 |         )}
41 |         <textarea
42 |           ref={ref}
43 |           id={id}
44 |           className={cn(
45 |             "w-full px-4 py-3 rounded-2xl border border-charcoal/25 bg-cream/50 text-charcoal text-sm transition-all
46 |             placeholder:text-charcoal/40 focus:outline-none focus:border-forest focus:ring-1 focus:ring-forest/30
47 |             disabled:opacity-50 min-h-[120px] resize-y",
48 |             error && "border-red-500 focus:border-red-500 focus:ring-red-500/30",
49 |             className
50 |           )}
51 |           {...props}
52 |         />
53 |         {error && <span className="text-xs text-red-600 font-medium px-2">{error}</span>}
54 |         {!error && helperText && <span className="text-xs text-charcoal/50 px-2">{helperText}</span>}
55 |       </div>
56 |     );
57 |     TextArea.displayName = "TextArea";
58 |

```

76. src/components/ui/Loader.tsx

```
1 | import React from "react";
2 | import { LoaderProps } from "@types";
3 | import { cn } from "@utils/cn";
4 |
5 | export const Loader: React.FC<LoaderProps> = ({ size = "md", className }) => {
6 |   return (
7 |     <div className={cn("flex items-center justify-center", className)} data-testid="loader">
8 |       <div
9 |         className={cn(
10 |           "animate-spin rounded-full border-t-2 border-b-2 border-forest",
11 |           size === "sm" && "h-6 w-6 border-t-2 border-b-2",
12 |           size === "md" && "h-10 w-10 border-t-2 border-b-2",
13 |           size === "lg" && "h-16 w-16 border-t-4 border-b-4"
14 |         )}
15 |       />
16 |     </div>
17 |   );
18 | };
19 |
```

77. src/components/ui/Magnetic.tsx

```

1 | "use client";
2 |
3 | import React, { useRef, useState, useEffect } from "react";
4 | import { motion, useMotionValue, useSpring, useReducedMotion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface MagneticProps {
8 |   children: React.ReactNode;
9 |   strength?: number; // Distance multiplier for magnetic attraction (e.g. 0.3)
10 |   className?: string;
11 | }
12 |
13 | export const Magnetic: React.FC<MagneticProps> = ({ children, strength = 0.35, className }) => {
14 |   const ref = useRef<HTMLDivElement | null>(null);
15 |   const shouldReduceMotion = useReducedMotion();
16 |   const [isTouchDevice, setIsTouchDevice] = useState(false);
17 |
18 |   // Monitor device layout interaction capabilities
19 |   useEffect(() => {
20 |     const checkTouch = () => {
21 |       setIsTouchDevice(
22 |         "ontouchstart" in window || navigator.maxTouchPoints > 0
23 |       );
24 |     };
25 |     checkTouch();
26 |   }, []);
27 |
28 |   const x = useMotionValue(0);
29 |   const y = useMotionValue(0);
30 |
31 |   const springConfig = { damping: 15, stiffness: 150, mass: 0.1 };
32 |   const springX = useSpring(x, springConfig);
33 |   const springY = useSpring(y, springConfig);
34 |
35 |   const handleMouseMove = (e: React.MouseEvent) => {
36 |     if (shouldReduceMotion || isTouchDevice || !ref.current) return;
37 |
38 |     const { clientX, clientY } = e;
39 |     const { left, top, width, height } = ref.current?.getBoundingClientRect();
40 |     const centerX = left + width / 2;
41 |     const centerY = top + height / 2;
42 |
43 |     // Relative displacement offsets from the component's midpoint
44 |     const offsetX = clientX - centerX;
45 |     const offsetY = clientY - centerY;
46 |
47 |     x.set(offsetX * strength);
48 |     y.set(offsetY * strength);
49 |   };
50 |
51 |   const handleMouseLeave = () => {
52 |     x.set(0);
53 |     y.set(0);
54 |   };
55 |
56 |   // Immediate pass-through layout for touch screens or reduced motion requests
57 |   if (shouldReduceMotion || isTouchDevice) {
58 |     return <div className={className}>{children}</div>;
59 |   }
60 |
61 |   return (
62 |     <div
63 |       ref={ref}
64 |       onMouseMove={handleMouseMove}
65 |       onMouseLeave={handleMouseLeave}
66 |       className={cn("relative inline-block", className)}
67 |     >

```

```
68 | <motion.div
69 |   style={{ x: springX, y: springY }}
70 |   className="w-full h-full"
71 | >
72 | {children}
73 | </motion.div>
74 | </div>
75 | );
76 | };
77 |
78 | export default Magnetic;
79 |
```

78. src/components/ui/Parallax.tsx

```
1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { motion, useScroll, useTransform } from "framer-motion";
5 | import { cn } from "@/utils/cn";
6 |
7 | interface ParallaxProps {
8 |   children: React.ReactNode;
9 |   /** How many pixels to shift vertically across the viewport scroll range */
10 |   strength?: number;
11 |   className?: string;
12 | }
13 |
14 | export const Parallax: React.FC<ParallaxProps> = ({
15 |   children,
16 |   strength = 40,
17 |   className,
18 | }) => {
19 |   const ref = useRef<HTMLDivElement>(null);
20 |
21 |   const { scrollYProgress } = useScroll({
22 |     target: ref,
23 |     offset: ["start end", "end start"],
24 |   });
25 |
26 |   const y = useTransform(scrollYProgress, [0, 1], [-strength, strength]);
27 |
28 |   return (
29 |     <div ref={ref} className={cn("overflow-hidden", className)}>
30 |       <motion.div style={{ y }}>{children}</motion.div>
31 |     </div>
32 |   );
33 | };
34 |
```

79. src/components/ui/ProjectCard.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import Link from "next/link";
5 | import { ProjectCardProps } from "@types";
6 | import { BackgroundPattern } from "../BackgroundPattern";
7 | import { Settings, Leaf, Palette, Terminal, Heart, Home } from "lucide-react";
8 | import { cn } from "@utils/cn";
9 |
10 | export const ProjectCard: React.FC<ProjectCardProps> = ({ project, className }) => {
11 |   const isFlagship = project.featured === true || project.slug === "the-wisdom-collective";
12 |
13 |   if (isFlagship) {
14 |     // Flagship Card: Full dark background with wave ribbons, spanning multiple columns on desktop
15 |     return (
16 |       <div
17 |         className={cn(
18 |           "relative lg:col-span-2 bg-navy text-white rounded-3xl p-8 flex flex-col justify-between overflow-hidden
19 |           shadow-sm border border-white/5 card-interactive min-h-[380px]",
20 |         )}
21 |       >
22 |         { /* Ribbon Wave SVG */ }
23 |         <svg
24 |           className="absolute inset-0 w-full h-full opacity-20 pointer-events-none"
25 |           viewBox="0 0 600 300"
26 |           fill="none"
27 |           xmlns="http://www.w3.org/2000/svg"
28 |         >
29 |           <path d="M 0 150 Q 150 50, 300 150 T 600 150" stroke="#F7DF7C" strokeWidth="8" strokeLinecap="round" />
30 |           <path d="M 0 170 Q 150 70, 300 170 T 600 170" stroke="#2D5B45" strokeWidth="8" strokeLinecap="round" />
31 |           <path d="M 0 190 Q 150 90, 300 190 T 600 190" stroke="#e3edf3" strokeWidth="8" strokeLinecap="round" />
32 |         </svg>
33 |
34 |         { /* Flagship Content */ }
35 |         <div className="relative z-10">
36 |           <span className="inline-block px-3 py-1 rounded-full bg-[#F7DF7C] text-charcoal font-heading font-extrabold
37 |             text-[10px] uppercase tracking-wider mb-8">
38 |             Flagship Program
39 |           </span>
40 |           <span className="block text-[11px] font-bold text-white/40 uppercase tracking-widest mb-1">
41 |             Our Projects
42 |           </span>
43 |           <h3 className="text-2xl sm:text-3xl font-extrabold font-heading text-white mb-4">
44 |             <Link
45 |               href={`\`our-projects/${project.slug}``}
46 |               className="hover:text-[#F7DF7C] transition-colors focus:outline-none focus-visible:ring-2
47 |               focus-visible:ring-[#F7DF7C]"
48 |             >
49 |               {project.title}
50 |             </Link>
51 |           </h3>
52 |           <p className="text-sm sm:text-base text-white/70 max-w-2xl leading-relaxed font-body mb-8">
53 |             {project.description}
54 |           </p>
55 |         </div>
56 |
57 |         { /* Flagship Metrics Row */ }
58 |         <div className="relative z-10 pt-6 border-t border-white/10 flex flex-wrap gap-6 text-xs text-white/75
59 |           font-semibold font-heading">
60 |           <div className="flex items-center gap-2">
61 |             <Home size={14} className="text-[#F7DF7C]" />
62 |             <span>50 Active Hubs</span>
63 |           </div>
64 |           <div className="flex items-center gap-2">
65 |             <Heart size={14} className="text-red-400" />
66 |             <span>10,000+ Mentorship Hours</span>
67 |           </div>
68 |         </div>
69 |       </div>
70 |     );
71 |   }
72 |
73 |   // Standard Card
74 |   return (
75 |     <div
76 |       className={cn(
77 |         "relative lg:col-span-2 bg-navy text-white rounded-3xl p-8 flex flex-col justify-between overflow-hidden
78 |         shadow-sm border border-white/5 card-interactive min-h-[380px]",
79 |       )}
80 |     >
81 |       { /* Standard Card Content */ }
82 |     </div>
83 |   );
84 | }

```

```

64 | </div>
65 | </div>
66 | </div>
67 | );
68 | }
69 |
70 | // Small Project Card: Top colored illustration half + bottom white content half
71 | const renderIllustration = () => {
72 |   switch (project.slug) {
73 |     case "curiosity-labs":
74 |       return (
75 |         <div className="relative h-48 w-full bg-[#fdf3c7] flex items-center justify-center overflow-hidden">
76 |           <BackgroundPattern variant="circuit" className="text-yellow-600/15" />
77 |           <Settings className="w-16 h-16 text-yellow-600/30 animate-spin-slow" />
78 |         </div>
79 |       );
80 |     case "green-roots":
81 |       return (
82 |         <div className="relative h-48 w-full bg-[#dcfce7] flex items-center justify-center overflow-hidden">
83 |           <BackgroundPattern variant="leaf" className="text-green-600/15" />
84 |           <Leaf className="w-16 h-16 text-green-600/30" />
85 |         </div>
86 |       );
87 |     case "code-bloom":
88 |       return (
89 |         <div className="relative h-48 w-full bg-[#dbeafe] flex items-center justify-center overflow-hidden">
90 |           <BackgroundPattern variant="circuit" className="text-blue-600/15" />
91 |           <Terminal className="w-16 h-16 text-blue-600/30" />
92 |         </div>
93 |       );
94 |     case "canvas-of-hope":
95 |       return (
96 |         <div className="relative h-48 w-full bg-[#fee2e2] flex items-center justify-center overflow-hidden">
97 |           <BackgroundPattern variant="wave" className="text-red-600/15" />
98 |           <Palette className="w-16 h-16 text-red-600/30" />
99 |         </div>
100 |       );
101 |     default:
102 |       return (
103 |         <div className="relative h-48 w-full bg-[#f4f6f0] flex items-center justify-center overflow-hidden">
104 |           <BackgroundPattern variant="leaf" className="text-forest/10" />
105 |           <Leaf className="w-16 h-16 text-forest/30" />
106 |         </div>
107 |       );
108 |   }
109 | };
110 |
111 | return (
112 |   <div
113 |     className={cn(
114 |       "flex flex-col h-full bg-card-bg rounded-3xl overflow-hidden border border-card-border shadow-xs
card-interactive",
115 |       className
116 |     )}
117 |   >
118 |     {/* Top half illustration */}
119 |     <div className="relative overflow-hidden shrink-0">
120 |       {renderIllustration()}
121 |       <div className="absolute top-4 left-4">
122 |         <span className="px-3 py-1 rounded-full border border-white bg-white/20 backdrop-blur-xs text-charcoal
font-heading font-extrabold text-[10px] uppercase tracking-wider">
123 |           {project.badge}
124 |         </span>
125 |       </div>
126 |     </div>
127 |
128 |     {/* Bottom half text info */}
129 |     <div className="flex flex-col flex-grow p-6 sm:p-8">
130 |       <h3 className="text-xl font-bold text-charcoal font-heading group-hover:text-forest transition-colors
duration-200 mb-3 leading-snug">

```



```

131 | <Link
132 | href={` /our-projects/${project.slug}`}
133 | className="focus:outline-none focus-visible:ring-2 focus-visible:ring-forest"
134 | >
135 | {project.title}
136 | </Link>
137 | </h3>
138 | <p className="text-sm text-charcoal/70 mb-6 line-clamp-3 leading-relaxed font-body">
139 | {project.description}
140 | </p>
141 | <div className="mt-auto pt-4 border-t border-charcoal/5 flex items-center gap-2 text-xs text-charcoal/65
font-bold font-heading">
142 | {project.slug === "curiosity-labs" && (
143 | <svg className="w-4 h-4 text-charcoal/40 fill-current" viewBox="0 0 24 24">
144 | <path d="M16 11c1.66 0 2.99-1.34 2.99-3s17.66 5 16 5c-1.66 0-3 1.34-3 3s1.34 3 3 3zm-8 0c1.66 0 2.99-1.34
2.99-3s9.66 5 8 5c6.34 5 5 1.34 5 8s1.34 3 3 3zm0 2c-2.33 0-7 1.17-7 3.5V19h14v-2.5c0-2.33-4.67-3.5-7-3.5zm8 0c-.29
0-.62.02-.97.05 1.16.84 1.97 2 1.97 3.45V19h6v-2.5c0-2.33-4.67-3.5-7-3.5z" />
145 | </svg>
146 | )}
147 | {project.slug === "green-roots" && (
148 | <svg className="w-4 h-4 text-charcoal/40 fill-none stroke-current" strokeWidth="2.5" viewBox="0 0 24 24">
149 | <path d="M12 2v20 M17 5H9.5a3.5 3.5 0 000 7h5a3.5 3.5 0 010 7H6" strokeLinecap="round" />
150 | </svg>
151 | )}
152 | {project.slug === "code-bloom" && (
153 | <svg className="w-4 h-4 text-charcoal/40 fill-none stroke-current" strokeWidth="2" viewBox="0 0 24 24">
154 | <rect x="2" y="3" width="20" height="14" rx="2" />
155 | <path d="M8 21h8 M12 17v4" />
156 | </svg>
157 | )}
158 | {project.slug === "canvas-of-hope" && (
159 | <svg className="w-4 h-4 text-charcoal/40 fill-none stroke-current" strokeWidth="2" viewBox="0 0 24 24">
160 | <circle cx="12" cy="12" r="10" />
161 | <path d="M8 14s1.5 2 4 2 4-2 4-2" />
162 | </svg>
163 | )}
164 | <span>{project.impactMetric}</span>
165 | </div>
166 | </div>
167 | </div>
168 | );
169 | };
170 |

```



```
68 | }) => {
69 |   return (
70 |     <div
71 |       className={cn(
72 |         "prose-premium",
73 |         proseSizes[size],
74 |         muted ? "text-charcoal/60" : "text-charcoal/75",
75 |         centered && "mx-auto text-center",
76 |         className
77 |       )}
78 |     >
79 |     {children}
80 |   </div>
81 | );
82 | };
83 |
```

81. src/components/ui/SectionDivider.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { motion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { Sparkles } from "lucide-react";
7 |
8 | export interface SectionDividerProps {
9 |   variant?: "minimal" | "premium" | "decorative";
10 |   icon?: React.ReactNode;
11 |   animate?: boolean;
12 |   className?: string;
13 | }
14 |
15 | export const SectionDivider: React.FC<SectionDividerProps> = ({
16 |   variant = "premium",
17 |   icon,
18 |   animate = true,
19 |   className,
20 | }) => {
21 |   const lineVariants = {
22 |     hidden: { scaleX: 0, opacity: 0 },
23 |     visible: {
24 |       scaleX: 1,
25 |       opacity: 1,
26 |       transition: { duration: 0.8, ease: [0.16, 1, 0.3, 1] },
27 |     },
28 |   };
29 |
30 |   const centerVariants = {
31 |     hidden: { scale: 0, opacity: 0 },
32 |     visible: {
33 |       scale: 1,
34 |       opacity: 1,
35 |       transition: { delay: 0.4, duration: 0.5, type: "spring", stiffness: 200, damping: 15 },
36 |     },
37 |   };
38 |
39 |   const currentIcon = icon || <Sparkles className="w-4 h-4 text-[#B38728]" />;
40 |
41 |   return (
42 |     <div className={cn("relative flex items-center justify-center my-12 w-full select-none", className)}>
43 |       {variant === "minimal" && (
44 |         <div className="flex items-center w-full max-w-lg">
45 |           <motion.div
46 |             variants={animate ? lineVariants : undefined}
47 |             initial="hidden"
48 |             whileInView="visible"
49 |             viewport={{ once: true, amount: 0.2 }}
50 |             className="h-[1px] bg-charcoal/10 flex-grow origin-right"
51 |           />
52 |           <motion.div
53 |             variants={animate ? centerVariants : undefined}
54 |             initial="hidden"
55 |             whileInView="visible"
56 |             viewport={{ once: true, amount: 0.2 }}
57 |             className="w-2 h-2 mx-4 rounded-full bg-linear-to-r from-[#BF953F] to-[#B38728]"
58 |           />
59 |           <motion.div
60 |             variants={animate ? lineVariants : undefined}
61 |             initial="hidden"
62 |             whileInView="visible"
63 |             viewport={{ once: true, amount: 0.2 }}
64 |             className="h-[1px] bg-charcoal/10 flex-grow origin-left"
65 |           />
66 |         </div>
67 |       )}

```

```

68 |
69 | {variant === "premium" && (
70 | <div className="flex items-center w-full max-w-2xl">
71 | <motion.div
72 |   variants={animate ? lineVariants : undefined}
73 |   initial="hidden"
74 |   whileInView="visible"
75 |   viewport={{ once: true, amount: 0.2 }}
76 |   className="h-[1px] bg-linear-to-l from-charcoal/20 via-charcoal/5 to-transparent flex-grow origin-right"
77 | />
78 | <motion.div
79 |   variants={animate ? centerVariants : undefined}
80 |   initial="hidden"
81 |   whileInView="visible"
82 |   viewport={{ once: true, amount: 0.2 }}
83 |   className="flex items-center justify-center p-2.5 mx-4 rounded-full bg-cream border border-[#BF953F]/30
shadow-xs"
84 | >
85 | {currentIcon}
86 | </motion.div>
87 | <motion.div
88 |   variants={animate ? lineVariants : undefined}
89 |   initial="hidden"
90 |   whileInView="visible"
91 |   viewport={{ once: true, amount: 0.2 }}
92 |   className="h-[1px] bg-linear-to-r from-charcoal/20 via-charcoal/5 to-transparent flex-grow origin-left"
93 | />
94 | </div>
95 | )}
96 |
97 | {variant === "decorative" && (
98 | <div className="flex flex-col items-center gap-1.5 w-full max-w-md">
99 | <div className="flex items-center w-full">
100 | <motion.div
101 |   variants={animate ? lineVariants : undefined}
102 |   initial="hidden"
103 |   whileInView="visible"
104 |   viewport={{ once: true, amount: 0.2 }}
105 |   className="h-[1px] bg-linear-to-l from-charcoal/15 to-transparent flex-grow origin-right"
106 | />
107 | <motion.div
108 |   variants={animate ? centerVariants : undefined}
109 |   initial="hidden"
110 |   whileInView="visible"
111 |   viewport={{ once: true, amount: 0.2 }}
112 |   className="mx-3 text-[#B38728] flex items-center justify-center"
113 | >
114 | {currentIcon}
115 | </motion.div>
116 | <motion.div
117 |   variants={animate ? lineVariants : undefined}
118 |   initial="hidden"
119 |   whileInView="visible"
120 |   viewport={{ once: true, amount: 0.2 }}
121 |   className="h-[1px] bg-linear-to-r from-charcoal/15 to-transparent flex-grow origin-left"
122 | />
123 | </div>
124 | {/* Subtle bottom decorative leaf/dot pattern */}
125 | <motion.div
126 |   initial={{ opacity: 0, y: 5 }}
127 |   whileInView={{ opacity: 1, y: 0 }}
128 |   viewport={{ once: true, amount: 0.2 }}
129 |   transition={{ delay: 0.6, duration: 0.4 }}
130 |   className="flex items-center gap-1.5"
131 | >
132 | <span className="w-1.5 h-1.5 rounded-full bg-[#BF953F]/40" />
133 | <span className="w-1.5 h-1.5 rounded-full bg-[#BF953F]/70" />
134 | <span className="w-1.5 h-1.5 rounded-full bg-[#BF953F]/40" />
135 | </motion.div>
136 | </div>

```

```
137 | })  
138 | </div>  
139 | );  
140 | };  
141 |  
142 | export default SectionDivider;  
143 |
```

82. src/components/ui/SectionHeading.tsx

```
1 | import React from "react";
2 | import { SectionHeadingProps } from "@types";
3 | import { cn } from "@utils/cn";
4 | import { Badge } from "../Badge";
5 |
6 | export const SectionHeading: React.FC<SectionHeadingProps> = ({
7 |   title,
8 |   subtitle,
9 |   badge,
10 |   centered = false,
11 |   className,
12 | }) => {
13 |   return (
14 |     <div
15 |       className={cn(
16 |         "flex flex-col gap-3 max-w-3xl mb-10 sm:mb-12",
17 |         centered ? "mx-auto text-center items-center" : "text-left items-start",
18 |         className
19 |       )}
20 |     >
21 |       {badge && <Badge label={badge} variant="info" className="w-fit" />}
22 |       <h2 className="text-3xl sm:text-4xl font-bold tracking-tight text-charcoal font-heading leading-tight">
23 |         {title}
24 |       </h2>
25 |       {subtitle && (
26 |         <p className="text-base sm:text-lg text-charcoal/65 leading-relaxed font-body">
27 |           {subtitle}
28 |         </p>
29 |       )}
30 |     </div>
31 |   );
32 | };
33 |
```

83. src/components/ui/Skeleton.tsx

[illegible]

Page 185 of 252

84. src/components/ui/SocialIcons.tsx

```

1 | import React from "react";
2 | import { SocialIconsProps } from "@types";
3 | import { cn } from "@utils/cn";
4 | import { Facebook, Twitter, Instagram, Linkedin, Youtube } from "lucide-react";
5 | import { siteConfig } from "@constants/data";
6 |
7 | export const SocialIcons: React.FC<SocialIconsProps> = ({
8 |   links,
9 |   className,
10 |   iconClassName,
11 | }) => {
12 |   const activeLinks = links || siteConfig.socials;
13 |
14 |   const renderIcon = (platform: string): React.ReactNode => {
15 |     const size = 18;
16 |     switch (platform) {
17 |       case "facebook":
18 |         return <Facebook size={size} />;
19 |       case "twitter":
20 |         return <Twitter size={size} />;
21 |       case "instagram":
22 |         return <Instagram size={size} />;
23 |       case "linkedin":
24 |         return <Linkedin size={size} />;
25 |       case "youtube":
26 |         return <Youtube size={size} />;
27 |       default:
28 |         return null;
29 |     }
30 |   };
31 |
32 |   return (
33 |     <div className={cn("flex items-center gap-3", className)}>
34 |       {activeLinks.map((link, index) => (
35 |         <a
36 |           key={index}
37 |           href={link.href}
38 |           target="_blank"
39 |           rel="noopener noreferrer"
40 |           className={cn(
41 |             "p-2.5 rounded-full bg-forest/10 text-forest hover:bg-forest hover:text-cream transition-all duration-255
42 |             cursor-pointer",
43 |             iconClassName
44 |           )}
45 |           aria-label={`Visit our ${link.platform} page`}
46 |           >
47 |             {renderIcon(link.platform)}
48 |           </a>
49 |         </div>
50 |       )}
51 |     );
52 |   );

```

85. src/components/ui/StatItem.tsx

```
1 | import React from "react";
2 | import { StatItemProps } from "@types";
3 |
4 | export const StatItem: React.FC<StatItemProps> = ({
5 |   value,
6 |   label,
7 |   icon,
8 |   description,
9 | }) => {
10 |   return (
11 |     <div className="flex flex-col items-center text-center p-6 sm:p-8 rounded-3xl bg-cream border border-forest/15
12 | hover:border-forest/30 transition-all duration-300 shadow-sm hover:shadow-md">
13 |       {icon} && <div className="text-forest mb-4 p-3.5 rounded-full bg-mint/40">{icon}</div>
14 |       <span
15 |         className="text-5xl sm:text-6xl font-normal text-forest tracking-tight mb-1 leading-none"
16 |         style={{ fontFamily: "var(--font-display)", fontVariantNumeric: "tabular-nums" }}
17 |       >
18 |         {value}
19 |       </span>
20 |       <span className="text-sm font-bold text-charcoal font-heading tracking-wider uppercase mb-2">
21 |         {label}
22 |       </span>
23 |       {description && (
24 |         <span className="text-xs sm:text-sm text-charcoal/60 leading-relaxed font-body">
25 |           {description}
26 |         </span>
27 |       )}
28 |     </div>
29 |   );
30 | }
```

86. src/components/ui/StickyScrollSection.tsx

```

1 | "use client";
2 |
3 | import React, { useRef, useState, useEffect } from "react";
4 | import Image from "next/image";
5 | import { cn } from "@utils/cn";
6 | import { useGSAP } from "@hooks/useGSAP";
7 | import { useReducedMotion } from "framer-motion";
8 | import ScrollTrigger from "gsap/ScrollTrigger";
9 |
10 | export interface StickyScrollStep {
11 |   title: string;
12 |   description: string;
13 |   imageSrc: string;
14 |   imageAlt: string;
15 | }
16 |
17 | export interface StickyScrollSectionProps {
18 |   steps: StickyScrollStep[];
19 |   className?: string;
20 | }
21 |
22 | export const StickyScrollSection: React.FC<StickyScrollSectionProps> = ({ steps, className }) => {
23 |   const containerRef = useRef<HTMLDivElement | null>(null);
24 |   const leftPanelRef = useRef<HTMLDivElement | null>(null);
25 |   const stepsRefs = useRef<(HTMLDivElement | null)[]>([]);
26 |   const shouldReduceMotion = useReducedMotion();
27 |   const [activeStep, setActiveStep] = useState(0);
28 |
29 |   // Monitor loading completions to recalculate GSAP measurements
30 |   const [imagesLoaded, setImagesLoaded] = useState(0);
31 |
32 |   useEffect(() => {
33 |     if (imagesLoaded >= steps.length) {
34 |       // Trigger a ScrollTrigger recalculation once all imagery height settles
35 |       requestAnimationFrame(() => {
36 |         ScrollTrigger.refresh();
37 |       });
38 |     }
39 |   }, [imagesLoaded, steps.length]);
40 |
41 |   // Active step transitions using GSAP ScrollTrigger context wrapper
42 |   useGSAP(() => {
43 |     // Completely disable GSAP scroll linking if prefers-reduced-motion is active
44 |     if (shouldReduceMotion) return;
45 |
46 |     // Track scrolling Narrative Steps (runs on all viewports, updating index)
47 |     stepsRefs.current.forEach((stepEl, idx) => {
48 |       if (!stepEl) return;
49 |       ScrollTrigger.create({
50 |         trigger: stepEl,
51 |         start: "top center",
52 |         end: "bottom center",
53 |         onToggle: (self) => {
54 |           if (self.isActive) {
55 |             setActiveStep(idx);
56 |           }
57 |         },
58 |       });
59 |     });
60 |   }, [shouldReduceMotion]);
61 |
62 |   const handleImageLoad = () => {
63 |     setImagesLoaded((prev) => prev + 1);
64 |   };
65 |
66 |   return (
67 |     <div

```

```

68 |   ref={containerRef}
69 |   className={cn(
70 |     "relative flex flex-col md:flex-row w-full bg-cream border-t border-b border-forest/5",
71 |     className
72 |   )}
73 | >
74 | {/*
75 |   Left Side: Sticky Media Display Panel.
76 |   On mobile, it scrolls naturally. On desktop, it is sticky.
77 | */}
78 | <div
79 |   ref={leftPanelRef}
80 |   className={cn(
81 |     "w-full md:w-1/2 overflow-hidden z-20",
82 |     shouldReduceMotion
83 |     ? "h-[250px] md:h-[450px] md:sticky md:top-24 rounded-3xl"
84 |     : "h-[300px] md:sticky md:top-24 md:h-[calc(100vh-120px)] flex items-center justify-center p-4 md:p-12"
85 |   )}
86 | >
87 |   <div className="w-full h-full relative rounded-3xl overflow-hidden shadow-xs border border-forest/10
bg-sage/20">
88 |     {steps.map((step, idx) => (
89 |       <div
90 |         key={idx}
91 |         className={cn(
92 |           "absolute inset-0 transition-all duration-700 ease-in-out",
93 |           shouldReduceMotion
94 |           ? activeStep === idx ? "opacity-100 scale-100 z-10" : "opacity-0 scale-98 z-0"
95 |           : activeStep === idx ? "opacity-100 scale-100 translate-y-0 z-10" : "opacity-0 scale-95 translate-y-4 z-0"
96 |         )}
97 |       >
98 |         <Image
99 |           src={step.imageSrc}
100 |           alt={step.imageAlt}
101 |           fill
102 |           priority={idx === 0}
103 |           onLoad={handleImageLoad}
104 |           sizes="(max-width: 768px) 100vw, 50vw"
105 |           className="object-cover"
106 |         />
107 |         <div className="absolute inset-0 bg-gradient-to-t from-charcoal/40 via-transparent to-transparent
pointer-events-none" />
108 |       </div>
109 |     )})
110 |   </div>
111 | </div>
112 |
113 | {/*
114 |   Right Side: Narrative Scrolling Texts.
115 |   Each step takes sufficient viewport space to trigger boundaries.
116 | */}
117 | <div className="w-full md:w-1/2 flex flex-col px-6 md:px-16 pb-16 md:pb-0 z-10">
118 |   {steps.map((step, idx) => (
119 |     <div
120 |       key={idx}
121 |       ref={(el) => {
122 |         stepsRefs.current[idx] = el;
123 |       }}
124 |       className={cn(
125 |         "flex flex-col justify-center min-h-[30vh] md:min-h-screen py-16 md:py-20 transition-all duration-500
text-left",
126 |         activeStep === idx
127 |         ? "opacity-100 translate-x-0"
128 |         : "opacity-45 -translate-x-2 md:opacity-20"
129 |       )}
130 |     >
131 |       <span className="text-xs font-bold font-heading uppercase tracking-wider text-forest/75 mb-3 block">
132 |         Step {idx + 1}
133 |       </span>
134 |       <h3 className="text-2xl sm:text-3xl font-extrabold text-charcoal font-heading leading-tight mb-4">

```

```
135 | {step.title}
136 | </h3>
137 | <p className="text-sm sm:text-base text-charcoal/80 leading-relaxed font-body">
138 | {step.description}
139 | </p>
140 | </div>
141 | )})
142 | </div>
143 | </div>
144 | );
145 | };
146 |
147 | export default StickyScrollSection;
148 |
```

87. src/components/ui/TestimonialSlider.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useEffect, useCallback } from "react";
4 | import { motion, AnimatePresence } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { Star, Quote, ChevronLeft, ChevronRight } from "lucide-react";
7 | import Image from "next/image";
8 |
9 | export interface TestimonialData {
10 |   name: string;
11 |   role: string;
12 |   avatar: string;
13 |   quote: string;
14 |   rating: number; // 1 to 5
15 |   company?: string;
16 |   logo?: string; // Optional logo path
17 | }
18 |
19 | export interface TestimonialSliderProps {
20 |   testimonials: TestimonialData[];
21 |   autoplay?: boolean;
22 |   interval?: number; // ms
23 |   className?: string;
24 | }
25 |
26 | export const TestimonialSlider: React.FC<TestimonialSliderProps> = ({
27 |   testimonials,
28 |   autoplay = true,
29 |   interval = 6000,
30 |   className,
31 | }) => {
32 |   const [activeIndex, setActiveIndex] = useState(0);
33 |   const [direction, setDirection] = useState(0); // -1: left, 1: right
34 |   const [isHovered, setIsHovered] = useState(false);
35 |
36 |   const handleNext = useCallback(() => {
37 |     setDirection(1);
38 |     setActiveIndex((prev) => (prev + 1) % testimonials.length);
39 |   }, [testimonials.length]);
40 |
41 |   const handlePrev = useCallback(() => {
42 |     setDirection(-1);
43 |     setActiveIndex((prev) => (prev - 1 + testimonials.length) % testimonials.length);
44 |   }, [testimonials.length]);
45 |
46 |   const jumpTo = (index: number) => {
47 |     setDirection(index > activeIndex ? 1 : -1);
48 |     setActiveIndex(index);
49 |   };
50 |
51 |   useEffect(() => {
52 |     if (!autoplay || isHovered) return;
53 |
54 |     const timer = setInterval(() => {
55 |       handleNext();
56 |     }, interval);
57 |
58 |     return () => clearInterval(timer);
59 |   }, [autoplay, interval, isHovered, handleNext]);
60 |
61 |   const current = testimonials[activeIndex];
62 |
63 |   const slideVariants = {
64 |     enter: (dir: number) => ({
65 |       x: dir > 0 ? "50%" : "-50%",
66 |       opacity: 0,
67 |     }),

```

```

68 | center: {
69 | x: 0,
70 | opacity: 1,
71 | },
72 | exit: (dir: number) => ({
73 | x: dir < 0 ? "50%" : "-50%",
74 | opacity: 0,
75 | })),
76 | };
77 |
78 | return (
79 | <div
80 | onMouseEnter={() => setIsHovered(true)}
81 | onMouseLeave={() => setIsHovered(false)}
82 | className={cn(
83 | "relative w-full max-w-2xl mx-auto p-6 sm:p-10 rounded-[32px] bg-cream border border-forest/10 shadow-xs flex
flex-col gap-6 select-none overflow-hidden text-center items-center justify-center cursor-default",
84 | className
85 | )}
86 | >
87 | {/* Decorative Gold top border */}
88 | <span className="absolute top-0 left-0 right-0 h-[3px] bg-linear-to-r from-[#BF953F] via-[#F7DF7C] to-[#B38728]
z-10" />
89 |
90 | {/* Quote Symbol background */}
91 | <div className="absolute top-6 left-6 text-forest/5 pointer-events-none z-0">
92 | <Quote className="w-20 h-20 rotate-180" />
93 | </div>
94 |
95 | <div className="relative w-full min-h-[180px] z-10 flex flex-col items-center justify-center">
96 | <AnimatePresence initial={false} mode="wait" custom={direction}>
97 | <motion.div
98 | key={activeIndex}
99 | custom={direction}
100 | variants={slideVariants}
101 | initial="enter"
102 | animate="center"
103 | exit="exit"
104 | transition={{
105 | x: { type: "spring", stiffness: 350, damping: 30 },
106 | opacity: { duration: 0.2 },
107 | }}
108 | className="w-full flex flex-col items-center gap-4"
109 | >
110 | {/* Stars rating */}
111 | <div className="flex items-center gap-1.5 justify-center">
112 | {Array.from({ length: 5 }).map((_, i) => (
113 | <Star
114 | key={i}
115 | className={cn(
116 | "w-4 h-4",
117 | i < current.rating ? "text-[#B38728] fill-[#B38728]" : "text-charcoal/10"
118 | )}
119 | />
120 | )}
121 | </div>
122 |
123 | {/* Testimonial Quote */}
124 | <p className="text-base sm:text-lg font-body text-charcoal/80 italic leading-relaxed max-w-xl">
125 | &ldquo;{current.quote}&rdquo;
126 | </p>
127 |
128 | {/* Profile Avatar & Details */}
129 | <div className="flex flex-col items-center gap-2 mt-2">
130 | <div className="relative w-12 h-12 rounded-full overflow-hidden border border-forest/15 shadow-sm">
131 | <Image
132 | src={current.avatar}
133 | alt={current.name}
134 | fill
135 | className="object-cover"

```



```

136 | />
137 | </div>
138 | <div className="flex flex-col">
139 | <span className="font-heading font-bold text-sm text-charcoal">
140 | {current.name}
141 | </span>
142 | <span className="text-xs text-charcoal/50 font-body">
143 | {current.role} {current.company ? `• ${current.company}` : ""}
144 | </span>
145 | </div>
146 | </div>
147 |
148 | {/* Company logo if present */}
149 | {current.logo && (
150 | <div className="relative w-20 h-8 opacity-45 grayscale hover:opacity-100 hover:grayscale-0 transition-all
duration-300 mt-1 flex items-center justify-center">
151 | <Image
152 | src={current.logo}
153 | alt="Company logo"
154 | fill
155 | className="object-contain"
156 | />
157 | </div>
158 | )}
159 | </motion.div>
160 | </AnimatePresence>
161 | </div>
162 |
163 | {/* Manual Chevron controls */}
164 | <div className="flex items-center justify-between w-full mt-2 z-10 px-2">
165 | <button
166 | onClick={handlePrev}
167 | aria-label="Previous testimonial"
168 | className="w-9 h-9 flex items-center justify-center rounded-full bg-forest/5 hover:bg-forest/10 text-forest
border border-forest/10 cursor-pointer focus:outline-hidden focus:ring-2 focus:ring-forest/30"
169 | >
170 | <ChevronLeft className="w-5 h-5" />
171 | </button>
172 |
173 | {/* Pagination Dots */}
174 | <div className="flex items-center gap-1.5 select-none">
175 | {testimonials.map((_, idx) => (
176 | <button
177 | key={idx}
178 | onClick={() => jumpTo(idx)}
179 | aria-label={`Go to slide ${idx + 1}`}
180 | className={cn(
181 | "w-2 h-2 rounded-full transition-all duration-200 cursor-pointer focus:outline-hidden",
182 | activeIndex === idx ? "w-5 bg-forest" : "bg-forest/20 hover:bg-forest/45"
183 | )}
184 | />
185 | )})}
186 | </div>
187 |
188 | <button
189 | onClick={handleNext}
190 | aria-label="Next testimonial"
191 | className="w-9 h-9 flex items-center justify-center rounded-full bg-forest/5 hover:bg-forest/10 text-forest
border border-forest/10 cursor-pointer focus:outline-hidden focus:ring-2 focus:ring-forest/30"
192 | >
193 | <ChevronRight className="w-5 h-5" />
194 | </button>
195 | </div>
196 | </div>
197 | );
198 | };
199 |
200 | export default TestimonialSlider;
201 |

```

88. src/components/ui/TextReveal.tsx

```

1 | "use client";
2 |
3 | import React from "react";
4 | import { motion, useReducedMotion } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface TextRevealProps {
8 |   children: string;
9 |   mode?: "chars" | "words";
10 |   delay?: number;
11 |   duration?: number;
12 |   stagger?: number;
13 |   className?: string;
14 | }
15 |
16 | export const TextReveal: React.FC<TextRevealProps> = ({
17 |   children,
18 |   mode = "words",
19 |   delay = 0,
20 |   duration = 0.6,
21 |   stagger = 0.03,
22 |   className,
23 | }) => {
24 |   const shouldReduceMotion = useReducedMotion();
25 |
26 |   // Fallback for prefers-reduced-motion to simplify accessibility
27 |   if (shouldReduceMotion) {
28 |     return <span className={className}>{children}</span>;
29 |   }
30 |
31 |   const words = children.split(" ");
32 |
33 |   const textContainerVariants = {
34 |     hidden: {},
35 |     visible: {
36 |       transition: {
37 |         staggerChildren: stagger,
38 |         delayChildren: delay,
39 |       },
40 |     },
41 |   };
42 |
43 |   const textItemVariants = {
44 |     hidden: { y: "100%", opacity: 0 },
45 |     visible: {
46 |       y: "0%",
47 |       opacity: 1,
48 |       transition: { duration, ease: [0.16, 1, 0.3, 1] },
49 |     },
50 |   };
51 |
52 |   return (
53 |     <span className={cn("relative inline", className)}>
54 |       {/*
55 |       1. Selectable, copyable, and search-indexable real text.
56 |       Rendered absolutely with opacity-0 to cover the visual spans and support selections.
57 |       */}
58 |       <span className="absolute inset-0 opacity-0 select-text pointer-events-auto z-10">
59 |         {children}
60 |       </span>
61 |
62 |       {/*
63 |       2. Visual animated spans rendered in normal layout flow.
64 |       Inherits parent typography, centering, and wrapping styles natively.
65 |       */}
66 |       <motion.span
67 |         aria-hidden="true"

```

```
68 | variants={textContainerVariants}
69 | initial="hidden"
70 | whileInView="visible"
71 | viewport={{ once: true, amount: 0.15 }}
72 | className="inline select-none pointer-events-none"
73 | >
74 | {mode === "chars" ? (
75 | words.map((word, wordIdx) => (
76 | <span key={wordIdx} className="inline-flex mr-[0.25em] overflow-hidden h-full">
77 | {word.split("").map((char, charIdx) => (
78 | <motion.span
79 | key={charIdx}
80 | variants={textItemVariants}
81 | className="inline-block"
82 | >
83 | {char}
84 | </motion.span>
85 | )})
86 | </span>
87 | ))
88 | ) : (
89 | words.map((word, idx) => (
90 | <span key={idx} className="inline-block overflow-hidden mr-[0.25em] h-full">
91 | <motion.span
92 | variants={textItemVariants}
93 | className="inline-block"
94 | >
95 | {word}
96 | </motion.span>
97 | </span>
98 | ))
99 | )}
100 | </motion.span>
101 | </span>
102 | );
103 | };
104 |
105 | export default TextReveal;
106 |
```

89. src/components/ui/ThemeToggle.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { Sun, Moon } from "lucide-react";
5 | import { m, AnimatePresence, useReducedMotion } from "framer-motion";
6 | import { useTheme } from "../providers/ThemeProvider";
7 | import { flushSync } from "react-dom";
8 |
9 | export const ThemeToggle: React.FC = () => {
10 |   const { theme, setTheme } = useTheme();
11 |   const shouldReduceMotion = useReducedMotion();
12 |
13 |   // Track pointer coordinates from onPointerDown
14 |   const pointerCoords = useRef<{ x: number; y: number } | null>(null);
15 |
16 |   const handlePointerDown = (e: React.PointerEvent<HTMLButtonElement>) => {
17 |     pointerCoords.current = { x: e.clientX, y: e.clientY };
18 |   };
19 |
20 |   const runCanvasRipple = (nextTheme: "light" | "dark", x: number, y: number, maxRadius: number) => {
21 |     // Resolve old theme wash background color from CSS theme variables
22 |     const docStyle = getComputedStyle(document.documentElement);
23 |     const lightBg = docStyle.getPropertyValue("--light-bg").trim() || "#F9F8F3";
24 |     const darkBg = docStyle.getPropertyValue("--dark-bg").trim() || "#141E15";
25 |     const oldColor = theme === "light" ? lightBg : darkBg;
26 |
27 |     // Create and scale fixed fullscreen canvas overlay
28 |     const canvas = document.createElement("canvas");
29 |     canvas.id = "theme-ripple-canvas";
30 |     canvas.style.position = "fixed";
31 |     canvas.style.inset = "0";
32 |     canvas.style.width = "100vw";
33 |     canvas.style.height = "100vh";
34 |     canvas.style.zIndex = "999999";
35 |     canvas.style.pointerEvents = "none";
36 |     document.body.appendChild(canvas);
37 |
38 |     const ctx = canvas.getContext("2d");
39 |     if (!ctx) {
40 |       setTheme(nextTheme);
41 |       canvas.remove();
42 |       return;
43 |     }
44 |
45 |     const dpr = Math.min(window.devicePixelRatio || 1, 2);
46 |     const width = window.innerWidth;
47 |     const height = window.innerHeight;
48 |
49 |     canvas.width = width * dpr;
50 |     canvas.height = height * dpr;
51 |     ctx.scale(dpr, dpr);
52 |
53 |     // Switch the theme state in React immediately so the DOM updates underneath
54 |     setTheme(nextTheme);
55 |
56 |     let startTime: number | null = null;
57 |     const duration = 650; // slightly faster for responsiveness
58 |
59 |     const animate = (timestamp: number) => {
60 |       if (!startTime) startTime = timestamp;
61 |       const elapsed = timestamp - startTime;
62 |       const progress = Math.min(elapsed / duration, 1);
63 |
64 |       // Easing: easeOutCubic
65 |       const easeOutCubic = 1 - Math.pow(1 - progress, 3);
66 |       const currentRadius = maxRadius * easeOutCubic;
67 |

```

```

68 | ctx.clearRect(0, 0, width, height);
69 |
70 | // 1. Draw the old background color covering the screen
71 | ctx.globalCompositeOperation = "source-over";
72 | ctx.fillStyle = oldColor;
73 | ctx.fillRect(0, 0, width, height);
74 |
75 | // 2. Erase a circular path from the overlay to reveal the new theme underneath
76 | ctx.globalCompositeOperation = "destination-out";
77 | ctx.beginPath();
78 | ctx.arc(x, y, currentRadius, 0, Math.PI * 2);
79 | ctx.fill();
80 |
81 | if (progress < 1) {
82 |   requestAnimationFrame(animate);
83 | } else {
84 |   canvas.remove();
85 | }
86 | };
87 |
88 | requestAnimationFrame(animate);
89 | };
90 |
91 | const handleToggle = (e: React.MouseEvent<HTMLButtonElement>) => {
92 |   const nextTheme = theme === "light" ? "dark" : "light";
93 |
94 |   // 1. Reduced Motion Accessibility Check
95 |   if (shouldReduceMotion) {
96 |     setTheme(nextTheme);
97 |     pointerCoords.current = null;
98 |     return;
99 |   }
100 |
101 |   // 2. Determine animation coordinates origin
102 |   let x = 0;
103 |   let y = 0;
104 |
105 |   if (pointerCoords.current && (pointerCoords.current.x !== 0 || pointerCoords.current.y !== 0)) {
106 |     x = pointerCoords.current.x;
107 |     y = pointerCoords.current.y;
108 |   } else {
109 |     // Keyboard interaction or fallback: use center of button
110 |     const rect = e.currentTarget.getBoundingClientRect();
111 |     x = rect.left + rect.width / 2;
112 |     y = rect.top + rect.height / 2;
113 |   }
114 |   pointerCoords.current = null; // Reset coordinates
115 |
116 |   const width = window.innerWidth;
117 |   const height = window.innerHeight;
118 |   const maxRadius = Math.hypot(
119 |     Math.max(x, width - x),
120 |     Math.max(y, height - y)
121 |   );
122 |
123 |   // 3. Check if browser supports View Transitions API
124 |   const docWithTransition = document as unknown as {
125 |     startViewTransition?: (callback: () => void) => void;
126 |   };
127 |   if (!docWithTransition.startViewTransition) {
128 |     runCanvasRipple(nextTheme, x, y, maxRadius);
129 |     return;
130 |   }
131 |
132 |   // 4. Set CSS custom properties on documentElement for View Transition keyframe interpolation
133 |   document.documentElement.style.setProperty("--ripple-x", `${x}px`);
134 |   document.documentElement.style.setProperty("--ripple-y", `${y}px`);
135 |   document.documentElement.style.setProperty("--ripple-r", `${maxRadius}px`);
136 |
137 |   docWithTransition.startViewTransition(() => {

```

```

138 | flushSync(() => {
139 |   setTheme(nextTheme);
140 | });
141 | });
142 | };
143 |
144 | return (
145 |   <button
146 |     onClick={handleToggle}
147 |     onPointerDown={handlePointerDown}
148 |     className="p-2.5 text-charcoal hover:text-forest bg-charcoal/5 hover:bg-charcoal/10 rounded-full cursor-pointer
focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40 transition-colors relative flex items-center
justify-center w-10 h-10"
149 |     aria-label="Toggle theme color"
150 |     aria-pressed={theme === "dark"}
151 |   >
152 |     <AnimatePresence mode="wait" initial={false}>
153 |       {theme === "light" ? (
154 |         <m.div
155 |           key="sun"
156 |           initial={{ scale: 0.5, rotate: -45, opacity: 0 }}
157 |           animate={{ scale: 1, rotate: 0, opacity: 1 }}
158 |           exit={{ scale: 0.5, rotate: 45, opacity: 0 }}
159 |           transition={{ type: "spring", stiffness: 300, damping: 20 }}
160 |           className="w-5 h-5 flex items-center justify-center text-charcoal"
161 |         >
162 |           <Sun size={20} className="stroke-[2.5]" />
163 |         </m.div>
164 |       ) : (
165 |         <m.div
166 |           key="moon"
167 |           initial={{ scale: 0.5, rotate: 45, opacity: 0 }}
168 |           animate={{ scale: 1, rotate: 0, opacity: 1 }}
169 |           exit={{ scale: 0.5, rotate: -45, opacity: 0 }}
170 |           transition={{ type: "spring", stiffness: 300, damping: 20 }}
171 |           className="w-5 h-5 flex items-center justify-center text-charcoal"
172 |         >
173 |           <Moon size={20} className="stroke-[2.5]" />
174 |         </m.div>
175 |       )}
176 |     </AnimatePresence>
177 |   </button>
178 | );
179 | };
180 |
181 | export default ThemeToggle;
182 |

```

90. src/components/ui/TiltCard.tsx

```

1 | "use client";
2 |
3 | import React, { useRef, useState, useEffect } from "react";
4 | import { motion, useMotionValue, useSpring, useTransform } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 |
7 | export interface TiltCardProps {
8 |   intensity?: number; // max tilt degrees
9 |   glare?: boolean; // render cursor glare
10 |   scale?: number; // scale factor on hover
11 |   children: React.ReactNode;
12 |   className?: string;
13 | }
14 |
15 | export const TiltCard: React.FC<TiltCardProps> = ({
16 |   intensity = 15,
17 |   glare = true,
18 |   scale = 1.02,
19 |   children,
20 |   className,
21 | }) => {
22 |   const cardRef = useRef<HTMLDivElement | null>(null);
23 |   const [isMobile, setIsMobile] = useState(false);
24 |
25 |   // Check if touch device on client-side
26 |   useEffect(() => {
27 |     if (typeof window !== "undefined") {
28 |       const isTouch = window.matchMedia("(pointer: coarse)").matches || navigator.maxTouchPoints > 0;
29 |       const id = requestAnimationFrame(() => {
30 |         setIsMobile(isTouch);
31 |       });
32 |       return () => cancelAnimationFrame(id);
33 |     }
34 |   }, []);
35 |
36 |   const x = useMotionValue(0.5);
37 |   const y = useMotionValue(0.5);
38 |
39 |   const springConfig = { damping: 25, stiffness: 200, mass: 0.5 };
40 |   const rotateX = useSpring(useTransform(y, [0, 1], [intensity, -intensity]), springConfig);
41 |   const rotateY = useSpring(useTransform(x, [0, 1], [-intensity, intensity]), springConfig);
42 |
43 |   // Glare coordinates
44 |   const glareOpacity = useSpring(0, springConfig);
45 |   const glareX = useTransform(x, [0, 1], ["0%", "100%"]);
46 |   const glareY = useTransform(y, [0, 1], ["0%", "100%"]);
47 |
48 |   const handleMouseMove = (e: React.MouseEvent<HTMLDivElement>) => {
49 |     if (isMobile || !cardRef.current) return;
50 |
51 |     const rect = cardRef.current.getBoundingClientRect();
52 |     const width = rect.width;
53 |     const height = rect.height;
54 |     const clientX = e.clientX - rect.left;
55 |     const clientY = e.clientY - rect.top;
56 |
57 |     x.set(clientX / width);
58 |     y.set(clientY / height);
59 |     glareOpacity.set(0.3);
60 |   };
61 |
62 |   const handleMouseLeave = () => {
63 |     x.set(0.5);
64 |     y.set(0.5);
65 |     glareOpacity.set(0);
66 |   };
67 |

```

```

68 | return (
69 | <div
70 | ref={cardRef}
71 | onMouseMove={handleMouseMove}
72 | onMouseLeave={handleMouseLeave}
73 | className={cn(
74 | "relative rounded-[32px] overflow-hidden select-none cursor-default",
75 | !isMobile && "perspective-[1000px]",
76 | className
77 | )}
78 | >
79 | <motion.div
80 | style={
81 | isMobile
82 | ? {}
83 | : {
84 | rotateX,
85 | rotateY,
86 | transformStyle: "preserve-3d",
87 | }
88 | }
89 | whileHover={isMobile ? { scale: 1.01 } : { scale }}
90 | transition={{ duration: 0.3 }}
91 | className="relative w-full h-full rounded-[inherit] overflow-hidden bg-cream border border-forest/10 shadow-xs"
92 | >
93 | /* Child content container with 3D depth */
94 | <div
95 | style={isMobile ? {} : { transform: "translateZ(30px)", transformStyle: "preserve-3d" }}
96 | className="relative z-10 w-full h-full"
97 | >
98 | {children}
99 | </div>
100 |
101 | /* Dynamic Sheen Glare */
102 | {glare && !isMobile && (
103 | <motion.div
104 | style={{
105 | opacity: glareOpacity,
106 | background: `radial-gradient(circle 250px at ${glareX} ${glareY}, rgba(255, 255, 255, 0.25), transparent 70%)`,
107 | }}
108 | className="absolute inset-0 pointer-events-none z-20"
109 | />
110 | )}
111 | </motion.div>
112 | </div>
113 | );
114 | };
115 |
116 | export default TiltCard;
117 |

```


91. src/components/ui/Timeline.tsx

```

1 | "use client";
2 |
3 | import React, { useRef } from "react";
4 | import { motion, useScroll, useSpring } from "framer-motion";
5 | import { cn } from "@utils/cn";
6 | import { Calendar } from "lucide-react";
7 |
8 | export interface TimelineItem {
9 |   id: string | number;
10 |   title: string;
11 |   subtitle?: string;
12 |   date: string;
13 |   content: React.ReactNode;
14 |   icon?: React.ReactNode;
15 | }
16 |
17 | export interface TimelineProps {
18 |   items: TimelineItem[];
19 |   orientation?: "vertical" | "horizontal";
20 |   variant?: "default" | "premium" | "outline";
21 |   className?: string;
22 | }
23 |
24 | export const Timeline: React.FC<TimelineProps> = ({
25 |   items,
26 |   orientation = "vertical",
27 |   variant = "premium",
28 |   className,
29 | }) => {
30 |   const containerRef = useRef<HTMLDivElement | null>(null);
31 |
32 |   // Track scroll progress across the container
33 |   const { scrollYProgress } = useScroll({
34 |     target: containerRef,
35 |     offset: ["start center", "end center"],
36 |   });
37 |
38 |   const scaleY = useSpring(scrollYProgress, { stiffness: 100, damping: 25, restDelta: 0.001 });
39 |
40 |   const isHorizontal = orientation === "horizontal";
41 |
42 |   const dotColorClass = {
43 |     default: "bg-forest border-cream",
44 |     premium: "bg-[#B38728] border-cream shadow-xs",
45 |     outline: "bg-cream border-forest",
46 |   };
47 |
48 |   const cardBorderClass = {
49 |     default: "bg-cream border-forest/15",
50 |     premium: "bg-cream border-forest/15 hover:border-[#BF953F]/40 shadow-xs",
51 |     outline: "bg-transparent border border-charcoal/20",
52 |   };
53 |
54 |   return (
55 |     <div
56 |       ref={containerRef}
57 |       className={cn(
58 |         "relative w-full",
59 |         isHorizontal ? "flex flex-col md:flex-row gap-6 md:gap-4 overflow-x-auto md:pb-8" : "flex flex-col gap-12",
60 |         className
61 |       )}
62 |     >
63 |       {/* 1. Vertical Layout */}
64 |       {!isHorizontal && (
65 |         <>
66 |           {/* Timeline background guide line */}

```

```

67 | <div className="absolute left-4 md:left-1/2 top-4 bottom-4 w-[2px] bg-charcoal/5 -translate-x-1/2
pointer-events-none" />
68 |
69 | /* Animated active progress indicator line */
70 | <motion.div
71 | style={{ scaleY, originY: 0 }}
72 | className="absolute left-4 md:left-1/2 top-4 bottom-4 w-[2px] bg-linear-to-b from-[#BF953F] via-[#F7DF7C]
to-[#B38728] -translate-x-1/2 pointer-events-none z-10"
73 | />
74 |
75 | {items.map((item, index) => {
76 |   const isLeft = index % 2 === 0;
77 |
78 |   return (
79 |     <div
80 |       key={item.id}
81 |       className="relative flex flex-col md:flex-row w-full items-start md:justify-between"
82 |     >
83 |       /* Timeline connection center node dot */
84 |       <div className="absolute left-4 md:left-1/2 w-8 h-8 rounded-full border-2 -translate-x-1/2 z-20 flex
items-center justify-center bg-cream shadow-sm pointer-events-none">
85 |         <motion.div
86 |           initial={{ scale: 0.5, opacity: 0 }}
87 |           whileInView={{ scale: 1, opacity: 1 }}
88 |           viewport={{ once: true, amount: 0.2 }}
89 |           transition={{ delay: 0.1, duration: 0.4 }}
90 |           className={cn("w-3.5 h-3.5 rounded-full", dotColorClass[variant])}
91 |         />
92 |       </div>
93 |
94 |       /* Left card spacing / Layout */
95 |       <div
96 |         className={cn(
97 |           "w-full md:w-[45%] pl-12 md:pl-0 flex flex-col",
98 |           isLeft ? "md:text-right md:items-end" : "md:opacity-0 md:pointer-events-none md:select-none"
99 |         )}
100 |       >
101 |         {isLeft && (
102 |           <motion.div
103 |             initial={{ opacity: 0, x: -30 }}
104 |             whileInView={{ opacity: 1, x: 0 }}
105 |             viewport={{ once: true, amount: 0.2 }}
106 |             transition={{ duration: 0.6, ease: [0.16, 1, 0.3, 1] }}
107 |             className={cn("p-6 rounded-[28px] border shadow-xs text-left", cardBorderClass[variant])}
108 |           >
109 |             <div className="flex items-center gap-2 mb-2 text-forest font-semibold text-sm">
110 |               {item.icon} <Calendar className="w-4 h-4" />
111 |             <span>{item.date}</span>
112 |           </div>
113 |           <h3 className="text-xl font-heading font-bold text-charcoal mb-1">
114 |             {item.title}
115 |           </h3>
116 |           {item.subtitle && (
117 |             <h4 className="text-sm font-semibold text-charcoal/50 mb-3">
118 |               {item.subtitle}
119 |             </h4>
120 |           )}
121 |           <div className="text-sm leading-relaxed text-charcoal/70 font-body">
122 |             {item.content}
123 |           </div>
124 |         </motion.div>
125 |       )}
126 |     </div>
127 |
128 |     /* Mid spacing helper */
129 |     <div className="hidden md:block w-[5%]" />
130 |
131 |     /* Right card spacing / Layout */
132 |     <div
133 |       className={cn(

```

```

134 | "w-full md:w-[45%] pl-12 md:pl-0 flex flex-col",
135 | !isLeft ? "md:text-left md:items-start" : "md:opacity-0 md:pointer-events-none md:select-none"
136 | })
137 | >
138 | {!isLeft && (
139 | <motion.div
140 | initial={{ opacity: 0, x: 30 }}
141 | whileInView={{ opacity: 1, x: 0 }}
142 | viewport={{ once: true, amount: 0.2 }}
143 | transition={{ duration: 0.6, ease: [0.16, 1, 0.3, 1] }}
144 | className={cn("p-6 rounded-[28px] border shadow-xs text-left", cardBorderClass[variant])}
145 | >
146 | <div className="flex items-center gap-2 mb-2 text-forest font-semibold text-sm">
147 | {item.icon || <Calendar className="w-4 h-4" />}
148 | <span>{item.date}</span>
149 | </div>
150 | <h3 className="text-xl font-heading font-bold text-charcoal mb-1">
151 | {item.title}
152 | </h3>
153 | {item.subtitle && (
154 | <h4 className="text-sm font-semibold text-charcoal/50 mb-3">
155 | {item.subtitle}
156 | </h4>
157 | )}
158 | <div className="text-sm leading-relaxed text-charcoal/70 font-body">
159 | {item.content}
160 | </div>
161 | </motion.div>
162 | )}
163 | </div>
164 | </div>
165 | );
166 | })}
167 | </>
168 | })
169 |
170 | /* 2. Horizontal Layout (stacks vertically on mobile, layout row on desktop) */
171 | {isHorizontal && (
172 | <div className="flex flex-col md:flex-row gap-8 md:gap-0 w-full relative pt-0 md:pt-16">
173 | /* Horizontal timeline guide line */
174 | <div className="hidden md:block absolute left-4 right-4 top-6 h-[2px] bg-charcoal/5 pointer-events-none" />
175 |
176 | {items.map((item, index) => {
177 |   return (
178 |     <div key={item.id} className="relative flex flex-col md:flex-1 items-start pl-8 md:pl-0 md:px-4">
179 |       /* Horizontal dot connect node */
180 |       <div className="absolute left-0 md:left-1/2 top-1.5 md:top-6 w-8 h-8 rounded-full border-2 -translate-x-1/2
181 |       -translate-y-1/2 z-20 flex items-center justify-center bg-cream shadow-sm pointer-events-none">
182 |         <motion.div
183 |           initial={{ scale: 0.5, opacity: 0 }}
184 |           whileInView={{ scale: 1, opacity: 1 }}
185 |           viewport={{ once: true, amount: 0.2 }}
186 |           transition={{ delay: 0.1, duration: 0.4 }}
187 |           className={cn("w-3.5 h-3.5 rounded-full", dotColorClass[variant])}
188 |         />
189 |       </div>
190 |       <motion.div
191 |         initial={{ opacity: 0, y: 20 }}
192 |         whileInView={{ opacity: 1, y: 0 }}
193 |         viewport={{ once: true, amount: 0.2 }}
194 |         transition={{ duration: 0.5, delay: index * 0.1 }}
195 |         className={cn("p-6 rounded-[28px] border shadow-xs w-full text-left", cardBorderClass[variant])}
196 |       >
197 |         <div className="flex items-center gap-2 mb-2 text-forest font-semibold text-sm">
198 |           {item.icon || <Calendar className="w-4 h-4" />}
199 |           <span>{item.date}</span>
200 |         </div>
201 |         <h3 className="text-lg font-heading font-bold text-charcoal mb-1">
202 |           {item.title}

```

```
203 | </h3>
204 | {item.subtitle && (
205 | <h4 className="text-xs font-semibold text-charcoal/50 mb-3">
206 | {item.subtitle}
207 | </h4>
208 | )}
209 | <div className="text-xs leading-relaxed text-charcoal/70 font-body">
210 | {item.content}
211 | </div>
212 | </motion.div>
213 | </div>
214 | );
215 | }}
216 | </div>
217 | )}
218 | </div>
219 | );
220 | };
221 |
222 | export default Timeline;
223 |
```

92. src/components/ui/index.ts

```
1 | // Existing components
2 | export { BackgroundPattern } from "./BackgroundPattern";
3 | export { Badge } from "./Badge";
4 | export { BlogCard } from "./BlogCard";
5 | export { Button } from "./Button";
6 | export { Container } from "./Container";
7 | export { Input } from "./Input";
8 | export { Loader } from "./Loader";
9 | export { ProjectCard } from "./ProjectCard";
10 | export { SectionHeading } from "./SectionHeading";
11 | export { SocialIcons } from "./SocialIcons";
12 | export { StatItem } from "./StatItem";
13 |
14 | // New Reusable UI Components
15 | export { AnimatedButton } from "./AnimatedButton";
16 | export { AnimatedCard } from "./AnimatedCard";
17 | export { AnimatedCounter } from "./AnimatedCounter";
18 | export { BeforeAfter } from "./BeforeAfter";
19 | export { DonationWidget } from "./DonationWidget";
20 | export { FAQAccordion } from "./FAQAccordion";
21 | export { FloatingButton } from "./FloatingButton";
22 | export { Gallery } from "./Gallery";
23 | export { GlassCard } from "./GlassCard";
24 | export { GradientHeading } from "./GradientHeading";
25 | export { ImpactCounter } from "./ImpactCounter";
26 | export { ImageSlider } from "./ImageSlider";
27 | export { SectionDivider } from "./SectionDivider";
28 | export { TestimonialSlider } from "./TestimonialSlider";
29 | export { TiltCard } from "./TiltCard";
30 | export { Timeline } from "./Timeline";
31 | export { BlurReveal } from "./BlurReveal";
32 | export { TextReveal } from "./TextReveal";
33 | export { ImageReveal } from "./ImageReveal";
34 | export { Magnetic } from "./Magnetic";
35 | export { StickyScrollSection } from "./StickyScrollSection";
36 | export { Parallax } from "./Parallax";
37 | export { Skeleton, CardSkeleton, SectionSkeleton, ImageSkeleton } from "./Skeleton";
38 | export { Section, Prose } from "./Section";
39 | export { styles } from "./styles";
40 |
```

93. src/components/ui/styles.ts

```
1 | /**
2 |  * Shared Design System Primitives & Token Mapping
3 |  * Reusable classes to ensure visual consistency across all components.
4 |  */
5 | export const styles = {
6 |   // Focus rings matching accessibility guidelines
7 |   focusRing: "focus-visible:ring-2 focus-visible:ring-forest/40 focus-visible:outline-hidden",
8 |
9 |   // Shadow tokens
10 |   shadow: {
11 |     sm: "shadow-xs border border-charcoal/5",
12 |     md: "shadow-sm border border-charcoal/10",
13 |     lg: "shadow-md border border-charcoal/15",
14 |     premium: "shadow-[0_10px_30px_rgba(27,34,30,0.04),0_1px_8px_rgba(27,34,30,0.02)] border border-forest/10",
15 |     premiumHover: "hover:shadow-[0_20px_40px_rgba(27,34,30,0.08),0_1px_15px_rgba(27,34,30,0.03)]",
16 |   },
17 |
18 |   // Glassmorphic backgrounds (Light / Premium)
19 |   glass: {
20 |     bg: "bg-cream/45 backdrop-blur-md",
21 |     border: "border border-cream/30",
22 |     glow: "shadow-[0_0_40px_rgba(247,223,124,0.15)]",
23 |   },
24 |
25 |   // Gold theme styles
26 |   gold: {
27 |     text: "bg-linear-to-r from-[#B38728] via-[#F7DF7C] to-[#BF953F] bg-clip-text text-transparent",
28 |     bg: "bg-linear-to-r from-[#BF953F] via-[#F7DF7C] to-[#B38728]",
29 |     border: "border border-[#BF953F]/30",
30 |     glow: "shadow-[0_0_20px_rgba(191,149,63,0.15)]",
31 |   },
32 |
33 |   // Transition settings
34 |   transition: "transition-all duration-300 cubic-bezier(0.16, 1, 0.3, 1)",
35 |   transitionFast: "transition-all duration-200 ease-in-out",
36 | };
37 |
38 | export default styles;
39 |
```

94. src/constants/data.ts

```

1 | import { NavItem, PageRoutes, Project, BlogPost, TeamMember, FAQItem, Testimonial } from "@/types";
2 | import { siteName, siteDescription } from "@/site";
3 |
4 | export const siteConfig = {
5 |   name: siteName,
6 |   description: siteDescription,
7 |   email: "hello@cognibloom.org",
8 |   phone: "+1 (555) 309-8422",
9 |   address: "108 Bloomingdale Rd, Suite 400, Seattle, WA 98101",
10 |   socials: [
11 |     { platform: "facebook", href: "https://facebook.com/cognibloom" },
12 |     { platform: "twitter", href: "https://twitter.com/cognibloom" },
13 |     { platform: "instagram", href: "https://instagram.com/cognibloom" },
14 |     { platform: "linkedin", href: "https://linkedin.com/company/cognibloom" },
15 |   ] as const,
16 | };
17 |
18 | export const navItems: NavItem[] = [
19 |   { label: "Home", href: PageRoutes.HOME },
20 |   { label: "About", href: PageRoutes.ABOUT_US },
21 |   { label: "Projects", href: PageRoutes.OUR_PROJECTS },
22 |   { label: "Blog", href: PageRoutes.BLOG },
23 | ];
24 |
25 | export const heroData = {
26 |   heading: "Sparking Universal Curiosity",
27 |   subheading: "We believe every child deserves a chance to learn, grow, and dream. Join us in making education a joyful adventure for all.",
28 |   primaryCtaText: "See Our Impact",
29 |   primaryCtaLink: PageRoutes.OUR_PROJECTS,
30 |   secondaryCtaText: "Get Involved",
31 |   secondaryCtaLink: PageRoutes.DONATE,
32 | };
33 |
34 | export const missionData = {
35 |   title: "Nurturing Joyful Wisdom",
36 |   description: "Through community education and engaging social initiatives, we create inspiring environments where learning blossoms naturally.",
37 |   bullets: [
38 |     "Arts & Creativity: Building local learning hubs that provide accessible resources and foster collaborative growth.",
39 |     "STEM & Innovation: Advocating for equitable access to educational tools and empowering marginalized voices.",
40 |     "Environment & Nature: Collaborating with like-minded organizations to amplify our impact and reach.",
41 |     "Holistic Well-being: An inspiring well-being process and holistic healthcare health."
42 |   ],
43 |   image: "https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=1000&auto=format&fit=crop"
44 | };
45 |
46 | export const focusCardsData = [
47 |   {
48 |     title: "Arts & Creativity",
49 |     description: "Building local learning hubs that provide accessible resources and foster collaborative growth.",
50 |     icon: "palette",
51 |     pattern: "leaf" as const,
52 |   },
53 |   {
54 |     title: "STEM & Innovation",
55 |     description: "Advocating for equitable access to educational tools and empowering marginalized voices.",
56 |     icon: "gear",
57 |     pattern: "circuit" as const,
58 |   },
59 |   {
60 |     title: "Environment & Nature",
61 |     description: "Collaborating with like-minded organizations to amplify our impact and reach.",
62 |     icon: "leaf",
63 |     pattern: "leaf" as const,
64 |   },

```

```

65 | {
66 |   title: "Holistic Well-being",
67 |   description: "An inspiring well-being process and holistic healthcare health.",
68 |   icon: "person",
69 |   pattern: "wave" as const,
70 | }
71 | ];
72 |
73 | export const aboutHeroData = {
74 |   heading: "Nurturing Joyful Wisdom.",
75 |   subheading: "We are Dua Charitable Trust, an educational NGO dedicated to transforming community learning into
an inspiring, inclusive, and deeply joyful adventure.",
76 |   image: "https://images.unsplash.com/photo-1503676260728-1c00da094a0b?q=80&w=1000&auto=format&fit=crop",
77 | };
78 |
79 | export const aboutStoryData = {
80 |   title: "Our Story",
81 |   cards: [
82 |     {
83 |       title: "The Beginning",
84 |       description: "Founded on the belief that education should not be a rigid institution but a blooming collective
effort, Dua started as a small community initiative. We saw a gap between traditional learning and the natural
curiosity of individuals."
85 |     },
86 |     {
87 |       title: "Our Vision",
88 |       description: "A world where joyful learning is accessible to all, empowering communities to grow together."
89 |     }
90 |   ]
91 | };
92 |
93 | export const coreValuesData = {
94 |   title: "Core Values",
95 |   values: [
96 |     {
97 |       title: "Joyful Learning",
98 |       description: "Education should be a delightful journey, not a chore.",
99 |       icon: "smiley"
100 |     },
101 |     {
102 |       title: "Community First",
103 |       description: "Empowering local voices and collective growth.",
104 |       icon: "community"
105 |     },
106 |     {
107 |       title: "Inquisitive Minds",
108 |       description: "Fostering curiosity and critical thinking in every environment.",
109 |       icon: "brain"
110 |     },
111 |     {
112 |       title: "Inclusive Access",
113 |       description: "Breaking down barriers to ensure education is for everyone.",
114 |       icon: "globe"
115 |     }
116 |   ]
117 | };
118 |
119 | export const impactStatsData = {
120 |   title: "Our Impact In Numbers",
121 |   subtitle: "Every action counts. Together with volunteers, donors, and families, we are creating measurable
ripples of educational impact.",
122 |   stats: [
123 |     { value: "5,000+", label: "Students Reached", description: "Sparking curiosity through interactive workshops."
},
124 |     { value: "50+", label: "Active Hubs", description: "Connecting retired educators with local rural learners." },
125 |     { value: "1,200+", label: "Laptops Donated", description: "Providing access to digital learning tools for
youth." },
126 |     { value: "10,000+", label: "Mentorship Hours", description: "Fostering intergenerational bonds and wisdom
transfer." }
127 |   ]

```



```
128 | };
129 |
130 | export const projectsData: Project[] = [
131 | {
132 |   id: "p1",
133 |   slug: "curiosity-labs",
134 |   title: "Curiosity Labs",
135 |   category: "STEM",
136 |   description: "Interactive workshops designed to spark interest in science and technology among primary school students through hands-on experiments.",
137 |   longDescription: "Curiosity Labs is our dedicated hands-on science and technology program. We set up mobile labs in community schools, guiding children through experiments in chemistry, physics, and programming, proving that science is a playground of questions rather than a list of facts.",
138 |   image: "https://images.unsplash.com/photo-1530210120071-aa792f6b7d6b?q=80&w=1000&auto=format&fit=crop",
139 |   badge: "STEM",
140 |   status: "active",
141 |   impactMetric: "Impact: 5,000+ Students",
142 |   pattern: "circuit",
143 |   featured: false,
144 |   goals: [
145 |     "Reach 10 new rural schools by late 2026.",
146 |     "Distribute 1,000 take-home science kits.",
147 |     "Conduct weekly teacher training webinars."
148 |   ],
149 |   timeline: "Ongoing"
150 | },
151 | {
152 |   id: "p2",
153 |   slug: "green-roots",
154 |   title: "Green Roots",
155 |   category: "Environment",
156 |   description: "A community-driven agricultural education program teaching sustainable farming practices and environmental stewardship to youth.",
157 |   longDescription: "Green Roots bridges classrooms and ecology. Students learn compost chemistry, soil biology, seed preservation, and native reforestation. By cultivating school gardens, children understand the food cycle and build long-term environmental stewardship.",
158 |   image: "https://images.unsplash.com/photo-1466692476868-aeefd1fb1e735?q=80&w=1000&auto=format&fit=crop",
159 |   badge: "Environment",
160 |   status: "active",
161 |   impactMetric: "Impact: 20 Communities",
162 |   pattern: "leaf",
163 |   featured: false,
164 |   goals: [
165 |     "Build 5 new organic school gardens this year.",
166 |     "Conduct native bird nesting workshops.",
167 |     "Maintain a community seed exchange vault."
168 |   ],
169 |   timeline: "Ongoing"
170 | },
171 | {
172 |   id: "p3",
173 |   slug: "code-bloom",
174 |   title: "Code Bloom",
175 |   category: "Digital Literacy",
176 |   description: "Providing access to technology and coding education for underprivileged teenagers, bridging the digital divide one line of code at a time.",
177 |   longDescription: "Code Bloom empowers teenagers in under-resourced areas with digital skills. We collect, refurbish, and distribute laptops, while hosting free programming Bootcamps in web development, python, and computational thinking.",
178 |   image: "https://images.unsplash.com/photo-1517694712202-14dd9538aa97?q=80&w=1000&auto=format&fit=crop",
179 |   badge: "Digital Literacy",
180 |   status: "active",
181 |   impactMetric: "Impact: 1,200 Laptops Donated",
182 |   pattern: "circuit",
183 |   featured: false,
184 |   goals: [
185 |     "Deliver 500 more laptops to community centers.",
186 |     "Mentor 100 students through industry-certified paths.",
187 |     "Host our annual hackathon for community issues."
188 |   ],
```

```

189 | timeline: "Ongoing"
190 | },
191 | {
192 | id: "p4",
193 | slug: "canvas-of-hope",
194 | title: "Canvas of Hope",
195 | category: "Arts",
196 | description: "Art therapy and creative expression workshops aimed at fostering emotional resilience and mental
well-being in vulnerable populations.",
197 | longDescription: "Canvas of Hope creates a safe harbor for emotional expression. Guided by art therapists and
volunteers, students express trauma and hope through clay, painting, music, and collaborative murals in shared
neighborhood spaces.",
198 | image: "https://images.unsplash.com/photo-1460661419201-fd4cecdf8a8b?q=80&w=1000&auto=format&fit=crop",
199 | badge: "Arts",
200 | status: "active",
201 | impactMetric: "Impact: 300+ Workshops",
202 | pattern: "wave",
203 | featured: false,
204 | goals: [
205 | "Publish an anthology of student paintings.",
206 | "Launch a mural collective across three towns.",
207 | "Introduce ceramic molding facilities to labs."
208 | ],
209 | timeline: "Ongoing"
210 | },
211 | {
212 | id: "p5",
213 | slug: "the-wisdom-collective",
214 | title: "The Wisdom Collective",
215 | category: "Flagship Program",
216 | description: "Our comprehensive mentorship program connecting retired educators with young learners in rural
areas, fostering intergenerational knowledge transfer and community bonding.",
217 | longDescription: "The Wisdom Collective is our flagship initiative. We coordinate local hubs where senior
educators teach, read with, and guide young learners. This program keeps elder knowledge alive, provides vital
tutoring to rural areas, and builds strong community bonds.",
218 | image: "https://images.unsplash.com/photo-1516321318423-f06f85e504b3?q=80&w=1000&auto=format&fit=crop",
219 | badge: "Flagship Program",
220 | status: "active",
221 | impactMetric: "50 Active Hubs • 10,000+ Mentorship Hours",
222 | pattern: "wave",
223 | featured: true,
224 | goals: [
225 | "Grow to 80 active community hubs by late 2026.",
226 | "Provide scholarship support for outstanding student scholars.",
227 | "Conduct intergenerational oral history storytelling cycles."
228 | ],
229 | timeline: "Ongoing"
230 | }
231 | ];
232 |
233 | export const blogData: BlogPost[] = [
234 | {
235 | id: "b1",
236 | slug: "sparking-universal-curiosity",
237 | title: "Sparking Universal Curiosity in the Classroom",
238 | category: "Education",
239 | excerpt: "Discover how our new curriculum initiatives are transforming traditional learning environments into
spaces of active exploration and joyful...",
240 | content: "True education is not about filling a bucket; it is about lighting a fire. Traditional classroom
settings often rely on passive listening and rote memorization, which can dim a child's natural curiosity. At Dua,
we've developed student-led project modules. Instead of listening to a lecture about plant cell biology, students
germinate seeds in custom transparent viewports, document daily mitosis visually, and teach their peers. By changing
kids from receivers to active explorers, we notice engagement scores surge, and a lifetime interest in learning is
sparked.",
241 | image: "https://images.unsplash.com/photo-1509062522246-3755977927d7?q=80&w=1000&auto=format&fit=crop",
242 | date: "Oct 15, 2024",
243 | readTime: "4 min read",
244 | readingTime: "4 min read",
245 | author: {
246 | name: "Arthur Glass",

```

```

247 | avatar: "https://images.unsplash.com/photo-1500648767791-00dcc994a43e?q=80&w=250&auto=format&fit=crop",
248 | role: "Education Coordinator"
249 | },
250 | tags: ["Curiosity", "Active Learning", "Classroom Reform"]
251 | },
252 | {
253 | id: "b2",
254 | slug: "building-stronger-communities",
255 | title: "Building Stronger Communities Through Shared Learning",
256 | category: "Community",
257 | excerpt: "A look into our recent community workshops and how collaborative educational experiences are
fostering stronger neighborhood bonds and...",
258 | content: "When neighborhoods learn together, they grow together. Over the past six months, Dua Charitable Trust
has organized over forty weekend learning festivals. These range from basic solar grid wiring to community oral
history compilation. When a grandparent and a teenager sit side-by-side soldering a solar controller or editing
audio, barriers break. Learning becomes a shared experience, building mutual respect and deep local bonds that
strengthen the social fabric of the entire area.",
259 | image: "https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=1000&auto=format&fit=crop",
260 | date: "Oct 02, 2024",
261 | readTime: "5 min read",
262 | readingTime: "5 min read",
263 | author: {
264 | name: "Marcus Vance",
265 | avatar: "https://images.unsplash.com/photo-1472099645785-5658abf4ff4e?q=80&w=250&auto=format&fit=crop",
266 | role: "Outreach Lead"
267 | },
268 | tags: ["Mentorship", "Community Building", "Oral History"]
269 | },
270 | {
271 | id: "b3",
272 | slug: "measuring-tactile-learning-impact",
273 | title: "Measuring the Impact of Tactile Learning",
274 | category: "Impact",
275 | excerpt: "We share our latest findings on how hands-on, tactile educational methods significantly improve
retention and engagement among young learners.",
276 | content: "Why do we remember the touch of soil, the smell of wood shavings, or the weight of a clay brick far
longer than a diagram on a digital board? Our latest cognitive assessments track student retention across tactile
versus digital learning styles. The results are clear: students engaging in manual prototyping show a 40% higher
retention of core scientific concepts six weeks later. Tactile learning engages motor control and spatial reasoning,
cementing academic lessons directly into memory.",
277 | image: "https://images.unsplash.com/photo-1457369804613-52c61a468e7d?q=80&w=1000&auto=format&fit=crop",
278 | date: "Sep 28, 2024",
279 | readTime: "6 min read",
280 | readingTime: "6 min read",
281 | author: {
282 | name: "Sonia Patel",
283 | avatar: "https://images.unsplash.com/photo-1438761681033-6461ffad8d80?q=80&w=250&auto=format&fit=crop",
284 | role: "Lead Researcher"
285 | },
286 | tags: ["Cognition", "Tactile learning", "Research Findings"]
287 | }
288 | ];
289 |
290 | export const teamMembers: TeamMember[] = [
291 | {
292 | name: "Sonia Patel",
293 | role: "Director of Education",
294 | bio: "Sonia spent ten years teaching in classrooms before joining Dua to pioneer hands-on, interdisciplinary
curriculum styles.",
295 | image: "https://images.unsplash.com/photo-1438761681033-6461ffad8d80?q=80&w=300&auto=format&fit=crop"
296 | },
297 | {
298 | name: "Marcus Vance",
299 | role: "Community Outreach Lead",
300 | bio: "Marcus organizes our community learning festivals, linking regional centers and building volunteer
networks.",
301 | image: "https://images.unsplash.com/photo-1472099645785-5658abf4ff4e?q=80&w=300&auto=format&fit=crop"
302 | }
303 | ];
304 |

```

```
305 | export const FAQData: FAQItem[] = [
306 | {
307 |   question: "Where do my donations go?",
308 |   answer: "Exactly 85% of every dollar goes directly into field operations, including workshop materials,
309 |   computers, art supplies, and community hub setups. The remaining 15% covers administrative and regulatory fees."
310 | },
311 | {
312 |   question: "How can I volunteer with Dua?",
313 |   answer: "We have teaching, mentoring, and administrative volunteer opportunities. Just register on our Contact
314 |   page or visit any local community hub."
315 | },
316 | {
317 |   question: "How do community hubs operate?",
318 |   answer: "Our hubs are local school or neighborhood spaces where retired educators and volunteers hold
319 |   after-school mentoring, reading labs, and arts workshops twice a week."
320 | },
321 | ];
322 |
323 | export const testimonialsData: Testimonial[] = [
324 | {
325 |   name: "Clara Henderson",
326 |   role: "Parent of Student",
327 |   avatar: "https://images.unsplash.com/photo-1444065381814-865dc9da92c0?q=80&w=200&auto=format&fit=crop",
328 |   quote: "Dua's Curiosity Labs changed my daughter's view of school. She went from dreading science to wanting to
329 |   build circuits at home."
330 | },
331 | {
332 |   name: "Principal Arthur Glass",
333 |   role: "Oakridge Elementary",
334 |   avatar: "https://images.unsplash.com/photo-1500648767791-00dcc994a43e?q=80&w=200&auto=format&fit=crop",
335 |   quote: "The Wisdom Collective tutoring program has dramatically boosted our reading comprehension scores and
336 |   forged real intergenerational friendships."
337 | },
338 | ];
339 |
340 | export const ctaData = {
341 |   title: "Ready to Bloom with Us?",
342 |   description: "Whether you want to get your hands dirty as a volunteer, fund digital literacy kits, or transition
343 |   your classroom to hands-on methods, there is a place for you in the collective.",
344 |   primaryCtaText: "Make a Donation",
345 |   primaryCtaLink: PageRoutes.DONATE,
346 |   secondaryCtaText: "Join as Volunteer",
347 |   secondaryCtaLink: PageRoutes.CONTACT,
348 | };
349 |
```

95. src/constants/navigation.ts

```
1 | import { NavItem, PageRoutes } from "@types";
2 | import { siteName } from "../site";
3 |
4 | export const navItems: NavItem[] = [
5 |   { label: "Home", href: PageRoutes.HOME },
6 |   { label: "About", href: PageRoutes.ABOUT_US },
7 |   { label: "Projects", href: PageRoutes.OUR_PROJECTS },
8 |   { label: "Blog", href: PageRoutes.BLOG },
9 | ];
10 |
11 | export const siteConfig = {
12 |   name: siteName,
13 |   donateLink: PageRoutes.DONATE,
14 |   contactLink: PageRoutes.CONTACT,
15 | };
16 |
```

96. src/constants/seedsOfChange.ts

```
1 | export interface SeedItem {
2 |   id: string;
3 |   title: string;
4 |   description: string;
5 |   href: string;
6 |   imageSrc: string;
7 |   imageAlt: string;
8 |   wash: "mint" | "sage" | "beige" | "cream";
9 | }
10 |
11 | export const seedsIntro = {
12 |   title: "Seeds of Change in Action",
13 |   description: "From mobile libraries to pop-up science fairs, our projects are designed to meet communities where they are, sparking a lifelong love for discovery.",
14 |   buttonLabel: "Explore All Projects",
15 |   buttonHref: "/our-projects",
16 | };
17 |
18 | export const seedsItems: SeedItem[] = [
19 |   {
20 |     id: "seeds-1",
21 |     title: "Digital Literacy for All",
22 |     description: "Bridging the technological divide by providing digital tools and training to students in underserved urban centers.",
23 |     href: "/our-projects/code-bloom",
24 |     imageSrc: "https://images.unsplash.com/photo-1544367567-0f2fcb009e0b?q=80&w=800&auto=format&fit=crop",
25 |     imageAlt: "Child in classroom using a digital tablet and smiling",
26 |     wash: "sage",
27 |   },
28 |   {
29 |     id: "seeds-2",
30 |     title: "STEAM Workshops in Rural Peru",
31 |     description: "Empowering students through hands-on science and technology projects that solve local community challenges.",
32 |     href: "/our-projects/curiosity-labs",
33 |     imageSrc: "https://images.unsplash.com/photo-1577896851231-70ef18881754?q=80&w=800&auto=format&fit=crop",
34 |     imageAlt: "Student in rural Peru Andes holding and assembling a wooden science project",
35 |     wash: "mint",
36 |   },
37 |   {
38 |     id: "seeds-3",
39 |     title: "The Mobile Library Initiative",
40 |     description: "Bringing curated book collections and reading workshops to remote areas where access to libraries is limited.",
41 |     href: "/our-projects/the-wisdom-collective",
42 |     imageSrc: "https://images.unsplash.com/photo-1516321318423-f06f85e504b3?q=80&w=800&auto=format&fit=crop",
43 |     imageAlt: "Mobile library yellow trailer with books and students reading outside",
44 |     wash: "beige",
45 |   },
46 |   {
47 |     id: "seeds-4",
48 |     title: "Art & Gardening for Empowerment",
49 |     description: "Using creative expression as a tool for building confidence and community identity among young learners.",
50 |     href: "/our-projects/canvas-of-hope",
51 |     imageSrc: "https://images.unsplash.com/photo-1466692476868-aef1dfb1e735?q=80&w=800&auto=format&fit=crop",
52 |     imageAlt: "Group of children planting and watering green saplings in a community garden",
53 |     wash: "mint",
54 |   },
55 | ];
56 |
```

97. src/constants/site.ts

```
1 | export const siteName = "Dua Charitable Trust";
2 | export const siteShortName = "Dua";
3 | export const siteTagline = "Nurturing Joyful Wisdom";
4 | export const siteUrl = process.env.NEXT_PUBLIC_SITE_URL ?? "https://duacharitabletrust.org";
5 | export const siteDescription = "An educational NGO dedicated to transforming community learning into an
6 | inspiring, inclusive, and deeply joyful adventure.";
```

98. src/constants/storyData.ts

```

1 | export interface StoryStep {
2 |   id: string;
3 |   badge: string;
4 |   title: string;
5 |   subtitle: string;
6 |   description: string;
7 |   imageSrc: string;
8 |   imageAlt: string;
9 |   buttonText: string;
10 |  buttonLink: string;
11 |  bgColor: string; // The soft background color for the storytelling slide
12 |  accentColor: string; // The primary theme color for progress bars & highlights
13 |  duration: number; // Animation duration multiplier
14 | }
15 |
16 | export const STORY_STEPS: StoryStep[] = [
17 | {
18 |   id: "children",
19 |   badge: "Child Support",
20 |   title: "Helping Children",
21 |   subtitle: "Nurturing the Seed of Curiosity",
22 |   description: "Empowering young minds with mentorship, protective shelter, and educational pathways to break the
cycle of poverty and nurture natural talent.",
23 |   imageSrc: "https://images.unsplash.com/photo-1488521787991-ed7bbaae773c?q=80&w=1200&auto=format&fit=crop",
24 |   imageAlt: "Children smiling and learning together in a community environment",
25 |   buttonText: "Support Childhood Projects",
26 |   buttonLink: "/our-projects",
27 |   bgColor: "#F9F8F3", // Clean soft cream
28 |   accentColor: "#D4A847", // Gold
29 |   duration: 1,
30 | },
31 | {
32 |   id: "healthcare",
33 |   badge: "Health & Well-being",
34 |   title: "Essential Healthcare",
35 |   subtitle: "Closer Clinics, Healthier Lives",
36 |   description: "Bringing primary medical clinics, hygiene awareness, and mental well-being circles directly to
isolated rural neighborhoods and school hubs.",
37 |   imageSrc: "https://images.unsplash.com/photo-1576091160550-2173dba999ef?q=80&w=1200&auto=format&fit=crop",
38 |   imageAlt: "Healthcare workers helping children with medical checkups",
39 |   buttonText: "Our Healthcare Hubs",
40 |   buttonLink: "/our-projects",
41 |   bgColor: "#F5F8F6", // Soft mint cream tint
42 |   accentColor: "#2D5B45", // Forest Green
43 |   duration: 1,
44 | },
45 | {
46 |   id: "education",
47 |   badge: "Interactive Learning",
48 |   title: "Equitable Education",
49 |   subtitle: "Igniting the Joy of Knowledge",
50 |   description: "Distributing interactive science kits, mobile school libraries, and computing devices to spark
lifelong curiosity in local learning hubs.",
51 |   imageSrc: "https://images.unsplash.com/photo-1503676260728-1c00da094a0b?q=80&w=1200&auto=format&fit=crop",
52 |   imageAlt: "Group of students reading and learning with an educator in a classroom",
53 |   buttonText: "Explore Learning Labs",
54 |   buttonLink: "/our-projects",
55 |   bgColor: "#F3F7F9", // Soft blue cream tint
56 |   accentColor: "#0F2A37", // Navy
57 |   duration: 1,
58 | },
59 | {
60 |   id: "food",
61 |   badge: "Nutrition Support",
62 |   title: "Food Security",
63 |   subtitle: "Healthy Meals, Focused Minds",

```



```
64 | description: "Sponsoring warm school lunches, classroom agro-gardens, and grocery distribution centers for
65 | families undergoing transition phases.",
66 | imageSrc: "https://images.unsplash.com/photo-1542838132-92c53300491e?q=80&w=1200&auto=format&fit=crop",
67 | imageAlt: "Fresh, healthy food and vegetables being shared",
68 | buttonText: "Sponsor Nutrition Programs",
69 | buttonLink: "/our-projects",
70 | bgColor: "#FAF4F0", // Soft warm orange tint
71 | accentColor: "#BA681E", // Warm Orange
72 | duration: 1,
73 | },
74 | {
75 | id: "community",
76 | badge: "Resilience",
77 | title: "Community Growth",
78 | subtitle: "Building Roots of Coexistence",
79 | description: "Co-creating public spaces for local cooperative farming, vocational training, and green parks to
80 | build long-term local resilience.",
81 | imageSrc: "https://images.unsplash.com/photo-1509062522246-3755977927d7?q=80&w=1200&auto=format&fit=crop",
82 | imageAlt: "People collaborating on community project work",
83 | buttonText: "Our Community Initiatives",
84 | buttonLink: "/our-projects",
85 | bgColor: "#F6F6F6", // Soft neutral grey tint
86 | accentColor: "#6B7B73", // Sage grey
87 | duration: 1,
88 | },
89 | ];
```

99. src/context/StoryContext.tsx

```
1 | "use client";
2 |
3 | import React, { createContext, useContext } from "react";
4 | import { MotionValue } from "framer-motion";
5 |
6 | export interface StoryContextType {
7 |   activeStep: number;
8 |   progress: MotionValue<number>;
9 |   direction: "up" | "down";
10 |   isReducedMotion: boolean;
11 |   stepsCount: number;
12 |   scrollToStep: (index: number) => void;
13 | }
14 |
15 | export const StoryContext = createContext<StoryContextType | null>(null);
16 |
17 | export const useStory = () => {
18 |   const context = useContext(StoryContext);
19 |   if (!context) {
20 |     throw new Error("useStory must be used within a StoryProvider");
21 |   }
22 |   return context;
23 | };
24 |
25 | interface StoryProviderProps {
26 |   children: React.ReactNode;
27 |   activeStep: number;
28 |   progress: MotionValue<number>;
29 |   direction: "up" | "down";
30 |   isReducedMotion: boolean;
31 |   stepsCount: number;
32 |   scrollToStep: (index: number) => void;
33 | }
34 |
35 | export const StoryProvider: React.FC<StoryProviderProps> = ({
36 |   children,
37 |   activeStep,
38 |   progress,
39 |   direction,
40 |   isReducedMotion,
41 |   stepsCount,
42 |   scrollToStep,
43 | }) => {
44 |   return (
45 |     <StoryContext.Provider
46 |       value={{
47 |         activeStep,
48 |         progress,
49 |         direction,
50 |         isReducedMotion,
51 |         stepsCount,
52 |         scrollToStep,
53 |       }}
54 |     >
55 |     {children}
56 |   </StoryContext.Provider>
57 | );
58 | };
59 |
```

100. src/hooks/useActiveSection.ts

```
1 | "use client";
2 |
3 | import { useEffect, useState } from "react";
4 | import { MotionValue } from "framer-motion";
5 |
6 | export function useActiveSection(progress: MotionValue<number>, stepsCount: number): number {
7 |   const [activeStep, setActiveStep] = useState(0);
8 |
9 |   useEffect(() => {
10 |     const unsubscribe = progress.on("change", (val) => {
11 |       // Divide progress (0 to 1) into equal intervals based on stepsCount
12 |       const stepIndex = Math.min(
13 |         stepsCount - 1,
14 |         Math.floor(val * stepsCount)
15 |       );
16 |       // Clamp index to prevent index out of bounds
17 |       const clampedIndex = Math.max(0, stepIndex);
18 |       setActiveStep(clampedIndex);
19 |     });
20 |
21 |     return () => unsubscribe();
22 |   }, [progress, stepsCount]);
23 |
24 |   return activeStep;
25 | }
26 | export default useActiveSection;
27 |
```

101. src/hooks/useActiveStory.ts

```
1 | "use client";
2 |
3 | import { useEffect, useState } from "react";
4 | import { MotionValue } from "framer-motion";
5 |
6 | export function useActiveStory(progress: MotionValue<number>, stepsCount: number): number {
7 |   const [activeStory, setActiveStory] = useState(0);
8 |
9 |   useEffect(() => {
10 |     const unsubscribe = progress.on("change", (val) => {
11 |       // Divide progress (0 to 1) into equal intervals based on stepsCount
12 |       const stepIndex = Math.min(
13 |         stepsCount - 1,
14 |         Math.floor(val * stepsCount)
15 |       );
16 |       // Clamp index to prevent index out of bounds
17 |       const clampedIndex = Math.max(0, stepIndex);
18 |       setActiveStory(clampedIndex);
19 |     });
20 |
21 |     return () => unsubscribe();
22 |   }, [progress, stepsCount]);
23 |
24 |   return activeStory;
25 | }
26 | export default useActiveStory;
27 |
```

102. src/hooks/useFocusTrap.ts

```

1 | "use client";
2 |
3 | import { useEffect, useRef, RefObject } from "react";
4 |
5 | export function useFocusTrap<T extends HTMLElement>(active: boolean): RefObject<T | null> {
6 |   const containerRef = useRef<T | null>(null);
7 |   const previouslyFocusedElementRef = useRef<HTMLElement | null>(null);
8 |
9 |   useEffect(() => {
10 |     if (typeof document === "undefined") return;
11 |
12 |     if (active) {
13 |       // Store the active element to restore it on close
14 |       previouslyFocusedElementRef.current = document.activeElement as HTMLElement;
15 |
16 |       const container = containerRef.current;
17 |       if (!container) return;
18 |
19 |       const focusableSelector =
20 |         'a[href], area[href], input:not([disabled]), select:not([disabled]), textarea:not([disabled]),
button:not([disabled]), iframe, object, embed, [tabindex="0"], [contenteditable]';
21 |
22 |       const getFocusableElements = (): HTMLElement[] => {
23 |         return Array.from(container.querySelectorAll<HTMLElement>(focusableSelector)).filter(
24 |           (el) => el.tabIndex !== -1
25 |         );
26 |       };
27 |
28 |       // Set focus to the first focusable element inside the modal
29 |       const focusableElements = getFocusableElements();
30 |       if (focusableElements.length > 0) {
31 |         focusableElements[0].focus();
32 |       }
33 |
34 |       const handleKeyDown = (e: KeyboardEvent): void => {
35 |         if (e.key !== "Tab") return;
36 |
37 |         const currentFocusables = getFocusableElements();
38 |         if (currentFocusables.length === 0) {
39 |           e.preventDefault();
40 |           return;
41 |         }
42 |
43 |         const firstEl = currentFocusables[0];
44 |         const lastEl = currentFocusables[currentFocusables.length - 1];
45 |
46 |         if (e.shiftKey) {
47 |           // Backward tab
48 |           if (document.activeElement === firstEl) {
49 |             lastEl.focus();
50 |             e.preventDefault();
51 |           }
52 |         } else {
53 |           // Forward tab
54 |           if (document.activeElement === lastEl) {
55 |             firstEl.focus();
56 |             e.preventDefault();
57 |           }
58 |         }
59 |       };
60 |
61 |       document.addEventListener("keydown", handleKeyDown);
62 |
63 |       return () => {
64 |         document.removeEventListener("keydown", handleKeyDown);
65 |         if (previouslyFocusedElementRef.current) {
66 |           previouslyFocusedElementRef.current.focus();

```

```
67 | }  
68 | };  
69 | }  
70 | }, [active]);  
71 |  
72 | return containerRef;  
73 | }  
74 |  
75 | export default useFocusTrap;  
76 |
```

103. src/hooks/useGSAP.ts

```
1 | import { DependencyList } from "react";
2 | import gsap from "gsap";
3 | import ScrollTrigger from "gsap/ScrollTrigger";
4 | import { useIsomorphicLayoutEffect } from "../useIsomorphicLayoutEffect";
5 |
6 | export function useGSAP(
7 |   callback: () => void | (() => void),
8 |   dependencies: DependencyList = []
9 | ): void {
10 |   useIsomorphicLayoutEffect(() => {
11 |     // Register ScrollTrigger client-side safely
12 |     gsap.registerPlugin(ScrollTrigger);
13 |
14 |     // Context scoping guarantees proper animation cleanup on unmount
15 |     const ctx = gsap.context(callback);
16 |
17 |     return () => {
18 |       ctx.revert();
19 |     };
20 |   }, dependencies);
21 | }
22 |
23 | export default useGSAP;
24 |
```

104. src/hooks/useIntersectionObserver.ts

```
1 | "use client";
2 |
3 | import { useState, useEffect, useRef, RefObject } from "react";
4 |
5 | export function useIntersectionObserver<T extends HTMLElement>(  
6 | options?: IntersectionObserverInit  
7 | ): [RefObject<T | null>, boolean] {  
8 |   const elementRef = useRef<T | null>(null);  
9 |   const [isIntersecting, setIsIntersecting] = useState<boolean>(false);  
10 |  
11 |   useEffect(() => {  
12 |     const currentElement = elementRef.current;  
13 |     if (!currentElement) return;  
14 |  
15 |     const observer = new IntersectionObserver(([entry]) => {  
16 |       setIsIntersecting(entry.isIntersecting);  
17 |     }, options);  
18 |  
19 |     observer.observe(currentElement);  
20 |  
21 |     return () => {  
22 |       if (currentElement) {  
23 |         observer.unobserve(currentElement);  
24 |       }  
25 |     };  
26 |   }, [options]);  
27 |  
28 |   return [elementRef, isIntersecting];  
29 | }  
30 |
```


105. src/hooks/useIsomorphicLayoutEffect.ts

```
1 | import { useEffect, useLayoutEffect } from "react";
2 |
3 | export const useIsomorphicLayoutEffect =
4 |   typeof window !== "undefined" ? useLayoutEffect : useEffect;
5 |
6 | export default useIsomorphicLayoutEffect;
7 |
```

106. src/hooks/useLenis.ts

```
1 | import { useLenis as useLenisProvider } from "@components/providers/LenisProvider";
2 |
3 | export function useLenis() {
4 |   return useLenisProvider();
5 | }
6 | export default useLenis;
7 |
```

107. src/hooks/useReducedMotion.ts

```
1 | "use client";
2 |
3 | import { useEffect, useState } from "react";
4 |
5 | export function useReducedMotion(): boolean {
6 |   const [prefersReducedMotion, setPrefersReducedMotion] = useState(false);
7 |
8 |   useEffect(() => {
9 |     if (typeof window === "undefined") return;
10 |
11 |     const mediaQuery = window.matchMedia("(prefers-reduced-motion: reduce)");
12 |
13 |     // Defer state update to next animation frame to prevent hydration mismatch
14 |     const frameId = requestAnimationFrame(() => {
15 |       setPrefersReducedMotion(mediaQuery.matches);
16 |     });
17 |
18 |     const listener = (event: MediaQueryListEvent) => {
19 |       setPrefersReducedMotion(event.matches);
20 |     };
21 |
22 |     mediaQuery.addEventListener("change", listener);
23 |     return () => {
24 |       cancelAnimationFrame(frameId);
25 |       mediaQuery.removeEventListener("change", listener);
26 |     };
27 |   }, []);
28 |
29 |   return prefersReducedMotion;
30 | }
31 | export default useReducedMotion;
32 |
```

108. src/hooks/useScrollDirection.ts

```
1 | "use client";
2 |
3 | import { useEffect, useState, useRef } from "react";
4 |
5 | export function useScrollDirection() {
6 |   const [direction, setDirection] = useState<"up" | "down">("down");
7 |   const lastScrollY = useRef(0);
8 |
9 |   useEffect(() => {
10 |     if (typeof window === "undefined") return;
11 |
12 |     lastScrollY.current = window.pageYOffset;
13 |
14 |     const handleScroll = () => {
15 |       const scrollY = window.pageYOffset;
16 |       // Define a threshold (e.g. 5px) to ignore tiny movements
17 |       const threshold = 5;
18 |       const diff = Math.abs(scrollY - lastScrollY.current);
19 |
20 |       if (diff > threshold) {
21 |         const currentDirection = scrollY > lastScrollY.current ? "down" : "up";
22 |         setDirection(currentDirection);
23 |         lastScrollY.current = scrollY > 0 ? scrollY : 0;
24 |       }
25 |     };
26 |
27 |     window.addEventListener("scroll", handleScroll, { passive: true });
28 |     return () => window.removeEventListener("scroll", handleScroll);
29 |   }, []);
30 |
31 |   return direction;
32 | }
33 | export default useScrollDirection;
34 |
```

109. src/hooks/useScrollLock.ts

```
1 | "use client";
2 |
3 | import { useEffect, useRef } from "react";
4 |
5 | export function useScrollLock(lock: boolean): void {
6 |   const originalStyleRef = useRef<{
7 |     overflow: string;
8 |     paddingRight: string;
9 |   }>({ overflow: "", paddingRight: "" });
10 |
11 |   useEffect(() => {
12 |     if (typeof document === "undefined") return;
13 |
14 |     const body = document.body;
15 |
16 |     if (lock) {
17 |       // Calculate scrollbar width to avoid layout shifting
18 |       const scrollbarWidth = window.innerWidth - document.documentElement.clientWidth;
19 |
20 |       // Save original styles
21 |       originalStyleRef.current = {
22 |         overflow: body.style.overflow,
23 |         paddingRight: body.style.paddingRight,
24 |       };
25 |
26 |       // Set styles
27 |       body.style.overflow = "hidden";
28 |       if (scrollbarWidth > 0) {
29 |         body.style.paddingRight = `${scrollbarWidth}px`;
30 |       }
31 |     } else {
32 |       // Restore styles
33 |       body.style.overflow = originalStyleRef.current.overflow;
34 |       body.style.paddingRight = originalStyleRef.current.paddingRight;
35 |     }
36 |
37 |     return () => {
38 |       body.style.overflow = originalStyleRef.current.overflow;
39 |       body.style.paddingRight = originalStyleRef.current.paddingRight;
40 |     };
41 |   }, [lock]);
42 | }
43 |
44 | export default useScrollLock;
45 |
```

110. src/hooks/useScrollPosition.ts

```
1 | "use client";
2 |
3 | import { useState, useEffect } from "react";
4 |
5 | export function useScrollPosition(): number {
6 |   const [scrollPosition, setScrollPosition] = useState<number>(0);
7 |
8 |   useEffect(() => {
9 |     if (typeof window === "undefined") return;
10 |
11 |     const handleScroll = (): void => {
12 |       setScrollPosition(window.scrollY);
13 |     };
14 |
15 |     window.addEventListener("scroll", handleScroll, { passive: true });
16 |     handleScroll();
17 |
18 |     return () => {
19 |       window.removeEventListener("scroll", handleScroll);
20 |     };
21 |   }, []);
22 |
23 |   return scrollPosition;
24 | }
25 |
```

111. src/hooks/useScrollProgress.ts

```
1 | "use client";
2 |
3 | import { RefObject } from "react";
4 | import { useScroll, MotionValue } from "framer-motion";
5 |
6 | export function useScrollProgress(ref: RefObject<HTMLElement | null>): MotionValue<number> {
7 |   const { scrollYProgress } = useScroll({
8 |     target: ref as RefObject<HTMLElement>,
9 |     offset: ["start start", "end end"],
10 |   });
11 |   return scrollYProgress;
12 | }
13 | export default useScrollProgress;
14 |
```

112. src/hooks/useWindowSize.ts

```
1 | "use client";
2 |
3 | import { useState, useEffect } from "react";
4 |
5 | export interface WindowSize {
6 |   width: number | undefined;
7 |   height: number | undefined;
8 | }
9 |
10 | export function useWindowSize(): WindowSize {
11 |   const [windowSize, setWindowSize] = useState<WindowSize>({
12 |     width: undefined,
13 |     height: undefined,
14 |   });
15 |
16 |   useEffect(() => {
17 |     if (typeof window === "undefined") return;
18 |
19 |     const handleResize = (): void => {
20 |       setWindowSize({
21 |         width: window.innerWidth,
22 |         height: window.innerHeight,
23 |       });
24 |     };
25 |
26 |     window.addEventListener("resize", handleResize);
27 |     handleResize();
28 |
29 |     return () => {
30 |       window.removeEventListener("resize", handleResize);
31 |     };
32 |   }, []);
33 |
34 |   return windowSize;
35 | }
36 |
```


113. src/layouts/Footer.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useEffect } from "react";
4 | import Link from "next/link";
5 | import { Container } from "@components/ui/Container";
6 | import { PageRoutes } from "@types";
7 | import { siteConfig } from "@constants/data";
8 | import { SocialIcons } from "@components/ui/SocialIcons";
9 |
10 | export const Footer: React.FC = () => {
11 |   const [mounted, setMounted] = useState(false);
12 |
13 |   useEffect(() => {
14 |     const frameId = requestAnimationFrame(() => setMounted(true));
15 |     return () => cancelAnimationFrame(frameId);
16 |   }, []);
17 |
18 |   // Render skeletal content during server render to prevent hydration mismatches
19 |   if (!mounted) {
20 |     return (
21 |       <footer
22 |         className="bg-navy text-cream-static pt-16 pb-12 relative overflow-hidden border-t-4 border-pistachio"
23 |         aria-label="Site Footer"
24 |       >
25 |         <Container size="xl">
26 |           <div className="h-64" />
27 |         </Container>
28 |       </footer>
29 |     );
30 |   }
31 |
32 |   return (
33 |     <footer
34 |       className="bg-navy text-cream-static pt-20 pb-12 relative overflow-hidden border-t-4 border-pistachio"
35 |       aria-label="Site Footer"
36 |     >
37 |       {/* Ambient background glow for premium three-dimensional depth */}
38 |       <div className="absolute top-0 left-1/4 w-96 h-96 bg-pistachio/30 rounded-full blur-3xl pointer-events-none" />
39 |       <div className="absolute bottom-0 right-1/4 w-80 h-80 bg-accent/5 rounded-full blur-3xl pointer-events-none" />
40 |
41 |       {/* Subtle geometric grid line pattern overlay */}
42 |       <svg
43 |         className="absolute inset-0 w-full h-full opacity-[0.03] pointer-events-none text-white"
44 |         fill="none"
45 |         stroke="currentColor"
46 |         strokeWidth="0.8"
47 |         aria-hidden="true"
48 |       >
49 |         <defs>
50 |           <pattern id="footer-grid" width="40" height="40" patternUnits="userSpaceOnUse">
51 |             <path d="M0 40h40v0" />
52 |           </pattern>
53 |         </defs>
54 |         <rect width="100%" height="100%" fill="url(#footer-grid)" />
55 |       </svg>
56 |
57 |       <Container size="xl" className="relative z-10">
58 |         <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-12 gap-10 lg:gap-16 pb-16">
59 |           {/* Column 1: Logo, description, and socials */}
60 |           <div className="lg:col-span-4 flex flex-col items-start gap-5">
61 |             <Link
62 |               href={PageRoutes.HOME}
63 |               className="flex items-center gap-2 focus:outline-none focus-visible:ring-2 focus-visible:ring-forest/40 rounded-md"
64 |               aria-label={` ${siteConfig.name} Home `}
65 |             >
66 |             {/* Sprout Circle Icon */}

```

```

67 | <svg
68 |   className="w-7 h-7 text-pistachio fill-none stroke-current"
69 |   viewBox="0 0 32 32"
70 |   strokeWidth="2.5"
71 |   aria-hidden="true"
72 | >
73 |   <circle cx="16" cy="16" r="14" />
74 |   <path d="M16 24V14 M16 16c0-3 3-5 6-5 M16 18c0-3 3-5 6-5" strokeLinecap="round" />
75 | </svg>
76 | <span className="font-heading font-bold text-lg sm:text-xl text-cream-static tracking-tight">
77 |   {siteConfig.name}
78 | </span>
79 | </Link>
80 | <p className="text-sm text-cream-static/70 leading-relaxed font-body max-w-sm">
81 |   {siteConfig.description}
82 | </p>
83 | <SocialIcons
84 |   className="mt-2 gap-4"
85 |   iconClassName="w-11 h-11 flex items-center justify-center p-0 rounded-full bg-white/[0.03] text-cream-static/90
border border-white/15 transition-all duration-300 hover:bg-pistachio hover:text-charcoal-static
hover:border-pistachio hover:scale-105"
86 | />
87 | </div>
88 |
89 | {/* Column 2: Explore */}
90 | <div className="lg:col-span-2 flex flex-col gap-5">
91 |   <h3 className="text-xs font-bold text-cream-static/40 uppercase tracking-wider font-body">
92 |     Explore
93 |   </h3>
94 |   <nav className="flex flex-col gap-3.5 text-sm font-semibold font-body" aria-label="Explore Links">
95 |     <Link href={PageRoutes.HOME} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
96 |       Home
97 |     </Link>
98 |     <Link href={PageRoutes.ABOUT_US} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
99 |       About Us
100 |     </Link>
101 |     <Link href={PageRoutes.OUR_PROJECTS} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
102 |       Our Projects
103 |     </Link>
104 |     <Link href={PageRoutes.BLOG} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
105 |       Community Blog
106 |     </Link>
107 |   </nav>
108 | </div>
109 |
110 | {/* Column 3: Get Involved */}
111 | <div className="lg:col-span-2 flex flex-col gap-5">
112 |   <h3 className="text-xs font-bold text-cream-static/40 uppercase tracking-wider font-body">
113 |     Get Involved
114 |   </h3>
115 |   <nav className="flex flex-col gap-3.5 text-sm font-semibold font-body" aria-label="Get Involved Links">
116 |     <Link href={PageRoutes.CONTACT} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
117 |       Volunteer
118 |     </Link>
119 |     <Link href={PageRoutes.DONATE} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
120 |       Donate Now
121 |     </Link>
122 |     <Link href={PageRoutes.CONTACT} className="text-cream-static/75 hover:text-pistachio transition-colors
duration-200">
123 |       Partner with Us
124 |     </Link>
125 |   </nav>
126 | </div>
127 |

```

```

128 |  { /* Column 4: Contact Info */}
129 |  <div className="lg:col-span-4 flex flex-col gap-5">
130 |  <h3 className="text-xs font-bold text-cream-static/40 uppercase tracking-wider font-body">
131 |  Contact Us
132 |  </h3>
133 |  <div className="flex flex-col gap-4 text-sm font-body text-cream-static/70">
134 |  <p className="leading-relaxed">{siteConfig.address}</p>
135 |  <div className="flex flex-col gap-1.5 font-semibold">
136 |  <a
137 |  href={`mailto:${siteConfig.email}`}
138 |  className="text-cream-static/80 hover:text-pistachio transition-colors duration-200"
139 |  >
140 |  {siteConfig.email}
141 |  </a>
142 |  <a
143 |  href={`tel:${siteConfig.phone}`}
144 |  className="text-cream-static/80 hover:text-pistachio transition-colors duration-200"
145 |  >
146 |  {siteConfig.phone}
147 |  </a>
148 |  </div>
149 |  </div>
150 |  </div>
151 |  </div>
152 |
153 |  { /* Footer Bottom copyright and legal */}
154 |  <div className="pt-8 border-t border-white/10 text-xs text-cream-static/40 flex flex-col sm:flex-row
justify-between items-center gap-4">
155 |  <p>© {new Date().getFullYear()} {siteConfig.name}. Nurturing Joyful Wisdom.</p>
156 |  <div className="flex gap-6 font-semibold" aria-label="Privacy & Terms">
157 |  <Link href="#" className="hover:text-cream-static transition-colors duration-200">
158 |  Privacy Policy
159 |  </Link>
160 |  <Link href="#" className="hover:text-cream-static transition-colors duration-200">
161 |  Terms of Service
162 |  </Link>
163 |  </div>
164 |  </div>
165 |  </Container>
166 |  </Footer>
167 |  );
168 |  };
169 |
170 |  export default Footer;
171 |

```

114. src/layouts/MainLayout.tsx

```
1 | import React from "react";
2 | import { Navbar } from "@components/sections/Navbar";
3 | import { Footer } from "../Footer";
4 |
5 | interface MainLayoutProps {
6 |   children: React.ReactNode;
7 | }
8 |
9 | export const MainLayout: React.FC<MainLayoutProps> = ({ children }) => {
10 |   return (
11 |     <div className="flex flex-col min-h-screen">
12 |       <Navbar />
13 |       <main id="main-content" className="flex-grow focus:outline-none" tabIndex={-1}>
14 |         {children}
15 |       </main>
16 |       <Footer />
17 |     </div>
18 |   );
19 | };
20 | export default MainLayout;
21 |
```

115. src/layouts/Navbar.tsx

```

1 | "use client";
2 |
3 | import React, { useState, useEffect, useRef } from "react";
4 | import Link from "next/link";
5 | import { usePathname } from "next/navigation";
6 | import { navItems, siteConfig } from "@/constants/data";
7 | import { Container } from "@components/ui/Container";
8 | import { Button } from "@components/ui/Button";
9 | import { Menu, X } from "lucide-react";
10 | import { cn } from "@utils/cn";
11 | import { PageRoutes } from "@types";
12 |
13 | export const Navbar: React.FC = () => {
14 |   const pathname = usePathname();
15 |   const [mobileMenuOpen, setMobileMenuOpen] = useState(false);
16 |   const firstFocusableRef = useRef<HTMLAnchorElement>(null);
17 |   const menuRef = useRef<HTMLDivElement>(null);
18 |
19 |   const toggleMobileMenu = (): void => {
20 |     setMobileMenuOpen(!mobileMenuOpen);
21 |   };
22 |
23 |   const closeMobileMenu = (): void => {
24 |     setMobileMenuOpen(false);
25 |   };
26 |
27 |   // Close on route change
28 |   useEffect(() => {
29 |     const frameId = requestAnimationFrame(() => {
30 |       closeMobileMenu();
31 |     });
32 |     return () => cancelAnimationFrame(frameId);
33 |   }, [pathname]);
34 |
35 |   // ESC key and Body scroll lock
36 |   useEffect(() => {
37 |     const handleKeyDown = (e: KeyboardEvent) => {
38 |       if (e.key === "Escape") {
39 |         closeMobileMenu();
40 |       }
41 |       if (e.key === "Tab" && mobileMenuOpen && menuRef.current) {
42 |         const focusables = menuRef.current.querySelectorAll<HTMLElement>(
43 |           'a[href], button:not([disabled]), input, textarea, [tabindex="0"]'
44 |         );
45 |         if (focusables.length === 0) return;
46 |         const first = focusables[0];
47 |         const last = focusables[focusables.length - 1];
48 |
49 |         if (e.shiftKey) {
50 |           if (document.activeElement === first) {
51 |             last.focus();
52 |             e.preventDefault();
53 |           }
54 |         } else {
55 |           if (document.activeElement === last) {
56 |             first.focus();
57 |             e.preventDefault();
58 |           }
59 |         }
60 |       }
61 |     };
62 |
63 |     if (mobileMenuOpen) {
64 |       document.addEventListener("keydown", handleKeyDown);
65 |       document.body.style.overflow = "hidden";
66 |       setTimeout(() => {
67 |         firstFocusableRef.current?.focus();

```

```

68 | }, 50);
69 | } else {
70 | document.body.style.overflow = "";
71 | }
72 |
73 | return () => {
74 | document.removeEventListener("keydown", handleKeyDown);
75 | document.body.style.overflow = "";
76 | };
77 | }, [mobileMenuOpen]);
78 |
79 | return (
80 | <header className="fixed top-0 left-0 right-0 z-50 bg-sage border-b border-charcoal/5 h-[72px] flex items-center
shadow-xs">
81 | <Container>
82 | <div className="flex items-center justify-between">
83 | <Link
84 | href={PageRoutes.HOME}
85 | className="flex items-center gap-2 text-forest focus:outline-none"
86 | onClick={closeMobileMenu}
87 | aria-label={` ${siteConfig.name} Home`}
88 | >
89 | { /* Sprout Circle Icon */ }
90 | <svg
91 | className="w-7 h-7 text-charcoal fill-none stroke-current"
92 | viewBox="0 0 32 32"
93 | strokeWidth="2.5"
94 | aria-hidden="true"
95 | >
96 | <circle cx="16" cy="16" r="14" />
97 | <path d="M16 24V14 M16 16c0-3 3-5 6-5 M16 18c0-3 3-5 6-5" strokeLinecap="round" />
98 | </svg>
99 | <span className="font-heading font-bold text-lg sm:text-xl tracking-tight text-charcoal">
100 | {siteConfig.name}
101 | </span>
102 | </Link>
103 |
104 | <nav className="hidden md:flex items-center gap-8" aria-label="Main Navigation">
105 | {navItems.map((item, index) => {
106 | const isActive = pathname === item.href;
107 | return (
108 | <Link
109 | key={index}
110 | href={item.href}
111 | aria-current={isActive ? "page" : undefined}
112 | className={cn(
113 | "text-sm font-semibold font-body hover:text-charcoal transition-colors relative py-1 focus:outline-none",
114 | isActive ? "text-charcoal font-extrabold" : "text-charcoal/70"
115 | )}
116 | >
117 | {item.label}
118 | {isActive && (
119 | <span className="absolute bottom-0 left-0 right-0 h-0.5 bg-charcoal rounded-full" />
120 | )}
121 | </Link>
122 | );
123 | })}
124 | </nav>
125 |
126 | <div className="hidden md:block">
127 | <Button
128 | label="Get Involved"
129 | variant="outline"
130 | size="sm"
131 | href={PageRoutes.DONATE}
132 | className="bg-transparent border border-charcoal/30 text-charcoal hover:bg-charcoal hover:text-cream
rounded-full px-6 py-2 font-bold transition-all duration-300 shadow-none"
133 | aria-label="Get Involved - Make a donation"
134 | />
135 | </div>

```

```

136 |
137 | <button
138 |   onClick={toggleMobileMenu}
139 |   className="md:hidden p-2 text-charcoal hover:text-forest focus:outline-none cursor-pointer"
140 |   aria-expanded={mobileMenuOpen}
141 |   aria-label="Toggle navigation menu"
142 | >
143 | {mobileMenuOpen ? <X size={24} /> : <Menu size={24} />}
144 | </button>
145 | </div>
146 | </Container>
147 |
148 | {mobileMenuOpen && (
149 |   <div
150 |     ref={menuRef}
151 |     className="md:hidden fixed inset-x-0 top-[72px] bottom-0 bg-sage/98 backdrop-blur-md z-40 flex flex-col p-6
animate-fade-in"
152 |     role="dialog"
153 |     aria-modal="true"
154 |     aria-label="Mobile Navigation Menu"
155 |   >
156 |     <nav className="flex flex-col gap-6 mb-8 mt-4">
157 |       {navItems.map((item, index) => {
158 |         const isActive = pathname === item.href;
159 |         return (
160 |           <Link
161 |             key={index}
162 |             ref={index === 0 ? firstFocusableRef : undefined}
163 |             href={item.href}
164 |             onClick={closeMobileMenu}
165 |             aria-current={isActive ? "page" : undefined}
166 |             className={cn(
167 |               "text-lg font-bold font-heading py-2 border-b border-charcoal/10 focus:outline-none",
168 |               isActive ? "text-charcoal" : "text-charcoal/80"
169 |             )}
170 |           >
171 |             {item.label}
172 |           </Link>
173 |         );
174 |       })}
175 |     </nav>
176 |     <div className="mt-auto">
177 |       <Button
178 |         label="Get Involved"
179 |         variant="outline"
180 |         size="lg"
181 |         href={PageRoutes.DONATE}
182 |         onClick={closeMobileMenu}
183 |         className="w-full text-center py-4 bg-transparent border border-charcoal/30 text-charcoal hover:bg-charcoal
hover:text-white transition-colors rounded-full font-bold"
184 |       />
185 |     </div>
186 |   </div>
187 | )}
188 | </header>
189 | );
190 | };
191 |
192 | export default Navbar;
193 |

```

116. src/types/index.ts

```
1 | import { ReactNode } from "react";
2 |
3 | export enum PageRoutes {
4 |   HOME = "/",
5 |   ABOUT_US = "/about-us",
6 |   OUR_PROJECTS = "/our-projects",
7 |   BLOG = "/blog",
8 |   CONTACT = "/contact",
9 |   DONATE = "/donate",
10 | }
11 |
12 | export interface NavItem {
13 |   label: string;
14 |   href: PageRoutes | string;
15 | }
16 |
17 | export interface ButtonProps {
18 |   label: string;
19 |   onClick?: () => void;
20 |   variant?: "primary" | "secondary" | "outline" | "text" | "accent";
21 |   size?: "sm" | "md" | "lg";
22 |   disabled?: boolean;
23 |   loading?: boolean;
24 |   type?: "button" | "submit" | "reset";
25 |   className?: string;
26 |   icon?: ReactNode;
27 |   iconPosition?: "left" | "right";
28 |   href?: string;
29 | }
30 |
31 | export interface BadgeProps {
32 |   label: string;
33 |   variant?: "success" | "warning" | "info" | "default" | "orange";
34 |   className?: string;
35 | }
36 |
37 | export interface ContainerProps {
38 |   children: ReactNode;
39 |   className?: string;
40 |   clean?: boolean;
41 |   size?: "default" | "wide" | "xl";
42 | }
43 |
44 | export interface SectionHeadingProps {
45 |   title: string;
46 |   subtitle?: string;
47 |   badge?: string;
48 |   centered?: boolean;
49 |   className?: string;
50 | }
51 |
52 | export type PatternVariant =
53 |   | "leaf"
54 |   | "circuit"
55 |   | "wave"
56 |   | "doodle"
57 |   | "project-grid";
58 |
59 | export interface Project {
60 |   id: string;
61 |   slug: string;
62 |   title: string;
63 |   description: string;
64 |   longDescription?: string;
65 |   image: string;
66 |   badge: string;
67 |   status: "active" | "completed" | "planned";
```



```
68 | impactMetric?: string;
69 | goals?: string[];
70 | timeline?: string;
71 | category: string;
72 | featured?: boolean;
73 | pattern?: PatternVariant;
74 | }
75 |
76 | export interface ProjectCardProps {
77 |   project: Project;
78 |   className?: string;
79 | }
80 |
81 | export interface BlogPost {
82 |   id: string;
83 |   slug: string;
84 |   title: string;
85 |   excerpt: string;
86 |   content?: string;
87 |   image: string;
88 |   date: string;
89 |   readTime: string;
90 |   readingTime?: string;
91 |   category: string;
92 |   author: {
93 |     name: string;
94 |     avatar: string;
95 |     role: string;
96 |   };
97 |   tags?: string[];
98 | }
99 |
100 | export interface BlogCardProps {
101 |   post: BlogPost;
102 |   className?: string;
103 | }
104 |
105 | export interface InputProps extends React.InputHTMLAttributes<HTMLInputElement> {
106 |   label?: string;
107 |   error?: string;
108 |   helperText?: string;
109 |   className?: string;
110 | }
111 |
112 | export interface TextAreaProps extends React.TextareaHTMLAttributes<HTMLTextAreaElement> {
113 |   label?: string;
114 |   error?: string;
115 |   helperText?: string;
116 |   className?: string;
117 | }
118 |
119 | export interface TeamMember {
120 |   name: string;
121 |   role: string;
122 |   bio: string;
123 |   image: string;
124 |   socials?: SocialLink[];
125 | }
126 |
127 | export interface SocialLink {
128 |   platform: "facebook" | "twitter" | "instagram" | "linkedin" | "youtube";
129 |   href: string;
130 | }
131 |
132 | export interface SocialIconsProps {
133 |   links?: SocialLink[];
134 |   className?: string;
135 |   iconClassName?: string;
136 | }
137 |
```

```
138 | export interface LoaderProps {
139 |   size?: "sm" | "md" | "lg";
140 |   className?: string;
141 | }
142 |
143 | export interface StatItemProps {
144 |   value: string;
145 |   label: string;
146 |   icon?: ReactNode;
147 |   description?: string;
148 | }
149 |
150 | export interface FAQItem {
151 |   question: string;
152 |   answer: string;
153 | }
154 |
155 | export interface Testimonial {
156 |   name: string;
157 |   role: string;
158 |   location?: string;
159 |   avatar: string;
160 |   quote: string;
161 | }
162 |
163 | // Section Props
164 | export interface HeroProps {
165 |   heading: string;
166 |   subheading: string;
167 |   primaryCtaText: string;
168 |   primaryCtaLink: string;
169 |   secondaryCtaText: string;
170 |   secondaryCtaLink: string;
171 |   backgroundImage?: string;
172 | }
173 |
174 | export interface MissionProps {
175 |   title: string;
176 |   description: string;
177 |   bullets: string[];
178 |   image?: string;
179 | }
180 |
181 | export interface ImpactStatsProps {
182 |   title: string;
183 |   subtitle: string;
184 |   stats: StatItemProps[];
185 | }
186 |
187 | export interface FeaturedProjectsProps {
188 |   title: string;
189 |   subtitle: string;
190 |   projects: Project[];
191 | }
192 |
193 | export interface TeamGridProps {
194 |   title: string;
195 |   subtitle: string;
196 |   members: TeamMember[];
197 | }
198 |
199 | export interface NewsletterProps {
200 |   title: string;
201 |   subtitle: string;
202 |   placeholderText?: string;
203 |   buttonText?: string;
204 | }
205 |
206 | export interface TestimonialsProps {
207 |   title: string;
```

```
208 | subtitle: string;
209 | testimonials: Testimonial[];
210 | }
211 |
212 | export interface CTAProps {
213 |   title: string;
214 |   description: string;
215 |   primaryCtaText: string;
216 |   primaryCtaLink: string;
217 |   secondaryCtaText: string;
218 |   secondaryCtaLink: string;
219 | }
220 |
221 | export interface FAQProps {
222 |   title: string;
223 |   subtitle: string;
224 |   faqs: FAQItem[];
225 | }
226 |
227 | export interface ContactFormProps {
228 |   title: string;
229 |   subtitle: string;
230 | }
231 |
```

117. src/utls/cn.ts

```
1 | import { ClassValue, clsx } from "clsx";
2 | import { twMerge } from "tailwind-merge";
3 |
4 | export function cn(...inputs: ClassValue[]): string {
5 |   return twMerge(clsx(inputs));
6 | }
7 |
```

118. src/utlis/preloadImages.ts

```
1 | /**
2 |  * Preloads a list of image URLs into the browser cache
3 |  * to prevent flickering during scroll-linked transitions.
4 |  */
5 | export function preloadImages(urls: string[]): Promise<void[]> {
6 |   if (typeof window === "undefined") return Promise.resolve([]);
7 |
8 |   const promises = urls.map((url) => {
9 |     return new Promise<void>((resolve) => {
10 |       const img = new window.Image();
11 |       img.src = url;
12 |       img.onload = () => resolve();
13 |       img.onerror = () => resolve(); // resolve anyway so we don't stall the app
14 |     });
15 |   });
16 |
17 |   return Promise.all(promises);
18 | }
19 | export default preloadImages;
20 |
```

119. src/utils/theme.ts

```
1 | export type Theme = "light" | "dark";
2 |
3 | export const THEME_STORAGE_KEY = "dua-theme";
4 |
5 | /**
6 |  * Resolves the initial theme state from localStorage or system preferences, SSR safe.
7 |  */
8 | export const getInitialTheme = (): Theme => {
9 |   if (typeof window === "undefined") return "light";
10 |
11 |   try {
12 |     const stored = window.localStorage.getItem(THEME_STORAGE_KEY);
13 |     if (stored === "light" || stored === "dark") {
14 |       return stored as Theme;
15 |     }
16 |
17 |     // Fallback to system preference
18 |     const media = window.matchMedia("(prefers-color-scheme: dark)");
19 |     return media.matches ? "dark" : "light";
20 |   } catch {
21 |     return "light";
22 |   }
23 | };
24 |
```

120. README.md

```
1 | # Cognibloom Collective Website
2 |
3 | This is a Next.js 14, Tailwind CSS v4, and TypeScript website for Cognibloom Collective, a non-profit
organization focused on forest conservation, organic farming, and eco-literacy.
4 |
5 | ## Tech Stack
6 | - Framework: Next.js 14 (App Router)
7 | - Language: TypeScript
8 | - Styling: Tailwind CSS v4
9 | - Icons: `lucide-react`
10 | - Utilities: `clsx`, `tailwind-merge`
11 |
12 | ## Getting Started
13 |
14 | First, run the development server:
15 |
16 | ```bash
17 | npm run dev
18 | ```
19 |
20 | Open [http://localhost:3000](http://localhost:3000) with your browser to see the result.
21 |
22 | ## Folder Structure
23 | - `src/app/` - Page routes and layouts.
24 | - `src/components/` - Section modules and UI elements.
25 | - `src/layouts/` - Navbar and Footer templates.
26 | - `src/constants/` - Static configurations and text contents.
27 | - `src/types/` - TypeScript interface mappings.
28 | - `src/hooks/` - Window resize, scroll tracking, and viewport observers.
29 | - `src/utils/` - Global classes and utilities.
30 |
```

121. eslint.config.mjs

```
1 | import { defineConfig, globalIgnores } from "eslint/config";
2 | import nextVitals from "eslint-config-next/core-web-vitals";
3 | import nextTs from "eslint-config-next/typescript";
4 |
5 | const eslintConfig = defineConfig([
6 |   ...nextVitals,
7 |   ...nextTs,
8 |   // Override default ignores of eslint-config-next.
9 |   globalIgnores([
10 |     // Default ignores of eslint-config-next:
11 |     ".next/**",
12 |     "out/**",
13 |     "build/**",
14 |     "next-env.d.ts",
15 |   ]),
16 | ]);
17 |
18 | export default eslintConfig;
19 |
```


122. next.config.ts

```
1 | import type { NextConfig } from "next";
2 |
3 | const nextConfig: NextConfig = {
4 |   images: {
5 |     remotePatterns: [
6 |       {
7 |         protocol: "https",
8 |         hostname: "images.unsplash.com",
9 |       },
10 |     ],
11 |   },
12 |   turbopack: {
13 |     root: process.cwd(),
14 |   },
15 | };
16 |
17 | export default nextConfig;
18 |
```

123. package.json

```
1 | {
2 |   "name": "ngo-site",
3 |   "version": "0.1.0",
4 |   "private": true,
5 |   "scripts": {
6 |     "dev": "next dev",
7 |     "build": "next build",
8 |     "start": "next start",
9 |     "lint": "eslint"
10 |   },
11 |   "dependencies": {
12 |     "clsx": "^2.1.1",
13 |     "framer-motion": "^11.18.2",
14 |     "gsap": "^3.15.0",
15 |     "lenis": "^1.3.25",
16 |     "lucide-react": "^0.468.0",
17 |     "next": "16.2.9",
18 |     "react": "19.2.4",
19 |     "react-dom": "19.2.4",
20 |     "tailwind-merge": "^3.6.0"
21 |   },
22 |   "devDependencies": {
23 |     "@tailwindcss/postcss": "^4",
24 |     "@types/node": "^20",
25 |     "@types/react": "^19",
26 |     "@types/react-dom": "^19",
27 |     "eslint": "^9",
28 |     "eslint-config-next": "16.2.9",
29 |     "tailwindcss": "^4",
30 |     "typescript": "^5"
31 |   }
32 | }
33 |
```

124. postcss.config.mjs

```
1 | const config = {  
2 |   plugins: {  
3 |     "@tailwindcss/postcss": {},  
4 |   },  
5 | };  
6 |  
7 | export default config;  
8 |
```

125. tsconfig.json

```
1 | {
2 |   "compilerOptions": {
3 |     "target": "ES2017",
4 |     "lib": ["dom", "dom.iterable", "esnext"],
5 |     "allowJs": true,
6 |     "skipLibCheck": true,
7 |     "strict": true,
8 |     "noEmit": true,
9 |     "esModuleInterop": true,
10 |    "module": "esnext",
11 |    "moduleResolution": "bundler",
12 |    "resolveJsonModule": true,
13 |    "isolatedModules": true,
14 |    "jsx": "react-jsx",
15 |    "incremental": true,
16 |    "plugins": [
17 |      {
18 |        "name": "next"
19 |      }
20 |    ],
21 |    "paths": {
22 |      "@/*": [".src/*"]
23 |    }
24 |  },
25 |   "include": [
26 |     "next-env.d.ts",
27 |     "**/*.ts",
28 |     "**/*.tsx",
29 |     ".next/types/**/*.ts",
30 |     ".next/dev/types/**/*.ts",
31 |     "**/*.mts"
32 |   ],
33 |   "exclude": ["node_modules"]
34 | }
35 |
```