PURCHASING APPROVAL

Standard Operating Procedure | Veriq Test Fixture

DOCUMENT	SOP-VERIQ-001	VERSION	1.0
DATE	17 Oct 2026	STATUS	Synthetic / Dry-run

This document is intentionally fictional and designed for safe verification testing. No live purchase processing is implemented.

1. Purpose and scope

This synthetic Standard Operating Procedure (SOP) defines a dry-run purchase approval process for Veriq testing. It applies only to the n8n sample workflow included in this pack. No purchase, notification, or audit record is actually persisted outside the workflow execution.

2. Input data

A request includes requestId, requesterEmail, vendorName, amount in Philippine pesos, isDuplicate (boolean), managerApproved (boolean), and managerId (string). For tests, the workflow receives one synthetic example purchase with amount PHP 12,500, isDuplicate=false, and managerApproved=false.

3. Mandatory procedural requirements

The requirements below are normative for this fixture. VERIQ should distinguish supported requirements from uncertain ones and cite SOP requirement IDs and matching n8n node names or IDs.

REQ-001 | Required fields: If requestId, requesterEmail, or vendorName is missing/empty, or amount is not a positive number, the request MUST be rejected before processing.

REQ-002 | Duplicate prevention: If isDuplicate=true, the request MUST be rejected and MUST NOT reach Process Purchase.

REQ-003 | High-value approval: For amount > PHP 10,000, managerApproved MUST be true AND managerId MUST be nonempty before the request reaches Process Purchase.

REQ-004 | Unapproved high-value request: A high-value request without valid manager approval MUST be held, not processed. The final status MUST be held_for_approval.

REQ-005 | Standard-value processing: For 0 < amount <= PHP 10,000 and complete, nonduplicate inputs, the request MAY be processed without requiring manager approval.

REQ-006 | Audit preparation: Every path that reaches Process Purchase MUST subsequently pass through Prepare Audit Entry before Final Status Output. The prepared audit data MUST include requestId, amount, managerApproved, and managerId. This fixture requires preparation only, not external persistence.

REQ-007 | Terminal status: Every handled request MUST reach Final Status Output with a finalStatus equal to processed, rejected, or held_for_approval.

REQ-008 | Approval identity: For high-value purchases, managerId alone is insufficient; managerApproved=true alone is also insufficient. Both must be present together before processing.

4. Verification boundaries

This SOP is intentionally limited to observable workflow structure and item fields. Veriq should NOT claim that a boolean field is proof of authentic approval. The workflow simulates processing and audit preparation; there are no live purchase systems, notifications, or persistent audit logs.

5. Test scenarios

T1: amount=12500, managerApproved=false, managerId="" -> held_for_approval. T2: amount=12500, managerApproved=true, managerId="MGR-01" -> processed with audit fields. T3: amount=8000, managerApproved=false -> processed with audit fields. T4: isDuplicate=true -> rejected. T5: vendorName="" -> rejected.

6. Acceptance rule

A matching node name is insufficient proof. Veriq must inspect reachability and branch conditions, identify paths that bypass controls, and mark unmodeled runtime behaviors as unverified.