

VantoOS Maytapi Hub — Spoke Integration Pack

Version 1.0 · For GetWell Grow, GetWell Hub, and any future WhatsApp-sending spoke

This pack lets a spoke join the VantoOS Maytapi mesh. The hub NEVER talks to Maytapi. Spokes keep owning their own Maytapi credentials and gateway calls. The hub only arbitrates: may I send? (**dnc_check**), I sent (**send_recorded**), the user replied STOP (**inbound_stop**), and one-time history sync (**events_backfill**).

Hub endpoint: POST

`https://zsvaqt1omgofwqkpwkeh.supabase.co/functions/v1/maytapi-hub-bridge`

1. Secrets you must install on your spoke

You will receive both of these values via the same secure channel we used for SUITE_BRIDGE_SECRET. Do NOT rotate MAYTAPI_HASH_SALT — GetWell Grow already has it set, and every existing phone_hash in your maytapi_messages, maytapi_inbound_unmatched, and maytapi_gate_audit tables was computed with it. Any new spoke reuses the same salt; if you mint your own, DNC and backfill lookups miss every existing record.

Secret	Purpose	Notes
SUITE_BRIDGE_SECRET	HMAC signing key for hub↔spoke calls	Reuse existing suite bridge secret
MAYTAPI_HASH_SALT	Salt for SHA-256 phone hashing	Reuse GetWell Grow's existing salt — never regenerate

2. Signing scheme (identical to suite-bridge-hub)

Every request to the hub carries four headers:

```
x-bridge-app      <your app_key, e.g. getwell_grow>
x-bridge-timestamp <Date.now() as string, ms since epoch>
x-bridge-nonce    <random string, e.g. crypto.randomUUID()>
x-bridge-signature HMAC_SHA256(SUITE_BRIDGE_SECRET,
                                `${ts}.${nonce}.${app_key}.${JSON.stringify(body)}`)
```

Timestamp drift tolerance is ±5 minutes. Stringify the body exactly as you sign it — no reordering, no whitespace drift.

3. Actions

3.1 *dnc_check* — *pre-send gate (call before every outbound send)*

```
POST /functions/v1/maytapi-hub-bridge
{
  "action": "dnc_check",
  "body": {
    "phone": "+27821234567",
    "event_class": "birthday"    // optional, defaults to "default" (6h)
  }
}

// 200 OK — allowed
{ "ok": true, "allowed": true, "blocked_until": null,
  "cooldown_seconds": 21600, "event_class": "birthday" }

// 200 OK — blocked by cooldown
{ "ok": true, "allowed": false, "blocked_until": "2026-07-21T22:14:00Z",
  "reason": "cooldown", "last_sent_at": "...", "last_sent_by": "vanto_crm",
  "last_campaign_type": "activation", "cooldown_seconds": 21600 }

// 200 OK — blocked by DNC
{ "ok": true, "allowed": false, "blocked_until": null,
  "reason": "dnc:stop_keyword", "recorded_at": "..." }
```

Fail-closed: if the hub call errors or times out, do NOT send. Log and retry.

3.2 *send_recorded* — *post-send ledger write*

```
POST /functions/v1/maytapi-hub-bridge
{
  "action": "send_recorded",
  "body": {
    "spoke_event_id": "<your own stable id, e.g. maytapi_messages.id>",
    "phone": "+27821234567",
    "campaign_type": "birthday",          // optional
    "maytapi_message_id": "abc123",      // optional
    "status": "sent",                    // sent|delivered|read|failed
    "sent_at": "2026-07-21T16:00:00Z",   // optional, defaults to now()
    "metadata": { "template": "birthday_v3" }
  }
}

// 200 OK
{ "ok": true, "recorded": true }
```

Idempotent on (spoke_app_key, spoke_event_id). Safe to retry.

3.3 *inbound_stop* — *user opted out*

```
POST /functions/v1/maytapi-hub-bridge
{
  "action": "inbound_stop",
  "body": {
    "phone": "+27821234567",
    "keyword": "STOP",                  // or UNSUBSCRIBE, CANCEL, etc.
    "message_id": "wamid.xxx",         // optional
    "received_at": "2026-07-21T16:05:00Z"
  }
}

// 200 OK
{ "ok": true, "dnc": true }
```

Call this from maytapi-inbound whenever the webhook receives a STOP-class keyword. The hub upserts DNC and every other spoke will see the block on their next dnc_check.

3.4 *events_backfill* — *one-time history sync*

```
POST /functions/v1/maytapi-hub-bridge
```

```
{
  "action": "events_backfill",
  "body": {
    "events": [
      { "spoke_event_id": "...", "phone": "+27...", "direction": "outbound",
        "campaign_type": "activation", "status": "sent",
        "sent_at": "2026-01-15T09:00:00Z" },
      ... // up to 500 per call
    ]
  }
}

// 200 OK
{ "ok": true, "received": 500, "upserted": 500 }
```

3.5 ping — connectivity check

```
POST /functions/v1/maytapi-hub-bridge
{ "action": "ping", "body": {} }
// 200 OK
{ "ok": true, "hub": "maytapi-hub-bridge", "app_key": "getwell_grow", "at": "..." }
```

4. Guardrails

- **Fail-closed:** any non-2xx or timeout on dnc_check → do not send.
- **Default cooldown:** 6h when event_class is missing/unknown. Marketing = 6h, Transactional (otp/order_confirmation/receipt) = 1h, Broadcast/promo = 24h. Tunable in the hub's Maytapi Hub admin page.
- **Rate limit:** at most 10 dnc_check/sec per spoke; batch send_recorded calls acceptable.
- **PII:** hub only stores SHA256(salt.phone) and the last 4 digits. No message bodies.
- **RLS:** all hub tables are admin-read-only via the console; writes are service-role via the edge function.

5. Acceptance tests (return results to VantoOS)

- T1.** POST ping with valid signature → 200 { ok:true, app_key:"" }
- T2.** POST ping with tampered signature → 401 { error:'bad_signature' }
- T3.** POST ping with timestamp older than 5 min → 401 { error:'timestamp_drift' }
- T4.** dnc_check for a fresh number → { allowed:true }
- T5.** send_recorded, then immediate dnc_check for same phone → { allowed:false, reason:'cooldown', blocked_until:<+6h> }
- T6.** inbound_stop for a number, then dnc_check → { allowed:false, reason:'dnc:stop_keyword' }

6. Reference spoke helper (TypeScript)

```
async function callHub(action: string, body: any) {
  const ts = Date.now().toString();
  const nonce = crypto.randomUUID();
  const app_key = "getwell_grow";
  const raw = JSON.stringify({ action, body });
  const sig = await hmacHex(SUITE_BRIDGE_SECRET, `${ts}.${nonce}.${app_key}.${raw}`);
  const res = await fetch(`${HUB_URL}/functions/v1/maytapi-hub-bridge`, {
    method: "POST",
    headers: {
      "content-type": "application/json",
      "x-bridge-app": app_key,
      "x-bridge-timestamp": ts,
      "x-bridge-nonce": nonce,
      "x-bridge-signature": sig,
    },
    body: raw,
  });
  return res.json();
}

// Pre-send gate
const gate = await callHub("dnc_check", { phone, event_class: "birthday" });
if (!gate.allowed) { logSkip(gate); return; }
await sendViaMaytapi(...);
await callHub("send_recorded", { spoke_event_id, phone, campaign_type: "birthday",
  maytapi_message_id, status: "sent" });
```

7. Shadow → Enforcing rollout

Wire dnc_check in **shadow mode** first: call the hub, log the answer, but always send. Compare 24-48h of logs to production sends. When the block rate looks sane, flip a feature flag to **enforcing**.