North-West University (NWU)
Faculty of Natural Science and Agriculture

ITRI626 – Deep learning for image classification · Practical project report

Recognising electronic components in web photographs

A duplicate-aware comparison of a scratch CNN, a fine-tuned ConvNeXt, a frozen SigLIP ViT and a frozen MobileCLIP2 hybrid

Group member	Student number
M van Niekerk	47817909
D Schoeman	45616779
M Adriaanzen	43054226
S Klopper	45757895

Lecturer: Prof. Absalom Ezugwu · Facilitator: Mr. Bernard Swanepoel

20 October 2026, revised 5 November 2026

Abstract. We classify web photographs of electronic components into 20 classes using the public Kaggle dataset Electronic Component Recognizer. After exact duplicates and 13 groups with contradictory labels are removed, 2,930 images remain; detected near-duplicates are grouped to keep each cluster within a single split, giving a stratified split (seed 42) of 2,010 training, 502 validation and 418 test images. Four models are trained on this split and scored once on the same test set: (A) a VGG-style CNN trained from scratch, (B) ConvNeXt-Tiny fine-tuned from ImageNet-22k weights, and two frozen encoders with trained linear heads: (C) SigLIP So400m and (D) MobileCLIP2-S3. Test accuracy is 0.400, 0.636, 0.823 and 0.773 (macro-F1 0.392, 0.628, 0.817, 0.770). C and D have overlapping individual 95% bootstrap intervals; paired McNemar tests reject equal accuracy for every pair. The comparison supports transfer learning: B exceeds the scratch baseline by 23.7 accuracy points; C and D exceed B by 18.7 and 13.6 points, respectively. Most remaining errors involve look-alike parts or images that do not show the labelled component. We recommend model C for accuracy, model D where a smaller research model is needed, and B for lower latency.

1 Introduction and problem motivation

Problem. Given one photograph, assign it to exactly one of 20 classes of electronic components and modules (Table 1). This is single-label, multiclass image classification of web photographs of arbitrary origin: product shots, close-ups, cluttered workbenches, renders and some diagrams.

Motivation. Recognising a part from a photograph helps to sort mixed parts bins and take inventory, to teach students to tell a diode from a resistor, and as the recognition stage of lab-assistant tools. Earlier work on electronic-component classification fine-tunes ImageNet networks [1] or designs dedicated CNNs for varied backgrounds [2]; inspection of assembled circuit boards is surveyed by Ling and Isa [3]. The task is also a good test of transfer learning. There are only about 100 training images per class, the data are noisy, and several classes look alike (resistor, diode and fuse are small axial bodies with leads; inductor coil and transformer are both windings).

Aim and scope. We compare four models, one trained from scratch and three using transfer learning (fine-tuning or frozen features), on one duplicate-aware train/validation/test split, evaluate all of them on the same held-out test set, explain their differences and recommend one. The scope is whole-image classification of the dataset's 20 classes; detecting several components in one image is out of scope.

Research question. Which way of using a neural network (training from scratch, fine-tuning ImageNet features, or a linear classifier on frozen web-scale image–text features) classifies these noisy web photographs best, and at what computational cost?

Target classes. We retain the public dataset's 20 roughly balanced classes, including confusable parts common on an electronics workbench (Table 1).

2 Dataset: source, classes, preparation and ethics

2.1 Source, licence and usage conditions

The images come from the Kaggle dataset Electronic Component Recognizer by the user mdfaisalahmed025 [4], `https://www.kaggle.com/datasets/mdfaisalahmed025/electronic-component-recognizer`, released under the MIT licence (use, copying, modification and redistribution with the copyright notice, without warranty). The author collected the images with DuckDuckGo image search, one query per class, so the labels are the search terms. The dataset card states 3,661 images, but our download contains 3,530 files; we could not determine the reason (the card may describe an earlier version), and all counts below refer to the files we received. The MIT licence covers the compilation, not the copyright of the individual web images, which stays with their owners. We therefore use the images only for this non-commercial course project, acknowledge the source, and do not commit the images to the project's Git repository. The download also ships a random train/validation/test assignment of the files; we do not use it, because it places copies of the same image on both sides (Section 2.5).

2.2 Class definitions and counts

Table 1 defines each class and gives its image count at every cleaning stage and in every split; Figure 1 shows four random training images per class.

2.3 Cleaning, label checking and corrections

The cleaning pipeline records a dataset manifest and an audit of all exclusions and duplicate groups; Table 2 summarises the counts.

1. **Decoding.** Every file was decoded and stored as an RGB JPEG (the unique files were 1,486 JPEG, 787 WebP, 402 PNG, 245 AVIF, 20 GIF and 3 MPO files; 345 transparent images were composited on white). No file was corrupt.




Figure 1: Four random training images of every class (in brackets: training images of the class). The mix of product photos, close-ups, renders, diagrams and off-topic pictures (e.g. the game console under switch, the infographic under led) is typical of the dataset.

Table 1: The 20 classes, their image counts at each cleaning stage and in each split.

		Cleaning				Split			
Class	Definition	Raw	Uniq.	Excl.	Final	Train	Val	Test	Flag.
battery holder	cradle or box holding cylindrical or coin cells	220	155	0	155	107	26	22	31
breadboard	solderless prototyping board with spring-clip holes	141	135	4	131	89	23	19	22
capacitor	two-terminal charge-storage part (electrolytic, ceramic, film)	121	117	1	116	79	20	17	16
connector	plug, socket or pin header joining cables or boards	114	110	0	110	76	18	16	11
crystal oscillator	quartz crystal or oscillator can / SMD clock package	232	152	1	151	104	26	21	50
diode	two-terminal rectifier, usually a banded axial body	151	148	3	145	99	25	21	56
fuse	protective glass, ceramic or blade cartridge	148	146	4	142	98	24	20	46
heat sink	finned metal block that dissipates heat	164	160	0	160	110	27	23	19
ic chip	packaged integrated circuit (DIP, SOIC, QFP)	166	157	0	157	109	26	22	15
inductor coil	wire wound on a core (toroid, choke, coil)	244	162	1	161	110	28	23	26
jumper wire	insulated lead with pin or socket ends	250	164	1	163	112	28	23	62
led	light-emitting diode (dome package, strip)	174	125	1	124	85	21	18	55
microcontroller board	development board with an MCU (Arduino, ESP32)	155	154	0	154	106	26	22	20
potentiometer	variable resistor with shaft or trimmer screw	161	147	0	147	101	25	21	14
power supply module	board-level AC/DC or DC/DC converter	251	156	2	154	105	27	22	23
relay	electrically operated switch (boxed coil and contacts)	167	160	4	156	107	27	22	61
resistor	fixed two-terminal resistor, colour bands or SMD	171	155	2	153	104	27	22	43
switch	manual switch (toggle, push-button, slide, DIP)	188	177	0	177	121	31	25	121
transformer	coupled windings on a laminated core	147	129	1	128	88	22	18	64
transistor	three-terminal semiconductor (TO-92, TO-220)	165	148	2	146	100	25	21	61
Total		3,530	2,957	27	2,930	2,010	502	418	816

Raw: files in the Kaggle download. Uniq.: unique images per class folder after collapsing exact duplicates (an image saved under two folders counts in both). Excl.: files in exact-duplicate groups with conflicting labels (removed). Final: images kept. Train/Val/Test: the fixed split. Flag.: images flagged as possibly off-topic (out of distribution) by the CLIP screen (kept).

2. **Exact duplicates.** Files with identical SHA-256 hashes were collapsed into one image (587 redundant copies in 533 groups). 13 groups (27 files) held the same image under two class folders, e.g. fuse and relay; their labels contradict each other, so they were removed, leaving 2,930 images.
3. **Near-duplicates.** Re-encoded or resized copies were linked when their perceptual-hash distance (the Hamming distance between pHash codes) was at most 10 and the cosine similarity of their CLIP ViT-B/32 [5] embeddings at least 0.85, or when the cosine alone was at least 0.92. This gave 91 clusters with 234 images (sizes 2 to 29), which are kept but always assigned to the same split (Section 2.5).
4. **Irrelevant or uncertain samples.** A CLIP zero-shot screen compares each image with the 20 class prompts and 9 distractor concepts (person, car, food, logo, text screenshot, cartoon or game art, circuit schematic, website screenshot, collage) and flags it when the distractor probability mass exceeds 0.25. It flagged 816 images (27.8%), concentrated in classes whose names are common words: 121 of 177 switch images (mostly Nintendo Switch consoles) and 64 of 128 transformer images (toy robots, cartoons). Flagged images are kept and reported

separately: in earlier 5-fold cross-validation, dropping them from training lowered the accuracy of a linear classifier on frozen SigLIP features (a linear probe, Section 3.3) from 0.825 to 0.792 overall and from 0.861 to 0.852 on unflagged images.

5. **Label errors.** A confident-learning audit [6] on out-of-fold probe probabilities listed 69 images whose given label is improbable while another class is highly probable.

How labels were obtained, checked and corrected. Labels come from the search query. They were checked automatically (conflicting duplicates, CLIP screen, confident-learning audit) and by inspecting image review sheets. The only correction applied was the removal of the 13 conflicting groups; we did not relabel images, which would need a manual review of all 2,930 images by more than one annotator. The test labels therefore contain the same noise as the training labels, which caps every model's measurable accuracy.

2.4 Class imbalance

After cleaning, the largest class (switch, 177 images) is 1.61 times the smallest (connector, 110); training classes have 76–121 images and test classes 16–25 (Table 1, Figure B.1 in Appendix B). Because the imbalance is mild we used no class weights and no re-sampling. Instead the split is stratified by class, early stopping and model selection use validation macro-F1 (every class counts equally), and we report macro averages and weighted F1.

2.5 Train/validation/test split and leakage prevention

The unit of splitting is the duplicate cluster: a near-duplicate cluster or a single image without near-duplicates (2,787 clusters). We split in two stages and always keep a cluster whole. First, StratifiedGroupKFold (scikit-learn [7]; 7 folds, shuffled, seed 42) partitions the clusters, and the fold whose class distribution is closest (total-variation distance) to the overall one becomes the test set (418 images), which is held out ("sealed") until the final evaluation. Second, the remaining 2,512 development images are divided by the same method into five grouped folds: fold 0 is the validation set (502) and folds 1–4 form the training set (2,010), i.e. 68.6/17.1/14.3%, close to the 70/15/15 split suggested in the brief. The class distribution of each split is in Table 1. The manifest fingerprint is 431315e87d2612cb. The exported splits, notebook and report-generation checks verify that no image or duplicate cluster occurs in two splits. Grouping matters: in the dataset's original random file split (counted over the raw file entries), 128 of 522 validation and 115 of 523 test entries are byte-identical copies of a training file, which inflates scores [8, 9] (Section 6.4). The test set was used once per model, after all choices had been fixed on validation data.

2.6 Ethical, privacy and licensing considerations

The task uses no health or personal records, and no person is a subject of the classification. As a web scrape, the data contain incidental people (the CLIP screen names "person" as the top distractor for 83 images) and trademarks (game consoles, brand logos). We identify no

Table 2: Cleaning pipeline; indented rows break down the row above.

Step	Count	Action
Raw image files in the Kaggle download	3,530	–
Unique files (distinct SHA-256 of the bytes)	2,943	–
redundant exact copies (533 duplicate groups)	587	collapsed to one
corrupt or undecodable files	0	–
duplicate groups with conflicting labels (27 files)	13	removed
Final images	2,930	kept
images in near-duplicate clusters (91 clusters, size 2–29)	234	kept, grouped
split units: clusters incl. singletons (groups, not images)	2,787	–
images flagged as possibly off-topic (CLIP screen)	816	kept, flagged

one; such images appear in our figures only as small thumbnails from the public dataset. Use follows Section 2.1: the source is acknowledged, the use is non-commercial and educational, and the images are not redistributed in the repository (they are rebuilt from the Kaggle download, Appendix D). The 407 photographs of the supplementary web holdout (Section 6.4) are from Wikimedia Commons under public-domain or Creative-Commons licences; author, licence and source of each are recorded in the accompanying attribution register. Pretrained weights come from their official timm releases [10]. The main risk is over-trust in a wrong label, which is why we report confidence and a reject option. Web search results may also over-represent clean product shots, so performance on cluttered workbench photographs can be lower (cf. the Wikimedia holdout in Section 6.4).

3 Methodology, selected models and transfer learning

Figure 2 shows the workflow. The same split files feed all four models; each is selected on the validation set only and scored once on the test set.

3.1 Model A: VGG-style CNN trained from scratch

A VGG-style network [11] written for this project: a stride-2 stem convolution, four stages of two 3×3 convolution–BatchNorm [12]–ReLU blocks (32, 64, 128, 256 channels) with max-pooling between stages, global average pooling, dropout 0.3 and a linear classifier; 1,187,636 parameters with He initialisation [13] and no pretrained weights. It shows what can be learned from about 2,000 images alone.




Figure 2: Shared preparation and evaluation of A–D. Duplicate clusters remain whole across the fixed split. All choices precede test scoring. Editable Excalidraw sources and vector exports accompany the report.

3.2 Model B: fine-tuned ConvNeXt-Tiny

ConvNeXt [14] modernises the ResNet design [15] with 7×7 depthwise convolutions, inverted bottlenecks, LayerNorm and GELU. We use the Tiny variant (27,835,508 parameters) with the timm weights, pretrained on ImageNet-22k and fine-tuned on ImageNet-1k [16]. The 1000-class head is replaced by a new 20-class linear layer, which is trained alone in the first epoch so that its large initial gradients do not disturb the pretrained features [17]. Afterwards all layers are trained, with layer-wise learning-rate decay 0.8 so that early, generic layers change less than late, task-specific ones. Fine-tuning ImageNet networks is the standard transfer recipe for small datasets [18, 19].

3.3 Model C: frozen SigLIP So400m ViT with a linear head

The Vision Transformer [20] splits an image into patches and processes the patch tokens with self-attention. SigLIP [21] trains a ViT image encoder and a text encoder on WebLI (a web-scale image–text collection) with a pairwise sigmoid loss. We use its shape-optimised So400m/14 encoder at 384×384 pixels (27 blocks, width 1152, patch size 14; timm weights pretrained on WebLI). The backbone is frozen. Each image is encoded once into its attention-pooled 1152-dimensional embedding; the features are standardised with the training-split mean and standard deviation, and only one linear layer with 1,152 inputs and 20 outputs (23,060 parameters) with softmax output is trained with cross-entropy and AdamW, i.e. the linear-probe protocol used for image–text models [5].

3.4 Model D: frozen MobileCLIP2-S3 hybrid with a linear head

MobileCLIP2 [22] provides compact image–text encoders. Its S3 image encoder is a FastViT convolution–attention hybrid [23], at 256×256 pixels with 122,775,668 parameters (3.5 times fewer than C; weights pretrained on DFNDR-2B). D uses C's frozen-feature procedure, training-only standardisation and selection rule, with a linear head with 3,072 inputs and 20 outputs (61,460 trainable parameters). It was selected using development folds to study the accuracy–cost trade-off. A–C meet the brief's three named families; D is supplementary, with approval as an additional family still unconfirmed.

3.5 Rationale for the models and evaluation protocol

The brief lists a small custom CNN, ConvNeXt and the Vision Transformer as separate suitable families; our models take one from each (plain CNN, modernised CNN, Vision Transformer) and span the transfer-learning spectrum: no transfer (A), full fine-tuning of supervised ImageNet features (B) and frozen features from web-scale image–text pretraining (C and D). Between B and C, architecture and pretraining data change together, so the comparison measures model plus pretraining as available to a practitioner; the supplementary benchmark (Section 6.4) provides additional comparisons, without isolating a causal effect of architecture.

Evaluation. On the test set we compute per-class precision, recall and F1, their macro averages (all classes equal) and weighted averages (by support), accuracy, balanced accuracy (equal to macro recall) and log-loss. Uncertainty is estimated with 2,000 bootstrap resamples of the test images [24]; pairs of models are compared on the same images with a paired bootstrap of the accuracy difference and an exact McNemar test [25], which tests whether, on the images where exactly one of the two models is right, each model is right equally often.

4 Experimental setup and hyperparameters

4.1 Preprocessing

Every image is decoded to 8-bit RGB, and each model uses the input size and normalisation of its weights. For evaluation (validation, test, and the feature extraction of C and D) the short side is resized to the input size divided by the crop fraction (0.875 for A and B, 0.9 for C, 1.0 for D) and

the centre square is cut out: 183→160 px bilinear for A, 256→224 px bicubic for B, 427→384 px bicubic for C; 256 px bicubic, with no short-side border removed, for D. Pixels are scaled to $[0, 1]$ and normalised per channel (mean and standard deviation 0.5 for A and C; ImageNet statistics for B; CLIP statistics for D, recorded in its run JSON).

4.2 Augmentation (training data only)

A and B are trained with RandomResizedCrop (aspect ratio 0.75–1.33), horizontal flips ($p = 0.5$) and RandAugment with two operations of magnitude 9 [26]; A also uses colour jitter 0.2 and a wider crop range (scale 0.35–1 instead of 0.5–1), because a network trained from scratch needs stronger regularisation (Figure 3). Validation and test images always receive the deterministic evaluation transform. The transformations are realistic for this domain: web photos of parts are taken at arbitrary zoom and framing (random crops), components have no canonical left–right orientation (horizontal flips), and lighting, white balance and compression vary between shops and phones (RandAugment's photometric operations, colour jitter). Vertical flips were not used because printed text and lighting in product shots have a natural "up", and MixUp/CutMix were not used because blended components cannot occur. C and D use no augmentation: their features are computed once from the evaluation crop, which keeps the frozen-feature protocol simple and cheap.

4.3 Hyperparameters

Table B.1 lists every training setting in two parts. Settings differ where the architectures require it. A randomly initialised CNN needs a high learning rate, many epochs and strong augmentation. A pretrained network needs a small learning rate and few epochs. A linear head on frozen, standardised features needs neither augmentation nor a learning-rate schedule. The recipe of B was fixed earlier in the project's grouped 5-fold cross-validation benchmark on the 2,512 development images only, and so was A's apart from its schedule: the benchmark's 120-epoch budget stopped A before it had converged, and the improvement study of Section 6.3, again on the development folds only, lengthened it to 200 epochs (patience 40). The 418 test images were never used for any of this. For each frozen head, the weight decay is selected on the validation set from $\{10^{-4}, 10^{-3}, 10^{-2}, 10^{-1}\}$ (Table B.5, Appendix B). The 3 smallest values (10^{-4} to 10^{-2}) reached the identical best validation macro-F1, because AdamW's decoupled decay [27] is negligible over a few dozen epochs at this learning rate; the tie was broken by the rule, fixed before the grid was run, that the smallest value wins. A and B use label smoothing 0.1 [28] and a cosine schedule [29]. All models are early-stopped on validation macro-F1, and the best validation epoch is tested. D uses the same grid and tie-break; all four values tied (Table B.6).




Figure 3: One training image, its evaluation crop and five random training augmentations per model. C uses frozen features of the evaluation crop; D (not pictured) likewise uses a deterministic 256 px view without augmentation.

4.4 Software, hardware and reproducibility

The models are implemented in PyTorch [30] with timm [10]; scikit-learn [7] provides the split and the reference probe, and uv [31] pins the environment. B was trained on one NVIDIA GeForce RTX 4060 Ti with 7.7 GiB of memory (all versions and the hardware are in Table B.2, Appendix B). The final run of A was trained after the improvement study (Section 6.3) on a second machine, one NVIDIA GeForce RTX 4070 Laptop GPU with 8.0 GiB (Windows 11; the same code, lock file and seed; its software versions are recorded with the run metadata). Peak GPU memory was 435 MB for A and 2,312 MB for B, and the heads of C and D were trained on the CPU from cached features. D's feature extraction and timing used the second machine (RTX 4070 Laptop). The training seed is 0 and the split seed 42. GPU training of A is not bit-for-bit reproducible (non-deterministic cuDNN kernels), so a re-run can differ slightly. Result files, the executed comparison notebook and reproduction instructions are available in the project repository (Appendix D).

Fairness. All four models use the same 2,010 training, 502 validation and 418 test images, the same selection rule (best validation macro-F1) and a single test evaluation each, with no test-time augmentation. Tuning effort is comparable: the recipes of A and B come from the earlier development-set benchmark, and each frozen head's only tuned setting is a four-value weight-decay grid on the validation set (Table B.5). Budgets differ only where the architecture requires it (Table B.1): A receives 200 epochs and converges within them (best epoch 184), whereas B begins to overfit within 20. B and C also differ in pretraining data, which we treat as part of each method (Section 6.5). D's crop fraction 1.0 was fixed on development data; C retains 0.9. No test number led to a change of any setting.

5 Results and model comparison

5.1 Overall test performance

Table 3 gives the test metrics: C (accuracy 0.823, macro-F1 0.817) > D (0.773, 0.770) > B (0.636, 0.628) > A (0.400, 0.392). Individual 95% bootstrap intervals overlap for C and D; the paired comparison favours C (39 images only C gets right, 18 only D; $p = 7.5 \times 10^{-3}$). All six pairwise McNemar tests reject equal accuracy (Table 4; unadjusted p-values). Balanced accuracy and macro and weighted averages are close because the classes are nearly balanced. Test accuracy is within about two points of validation accuracy at the selected epoch for all four models (Table B.3). C has the lowest log-loss (0.614); this favours its probabilistic predictions on average, although log-loss alone does not establish calibration.

The reference rows use different fitting procedures and are not matched main models. R1 fits a scikit-learn logistic-regression head on C's training features (0.833). R2 (Deployed) refits on train plus validation and fuses with SigLIP's zero-shot head (0.837); R3 (Small) does the same with MobileCLIP2-S3 (0.806). Their extra fitting data and heads prevent attributing these gains solely to backbone choice (Figure C.1).

5.2 Learning curves

Figure 4 shows training and validation loss and validation accuracy and macro-F1 per epoch; Table B.3 (Appendix B) gives the values at the selected epoch. Losses are plain cross-entropy.

- A improves slowly for most of its 200-epoch budget and is selected at epoch 184. There its training accuracy is 0.83 but its validation accuracy only 0.378. The validation loss is lowest at epoch 81 (2.447; chance level $\ln 20 = 3.00$) and then rises to 2.519 while validation accuracy and macro-F1 still improve: the network grows more confident without changing many decisions, and in its second hundred epochs it also fits the training set (training cross-entropy 0.712). The 120-epoch schedule of the earlier benchmark stopped it before this point (Section 6.3).

Table 3: Test-set metrics (n = 418, same images for all models). Bold: best main model. CI: 95% percentile bootstrap (2,000 resamples).

Model	Acc.	Bal. acc.	Macro P	Macro R	Macro F1	Weighted F1	Log loss
A: scratch CNN	0.400	0.391	0.399	0.391	0.392	0.400	2.361
95% CI	[0.354, 0.445]				[0.342, 0.432]		
B: ConvNeXt-T (fine-tuned)	0.636	0.630	0.642	0.630	0.628	0.632	1.346
95% CI	[0.591, 0.682]				[0.578, 0.668]		
C: SigLIP ViT (frozen + linear)	**0.823**	**0.821**	**0.827**	**0.821**	**0.817**	**0.820**	**0.614**
95% CI	[0.787, 0.859]				[0.774, 0.851]		
D: MobileCLIP2-S3	0.773	0.772	0.779	0.772	0.770	0.772	0.800
95% CI	[0.732, 0.811]				[0.726, 0.806]		
Reference rows (refitted or alternative heads; not matched main models)							
R1: SigLIP + sklearn probe	0.833	0.830	0.838	0.830	0.829	0.832	0.606
R2: deployed fused model	0.837	0.836	0.843	0.836	0.834	0.836	0.527
R3: Small (refitted + fused)	0.806	0.804	0.811	0.804	0.802	0.806	0.651

Table 4: Paired comparisons on the same 418 test images: accuracy difference Δ as a proportion (×100 = percentage points, as in the text), paired-bootstrap interval, discordant counts, exact McNemar test.

Pair	Δ accuracy	95% CI	Only 1st right	Only 2nd right	McNemar p
B − A	+0.237	+0.189 to +0.289	119	20	2.4×10^{-18}
C − B	+0.187	+0.141 to +0.232	92	14	3.1×10^{-15}
C − A	+0.423	+0.373 to +0.474	184	7	1.1×10^{-45}
C − D	+0.050	+0.014 to +0.086	39	18	7.5×10^{-3}
D − B	+0.136	+0.091 to +0.179	80	23	1.5×10^{-8}
D − A	+0.373	+0.325 to +0.423	166	10	1.3×10^{-37}

- B profits from its pretrained features at once: validation accuracy passes 0.5 in epoch 4 and plateaus near 0.618, while training accuracy rises to 0.91 and validation loss stays at about 1.431, i.e. a 28-million-parameter network overfits a small, noisy training set. The cosine schedule and early stopping (best epoch 19 of 20) keep it from getting worse.
- C passes 0.75 validation accuracy in epoch 3 and reaches 0.803. Training accuracy goes to 1.00, since 1,152 standardised features are almost linearly separable for 2,010 images. Validation loss is lowest in epoch 10 (0.756) and then creeps up while accuracy and macro-F1 stay flat: the head grows more confident without changing many decisions. Early stopping selected epoch 14.
- D reaches validation accuracy 0.775 and macro-F1 0.772 at epoch 11 of 31; its 3,072-dimensional features support the same inexpensive head-fitting procedure.

5.3 Per-class results and confusion matrices

Figure 5 plots the per-class test F1; the full per-class precision, recall and F1 values are in Tables A.1 and A.3 (Appendix A). Model C is strongest overall; its weakest class is resistor (F1 0.61, recall 0.45) and its strongest switch (0.96). B is weakest on fuse (F1 0.34, recall 0.25). A exceeds F1 0.5 only for a few visually distinctive classes (microcontroller board, switch, jumper wire, heat sink). The confusion matrices (Figure A.1) show A's errors spread over the whole matrix, B's concentrated in a few blocks, and those of C and D almost diagonal; Section 6.2 analyses the largest off-diagonal entries.

5.4 Correct and incorrect predictions

Figure 6 shows C's six random correct predictions and its six most confident errors with true class, prediction and softmax confidence. A and B appear in Figure A.3, and D in Figure B.2. Many of C's confident errors are images that do not show the labelled component: a DIP chip labelled transistor, a breadboard power module labelled breadboard, a fibre-optic pigtail and a coaxial




Figure 4: Learning curves (one column per model). Top: cross-entropy; dotted: label-smoothed training objective (A, B). Bottom: training accuracy, validation accuracy and macro-F1. Training curves of A and B are measured on augmented batches; the grey line marks the epoch whose weights were tested.




Figure 5: Per-class test F1 of the four models, sorted by model C; the number after each class is its training-set size.

plug labelled jumper wire, and an icon sheet and a “Capacitor vs Resistor” banner labelled resistor. A’s most confident errors include a sheet of package drawings labelled diode, an LED arrow sign labelled power supply module and handwritten notes labelled inductor coil.

5.5 Agreement between the models and computational cost

A, B and C are right on 143 test images and all three wrong on 57 (Figure A.4). 75 images are recognised only by C and 109 by B and C but not A, whereas C is wrong on only 17 images that A or B get right (examples in Figure 7).

Accuracy has a price (Table B.4 in Appendix B): C needs 31.1 ms per image on the GPU at batch size 1, about 11 times as long as B (2.79 ms), and 893.5 ms on an 8-thread CPU, about 49 times as long as B (18.4 ms); its frozen backbone weighs 1,633.6 MB in fp32. D uses 468.4 MB of fp32 weights. On D’s PC, its 15.16 ms GPU and 111.5 ms CPU times compare with 37.94 and 1,563.3 ms for C’s tower: about 2.5 and 14 times faster, respectively. This is a same-machine anchor, not a ratio against C’s different-PC table row; it also excludes C’s head and preprocessing.

6 Discussion, limitations and error analysis

6.1 Why the models differ

The ranking follows how much relevant visual knowledge each model brings to a 2,010-image problem, rather than depth or parameter count. A starts from random weights and must learn edges, textures, shapes and classes at once from about 100 images per class; its learning curves show it is data-limited, as does the improvement study of Section 6.3 (more epochs helped; more capacity, residual blocks, stronger augmentation and better initialisation did not), and its per-class F1 correlates with the number of training images (Spearman ρ over the 20 classes +0.51, against +0.56 for B and +0.43 for C). B re-uses ImageNet-22k features that already encode objects, materials and shapes, so it learns quickly; but ImageNet contains few electronic parts, so the features are generic, and fine-tuning all 28 million parameters on 2,010 noisy images shows a generalisation gap (training accuracy 0.91 against 0.618 on validation). C uses a 428-million-parameter encoder pretrained on web image–text pairs. Its embedding already separates the classes: SigLIP zero-shot classification, with no training at all, reaches macro-F1 0.776 in the benchmark (Section 6.4). It is also the least affected by off-topic images (0.759 on flagged




Figure 6: Model C: six random correct predictions (top row) and six most confident errors (bottom row, red frame, true → predicted). Confidence is the softmax probability of the predicted class. MCU board = microcontroller board; PSU module = power supply module; crystal osc. = crystal oscillator; batt. holder = battery holder. A and B are shown in Figure A.3; D in Figure B.2.



Figure 7: Disagreements among A–C. Rows: C right and B wrong; B right and C wrong; all three wrong. Titles give the true class (bold) and each model's prediction; ticks mark correct predictions and crosses errors. Abbreviations as in Figure 6. The agreement counts are plotted in Figure A.4.

test images against 0.500 for B, Section 6.2), plausibly because such images resemble its web pretraining data. Freezing the backbone means label noise cannot distort it, and training the 23,060 head parameters takes 1.7 s for the whole grid on cached features. D repeats this strategy with a smaller hybrid: 5.0 accuracy points below C and 13.6 above B. These results support the value of the representation; architecture and pretraining are not independently controlled.

6.2 Error analysis

Look-alike components. Table 5 lists the most frequent confusions. C's largest are resistor → inductor coil (4) and jumper wire → connector (3); B's are resistor → crystal oscillator (5) and ic chip → microcontroller board (4). These pairs share shapes: colour-banded axial bodies (some inductors look like fat resistors), cables with plugs, chips mounted on boards. Resistor is C's hardest class: precision 0.91 but recall only 0.45, partly because several test "resistors" are icon sheets, banners or schematics. A's confusions (e.g. fuse → connector, fuse → switch) are spread widely and often have no obvious visual explanation, consistent with a model that has not learned robust shape features. Diode and led are related devices that are often shown together in infographics (2 of C's errors are diode → led). Summed over A, B and C, the most frequent confusions are resistor → crystal oscillator (8); jumper wire → connector (7); transistor → diode (7); crystal oscillator → relay (6).

Data quality matters more than class imbalance. On the 306 test images that the CLIP screen did not flag, accuracy is 0.435 (A), 0.686 (B) and 0.846 (C); on the 112 flagged ones it is 0.304, 0.500 and 0.759. D scores 0.807 on unflagged and 0.679 on flagged images. B loses most (19 points; A 13, C 9, D 13), and C stays far ahead on flagged images, plausibly because its pretraining has seen such web content. A, B and C fail on 57 test images, many of them infographics, diagrams or scenes without the labelled component, where the label rather than the prediction is often questionable (Figure 7). Class imbalance, by contrast, is not an important factor: the size ratio is only 1.61, and C's per-class F1 is not significantly related to class size ($\rho = +0.43$, $p = 0.06$).

Confidence is informative. C's mean softmax confidence is 0.87 on correct and 0.47 on wrong predictions (B: 0.76 and 0.43), so a reject option can catch many errors [32, 33]. The deployed model uses one: at a confidence threshold of 0.5 it answers 87.1% of the test images and is right on 0.909 of those.

6.3 Can the scratch CNN be improved?

A 19-experiment study used development folds only to test whether recipe changes close the gap as documented in the supplementary scratch-CNN study. Resolution, capacity, depth, residual blocks, regularisation, augmentation and initialisation changes produced no consistent gain. Training to convergence (200 rather than 120 epochs) did help: five-fold macro-F1 rose by 3.5 points, with gains on all folds (Table C.1, Appendix C). That schedule is A in this report; its recorded test gain is 5.6 macro-F1 points, not a selection criterion. It still overfits (0.83 training accuracy versus 0.378 validation). On the independent Wikimedia set A reaches 0.257 macro-F1, against 0.816 for Deployed. The tested recipe improvements did not close the transfer-learning gap.

Table 5: Most frequent test confusions of A–C (true → predicted) per model, from their recorded confusion matrices; equal counts are listed alphabetically. MCU board: microcontroller board.

	A: scratch CNN		B: ConvNeXt-T (fine-tuned)		C: SigLIP ViT (frozen + linear)	
#	True → predicted	n	True → predicted	n	True → predicted	n
1	crystal oscillator → relay	5	resistor → crystal oscillator	5	resistor → inductor coil	4
2	inductor coil → resistor	4	ic chip → MCU board	4	jumper wire → connector	3
3	transistor → diode	4	capacitor → diode	3	battery holder → led	2
4	battery holder → heat sink	3	heat sink → crystal oscillator	3	breadboard → power supply module	2
5	capacitor → relay	3	led → switch	3	capacitor → inductor coil	2
6	connector → potentiometer	3	led → transistor	3	diode → led	2

6.4 Supporting evidence from the wider study

The project's broader study (details in Appendix C) supports the comparison. Grouped 5-fold cross-validation over eleven families reproduces the ordering (macro-F1: scratch CNN 0.355 with the benchmark's 120-epoch schedule, 0.390 with the 200-epoch schedule of Section 6.3; ConvNeXt-T fine-tuned 0.641, frozen SigLIP So400m probe 0.824), and every ImageNet-pretrained fine-tune (0.547–0.654) stays below SigLIP zero-shot classification without any training (0.776). The dataset's original file-level split leaks duplicates and inflates linear-probe accuracy by 5.5 to 13.6 points, more for weaker models. On 407 fresh Wikimedia Commons photographs the deployed SigLIP-based model (R2) scored 0.821 accuracy, close to its in-distribution result.

6.5 Limitations

This comparison uses one training seed and one fixed test split, with about 21 images per class. Unreviewed search-term labels, residual duplicates and CLIP-derived off-topic flags limit interpretation; the screen shares a lineage with the frozen image–text encoders. Architecture, pretraining data and training budgets change together, so the scores compare practical recipes rather than isolate their causes. D also differs in evaluation crop and timing hardware; its weights have research-use restrictions. C's cost (428.2 million parameters; 893.5 ms per CPU image) limits deployment. The detailed limitations and provenance are retained in Appendix C; neither holdout should be reused for selection.

7 Conclusion

On the fixed, duplicate-aware split, C (SigLIP, accuracy 0.823, macro-F1 0.817) leads D (MobileCLIP2-S3, 0.773, 0.770), B (ConvNeXt-T, 0.636, 0.628) and A (scratch CNN, 0.400, 0.392). Both frozen encoders outperform the tested fine-tuned and scratch networks, although architecture and pretraining remain confounded. Training A to convergence helped without closing the gap.

Recommendation. Choose C for accuracy when its memory and latency are acceptable. D trades 5.0 accuracy points for 3.5 times fewer parameters and lower measured latency, subject to research-use restrictions. B offers still lower latency. Deployed (R2, 0.837) and Small (R3, 0.806) refit on development rows and fuse with zero-shot heads; they are distinct from C and D. Fast retains SigLIP at 308 px with INT8 TensorRT. Their fitting and timing protocols differ.

Lessons learned. On this small, noisy dataset, pretrained representation and a duplicate-aware split matter more than the classifier fitted on top. Better labels and cleaner homonym classes are promising next steps; future selection requires fresh evaluation data rather than further use of the spent holdouts.

References

[1] Y. Shao, L. Zhou, F. Tang, X. Shi, D. Chen, and S. Xia, "Comparative performance of finetuned ImageNet pre-trained models for electronic component classification," in *Proc. 7th Int. Conf. Universal Village (UV)*, pp. 1–10, 2024. https://doi.org/10.1109/uv63228.2024.11189118.

[2] L. Zhou and L. Zhang, "A novel convolutional neural network for electronic component classification with diverse backgrounds," in *Modeling and Simulation in Manufacturing*, pp. 191–207, World Scientific, 2025. https://doi.org/10.1142/9789819801473_0011.

[3] Q. Ling and N. A. M. Isa, "Printed circuit board defect detection methods based on image processing, machine learning and deep learning: A survey," *IEEE Access*, vol. 11, pp. 15921–15944, 2023. https://doi.org/10.1109/access.2023.3245093.

[4] mdfaisalahmed025, "Electronic Component Recognizer." Kaggle dataset (20 classes), https://www.kaggle.com/datasets/mdfaisalahmed025/electronic-component-recognizer. Accessed 17 October 2026.

[5] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever, "Learning transferable visual models from natural language

supervision," in *Proc. 38th Int. Conf. Mach. Learn. (ICML)*, vol. 139 of *Proc. Mach. Learn. Res.*, pp. 8748–8763, 2021. https://proceedings.mlr.press/v139/radford21a.html.

[6] C. Northcutt, L. Jiang, and I. Chuang, "Confident learning: Estimating uncertainty in dataset labels," *J. Artif. Intell. Res.*, vol. 70, pp. 1373–1411, 2021. https://doi.org/10.1613/jair.1.12125.

[7] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, *et al.*, "Scikit-learn: Machine learning in Python," *J. Mach. Learn. Res.*, vol. 12, pp. 2825–2830, 2011. https://jmlr.org/papers/v12/pedregosa11a.html.

[8] B. Barz and J. Denzler, "Do we train on test data? Purging CIFAR of near-duplicates," *J. Imaging*, vol. 6, no. 6, p. 41, 2020. https://doi.org/10.3390/jimaging6060041.

[9] S. Kapoor and A. Narayanan, "Leakage and the reproducibility crisis in machine-learning-based science," *Patterns*, vol. 4, no. 9, p. 100804, 2023. https://doi.org/10.1016/j.patter.2023.100804.

[10] R. Wightman, "PyTorch Image Models (timm)." GitHub repository, https://github.com/huggingface/pytorch-image-models, 2019.

[11] K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2015. https://arxiv.org/abs/1409.1556.

[12] S. Ioffe and C. Szegedy, "Batch normalization: Accelerating deep network training by reducing internal covariate shift," in *Proc. 32nd Int. Conf. Mach. Learn. (ICML)*, vol. 37 of *Proc. Mach. Learn. Res.*, pp. 448–456, 2015. https://proceedings.mlr.press/v37/ioffe15.html.

[13] K. He, X. Zhang, S. Ren, and J. Sun, "Delving deep into rectifiers: Surpassing human-level performance on ImageNet classification," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, pp. 1026–1034, 2015. https://doi.org/10.1109/ICCV.2015.123.

[14] Z. Liu, H. Mao, C.-Y. Wu, C. Feichtenhofer, T. Darrell, and S. Xie, "A ConvNet for the 2020s," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 11966–11976, 2022. https://doi.org/10.1109/cvpr52688.2022.01167.

[15] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 770–778, 2016. https://doi.org/10.1109/cvpr.2016.90.

[16] O. Russakovsky, J. Deng, H. Su, J. Krause, S. Satheesh, S. Ma, Z. Huang, A. Karpathy, A. Khosla, M. Bernstein, A. C. Berg, and L. Fei-Fei, "ImageNet large scale visual recognition challenge," *Int. J. Comput. Vis.*, vol. 115, no. 3, pp. 211–252, 2015. https://doi.org/10.1007/s11263-015-0816-y.

[17] A. Kumar, A. Raghunathan, R. Jones, T. Ma, and P. Liang, "Fine-tuning can distort pretrained features and underperform out-of-distribution," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2022. https://arxiv.org/abs/2202.10054.

[18] J. Yosinski, J. Clune, Y. Bengio, and H. Lipson, "How transferable are features in deep neural networks?," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 27, pp. 3320–3328, 2014. https://proceedings.neurips.cc/paper/2014/hash/532a2f85b6977104bc93f8580abbb330-Abstract.html.

[19] S. Kornblith, J. Shlens, and Q. V. Le, "Do better ImageNet models transfer better?," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 2656–2666, 2019. https://doi.org/10.1109/cvpr.2019.00277.

[20] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly, J. Uszkoreit, and N. Houlsby, "An image is worth 16x16 words: Transformers for image recognition at scale," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2021. https://arxiv.org/abs/2010.11929.

[21] X. Zhai, B. Mustafa, A. Kolesnikov, and L. Beyer, "Sigmoid loss for language image pre-training," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, pp. 11941–11952, 2023. https://doi.org/10.1109/iccv51070.2023.01100.

[22] F. Faghri, P. K. A. Vasu, C. Koc, V. Shankar, A. Toshev, O. Tuzel, and H. Pouransari, "MobileCLIP2: Improving multi-modal reinforced training," *Transactions on Machine Learning Research*, 2025. https://arxiv.org/abs/2508.20691.

[23] P. K. A. Vasu, J. Gabriel, J. Zhu, O. Tuzel, and A. Ranjan, "FastViT: A fast hybrid vision transformer using structural reparameterization," in *Proc. IEEE/CVF Int. Conf. Comput. Vis. (ICCV)*, pp. 5762–5772, 2023. https://doi.org/10.1109/ICCV51070.2023.00532.

[24] B. Efron, "Bootstrap methods: Another look at the jackknife," *Ann. Statist.*, vol. 7, no. 1, pp. 1–26, 1979. https://doi.org/10.1214/aos/1176344552.

[25] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," *Psychometrika*, vol. 12, no. 2, pp. 153–157, 1947. https://doi.org/10.1007/BF02295996.

[26] E. D. Cubuk, B. Zoph, J. Shlens, and Q. V. Le, "RandAugment: Practical automated data augmentation with a reduced search space," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. Workshops (CVPRW)*, pp. 3008–3017, 2020. https://doi.org/10.1109/cvprw50498.2020.00359.

[27] I. Loshchilov and F. Hutter, "Decoupled weight decay regularization," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2019. https://arxiv.org/abs/1711.05101.

[28] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, "Rethinking the Inception architecture for computer vision," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, pp. 2818–2826, 2016. https://doi.org/10.1109/cvpr.2016.308.

[29] I. Loshchilov and F. Hutter, "SGDR: Stochastic gradient descent with warm restarts," in *Proc. Int. Conf. Learn. Represent. (ICLR)*, 2017. https://arxiv.org/abs/1608.03983.

[30] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, *et al.*, "PyTorch: An imperative style, high-performance deep learning library," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 32, 2019. https://proceedings.neurips.cc/paper/2019/hash/bdbca288fee7f92f2bfa9f7012727740-Abstract.html.

[31] Astral Software, "uv: an extremely fast Python package and project manager." https://docs.astral.sh/uv/, 2024.

[32] C. Chow, "On optimum recognition error and reject tradeoff," *IEEE Trans. Inf. Theory*, vol. 16, no. 1, pp. 41–46, 1970. https://doi.org/10.1109/tit.1970.1054406.

[33] Y. Geifman and R. El-Yaniv, "Selective classification for deep neural networks," in *Adv. Neural Inf. Process. Syst. (NeurIPS)*, vol. 30, 2017. https://proceedings.neurips.cc/paper/2017/hash/4a8423d5e91fda00bb7e46540e2b0cf1-Abstract.html.

A Detailed evaluation results

Table A.1 gives the per-class test precision, recall and F1 of A–C, and Table A.2 those of R1 and R2 on the same test images. Table A.3 adds D and R3 (Small). The per-class image counts of every split are in Table 1.

Table A.1: Per-class test precision (P), recall (R) and F1 (n = test images per class). Best F1 among A–C per class in bold.

		A: scratch CNN			B: ConvNeXt-T			C: SigLIP ViT		
Class	n	P	R	F1	P	R	F1	P	R	F1
battery holder	22	0.57	0.59	0.58	0.73	0.73	0.73	0.79	0.86	**0.83**
breadboard	19	0.45	0.47	0.46	0.65	0.68	0.67	0.83	0.79	**0.81**
capacitor	17	0.33	0.29	0.31	0.75	0.53	0.62	0.80	0.71	**0.75**
connector	16	0.36	0.31	0.33	0.77	0.62	0.69	0.76	0.81	**0.79**
crystal oscillator	21	0.24	0.24	0.24	0.45	0.62	0.52	0.76	0.90	**0.83**
diode	21	0.40	0.38	0.39	0.48	0.76	0.59	0.86	0.86	**0.86**
fuse	20	0.16	0.20	0.18	0.56	0.25	0.34	0.94	0.75	**0.83**
heat sink	23	0.38	0.43	0.41	0.73	0.70	0.71	0.87	0.87	**0.87**
ic chip	22	0.47	0.41	0.44	0.76	0.59	0.67	0.88	0.68	**0.77**
inductor coil	23	0.40	0.26	0.32	0.64	0.61	0.62	0.78	0.91	**0.84**
jumper wire	23	0.52	0.57	0.54	0.83	0.87	**0.85**	0.83	0.83	0.83
led	18	0.21	0.22	0.22	0.42	0.44	0.43	0.68	0.94	**0.79**
microcontroller board	22	0.68	0.68	0.68	0.73	0.86	0.79	0.87	0.91	**0.89**
potentiometer	21	0.67	0.57	0.62	0.65	0.71	0.68	0.91	0.95	**0.93**
power supply module	22	0.42	0.36	0.39	0.79	0.68	0.73	0.74	0.77	**0.76**
relay	22	0.24	0.36	0.29	0.67	0.73	0.70	0.79	0.86	**0.83**
resistor	22	0.30	0.27	0.29	0.50	0.36	0.42	0.91	0.45	**0.61**
switch	25	0.61	0.68	0.64	0.66	0.76	0.70	0.96	0.96	**0.96**
transformer	18	0.25	0.22	0.24	0.56	0.56	0.56	0.79	0.83	**0.81**
transistor	21	0.32	0.29	0.30	0.52	0.52	0.52	0.80	0.76	**0.78**
Macro average	418	0.40	0.39	0.39	0.64	0.63	0.63	0.83	0.82	0.82

Table A.2: Per-class test results of the reference models. R1: scikit-learn logistic-regression probe (inverse regularisation $C = 0.01$) on the same frozen SigLIP features and training split as C. R2: the deployed model (probe fitted on train + validation, fused with the zero-shot text head, temperature 0.898).

		R1: sklearn probe			R2: deployed		
Class	*n*	P	R	F1	P	R	F1
battery holder	22	0.77	0.91	0.83	0.83	0.86	0.84
breadboard	19	0.79	0.79	0.79	0.84	0.84	0.84
capacitor	17	0.80	0.71	0.75	0.81	0.76	0.79
connector	16	0.76	0.81	0.79	0.76	0.81	0.79
crystal oscillator	21	0.73	0.90	0.81	0.76	0.90	0.83
diode	21	0.86	0.86	0.86	0.86	0.86	0.86
fuse	20	0.94	0.85	0.89	0.94	0.80	0.86
heat sink	23	0.91	0.87	0.89	0.87	0.87	0.87
ic chip	22	0.94	0.73	0.82	0.94	0.77	0.85
inductor coil	23	0.84	0.91	0.88	0.91	0.87	0.89
jumper wire	23	0.83	0.83	0.83	0.76	0.83	0.79
led	18	0.73	0.89	0.80	0.68	0.94	0.79
microcontroller board	22	0.87	0.91	0.89	0.91	0.91	0.91
potentiometer	21	0.91	0.95	0.93	0.91	1.00	0.95
power supply module	22	0.71	0.77	0.74	0.70	0.73	0.71
relay	22	0.79	0.86	0.83	0.79	0.86	0.83
resistor	22	1.00	0.59	0.74	1.00	0.55	0.71
switch	25	0.96	0.92	0.94	0.96	0.96	0.96
transformer	18	0.78	0.78	0.78	0.78	0.78	0.78
transistor	21	0.84	0.76	0.80	0.85	0.81	0.83
Macro average	418	0.84	0.83	0.83	0.84	0.84	0.83

Table A.3: Per-class test results of D and R3 (Small). D fits a linear head on training rows only; R3 refits on development rows and fuses with the zero-shot head. They are different classifiers.

		D: MobileCLIP2-S3			R3: Small fused		
Class	*n*	P	R	F1	P	R	F1
battery holder	22	0.86	0.86	0.86	0.86	0.82	0.84
breadboard	19	0.79	0.79	0.79	0.83	0.79	0.81
capacitor	17	0.82	0.82	0.82	0.82	0.82	0.82
connector	16	0.70	0.88	0.78	0.72	0.81	0.76
crystal oscillator	21	0.64	0.76	0.70	0.73	0.90	0.81
diode	21	0.63	0.81	0.71	0.72	0.86	0.78
fuse	20	0.84	0.80	0.82	0.84	0.80	0.82
heat sink	23	0.79	0.83	0.81	0.83	0.87	0.85
ic chip	22	0.88	0.64	0.74	0.94	0.68	0.79
inductor coil	23	0.68	0.74	0.71	0.75	0.78	0.77
jumper wire	23	0.86	0.78	0.82	0.95	0.83	0.88
led	18	0.61	0.61	0.61	0.62	0.72	0.67
microcontroller board	22	0.72	0.82	0.77	0.87	0.91	0.89
potentiometer	21	0.95	0.90	0.93	0.91	0.95	0.93
power supply module	22	0.71	0.68	0.70	0.70	0.73	0.71
relay	22	0.81	0.77	0.79	0.75	0.82	0.78
resistor	22	0.92	0.55	0.69	0.92	0.55	0.69
switch	25	0.89	0.96	0.92	0.92	0.96	0.94
transformer	18	0.70	0.78	0.74	0.68	0.72	0.70
transistor	21	0.78	0.67	0.72	0.84	0.76	0.80
Macro average	418	0.78	0.77	0.77	0.81	0.80	0.80




Figure A.1: Test confusion counts for A and B ($n = 418$). Numbered axes use the class key on the right; rows are true classes and columns predictions. Zero cells are blank. The count scale is shared with Figure A.2.




Figure A.2: Test confusion counts for C and D, with the same class key and count scale as Figure A.1.




Figure A.3: Model A (upper panel) and B (lower panel): six random correct predictions and six most confident errors per model. Image selections, predictions and confidence values are unchanged; labels follow Figure 6.




Figure A.4: Test images by the subset of A, B and C that classifies them correctly (D excluded).

B Additional dataset and training details

Table B.1: Training settings: architecture and data. Epochs are counted from 1. Optimisation and runtime settings continue below.

	■ **A**: scratch CNN	■ **B**: ConvNeXt-T (fine-tuned)	■ **C**: SigLIP ViT (frozen + linear)	■ **D**: MobileCLIP2-S3 (frozen + linear)
MODEL				
Model / variant	VGG-style CNN (scratch), width 32, 4 stages, dropout 0.3	ConvNeXt-Tiny, stochastic depth (drop-path rate) 0.1	ViT-So400m/14 (SigLIP), frozen; linear head (1,152 inputs, 20 outputs)	FastViT hybrid (MobileCLIP2-S3), frozen; linear head (3,072 inputs, 20 outputs)
Pretrained weights	none (He initialisation)	ImageNet-22k→1k	WebLI	DFNDR-2B
Trainable / total params	1,187,636 / 1,187,636	27,835,508 / 27,835,508	23,060 / 428,248,660	61,460 / 122,775,668
DATA AND AUGMENTATION				
Input size (px)	160×160	224×224	384×384	256×256
Augmentation (training only)	RandomResizedCrop (scale 0.35–1), h-flip 0.5, RandAugment (2, 9), colour jitter 0.2	RandomResizedCrop (scale 0.5–1), h-flip 0.5, RandAugment (2, 9)	none (features of the evaluation crop)	none (features of the evaluation crop)
Class weights / sampling	none (uniform shuffling)	none (uniform shuffling)	none (uniform shuffling)	none (uniform shuffling)
Batch size; grad. accumulation	64; none	32; none	256; none	256; none

Table B.2 lists the software and hardware of the training run.

Table B.3 gives the state of each model at its selected epoch, Table B.4 model size and inference time, Figure B.1 the class distribution before and after cleaning and per split (the numbers are in Table 1), and Table B.5 the weight-decay grid of model C's head.

Table B.1: Training settings (continued): optimisation, stopping and runtime. Times for C/D exclude feature extraction.

	A: scratch CNN	**B**: ConvNeXt-T (fine-tuned)	**C**: SigLIP ViT (frozen + linear)	**D**: MobileCLIP2-S3 (frozen + linear)
OPTIMISATION				
Optimiser	AdamW, grad. clip 1.0	AdamW, grad. clip 1.0	AdamW	AdamW
Learning rate	0.002	0.0002	0.001	0.001
LR schedule	linear warm-up 5 epochs, cosine to 0	head only in epoch 1, then all layers; warm-up 2 epochs, cosine to 0; layer-wise LR decay 0.8	constant	constant
Weight decay	0.05 (fixed)	0.05 (fixed)	0.0001 (grid on val., Table B.5)	0.0001 (grid on val., Table B.6)
Loss	cross-entropy, label smoothing 0.1	cross-entropy, label smoothing 0.1	cross-entropy, label smoothing 0.0	cross-entropy, label smoothing 0.0
REGULARISATION AND STOPPING				
Early stopping	val. macro-F1, patience 40	val. macro-F1, patience 6	val. macro-F1, patience 20	val. macro-F1, patience 20
Epochs (max / run / best)	200 / 200 / 184	20 / 20 / 19	200 / 34 / 14	200 / 31 / 11
RUNTIME				
Numerical precision	mixed fp16	mixed fp16	fp16 features, fp32 head	fp16 features, fp32 head
Random seed (training; split)	0; 42	0; 42	0; 42	0; 42
Training time	390 s (GPU)	120 s (GPU)	1.7 s for all 4 grid runs (CPU, cached features)	2.4 s for all 4 grid runs (CPU, cached features)

Table B.2: Software and hardware of the training run of B and C; the final run of A and the extraction and timing of D used a second machine (Section 4.4).

Component	Version / specification
Python	3.12.14
PyTorch / torchvision	2.11.0+cu128 / 0.26.0+cu128
timm (architectures and weights)	1.0.30
open_clip_torch	3.3.0
scikit-learn / NumPy / pandas	1.9.1 / 2.5.4 / 3.0.6
Pillow / matplotlib	13.0.0 / 3.11.2
ONNX / onnxruntime (deployment)	1.23.2 / 1.31.0
CUDA (torch build) / cuDNN	12.8 / 91900
GPU	NVIDIA GeForce RTX 4060 Ti, 7.7 GiB memory (compute capability 8.9)
NVIDIA driver	615.71.09
CPU / RAM	AMD Ryzen 7 8700F 8-Core Processor (16 logical cores) / 30.7 GiB
Operating system	Linux-7.2.7-1-cachyos-x86_64-with-glibc2.44
Environment manager	uv (locked dependencies)

Table B.3: State at the selected (best validation macro-F1) epoch. CE: cross-entropy.

Model	Epochs run	Best epoch	Train acc.	Val. acc.	Val. macro-F1	Train CE	Val. CE
A: scratch CNN	200	184	0.832	0.378	0.374	0.712	2.519
B: ConvNeXt-T (fine-tuned)	20	19	0.904	0.618	0.617	0.542	1.431
C: SigLIP ViT (frozen + linear)	34	14	0.986	0.803	0.801	0.139	0.759
D: MobileCLIP2-S3	31	11	0.999	0.775	0.772	0.048	0.900

Table B.4: Model size and inference time: forward pass of a preprocessed tensor after warm-up, fp16 on the GPU, fp32 on 8 CPU threads, without JPEG decoding and resizing. C's and D's checkpoints hold only the trained heads; the large backbone weights are additional. D was timed on an RTX 4070 Laptop, while A–C were timed on the environment-table PC. D's tower was reparameterised for inference. MB follows the source files' 2^{20}-byte convention (MiB); these are not complete application download sizes.

Model	Params (M)	Trainable params	Input (px)	Checkpoint (MB)	GPU, $b = 1$ (ms/img)	GPU, $b = 32$ (ms/img)	CPU, $b = 1$ (ms/img)
A: scratch CNN	1.19	1,187,636	160	4.56	0.52	0.046	1.7
B: ConvNeXt-T (fine-tuned)	27.84	27,835,508	224	106.24	2.79	0.803	18.4
C: SigLIP ViT (frozen + linear)	428.25	23,060	384	0.10	31.10	22.475	893.5
D: MobileCLIP2-S3	122.78	61,460	256	0.26	15.16	3.098	111.5
C tower (D's PC)	428.25	–	384	–	37.94	27.877	1,563.3




Figure B.1: Left: images per class in the raw download (light) and after cleaning (dark). Right: the split of the cleaned images into training, validation and test sets (68.6 / 17.1 / 14.3%).

Table B.5: Weight-decay selection for model C's head on the validation set (learning rate 10^{-3}, batch 256, at most 200 epochs, patience 20). The 3-way tie was broken by the pre-set smallest-value rule. CE: cross-entropy.

Weight decay	Best epoch	Epochs run	Val. acc.	Val. macro-F1	Val. CE	Selected
0.0001	14	34	0.8028	0.8011	0.7595	yes
0.001	14	34	0.8028	0.8011	0.7594	
0.01	14	34	0.8028	0.8011	0.7594	
0.1	21	41	0.8008	0.7999	0.7736	

Table B.6: D's validation weight-decay grid: same learning rate, batch and stopping rule as C. All four values tied on macro-F1; the pre-set smallest-value rule selected 10^{-4}.

Weight decay	Best epoch	Val. acc.	Val. macro-F1	Val. CE
0.0001	11	0.775	0.772	0.900
0.001	11	0.775	0.772	0.900
0.01	11	0.775	0.772	0.899
0.1	11	0.775	0.772	0.898




Figure B.2: D: six random correct predictions and six most confident errors; layout and abbreviations as in Figure 6. Confidence is uncalibrated softmax probability.

C Supporting analysis

This appendix details the supporting results summarised in Section 6.4. In Table C.2, fine-tuning used one fixed recipe per family, the probe is a logistic regression on frozen features, and zero-shot uses the model's text encoder with class-name prompts and no training.

Eleven-family benchmark. Grouped 5-fold cross-validation on the 2,512 development images (Table C.2) reproduces the ordering: scratch CNN 0.355 macro-F1, ConvNeXt-T fine-tuned 0.641, frozen SigLIP So400m probe 0.824. All six ImageNet-pretrained fine-tunes lie between 0.547 and 0.654, SigLIP zero-shot classification without training (0.776) beats all of them, and partial fine-tuning of the SigLIP backbone (0.812, three folds) did not beat the frozen probe.

Leakage of the original split. Under the dataset's original file-level split, 198 of the 853 deduplicated development images that it places in validation or test (23.2%) also have a copy in its training part (our own test images are excluded; Section 2.5 counts raw file entries instead), which inflates three linear probes by 5.5 (SigLIP), 11.0 (ConvNeXt-T) and 13.6 (ResNet-50) points in the recorded leakage simulation. Weaker models gain most, so leakage also compresses the gaps between models.

Out-of-source test and deployment. The deployed model (R2) was tested once on 407 Wikimedia Commons photographs collected after it was frozen: 0.821 accuracy and 0.816 macro-F1, close to its in-distribution result. Its weakest classes there are led (recall 0.47; 7 errors to diode), switch (0.52; real switches predicted ic chip 6 times, a consequence of the console-dominated training class) and transformer (0.67; 5 errors to inductor coil). It is exported to ONNX for an OpenCV demo and a Rust desktop application.

Efficiency study and packaged models. Model selection in the efficiency study used five grouped development folds, rather than test results. With the fused recipe and the same RTX 4070 Laptop, fp16 ONNX Runtime CUDA batch-1 latency was 31.9 ms for SigLIP at 384 px, 20.4 ms at 308 px and 8.9 ms for MobileCLIP2-S3. Their development OOF macro-F1 values were 0.840, 0.822 and 0.801. The 308 px row measures the Fast-resolution tower at fp16; it is not an INT8 TensorRT measurement. These runtime measurements differ from Table B.4's PyTorch timings and exclude image decoding and resizing. The packaged Small model subsequently scored 0.806 accuracy and 0.802 macro-F1 once on the 418 test rows. It is R3 here; its 0.55 abstention threshold and fitted fusion must not be attributed to D. No new test evaluation was performed for this report revision.

Table C.1: Scratch-CNN improvement study. Development: grouped 5-fold macro-F1 (mean ± SD over folds). Test and holdout: one training run on the fixed split, scored once. The 120-epoch row is the model A of the previous build of this report; R2 is the deployed model of Table 3.

Recipe	Epochs	Dev. 5-fold macro-F1	Test macro-F1	Test acc.	Holdout macro-F1	Holdout acc.
A, previous build	120	0.355 ± 0.015	0.336	0.354	–	–
A, this report	200	0.390 ± 0.007	0.392	0.400	0.257	0.283
Deployed SigLIP model (R2)	–	–	0.834	0.837	0.816	0.821




Figure C.1: Three distinct uses of the data: matched course models, development-fold efficiency selection and refitted deployment references. OOF means out-of-fold. Excalidraw sources accompany the exports.

Table C.2: Supporting benchmark: grouped 5-fold CV macro-F1 (mean ± SD over folds) on the development set. †Three folds only. C shares the SigLIP backbone with the probe column; the head-fitting procedure differs.

Family (variant)	Fine-tune	Frozen linear probe	Zero-shot
Classical: HOG + colour histogram + SVM	0.206 ± 0.017 (classical pipeline)		
Scratch CNN (model A's network, 120-epoch recipe)	0.355 ± 0.015	–	–
ResNet-50	0.580 ± 0.012	0.515 ± 0.018	–
MobileNetV3-L	0.547 ± 0.016	–	–
EfficientNetV2-S	0.608 ± 0.024	–	–
ConvNeXt-T (as model B)	0.641 ± 0.034	0.593 ± 0.021	–
ViT-B/16 (AugReg)	0.654 ± 0.032	–	–
Swin-T	0.639 ± 0.034	–	–
DINOv2 (FT: ViT-B/14; probe: ViT-L/14)	0.668 ± 0.024	0.667 ± 0.019	–
CLIP (FT: ViT-B/16; others: ViT-L/14@336)	0.702 ± 0.017	0.721 ± 0.019	0.609 ± 0.029
SigLIP So400m/14@384 (backbone of C)	0.812 ± 0.023†	0.824 ± 0.012	0.776 ± 0.018

Detailed limitations of the comparison.

1. **One split, one training seed.** With about 21 test images per class, one image can materially change a per-class F1, and the precision of an accuracy difference depends on the models' paired errors; no fixed significance threshold applies. The cross-validation benchmark gives the same ordering.
2. **Noisy labels and scope.** Labels are unreviewed search terms and 27.8% of the images are flagged as possibly off-topic (by an automated screen that no person verified). Measured accuracy need not represent performance on clean photographs. Because no person checked the test labels either, per-class scores for homonym classes (switch, transformer) partly measure the scrape rather than the model.
3. **Screen and model share a lineage.** The off-topic flags come from a CLIP model, a relative of C's SigLIP encoder, so the flagged/unflagged comparison in Section 6.2 may favour C.
4. **Residual near-duplicates.** The near-duplicate rule (pHash and CLIP thresholds) can miss heavily edited copies, so some train–test similarity may remain.
5. **Unequal pretraining and budgets.** C's backbone was trained on far more data than B's, so the comparison measures model and pretraining together. The budgets of A and B were fixed by earlier cross-validation, not tuned exhaustively. A was then trained to convergence, and the study of Section 6.3 found no further recipe gain, so the observed gap of 42.3 points to C persists under the tested budgets.
6. **D's asymmetries.** D uses a different crop fraction and was timed on a second PC; the same-PC C-tower anchor is reported separately. Its weights have research-use restrictions under the Apple Machine Learning Research Model License; commercial suitability is not established.
7. **Cost.** C has 428.2 million parameters and needs about 893.5 ms per image on a CPU, which rules it out for microcontrollers or real-time video without a GPU.

D Reproduction

The project repository contains the source code, executed comparison notebook, fixed split assignments, committed predictions and metrics, figure sources and build instructions. The repository is private; access requires a collaborator invitation. Raw images are obtained separately from the Kaggle source cited in Section 2.1. Rebuilding the cleaned dataset should reproduce 2,930 images and manifest fingerprint 431315e87d2612cb.

Python dependencies are pinned by the committed lockfile and managed with uv. The report tables and number macros are generated from committed results, and the PDF is compiled with LaTeX. Rebuilding the report neither trains models nor scores images. The comparison notebook also defaults to displaying recorded results without retraining.

The accompanying records identify the sources of the cleaning ablation, label audit, off-topic flags, confidence thresholds and broader benchmark. Each reported number is linked to its source in a machine-readable provenance register. Wikimedia photograph credits are retained in the attribution register.

Training and data-rebuild procedures are provided for historical reproducibility. Both recorded holdouts are spent; use development or synthetic inputs for routine checks. Model A was imported from the improvement study's fold-0 run rather than retrained for this report.